

91-13825

# SURFACE OBSERVATION CLIMATIC SUMMARIES

**FOR** 

# **CAMP CASEY, KOREA**

Prepared by

OL-A, USAFETAC ASHEVILLE, NORTH CAROLINA 28801-2723


**JUNE 1991** 

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED

USAF
ENVIRONMENTAL TECHNICAL
APPLICATIONS CENTER

Scott Air Force Base, Illinois, 62225-5438

# DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

### REVIEW AND APPROVAL STATEMENT

USAFETAC/DS-91/249, SURFACE OBSERVATION CLIMATIC SUMMARIES FOR CAMP CASEY/TONGDUCHON KO, JUNE 1991, HAS BEEN REVIEWED AND IS APPROVED FOR PUBLIC RELEASE. THERE IS NO OBJECTION TO UNLIMITED DISTRIBUTION OF THIS DOCUMENT TO THE PUBLIC AT LARGE, OR BY THE DEFENSE TECHNICAL INFORMATION CENTER (DTIC) TO THE NATIONAL TECHNICAL INFORMATION SERVICE (NTIS).

JOSEPH L. BOYTE CHIEF, CLIMATIC ALFLICATIONS, OL-A

FOR THE COMMANDER

WALTER S. BURGMANN

SCIENTIFIC AND TECHNICAL INFORMATION

PROGRAM MANAGER

2 - SEP 10 .

Account to the Control of the Control of the Control of Control of

11

### REPORT DOCUMENTATION PAGE

- 2. REPORT DATE: JUNE 1991
- 3. REPORT TYPE AND DATES COVERED: DATA SUMMARY, MAY 1953 TO JUNE 1990
- 4. TITLE AND SUBTITLE: SURFACE OBSERVATION CLIMATIC SUMMARIES (SOCS) FOR CAMP CASEY/TONGDUCHON, KOREA
- 7. PERFORMING ORGANIZATION NAME AND ADDRESS. OPERATING LOCATION A, USAFETAC, FEDERAL BUILDING, ASHEVILLE, NC 28801-2723
- 8. PERFORMING ORGANIZATION REPORT NUMBER: USAFETAC/DS-91/249
- 9. SPONSORING/MONITORING AGENCY NAME AND ADDRESS: USAF ENVIORNMENTAL TECHNICAL APPLICATIONS CENTER (USAFETAC), SCOTT AFB, IL 62225-5438
- 11. SUPPLEMENTARY NOTES: EFFECTIVE JULY 1 1988, THIS PRODUCT REPLACED TWO USAFETAC DOCUMENTS FORMERLY KNOWN AS THE REVISED UNIFORM SUMMARY OF SURFACE OBSERVATIONS (RUSSWO) AND THE LIMITED SURFACE OBSERVATIONS CLIMATIC SUMMARY (LISOCS). EXISTING RUSSWOS AND LISOCS WILL CONTINUE IN USE, BUT WILL EVENTUALLY BE BY A SOCS.
- 12A. DISTRIBUTION/AVAILABILITY STATEMENT: APPROVED FOR PUBLIC RELEASE, DISTRIBUTION IS UNLIMITED.
- 13. ABSTRACT: SURFACE OBSERVATION CLIMATIC SUMMARIES (SOCS) PROVIDE STATISTICAL CLIMATIC SUMMARIES OF SURFACE WEATHER OBSERVATIONS TAKEN AND RECORDED AT SPECIFIED USAF, CIVILIAN AND FOREIGN OBSERVING STATIONS. HOURLY OBSERVATIONS ARE SUMMARIZED FROM A 10-YEAR PERIOD OF RECORD (POR). "SUMMARY OF DAY" (SOD) INFORMATION IS SUMMARIZED FROM ALL AVAILABLE DATA IN THE OL-A, USAFETAC CLIMATIC DATABASE.
- 14. SUBJECT TERMS: CLIMATOLOGY, METEOROLOGICAL DATA, ATMOSPHERIC PHENOMENA, WEATHER, SOCS, CAMP CASEY/TONGDUCHON, KOREA, CEILING, CLOUD COVER, SNOW DEPTH, HUMIDITY, PRESSURE PRECIPITATION, SNOW TEMPERATURE, VISIBILITY, WIND.
- 15. NUMBER OF PAGES: 375
- 17. SECURITY CLASSIFICATION OF REPORT: UNCLASSIFIED
- 18. SECURITY CLASSIFICATION OF THIS PAGE: UNCLASSIFIED
- 19. SECURITY CLASSIFICATION OF ABSTRACT: UNCLASSIFIED
- 20. LIMITATION OF ABSTRACT: UL

DTIC STANDARD FORM 298

### PREFACE

EFFECTIVE 1 JULY 1988, THE SURFACE OBSERVATION CLIMATIC SUMMARIES (SOCS) REPLACED TWO OTHER USAFETAC PRODUCTS OF LONG STANDING: THE RUSSWO (REVISED UNIFORM SUMMARY OF SURFACE WEATHER OBSERVATIONS) AND LISOCS (LIMITED SURFACE OBSERVATION CLIMATIC SUMMARY). RUSSWOS AND LISOCS NOW IN EXISTENCE WILL CONTINUE TO BE USED UNTIL THEY ARE EVENTUALLY REPLACED BY SOCS.

THIS PRODUCT HAS BEEN ISSUED IN OTHER FORMS UNDER SEVERAL OTHER NAMES. IT WAS INTRODUCED IN THE EARLY 1940'S AS THE "SFCSUM," OR "SURFACE SUMMARY." THE ORIGINAL "USSWO," OR "UNIFORM SUMMARY OF SURFACE WEATHER OBSERVATIONS," DEBUTED IN 1946. THE USSWO GRADUALLY EVOLVED INTO THE "RUSSWO" AND THE "LISOCS." IT FINALLY BECAME THE NEW "SURFACE OBSERVATION CLIMATIC SUMMARIES" OR "SOCS" IN JULY 1988.

THE SOCS (LIKE ITS PREDECESSORS) IS PREPARED BY USAFETAC'S OPERATING LOCATION A AT ASHEVILLE, NC 28801-2723. HERE, CLIMATOLOGISTS USE STATE-OF-THE-ART COMPUTER TECHNOLOGY TO SUMMARIZE WEATHER OBSERVATIONS COLLECTED FROM SELECTED MILITARY, CIVILIAN, AND FOREIGN REPORTING STATIONS. SUMMARIES ARE PREPARED FROM DATA THAT HAS BEEN COLLECTED, QUALITY-CONTROLLED, AND STORED IN OL-A'S WORLDWIDE SURFACE WEATHER OBSERVATION DATABASE.

ALTHOUGH PREVIOUS VERSIONS OF THIS PRODUCT ONLY OFFERED SIX PARTS, SOCS PROVIDES EIGHT (A-H). THE ADDITIONS ARE THE CROSSWIND AND HEATING-COOLING DEGREE DAY SYMMARIES. PRECEDING FACH PART IS A BRIEF DISCUSSION OF THAT PARTICULAR PART, A DESCRIPTION OF THE DATA, AND AN EXPLANATION OF HOW THE DATA IS PRESENTED.

# CONTENTS

| INTRODUCTION.       1         STATION PERIOD OF RECORD.       1         DATA SOURCES.       1         TERMS EXPLAINED.       1         TIME CONVENTIONS.       2         ABBREVIATIONS.       2         SUMMARY DESCRIPTIONS.       2 |
|---|
| STATION HISTORY   |
| PART A - ATMOSPHERIC PHENOMENA SUMMARIES  |
| PERCENT OCCURRENCE FREQUENCY (FROM HOURLY OBS)  |
| PERCENT OCCURRENCE FREQUENCY (FROM SOD DATA)  |
| PERCENT OCCURRENCE FREQUENCY (THUNDERSTORMS)  |
| VERSUS WIND DIRECTIONPERCENT OCCUPRENCE FREQUENCY   |
|   |
| PART B - PRECIPITATION, SNOWFALL, AND SNOW DEPTH  |
| PRECIPITATION   |
| PERCENT OCCURRENCE FREQUENCYB-2-1   |
| MONTHLY TOTALSB-2-2   |
| DAILY EXTREMESB-2-3   |
| SNOWFALL  |
| PERCENT OCCURRENCE FREQUENCYB-3-1   |
| MONTHLY TOTALSB-3-2   |
| DAILY EXTREMESB-3-3   |
| SNOW DEPTH  |
| PERCENT OCCURRENCE FREQUENCY  |
| DAILY EXTREMESB-4-2   |
|   |
| SNOWFALL/SNOW DETTH   |
| FIRST AND LAST DAYS OF OCCURRENCE BY SNOW-YEARB-5-1   |
|   |
| PART C ~ SURFACE WIND   |
| PEAK WINDS (FROM SOD DATA)  |
| PEAK WINDSPERCENT OCCURRENCE FREQUENCY (FROM SOD DATA)  |
| WIND DIRECTION VS WIND SPEEDPOF (FROM HOURLY OBS)   |
|   |
| PART D ~ CEILING, VISIBILITY AND SKY COVER  |
|   |
| CEILING VS VISIBILITYPOF (FROM HOURLY OBS)  |

| PART E - TEMPERATURE AND RELATIVE HUMIDITYE-1-1              |
|--|
| TEMPERATURESCUMULATIVE POF (FROM SOD DATA)                   |
| MAXIMAE-2-1  |
| MINIMAE-2-2  |
| MEAN   |
| MONTHLY TEMPERATURES (FROM SOD DATA)                         |
| MAXIMA   |
| MINIMAE-3-2  |
| MEANE-4-1  |
|  |
| DRY BULB, WET BULB, DEW POINT TEMPERATURES (FROM HOURLY OBS) |
| DRY BULB   |
| WEI BULBE-5-2  |
| DEW POINTE-5-3   |
| RELATIVE HUMIDITY (FROM HOURLY OBS)                          |
| CUMULATIVE PERCENT OCCURRENCE FREQUENCYE-6-1                 |
| PART F - PRESSURE (FROM HOURLY OBS)F-1-1                     |
| SEA LEVEL PRESSURE   |
| ALTIMETER SETTINGF-3-1                                       |
| STATION PRESSUREF-4-1  |
|  |
| PART G - CROSSWIND SUMMARIES (FROM HOURLY OBS)               |
| PERCENT OCCURRENCE FREQUENCY                                 |
| PART H - DEGREE DAY SUMMARIES (FROM HOURLY OBS)H-1-1         |
| HEATING DEGREE DAYSH-2-1                                     |
| COOLING DEGREE DAYS  |
| COURTE DESIGN DIVISION NO.                                   |
|  |

\*\*\* NOTE: THE AWS CLIMATIC BRIEF IS ATTACHED AT THE END OF THE SOCS \*\*\*

### INTRODUCTION

### STATION PERIOD OF RECORD.

HOURLY OBSERVATIONS: JUL 80 - JUN 90 (METAR) (MISSING DATA FOR 2000-0400 LST, JUL 80 - FEB 88).

SUMMARY OF DAY DATA: MAR 88 - JUN 90 (FULL TIME).

SUMMARY OF DAY DATA: MAY 53 - FEB 88 (PART TIME).

HOURS SUMMARIZED: 0000 LST THROUGH 2300 LST.

DATA SOURCES. THESE SUMMARIES ARE COMPILED FROM "HOURLY OBSERVATIONS" AND/ OR SUMMARY OF DAY DATA," DEPENDING ON THE PHENOMENA OR OCCURRENCE BEING SUMMARIZED. THE TWO SOURCES ARE DEFINED IN "TERMS EXPLAINED."

### TERMS EXPLAINED:

- BIVARIATE DISTRIBUTION: A BIVARIATE DISTRIBUTION GIVES THE JOINT DISTRIBUTIONS OF TWO RELATED VARIABLES. AN EXAMPLE IS THE BIVARIATE DISTRIBUTION OF CEILING AND VISIBILITIES IN PART D. EACH ROW AND EACH COLUMN OF A BIVARIATE DISTRIBUTION IS A FREQUENCY DISTRIBUTION. JOINT FREQUENCIES ARE FOUND AT THE ROW-COLUMN INTERSECTIONS.
- HOURLY OBSERVATIONS: ALL RECORD OR RECORD-SPECIAL OBSERVATIONS ON AWS FORMS 10/10A (OR EQUIVALENT) AT SCHEDULED HOURLY INTERVALS.
- SUMMARY OF DAY (SOD) DATA: DATA COMPILED FROM ALL AVAILABLE OBSERVATIONAL SOURCES, INCLUDING HOURLY OBSERVATIONS, SPECIAL OBSERVATIONS, REMARKS, AND ACTUAL "SUMMARY OF DAY" DATA RECORDED IN COLUMNS 44-73 OF AWS FORMS 10/10A (OR EQUIVALENT) FOR ANY GIVEN DAY. NOTE: EXTREMES OCCURRING DURING NON-OPERATIONAL HOURS AND/OR DAYS ARE NOT REFLECTED IN THESE SUMMARIES.
- MEAL: THE SUM OF ALL THE VALUES DIVIDED BY THE NUMBER OF VALUES.
- MEASURABLE AMOUNT: ANY PRECIPITATION OR SNOWFALL AMOUNT GREATER THAN A TRACE.
- MEDIAN: THE MIDDLE VALUE WHEN THE VALUES ARE IN ASCENDING ORDER. IF THE NUMBER OF VALUES IS EVEN, THE MEDIAN IS HALFWAY BETWEEN THE TWO MIDDLE VALUES.
- PERCENT OCCURRENCE FREQUENCY (POF): IN STATISTICS, FREQUENCY IS THE NUMBER OF TIMES A GIVEN COUNT OR EVENT OCCURS. IN THE SOCS, THIS IS EXPRESSED AS THE PERCENT OCCURRENCE FREQUENCY (POF), WHERE THE FREQUENCY (NUMBER OF OCCURRENCES) IS GIVEN AS A PERCENT OF ALL POSSIBLE OCCURRENCES IN THE SAMPLE (PERIOD SUMMARIZED). FOR EXAMPLE, IF SNOW FELL ON 5 OUT OF 100 DAYS WE COULD EXPRESS THE "PERCENT OCCURRENCE FREQUENCY" OF SNOW AS 5 PERCENT OVER THE 100-DAY PERIOD. MAY BE USED INTERCHANGEABLY WITH "PERCENT FREQUENCY OF OCCURRENCE."

PERIOD OF RECORD: THE SIZE OF THE OBSERVATIONAL DATA SAMPLE, IN YEARS.

PRECIPITATION: A TERM THAT INCLUDES BOTH LIQUID PRECIPITATION AND WATER EQUIVALENT.

STANDARD DEVIATION: A MEASURE OF DISPERSION ON THE VARIABILITY OF THE QUANTITY CONCERNED ABOUT ITS ARITHMETIC MEAN. THE LARGER THE STANDARD DEVIATION, THE GREATER THE VARIABILITY.

TIME CONVENTIONS: ALL TIMES IN THE SOCS ARE EXPRESSED IN LOCAL STANDARD TIME (LST). USERS SHOULD MAKE ADJUSTMENTS FOR DAYLIGHT SAVING TIMES IN THEIR AREAS. IN SUMMARIES THAT SHOW PLUPNAL VARIATIONS, THE DATA IS SUMMARIZED USING THE FOLLOWING STANDARD 3-SOUR PERIODS (ALL LST):

| 0000-0200 | 1200-1400 |
|-----------|-----------|
| 0300-0500 | 1500-1700 |
| 0600-0800 | 1800-2000 |
| 0900-1100 | 2100-2300 |

NOTE 1. DURING PART TIME PERIODS, THE FIRST AND LAST 3-HOUR PERIODS MAY HAVE SIGNIFICANT SHORTFALLS IN OBSERVATION COUNTS.

### ABBREVIATIONS USED:

| AMT  | AMOUNT                   | LT     | LESS THAN                    |
|------|--------------------------|--------|------------------------------|
| ANN  | ANNUAL                   | M      | METER                        |
| BARO | BAROMETER                | MB     | MILLIBAR                     |
| C    | CENTIGRADI (CELSIUS)     | MPS    | METERS PER SECOND            |
| DEG  | DEGREE                   | MSL    | MEAN SEA LEVEL               |
| DB   | DRY BULB TEMPERATURE     | MEAS   | MEASURABLE                   |
| DP   | DEW POINT TEMPERATURE    | NO.    | NUMBER                       |
| EQ   | EQUAL                    | OBS    | OBSERVATION                  |
| F    | FAHRENHEIT               | OBST   | OBSTRUCTION                  |
| FRZG | FREEZING                 | POF    | PERCENT OCCURRENCE FREQUENCY |
| FT   | FEET                     | PRECIP | PRECIPITATION                |
| GE   | GREATER THAN OR EQUAL TO | SD     | STANDARD DEVIATION           |
| GMT  | GREENWICH MEAN TIME      | SOD    | SUMMARY OF DAY               |
| GT   | GREATER THAN             | TEMP   | TEMPERATURE                  |
| HG   | INCHES OF MERCURY        | TSTM   | THUNDERSTORM                 |
| HT   | HEIGHT                   | VSBY   | VISIBILITY                   |
| KTS  | KNOTS                    | VSN    | VISION                       |
| LE   | LESS THAN OR EQUAL TO    | WB     | WET BULB TEMPERATURE         |
| LST  | LOCAL STANDARD TIME      | WBAN   | AWS FORM 10/10A              |
|      |                          | UTC    | *COORDINATED UNIVERSAL TIME  |
|      |                          |        |                              |

SUMMARY DESCRIPTION: A BRIEF DESCRIPTION OF THE DATA PRECEDES EACH PART IN THE SOCS.

NOTE: OL-A/USAFETAC DERIVES STATION LATITUDE/LONGITUDE COORDINATES AND AIRFIELD ELEVATION DATA FROM THE AWS MASTER STATION CATALOG. THIS INFORMATION IS PRESENTED ON THE AWS CLIMATIC BRIEF FOR EACH STATION. THE STATION DATA MAY DIFFER FROM INFORMATION CONTAINED IN THE SOCS STATION HISTORY (DATA SUPPLIED BY AWS UNITS). THE STATION DATA MAY ALSO VARY FROM DATA PRESENTED IN DOD FLIGHT INFORMATION PUBLICATIONS (FLIP).

<sup>\*</sup> UTC REPLACED GMT ON 1 AUGUST 1988

| STATIC  |  | STATION NAME  |                   |   | LAT   | TITUDE  | LONGITUDE   | FLD SLEV (                   | FT)     | CALL S          | SIGN                 | WMO | NMBR           |
|---|--|---|-------------------|---|-------|---|---|------------------------------|---------|-----------------|----------------------|-----|----------------|
| ON SUM<br>47106                                 |  | CAMP CASEY/TONGDUCHON,  | KOREA             |   | N 3   | 7 55  | E 127 03  | 196                          |         | RKST            |                      |     |                |
|   |  | STA   | TION LOCA         | TION  | AND I | NSTRUME   | NTATION HIS   | PORY                         |         |                 |                      |     |                |
| Nmbr  | GEOGRAF  | PHICAL LOCATION & NAME  | Type<br>of        | At  |       | Locatio   | l l   | E LONGITUD                   |         | lev Abo         |                      |     | OBS<br>PEF     |
| Loc   |  | l men been less a man   | Station           | Fr  | om    | To  |   |                              | - 1     | D (FT)          |                      | - 1 | DAY            |
| 1 2 3   | Camp Cas<br>Same<br>Same   | sey/Tongduchon, Korea   | AAF<br>AAF<br>AAF | May<br>Mar<br>Nov   | 59    | Feb 59<br>Oct 60<br>Jun 91                                    | N 37 55   | E 127 04<br>E 127 03<br>Same | 19      | 84<br>96<br>ame | None<br>None<br>None |     | 13<br>13<br>15 |
| Nmbr<br>of<br>Loc                               | Date of<br>Change  | SURFACE WIND  | EQUIPMENT         | <br>  | TYI   | ON<br>PE OF<br>SMITTER  | TYPE OF RECORDER  | HT ABOVE GROUND              |         | RKS, AL         |                      |     | -              |
| 1<br>2<br>3<br>4<br>5<br>6<br>7<br>8<br>9<br>10 | May 53<br>Apr 54<br>Apr 55<br>Apr 58<br>Mar 59<br>Apr 60<br>Apr 65<br>Jan 71<br>Jan 82<br>Jan 91 | Not available Hand velometer Winds estimated 24 ft NE of stattion 50' W side rnwy on to On control tower On aircraft hangar 210'W ctrln,1300'fm e Same Same |                   | N/A<br>None<br>None<br>AN/GM<br>Same<br>AN/GM<br>Same<br>Same |       | N/A<br>None<br>None<br>None<br>None<br>None<br>RO-362<br>Same | N/A<br>N/A<br>N/A<br>27 ft<br>40 ft<br>80 ft<br>75 ft<br>Same<br>Same | No wá                        | ind equ | lipment         |                      |     |                |

| PPPPP | PPP  | AAA   | AAA   | RRRR     | RRRR  | TTTTTTTTT     | AAA   | AAA   |
|-------|------|-------|-------|----------|-------|---------------|-------|-------|
| PPPPP | PPPP | AAAA  | АААА  | RRRR     | RRRRR | TTTTTTTTT     | AAAA  | AAAA  |
| PP    | PP   | λA    | AA    | RR       | RR    | TT            | AA    | AA    |
| PP    | PP   | AA    | AA    | RR       | RR    | TT            | AA    | AA    |
| PPPPP | PPPP | AA    | AA    | RRRRRRRR |       | TT            | AA    | AA    |
| PPPPP | PPP  | AAAAA | AAAA  | RRRR     | RRRR  | TT            | AAAAA | AAAAA |
| PP    |      | AAAAA | AAAAA | RR       | RR    | TT            | AAAAA | AAAAA |
| PP    |      | AA    | AA    | RR       | RR    | $\mathbf{TT}$ | AA    | AA    |
| PP    |      | AA    | AA    | RR       | RR    | <b>T</b> T    | AA    | AA    |
| PP    |      | AA    | AA    | RR       | RR    | TT            | AA    | AA    |

### PART A

### ATMOSPHERIC PHENOMENA SUMMARIES

THIS PART SUMMARIZES SPECIFIED ATMOSPHERIC PHENOMENA IN CATEGORIES AS FOLLOWS:

Ti JNDERSTORMS: ALL REPORTED OCCURRENCES OF THUNDERSTORMS, TORNADOES, AND WATERSPOUTS.

.IQUID PRECIPITATION: RAIN OR DRIZZLE FALLING TO THE GROUND BUT NOT FREEZING.

FREEZING PRECIPITATION: FREEZING RAIN OR FREEZING DRIZZLE (GLAZE).

FROZEN PRECIPITATION: SNOW, SNOW PELLETS, SLEET, SNOW GRAINS, ICE CRYSTALS, ICE PELLETS. IN JANUARY 1968, SNOW PELLETS BECAME KNOWN AS SMALL HAIL.

HAIL: ALL OCCURRENCES OF HAIL.

ALL PRECIPITATION: INCLUDES ALL OBSERVATIONS REPORTING PRECIPITATION. BECAUSE MORE THAN ONE TYPE OF PRECIPITATION MAY BE INCLUDED IN THE SAME OBSERVATION, THE SUM OF PERCENTAGES IN THE INDIVIDUAL CATEGORIES MAY EXCEED THE PERCENTAGES IN THIS CATEGORY.

FOG: INCLUDES ALL REPORTED FOG, ICE FOG, AND GROUND FOG.

SMOKE AND/OR HAZE: SMOKE, HAZE, OR COMBINATIONS OF THE TWO.

BLOWING SNOW: ALL REPORTS OF BLOWING SNOW, INCLUDING DRIFTING SNOW, WHEN REPORTED.

DUST AND/OR SAND: DUST, SAND, BLOWING DUST, BLOWING SAND, OR COMBINATIONS OF THESE.

BLOWING SPRAY: THE "ALL OBSTRUCTIONS TO VISION" CATEGORY ACCOUNTS FOR BLOWING SPRAY, IF AND AS REPORTED.

ALL OBSTRUCTIONS TO VISION: THIS CATEGORY INCLUDES ALL REPORTS OF OBSTRUCTIONS TO VISION. SINCE THE OCCUPRENCE OF MORE THAN ONE OBSTRUCTION TO VISION MAY BE REPORTED IN THE SAME ORSERVATION, THE SUM OF THE PERCENTAGES IN THE INDIVIDUAL CATEGORIES MAY EXCEED THE PERCENTAGES IN THIS CATEGORY

## SPECIFIED PHENOMENA -- PERCENT OCCURRENCE FREQUENCY.

THESE TABLES GIVE THE PERCENT OCCURRENCE FREQUENCY (FOF) FOR THE ATMOSPHERIC PHENOMENA SHOWN. THE DATA WAS TAKEN FROM HOURLY OBSERVATIONS ONLY, AND IS SUMMARIZED AS FOLLOWS:

- BY FIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

A - 1 - 2

- SPECIFIED PHENOMENA--PERCENT OCCURRENCE FREQUENCY (POF).

  THIS TABLE IS THE ONLY ONE IN PART A THAT IS PRODUCED FROM SUMMARY OF DAY
  DATA. DATA IS SUMMARIZED MONTHLY AND ANNUALLY FOR ALL YEARS COMBINED.
- THUNDERSTORMS--PERCENT OCCURRENCE FREQUENCY.

  THIS TABLE GIVES THE PERCENT OCCURRENCE FREQUENCY OF THUNDERSTORMS REPORTED ON
  THE HOURLY OBSERVATION. DATA IS SUMMARIZED SAME AS FOR FIRST TABLE IN THIS PART.
- SPECIFIED PHENOMENA VS WIND DIRECTION--PERCENT OCCURRENCE FREQUENCY.
  THESE TABLES INCLUDE SUMMARY OF MONTH FOR ALL HOURS AND YEARS COMBINED. WIND DIRECTION CATEGORIES ARE AS SPECIFIED BY THE LOCAL WEATHER STATION.
- NOTE 1: REPORTING PRACTICES HAVE CHANGED WITH TIME. METAR AND SYNOPTIC REPORTING STATIONS RECORD (ON AWS FORMS 10/10A) AND TRANSMIT LONGLINE ONLY THE HIGHEST ORDER ATMOSPHERIC PHENOMENA THAT AFFECTS VISIBILITY. METAR STATIONS STARTED THIS PROCEDURE IN JANUARY 1968, BUT SYNOPTIC STATIONS ALWAYS DID IT THAT WAY. IN JANUARY 1970, METAR STATIONS STARTED RECORDING ALL ALMOSPHERIC PHENOMENA THAT AFFECTED VISIBILITY, BUT CONTINUED TO TRANSMIT ONLY THE HIGHEST ORDER. FOR EXAMPLE, IF THE RECORDED OBSERVATION INCLUDED RAIN, FOG AND HAZE, ONLY THE RAIN WAS TRANSMITTED. BECAUSE OF THESE PROCEDURES, THE USAFETAC DATABASE WOULD SHOW ONLY RAIN AS AN OBSTRUCTION. THEREFORE, THE OBSTRUCTION TO VISION (AND TO A LESSER EXTENT, PRECIPITATION) SUMMARIES FOR METAR AND SYNOPTIC STATIONS ARE HIGHLY QUESTIONABLE.
- NOTE 2: FOREIGN METAR REPORTING STATIONS FREQUENTLY DO NOT TRANSMIT OBSTRUCTIONS TO VISION WHEN VISIBILITIES EXCEED 1000 METERS.
- NOTE 3: A VALUE OF ".O" IN ANY SUMMARY REPRESENTS ONE OR MORE OCCURRENCES THAT, IN AGGREGATE, AMOUNT TO LESS THAN .05 PERCENT.
- NOTE 4: DURING PART TIME PERIODS, THESE TABLES MAY NOT ACCURATELY REFLECT NIGHTTIME AND/OR WEEKEND OCCURRENCES OF CERTAIN PHENOMENA.

# PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 PERIOD OF RECORD: JUL 80 - JUN 90 STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9 MONTH: JAN HOURS TSTMS LIQUID FREEZ FROZEN HAIL ALL FOG SMOKE BLOWING DUST ALL TOTAL &/OR &/OR PRECIP PRECIP PRECIP PRECIP SNOW OBST NO. OF HAZE SAND TO VSN OBS ...... 00-02 12.8 8.4 21.2 29.6 10.6 61.5 179 67.8 03-05 13.9 8.3 22.2 39.4 6.1 180 8.3 17.8 50.6 6.7 75.0 180 06-08 9.4 09-11 6.7 10.8 17.5 45.0 15.0 77.5 120 12-14 8.3 13.3 21.7 18.9 26.7 67.2 180 15-17 3.9 13.3 17.2 13.3 16.7 47.2 180 18-20 6.1 11.1 17.2 17.8 17.2 52.2 180 21-23 8.3 8.9 17.2 24.4 15.0 56.7 180 ALL 29.2 1379 HOURS 10.3 19.1 14.2 MONTH: FEB ...... 68.5 00-02 9.1 2.4 11.5 38.8 18.2 03.06 7.9 3.6 11.5 47.9 9.1 68.5 165 06-08 6.0 3.6 9.6 62.7 3.0 75.3 166 14.3 29.5 76.8 09-11 11.6 2.7 33.0 112 12.5 16.1 66.1 12-14 3.6 11.3 38.7 15-17 11.3 3.0 14.3 5.4 32.7 52.4 168 18-20 10.8 2.4 13.3 12.0 37.3 62.7 166 60.7 21-23 8.0 8.0 28.2 24.5 163 ALL 9.6 2.7 12.3 29.4 65.9 1273 HOURS

### PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA FROM HOURLY OBSERVATIONS

STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 LST TO UTC: - 9 MONTH: MAR HOURS TSTMS LIQUID FREEZ FROZEN HAIL ALL FOG SMOKE BLOWING DUST ALL TOTAL (LST) PRECIP PRECIP PRECIP PRECIP &/OR &/OR OBST NO. OF TO VSN HAZE SAND OBS 00-02 11.3 ,5 11.8 32.3 8.6 52.7 186 03-05 11.3 2.2 13.4 43.0 11.3 67.7 186 06-08 10.8 60.2 186 1.1 11.8 8.6 80.6 09-11 9.7 30.6 78.2 2.4 12.1 35.5 124 12.4 4.8 39.8 60.2 12-14 3.2 15.6 186 15-17 10.8 1.6 12.4 2.2 32.3 46.8 186 14.0 18-20 14.0 8.1 26.9 48.9 186 10.8 10.8 24.2 48.9 186 21-23 14.0 ALL HOURS 11.4 1.3 12.8 25.5 21.5 59.7 1426 MONTH: APR 00-02 . 6 5.3 5.3 32.4 17.6 55.3 170 9.4 42.1 9.4 60.8 171 03-05 9.4 169 06-08 11.8 11.8 39.1 18.3 69.2 09-11 8.0 8.0 11.6 33.9 53.6 112 165 12-14 9.7 9.7 4.2 26.7 40.6 11.5 4.8 20.0 36.4 165 15-17 11.5 9.1 165 18-20 6.7 6.7 18.8 34.5 21-23 7.8 7.8 16.8 24.0 48.5 167 ALL HOURS .2 8.8 20.6 20.5 49.8 1284 8.8

# PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9 MONTH: MAY ...... HOURS TSTMS LIQUID FREEZ FROZEN HAIL ALL FOG SMOKE BLOWING DUST ALL TOTAL (LST) PRECIP PRECIP PRECIP PRECIP &/OR SNOW &/OR OBST NO. OF HAZE SAND TO VSN OBS ....... 14.4 38.9 13.3 00-02 | 1.7 14.4 66.7 180 03-05 17.8 17.8 47.8 8.3 73.9 180 06-08 8.3 77.2 180 14.4 14.4 54.4 09-11 40.0 67.5 10.8 10.8 16.7 120 12-14 7.8 7.8 4.4 35.0 47.2 180 15-17 1.1 10.1 10.1 4.5 26.8 41.3 179 18-20 2.8 14.4 14.4 8.9 22.8 46.1 180 21-23 .6 12.2 12.2 18.8 24.9 55.8 181 ALL .8 12.8 HOURS 12.8 24.6 21.7 59.1 1380 MONTH: JUN ..... 00-02 | 1.7 17.8 17.8 48.3 6.7 72.8 180 03-05 1.1 19.4 19.4 53.9 4.4 77.8 180 06-08 .6 20.0 20.0 47.2 5.6 72.8 180 09-11 19.2 19.2 15.8 36.7 71.7 120 67.2 12-14 18.9 18.9 8.3 40.0 180 15-17 17.2 17.2 8.3 31.7 57.2 180 18-20 17.8 17.8 13.9 23.3 55.0 21-23 15.6 15.6 32.2 12.8 60.6 180 ALL HOURS 29.1 19.4 66.7 1380 18.2 18.2

# PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO MONTH: JUL LST TO UTC: - 9 HOURS TSTMS LIQUID FREEZ FROZEN HAIL ALL FOG SMOKE BLOWING DUST ALL TOTAL &/OR SNOW &/OR (LST) PRECIP PRECIP PRECIP PRECIP OBST NO. OF HAZE SAND TO VSN OBS 00-02 1.1 13.3 13.3 64.4 1.1 78.9 90 03-05 3.3 14.4 14.4 64.4 78.9 90 06-08 20.0 20.0 65.6 1.1 86.7 90 09-11 1.7 17.2 17.2 19.0 34.5 70.7 58 12-14 1.1 18.4 18.4 4.6 44.8 67.8 87 15-17 11.5 11.5 8.0 28.7 48.3 87 11.5 11.5 9.2 24.1 44.8 87 18-20 21-23 13.8 13.8 39.1 20.7 73.6 ALL .9 14.9 HOURS 14.9 35.4 18.5 68.8 676 MONTH: AUG 15.1 38.7 2.2 00-02 15.1 55.9 93 8.6 40.9 2.2 03-05 8.6 51.6 93 06-08 7.5 7.5 37.6 5.4 50.5 93 09-11 6.5 6.5 21.0 3.2 30.6 62 12-14 8.6 5.4 20.4 34.4 93 8.6 30.1 15-17 15.1 15.1 15.1 93 18-20 1.1 14.0 14.0 7.5 14.0 35.5 93 21-23 11.8 11.8 28.0 11.8 51.6 93 ALI. 713 HOURS .1 11.1 11.1 22.4

# PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF R

PERIOD OF RECORD: JUL 80 - JUN 90

| 01111101       |     | 471000           | LST TO          | UTC: -           | 9             |               |      |                       | MONTH:                                  | SEP                  |                       | 0 - 0011 90            |
|----------------|-----|------------------|-----------------|------------------|---------------|---------------|------|-----------------------|---|----------------------|-----------------------|------------------------|
| HOURS<br>(LST) |     | LIQUIP<br>PRECIP | FREEZ<br>PRECIP | FROZEN<br>PRECIP | HAIL          | ALL<br>PRECIP | FOG  | smoke<br>&/or<br>Haze | BLOWING<br>SNOW                         | DUST<br>&/OR<br>SAND | ALL<br>OBST<br>TO VSN | TOTAL<br>NO. OF<br>OBS |
| 00-02          |     | 4.4              |                 | • • • • • • • •  | • • • • • • • | 4.4           | 60.0 | 1.1                   |   | • • • • • •          | 65.6                  | 90                     |
| 03-05          |     | 8.9              |                 |                  |               | 8.9           | 66.7 |                       |   |                      | 75.6                  | 90                     |
| 06-08          |     | 10.0             |                 |                  |               | 10.0          | 63.3 |                       |   |                      | 73.3                  | 90                     |
| 09-11          |     | 6.7              |                 |                  |               | 6.7           | 18.3 | 23.3                  |   |                      | 48.3                  | 60                     |
| 12-14          |     | 6.7              |                 |                  |               | 6.7           | 2.2  | 21.1                  |   |                      | 30.0                  | 90                     |
| 15-17          | 4.4 | 7.8              |                 |                  |               | 7.8           | 2.2  | 12.2                  |   |                      | 22.2                  | 90                     |
| 18-20          |     | 10.0             |                 |                  |               | 10.0          | 11.1 | 14.4                  |   |                      | 35.6                  | 90                     |
| 21-23          |     | 10.0             |                 |                  |               | 10.0          | 43.3 | 3.3                   |   |                      | 56.7                  | 90                     |
| ALL<br>HOURS   | .6  | 8.1              |                 |                  |               | 8.1           |      | 8.8                   |   |                      | 51.0                  | 690                    |
|                |     |                  |                 |                  |               |               |      |                       | MONTH: (                                | OCT                  |                       |                        |
| 00-02          |     | 3.2              |                 | • • • • • • • •  | • • • • • •   | 3.2           | 63.4 |                       | • | • • • • • • •        | 67.7                  | 93                     |
| 03-05          |     | 9.7              |                 |                  |               | 9.7           | 72.0 |                       |   |                      | 81.7                  | 93                     |
| 06-08          |     | 10.8             |                 |                  |               | 10.8          | 71.0 | 3.2                   |   |                      | 84.9                  | 93                     |
| 09-11          |     | 6.5              |                 |                  |               | 6.5           | 29.0 | 16.1                  |   |                      | 51.6                  | 62                     |
| 12-14          | 2.2 | 9.7              |                 |                  |               | 9.7           | 6.5  | 16.1                  |   |                      | 32.3                  | 93                     |
| 15-17          | 1.1 | 4.3              |                 |                  |               | 4.3           | 4.3  | 9.7                   |   |                      | 18.3                  | 93                     |
| 18-20          |     | 1.1              |                 |                  |               | 1.1           | 22.6 | 8.6                   |   |                      | 32.3                  | 93                     |
| 21-23          |     | 1.1              |                 |                  |               | 1.1           | 49.5 | 2.2                   |   |                      | 52.7                  | 93                     |
| ALL<br>HOURS   | .4  | 5.8              |                 |                  |               | 5.8           | 40.3 |                       |   | •••••                | 52.7                  | 713                    |

# PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: NOV TSTMS LIQUID FREEZ FROZEN HAIL ALL FOG SMOKE BLOWING DUST ALL HOURS TOTAL &/OR (LST) PRECIP PRECIP PRECIP PRECIP SNOW &/OR OBST NO. OF HAZE SAND TO VSN OBS 00-02 14.3 14.3 44.0 58.3 84 59.5 03-05 14.3 14.3 73.8 84 06-08 15.5 50.0 3.6 69.0 14.3 1.2 84 09-11 12.5 12.5 37.5 7.1 57.1 56 12-14 11.9 1.2 13.1 4.8 26.2 44.0 84 15-17 13.1 13.1 19.0 32.1 84 15.5 41.7 18-20 10.7 1.2 11.9 14.3 84 21-23 9.5 33.3 2.4 45.2 ALL HOURS 12.6 .5 13.0 30.3 9.2 52.5 644 MONTH: DEC 00-02 9.0 9.0 49.4 60.7 89 03-05 5.6 5.6 60.0 65.6 90 06-08 3.3 5.6 8.9 62.2 4.4 75.6 90 60 09-11 53.3 15.0 76.7 1.7 6.7 8.3 27.8 23.3 12-14 4.4 3.3 7.8 58.9 90 15-17 8.9 4.4 13.3 13.3 20.0 46.7 90 18-20 5.8 4.7 10.5 26.7 16.3 53.5 86 47.6 59.5 21-23 3.6 4.8 8.3 3.6 84 ALL HOURS 3.5 9.0 42.1 10.5 61.6 679

# PERCENTAGE FREQUENCY OF VARIOUS ATMOSPHERIC PHENOMENA FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

|        |       |                  | LST TO          | UTC: - 9         | }    |               |      |                       | HOURS:          | ALL                  |                       |                        |
|--------|-------|------------------|-----------------|------------------|------|---------------|------|-----------------------|-----------------|----------------------|-----------------------|------------------------|
| MONTH  | TSTMS | LIQUID<br>PRECIP | FREEZ<br>PRECIP | FROZEN<br>PRECIP | HAIL | ALL<br>PRECIP | FOG  | SMOKE<br>&/OR<br>HAZE | BLOWING<br>SNOW | DUST<br>&/OR<br>SAND | ALL<br>OBST<br>TO VSN | TOTAL<br>NO. OF<br>OBS |
| JAN    |       | 8.8              | • • • • • • •   | 10.3             |      | 19.1          | 29.2 | 14.2                  | • • • • • • • • | • • • • • • •        | 62.5                  | 1379                   |
| FEB    |       | 9.6              |                 | 2.7              |      | 12.3          | 29.4 | 24.3                  |                 |                      | 55.9                  | 1273                   |
| MAR    |       | 11.4             |                 | 1.3              |      | 12.8          | 25.5 | 21.5                  |                 |                      | 59.7                  | 1426                   |
| APR    | .2    | 8.8              |                 |                  |      | 8.8           | 20.6 | 20.5                  |                 |                      | 49.8                  | 1284                   |
| MAY    | .8    | 12.8             |                 |                  |      | 12.8          | 24.6 | 21.7                  |                 |                      | 59.1                  | 1380                   |
| JUN    | .4    | 18.2             |                 |                  |      | 18.2          | 29.1 | 19.4                  |                 |                      | 66.7                  | 1380                   |
| JUI    | .9    | 14.9             |                 |                  |      | 14.9          | 35.4 | 18.5                  |                 |                      | 68.8                  | 676                    |
| AUG    | .1    | 11.1             |                 |                  |      | 11.1          | 22.4 | 9.5                   |                 |                      | 43.1                  | 713                    |
| SEP    | .6    | 8.1              |                 |                  |      | 8.1           | 34.1 | 8.8                   |                 |                      | 51.0                  | 690                    |
| oct    | .4    | 5.8              |                 |                  |      | 5.8           | 40.3 | 6.7                   |                 |                      | 52.7                  | 713                    |
| NOV    |       | 12.6             |                 | .5               |      | 13.0          | 30.3 | 9.2                   |                 |                      | 52.5                  | 644                    |
| DEC    |       | 3.5              |                 | 5.4              |      | 9.0           | 42.1 | 10.5                  |                 |                      | 61.6                  | 679                    |
| ANNUAL | .3    | 10.9             |                 | 1.9              |      | 12.8          | 29.0 | 16.9                  |                 | •                    | 58.7                  | 12237                  |

j

# PERCENTAGE FREQUENCY OF DAYS WITH VARIOUS ATMOSPHERIC PHENOMENA FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: 5305-9006 MONTH: ALL HOURS: ALL

|        |       |                  | LST TO U        | rc: -09          |      |               |      |                       | MONTH: ALL                              | HOURS                | : ALL                 |                        |
|--------|-------|------------------|-----------------|------------------|------|---------------|------|-----------------------|---|----------------------|-----------------------|------------------------|
| MONTH  | TSTMS | LIQUID<br>PRECIP | FREEZ<br>PRECIP | FROZEN<br>PRECIP | HAIL | ALL<br>PRECIP | FOG  | SMOKE<br>&/OR<br>HAZE | BLOWING<br>SNOW                         | DUST<br>&/OR<br>SAND | ALL<br>OBST<br>TO VSN | TOTAL<br>NO. OF<br>OBS |
| JAN    |       | 6.5              | .1              | 23.5             | .2   | 26.0          | 44.0 | 81.9                  | • |                      | 88.6                  | 1061                   |
| FEB    | .1    | 8.6              | .1              | 15.0             |      | 20.9          | 39.9 | 81.0                  |   |                      | 86.2                  | 978                    |
| MAR    | .1    | 18.6             |                 | 10.2             | .1   | 24.9          | 49.1 | 77.7                  |   | .1                   | 86.4                  | 1093                   |
| APR    | 1.4   | 26.3             |                 | .9               | .2   | 26.6          | 48.9 | 70.3                  |   |                      | 83.0                  | 1044                   |
| MAY    | 2.9   | 25.8             |                 |                  | .5   | 25.8          | 50.2 | 64.3                  |   |                      | 79.5                  | 1104                   |
| JUN    | 3.6   | 35.1             |                 |                  |      | 35.1          | 58.3 | 66.3                  |   |                      | 84.3                  | 1087                   |
| JUL    | 7.0   | 53.0             |                 |                  |      | 53.0          | 72.7 | 53.9                  |   |                      | 88.6                  | 1052                   |
| AUG    | 7.6   | 45.8             |                 |                  |      | 45.8          | 69.0 | 54.7                  |   |                      | 84.5                  | 1064                   |
| SEP    | 2.9   | 27.9             |                 |                  |      | 27.9          | 68.1 | 53.6                  |   |                      | 81.0                  | 1005                   |
| ост    | 1.5   | 17.8             | .1              | .4               | .1   | 18.0          | 68.0 | 65.6                  |   |                      | 83.7                  | 1038                   |
| NOV    | .9    | 22.2             |                 | 4.1              | .5   | 25.1          | 60.4 | 68.8                  |   |                      | 82.1                  | 994                    |
| DEC    | .2    | 12.3             | .3              | 16.7             | .2   | 24.9          | 49.4 | 76.3                  |   |                      | 83.6                  | 1020                   |
|        |       |                  |                 |                  |      |               |      |                       |   |                      |                       |                        |
| ANNUAL | 2.4   | 25.2             | .0              | 5.8              | .1   | 29.6          | 56.5 | 67.8                  |   | .0                   | 84.3                  | 12540                  |

......

# PERCENTAGE FREQUENCY OF OCCURRENCE OF THUNDERSTORMS FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

| HOURS (LST)  | JAN                                     | FEB  | MAR               | APR  | MAY  | JUN  | JUL | AUG | SEP | OCT | NOV             | DEC | ••  |
|--------------|---|------|-------------------|------|------|------|-----|-----|-----|-----|-----------------|-----|-----|
| 00-02        | · • • • • • • • • • • • • • • • • • • • |      | • • • • • • • • • | .6   | 1.7  | 1.7  | 1.1 |     |     |     | • • • • • • • • |     | • • |
| 03-05        |   |      |                   |      |      | 1.1  | 3.3 |     |     |     |                 |     |     |
| 06-08        |   |      |                   | .6   |      | .6   |     |     |     |     |                 |     |     |
| 09-11        |   |      |                   |      |      |      | 1.7 |     |     |     |                 |     |     |
| 12-14        |   |      |                   |      |      |      | 1.1 |     |     | 2.2 |                 |     |     |
| 15-17        |   |      |                   |      | 1.1  |      |     |     | 4.4 | 1.1 |                 |     |     |
| 18-20        |   |      |                   |      | 2.8  |      |     | 1.1 |     |     |                 |     |     |
| 21-23        |   |      |                   |      | .6   |      |     |     |     |     |                 |     |     |
| ALL<br>HOURS |   |      |                   | .2   | .8   | .4   | .9  | .1  | .6  | .4  |                 |     |     |
| TOTAL<br>OBS | 1379                                    | 1273 | 1426              | 1284 | 1380 | 1380 | 676 | 713 | 690 | 713 | 644             | 679 | ••  |

# PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN HOURS: ALL ...... PHENOMENA | CALM VARIABLE 331 - 050 051 - 150 151 - 180 181 - 240 241 - 330 NO OF OBS TSTMS LIQUID .8 79.3 3.3 1.7 7.4 121 PRECIP FREEZING PRECIP FROZEN 11.6 62.0 3.9 17.8 4.7 129 PRECIP .5 2.0 15.6 7.2 403 FOG 43.9 30.8 FOG WITH VIS 43.3 31.9 .5 1.3 15.5 7.5 386 GE 1/2 MILES TOTAL OBS | 489 6 536 17 24 146 161 1379

.......

|                              |       |                     |         |                       | M   | ONTH: FEB | HOURS: ALL |                     |
|------------------------------|-------|---------------------|---------|-----------------------|-----|-----------|------------|---------------------|
| TSTMS                        | ••••• | • • • • • • • • • • | ••••••• | • • • • • • • • • • • |     |           |            | • • • • • • • • • • |
| LIQUID<br>PRECIP             | 16.4  |                     | 43.4    | 9.8                   | 2.5 | 14.8      | 13.1       | 122                 |
| FREEZING<br>PRECIP           |       |                     |         |                       |     |           |            |                     |
| FROZEN<br>PRECIP             | 16.1  |                     | 74.2    |                       |     | 6.5       | 3.2        | 31                  |
| FOG                          | 40.9  |                     | 35.8    | .3                    | 1.9 | 11.0      | 10.2       | 374                 |
| FOG WITH VIS<br>GE 1/2 MILES | 39.9  |                     | 36.9    | .3                    | 2.0 | 10.3      | 10.6       | 358                 |
| TOTAL OBS                    | 380   | 3                   | 504     | 24                    | 25  | 167       | 170        | 1273                |

# PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

| USAFETAC, ASHE               | EVILLE NC | VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS |               |           |           |            |             |   |  |  |  |  |  |
|------------------------------|-----------|--|---------------|-----------|-----------|------------|-------------|---|--|--|--|--|--|
| STATION NUMBER               |           | LST TO UTO                                     | : - 9         |           |           | MONTH: MAR | HOURS: AJ.L |   |  |  |  |  |  |
| PHENOMENA                    | CALM      | VARIABLE                                       | 331 - 050     | 051 - 150 | 151 - 180 | 181 - 240  | 241 - 330   | NO OF OBS                               |  |  |  |  |  |
| TSTMS                        |           | • • • • • • • • • • • • •                      | ••••••        |           |           |            | ••••••      | • |  |  |  |  |  |
| LIQUID<br>PRECIP             | 20.2      | 1.2  | 46.0          | 4.3       | 1.2       | 20.2       | 6.7         | 163                                     |  |  |  |  |  |
| FREEZING<br>PRECIP           |           |  |               |           |           |            |             |   |  |  |  |  |  |
| FROZEN<br>PRECIP             | 25.0      |  | 41.7          |           |           | 8.3        | 25.0        | 12                                      |  |  |  |  |  |
| FOG                          | 54.8      |  | 15.7          | .8        | 4.1       | 22.0       | 2.5         | 363                                     |  |  |  |  |  |
| FOG WITH VIS<br>GE 1/2 MILES | 54.5      |  | 15.6          | .6        |           | 22.7       |             | 352                                     |  |  |  |  |  |
| ,                            | 460       | 11   | 386           | 55        | 43        | 331        | 140         | 1426                                    |  |  |  |  |  |
|                              |           |  |               |           |           | MONTH: APR | HOURS: ALL  |   |  |  |  |  |  |
| TSTMS                        | 50.0      |  |               |           |           |            | 50.0        | 2                                       |  |  |  |  |  |
| LIQUID<br>PRECIP             | 21.6      | 3.6  | 22.5          | 4.5       | 4.5       | 36.9       | 6.3         | 111                                     |  |  |  |  |  |
| FREEZING<br>PRECIP           |           |  |               |           |           |            |             |   |  |  |  |  |  |
| FROZEN<br>PRECTP             |           |  |               |           |           |            |             |   |  |  |  |  |  |
| FOG                          | 48.5      |  | 23.1          | 3.4       | 6.8       | 13.3       | 4.9         | 264                                     |  |  |  |  |  |
| FOG WITH VIS<br>GE 1/2 MILES | 49.4      |  | 2 <b>4.</b> 7 |           |           | 13.0       |             | 231                                     |  |  |  |  |  |
| TOTAL OBS                    | 464       | 31   | 261           | 38        | 50        | 300        | 140         | 1284                                    |  |  |  |  |  |

# PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA VERSUS WIND DIRECTION FROM HOURLY OBSEFVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAY HOURS: ALL ..... PHENOMENA CALM VAPIABLE 331 - 050 051 - 150 151 - 180 181 - 240 241 - 330 NO OF OBS ...... 27.3 9.1 18.2 27.3 9.1 27.4 7.7 6.5 33.9 4.8 11 TSTMS 9.1 14.3 5.4 FIGNID PRECIP FREEZING PRECIP FROZEN PRECIP 45.7 .3 13.5 2.6 7.3 26.4 4.1 341 FOG 13.6 6.5 26.5 FOG WITH VIS 2.8 4.3 324 46.0 .3 GE 1/2 MILES TOTAL ORS | 379 38 265 61 83 437 117 1380 1380 

|                              |      |     |      |      | M    | ONTH: JUN | HOURS: ALL |      |  |
|------------------------------|------|-----|------|------|------|-----------|------------|------|--|
| TSTMS                        | 50.0 |     |      |      | 16.7 |           | 33.3       | 6    |  |
| LIQUID<br>PRECIP             | 19.6 | 1.6 | 31.4 | 10.2 | 4.5  | 26.5      | 6.1        | 245  |  |
| FREEZING<br>PRECIP           |      |     |      |      |      |           |            |      |  |
| FROZEN<br>PRECIP             |      |     |      |      |      |           |            |      |  |
| FOG                          | 41.6 | .5  | 18.5 | .7   | 6.7  | 23.9      | 8.0        | 401  |  |
| FOG WITH VIS<br>GE 1/2 MILES | 41.3 | .5  | 18.4 | .8   | 6.6  | 24.2      | €.2        | 392  |  |
| TOTAL BS                     | 369  | 11  | 343  | 73   | 84   | 357       | 143        | 1380 |  |

# PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUNHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL HOURS: ALL PHENOMENA CALM VARIABLE 331 - 050 051 - 150 151 - 180 181 - 240 241 - 330 NO OF OBS ...... 33.3 33.3 16.7 6 4.1 11.3 12.4 97 16.7 TSTMS 12.4 40.2 4.1 LIQUID 27.8 PRECIP FREEZING PRECIP FROZEN PRECIP 2.9 16.3 4.6 239 17.6 FOG 58.6 58.3 17.9 2.6 4.7 FOG WITH VIS 16.6 235 GE 1/2 LES TOTAL OBS | 221 0 154 9 36 178 78 676

|                              |      |     |      |     | м   | ONTH: AUG | HOURS: ALL |     |
|------------------------------|------|-----|------|-----|-----|-----------|------------|-----|
| TSTMS                        |      |     |      |     |     | 100.0     |            | 1   |
| LIQUID<br>PRECIP             | 38.5 | 1.3 | 25.6 | 6.4 | 5.1 | 12.8      | 10.3       | 78  |
| FREEZING<br>PRECIP           |      |     |      |     |     |           |            |     |
| PRECIP                       |      |     |      |     |     |           |            |     |
| FOG                          | 51.9 |     | 20.6 |     | 1.3 | 15.6      | 10.6       | 160 |
| FOG WITH VIS<br>GE 1/2 MILES | 51.0 |     | 21.0 |     | 1.3 | 15.9      | 10.8       | 157 |
| TOTAL ORS                    | 182  | 16  | 257  | 45  | 21  | 100       | 92         | 713 |

# PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

| STATION NUMBER               | R: 471066 | STATION NA |           | (/TONGDUCHON | PERIOD OF RECORD: JUL 80 - JUN 90<br>MONTH: SEP HOURS: ALL |      |                           |           |  |  |
|------------------------------|-----------|------------|-----------|--------------|--|------|---------------------------|-----------|--|--|
| PHENOMENA                    | CALM      | VARIABLE   | 331 - 050 |              |  |      | 241 - 330                 | NO OF OBS |  |  |
| TSTMS                        |           |            | 25.0      | 25.0         | 25.0   | 25.0 | • • • • • • • • • • • • • | 4         |  |  |
| LIQUID<br>PRECIP             | 11.1      |            | 74.1      | 1.9          |  | 9.3  | 3.7                       | 54        |  |  |
| FREEZING<br>PRECIP           |           |            |           |              |  |      |                           |           |  |  |
| FROZEN<br>PRECIP             |           |            |           |              |  |      |                           |           |  |  |
| FOG                          | 46.4      |            | 34.5      | 1.7          | 2.1  | 10.6 | 4.7                       | 235       |  |  |
| FCG WITH VIS<br>GE 1/2 MILES | 45.0      |            | 35.1      | 1.9          | 1.9  | 10.9 | 5.2                       | 211       |  |  |
| TOTAL OBS                    | 187       | 7          | 283       | 24           | 19   | 91   | 79                        | 690       |  |  |
| •••••                        |           |            |           |              | •••••  |      | HOURS: ALL                | ••••••    |  |  |
|                              |           |            |           |              |  |      |                           |           |  |  |
| TSTMS                        |           |            | 33.3      |              |  | 33.3 | 33.3                      | 3         |  |  |
| LIQUID<br>PRECIP             | 10.5      |            | 21.1      | 5.3          | 13.2   | 42.1 | 7.9                       | 38        |  |  |
| FREEZING<br>PRECIP           |           |            |           |              |  |      |                           |           |  |  |
| FROZEN<br>PRECIP             |           |            |           |              |  |      |                           |           |  |  |
| FOG                          | 50.2      |            | 26.8      | 1.0          | 6.6  | 11.5 | 3.8                       | 287       |  |  |
| FOG WITH VIS<br>GE 1/2 MILES | 51.3      |            | 25.4      | 1.3          | 6.1  | 11.4 | 4.4                       | 228       |  |  |
| TOTAL OBS                    | 224       | 0          | 236       | 18           | 39   | 122  | 74                        | 713       |  |  |

TOTAL OBS 298 4 167

# PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: NOV HOURS: ALL ...... PHENOMENA CALM VARIABLE 331 - 050 051 - 150 151 - 180 181 - 240 241 - 330 NO OF OBS ...... TSTMS LIQUID 39.5 2.5 4.9 12.3 6.2 34.6 PRECIP FREEZING PRECIP 33.3 FROZEN 66.7 3 PRECIP 14.4 5.1 3.1 195 FOG 53.3 24.1 FOG WITH VIS 2.7 52.5 25.1 4.9 14.8 183 GE 1/2 MII-ES TOTAL OBS | 225 10 196 5 24 79 105 644 TOTAL OBS 225 10 196 MONTH: DEC HOURS: ALL TSTMS TIONID 70.8 12.5 12.5 4.2 24 PRECIP FREEZING PRECIP 12.1 15.2 FROZEN 63.6 9.1 3.3 PRECIP 16.4 25.5 .3 4.9 7.0 FOG 45.8 286 16.2 FOG WITH VIS 44.9 . 4 7.4 272 26.1 5.1 GE 1/2 MILES 

21 95

2

92

679

### PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTHS: ALL PHENOMENA | CALM VARIABLE 331 - 050 051 - 150 151 - 180 181 - 240 241 - 330 NO OF OBS 15.2 6.1 18.2 24.2 TSTMS 18.2 18.2 33 20.7 1.6 39.5 6.1 3.9 20.7 7.5 1302 LIQUID PRECIP FREEZING PRECIP 1.0 53.4 21.2 2.4 208 FROZEN 14.9 7.2 PRECIP FOG 47.7 . 1 23.9 1.0 4.4 17.0 5.9 3548 FOG WITH VIS 47.3 .1 24.2 .9 4.0 17.2 6.3 3329 GE 1/2 MILES TOTAL OBS | 3878 137 3588 371 469 2403 1391 12237

.......

| PPPPP     | PPPPPPPP AAAAA |         | RRRR  | RRRR | TTTTTTTTTT | REBERERE |            |      |  |
|-----------|----------------|---------|-------|------|------------|----------|------------|------|--|
| ppppppppp |                |         |       |      | RRRRR      | TTTTTTTT | BBBBBBBBBB |      |  |
|           |                | AAAAAAA |       |      |            |          |            |      |  |
| PP        | PP             | AA      | AA    | RR   | RR         | TT       | BB         | BB   |  |
| PP        | PP             | AA      | AA    | RR   | RR         | TT       | BB         | BB   |  |
| PPPPP     | PPPP           | AA      | AA    | RRRR | RRRRR      | TT       | BBBBBB     | BBBB |  |
| PPPPP     | PPP            | AAAAA   | AAAAA | RRRR | RRRR       | TT       | ввввв      | BBBB |  |
| PP        |                | ААААА   | AAAAA | RR   | RR         | TT       | BB         | BB   |  |
| PP        |                | AA      | AA    | RR   | RR         | TT       | BB         | BB   |  |
| PP        | PP             |         | AA    | RR   | RR         | TT       | BBBBBB     | BBBB |  |
| pp        |                | AA      | AA    | RR   | RR         | ਪ੍ਰਵਾ    | вавававая  |      |  |

### PART B

### PRECIPITATION, SNOWFALL, SNOW DEPTH SUMMARIES

ALL TABLES IN PART B ARE CREATED FROM SUMMARY OF DAY (SOD) DATA.

### PERCENT OCCURRENCE FREQUENCY.

THESE TABLES GIVE THE PERCENT OCCURRENCE FREQUENCY OF PRECIPITATION, SNOWFALL AND SNOW DEPTH. DATA IS SUMMARIZED FOR ALL YEARS COMBINED. SUMMARIES INCLUDE THE PERCENT OF DAYS WITH MEASURABLE AMOUNTS, PERCENT OF DAYS WITH NO AMOUNTS, PERCENT OF DAYS WITH TRACES, AND PERCENT OF DAYS WITH SPECIFIED AMOUNTS. SUMMARIES ALSO PROVIDE AN OBSERVATION COUNT. A VALUE OF ".0" INDICATES ONE OR MORE OCCURRENCES THAT, IN AGGREGATE, AMOUNT TO LESS THAN .05 PERCENT.

### MONTHLY TOTALS.

THESE TABLES GIVE THE TOTAL MONTHLY PRECIPITATION AND SNOWFALL RESPECTIVELY.
THEY ARE SUMMARIZED BY MONTH FOR ALL YEARS. THE TABLES ALSO GIVE THE GREATEST
AMOUNTS, LEAST AMOUNTS, MEAN, MEDIAN, STANDARD DEVIATIONS, AND TOTAL AVAILABLE
OBSERVATIONS. AN ASTERISK (\*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS
THAN 90% OF THE DATA ARE AVAILABLE. AN ASTERISK ALSO DENOTES A YEAR(S) WITH ONE
OR MORE MISSING AND/OR INCOMPLETE MONTHS. INCOMPLETE MONTHS/YEARS ARE NOT INCLUDED
IN STATISTICAL COMPUTATIONS. NOTE: LEAST AMOUNTS ARE DERIVED FROM COMPLETE
MONTHS/YEARS ONLY. ".00" MEANS NO PRECIPITATION FOR THE MONTH, ".0" MEANS NO
SNOWFALL FOR THE MONTH.

### DAILY EXTREMES.

THESE TABLES GIVE THE MAXIMUM DAILY REPORTED AMOUNTS (BY INDIVIDUAL YEAR-MONTH) FOR PRECIPITATION, SNOWFALL, AND SNOW DEPTH, RESPECTIVELY. THEY SHOW THE GREATEST AMOUNTS FOR EACH MONTH AND THE TOTAL NUMBER OF AVAILABLE OBSERVATIONS FOR EACH MONTH AND YEAR. AN ASTERISK (\*) INDICATES A MONTH FOR WHICH LESS THAN 90% OF DATA ARE AVAILABLE. AN ASTERISK ALSO DENOTES A YEAR(S) WITH ONE OR MORE MISSING AND/OR INCOMPLETE MONTHS. ".00" MEANS NO PRECIPITATION FOR THE MONTH, ".0" MEANS NO SNOW DEPTH FOR THE MONTH.

SNOWFALL/SNOW DEPTH--FIRST AND LAST DAYS OF OCCURRENCE BY SNOW YEAR.

THIS SUMMARY GIVES THE FIRST AND LAST OCCURRENCES OF SNOWFALL AND SNOW
DEPTH FOR THE SNOW-YEAR DURING THE PERIOD OF RECORD. FOR THIS SUMMARY, THE
SNOW-YEAR IS CONSIDERED TO RUN FROM 1 AUGUST TO 31 JULY. TABLES SUMMARIZE
THE DATA BY SNOW-YEAR, BY MONTH, AND BY DAY. THE FIRST (OR LAST) ENTRY IN
COLUMN 69 OF AWS FORMS 10/10A (OR EQUIVALENT) AS EITHER A TRACE OR A MEASURABLE
AMOUNT DEFINES THE FIRST (OR LAST) SNOWFALL FOR THE THE YEAR. THE FIRST (OR LAST)
ENTRY IN COLUMN 69 OTHER THAN ".O" OR "TRACE" DEFINES THE FIRST (OR LAST)
MEASURABLE SNOWFALL. FINALLY, THE 1200 GMT ENTRY COLUMN 70 OF AWS FORM 10/10A
(OR EQUIVALENT) DEFINES THE FIRST (OR LAST) OCCURRENCE OF SNOW DEPTH. THE LAST
SNOW DEPTH IS CONSIDERED THE LAST SNOW MELT. THIS SUMMARY IS NOT PROVIDED
WHEN NO SNOWFALL OCCURS DURING THE GIVEN POR.

- NOTE 1. IF THE MINIMUM AMOUNT RECORDED IN THE MONTHLY TOTALS OR DAILY EXTREMES IS A TRACE, THE WORD "TRACE" WILL APPEAR IN THE APPROPRIATE COLUMN.
- NOTE 2. TABLES INCLUDE STATISTICAL DATA ONLY WHEN FIVE (5) OR MORE SETS OF COMPLETE MONTHS ARE AVAILABLE.
- NOTE 3. THE OBSERVATION COUNTS OR THE STATION HISTORY MIGHT PROVIDE CLUES AS TO WHY CERTAIN DATA ARE MISSING. FOR EXAMPLE, ONLY A FEW MISSING OBSERVATIONS MIGHT IMPLY MISSING DATA BECAUSE OF EQUIPMENT MALFUNCTION, BUT MORE THAN SEVERAL MISSING OBSERVATIONS USUALLY MEANS THE STATION IS (OR HAS BEEN) CLOSED.
- NOTE 4. IN DAILY AND MONTHLY AMOUNTS SUMMARIES, THE LAST ENTRY ON THE PAGE GIVES THE GREATEST AMOUNT FOR THE PERIOD OF RECORD.
- NOTE 5. BEFORE JANUARY 1956, SNOWFALL OCCURRENCES IN THE SUMMARY OF DAY INCLUDED HAIL.
- NOTE 6. SNOW DEPTH REPORTING TIMES FOR USAF, NAVY AND CIVIL STATIONS ARE AS FOLLOWS:

| AIR FORCE             |          | NAVY AND NATIONAL WEATHER | SERVICE  |  |  |
|-----------------------|----------|---------------------------|----------|--|--|
| THROUGH 1945:         | 0800 LST | THROUGH JUN 1952:         | 0030 GMT |  |  |
| JAN 1946 TO MAY 1957: | 1230 LST | JUN 1952 TO MAY 1957:     | 1230 GMT |  |  |
| JUN 1957 TO PRESENT:  | 1200 GMT | JUN 1957 TO PRESENT:      | 1200 GMT |  |  |

NOTE 7. 24-HOUR PRECIPITATION (INCLUDING SNOWFALL AND SNOW DEPTH) VALUES DERIVED FROM PART TIME PERIODS MAY NOT REFLECT TRUE 24-HOUR AMOUNTS. RECORDED AMOUNTS FOLLOWING WEEKENDS AND/OR HOLIDAYS FREQUENTLY REPRESENT AMOUNTS MEASURED FOR PERIODS GREATER THAN 24 HOURS. IN ADDITION, 24-HOUR AMOUNTS MAY NOT REPRESENT THE STANDARD CLIMATOLOGICAL 24-HOUR "MIDNIGHT TO MIDNIGHT" AMOUNT. DATA FROM PART TIME PERIODS MAY NOT ACCURATELY REFLECT NIGHTTIME PRECIPITATION EVENTS.

### CONVERSIONS:

- 1 INCH = 25.39998 MILLIMETERS
- 1 MILLIMETER = .03937 INCHES

# OPERATING LOCATION 'A' PERCENTAGE FREQUENCY OF OCCURRENCE OF PRECIPITATION IN INCHES USAFETAC, ASHEVILLE NC FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: 5305-9006

| STATION NUMBER:           | 471066 |      | N NAME:<br>OUTC: -0 |      | EY/TONGD | UCHON KO | 1    | PERIOD OF RECORD: 5305-9006 MONTH: ALL HOURS: ALL |      |      |      |      |       |
|---------------------------|--------|------|---------------------|------|----------|----------|------|---|------|------|------|------|-------|
| AMOUNTS<br>(INCHES)       | JAN    | FEB  | MAR                 | APR  | MAY      | NUL      | JUL  | Aug   | SEP  | OCT  | NOV  | DEC  | ANN   |
| NONE                      | 65.7   | 71.0 | 66.9                | 65.1 | 66.3     | 56.1     | 38.7 | 48.2  | 65.7 | 74.2 | 64.3 | 66.6 | 62.3  |
| TRACE                     | 17.1   | 13.3 | 12.0                | 10.5 | 10.0     | 11.7     | 9.0  | 9.1   | 7.4  | 8.2  | 12.5 | 15.6 | 11.4  |
| .01                       | 2.1    | 1.4  | 2.1                 | 1.4  | 1.5      | 2.3      | 2.5  | 2.0   | 1.7  | 1.3  | 2.4  | 1.7  | 1.9   |
| .0205                     | 4.7    | 3.6  | 5.7                 | 5.1  | 3.6      | 6.3      | 6.3  | 4.6   | 4.5  | 4.0  | 5.8  | 5.7  | 5.0   |
| .0610                     | 3.5    | 3.2  | 3.8                 | 3.2  | 2.4      | 3.6      | 5.1  | 3.0   | 2.9  | 2.1  | 3.1  | 3.6  | 3.3   |
| .1125                     | 3.9    | 3.5  | 4.1                 | 5.0  | 5.7      | 7.2      | 6.4  | 5.3   | 3.5  | 3.7  | 5.6  | 3.7  | 4.8   |
| .2650                     | 2.3    | 2.1  | 2.6                 | 3.8  | 5.0      | 4.2      | 6.3  | 6.5   | 4.2  | 2.7  | 3.5  | 1.9  | 3.8   |
| .51-1.00                  | .8     | 1.6  | 1.9                 | 3.4  | 2.9      | 4.0      | 8.5  | 7.6   | 4.2  | 2.8  | 1.7  | 1.0  | 3.4   |
| 1.01-2.50                 |        | .3   | .7                  | 2.3  | 2.3      | 3.5.     | 10.9 | 9.2   | 3.9  | 1.0  | .9   | .2   | 2.9   |
| 2.51-5.00                 |        |      | .1                  | .1   | .3       | .9       | 4.6  | 3.3   | 1.9  | .1   | .1   |      | .9    |
| 5.01-10.00                |        |      |                     | .1   |          | .2       | 1.6  | 1.2   | .1   |      |      |      | .3    |
| 10.01-20.00               |        |      |                     |      | .1       |          | .1   |   | .1   |      |      |      | .0    |
| OVER 20.00                |        |      |                     |      |          |          |      |   |      |      |      |      |       |
| DAYS WITH<br>MEAS AMTS    | 17.2   | 15.7 | 21.1                | 24.4 | 23.7     | 32.2     | 52.2 | 42.7  | 26.9 | 17.6 | 23.1 | 17.8 | 26.3  |
| TOTAL NO. OF OBSERVATIONS | 1059   | 978  | 1092                | 1040 | 1095     | 1090     | 1051 | 1063  | 1004 | 1038 | 1021 | 1048 | 12579 |

# TOTAL MONTHLY PRECIPITATION AMOUNTS IN INCHES FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: -09

MONTH: ALL BU'RS: ALL

| LST TO UTC: -09 |       |   |                 |                 |        |        | MONTH: ALL HC'IRS: ALL |        |        |        |       |       |        |
|-----------------|-------|---|-----------------|-----------------|--------|--------|------------------------|--------|--------|--------|-------|-------|--------|
| YEAR            | JAN   | FEB                                     | MAR             | APR             | MAY    | JUN    | JUL                    | AUG    | SEP    | OCT    | NOV   | DEC   | ANNUAL |
| 53              |       | • | • • • • • • • • | • • • • • • • • | 4.33*  | 5.45   | 6.84*                  |        | •••••  | .15*   | .20   | 1.14  | 18.11* |
| 54              | .58   | 4.08                                    | .11             | 1.82            | 2.19   | 6.04   | 16.35                  | 10.87  | 4.08   | 1.77   | .58   | 1.48  | 49.95  |
| 55              | .83   | .94                                     | .58             | 2.47            | 2.82   | 12.06  | 20.51                  | 2.66   | 7.91   | 1.19   | 2.04  | .40   | 54.41  |
| 56              | .47   | 1.13                                    | 4.63            | 1.86            | 1.83   | 9.49   | 18.38                  | 2.24   | 11.14  | 1.08   | .53   | .71   | 53.49  |
| 57              | .86   | .57                                     | .43             | 3.34            | 1.21   | -41    | 18.04                  | 11.71  | .13    | 2.10   | 1.08  | 3.12  | 43.00  |
| 58              | 1.06  | .50                                     | .27             | 1.21            | .12    | .69    | 8.46                   | 4.67   | 5.60   | .30    | .41   | .26   | 23.55  |
| 59              | .20   | .72                                     | .66             | 1.78            | 1.47   | .97    | 10.77                  | 16.22  | 5.84   | .87    | .58   | .33   | 40.41  |
| 60              | TRACE | TRACE                                   | 1.11            | TRACE           | .53    | 5.21   | 6.99                   | 4.03   | .84    | .20    | .41   | .37   | 19.69  |
| 61              | 1.09  | .13                                     | .23             | 1.45            | 1.56   | .81    | 17.62                  | 17.91  | 5.73   | TRACE  | .66   | .08   | 47.27  |
| 62              | .37   | 1.41                                    | .45             | .82             | TRACE  | 1.92   | 8.13                   | 10.50  | 2.17   | TRACE  | .10   | .40   | 26.27  |
| 63              | .36   | .37                                     | .64             | 2.89            | 2.59   | 8.30   | 18.00                  | 4.42   | 1.30   | TRACE  | .36   | .31   | 39.54  |
| 64              | .36   | .88                                     | .34             | 5.02            | .49    | 1.76   | 24.42                  | 22.11  | 7.52   | 2.17   | .88   | .37   | 66.32  |
| 65              | .32   | .01                                     | .56             | .80             | .57    | .26    | 30.95                  | 12.39  | 1.17   | 1.93   | 3.34  | .15   | 52.45  |
| 66              | .33   | 1.27                                    | 2.40            | .00*            | 1.76   | 7.94   | 45.84                  | 10.54  | 15.26  | 3.94   | 2.36  | .34   | 91.98* |
| 67              | .60   | 2.16                                    | 3.46            | 2.96            | 2.61   | 3.89   | 18.31                  | 21.89  | 3.21*  | .74*   | 1.69* | .47*  | 61.99* |
| 68              | .38*  | .40*                                    | 1.80*           | 1.78*           | 2.29*  | 2.54*  | 15.49*                 | 12.41* | 3.27*  | 4.54*  | 1.63* | .59*  | 47.12* |
| 69              | 1.18* | 1.27*                                   | .15*            | 9.65*           | 13.15* | 1.92*  | 24.33*                 | 13.45* | 4.35*  | -58*   | 1.25* | .98*  | 72.27* |
| 70              | .24*  | 1.86*                                   | .80*            | .11*            | 2.33*  | 7.88*  | 10.84*                 | 17.79* | 30.19* | 3.91*  | 2.71* | 1.10* | 79.76* |
| 71              | .58*  | 1.27*                                   | 2.13*           | 2.03*           | 3.85*  | 3.84*  | 20.32*                 | 7.20*  | 9.20*  | 1.15*  | -40*  | 1.54* | 53.51* |
| 72              | 2.19* | .72*                                    | 2.24*           | 1.39*           | 3.73*  | 1.76*  | 11.69*                 | 28.70* | 2.69*  | 3.14*  | 3.28* | .29*  | 61.82* |
| 73              | .71*  | .03*                                    | .62*            | 5.11*           | 3.06*  | 3.32*  | 7.34*                  | 14.88* | 3.30*  | .27*   | 1.21* | .18*  | 40.03* |
| 74              | .18*  | .55*                                    | .71*            | .93*            | 9.83*  | 2.52*  | 7.00*                  | 12.94* | 3.43*  | 2.03*  | .19*  | .29*  | 40.60* |
| 75              | .39*  | .27*                                    | 1.67*           | 3.86*           | 3.51*  | 2.39*  | 28.44*                 | 6.60*  | 8.05*  | .87*   | .97*  | .47*  | 57.49* |
| 76              | .17*  | 1.68*                                   | .30*            | 1.26*           | 2.88*  | 3.25   | 5.21*                  | 26.46  | 4.70*  | 1.50*  | 1.83* | 1.00* | 50.24* |
| 77              | .08*  | TRACE*                                  | .69*            | 7.91            | 1.90*  | 1.64*  | 13.49*                 | 7.65*  | 2.23*  | TRACE* | 3.11* | 1.91* | 40.61* |
| 78              | 1.10* | 1.03*                                   | 1.65            | 1.13*           | 1.19*  | 14.75* | 12.25*                 | 21.23  | 3.65*  | 1.22*  | -40*  | .99*  | 60.59* |
| 79              | .89*  | 1.37*                                   | 3.76            | 6.96*           | 3.71*  | 9.03   | 7.00*                  | 13.63* | 1.48*  | .35*   | .83*  | 1.82* | 50.83* |
| 80              | .47*  | TRACE                                   | .76             | 6.91            | 2.84   | 2.58   | 11.24                  | 11.85  | 3.92   | .86    | .53   | .83   | 42.79* |
| 81              | .44   | .34                                     | 1.57            | ?.32            | 2.80   | 5.97   | 29.89                  | 9.41   | 9.04   | 2.00   | 1.33  | .31   | 65.42  |
| 82              | .91   | .14                                     | 1.76            | . 14            | 5.06   | .80    | 5.08                   | 14.46  | .37    | 2.87   | 5.98  | 1.36  | 38.93  |
| 83              | .60   | .47                                     | 2.44            | 5.07            | 2.36   | 2.72   | 17.89                  | 3.87   | 5.10   | 2.17   | 1.12  | .46   | 44.27  |
| 84              | .22   | .20                                     | .74             | 2.73            | 4.25   | 3.93   | 11.02                  | 19.50  | 12.87  | .59    | .90   | .90   | 57.85  |
| 85              | .99   | .89                                     | 2.07            | 3.10            | 5.85   | 1.17   | 6.07                   | 16.32  | 15.41  | 5.29   | 1.03* | 2.17  | 60.36* |

## TOTAL MONTHLY PRECIPITATION AMOUNTS IN INCHES FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006 LST TO UTC: -09 MONTH: ALL HOURS: ALL

|           |       | ь     | 31 10 010 | -09   |       |       |       |       | POWI  | 1. 200 | 1100100. | TÚD   |        |
|-----------|-------|-------|-----------|-------|-------|-------|-------|-------|-------|--------|----------|-------|--------|
| YEAR      | JAN   | FEB   | MAR       | APR   | MAY   | JUN   | JUL   | AUG   | SEP   | OCT    | NOV      | DEC   | ANNUAL |
| 86        |       | 39    | 1.40      | .62   | 2.60  | 4.94  | 14.37 | 12.98 | 3.79  | 2.75   | 1.89     | 1.12  | 47.23  |
| 87        | 1.80  | 1.18  | 1.04      | 2.28  | 3.45  | 5.27  | 15.18 | 23.94 | 1.75  | .64    | 2.48*    | TRACE | 59.01* |
| 88        | .15   | .21   | 1.04      | 2.41  | 2.03  | 3.44  | 24.08 | 3.22  | 2.66  | .45    | .34      | .32   | 40.35  |
| 89        | 1.69  | .75   | 4.73      | .67   | 2.64  | 4.03  | 9.04  | 8.59  | 5.94  | 2.15   | 7.90     | .41   | 48.54  |
| 90        | 2.47  | 2.41  | 3.14      | 4.25  | 3.53  | 14.84 |       |       |       |        |          |       | 30.65* |
|           |       |       |           |       |       |       |       |       |       |        |          |       |        |
| LEAST     | TRACE | TRACE | .11       | TRACE | TRACE | .26   | 5.08  | 2.24  | .13   | TRACE  | .10      | TRACE | 19.69  |
| GREATEST  | 2.47  | 4.08  | 4.73      | 9.65  | 13.15 | 14.84 | 45.84 | 28.70 | 30.19 | 5.29   | 7.90     | 3.12  | 91.98  |
| MEAN      | .71   | .85   | 1.55      | 2.59  | 2.29  | 4.54  | 16.94 | 12.46 | 5.63  | 1.53   | 1.52     | .72   | 45.21  |
| MEDIAN    | .53   | .57   | 1.04      | 2.32  | 2.36  | 3.91  | 16.99 | 11.78 | 5.10  | 1.19   | .77      | .40   | 47.23  |
| SD        | .587  | .921  | 1.351     | 1.986 | 1.451 | 3.688 | 0.353 | 7.185 | 4.553 | 1.341  | 1.947    | .725  | 12.615 |
| TOTAL OBS | 1059  | 978   | 1092      | 1040  | 1095  | 1090  | 1051  | 1063  | 1004  | 1038   | 1021     | 1048  | 12579  |

THE GREATEST VALUE OF 45.84 OCCURRED ON 07/66

NOTE: \*THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

# EXTREME DAILY PRECIPITATION AMOUNTS IN INCHES FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006 LST TO UTC: -09 MONTH: ALL HOURS: ALL

|      |       | LS     | T TO UTC      | : -09       |             |       |              |       | MONTH           | I: ALL | HOURS: A | LL   |        |
|------|-------|--------|---------------|-------------|-------------|-------|--------------|-------|-----------------|--------|----------|------|--------|
| YEAR | JAN   | FEB    | MAR           | APR         | MAY         | JUN   | JUL          | AUG   | SEP             | OCT    | NOV      | DEC  | ANNUAL |
| 53   |       | •••••  | • • • • • • • |             | 1.73*       | 1.24  | 2.49*        |       | • • • • • • • • | .15*   | .20      | .89  | 2.49*  |
| 54   | .23   | 1.05   | .10           | .79         | .90         | 1.96  | 2.90         | 1.79  | 1.32            | .64    | .35      | .75  | 2.90   |
| 55   | .30   | .30    | .24           | .79         | 1.04        | 4.49  | 5.63         | 1.82  | 2.32            | .90    | .93      | .12  | 5.63   |
| 56   | .15   | .87    | 2.50          | £ 4         | E0.         | 2.82  | E 05         | 1.27  | 4.21            | .38    | .39      | .31  | 5.95   |
| 57   | .15   | .21    | .12           | .64<br>1.40 | .59<br>1.02 | .18   | 5.95<br>4.61 | 2.18  | .05             | .76    | .34      | 1.74 | 4.61   |
| 58   | .40   |        | .12           |             |             | .41   | 4.25         | 1.99  | 2.29            | .19    | .20      | .21  | 4.25   |
|      |       | .50    |               | . 47        | .10         |       |              | 6.82  | 2.54            |        |          |      | 6.82   |
| 59   | .10   | .31    | .45           | .92         | •69<br>30   | .21   | 2.65         |       |                 | .55    | .58      | .30  |        |
| 60   | TRACE | TRACE  | .83           | TRACE       | .38         | 3.15  | 2.24         | 1.07  | .28             | .20    | .32      | .27  | 3.15   |
| 61   | .33   | .10    | .20           | 1.19        | 1.27        | .23   | 6.41         | 7.19  | 2.08            | TRACE  | .40      | .07  | 7.19   |
| 62   | .23   | 1.02   | .20           | -40         | TRACE       | 1.17  | 4.89         | 2.08  | .92             | TRACE  | .10      | .10  | 4.89   |
| 63   | .10   | .36    | .64           | 1.21        | •90         | 5.52  | 3.21         | 1.67  | .73             | TRACE  | .14      | .10  | 5.52   |
| 64   | .18   | .52    | .12           | 1.14        | .44         | .86   | 7.87         | 5.51  | 3.74            | 1.67   | .42      | .18  | 7.87   |
| 65   | .14   | .01    | .44           | .46         | .15         | .14   | 6.90         | 2.01  | .51             | 1.21   | 1.24     | .12  | 6.90   |
| 66   | .30   | .94    | .81           | .00*        | .58         | 3.82  | 7.79         | 2,91  | 4.73            | 1.39   | 1.18     | .20  | 7.79*  |
| 67   | .41   | 1.21   | 1.81          | .84         | 1.46        | 1.07  | 6.60         | 4.86  | 1.23*           | .26*   | .80*     | .29* | 6.60*  |
| 68   | .18*  | .40*   | 1.23*         | .83*        | .70*        | 1.58* | 4.04*        | 4.16* | 2.66*           | 2.22*  | 1.17*    | .21* | 4.16*  |
| 69   | .35*  | .51*   | .07*          | 5.20*       | 10.47*      | .65*  | 3.89*        | 3.75* | 1.95*           | .30*   | .42*     | .25* | 10.47* |
| 70   | .22*  | .83*   | .50*          | -09*        | .73*        | 2.09* | 2.91*        | 5.51* | 11.69*          | 2.54*  | 1.54*    | .50* | 11.69* |
| 71   | .21*  | .34*   | 1.30*         | .84*        | 1.59*       | 1.37* | 3.82*        | 3,64* | 3.07*           | .74*   | .24*     | .70* | 3.82*  |
| 72   | .83*  | .53*   | .56*          | .50*        | 1.16*       | 1.13* | 3.73*        | 6.63* | .69*            | .91*   | 1.06*    | .11* | 6.63*  |
| 73   | .56*  | .02*   | .30*          | 1.96*       | 1.31*       | 1.55* | 2.41*        | 2.80* | 1.25*           | .13*   | .50*     | .07* | 2.80*  |
| 74   | .15*  | .14*   | .30*          | .37*        | 3.78*       | .93*  | 1.83*        | 3.43* | 2.06*           | .90*   | .09*     | .27* | 3.78*  |
| 75   | .28*  | .15*   | .60*          | 2.17*       | 1.09*       | .93*  | 7.12*        | 2.29* | 1.93*           | .52*   | .39*     | .36* | 7.12*  |
| 76   | .14*  | .89*   | .25*          | .50*        | .99*        | 1.38  | 1.45*        | 9.82  | 2.45*           | .65*   | .70*     | .64* | 9.82*  |
| 77   | .06*  | TRACE* | .57*          | 2.53        | 1.26*       | .80*  | 4.15*        | 5.02* | 1.54*           | TRACE* | .83*     | .53* | 5.02*  |
| 78   | .45*  | .51*   | .94           | .21*        | 1.10*       | 6.12* | 3.00*        | 4.49  | 1.32*           | .51*   | .20*     | .35* | 6.12*  |
| 79   | .64*  | .37*   | 1.84          | 2.08*       | 1.28*       | 2.47  | 1.85*        | 6.24* | .52*            | .20*   | .62*     | .97* | 6.24*  |
| 80   | .31*  |        | .51           | 2.41        | .70         | .69   | 4.37         | 3.18  | 2.02            | .50    | .25      | .30  | 4.37*  |
| 80   | .31^  | TRACE  | .51           | 2.41        | .70         | .69   | 4.37         | 3.10  | 2.02            | .50    | .25      | .30  | 4.37   |
| 81   | .21   | .12    | .72           | 1.28        | 1.01        | 2.69  | 5.27         | 3.39  | 4.93            | .57    | .51      | .11  | 5.22   |
| 82   | .83   | .08    | .51           | -08         | 2.65        | .30   | 1.96         | 8.33  | .28             | 2.07   | 2.39     | .38  | 8.33   |
| 83   | .50   | .21    | 1.01          | 1.50        | 1.16        | 1.69  | 3.60         | 1.15  | 2.51            | 1.11   | .39      | .15  | 3.60   |
| 84   | .12   | .13    | .25           | 1.12        | 2.32        | .93   | 2.39         | 5.44  | 9.37            | .44    | .36      | .66  | 9.37   |
| 85   | .35   | .41    | 1.69          | .92         | 2.15        | .42   | 2.47         | 5.32  | 4.56            | 1.46   | .30*     | 1.27 | 5.32*  |
|      |       |        |               |             |             |       |              |       |                 |        |          |      |        |

## EXTREME DAILY PRECIPITATION AMOUNTS IN INCHES FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006

LST TO UTC: -09 MONTH: ALL HOURS: ALL

| YEAR                       | JAN                             | FEB                             | MAR                               | APR                                | MAY                       | JUN   | JUL                           | AUG                         | SEP                         | OCT                       | NOV                                | DEC                        | ANNUAL                                  |
|----------------------------|---------------------------------|---------------------------------|-----------------------------------|------------------------------------|---------------------------|---|-------------------------------|-----------------------------|-----------------------------|---------------------------|------------------------------------|----------------------------|---|
| 86<br>87<br>88<br>89<br>90 | .23<br>.62<br>.06<br>.38<br>.89 | .20<br>.84<br>.10<br>.29<br>.74 | .44<br>.38<br>.62<br>3.49<br>1.21 | .43<br>1.69<br>1.06<br>.27<br>2.10 | .60<br>1.97<br>.99<br>.78 | JUN<br>1.57<br>2.13<br>1.12<br>1.22<br>3.58 | 3.73<br>3.81<br>10.18<br>2.15 | 2.95<br>7.51<br>.79<br>2.93 | 2.15<br>.95<br>1.92<br>3.90 | 1.09<br>.44<br>.39<br>.58 | NOV<br>.70<br>1.10*<br>.24<br>3.49 | .62<br>TRACE<br>.27<br>.24 | 3.73<br>7.51*<br>10.18<br>3.90<br>3.58* |
| GREATEST                   | .89                             | 1.21                            | 3.49                              | 5.20                               | 10.47                     | 6.12  | 10.18                         | 9.82                        | 11.69                       | 2.54                      | 3.49                               | 1.74                       | 11.69                                   |
| TOTAL OBS                  | 1059                            | 978                             | 1092                              | 1040                               | 1095                      | 1090  | 1051                          | 1063                        | 1004                        | 1038                      | 1021                               | 1048                       | 12579                                   |

THE GREATEST VALUE OF 11.69 OCCURRED ON 09/17/70

NOTE: \*THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

......

### PERCENTAGE FREQUENCY OF OCCURRENCE OF SNOWFALL IN INCHES

FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006 LST TO UTC: -09 MONTH: ALL HOURS: ALL AMOUNTS JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV DEC ANN (INCHES) 69.6 79.4 86.6 99.0 100.0 99.9 100.0 100.0 100.0 99.5 94.4 77.5 92.3 15.0 .5 4.1 4.9 TRACE 18.2 11.5 9.2 .9 .1 2.5 .9 0.1-0.4 3.0 .6 3.6 1.5 .1 0.5-1.4 4.9 3.1 1.8 .3 2.7 1.1 .5 1.6 1.5-2.4 1.6 1.5 .6 . 4 .2 .5 .2 2.5-3.4 .9 .9 .1 3.5-4.4 .8 . 3 .2 . 1 4.5-6.4 .3 .2 .2 . 1 .0 6.5-10.4 .1 . 1 .1 10.5-15.4 15.5-25.4 25.5-50.4 OVER 50.4 DAYS WITH MEAS AMTS 12.2 9.1 4.2 .1 1.5 7.5 2.8 TOTAL NO. OF 977 1093 1044 1094 1090 1052 1063 1005 1039 1022 1020 12558 OBSERVATIONS 1059

# TOTAL MONTHLY SNOWFALL AMOUNTS IN INCHES FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006 LST TO UTC: -09 MONTH: ALL HOURS: ALL

|     |        | Ге     | ST TO UTC | : -09  |     |       |     |     | PIONIT | : ALL  | HOURS: A | πn     |        |
|-----|--------|--------|-----------|--------|-----|-------|-----|-----|--------|--------|----------|--------|--------|
| EAR | JAN    | FEB    | MAR       | APR    | MAY | JUN   | JUL | AUG | SEP    | OCT    | NOV      | DEC    | ANNUAL |
| 53  |        |        |           |        | .0* | .0    | .0* |     |        | .0*    | .0       | TRACE  | TRACE* |
| 54  | 3.5    | TRACE  | TRACE     | .0     | .0  | .0    | .0  | .0  | .0     | .0     | .0       | *      | 3.5*   |
| 55  | 8.5    | 5.8    | TRACE     | .0     | .0  | .0    | .0  | .0  | .0     | .0     | TRACE    | 19     | 16.2   |
| 56  | 2.9    | 11.1   | 6.4       | .0     | .0  | .0    | .0  | .0  | .0     | .0     | .9       | 5.1    | 26.4   |
| 57  | 4.5    | 5.6    | 1.7       | .0     | .0  | .0    | .0  | .0  | .0     | .0     | .0       | .7     | 12.5   |
| 58  | 8.1    | 5.0    | 1.0       | .0     | .0  | .0    | .0  | .0  | .0     | .0     | .0       | 2.1    | 16.2   |
| 59  | 2.0    | .2     | TRACE     | .0     | .0  | .0    | .0  | .0  | .0     | .0     | .0       | .3     | 2.5    |
| 60  | TRACE  | TRACE  | .0        | .0     | .0  | .0    | -0  | .0  | .0     | .0     | TRACE    | .8     | .8     |
| 61  | 11.0   | 1.0    | 2.0       | .0     | .c  | .0    | .0  | .0  | .0     | .0     | .0       | TRACE  | 14.0   |
| 62  | 4.6    | 6.1    | 4.0       | .2     | .0  | TRACE | .0  | .0  | .0     | .0     | TRACE    | 3.4    | 18.3   |
| 63  | 3.6    | 3.7    | TRACE     | TRACE  | .0  | .0    | .0  | .0  | .0     | .0     | . 4      | 1.4    | 9.1    |
| 64  | 2.4    | 8.6    | 2.4       | .0     | .0  | .0    | .0  | .0  | .0     | .0     | TRACE    | TRACE  | 13.4   |
| 65  | 3.4    | . 1    | TRACE     | .0     | .0  | .0    | .0  | .0  | .0     | .0     | .5       | .1     | 4.1    |
| 66  | .3     | 2.9    | 4.8       | .0     | .0  | .0    | .0  | .0  | .0     | TRACE  | 1.6      | 2.7    | 12.3   |
| 67  | 1.7    | 2.7    | TRACE     | TRACE  | .0  | .0    | .0  | .0  | .0*    | .0*    | TRACE*   | 4.4*   | 8.8*   |
| 68  | 4.6*   | TRACE* | 1.2*      | .0*    | .0* | .0*   | .0* | .0* | .0*    | .0*    | TRACE*   | .4*    | 6.2*   |
| 69  | 12.7*  | 3.3*   | .7*       | TRACE* | .0* | .0*   | .0* | .0* | .0*    | TRACE* | TRACE*   | 6.8*   | 23.5*  |
| 70  | 2.8*   | 1.1*   | 6.5*      | .0*    | .0* | .0*   | .0* | .0* | .0*    | .0*    | TRACE*   | 2.8*   | 13.2*  |
| 71  | 8.9*   | 6.9*   | 5.4*      | .0*    | .0* | .0*   | .0* | .0* | .0*    | .0*    | .0*      | 4.5*   | 25.7*  |
| 72  | 2.5*   | 6.5*   | TRACE*    | .0*    | .0* | .0*   | .0* | .0* | .0*    | .0*    | 3.3*     | TRACE* | 12.3*  |
| 73  | 1.1*   | .0*    | .2*       | .0*    | .0* | .0*   | .0* | .0* | .0*    | .0*    | 1.8*     | 2.0*   | 5.1*   |
| 74  | 2.7*   | 2.8*   | 2.2*      | .0*    | .0* | .0*   | .0* | .0* | .0*    | .0*    | .4*      | .4*    | 8.5*   |
| 75  | 1.0*   | 1.3*   | 1.0*      | •0*    | .0* | .0*   | .0* | .0* | .0*    | .0*    | .0*      | .1*    | 3.4*   |
| 76  | TRACE* | 1.0*   | TRACE*    | .0.    | .0* | .0    | .0* | .0  | .0*    | TRACE* | 1.2*     | 1.6*   | 3.8*   |
| 77  | .2*    | TRACE* | .3*       | TRACE  | .0* | .0*   | .0* | .0* | .0*    | .0*    | 2.8*     | 5.2*   | 8.5*   |
| 78  | 11.7*  | 6.8*   | 1.4       | .0*    | .0* | .0*   | .0* | .0  | .0*    | .0*    | .0*      | TRACE* | 19.9*  |
| 79  | 4.9*   | 4.4*   | TRACE     | .0*    | .0* | .0    | .0* | .0* | .0*    | .0*    | TRACE*   | 8.0*   | 17.3*  |
| 80  | .7*    | TRACE  | TRACE     | .0     | .0  | .0    | .0  | .0  | .0     | TRACE  | TRACE    | 6.7    | 7.4*   |
| 81  | 7.7    | 3.0    | 1.0       | .0     | .0  | .0    | .0  | .0  | .0     | TRACE  | 2.0      | 2.6    | 16.3   |
| 82  | .8     | . 3    | TRACE     | .0     | .0  | .0    | .0  | .0  | .0     | .0     | .0       | 9.7    | 10.8   |
| 83  | 1.1    | 6.6    | .5        | TRACE  | .0  | .0    | .0  | .0  | .0     | .0     | 1.5      | 4.2    | 13.9   |
| 84  | 2.0    | 2.8    | 3.4       | .0     | .0  | .0    | .0  | .0  | .0     | .0     | TRACE    | .9     | 9.1    |
| 85  | 18.5   | 9.3    | TRACE     | .0     | .0  | .0    | .0  | .0  | .0     | .0     | .4*      | 3.8    | 32.0*  |

# TOTAL MONTHLY SNOWFALL AMOUNTS IN INCHES FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006

LST TO UTC: -09 MONTH: ALL HOURS: ALL

| YEAR                       | JAN                              | FEB                              | MAR                                     | APR                           | MAY            | JUN            | JUL         | AUG         | SEP         | OCT         | NOV                         | DEC                       | ANNUAL                               |
|----------------------------|----------------------------------|----------------------------------|---|-------------------------------|----------------|----------------|-------------|-------------|-------------|-------------|-----------------------------|---------------------------|--------------------------------------|
| 86<br>87<br>88<br>39<br>90 | 5.4<br>10.5<br>2.2<br>.8<br>15.4 | 4.4<br>2.3<br>2.5<br>TRACE<br>.9 | TRACE<br>TRACE<br>1.5<br>TRACE<br>TRACE | .0<br>.0<br>.0<br>TRACE<br>.0 | .0 .0 .0 .0 .0 | .0 .0 .0 .0 .0 | .0 .0 .0 .0 | .0 .0 .0 .0 | .0 .0 .0 .0 | .0 .0 .0 .0 | TRACE<br>.0*<br>.0<br>TRACE | 1.5<br>TRACE<br>.4<br>3.4 | 11.3<br>12.8*<br>6.6<br>4.2<br>16.3* |
|                            |                                  |                                  |   |                               | ••••           |                |             |             |             |             |                             |                           |                                      |
| LEAST                      | TRACE                            | TRACE                            | .0                                      | .0                            | .0             | .0             | .0          | .0          | .0          | .0          | .0                          | TRACE                     | .8                                   |
| GREATEST                   | 18.5                             | 11.1                             | 6.5                                     | .2                            | .0             | TRACE          | .0          | .0          | .0          | TRACE       | 3.3                         | 9.7                       | 32.0                                 |
| MEAN                       | 5.0                              | 3.4                              | 1.1                                     | .0                            | .0             | TRACE          | .0          | .0          | .0          | TRACE       | .3                          | 2.2                       | 11.5                                 |
| MEDIAN                     | 3.5                              | 2.8                              | TRACE                                   | .0                            | .0             | .0             | .0          | .0          | -0          | .0          | TRACE                       | 1.5                       | 12.3                                 |
| SD                         | 4.839                            | 3.196                            | 1.722                                   | .039                          | .000           | .000           | .000        | .000        | .000        | .000        | .612                        | 2.454                     | 6.202                                |
| TOTAL OBS                  | 1059                             | 977                              | 1093                                    | 1044                          | 1094           | 1090           | 1052        | 1063        | 1005        | 1039        | 1022                        | 1020                      | 12558                                |

THE GREATEST VALUE OF 18.5 OCCURRED ON 01/85

NOTE: \*THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

# EXTREME DAILY SNOWFALL AMOUNTS IN INCHES FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006

| YEAR  |      |                   | LS            | ST TO UTC | : -09           |        |       |        |               | MONTH | : ALL  | HOURS: A | LL     |        |
|---|------|-------------------|---------------|-----------|-----------------|--------|-------|--------|---------------|-------|--------|----------|--------|--------|
| 53  | YEAR | JAN               | FEB           | MAR       | APR             | MAY    | JUN   | JUL    | AUG           | SEP   | OCT    | NOV      | DEC    | ANNUAL |
| 54  |      | • • • • • • • • • | • • • • • • • |           | • • • • • • • • | <br>0* |       | <br>0* | • • • • • • • |       | 0*     |          | TRACE  | TRACE* |
| 55   3.1   3.1   TRACE   .0   .0   .0   .0   .0   .0   .0   TRACE   1.2   3.1   | i    | 2.3               | TRACE         | TRACE     | . 0             |        |       |        | .0            | . 0   |        |          |        |        |
| 57  | 1    |                   |               |           |                 |        |       |        |               |       |        |          | 1.2    |        |
| 57  | 56   | .9                | 8.7           | 5.0       | .0              | .0     | .0    | .0     | .0            | .0    | .0     | .9       | 3.1    | 8.7    |
| 58         4.0         5.0         1.0         .0 | 57   |                   |               |           |                 | .0     |       | .0     | .0            |       |        |          |        | 4.1    |
| 60 TRACE TRACE 0.0 0.0 0.0 0.0 0.0 0.0 TRACE 6.6 6.6 61 3.3 1.0 2.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 TRACE 3.3 62 2.3 3.1 2.0 2 0.0 TRACE 0.0 0.0 0.0 TRACE 1.0 3.1 63 1.0 3.6 TRACE TRACE 0.0 0.0 0.0 0.0 TRACE 1.0 3.6 64 1.0 5.2 1.2 0.0 0.0 0.0 0.0 0.0 TRACE TRACE 5.2 65 1.4 1.1 TRACE 0.0 0.0 0.0 0.0 0.0 TRACE TRACE 5.2 65 1.4 0.1 TRACE 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.   | 58   |                   |               |           |                 |        |       |        |               |       |        |          |        |        |
| 61  | 59   | 1.0               | .2            | TRACE     | .0              | .0     | .0    | .0     | .0            | .0    | .0     | .0       | .3     | 1.0    |
| 62  | 60   | TRACE             | TRACE         | .0        | .0              | .0     | .0    | .0     | .0            | .0    | .0     | TRACE    | .6     | .6     |
| 63  | 61   | 3.3               | 1.0           | 2.0       | .0              | .0     | .0    | .0     | .0            | .0    | .0     | .0       | TRACE  | 3.3    |
| 64  | 65   | 2.3               | 3.1           | 2.0       | .2              | .0     | TRACE | .0     | .0            | .0    | .0     | TRACE    | 1.0    | 3.1    |
| 65  | 63   | 1.0               | 3.6           | TRACE     | TRACE           | .0     | .0    | .0     | .0            | .0    | .0     | . 4      | 1.0    | 3.6    |
| 66  | 64   | 1.0               | 5.2           | 1.2       | .0              | .0     | .0    | .0     | .0            | .0    | .0     | TRACE    | TRACE  | 5.2    |
| 1.0   2.0   TRACE   TRACE   .0   .0   .0   .0   .0   .0   TRACE   2.9   2.9   | 65   | 1.4               | .1            | TRACE     | .0              | .0     | .0    | .0     | .0            | .0    | .0     | .4       | .1     | 1.4    |
| 68         3.0* TRACE*         1.0* .0* .0* .0* .0* .0* .0* .0* .0* .0*   | 66   | .2                | 2.9           | 3.0       | .0              | .0     | .0    | .0     | .0            | .0    | TRACE  | 1.6      | 2.0    | 3.0    |
| 69       3.5*       1.8*       .6*       TRACE*       .0*       .0*       .0*       .0*       .0*       TRACE*       2.3*       3.5*         70       2.4*       .9*       4.6*       .0*   | 67   | 1.0               | 2.0           | TRACE     | TRACE           | .0     | .0    | .0     | .0            | .0*   | .0*    | TRACE*   | 2.9*   | 2.9*   |
| 70  | 68   | 3.0*              | TRACE*        | 1.0*      | .0*             | .0*    | .0*   | .0*    | .0*           | .0*   | .0*    | TRACE*   | .4*    | 3.0*   |
| 71  | 69   | 3.5*              | 1.8*          | .6*       | TRACE*          | .0*    | .0*   | .0*    | .0*           | .0*   | TRACE* | TRACE*   | 2.3*   | 3.5*   |
| 72       1.3*       3.2*       TRACE*       .0*       .0*       .0*       .0*       .0*       .0*       .0*       .3*       TRACE*       3.3*         73       .8*       .0*       .2*       .0*  | 70   | 2.4*              | .9*           | 4.6*      | .0*             | .0*    | .0*   | .0*    | .0*           | .0*   | .0*    | TRACE*   | 2.8*   | 4.6*   |
| 73       .8*       .0*       .2*       .0   | 71   | 4.3*              | 3.0*          | 2.1*      | .0*             | .0*    | .0*   | .0*    | .0*           |       | .0*    | .0*      | 3.5*   | 4.3*   |
| 74       2.4*       1.3*       .8*       .0*  | 72   |                   | 3.2*          | TRACE*    | .0*             | .0*    | .0*   | .0*    | .0*           | .0*   | .0*    | 3.3*     | TRACE* | 3.3*   |
| 75  | 73   | .8*               | .0*           | .2*       | .0*             | .0*    | .0*   | .0*    | .0*           | .0*   | .0*    | 1.6*     | •9*    | 1.6*   |
| TRACE* 1.0* TRACE* .0* .0* .0 .0* .0 .0* TRACE* .7* 1.5* 1.5*  77   | 74   | 2.4*              | 1.3*          | .8*       |                 | .0*    | .0*   | .0*    | .0*           | .0*   | .0*    | .4*      | -3*    | 2.4*   |
| 77  | 75   | .5*               | 1.3*          | 1.0*      | .0*             | .0*    | .0*   | .0*    | .0*           | .0*   | .0*    | .0*      | -1*    | 1.3*   |
| 78  | 76   | TRACE*            | 1.0*          | TRACE*    | .0*             | .0*    | .0    | .0*    | .0            | .0*   | TRACE* | .7*      | 1.5*   | 1.5*   |
| 79  | 77   | .2*               | TRACE*        | .3*       | TRACE           | .0*    | .0*   | .0*    | .0*           | .0*   | -0*    | 2.8*     | 3.5*   | 3.5*   |
| 80  | 78   | 4.5*              | 4.3*          | 1.1       | .0*             | .0*    | .0*   | .0*    | .0            | .0*   | .0*    | .0*      | TRACE* | 4.5*   |
| 81  | 79   | 4.3*              | 1.5*          | TRACE     | .0*             | .0*    | .0    | .0*    | .0*           | .0*   | .0*    | TRACE*   | 7.0*   | 7.0*   |
| 82       .4       .3       TRACE       .0       .0       .0       .0       .0       .0       .0       .3       3.3         83       .5       3.2       .5       TRACE       .0       .0       .0       .0       .0       .0       1.5       2.0       3.2         84       1.0       1.3       1.9       .0       .0       .0       .0       .0       TRACE       .6       1.9  | 80   | .7*               | TRACE         | TRACE     | .0              | .0     | .0    | .0     | .0            | .0    | TRACE  | TRACE    | 3.0    | 3.0*   |
| 83 .5 3.2 .5 TRACE .0 .0 .0 .0 .0 .0 1.5 2.0 3.2 84 1.0 1.3 1.9 .0 .0 .0 .0 .0 .0 .0 TRACE .6 1.9   | 81   | 2.0               | 1.0           | 1.0       | .0              | -0     | .0    | .0     | .0            | .0    | TRACE  | 2.0      | 2.0    | 2.0    |
| 84 1.0 1.3 1.9 .0 .0 .0 .0 .0 .0 TRACE .6 1.9   | 82   | . 4               | . 3           | TRACE     | .0              | .0     | -0    | .0     | .0            | .0    | .0     | .0       | 3.3    | 3.3    |
|   | 83   | .5                | 3.2           | •5        | TRACE           | .0     | .0    | .0     | .0            | .0    | .0     | 1.5      | 2.0    | 3.2    |
| 85 7.0 4.1 TRACE .0 .0 .0 .0 .0 .0 .4* 2.1 7.0*   | 84   | 1.0               | 1.3           | 1.9       | .0              | .0     | .0    | .0     | .0            | .0    | .0     | TRACE    | .6     | 1.9    |
|   | 85   | 7.0               | 4.1           | TRACE     | .0              | .0     | .0    | .0     | .0            | .0    | .0     | .4*      | 2.1    | 7.0*   |

STATION NUMBER: 471066

### EXTREME DAILY SNOWFALL AMOUNTS IN INCHES FROM SUMMARY OF DAY DATA

PERIOD OF RECORD: 5305-9006

Their bold and but

STATION NAME: CAMP CASEY/TONGDUCHON KO

|      |     |       | OTU OT T |       |     |     |     |     | MONTH: |     | HOURS: A |       |        |
|------|-----|-------|----------|-------|-----|-----|-----|-----|--------|-----|----------|-------|--------|
| YEAR | JAN | FEB   | MAR      | APR   | MAY | JUN | JUL | AUG | SEP    | OCT | NOV      | DEC   | ANNUAL |
| 86   | 3.5 | 1.7   | TRACE    | .0    | .0  | .0  | .0  | .0  | .0     | .0  | TRACE    | 1.5   | 3.5    |
| 87   | 6.2 | 2.0   | TRACE    | .0    | .0  | .0  | .0  | .0  | .0     | .0  | .0*      | TRACE | 6.2*   |
| 88   | 1.0 | 2.5   | 1.5      | TRACE | .0  | .0  | .0  | .0  | .0     | .0  | .0       | .4    | 2.5    |
| 89   | .6  | TRACE | TRACE    | .0    | .0  | .0  | .0  | .0  | .0     | .0  | TRACE    | 2.2   | 2.2    |
| 90   | 6.2 | .5    | TRACE    | .0    | .0  | .0  |     |     |        |     |          |       | 6.2*   |

GREATEST 7.0 8.7 5.0 .2 .0 TRACE .0 .0 TRACE 3.3 7.0 8.7

TOTAL OBS 1059 977 1093 1044 1094 1090 1052 1063 1005 1039 1022 1020 12558

THE GREATEST VALUE OF 8.7 OCCURRED ON 02/28/56

NOTE: \*THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

B - 3 - 3B

### PERCENTAGE FREQUENCY OF OCCURRENCE OF SNOW DEPTH IN INCHES FROM SUMMARY OF DAY DATA

PERIOD OF RECORD: 5305-9006 STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO MONTH: ALL HOURS: ALL LST TO UTC: -09 JAN FEB APR MAY JUN JUL AUG SEP OCT NOV DEC AMOUNTS MAR ANN (INCHES) NONE 58.5 68.0 92.9 99.9 100.0 100.0 100.0 100.0 100.0 97.3 83.7 91.8 .1 10.1 3.9 15.3 16.4 4.3 1.6 TRACE 9.1 7.6 .2 3.1 1.7 1 1.4 7.3 4.1 .6 . 4 1.9 1.2 3 5.3 2.0 . 4 .7 .7 .5 4.2 1.5 .2 4-6 . 4 . 4 7-12 . 5 . 4 . 1 .1 13-24 25-36 37-48 49-60 61-120 **OVER 120** DAYS WITH 26.2 15.6 1.2 6.2 4.3 MEAS AMTS 2.8 TOTAL NO. OF OBSERVATIONS 1060 978 1092 1044 1104 1090 1052 1063 1006 1045 1022 1052 12608

# EXTREME DAILY SNOW DEPTH AMOUNTS IN INCHES FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: -09

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: 5305-9006

MONTH: ALL HOURS: ALL

|      |        | -               | ST TO UTC | 03    |     |     |     |     | MONTH: | LIDD . | HOURS: A |        |        |
|------|--------|-----------------|-----------|-------|-----|-----|-----|-----|--------|--------|----------|--------|--------|
| YEAR | JAN    | FEB             | MAR       | APR   | MAY | JUN | JUL | AUG | SEP    | ост    | NOV      | DEC    | ANNUAL |
| 53   |        | • • • • • • • • |           | ••••• | 0   | 0   | 0*  |     |        | 0*     | 0        | 0      | 0*     |
| 54   | 2      | 5               | 0         | 0     | ō   | ō   | 0   | 0   | 0      | ō      | ō        | ō      | 5      |
| 55   | 3      | 2               | 0         | Ō     | ō   | ō   | 0   | 0   | 0      | ō      | ō        | 1      | 3      |
|      | ł      |                 |           |       |     |     |     |     |        |        |          |        |        |
| 56   | 1      | 8               | 5         | 0     | 0   | 0   | 0   | 0   | 0      | 0      | 1        | 3      | 8      |
| 57   | 5      | 4               | 2         | 0     | 0   | 0   | 0   | 0   | 0      | 0      | 0        | TRACE  | 5      |
| 58   | 4      | 5               | 1         | 0     | 0   | 0   | 0   | 0   | 0      | 0      | 0        | 2      | 5      |
| 59   | 1      | TRACE           | TRACE     | 0     | 0   | 0   | 0   | 0   | 0      | 0      | 0        | TRACE  | 1      |
| 60   | TRACE  | TRACE           | 0         | 0     | 0   | 0   | 0   | 0   | 0      | 0      | 0        | 0      | TRACE  |
| 61   | 4      | 1               | 2         | 0     | 0   | 0   | 0   | 0   | 0      | 0      | 0        | TRACE  | 4      |
| 62   | 2      | 3               | 2         | 0     | 0   | 0   | 0   | 0   | 0      | 0      | TRACE    | 1      | 3      |
| 63   | 3      | 4               | TRACE     | TRACE | 0   | 0   | 0   | 0   | 0      | 0      | TRACE    | 1      | 4      |
| ь4   | TRACE  | 4               | 1         | 0     | 0   | 0   | 0   | 0   | 0      | 0      | 0        | TRACE  | 4      |
| 65   | 1      | 0               | TRACE     | 0     | 0   | 0   | 0   | 0   | 0      | 0      | 0        | TRACE  | 1      |
| 66   | TRACE  | 3               | 4         | 0     | 0   | 0   | 0   | 0   | 0      | 0      | TRACE    | 2      | 4      |
| 67   | 1      | 2               | 0         | 0     | 0   | 0   | 0   | 0   | 0*     | 0*     | 0*       | 2*     | 2*     |
| 68   | 3*     | 2*              | TRACE*    | 0*    | 0*  | 0*  | 0*  | 0*  | 0*     | 0*     | 0*       | TRACE* | 3*     |
| 69   | 7*     | 9*              | 1*        | 0*    | 0*  | 0*  | 0*  | 0*  | 0*     | 0*     | TRACE*   | 2*     | 9*     |
| 70   | 2*     | TRACE*          | 3*        | 0*    | 0*  | 0*  | 0*  | 0*  | 0*     | 0*     | 0*       | 2*     | 3*     |
| 71   | 4*     | 2*              | 1*        | 0*    | 0*  | 0*  | 0*  | 0*  | 0*     | 0*     | 0*       | 1*     | 4*     |
| 72   | 1*     | 2*              | 0*        | 0*    | 0*  | 0*  | 0*  | 0*  | 0*     | C*     | 4*       | 1*     | 4*     |
| 73   | 2*     | 0*              | TRACE*    | 0*    | 0*  | 0*  | 0*  | 0*  | 0*     | 0*     | 2*       | 1*     | 2*     |
| 74   | 3*     | 2*              | 1*        | 0*    | 0*  | 0*  | 0*  | 0*  | 0*     | 0*     | 0*       | TRACE* | 3*     |
| 75   | TRACE* | TRACE*          | 1*        | 0*    | 0*  | 0*  | 0*  | 0*  | 0*     | 0*     | 0*       | 0*     | 1*     |
| 76   | TRACE* | 0*              | TRACE*    | 0*    | 0*  | 0   | 0*  | 0   | 0*     | 0*     | 1*       | TRACE* | 1*     |
| 77   | TRACE* | 0*              | TRACE*    | 0     | 0*  | 0*  | 0*  | 0*  | 0*     | 0*     | 3*       | 4*     | 4*     |
| 78   | 5*     | 2*              | 2         | 0*    | 0*  | 0*  | 0*  | 0   | 0*     | 0*     | 0*       | TRACE* | 5*     |
| 79   | 4*     | 4*              | TRACE     | 0*    | 0*  | 0   | 0*  | 0*  | 0*     | 0*     | 0*       | 7*     | 7*     |
| 80   | 1*     | 1               | 0         | o     | o   | o   | ō   | Ō   | o      | 0      | n        | 3      | 3*     |
| 81   | 6      | 1               | 1         | 0     | 0   | 0   | 0   | 0   | 0      | 0      | 2        | 3      | 6      |
| 82   | TRACE  | 0               | 0         | Ō     | ō   | ō   | ō   | ō   | 0      | ō      | 0        | 1      | 1      |
| 83   | TRACE  | 3               | TRACE     | 0     | Ö   | 0   | 0   | 0   | 0      | 0      | TRACE    | 3      | 3      |
| 84   | 5      | 2               | TRACE     | o     | 0   | ō   | ō   | ō   | 0      | ō      | 0        | TRACE  | 5      |
| 85   | 7      | 4               | TRACE     | ō     | Ö   | ō   | 0   | Ö   | ō      | ō      | TRACE*   | 2      | 7*     |

#### EXTREME DAILY SNOW DEPTH AMOUNTS IN INCHES FROM SUMMARY OF DAY DATA

| STATION NUM | MBER: 471066          | STATION NA |     | CASEY/TO | NGDUCHON | KO  |     |        |     | RD: 5305- |     |        |
|-------------|-----------------------|------------|-----|----------|----------|-----|-----|--------|-----|-----------|-----|--------|
|             |                       | LST TO UTC |     |          |          |     |     | MONTH: |     | OURS: ALL |     |        |
| YEAR        | JAN                   | FEB MAR    | APR | MAY      | JUN      | JUL | AUG | SEP    | OCT | NOV       | DEC | ANNUAL |
|             | • • • • • • • • • • • | . <b></b>  |     |          |          |     |     |        |     |           |     |        |

|          | • • • • • • • • |       |       |        |    |    |    |    |    | . <b></b> . |    | · · · · · · · · · · · |              |
|----------|-----------------|-------|-------|--------|----|----|----|----|----|-------------|----|-----------------------|--------------|
| 86       | 4               | 3     | 0     | 0      | 0  | 0  | 0  | 0  | 0  | 0           |    | TRACE                 | 4            |
| 87       | 5               | 2     | TRACE | 0      | 0  | 0  | 0  | 0  | 0  | 0           | 0* | 0                     | 5*           |
| 88       | TRACE           | 2     | 2     | 0      | 0  | 0  | 0  | 0  | 0  | 0           | 0  | TRACE                 | 2<br>2<br>8* |
| 89       | 2               | TRACE | 0     | 0      | 0  | 0  | 0  | 0  | 0  | 0           | 0  | 2                     | 2            |
| 90       | 4               | 8     | 0     | 0      | 0  | 0  |    |    |    |             |    |                       | 8*           |
|          |                 |       |       |        |    |    |    |    |    |             |    |                       |              |
|          |                 |       |       |        |    |    |    |    |    | <b></b> -   |    |                       |              |
| GREATEST | 7*              | 9*    | 5*    | TRACE* | 0* | 0* | 0* | 0* | 0* | 0*          | 4* | 7*                    | 9*           |

THE GREATEST VALUE OF

9 OCCURRED ON 02/01/69

NOTE: \*THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

B - 4 - 2B

1060 978 1092 1044 1104 1090 1052 1063 1006 1045 1022 1052 12608

# FIRST AND LAST DAYS OF OCCURRENCE BY SNOW-YEAR FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: 5305-9006 SNOW-YEAR: 1 AUG - 31 JUL

|               |      | FIRST    | FIRST                                   | FIRST                                   | LAST                                    | LAST       | LAST                                    |
|---------------|------|----------|---|---|---|------------|---|
|               |      | SNOWFALL | MEASURABLE                              | MEASURABLE                              | SNOWFALL                                | MEASURABLE | MEASURABLE                              |
| SNOW-Y        | /EAR |          | SNOWFALL                                | SNOW DEPTH                              |   | SNOWFALL   | SNOW DEPTH                              |
| • • • • • • • |      |          | • | • | • | •••••      | • |
| 53 -          |      | DEC 07   | JAN 14                                  | JAN 14                                  | MAR 15                                  | JAN 28     | FEB 01                                  |
| 54 -          | 55   | JAN 04   | JAN 05                                  | JAN 05                                  | MAR 02                                  | FEB 21     | FEB 21                                  |
| 55 -          | 56   | NOV 05   | DEC 20                                  | DEC 29                                  | MAR 26                                  | MAR 12     | MAR 13                                  |
| 56 -          | 57   | NOV 29   | NOV 29                                  | NOV 29                                  | MAR 31                                  | MAR 24     | MAR 08                                  |
| 57 -          | 58   | DEC 05   | DEC 05                                  | JAN 02                                  | MAR 30                                  | MAR 02     | MAR 02                                  |
| 58 -          | 59   | DEC 20   | DEC 27                                  | DEC 27                                  | MAR 10                                  | FEB 15     | JAN 12                                  |
| 59 -          | 60   | DEC 23   | DEC 23                                  |   | FEB 21                                  | DEC 23     |   |
| 60 -          | 61   | NOV 26   | DEC 12                                  | JAN 03                                  | MAR 27                                  | MAR 27     | MAR 27                                  |
| 61 -          | 62   | DEC 08   | JAN 01                                  | JAN 01                                  | JUN 20                                  | APR 03     | MAR 27                                  |
| 62 -          | 63   | NOV 04   | DEC 02                                  | DEC 05                                  | APR 09                                  | FEB 26     | FEB 28                                  |
| 63 -          | 64   | NOV 27   | NOV 27                                  | DEC 10                                  | MAR 26                                  | MAR 26     | MAR 20                                  |
| 64 -          | 65   | NOV 13   | JAN 11                                  | JAN 11                                  | MAR 28                                  | FEB 05     | JAN 15                                  |
| 65 -          | 66   | NOV 27   | NOV 27                                  | FEB 22                                  | MAR 29                                  | MAR 24     | MAR 07                                  |
| 66 -          | 67   | OCT 28   | NOV 20                                  | DEC 08                                  | APR 04                                  | FEB 16     | FEB 05                                  |
| 67 –          | 68   | NOV 23   | DEC 13                                  | DEC 14                                  | MAR 12                                  | MAR 12     | FEB 23                                  |
| 68 -          | 69   | NOV 09   | DEC 23                                  | JAN 28                                  | APR 07                                  | MAR 12     | MAR 04                                  |
| 69 -          | 70   | OCT 09   | DEC 10                                  | DEC 10                                  | MAR 24                                  | MAR 18     | MAR 18                                  |
| 70 -          | 71   | NOV 25   | DEC 01                                  | DEC 01                                  | MAR 24                                  | MAR 24     | MAR 24                                  |
| 71 -          | 72   | DEC 03   | DEC 11                                  | DEC 14                                  | MAR 31                                  | FEB 26     | FEB 15                                  |
| 72 -          | 73   | NOV 24   | NOV 24                                  | NOV 24                                  | MAR 16                                  | MAR 16     | JAN 11                                  |
| 73 -          | 74   | NOV 08   | NOV 17                                  | NOV 20                                  | MAR 21                                  | MAR 21     | MAR 11                                  |
| 74 -          | 75   | NOV 11   | NOV 25                                  | MAR 06                                  | MAR 06                                  | MAR 06     | MAR 06                                  |
| 75 –          | 76   | DEC 22   | DEC 22                                  |   | MAR 23                                  | FEB 17     |   |
| 76 -          | 77   | OCT 30   | NOV 23                                  | NOV 24                                  | APR 18                                  | MAR 25     | NOV 24                                  |
| 77 -          | 78   | NOV 29   | NOV 29                                  | NOV 29                                  | MAR 22                                  | MAR 22     | MAR 01                                  |
| 78 -          | 79   | DEC 02   | JAN 17                                  | JAN 31                                  | MAR 26                                  | FEB 27     | FEB 07                                  |
| 79 -          | 80   | NOV 28   | DEC 26                                  | DEC 26                                  | MAR 23                                  | JAN 30     | FEB 01                                  |
| 80 -          | 81   | OCT 26   | DEC 03                                  | DEC 03                                  | MAR 26                                  | MAR 09     | MAR 09                                  |
| 81 -          | 82   | OCT 23   | NOV 10                                  | NOV 10                                  | MAR 17                                  | FEB 09     | DEC 21                                  |
| 82 -          | 83   | DEC 02   | DEC 11                                  | DEC 11                                  | APR 03                                  | MAR 13     | FEB 20                                  |
| 83 -          | 84   | NOV 12   | NOV 16                                  | DEC 24                                  | MAR 27                                  | MAR 27     | FEB 13                                  |
| 84 -          | 85   | NOV 19   | DEC 16                                  | JAN 10                                  | MAR 08                                  | FEB 20     | FEB 28                                  |
| 85 -          | 86   | NOV 10   | NOV 25                                  | DEC 01                                  | MAR 19                                  | FEB 18     | FEB 18                                  |

### FIRST AND LAST DAYS OF OCCURRENCE BY SNOW-YEAR FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERJOR OF RECORD: 5305-9006 SNOW-YEAR: 1 AUG - 31 JUL

| SNOW-YEAR                                | FIRST<br>SNOWFALL                    | FIRST<br>MEASURABLE<br>SNOWFALL      | FIRST<br>MEASURABLE<br>SNOW DEPTH    | LAST<br>SNOWFALL                     | LAST<br>MEASURABLE<br>SNOWFALL       | LAST<br>MEASURABLE<br>SNOW DEPTH     | •••• |
|--|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|------|
| 86 - 87<br>87 - 88<br>88 - 89<br>89 - 90 | NOV 30<br>DEC 03<br>DEC 10<br>NOV 18 | DEC 19<br>JAN 07<br>DEC 19<br>DEC 14 | JAN 03<br>FEB 05<br>JAN 13<br>DEC 24 | MAR 25<br>APR 19<br>MAR 16<br>MAR 17 | FEB 28<br>MAR 08<br>JAN 26<br>FEB 10 | FEB 05<br>MAR 08<br>JAN 26<br>FEB 06 |      |
| MEDIAN-DATE                              | NOV 26                               | DEC 11                               | DEC 24                               | MAR 25                               | MAR 06                               | FEB 23                               |      |

| PPPPP | PPP  | AAA   | AAA   | RRRR | RRRR  | TTTTTTTT  | ccc  | CCC  |
|-------|------|-------|-------|------|-------|-----------|------|------|
| PPPPP | PPPP | AAAA  | AAAA  | RRRR | RRRRR | TTTTTTTTT | cccc | CCCC |
| PP    | PP   | AA    | AA    | RR   | RR    | TT        | CC   | CC   |
| PP    | PP   | AA    | AA    | RR   | RR    | TT        | ÇC   |      |
| PPPPP | PPPP | AA    | AA    | RRRR | RRRRR | TŤ        | CC   |      |
| PPPPP | PPP  | AAAAA | AAAAA | RRRR | RRRR  | TT        | CC   |      |
| PP    |      | AAAAA | AAAAA | RR   | RR    | TT        | CC   |      |
| PP    |      | AA    | AA    | RR   | RR    | TT        | CC   | CC   |
| PP    |      | AA    | AA    | RR   | RR    | TT        | cccc | CCCC |
| PP    |      | AA    | AA    | RR   | RR    | TT        | ccc  | CCC  |

#### PART C

#### SURFACE WIND SUMMARIES

#### PEAK WINDS.

THESE TABLES ARE CREATED FROM SUMMARY OF DAY DATA. SPEEDS ARE IN KNOTS. DIRECTIONS ARE TO 16 COMPASS POINTS FROM THE BEGINNING OF PERIOD OF RECORD THROUGH JUNE 1968, BUT IN JULY 1968, ALL STATIONS EXCEPT THOSE OF THE NATIONAL WEATHER SERVICE STARTED RECORDING DIRECTIONS IN TENS OF DEGREES. DATA IS SUMMARIZED BY MONTH FOR EACH YEAR FOR THE ENTIRE PERIOD OF RECORD AVAILABLE. GIVEN: THE GREATEST MONTHLY VALUE FOR ALL YEARS COMBINED, THE GREATEST YEARLY VALUE FOR ALL YEARS COMBINED, AND THE DATE OF THE ABSOLUTE PEAK WIND RECORDED FOR THE ENTIRE PERIOD OF RECORD. AN ASTERISK (\*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS THAN 90% OF THE DATA ARE AVAILABLE. AN ASTERISK ALSO DENOTES A YEAR(S) WITH ONE OR MORE MISSING AND/OR INCOMPLETE MONTHS.

#### PEAK WINDS -- PERCENT OCCURRENCE FREQUENCY.

ALSO FROM SUMMARY OF DAY DATA. DATA IS SUMMARIZED BY MONTH, FOR ALL YEARS COMBINED, FOR ELEVEN WIND SPEED GROUPS. THE 1-4 KNOT SPEED GROUP INCLUDES CALM WINDS. IF THE PEAK WIND IS REPORTED FOR A PARTICULAR DAY AS "CALM," THAT COUNT GOES INTO THE "1-4 KNOT" CATEGORY. TABLES INCLUDE MEANS, MEDIANS, AND TOTAL OBSERVATION COUNTS. THE VALUES IN THIS SUMMARY ACCOUNT FOR A PEAK WIND BEING RECORDED FOR EACH DAY OF EACH MONTH.

WIND DIRECTION VS WIND SPEED--PERCENT OCCURRENCE FREQUENCY.
THESE TABLES ARE CREATED FROM HOURLY OBSERVATIONS. THEY SUMMARIZE
THE DATA AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).
- THESE TABLES GIVE A BIVARIATE DISTRIBUTION OF THE PERCENT OCCURRENCE FREQUENCY (POF) FOR ELEVEN WIND SPEED GROUPS VERSUS TWELVE WIND DIRECTION SECTORS GIVEN IN 30 DEGREE INCREMENTS. "CALM" AND "VARIABLE" WINDS ARE GIVEN SEPARATELY. CARDINAL WIND DIRECTIONS (N,E,S,W) APPEAR FOR REFERENCE. TOTAL PERCENTAGES, MEANS, AND MEDIANS FOR EACH SECTOR, ALONG WITH TOTAL OBSERVATION COUNTS, ARE PRINTED BELOW EACH SUMMARY.
- ALSO PROVIDED: A BIVARIATE DISTRIBUTION OF WIND DIRECTION VERSUS WIND SPEED FOR SPECIFIED CEILING/VISIBILITY CONDITIONS. THESE CONDITIONS ARE:

WHEN THE VISIBILITY IS GREATER THAN OR EQUAL TO 1/2 MILES (0800 METERS)
THE CEILING MUST BE GREATER THAN OR EQUAL TO 200 FEET BUT LESS THAN 1500 FEET.
IF THIS CONDITION IS NOT MET, THEN THE FOLLOWING CONDITION IS TESTED:
WHEN THE CEILING IS GREATER THAN OR EQUAL TO 200 FEET, THE VISIBILITY MUST
BE GREATER THAN OR EQUAL TO 1/2 (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS).

CONVERSION: 1 KNOT = .514791 METERS PER SECOND

### PEAK SURFACE WINDS IN KNOTS FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006 LST TO UTC: -09 MONTH: ALL HOURS: ALL

|      |        | 1      | 331 10 01 | 03     |        |        |        |        | PION            | iii. Aug | noons. | KILL   |        |
|------|--------|--------|-----------|--------|--------|--------|--------|--------|-----------------|----------|--------|--------|--------|
| YEAR | JAN    | FEB    | MAR       | APR    | MAY    | JUN    | JUL    | AUG    | SEP             | OCT      | NOV    | DEC    | ANN    |
| 53   |        | •••••  |           |        | *      | *      | *      |        | • • • • • • • • | *        | *      | *      | *      |
| 54   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 55   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 56   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 57   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 58   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 59   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 60   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 61   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 62   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 63   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 64   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 65   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 66   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 67   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 68   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 69   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 70   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 71   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 72   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 73   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 74   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 75   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 76   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 77   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 78   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 79   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 80   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | *      | *      |
| 81   | *      | *      | *         | *      | *      | *      | *      | *      | *               | *        | *      | 30/*17 | 30/*17 |
| 82   | 36/ 20 | 28/ 20 | 24/ 20    | 36/*22 | *      | *      | 14/*21 | 22/ 26 | 27/*24          | 01/*20   | *      | *      | 22/*26 |
| 83   | 01/*10 | 29/*21 | 36/ 19    | 22/ 40 | 32/ 25 | 14/ 31 | 12/ 28 | 11/ 38 | 06/*27          | 24/ 22   | 20/*21 | *      | 22/*40 |
| 84   | 33/*20 | 30/*27 | 23/ 29    | 30/*23 | *      | *      | 07/*24 | 23/ 25 | 35/*26          | *        | 05/*22 | 27/*25 | 23/*29 |
| 85   | 29/*22 | 10/*18 | 31/ 26    | 27/ 39 | 03/*22 | 24/*13 | 23/*18 | *      | *               | *        | *      | *      | 27/*39 |
|      | 1      |        |           |        |        |        |        |        |                 |          |        |        |        |

#### PEAK SURFACE WINDS IN KNOTS FROM SUMMARY OF DAY DATA

STATION NUMBER: 47106 STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: -09

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: 5305-9006

MONTH: ALL HOURS: ALL

THE PEAK WIND OF 45 FROM 01/ OCCURRED ON 07/16/87

NOTE: \*THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF DATA AVAILABLE FOR THE MONTH
STHE VALUE IS 100 OR GREATER WITH LESS THAN 90% OF DATA AVAILABLE FOR THE MONTH

C - 2 - 1B

### PERCENTAGE FREQUENCY OF OCCURRENCE OF DAILY PEAK WINDS

FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006

LST TO UTC: -09 MONTH: ALL HOURS: ALL

|        |        |      | 51 10 01 | C03   |       |           |        |       |       |            |       |      |        |       |
|--------|--------|------|----------|-------|-------|-----------|--------|-------|-------|------------|-------|------|--------|-------|
|        |        |      |          |       | WI    | ND SPEEDS | IN KNO | ots   |       |            |       | MEAN | MEDIAN | TOTAL |
| MONTH  | CALM-4 | 5-9  | 10-14    | 15-19 | 20-24 | 25-29     | 30-34  | 35-39 | 40-49 | 50-64      | GE 65 | WIND | WIND   | OBS   |
| JAN    | 3.2    | 34.0 | 40.4     | 16.7  | 5.1   | 6         | .0     | .0    | .0    | .0         |       | 11.3 | 11.0   | 156   |
| 0741   | 3.2    | 34.0 | 40.4     | 2017  | J.1   | ,,        |        |       |       |            | •     |      |        |       |
| FEB    | .0     | 28.5 | 44.9     | 17.1  | 8.9   | .6        | .0     | .0    | .0    | .0         | .0    | 12.4 | 11.0   | 158   |
| MAR    | .5     | 10.4 | 41.5     | 33.0  | 11.8  | 2.8       | .0     | .0    | .0    | .0         | .0    | 14.6 | 14.0   | 212   |
| APR    | .7     | 1.5  | 34.3     | 29.1  | 24.6  | 6.7       | .7     | 1.5   | .7    | .0         | .0    | 17.3 | 16.0   | 134   |
| MAY    | .0     | 6.4  | 48.9     | 31.9  | 7.8   | 2.8       | 1.4    | .0    | .7    | .0         | .0    | 15.0 | 14.0   | 141   |
| JUN    | .0     | 9.1  | 56.4     | 27.3  | 5.5   | .0        | 1.8    | .0    | .0    | .0         | .0    | 13.8 | 13.0   | 110   |
| JUL    | .6     | 18.5 | 49.7     | 22.3  | 6.4   | 1.3       | .6     | .0    | .6    | .0         | .0    | 13.4 | 12.0   | 157   |
| AUG    | 1.7    | 23.9 | 46.7     | 18.3  | 5.6   | 3.3       | .0     | .6    | .0    | .0         | .0    | 12.8 | 12.0   | 180   |
| SEP    | .7     | 36.4 | 40.0     | 11.4  | 7.1   | 1.4       | 2.1    | .0    | .7    | .0         | .0    | 12.3 | 10.0   | 140   |
| OCT    | 1.5    | 38.0 | 35.0     | 19.7  | 4.4   | .7        | .7     | .0    | .0    | .0         | .0    | 11.6 | 11.0   | 137   |
| NOV    | 3.9    | 37.3 | 33.3     | 13.7  | 7.8   | 2.9       | 1.0    | .0    | .0    | . <b>o</b> | .0    | 11.8 | 10.0   | 102   |
| DEC    | 2.8    | 33.3 | 38.9     | 18.5  | 4.6   | 1.9       | .0     | .:    | .0    | .0         | .0    | 11.5 | 10.5   | 108   |
|        |        |      |          |       |       |           |        |       |       |            |       |      |        |       |
| ANNUAL | 1.2    | 22.5 | 42.7     | 22.0  | 8.4   | 2.1       | .6     | .2    | .2    | .0         | .0    | 13.2 | 12.0   | 1735  |

## PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN HOURS: 00-02

| • |          | •••••  | • • • • • • • |             | WIND S      | SPEED IN      | KNOTS  | • • • • • • •   | • • • • • • |         |        | • • • • • • •                           | • • • • • •  | • • • • • • •  |
|---|----------|--------|---------------|-------------|-------------|---------------|--------|-----------------|-------------|---------|--------|---|--------------|----------------|
| DIRECTION (DEGREES)                     | 1-4      | 5-9    | 10-14         | 15-19       | 20-24       | 25-29         | 30-34  | 35-39           | 40-49       | 50-64   | GE 65  | TOTAL<br>%                              | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 18.4     | 7.3    |               | • • • • • • |             | • • • • • • • | •••••  | •••••           | •••••       |         | ••••   | 25.7                                    | 3.6          | 3.5            |
| 020-040                                 | 6.1      | 1.1    |               |             |             |               |        |                 |             |         |        | 7.3                                     | 3.3          | 3.0            |
| 050-070                                 | .6       |        |               |             |             |               |        |                 |             |         |        | .6                                      | 4.0          | 4.0            |
| (E) 080-100                             | .6       |        |               |             |             |               |        |                 |             |         |        | .6                                      | 4.0          | 4.0            |
| 110-130                                 |          |        |               |             |             |               |        |                 |             |         |        |   |              |                |
| 140-160                                 |          |        |               |             |             |               |        |                 |             |         |        |   |              |                |
| (S) 170-190                             | 1.1      |        |               |             |             |               |        |                 |             |         |        | 1.1                                     | 2.0          | 2.0            |
| 200-220                                 | 2.8      | .6     |               |             |             |               |        |                 |             |         |        | 3.4                                     | 3.0          | 2.5            |
| 230-250                                 | 1.1      |        |               |             |             |               |        |                 |             |         |        | 1.1                                     | 2.5          | 2.5            |
| (W) 260-280                             |          | .6     |               |             |             |               |        |                 |             |         |        | .6                                      | 5.0          | 5.0            |
| 290-310                                 | 2.2      | .6     |               |             |             |               |        |                 |             |         |        | 2.8                                     | 2.4          | 2.0            |
| 320-340                                 | 7.3      | 2.8    |               |             |             |               |        |                 |             |         |        | 10.1                                    | 3.5          | 3.0            |
| VARIABLE                                |          | •••••  |               |             | • • • • • • |               | •••••  | • • • • • • • • |             |         |        | • | • • • • • •  |                |
| CALM                                    | 11111111 | ////// | 111111        | 1111111     | //////      | ////////      | ////// | ///////         | ///////     | (////// | ////// | / 46.9                                  | /////        | 111111         |
| TOTALS                                  | 40.2     | 13.0   |               |             |             |               |        |                 |             |         |        | 100.0                                   | 1.8          | 3.0            |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: JAN HOURS: 03-05

| • | • • • • • • • • | • • • • • • |        |         |        |                   |        | •••••   |             |        |               |            |              | • |
|---|-----------------|-------------|--------|---------|--------|-------------------|--------|---------|-------------|--------|---------------|------------|--------------|---|
| DIRECTION (DEGREES)                     | 1-4             | 5-9         | 10-14  | 15-19   |        | SPEED IN<br>25-29 |        | 35-39   | 40-49       | 50-64  | GE 65         | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND                          |
| (N) 350-010                             | 18.3            | 6.1         | 1.7    |         | ••••   |                   |        | •••••   | • • • • • • | ••••   |               | 26.1       | 3.7          | 3.0                                     |
| 020-040                                 | 5.0             | 4.4         |        |         |        |                   |        |         |             |        |               | 9.4        | 3.9          | 4.0                                     |
| 050-070                                 |                 | 1.1         |        |         |        |                   |        |         |             |        |               | 1.1        | 5.0          | 5.0                                     |
| (E) 090-100                             | .6              |             |        |         |        |                   |        |         |             |        |               | .6         | 2.0          | 2.0                                     |
| 110-130                                 |                 |             |        |         |        |                   |        |         |             |        |               |            |              |   |
| 140-160                                 |                 |             |        |         |        |                   |        |         |             |        |               |            |              |   |
| (S) 170-190                             | 2.2             | .6          |        |         |        |                   |        |         |             |        |               | 2.8        | 2.6          | 2.0                                     |
| 200-220                                 | 3.9             |             |        |         |        |                   |        |         |             |        |               | 3.9        | 1.4          | 1.0                                     |
| 230-250                                 | .6              |             |        |         |        |                   |        |         |             |        |               | .6         | 1.0          | 1.0                                     |
| (W) 260-280                             | 1.1             |             |        |         |        |                   |        |         |             |        |               | 1.1        | 4.0          | <b>4</b> .ü                             |
| 290-310                                 | 1.1             | 1.1         |        |         |        |                   |        |         |             |        |               | 2.2        | 3.5          | 4.0                                     |
| 320-340                                 | 6.7             | .6          |        |         |        |                   |        |         |             |        |               | 7.2        | 2.2          | 2.0                                     |
| 333 313                                 |                 | •••         |        |         |        |                   |        |         |             |        |               | , , ,      |              | 2.0                                     |
| VARIABLE                                |                 | • • • • • • |        |         | •••••  |                   |        | •••••   |             |        | • • • • • • • | •••••      | ••••         |   |
| CALM                                    | //////          | //////      | ////// | /////// | ////// | ///////           | ////// | /////// | //////      | ////// | ////////      | 45.0       | /////        | //////                                  |
| TOTALS                                  | 39.5            | 13.9        | 1.7    |         |        |                   |        |         |             |        |               | 100.0      | 1.8          | 3.0                                     |
|   |                 |             |        |         |        |                   |        |         |             |        |               |            |              |   |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

MONTH: JAN HOURS: 06-08

|                     |                 | LS     | T TO UI       | :C: - 9       |         |          |         |               | MONTH   | : JAN       | HOUR    | S: 06-08   | 3            |                 |
|---------------------|-----------------|--------|---------------|---------------|---------|----------|---------|---------------|---------|-------------|---------|------------|--------------|-----------------|
|                     | • • • • • • • • |        | • • • • • • • | • • • • • • • | WIND S  | SPEED IN | KNOTS   | •••••         |         | • • • • • • |         |            |              | • • • • • • •   |
| DIRECTION (DEGREES) | 1-4             | 5-9    | 10-14         | 15-19         |         | 25-29    |         | 35-39         | 40~49   | 50-64       | GE 65   | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND  |
| (N) 350-010         | 19.4            | 10.6   | 1.7           |               | •••••   |          | •••••   | • • • • • • • |         | •••••       |         | 31.7       | 4.4          | 3.0             |
| 020-040             | 2.8             | 2.2    |               |               |         |          |         |               |         |             |         | 5.0        | 3.8          | 4.0             |
| 050-070             | .6              | 1.1    |               |               |         |          |         |               |         |             |         | 1.7        | 5.3          | 5.0             |
| (E) 080-100         |                 |        |               |               |         |          |         |               |         |             |         |            |              |                 |
| 110-130             |                 |        |               |               |         |          |         |               |         |             |         |            |              |                 |
| 140-160             | .6              |        |               |               |         |          |         |               |         |             |         | .6         | 2.0          | 2.0             |
| (S) 170-190         | 3.9             |        |               |               |         |          |         |               |         |             |         | 3.9        | 1.7          | 2.0             |
| 200-220             | 7.2             |        |               |               |         |          |         |               |         |             |         | 7.2        | 1.9          | 2.0             |
| 230-250             | 1.1             |        |               |               |         |          |         |               |         |             |         | 1.1        | 1.5          | 1.5             |
| (W) 260-280         |                 |        |               |               |         |          |         |               |         |             |         |            |              |                 |
| 290-310             | 1.7             | 1.1    |               |               |         |          |         |               |         |             |         | 2.8        | 4.2          | 3.0             |
| 320-340             | 5.0             | 1.1    |               |               |         |          |         |               |         |             |         | 6.1        | 3.0          | 2.0             |
|                     | <br>            |        |               |               |         |          |         |               |         |             |         |            |              | · • • • • • • • |
| VARIABLE            |                 |        |               |               |         |          |         |               |         |             |         |            |              |                 |
| CALM                | 11111111        | ////// | //////        | ///////       | //////  | ///////  | 11/1/// | ///////       | /////// | //////      | /////// | 40.0       | /////        | /////           |
| TOTALS              | 42.3            | 16.1   | 1.7           |               |         |          |         |               |         |             |         | 100.0      | 2.2          | 3.0             |
|                     |                 |        | TС            | ATAT. NIIM    | IBER OF | OBSERVA  | TIONS   | 180           |         |             |         |            |              |                 |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: JAN HOURS: 09-11

|                     |         | гэ            | 1 10 01       | C: - 9 |               |          |         |   | MONTH   | : JAN  | пос         | RS: 09-1   |              |                |
|---------------------|---------|---------------|---------------|--------|---------------|----------|---------|---|---------|--------|-------------|------------|--------------|----------------|
|                     |         | • • • • • • • | • • • • • • • |        | WIND S        | SPEED IN | KNOTS   | •••••                                   |         |        |             |            | • • • • • •  |                |
| DIRECTION (DEGREES) | 1-4     | 5-9           | 10-14         | 15-19  |               | 25-29    |         | 35-39                                   | 40-49   | 50-64  | GE 65       | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 10.0    | 10.0          | .8            | •••••  | •••••         |          |         | •••••                                   |         |        | • • • • • • | 20.8       | 5.0          | 5.0            |
| 020-040             | 3.3     | 7.5           |               |        |               | •        |         |   |         |        |             | 10.8       | 4.6          | 5.0            |
| 050-070             | 1.7     | .8            |               |        |               |          |         |   |         |        |             | 2.5        | 2.7          | 1.0            |
| (E) 080-100         | }       |               |               |        |               |          |         |   |         |        |             |            |              |                |
| 110-130             | ļ       |               |               |        |               |          |         |   |         |        |             |            |              |                |
| 140-160             |         |               |               |        |               |          |         |   |         |        |             |            |              |                |
| (S) 170-190         | 9.2     |               |               |        |               |          |         |   |         |        |             | 9.2        | 2.5          | 3.0            |
| 200-220             | 10.8    | .8            |               |        |               |          |         |   |         |        |             | 11.7       | 2.6          | 2.0            |
| 230-250             | .8      |               |               |        |               |          |         |   |         |        |             | .8         | 2.0          | 2.0            |
| (W) 260-280         |         | .8            |               |        |               |          |         |   |         |        |             | .8         | 6.0          | 6.0            |
| 290~310             | .8      | .8            |               |        |               |          |         |   |         |        |             | 1.7        | 4.0          | 4.0            |
| 320-340             | 5.8     |               | .8            |        |               |          |         |   |         |        |             | 6.7        | 3.1          | 2.0            |
| VARIABLE            | :<br>   | 8             | 8             |        | • • • • • • • |          |         | • |         | •••••  | • • • • •   | 1.7        | 11.0         | 11.0           |
| CALM                | 1111111 | //////        | //////        | ////// | ///////       | (1/1//// | /////// | ///////                                 | /////// | ////// | '/////      | / 33.3     | /////        | /////          |
| TOTALS              | 42.4    | 21.5          | 2.4           |        |               |          |         |   |         |        |             | 100.0      | 2.7          | 3.0            |
|                     |         |               |               |        |               |          |         |   |         |        |             |            |              |                |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN HOURS: 12-14

| •••••               | • • • • • • • | • • • • • • | • • • • • • | • • • • • • • | WIND S | SPEED IN | KNOTS   | •••••       | • • • • • • | • • • • • • | •••••         | • • • • • • • | • • • • • •  | • • • • • • •  |
|---------------------|---------------|-------------|-------------|---------------|--------|----------|---------|-------------|-------------|-------------|---------------|---------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4           | 5-9         | 10-14       | 15-19         | 20-24  | 25-29    | 30-34   | 35-39       | 40-49       | 50-64       | GE 65         | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 10.6          | 11.1        | •••••       | • • • • • •   | •••••  |          |         | •••••       |             |             | •••••         | 21.7          | 4.6          | 5.0            |
| 020-040             | 5.6           | 2.2         |             |               |        |          |         |             |             |             |               | 7.8           | 3.9          | 4.0            |
| 050-070             |               |             |             |               |        |          |         |             |             |             |               |               |              |                |
| (E) 080-100         | .6            |             |             |               |        |          |         |             |             |             |               | .6            | 1.0          | 1.0            |
| 110-130             | .6            |             |             |               |        |          |         |             |             |             |               | .6            | 1.0          | 1.0            |
| 140-160             | 2.2           |             |             |               |        |          |         |             |             |             |               | 2.2           | 2.3          | 2.5            |
| (S) 170-190         | 7.8           |             |             |               |        |          |         |             |             |             |               | 7.8           | 2.1          | 2.0            |
| 200-220             | 13.9          | 1.1         |             |               |        |          |         | •           |             |             |               | 15.0          | 2.5          | 2.0            |
| 230-250             | 2.8           | .6          |             |               |        |          |         |             |             |             |               | 3.3           | 2.3          | 2.0            |
| (W) 260-280         | 3.3           |             |             |               |        |          |         |             |             |             |               | 3.3           | 2.2          | 2.0            |
| 290-310             | 5.6           | .6          |             |               |        |          |         |             |             |             |               | 6.1           | 2.6          | 3.0            |
| 320-340             | 5.6           | 3.9         |             |               |        |          |         |             |             |             |               | 9.4           | 3.3          | 2.0            |
| VARIABLE            |               | 1.1         | 6           |               | •••••  |          |         | • • • • • • |             |             | • • • • • • • | 1.7           | 8.0          | 7.0            |
|                     | ///////       |             |             | ,,,,,,,       |        | ,,,,,,,, | ,,,,,,  | ,,,,,,,     |             |             | ,,,,,,,,      |               |              |                |
| CALM                |               |             |             | 1111111       | ////// | 1111111  | 1111111 | 11/1///     | ///////     | 1111111     | 1111111       |               |              |                |
| TOTALS              | 58.6          | 20.6        | .6          |               |        |          |         |             |             |             |               | 100.0         | 2.6          | 3.0            |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN HOURS: 15-17 ...... WIND SPEED IN KNOTS 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN DIRECTION (DEGREES) WIND WIND \* (N) 350-010 14.4 11.7 1.7 27.8 4.4 4.0 020-040 7.2 1.1 8.3 2.8 2.0 050-070 .6 .6 3.0 3.0 (E) 080-100 1.0 .6 -6 1.3 110-130 .6 .6 1.0 1.0 140-160 .6 .6 2.0 2.0 (S) 170-190 5.0 5.0 2.4 2.0 200-220 10.6 1.1 11.7 2.5 2.0 230-250 3.9 2.4 2.0 (W) 260-280 5.6 5.6 1.7 2.0 290-310 7.8 1.1 8.9 2.6 2.0 320-340 7.8 2.0 VARIABLE CALM TOTALS 64.7 19.5 1.7 100.0 2.7 2.0

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: JAN HOURS: 18-20

LST TO UTC: - 9 WIND SPEED IN KNOTS 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN DIRECTION 1-4 (DEGREES) % WIND WIND (N) 350-010 16.1 7.2 1.1 24.4 3.8 3.0 020-040 7.2 6.7 .6 2.5 2.0 050-070 .6 .6 1.0 1.0 (E) 080-100 110-130 140-160 (S) 170-190 4.0 4.0 .6 .6 200-220 2.3 230-250 2.8 2.8 1.6 2.0 (W) 260-280 1.1 1.1 1.5 1.5 290-310 2.0 3.3 1.8 320~340 13.3 3.9 17.2 3.0 VARIABLE ///////// 38.9 //////// CALM TOTALS 47.3 12.9 1.1 100.0 1.9 2.0

OPERATING LOCATION "A"

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

USAFETAC, ASHEVILLE NC STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 HOURS: 21-23 MONTH: JAN LST TO UTC: - 9 WIND SPEED IN KNOTS 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN DIRECTION (DEGREES) \* WIND WIND ...... (N) 350-010 17.8 11.1 28.9 4.0 3.5 020-040 8.3 1.1 2.5 2.0 9.4 050-070 .6 2.0 2.0 .6 (E) 080-100 110-130 140-160 (S) 170-190 1.1 1.1 2.5 2.5 200-220 2.8 .6 3.3 2.7 2.0 230-250 .6 .6 1.0 1.0 (W) 260-280 .6 2.0 .6 2.0 290-310 1.7 1.1 2.8 3.6 4.0 320-340 8.9 8.9 2.5 2.0 VARIABLE //////// 43.9 //////// CALM TOTALS 42.4 13.9 100.0 3.0 1.9

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: JAN HOURS: ALL

| •••••       | • • • • • • • • |        | • • • • • • |             | WIND S        | SPEED IN      | KNOTS       | • • • • • • • | •••••   | • • • • • • | •••••   | • • • • • • • | •••••  | • • • • • • • |
|-------------|-----------------|--------|-------------|-------------|---------------|---------------|-------------|---------------|---------|-------------|---------|---------------|--------|---------------|
| DIRECTION   | 1-4             | 5-9    | 10-14       | 15-19       | 20-24         | 25-29         | 30-34       | 35-39         | 40-49   | 50-64       | GE 65   | TOTAL         | MEAN   | MEDIAN        |
| (DEGREES)   |                 |        |             | • • • • • • |               |               |             |               | •••••   |             |         | 8             | WIND   | WIND          |
| (N) 350-010 | 15.9            | 9.4    | .9          | • • • • • • | •••••         | • • • • • • • | •••••       | • • • • • •   | •••••   |             | •••••   | 26.1          | 4.1    | 4.0           |
| 020-040     | 5.7             | 2.3    |             |             |               |               |             |               |         |             |         | 8.0           | 3.4    | 3.0           |
| 050-070     | .5              | .4     |             |             |               |               |             |               |         |             |         | .9            | 3.7    | 3.5           |
| (E) 080-100 | .3              |        |             |             |               |               |             |               |         |             |         | .3            | 2.0    | 1.5           |
| 110-130     | .1              |        |             |             |               |               |             |               |         |             |         | .1            | 1.0    | 1.0           |
| 140-160     | .4              |        |             |             |               |               |             |               |         |             |         | .4            | 2.2    | 2.0           |
| (S) 170-190 | 3.6             | .1     |             |             |               |               |             |               |         |             |         | 3.7           | 2.3    | 2.0           |
| 200-220     | 6.7             | .6     |             |             |               |               |             |               |         |             |         | 7.3           | 2.4    | 2.0           |
| 230-250     | 1.7             | .1     |             |             |               |               |             |               |         |             |         | 1.9           | 2.0    | 2.0           |
| (W) 260-280 | 1.5             | .1     |             |             |               |               |             |               |         |             |         | 1.7           | 2.3    | 2.0           |
| 290-310     | 3.1             | .8     |             |             |               |               |             |               |         |             |         | 3.9           | 2.9    | 2.0           |
| 320-340     | 7.6             | 2.1    | .1          |             |               |               |             |               |         |             |         | 9.8           | 3.1    | 2.0           |
| VARIABLE    | :               |        |             |             | • • • • • • • |               | • • • • • • | • • • • • •   |         | • • • • • • |         |               | 9.0    | 8.5           |
|             |                 |        |             | ,,,,,,,     | ,,,,,,,       |               |             |               |         |             |         |               |        |               |
| CALM        | 1///////        | 111111 | ,,,,,,,     | ,,,,,,,     | //////        | 1111111       | //////      | 1111111       | ,,,,,,, | 1111111     | 1111111 | 35.5          | 111111 | /////         |
| TOTALS      | 47.1            | 16.2   | 1.1         |             |               |               |             |               |         |             |         | 100.0         | 2.2    | 3.0           |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

MONTH: JAN HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

| DIRECTION   |            |        | 10.14  |         |               | PEED IN |               | 25 20  | 40.40   | 50.64   |       |          |       |        |
|-------------|------------|--------|--------|---------|---------------|---------|---------------|--------|---------|---------|-------|----------|-------|--------|
|             | 1-4        | 5-9    |        | 15-19   | 20~24         | 25-29   |               |        | 40-49   | 50-64   | GE 6  | 5 TOTAL  |       | MEDIAN |
| (DEGREES)   | ļ          |        |        |         |               |         |               |        |         |         |       | 8        | WIND  | WIND   |
| (N) 350-010 | 10.5       | 21.3   | 1.9    |         | •••••         |         | • • • • • • • | •••••  | •••••   |         |       | 33.7     | 5.8   | 6.0    |
| 020-040     | 1.9        | 2.3    |        |         |               |         |               |        |         |         |       | 4.3      | 4.1   | 5.0    |
| 050-070     | .4         |        |        |         |               |         |               |        |         |         |       | .4       | 1.0   | 1.0    |
| (E) 080-100 | .4         |        |        |         |               |         |               |        |         |         |       | .4       | 2.0   | 2.0    |
| 110-130     | :          |        |        |         |               |         |               |        |         |         |       |          |       |        |
| 140-160     | l          |        |        |         |               |         |               |        |         |         |       |          |       |        |
| (S) 170-190 | 4.3        |        |        |         |               |         |               |        |         |         |       | 4.3      | 2.3   | 2.0    |
| 200-220     | 10.5       | 1.6    |        |         |               |         |               |        |         |         |       | 12.0     | 2.9   | 3.0    |
| 230-250     | 1.9        |        |        |         |               |         |               |        |         |         |       | 1.9      | 1.6   | 1.0    |
| (W) 260-280 | .4         |        |        |         |               |         |               |        |         |         |       | .4       | 2.0   | 2.0    |
| 290-310     | .8         |        |        |         |               | •       |               |        |         |         |       | .8       | 1.0   | 1.0    |
| 320-340     | 8.5        | 1.9    |        |         |               |         |               |        |         |         |       | 10.5     | 2.8   | 2.0    |
| VARIABLE    | :<br> <br> |        |        |         | • • • • • • • | •••••   | • • • • • •   | •••••  |         |         |       | •••••    |       | •••••  |
| CALM        | 1111111    | ////// | ////// | /////// | ///////       | 7////// | //////        | ////// | '////// | /////// | ///// | /// 31.4 | ///// | ////// |
| TOTALS      | 39.6       | 27.1   | 1.9    |         |               |         |               |        |         |         |       | 100.0    | 2.9   | 4.0    |

TOTAL NUMBER OF OBSERVATIONS 258

C - 4 - 10

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

TOTALS

49.6 14.5

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: FEB HOURS: 00-02

WIND SPEED IN KNOTS DIRECTION 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) ¥ WIND WIND ...... (N) 350-010 21.8 7.3 3.4 29.1 3.0 020-040 8.5 .6 9.1 2.0 2.0 050-070 .6 1.2 5.0 5.0 (E) 080-100 110-130 140-160 .6 .6 1.0 1.0 (S) 170-190 1.2 1.2 2.5 2.5 200-220 3.0 2.6 2.0 230-250 1.8 .6 2.4 3.0 3.0 (W) 260-280 .6 .6 1.2 4.5 4.5 290-310 1.8 1.2 3.0 3.6 3.0 320-340 10.3 3.0 13.3 3.5 3.0 VARIABLE CALM 

TOTAL NUMBER OF OBSERVATIONS 165

100.0 2.0

3.0

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: FEB HOURS: 03-05

| • | • • • • • • • •                            | • • • • • • | • • • • • • • | • • • • • • • | WIND S | PEED IN | KNOTS  | • • • • • • | • • • • • •   | •••••  |         | • • • • • • • | • • • • •    | •••••          |
|---|--|-------------|---------------|---------------|--------|---------|--------|-------------|---------------|--------|---------|---------------|--------------|----------------|
| DIRECTION (DEGREES)                     | 1-4  | 5-9         | 10-14         | 15-19         | 20-24  | 25-29   | 30-34  | 35-39       | 40-49         | 50~64  | GE 65   | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 28.5                                       | 6.7         | •••••         | •••••         | •••••  |         |        | •••••       | •••••         | ••••   |         | 35.2          | 3.1          | 2.0            |
| 020-040                                 | 4.8  |             |               |               |        |         |        |             |               |        |         | 4.8           | 1.3          | 1.0            |
| 050-070                                 | 1.8  |             |               |               |        |         |        |             |               |        |         | 1.8           | 1.3          | 1 0            |
| (E) 080-100                             | ļ  |             |               |               |        |         |        |             |               |        |         |               |              |                |
| 110-130                                 |  |             |               |               |        |         |        |             |               |        |         |               |              |                |
| 140-160                                 | .6   |             |               |               |        |         |        |             |               |        |         | .6            | 1.0          | 1.0            |
| (S) 170-190                             | 1.8  |             |               |               |        |         |        |             |               |        |         | 1.8           | 2.7          | 2.0            |
| 200-220                                 | 2.4  | .6          |               |               |        |         |        |             |               |        |         | 3.0           | 3.0          | 3.0            |
| 230-250                                 | 1.2  | .6          |               |               |        |         |        |             |               |        |         | 1.8           | 2.7          | 2.0            |
| (W) 260-280                             | .6   |             |               |               |        |         |        |             |               |        |         | .6            | 1.0          | 1.0            |
| 290-310                                 | 1.8  |             |               |               |        |         |        |             |               |        |         | 1.8           | 2.7          | 2.0            |
| 320-340                                 | 7.9  |             |               |               |        |         |        |             |               |        |         | 7.9           | 2.0          | 2.0            |
|   | }<br>• • • • • • • • • • • • • • • • • • • |             |               |               |        |         |        | •           | • • • • • • • |        |         | • • • • • • • |              |                |
| VARIABLE                                |  |             |               |               |        |         |        |             |               |        |         |               |              |                |
| CALM                                    | 11111111                                   | '/////      | 11/1///       | 7//////       | 7///// | '////// | ////// | 1111111     | 7777777       | 1///// | (////// | 40.6          | /////        | 11/1///        |
| TOTALS                                  | 51.4                                       | 7.9         |               |               |        |         |        |             |               |        |         | 100.0         | 1.6          | 2.0            |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

HOURS: 06-08 MONTH: FEB LST TO UTC: - 9 WIND SPEED IN KNOTS DIRECTION 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) WIND WIND ..... (N) 350-010 22.3 7.8 .6 30.7 3.7 3.0 020-040 3.0 1.2 4.2 2.7 2.0 050-070 .6 .6 2.0 2.0 (E) 080-100 110-130 140-160 (S) 170-190 3.0 3.0 1.6 2.0 200-220 6.0 6.0 1.9 1.5 230-250 1.8 .6 2.4 3.3 3.5 (W) 260-280 290-310 2.0 2.0 320-340 6.6 6.6 2.5 2.0 VARIABLE CALM TOTALS 43.9 9.6 100.0 1.7 2.0 .6

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

| LST TO UTC: - 9                         |                 |        |        |         |               |               |           | MONTH   | : FEB   | HOUR                                    | s: 09-11                                |        | •            |                |
|---|-----------------|--------|--------|---------|---------------|---------------|-----------|---------|---------|---|---|--------|--------------|----------------|
| • | • • • • • • • • |        |        |         |               | SPEED IN      |           | •••••   |         | •••••                                   | • • • • • •                             |        | •••••        | • • • • • • •  |
| DIRECTION (DEGREES)                     | 1-4             | 5-9    | 10-14  | 15-19   | 20-24         | 25-29         | 30-34     | 35-39   | 40-49   | 50-64                                   | GE 65                                   | TOTAI. | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 12.5            | 10.7   | 2.7    | •••••   | •••••         | • • • • • • • |           | •••••   |         | •••••                                   | •••••                                   | 25.9   | 4.7          | 5.0            |
| 020-040                                 | 4.5             | .9     |        |         |               |               |           |         |         |   |   | 5.4    | 3.3          | 3.5            |
| 050-070                                 | ļ               |        |        |         |               |               |           |         |         |   |   |        |              |                |
| (E) 080-100                             | ļ               |        |        |         |               |               |           |         |         |   |   |        |              |                |
| 110-130                                 | Ì               | .9     |        |         |               |               |           |         |         |   |   | .9     | 5.0          | 5.0            |
| 140-160                                 | 1.8             |        | .9     |         |               |               |           |         |         |   |   | 2.7    | 4.7          | 2.0            |
| (S) 170-190                             | 7.1             | .9     |        |         |               |               |           |         |         |   |   | 8.0    | 2.7          | 2.0            |
| 200-220<br>230-250                      | 7.1             | 2.7    |        |         |               |               |           |         |         |   |   | 9.8    | 3.1<br>5.7   | 2.0<br>6.0     |
| (W) 260-280                             | .9              | 1.0    |        |         |               |               |           |         |         |   |   | .9     | 1.0          | 1.0            |
| 290-310                                 | 1.8             |        |        |         |               |               |           |         |         |   |   | 1.8    | 4.0          | 4.0            |
| 320-340                                 | 10.7            | .9     |        |         |               |               |           |         |         |   |   | 11.6   | 2.2          | 2.0            |
| VARIABLE                                | l<br><br>l      |        |        |         | • • • • • • • |               | <b></b> . |         |         | • | • |        |              |                |
| AUITADID                                |                 |        |        |         |               |               |           |         |         |   |   |        |              |                |
| CALM                                    | 11111111        | ////// | 1!//// | /////// | (//////       | (///////      | '//////   | '////// | '////// | 11/1///                                 | '//////                                 |        | //////       | 11/1///        |
| TOTALS                                  | 47.3            | 18.8   | 3.6    |         |               |               |           |         |         |   |   | 100.0  | 2.6          | 3.0            |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: FEB

LST TO UTC: - 9 HOURS: 12-14

| WIND SPEED IN KNOTS |         |        |        |               |               |               |        |   |               |               |         |             |              |                |
|---------------------|---------|--------|--------|---------------|---------------|---------------|--------|---|---------------|---------------|---------|-------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4     | 5-9    | 10-14  | 15-19         | 20~24         | 25-29         | 30-34  | 35-39                                   | 40-49         | 50-64         | GE 65   | TOTAL<br>%  | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 13.1    | 6.5    | 1.2    | • • • • • • • | • • • • • • • | • • • • • • • |        | • | • • • • • • • | • • • • • • • | •••••   | 20.8        | 4.2          | 4.0            |
| (N) 350-010         | 13.1    | 6.5    | 1.2    |               |               |               |        |   |               |               |         | 20.8        | 4.2          | 4.0            |
| 020-040             | 1.2     | 3.6    | 1.2    |               |               |               |        |   |               |               |         | 6.0         | 6.2          | 5.5            |
| 050-070             | .6      |        | .6     |               |               |               |        |   |               |               |         | 1.2         | 7.0          | 7.0            |
| (E) 080-100         |         | .6     |        |               |               |               |        |   |               |               |         | .6          | 5.0          | 5.0            |
| 110-130             |         | 1.2    |        |               |               |               |        |   |               |               |         | 1.2         | 8.0          | 8.0            |
| 140-160             | 1.8     |        |        |               |               |               |        |   |               |               |         | 1.8         | 1.7          | 2.0            |
| (S) 170-190         | 6.0     | 1.8    |        |               |               |               |        |   |               |               |         | 7.7         | 3.2          | 3. )           |
| 200-220             | 13.1    | 6.0    |        |               |               |               |        |   |               |               |         | 19.0        | 3.3          | 3.0            |
| 230-250             | 3.0     | 2.4    |        |               |               |               |        |   |               |               |         | 5.4         | 4.8          | 4.0            |
| (W) 260-280         | .6      | .6     |        |               |               |               |        |   |               |               |         | 1.2         | 4.5          | 4.5            |
| 290-310             | 4.8     | 2.4    |        |               |               |               |        |   |               |               |         | 7.1         | 3.6          | 4.0            |
| 320-340             | 7.7     | 1.2    |        |               |               |               |        |   |               |               |         | 8.9         | 2.9          | 3.0            |
|                     | ,<br>   |        |        |               |               |               |        |   |               |               |         | . <b></b> . |              |                |
| VARIABLE            |         | .6     |        |               |               |               |        |   |               |               |         | .6          | 7.0          | 7.0            |
| CALM                | /////// | ////// | ////// | //////        | 1111111       | '//////       | ////// | <b>///</b> ////                         |               | 111111        | '////// | 18.5        | /////        | /////          |
| TOTALS              | 51.9    | 26.9   | 3.0    |               |               |               |        |   |               |               |         | 100.0       | 3.2          | 4.6            |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: FEB HOURS: 15-17

| ·                   |         |         |        |             |        |                   |        |         |        |         |          |       |              |                |
|---------------------|---------|---------|--------|-------------|--------|-------------------|--------|---------|--------|---------|----------|-------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4     | 5-9     | 10-14  | 15~19       |        | SPEED IN<br>25-29 |        | 35-39   | 40-49  | 50-64   | GE 65    | TOTAL | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 11.9    | 10.7    | .6     |             |        |                   |        | •••••   |        | •••••   |          | 23.2  | 4.5          | 4.0            |
| 020~040             | 4.2     | 3.6     | .6     | .6          |        |                   |        |         |        |         |          | 8.9   | 5.5          | 5.0            |
| 050~070             | .6      |         |        |             |        |                   |        |         |        |         |          | .6    | 2.0          | 2.0            |
| (E) 080-100         | 1.8     | .6      |        |             |        |                   |        |         |        |         |          | 2.4   | 3.5          | 3.0            |
| 110-130             |         |         |        |             |        |                   |        |         |        |         |          |       |              |                |
| 140-160             | .6      |         |        |             |        |                   |        |         |        |         |          | .6    | 4.0          | 4.0            |
| (S) 170-190         | 2.4     | .6      |        |             |        |                   |        |         |        |         |          | 3.0   | 3.8          | 4.0            |
| 200-220             | 6.0     | 6.0     |        |             |        |                   |        |         |        |         |          | 11.9  | 4.4          | 4.5            |
| 230-250             | 8.3     | 6.0     |        |             |        |                   |        |         |        |         |          | 14.3  | 4.0          | 3.5            |
| (W) 260-280         | 1.8     | 1.2     |        |             |        |                   |        |         |        |         |          | 3.0   | 3.8          | 3.0            |
| 290-310             | 8.9     | .6      |        |             |        |                   |        |         |        |         |          | 9.5   | 2.6          | 2.0            |
| 320-340             | 14.3    | 1.2     |        |             |        |                   |        |         |        |         |          | 15.5  | 3.0          | 3.0            |
|                     | [<br>   |         |        | • • • • • • |        |                   |        |         |        |         |          |       |              |                |
| VARIABLE            |         | 1.2     |        |             |        |                   |        |         |        |         |          | 1.2   | 7.5          | 7.5            |
| CALM                | 1111111 | /////// | ////// | //////      | ////// | '///////          | ////// | 1111111 | ////// | 1111111 | '/////// | 6.0   | //////       | /////          |
| TOTALS              | 60.8    | 31.7    | 1.2    | .6          |        |                   |        |         |        |         |          | 100.0 | 3.8          | 4.0            |

# PERCENTAGE PREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9 MONTH: FEB HOURS: 18-20 WIND SPEED IN KNOTS DIRECTION 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN 1-4 (DEGREES) WIND WIND (N) 350-010 4.2 1.2 13.9 3.0 19.3 3.5 020-040 1.8 3.1 2.5 6.6 8.4 050-070 1.2 1.2 1.0 1.0 (E) 080-100 110-130 1.2 1.8 3.7 3.0 140-160 (S) 170-190 2.0 2.0 .6 .6 200-220 7.2 7.8 3.2 3.0 230-250 8.4 9.0 2.5 2.0 .6 (W) 260-280 .6 2.6 2.0 290-310 5.4 .6 6.0 2.8 3.0 320-340 3.0 11.4 1.8 13.3 3.0 VAR.ABLE CALM TOTALS 63.1 10.8 1.2 100.0 2.3 3.0

TOTAL NUMBER OF OBSERVATIONS 166

C - 4 - 17

STATION NUMBER: 471066

VARIABLE

53.3 7.9

.6

CALM

## PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: FEB HOURS: 21-23 WIND SPEED IN KNOTS DIRECTION 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) 8 WIND WIND ...... (N) 350-010 20.2 5.5 25.8 020-040 14.1 14.1 2.0 2.0 050-070 1.8 1.8 1.7 1.0 (E) 080-100 110-130 140-160 (S) 170-190 3.0 .6 .6 3.0 200-220 230-250 1.2 1.2 1.5 1.5 (W) 260-280 2.0 2.0 .6 .6 290-310 320-340 12.3 1.8 .6 14.7 3.2 3.0

STATION NAME: CAMP CASEY/TONGDUCHON KO

TOTAI, NUMBER OF OBSERVATIONS 163

100.0

1.7

2.0

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: FEB HOURS: ALL

....... WIND SPEED IN KNOTS DIRECTION 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN ♦ WIND WIND (DEGREES) (N) 350-010 18.2 7.3 .7 3.7 26.2 3.0 020-040 5.9 1.5 .2 .1 7.7 3.2 2.0 050-070 2.8 2.0 .9 . 1 . 1 1.1 (E) 080-100 .2 .2 . 4 3.8 4.0 110-130 .2 .3 .5 5.3 5.0 140-160 .6 .1 .7 2.8 2.0 (S) 170-190 2.7 2.8 2.0 . 4 3.1 200-220 5.8 2.1 7.9 3.3 3.0 230-250 3.5 1.6 5.0 3.6 3.0 (W) 260-280 1.6 3.0 3.0 . 4 290-310 3.2 .6 3.8 3.0 3.0 320-340 10.1 1.3 11.5 2.9 3.0 .1 VARIABLE 7.3 7.0 CALM TOTALS 52.9 16.0 100.0 1.2 . 1 2.4 3.0

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: FEB HOURS: ALL LST TO UTC: - 9

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS). AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

|             |          | •••••       |               |             | WIND S        | PEED IN | KNOTS       | •••••                                   |               |               | • • • • | •••• |       | ••••• | •••••  |
|-------------|----------|-------------|---------------|-------------|---------------|---------|-------------|---|---------------|---------------|---------|------|-------|-------|--------|
| DIRECTION   | 1-4      | 5-9         | 10-14         | 15-19       | 20-24         | 25-29   | 30-34       | 35-39                                   | 40-49         | 50-64         | GE      | 65   | TOTAL | MEAN  | MEDIAN |
| (DEGREES)   |          | • • • • • • | • • • • • •   | •••••       | • • • • • • • | •••••   | • • • • • • | •••••                                   | • • • • • • • | •••••         | ••••    | •••• | *     | WIND  | WIND   |
| (N) 350-010 | 23.5     | 5.5         | • • • • • • • | • • • • • • |               |         | • • • • • • | •••••                                   | • • • • • •   | •••••         | ••••    | •••• | 29.0  | 3.2   | 3.0    |
| 020-040     | 2.1      |             |               |             |               |         |             |   |               |               |         |      | 2.1   | 1.6   | 2.0    |
| 050-070     |          |             |               |             |               |         |             |   |               |               |         |      |       |       |        |
| (E) 080-100 |          |             |               |             |               |         |             |   |               |               |         |      |       |       |        |
| 110-130     |          |             |               |             |               |         |             |   |               |               |         |      |       |       |        |
| 140-160     | <u>}</u> |             |               |             |               |         |             |   |               |               |         |      |       |       |        |
| (S) 170-190 | 4.6      |             |               |             |               |         |             |   |               |               |         |      | 4.6   | 2.2   | 2.0    |
| 200-220     | 8.0      | 2.5         |               |             |               |         |             |   |               |               |         |      | 10.5  | 3.1   | 3.0    |
| 230-250     | 2.1      | .4          |               |             |               |         |             |   |               |               |         |      | 2.5   | 3.0   | 3.0    |
| (W) 260-280 | .4       | . 4         |               |             |               |         |             |   |               |               |         |      | .8    | 4.5   | 4.5    |
| 290-310     | 1.3      | .4          |               |             |               |         |             |   |               |               |         |      | 1.7   | 3.8   | 4.0    |
| 320-340     | 13.4     | .3          |               |             |               |         |             |   |               |               |         |      | 14.7  | 2.5   | 2.0    |
| VARIABLE    |          | • • • • • • | • • • • • • • | •••••       |               | •••••   |             | • | •••••         | • • • • • • • | • • • • | •••• |       |       | •••••  |
| CALM        | 11111111 | //////      | //////        | //////      | ///////       | //////  | //////      | ///////                                 | //////        | //////        | ////    | ///  | 34.0  | ///// | /////  |
| TOTALS      | 55.4     | 10.5        |               |             |               |         |             |   |               |               |         |      | 100.0 | 1.9   | 2.0    |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: MAR HOURS: 00-02

|                     |               | го          | 1 10 01     | C: - 9      |        |                 |         |             | MONTH   | : MAK       | noor          | w: 00-02      | 4            |                |
|---------------------|---------------|-------------|-------------|-------------|--------|-----------------|---------|-------------|---------|-------------|---------------|---------------|--------------|----------------|
|                     | • • • • • • • |             | •••••       |             | WIND S | SPEED IN        | KNOTS   | • • • • • • |         | • • • • • • | • • • • • • • | • • • • • • • |              | • • • • • • •  |
| DIRECTION (DEGREES) | 1-4           | 5-9         | 10-14       | 15-19       | 20-24  | 25-29           | 30-34   | 35-39       | 40-49   | 50-64       | GE 65         | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 12.9          | 5.4         | •••••       | • • • • • • |        | • • • • • • • • | •••••   | •••••       | •••••   |             | ******        | 18.3          | 3.3          | 2.0            |
| 020-040             | 9.7           | 1.1         |             |             |        |                 |         |             |         |             |               | 10.8          | 2.1          | 2.0            |
| 050-070             | 2.7           |             |             |             |        |                 |         |             |         |             |               | 2.7           | 2.2          | 2.0            |
| (E) 080-100         |               |             |             |             |        |                 |         |             |         |             |               |               |              |                |
| 110-130             | -5            |             |             |             |        |                 |         |             |         |             |               | .5            | 1.0          | 1.0            |
| 140-160             |               |             |             |             |        |                 |         |             |         |             |               |               |              |                |
| (S) 170-190         | 3.2           | .5          |             |             |        |                 |         |             |         |             |               | 3.8           | 3.3          | 3.0            |
| 200-220             | 2.2           | 2.7         |             |             |        |                 |         |             |         |             |               | 4.8           | 4.8          | 5.0            |
| 230-250             | 2.7           | .5          |             |             |        |                 |         |             |         |             |               | 3.2           | 2.3          | 1.5            |
| (W) 260-280         | .5            |             |             |             |        |                 |         |             |         |             |               | .5            | 1.0          | 1.0            |
| 290-310             | .5            | .5          |             |             |        |                 |         |             |         |             |               | 1.1           | 5.0          | 5.0            |
| 320-340             | 5.4           |             |             |             |        |                 |         |             |         |             |               | 5.4           | 2.6          | 2.5            |
| VARIABLE            |               | • • • • • • | • • • • • • |             | •••••  |                 | •••     |             |         |             | • • • • • •   | • • • • • • • |              | • • • • • • •  |
| CALM                | 1111111       | //////      | //////      | //////      | 111111 | (111111         | /////// | 1111111     | 1111111 | 111111      | ///////       | 48.9          | /////        | //////         |
| TOTALS              | 40.3          | 10.7        |             |             |        |                 |         |             |         |             |               | 100.0         | 1.5          | 2.0            |
|                     |               |             |             |             |        |                 |         |             |         |             |               |               |              |                |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: MAR HOURS: 03-05

|                     |          |             |               |         | WIND S  | PEED IN | KNOTS   |         |         | ******  |         |            |              | • |
|---------------------|----------|-------------|---------------|---------|---------|---------|---------|---------|---------|---------|---------|------------|--------------|---|
| DIRECTION (DEGREES) | 1-4      | 5-9         | 10-14         | 15-19   | 20-24   | 25-29   | 30-34   | 35-39   | 40-49   | 50-64   | GE 65   | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND                          |
| (N) 350-010         | 15.1     | 5.9         | • • • • • • • | •••••   |         | •••••   |         |         |         |         | •••••   | 21.0       | 3.0          | 2.0                                     |
| 020-040             | 3.8      | 1.1         |               |         |         |         |         |         |         |         |         | 4.8        | 2.9          | 3.0                                     |
| 050-070             | 1.1      | 1.1         |               |         |         |         |         |         |         |         |         | 2.2        | 5.0          | 5.5                                     |
| (E) 080-100         |          | .5          |               |         |         |         |         |         |         |         |         | .5         | 7.0          | 7.0                                     |
| 110-130             |          |             |               |         |         |         |         |         |         |         |         |            |              |   |
| 140-160             |          |             |               |         |         |         |         |         |         |         |         |            |              |   |
| (S) 170-190         | 2.7      |             |               |         |         |         |         |         |         |         |         | 2.7        | 2.0          | 2.0                                     |
| 200-220             | 6.5      | 1.1         |               |         |         |         |         |         |         |         |         | 7.5        | 2.9          | 2.5                                     |
| 230-250             |          |             |               |         |         |         |         |         |         |         |         |            |              |   |
| (W) 260-280         |          |             |               |         |         |         |         |         |         |         |         |            |              |   |
| 290-310             |          |             |               |         |         |         |         |         |         |         |         |            |              |   |
| 320-340             | 4.3      |             |               |         |         |         |         |         |         |         |         | 4.3        | 3.0          | 3.5                                     |
| VARIABLE            | !<br>    | • • • • • • |               |         |         |         |         |         |         |         |         |            | •••••        |   |
| CALM                | //////// | /////       | //////        | /////// | /////// | 1111111 | 1111111 | 1111111 | /////// | 1111111 | '////// | 57.0       | //////       | /////                                   |
| TOTALS              | 33.5     | 9.7         |               |         |         |         |         |         |         |         |         | 100.0      | 1.3          | 2.5                                     |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 HOURS: 06-08 LST TO UTC: - 9 MONTH: MAR

| •••••               | • • • • • • • • • • | • • • • • | • • • • • • | • • • • • •   | WIND S      | SPEED IN | KNOTS       | • • • • • • • | • • • • • • |         | • • • • • • • | • • • • • • |              | • • • • • •    |
|---------------------|---------------------|-----------|-------------|---------------|-------------|----------|-------------|---------------|-------------|---------|---------------|-------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4                 | 5-9       | 10-14       | 15-19         |             | 25-29    |             | 35-39         | 40-49       | 50-64   | G⊡ 65         | TOTAL<br>%  | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 15.6                | 5.4       | 5           | • • • • • • • | • • • • • • |          |             | •••••         |             |         |               | 21.5        | 3.3          | 2.0            |
| 020-040             | 3.8                 | 1.1       |             |               |             |          |             |               |             |         |               | 4.8         | 3.7          | 4.0            |
| 050-070             | 1.6                 |           |             |               |             |          |             |               |             |         |               | 1.6         | 1.3          | 1.0            |
| (E) 080-100         |                     |           |             |               |             |          |             |               |             |         |               |             |              |                |
| 110-130             |                     |           |             |               |             |          |             |               |             |         |               |             |              |                |
| 140-160             |                     |           |             |               |             |          |             |               |             |         |               |             |              |                |
| (S) 170-190         | 4.8                 | 1.1       |             |               |             |          |             |               |             |         |               | 5.9         | 2.7          | 2.0            |
| 200-220             | 8.1                 | .5        |             |               |             |          |             |               |             |         |               | 8.6         | 2.5          | 2.0            |
| 230-250             | 3.2                 |           |             |               |             |          |             | •             |             |         |               | 3.2         | 3.3          | 4.0            |
| (W) 260-280         |                     |           |             |               |             |          |             |               |             |         |               |             |              |                |
| 290-310             |                     |           |             |               |             |          |             |               |             |         |               |             |              |                |
| 320-340             | 5.9                 |           |             |               |             |          |             |               |             |         |               | 5.9         | 2.0          | 2.0            |
| VARIABLE            |                     | • • • • • |             |               | • • • • • • |          | • • • • • • | • • • • • •   | • • • • • • |         |               | • • • • • • | • • • • • •  |                |
| VARIABLE            |                     |           |             |               |             |          |             |               |             |         |               |             |              |                |
| CALM                | ////////            | /////     | 1111111     | ///////       | //////      | ///////  | //////      | '//////       | //////      | '////// | ///////       | 48.4        | /////        | /////          |
| TOTALS              | 43.0                | 8.1       | .5          |               |             |          |             |               |             |         |               | 100.0       | 1.5          | 2.0            |
|                     |                     |           | TO          | TAL NUM       | BER OF      | OBSERVA  | TIONS       | 186           |             |         |               |             |              |                |

C - 4 - 23

## PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAR HOURS: 09-11

| • | • • • • • • • • |        |         | • • • • • • | WIND S      | SPEED IN      | KNOTS       | •••••         | • • • • • • | •••••  |          | • • • • • • | • • • • • •  | • • • • • • •  |
|---|-----------------|--------|---------|-------------|-------------|---------------|-------------|---------------|-------------|--------|----------|-------------|--------------|----------------|
| DIRECTION (DEGREES)                     | 1-4             | 5-9    | 10-14   | 15-19       |             | 25-29         |             | 35-39         | 40-49       | 50-54  | GE 65    | TOTAL<br>%  | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 11.3            | 10.5   | .8      | •••••       | • • • • • • | • • • • • • • | •••••       | • • • • • • • | •••••       | •••••  |          | 22.6        | 4.7          | 4.5            |
| 020-040                                 | 2.4             | 3.2    |         |             |             |               |             |               |             |        |          | 5.6         | 5.1          | 5.0            |
| 050-070                                 |                 |        |         |             |             |               |             |               |             |        |          |             |              |                |
| (E) 080-100                             |                 |        |         |             |             |               |             |               |             |        |          |             |              |                |
| 110-130                                 |                 |        |         |             |             |               |             |               |             |        |          |             |              |                |
| 140-160                                 | 1.6             |        |         |             |             |               |             |               |             |        |          | 1.6         | 3.0          | 3.0            |
| (S) 170-190                             | 11.3            | 3.2    |         |             |             |               |             |               |             |        |          | 14.5        | 3.6          | 4.0            |
| 200-220                                 | 24.2            | 8.1    |         |             |             |               |             |               |             |        |          | 32.3        | 3.9          | 4.0            |
| 230-250                                 |                 | 1.6    |         |             |             |               |             |               |             |        |          | 1.6         | 5.5          | 5.5            |
| (W) 260-280                             | .8              |        |         |             |             |               |             |               |             |        |          | .8          | 1.0          | 1.0            |
| 290-310                                 | 2.4             | .8     |         |             |             |               |             |               |             |        |          | 3.2         | 3.5          | 3.5            |
| 320-340                                 | 3.2             | .8     |         |             |             |               |             |               |             |        |          | 4.0         | 3.6          | 3.0            |
|   |                 |        |         | ••••        |             |               | . <b></b> . |               | . <b></b> . |        |          |             |              |                |
| VARIABLE                                |                 |        |         |             |             | •             |             |               |             |        |          |             |              |                |
| CALM                                    | 1111111         | ////// | 1111111 | ///////     | //////      | ///////       | ///////     | ///////       | ///////     | ////// | //////// | 13.7        | /////        | //////         |
| TOTALS                                  | 57.2            | 28.2   | .8      |             |             |               |             |               |             |        |          | 100.0       | 3.5          | 4.0            |
|   |                 |        | TV.     | אווא זגייע  | משם         | OBSERVA       | PKONS       | 124           |             |        |          |             |              |                |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: MAR HOURS: 12-14

LST TO UTC: - 9

| •••••               | • • • • • • •                              | • • • • • • | ••••• | • • • • • • • | WIND S        | SPEED IN          | KNOTS   | • • • • • • • | •••••                                   | • • • • • • • | ••••• | • • • • • • • | • • • • • •  | • • • • • •    |
|---------------------|--|-------------|-------|---------------|---------------|-------------------|---------|---------------|---|---------------|-------|---------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4  | 5-9         | 10-14 | 15-19         | 20-24         | 25-29             | 30-34   | 35-39         | 40-49                                   | 50-64         | GE 65 | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 6.5  | 7.5         | ••••• | • • • • • • • | • • • • • • • |                   |         | •••••         | •••••                                   | • • • • • •   | ••••• | 14.0          | 4.8          | 5.0            |
| 020-040             | 3.8  | 2.7         |       |               |               |                   |         |               |   |               |       | 6.5           | 4.1          | 3.5            |
| 050-070             | 1.1  | 1.1         | .5    |               |               |                   |         |               |   |               |       | 2.7           | 6.4          | 8.0            |
| (E) 080-100         | .5   | 3.2         |       |               |               |                   |         |               |   |               |       | 3.8           | 6.0          | 6.0            |
| 110-130             | 1.1  |             |       |               |               |                   |         |               |   |               |       | 1.1           | 3.0          | 3.0            |
| 140-160             | 3.2  | .5          |       |               |               |                   |         |               |   |               |       | 3.8           | 3.9          | 4.0            |
| (S) 170-190         | 8.1  | 1.6         |       |               |               |                   |         |               |   |               |       | 9.7           | 3.8          | 4.0            |
| 200-220             | 12.9                                       | 12.9        | .5    |               |               |                   |         |               |   |               |       | 26.3          | 4.7          | 5.0            |
| 230-250             | 5.9  | 3.2         |       |               |               |                   |         |               |   |               |       | 9.1           | 3.9          | 4.0            |
| (W) 260-280         | 2.2  |             |       |               |               |                   |         |               |   |               |       | 2.2           | 2.5          | 2.5            |
| 290-310             | 3.2  | 3.2         | .5    |               |               |                   |         |               |   |               |       | 7.0           | 5.2          | 6.0            |
| 320-340             | 3.2  | 3.2         |       |               |               |                   |         |               |   |               |       | 6.5           | 4.3          | 4.5            |
| VARIABLE            | !<br>• • • • • • • • • • • • • • • • • • • | 1.1         | 1.1   |               | • • • • • •   | · · · · · · · · · |         |               | • |               |       | 2.2           | 9.8          | 9.5            |
| CAIM                | 11111111                                   |             |       | //////        | //////        | ////////          | 1111111 | 1111111       | ///////                                 | 1111111       |       |               | /////        |                |
| TOTALS              | 51.7                                       | 40.2        | 2.6   |               |               |                   |         |               |   |               |       | 100.0         | 4.4          | 4.0            |

CALM TOTALS

38.7 44.1

9.7

.5

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAR HOURS: 15-17 WIND SPEED IN KNOTS 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN DIRECTION (DEGREES) WIND WIND 8 (N) 350-010 2.7 6.5 2.2 6.3 6.0 020-040 3.2 1.1 4.3 3.8 3.5 050-070 1.1 . 5 1.6 3.2 6.7 7.0 (E) 080-100 1.6 .5 2.2 3.5 2.5 110-130 1.1 1.1 7.0 7.0 140-160 (S) 170-190 3.2 3.2 6.5 4.4 4.5 200-220 6.5 10.2 3.8 . 5 21.0 6.7 7.0 230-250 3.8 5.9 . 5 10.2 5.4 6.0 (W) 260-280 4.3 3.2 7.5 3.8 3.5 290-310 4.8 3.8 .5 9.1 4.4 4.0 320-340 7.5 5.4 1.1 14.0 4.7 4.0 VARIABLE 1.6 1.1 2.7 9.2 9.0

TOTAL NUMBER OF OBSERVATIONS 186

100.0 5.1 6.0

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAR HOURS: 18-20

WIND SPEED IN KNOTS 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN DIRECTION 1-4 (DEGREES) \* WIND WIND ...... (N) 350-010 3.8 4.3 .5 8.6 5.0 5.0 020-040 1.6 3.2 4.7 5.0 050-070 1.6 1.1 2.7 4.6 4.0 (E) 080-100 1.1 1.1 .5 5.2 2.7 5.0 110-130 1.6 1.6 2.0 2.0 140-160 .5 1.1 5.0 5.0 (S) 170-190 2.7 . 5 .5 3.8 3.9 2.0 200-220 14.0 7.5 1.1 22.6 4.5 4.0 230-250 8.6 5.4 3.9 4.0 (W) 260-280 5.9 .5 2.9 2.0 6.5 290-310 5.9 .5 2.8 2.0 6.5 320-340 2.2 4.8 .5 5.8 6.0 VARIABLE 8.0 CALM TOTALS 49.5 28.9 3.1 100.0 3.5 4.0

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: MAR HOURS: 21-23

|                     |          |             |             |         |             |               |               |         |               |       | •             |               |              |                |
|---------------------|----------|-------------|-------------|---------|-------------|---------------|---------------|---------|---------------|-------|---------------|---------------|--------------|----------------|
|                     |          | • • • • • • |             |         |             | SPEED IN      |               | •••••   | •••••         | ••••• |               | • • • • • • • |              | •••••          |
| DIRECTION (DEGREES) | 1-4      | 5-9         | 10-14       | 15-19   | 20-24       | 25-29         | 30-34         | 35-39   | 40-49         | 50-64 | GE 65         | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 4.8      | 5.4         |             |         |             | · • • • • • • | • • • • • • • |         | • • • • • • • |       | • • • • • • • | 10.2          | 4.3          | 5.0            |
| 020-040             | 11.8     | 2.2         |             |         |             |               |               |         |               |       |               | 14.0          | 2.7          | 2.0            |
| 050-070             | 1.1      | 5           |             |         |             |               |               |         |               |       |               | 1.6           | 2.7          | 2.0            |
| (E) 080-100         | 1.1      |             |             |         |             |               |               |         |               |       |               | 1.1           | 1.0          | 1.0            |
| 110-130             | 1.1      |             |             |         |             |               |               |         |               |       |               | 1.1           | 2.0          | 2.0            |
| 140-160             | .5       |             |             |         |             |               |               |         |               |       |               | .5            | 4.0          | 4.0            |
| (S) 170-190         | .5       | .5          |             |         |             |               |               |         |               |       |               | 1.1           | 4.0          | 4.0            |
| 200-220             | 3.2      | 1.6         | 1.1         |         |             |               |               |         |               |       |               | 5.9           | 5.2          | 4.0            |
| 230-250             | 2.7      | .5          |             |         |             |               |               |         |               |       |               | 3.2           | 3.2          | 3.5            |
| (W) 260-280         | .5       |             |             |         |             |               |               |         |               |       |               | .5            | 2.0          | 2.0            |
| 290-310             | .5       |             |             |         |             |               |               |         |               |       |               | .5            | 1.0          | 1.0            |
| 320-340             | 3.8      | 2.2         | - 5         |         |             |               |               |         |               |       |               | 6.5           | 5.1          | 3.0            |
| VARIABLE            | <u>:</u> |             | • • • • • • |         | • • • • • • |               |               |         |               |       |               | 5             | 7.0          | 7.0            |
| CALM                | 11111111 |             | 1111111     | 1111111 | ///////     | ////////      | 1111111       | 1111111 | 1111111       |       | '//////       |               |              | 111111         |
| TOTALS              | 31.6     | 13.4        | 1.6         |         |             |               |               |         |               |       |               | 100.0         | 1.7          | 3.0            |
|                     |          |             |             |         |             |               |               |         |               |       |               |               |              |                |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: MAR HOURS: ALL

|             | • • • • • • • • |        | • • • • • • |         |        | SPEED IN |             | • • • • • • | •••••         | • • • • • • | · • • • • • • • | • • • • • • • • | · · · · · · · | • • • • • • • |
|-------------|-----------------|--------|-------------|---------|--------|----------|-------------|-------------|---------------|-------------|-----------------|-----------------|---------------|---------------|
| DIRECTION   | 1-4             | 5-9    | 10-14       | 15-19   |        | 25-29    |             | 35-39       | 40-49         | 50-64       | GE 65           | TOTAL           | MEAN          | MEDIAN        |
| (DEGREES)   |                 |        |             |         |        |          | • • • • • • |             | • • • • • • • |             |                 | *               | WIND          | MIND          |
| (N) 350-010 | 9.0             | 6.2    | .5          |         |        | •••••    | •••••       |             | •••••         |             |                 | 15.6            | 4.1           | 4.0           |
| 020-040     | 5.1             | 1.7    |             |         |        |          |             |             |               |             |                 | 6.8             | 3.2           | 2.0           |
| 050-070     | 1.3             | .7     | .1          |         |        |          |             |             |               |             |                 | 2.2             | 4.5           | 4.0           |
| (E) 080-100 | .6              | .7     | .1          |         |        |          |             |             |               |             |                 | 1.3             | 4.8           | 5.0           |
| 110~130     | .6              | . 1    |             |         |        |          |             |             |               |             |                 | .7              | 3.1           | 2.5           |
| 140-160     | .7              | .2     |             |         |        |          |             |             |               |             |                 | .9              | 4.0           | 4.0           |
| (S) 170-190 | 4.3             | 1.3    | .1          |         |        |          |             |             |               |             |                 | 5.6             | 3.5           | 3.5           |
| 200-220     | 9.0             | 5.5    | .8          | .1      |        |          |             |             |               |             |                 | 15.4            | 4.6           | 4.0           |
| 230-250     | 3.5             | 2.2    | .1          |         |        |          |             |             |               |             |                 | 5.8             | 4.1           | 4.0           |
| (W) 260-280 | 1.8             | .5     |             |         |        |          |             |             |               |             |                 | 2.3             | 3.1           | 2.0           |
| 290-310     | 2.2             | 1.1    | .1          |         |        |          |             |             |               |             |                 | 3.4             | 4.1           | 3.0           |
| 320-340     | 4.5             | 2.1    | .3          |         |        |          |             |             |               |             |                 | 6.9             | 4.1           | 4.0           |
| vantan: c   |                 |        |             |         |        |          |             |             |               |             |                 |                 |               |               |
| VARIABLE    |                 | .5     | .3          |         |        |          |             |             |               |             |                 | .8              | 9.1           | 9.0           |
| CALM        | 1//////         | ////// | //////      | /////// | ////// | (/////// | ///////     | (//////     | '//////       | ///////     | ///////         | 32.3            | //////        | 111111        |
| TOTALS      | 42.6            | 22.8   | 2.4         | .1      |        |          |             |             |               |             |                 | 100.0           | 2.8           | 4.0           |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: MAR HOURS: ALL

LST TO UTC: - 9

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS). AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

|                        |          |         |         |         | WIND S  | PEED IN | KNOTS   |         |         |         |      |         |       |            |         |
|------------------------|----------|---------|---------|---------|---------|---------|---------|---------|---------|---------|------|---------|-------|------------|---------|
| DIRECTION              | 1 - 4    | 5-9     | 10-14   | 15-19   | 20-24   | 25-29   | 30-34   | 35-39   | 40-49   | 50-64   | GE   | 65      | TOTAL | MEAN       | MEDIAN  |
| (DEGREES)              |          |         |         | •••••   |         |         |         |         |         |         |      | • • • • | *     | MIND       | WIND    |
| (N) 350-010            | 3.7      | 1.9     | ,6      | •••••   |         |         |         |         | •••••   |         |      | • • • • | 6.2   | 4.7        | 4.0     |
| 020-040                | 1.2      | 1.2     |         |         |         |         |         |         |         |         |      |         | າ.5   | 3.8        | 4.0     |
| 050-070                | .6       | 1.2     |         |         |         |         |         |         |         |         |      |         | 1.9   | 5.7        | 7.0     |
| (E) 080-100            |          | .6      |         |         |         |         |         |         |         |         |      |         | .6    | 7.0        | 7.0     |
| 110-130                |          |         |         |         |         |         |         |         |         |         |      |         |       |            |         |
| 140-160                | .6       |         |         |         |         |         |         |         |         |         |      |         | .6    | 3.0        | 3.0     |
| (S) 170-190            | 6.2      | 1.2     |         |         |         |         |         |         |         |         |      |         | 7.4   | 3.5        | 3.5     |
| 200-220                | 20.4     | 3.7     |         |         |         |         |         |         |         |         |      |         | 24.1  | 3.3        | 3.0     |
| 230-250                | 5.6      | 1.9     |         |         |         |         |         |         |         |         |      |         | 7.4   | 3.4<br>2.0 | 4.0     |
| (W) 260-280<br>290-310 | .6       | 1.2     |         |         |         |         |         |         |         |         |      |         | 1.9   | 5.0        | 5.0     |
| 320-340                | 3.7      | 1.2     |         |         |         |         |         |         |         |         |      |         | 4.9   | 4.3        | 1.5     |
|                        |          |         |         |         |         |         |         |         |         |         |      |         |       |            |         |
| VARIABLE               |          | •       |         |         |         |         |         |         |         |         |      |         |       |            |         |
| CALM                   | 11111111 | (111111 | 1111111 | /////// | 7////// | 1////// | 7777777 | 11/1/// | 11///// | 1////// | //// | ////    | 42.0  | //////     | 11/1/// |
| TOTALS                 | 43.2     | 14.1    | . 6     |         |         |         |         |         |         |         |      |         | 100.0 | 2.2        | ٠.0     |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: APR HOURS: 00-02

|                     | • • • • • • •        |         | • • • • • • | • • • • • • • | WIND S | PEED IN | KNOTS   | • • • • • •   |               |               |         | • • • • • • •   | • • • • • •  |                |
|---------------------|----------------------|---------|-------------|---------------|--------|---------|---------|---------------|---------------|---------------|---------|-----------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4                  | 5-9     | 10-14       | 15-19         | 20-24  | 25-29   | 30-34   | 35-39         | 40-49         | 50- <b>~4</b> | GE 65   | TOTAL<br>%      | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 10.6                 | 1.2     | 1.2         | • • • • • • • | •••••  | •••••   |         | • • • • • • • | • • • • • • • |               |         | 12.9            | 3.4          | 2.0            |
| 020-040             | 5.9                  |         |             |               |        |         |         |               |               |               |         | 5.9             | 2.3          | 2.0            |
| 050~070             | 2.9                  |         |             |               |        |         |         |               |               |               |         | 2.9             | 1.4          | 1.0            |
| (E) 080-100         | .6                   |         |             |               |        |         |         |               |               |               |         | .6              | 3.0          | 3.0            |
| 110-130             | .6                   |         |             |               |        |         |         |               |               |               |         | .6              | 3.0          | 3.0            |
| 140-160             | .6                   | .6      |             |               |        |         |         |               |               |               |         | 1.2             | 3.5          | 3.5            |
| (S) 170-190         | 4.1                  |         |             |               |        |         |         |               |               |               |         | 4.1             | 2.3          | 2.0            |
| 200-220             | 1.2                  | .6      | .6          |               |        |         |         |               |               |               |         | 2.4             | 5.8          | 5.0            |
| 230-250             | .6                   |         |             |               |        |         |         |               |               |               |         | .6              | 4.0          | 4.0            |
| (W) 260-280         |                      |         |             |               |        |         |         |               |               |               |         |                 |              |                |
| 290-310             | .6                   |         |             |               |        |         |         |               |               |               |         | .6              | 2.0          | 2.0            |
| 320-340             | 3.5                  |         |             |               |        |         |         |               |               |               |         | 3.5             | 2.7          | 2.5            |
|                     | !<br>; · · · · · · · |         |             |               |        |         |         |               |               |               |         | • • • • • • • • |              |                |
| VARIABLE            | Í                    | 1.2     |             |               |        |         |         |               |               |               |         | 1.2             | 8.5          | 8.5            |
| CALM                | 11111111             | /////// | ///////     | ///////       | ////// | /////// | /////// | ////////      | ///////       | 1/////        | /////// | 63.5            | /////        | /////          |
| TOTALS              | 31.2                 | 3.6     | 1.8         |               |        |         |         |               |               |               |         | 100.0           | 1.2          | 2.0            |

## PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: APR HOURS: 03-05

| ************        |          | • • • • • • |               | •••••   | WIND S        | SPEED IN | KNOTS  | •••••   | • • • • • •   | • • • • • • | • • • • • • • | •••••       |              | •••••          |
|---------------------|----------|-------------|---------------|---------|---------------|----------|--------|---------|---------------|-------------|---------------|-------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4      | 5-9         | 10-14         | 15-19   | 20-24         | 25-29    | 30-34  | 35-39   | 40-49         | 50-64       | GE 65         | TOTAL<br>%  | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 16.4     | 1.8         | • • • • • • • | •••••   | • • • • • • • |          |        | •••••   | • • • • • • • |             |               | 18.1        | 2.7          | 2.0            |
| 020-040             | 3.5      | .6          |               |         |               |          |        |         |               |             |               | 4.1         | 2.3          | 2.0            |
| 050-070             | 2.9      |             |               |         |               |          |        |         |               |             |               | 2.9         | 1.4          | 1.0            |
| (E) 080-100         |          |             |               |         |               |          |        |         |               |             |               |             |              |                |
| 110-130             | <u> </u> |             |               |         |               |          |        |         |               |             |               |             |              |                |
| 140-160             | .6       |             |               |         |               |          |        |         |               |             |               | .6          | 4.0          | 4.0            |
| (S) 170-190         | 4.1      | 1.2         | .6            |         |               |          |        |         |               |             |               | 5.8         | 3.8          | 3.0            |
| 200-220             | 3.5      | .6          |               |         |               |          |        |         |               |             |               | 4.1         | 4.0          | 4.0            |
| 230-250             |          | 1.8         |               |         |               |          |        |         |               |             |               | 1.8         | 6.3          | 6.0            |
| (W) 260-280         |          |             |               |         |               |          |        |         |               |             |               |             |              |                |
| 290-310             |          |             |               |         |               |          |        |         |               |             |               |             |              |                |
| 320-340             | 4.1      |             |               |         |               | •        |        |         |               |             |               | 4.1         | 2.4          | 2.0            |
| VARIABLE            | :<br>    |             |               |         | • • • • • •   |          |        | •••••   |               | ••••        |               | • • • • • • |              | • • • • • • •  |
| CALM                | //////// | //////      | ///////       | /////// | //////        | ///////  | ////// | /////// | ///////       | //////      | ////////      | 58.5        | /////        | //////         |
| TOTALS              | 35.1     | 6.0         | .6            |         |               |          |        |         |               |             |               | 100.0       | 1.3          | 2.0            |
|                     |          |             | TC            | TAL NUM | BER OF        | OBSERVA  | TIONS  | 171     |               |             |               |             |              |                |

.......

STATION NUMBER: 471066

320-340

VARIABLE

CALM TOTALS

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: APR HOURS: 06-08 LST TO UTC: - 9 WIND SPEED IN KNOTS DIRECTION 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) 8 WIND WIND ...... (N) 350-010 9.5 3.6 .6 13.6 3.5 3.0 020-040 4.7 4.7 2.1 2.0 050-070 1.8 1.8 1.3 1.0 (E) 080-100 .6 .6 4.0 4.0 110-130 1.8 1.7 2.0 1.8 140-160 1.2 1.2 1.5 1.5 (S) 170-190 4.1 3.0 7.1 4.5 4.0 200-220 1.2 1.8 9.5 5.3 4.0 230-250 .6 .6 1.0 1.0 (W) 260-280 2.0 .6 .6 2.0 290-310 .6 .6 1.2 3.5 10.7

STATION NAME: CAMP CASEY/TONGDUCHON KO

TOTAL NUMBER OF OBSERVATIONS 169

.6

2.4

1.2

9.6

42.1

////////// 45.6 /////////

11.8

3.0

100.0 1.9 3.0

3.0

## PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: APR HOURS: 09-11

| • | • • • • • • • • |        | • • • • • • | • • • • • • | WIND S  | PEED IN | KNOTS  | •••••   | • • • • • • • | • • • • • •   | • • • • • • • |            | •••••        |                |
|---|-----------------|--------|-------------|-------------|---------|---------|--------|---------|---------------|---------------|---------------|------------|--------------|----------------|
| DIRECTION (DEGREES)                     | 1-4             | 5-9    | 10-14       | 15~19       | 20-24   | 25-29   | 30-34  | 35-39   | 40-49         | 50-64         | GE 65         | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 3.6             | 7.1    | .9          | • • • • • • |         |         |        |         |               | • • • • • • • |               | 11.6       | 5.7          | 6.0            |
| 020-040                                 | .9              | 2.7    |             |             |         |         |        |         |               |               |               | 3.6        | 5.3          | 5.0            |
| 050-070                                 | .9              | .9     |             |             |         |         |        |         |               |               |               | 1.8        | 4.5          | 4.5            |
| (E) 080-100                             |                 |        |             |             |         |         |        |         |               |               |               |            |              |                |
| i10-130                                 |                 |        |             |             |         |         |        |         |               |               |               |            |              |                |
| 140-160                                 |                 | .9     |             |             |         |         |        |         |               |               |               | .9         | 8.0          | 8.0            |
| (S) 170-190                             | 8.0             | 2.7    | .9          |             |         |         |        |         |               |               |               | 11.6       | 4.3          | 4.0            |
| 200-220                                 | 14.3            | 8.0    | 1.8         |             |         |         |        |         |               |               |               | 24.1       | 4.4          | 4.0            |
| 230-250                                 | 1.8             | 3.6    |             |             |         |         |        |         |               |               |               | 5.4        | 4.8          | 6.0            |
| (W) 260-280                             |                 | .9     |             |             |         |         |        |         |               |               |               | .9         | 8.0          | 8.0            |
| 290-310                                 | 1.8             | 3.6    |             |             |         |         |        |         |               |               |               | 5.4        | 6.0          | 7.0            |
| 320-340                                 | 3.5             |        |             |             |         |         |        |         |               |               |               | 3.6        | 2.5          | 2.5            |
| VARIABLE                                | :<br>           | 1.8    | 1.8         |             |         | •••••   |        |         | • • • • • •   |               |               | 3.6        | 10.5         | 10.0           |
| CALM                                    | 11111111        | ////// | //////      | //////      | /////// | 11/1/1/ | ////// | /////// | ///////       | //////        | ///////       | 27.7       | //////       | /////          |
| TOTALS                                  | 34.9            | 32.2   | 5.4         |             |         |         |        |         |               |               |               | 100.0      | 3.7          | 5.0            |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

MONTH: APR HOURS: 12-14

|                     | • • • • • • • • |         | • • • • • • |        | WIND S | SPEED IN      | KNOTS       | • • • • • • •                           | • • • • • • |             | •••••  | • • • • • • • | • • • • • •  | • • • • • •    |
|---------------------|-----------------|---------|-------------|--------|--------|---------------|-------------|---|-------------|-------------|--------|---------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4             | 5-9     | 10-14       | 15-19  | 20-24  | 25-29         | 30-34       | 35-39                                   | 40-49       | 50-64       | GE 65  | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 4.2             | 5.5     | 3.6         |        |        | • • • • • • • |             | •••••                                   | • • • • • • | • • • • • • | •••••  | 13.3          | 7.0          | 6.5            |
| 020-040             | 1.2             | 2.4     |             |        |        |               |             |   |             |             |        | 3.6           | 4.8          | 5.5            |
| 050-070             | 1.8             |         |             |        |        |               |             |   |             |             |        | 1.8           | 3.7          | 4.0            |
| (E) 080-100         |                 |         |             |        |        |               |             |   |             |             |        |               |              |                |
| 110-130             | .6              |         |             |        |        |               |             |   |             |             |        | .6            | 4.0          | 4.0            |
| 140-160             | 1.2             |         |             |        |        |               |             |   |             |             |        | 1.2           | 2.5          | 2.5            |
| (S) 170-190         | 6.7             | 3.0     | 1.2         |        |        |               |             |   |             |             |        | 10.9          | 4.9          | 4.0            |
| 200-220             | 10.9            | 9.7     | 5.5         | .6     |        |               |             |   |             |             |        | 26.7          | 6.3          | 5.0            |
| 230-250             | 3.6             | 4.2     | 1.8         | .6     |        |               |             |   |             |             |        | 10.3          | 6.4          | 5.0            |
| (W) 260-280         | 2.4             | .6      | .6          |        |        |               |             |   |             |             |        | 3.6           | 4.8          | 3.5            |
| 290-310             | 3.6             | 1.8     | 1.2         |        |        |               |             |   |             |             |        | 6.7           | 5.6          | 4.^            |
| 320+340             | 3.6             | 3.0     |             |        |        |               |             |   |             |             |        | 6.7           | 4.4          | 4.0            |
| VARIABLE            | :<br>           | 1.2     | 1.8         | 1.2    |        | • • • • • • • | • • • • • • | • |             |             | •••••  | 4.2           | 12.1         | 13.0           |
| CALM                | (1111111        | (1/1/// | //////      | ////// | ////// | 1111111       | //////      | (//////                                 | //////      | //////      | ////// | 10.3          | /////        | /////          |
| TOTALS              | 39.8            | 31.4    | 15.7        | 2.4    |        |               |             |   |             |             |        | 100.0         | 5.4          | 5.0            |

TOTAL NUMBER OF OBSERVATIONS 165 ......

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: APR HOURS: 15-17

|                     | • • • • • • • • • | • • • • • • |       |               | WIND S      | PEED IN | KNOTS   |   | • • • • • • | •••••         | •••• | • • • • |            | •••••        |                |
|---------------------|-------------------|-------------|-------|---------------|-------------|---------|---------|---|-------------|---------------|------|---------|------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4               | 5-9         | 10-14 | 15-19         | 20-24       | 25-29   | 30-34   | 35-39                                   | 40-49       | 50-64         | GE   | 65      | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 1.2               | 4.2         | .6    | •••••         | • • • • • • | •••••   |         | •••••                                   | • • • • • • | •••••         |      | • • • • | 6.1        | 6.2          | 6.0            |
| 020-040             | 1.8               | 3.0         | 1.2   |               |             |         |         |   |             |               |      |         | 6.1        | 5.9          | 5.0            |
| 050-070             |                   | 1.2         |       |               |             |         |         |   |             |               |      |         | 1.2        | 6.5          | 6.5            |
| (E) 080-100         |                   |             |       |               |             |         |         |   |             |               |      |         |            |              |                |
| 110-130             |                   |             |       |               |             |         |         |   |             |               |      |         |            |              |                |
| 140-160             | 1.2               |             |       |               |             |         |         |   |             |               |      |         | 1.2        | 2.5          | 2.5            |
| (S) 170-190         | 3.0               | 3.0         |       |               |             |         |         |   |             |               |      |         | 6.1        | 5.4          | 5.0            |
| 200-220             | 5.5               | 9.7         | 7.3   | .6            |             |         |         |   |             |               |      |         | 23.0       | 7.5          | 6.5            |
| 230-250             | 10.3              | 4.8         | .6    |               |             |         |         |   |             |               |      |         | 15.8       | 3.9          | 3.5            |
| (W) 260-280         | 6.1               | 3.0         |       |               |             |         |         |   |             |               |      |         | 9.1        | 3.9          | 4.0            |
| 290-310             | 3.6               | 3.6         |       |               |             |         |         |   |             |               |      |         | 7.3        | 4.9          | 4.5            |
| 320-340             | 3.6               | 6.1         | 1.2   | .6            |             |         |         |   |             |               |      |         | 11.5       | 5,9          | 6.0            |
| VARIABLE            | ,<br>             | 1.2         | 5.5   | • • • • • • • |             |         |         | • |             | • • • • • • • |      |         | 6.7        | 11,1         | 10.0           |
| CALM                | ////////          |             |       | ///////       | ///////     | 1111111 | /////// | ·///////                                | ///////     | 1111111       | 1111 | ////    |            |              |                |
|                     |                   |             |       |               | ,,,,,,      | ,,,,,,, | ,,,,    | ,,,,,,,                                 | , , , , ,   | ,,,,          | ,    | ,       |            |              |                |
| TOTALS              | 36.3              | 39.8        | 16.4  | 1.2           |             |         |         |   |             |               |      |         | 100.0      | 5.7          | 5.0            |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: APR HOURS: 18-20

|                        |         | LS          | T TO UT | C: - 9        |               |          |        |             | MONTH   | : APR       | HOUR    | S: 18-20      | ,            |                |
|------------------------|---------|-------------|---------|---------------|---------------|----------|--------|-------------|---------|-------------|---------|---------------|--------------|----------------|
|                        |         | • • • • • • |         | • • • • • • • | WIND S        | SPEED IN | KNOTS  | •••••       | •••••   | • • • • • • | •••••   | • • • • • • • | • • • • • •  | • • • • • • •  |
| DIRECTION<br>(DEGREES) | 1-4     | 5-9         | 10-14   | 15-19         | 20-24         | 25-29    | 30-34  | 35-39       | 40-49   | 50-64       | GE 65   | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010            | 3.6     | 1.8         | 1.2     | • • • • • •   | • • • • • • • |          | •••••  |             | •••••   |             | •••••   | 6.7           | 4.6          | 4.0            |
| 020-040                | 2.4     | 1.8         |         |               |               |          |        |             |         |             |         | 4.2           | 4.4          | 4.0            |
| 050~070                | 1.2     |             |         |               |               |          |        |             |         |             |         | 1.2           | 1.0          | 1.0            |
| (E) 080-100            |         | .6          |         |               |               |          |        |             |         |             |         | .6            | 6.0          | €.0            |
| 110-130                | .6      | .6          |         |               |               |          |        |             |         |             |         | 1.2           | 4.5          | 4.5            |
| 140-160                | .6      |             |         |               |               |          |        |             |         |             |         | .6            | 4.0          | 4.0            |
| (S) 170-190            | 1.8     | .6          |         |               |               |          |        |             |         |             |         | 2.4           | 3.5          | 3.5            |
| 200-220                | 14.5    | 10.3        | .6      | 1.8           |               |          |        |             |         |             |         | 27.3          | 5.4          | 4.0            |
| 230-250                | 7.3     | 7.9         |         |               |               |          |        |             |         |             |         | 15.2          | 4.8          | 5.0            |
| (W) 260-280            | 4.8     | .6          |         |               |               |          |        |             |         |             |         | 5.5           | 3.2          | 3.0            |
| 290-310                | 3.6     | 1.8         |         |               |               |          |        |             |         |             |         | 5.5           | 3.8          | 4.0            |
| 320-340                | 1.2     | 2.4         |         |               |               |          |        |             |         |             |         | 3.6           | 5.7          | 6.0            |
| VARIABLE               | .6      | 6           | 1.2     |               |               |          |        | • • • • • • | •••••   |             |         | 2.4           | 7.5          | 8.5            |
| CALM                   | /////// | //////      | /////// | 1111111       | //////        | ///////  | ////// | 11/1///     | /////// | ///////     | /////// | 23.6          | /////        | /////          |
| TOTALS                 | 42.2    | 29.0        | 3.0     | 1.8           |               |          |        |             |         |             |         | 100.0         | 3.7          | 4.0            |
|                        |         |             |         |               |               |          |        |             |         |             |         |               |              |                |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

| omitted worlds                          | 471000   | LS          | T TO UT       | C: - 9        | an chor | 117 101100 | ocnon i     |               | MONTH         | : APR  | HOUR          | S: 21-23   | 0011 3       |                |
|---|----------|-------------|---------------|---------------|---------|------------|-------------|---------------|---------------|--------|---------------|------------|--------------|----------------|
| • |          | • • • • • • | • • • • • • • | • • • • • •   | WIND S  | PEED IN    | KNOTS       | • • • • • • • | • • • • • • • |        | • • • • • • • |            | •••••        | •••••          |
| DIRECTION (DEGREES)                     | 1-4      | 5-9         | 10-14         | 15-19         | 20-24   | 25-29      | 30-34       | 35-39         | 40-49         | 50-64  | GE 65         | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 9.6      | 1.8         | .6            | •••••         | •••••   | •••••      |             | •••••         | •••••         |        | • • • • • • • | 12.0       | 3.1          | 2.0            |
| 020-040                                 | 8.4      | .6          |               |               |         |            |             |               |               |        |               | 9.0        | 2.7          | 2.0            |
| 050-070                                 | 3.6      |             |               |               |         |            |             |               |               |        |               | 3.6        | 1.8          | 2.0            |
| (E) 080-100                             | 1.8      |             |               |               |         |            |             |               |               |        |               | 1.8        | 2.0          | 2.0            |
| 110-130                                 | 1.2      |             |               |               |         |            |             |               |               |        |               | 1.2        | 1.5          | 1.5            |
| 140-160                                 |          |             |               |               |         |            |             |               |               |        |               |            |              |                |
| (S) 170-190                             | 1.8      |             |               |               |         |            |             |               |               |        |               | 1.8        | 2.7          | 2.0            |
| 200-220                                 | 7.2      | 3.0         | 1.2           |               | .6      |            |             |               |               |        |               | 12.0       | 5.2          | 3.5            |
| 230-250                                 | 1.2      |             |               |               |         |            |             |               |               |        |               | 1.2        | 2.5          | 2.5            |
| (W) 260-280                             | .6       |             |               |               |         |            |             |               |               |        |               | .6         | 2.0          | 2.0            |
| 290-310                                 |          |             |               |               |         |            |             |               |               |        |               |            |              |                |
| 320-340                                 | 3.6      | 2.4         |               |               |         |            |             |               |               |        |               | 6.0        | 4.4          | 4.0            |
| VARIABLE                                | .6       | 6           | 6             | • • • • • • • |         |            | • • • • • • | •••••         | • • • • • •   |        | • • • • • • • | 1.8        | 6.3          | 6.0            |
| CALM                                    | 11111111 | /////       | //////        | //////        | 1111111 | ///////    | //////      | ///////       | ///////       | ////// | 1111111       | 49.1       | /////        | /////          |
| TOTALS                                  | 39.6     | 8.4         | 2.4           |               | .6      |            |             |               |               |        |               | 100.0      | 1.8          | 2.0            |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

MONTH: APR HOURS: ALL

|                        |         |        |         | • • • • • • |        | SPEED IN          |        |               | •••••       |         |               | • • • • • • • |                   |            |
|------------------------|---------|--------|---------|-------------|--------|-------------------|--------|---------------|-------------|---------|---------------|---------------|-------------------|------------|
| DIRECTION              | 1-4     | 5-9    |         |             |        | 25-29             |        |               | 40-49       | 50-64   | GE 65         | TOTAL         | MEAN              | MEDIAN     |
| (DEGREES)              |         |        |         |             |        | · • • • • • • • • |        |               |             |         |               | 8             | WIND              | WIND       |
| (N) 350-010            | 7.6     | 3.2    | 1.1     |             |        |                   |        |               |             |         |               | 11.8          | 4.2               | 3.0        |
| 020-040                | 3.7     | 1.3    | .2      |             |        |                   |        |               |             |         |               | 5.2           | 3.5               | 3.0        |
| 050-070                | 1.9     | .2     |         |             |        |                   |        |               |             |         |               | 2.2           | 2.3               | 2.0        |
| (E) 080-100            | .4      | . 1    |         |             |        |                   |        |               |             |         |               | .5            | 3.2               | 2.5        |
| 110-130                | .6      | . 1    |         |             |        |                   |        |               |             |         |               | .7            | 2.7               | 2.0        |
| 140-160                | .7      | .2     |         |             |        |                   |        |               |             |         |               | .9            | 3.3               | 3.0        |
| (S) 170-190            | 4.0     | 1.6    | .3      |             |        |                   |        |               |             |         |               | 6.0           | 4.3               | 4.0        |
| 200-220                | 7.6     | 5.2    | 2.3     | .5          | .1     |                   |        |               |             |         |               | 15.7          | 5.8               | 5.0        |
| 230-250<br>(W) 260-280 | 3.2     | 2.7    | .1      | .1          |        |                   |        |               |             |         |               | 6.3<br>2.6    | <b>4.8</b><br>3.9 | 4.0<br>3.0 |
| 290-310                | 1.7     | 1.3    | .2      |             |        |                   |        |               |             |         |               | 3.2           | 4.9               | 4.0        |
| 320-340                | 4.3     | 1.9    | .2      | .1          |        |                   |        |               |             |         |               | 6.5           | 4.1               | 4.0        |
| VARIABLE               | .2      | 8      | 1.3     | 2           | •••••  |                   | •••••  | • • • • • • • | • • • • • • |         | • • • • • • • | 2.4           | 10.2              | 10.0       |
| CALM                   | /////// | ////// | /////// | //////      | 1///// | ///////           | ////// | 11/1///       | ///////     | /////// | 1111111       | 36.1          | /////             | /////      |
| TOTALS                 | 37.8    | 19.2   | 6.0     | .9          | .1     |                   |        |               |             |         |               | 100.0         | 3.0               | 4.0        |

TOTAL NUMBER OF OBSERVATIONS 1284

......

## PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

MONTH: APR HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

|             |         |        |               |         | WIND S | PEED IN | KNOTS  |             |        |        |        |       |               |   |
|-------------|---------|--------|---------------|---------|--------|---------|--------|-------------|--------|--------|--------|-------|---------------|---|
| DIRECTION   | 1-4     | 5-9    | 10-14         | 15-19   | 20-24  | 25-29   | 30-34  | 35-39       | 40-49  | 50-64  | GE 65  | TOTAL | MEAN          | MEDIAN                                  |
| (DEGREES)   | 1       |        |               |         |        |         |        |             |        |        |        | *     | WIND          | WIND                                    |
| (N) 350-010 | 6.2     | 1.0    |               |         |        |         |        | •••••       | •••••  |        |        | 7.2   | 2.9           | 2.0                                     |
| 020-040     | 4.1     | 2.1    |               |         |        |         |        |             |        |        |        | 6.2   | 3.0           | 2.5                                     |
| 050-070     | 3.1     |        |               |         |        |         |        |             |        |        |        | 3.1   | 1.7           | 1.0                                     |
| (E) 080-100 |         | 1.0    |               |         |        |         |        |             |        |        |        | 1.0   | 6.0           | 6.0                                     |
| 110-130     |         |        |               |         |        |         |        |             |        |        |        |       |               |   |
| 140-160     | 1.0     |        |               |         |        | •       |        |             |        |        |        | 1.0   | 1.0           | 1.0                                     |
| (S) 170-190 | 5.2     |        |               |         |        |         |        |             |        |        |        | 5.2   | 1.8           | 2.0                                     |
| 200-220     | 11.3    | 9.3    | 2.1           |         |        |         |        |             |        |        |        | 22.7  | 5.2           | 4.5                                     |
| 230-250     | 2.1     | 7.2    |               |         |        |         |        |             |        |        |        | 9.3   | 5.2           | 6.0                                     |
| (W) 260-280 |         | 1.0    |               |         |        |         |        |             |        |        |        | 1.0   | 6.0           | 6.0                                     |
| 290-310     | 2.1     | 1.0    |               |         |        |         |        |             |        |        |        | 3.1   | 5.3           | 4.0                                     |
| 320-340     | 6.2     |        |               |         |        |         |        |             |        |        |        | 6.2   | 2.0           | 2.0                                     |
| VARIABLE    | 1       |        | • • • • • • • |         |        |         |        | • • • • • • |        |        |        |       | · · · · · · · | • |
| ANKINDE     | j       |        |               |         |        |         |        |             |        |        |        |       |               |   |
| CALM        | /////// | ////// | ///////       | /////// | ////// | 1////// | ////// | ///////     | ////// | ////// | 1///// | 34.0  | //////        | /////                                   |
| TOTALS      | 41.3    | 22.6   | 2.1           |         |        |         |        |             |        |        |        | 100.0 | 2.6           | 3.5                                     |
|             |         |        |               |         |        |         |        |             |        |        |        |       |               |   |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: - 9

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: MAY HOURS: 00-02

| • |         |        | • • • • • • • |        |        |                   |        | • • • • • • • | • • • • • • • |               |                 | • • • • • • • |              |                |
|---|---------|--------|---------------|--------|--------|-------------------|--------|---------------|---------------|---------------|-----------------|---------------|--------------|----------------|
| DIRECTION (PEGREES)                     | 1-4     | 5-9    | 10-14         | 15-19  |        | SPEED IN<br>25-29 |        | 35-39         | 40-49         | 50~64         | GE 65           | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 14.4    | 5.0    |               |        |        | •••••             |        | • • • • • • • | •••••         | • • • • • • • | • • • • • • • • | 19.4          | 3.2          | 2.0            |
| 020-040                                 | 3.3     | 1.7    |               |        |        |                   |        |               |               |               |                 | 5.0           | 3.6          | 2.0            |
| 050-070                                 | 1.7     | .6     |               |        |        |                   |        |               |               |               |                 | 2.2           | 2.5          | 1.5            |
| (E) 080-100                             |         | .6     |               |        |        |                   |        |               |               |               |                 | .6            | 6.0          | 6.0            |
| 110-130                                 |         |        |               |        |        |                   |        |               |               |               |                 |               |              |                |
| 140-160                                 | .6      |        |               |        |        |                   |        |               |               |               |                 | .6            | 1.0          | 1.0            |
| (S) 170-190                             | 4.4     | .6     |               |        |        |                   |        |               |               |               |                 | 5.0           | 2.8          | 2.0            |
| 200-220                                 | 6.7     | 1.1    |               |        |        |                   |        |               |               |               |                 | 7.8           | 2.8          | 2.0            |
| 230-250                                 | 1.1     | 1.1    |               |        |        |                   |        |               |               |               |                 | 2.2           | 3.8          | 3.5            |
| (₩) 260-280                             | .6      | .6     |               |        |        |                   |        |               |               |               |                 | 1.1           | 3.5          | 3.5            |
| 290-310                                 | .6      |        |               |        |        |                   |        |               |               |               |                 | .6            | 2.0          | 2.0            |
| 320-340                                 | 1.1     |        | .6            |        |        |                   |        |               |               |               |                 | 1.7           | 5.3          | 2.0            |
|   | <br>    |        |               |        |        |                   |        |               |               |               |                 |               |              |                |
| VARIABLE                                |         | .6     |               |        |        |                   |        |               |               |               |                 | .6            | 7.0          | 7.0            |
| CALM                                    | 1111111 | ////// | //////        | ////// | ////// | ///////           | ////// | 7/////        | //////        | //////        | '//////         | 53.3          | /////        | /////          |
| TOTALS                                  | 34.5    | 11.9   | .6            |        |        |                   |        |               |               |               |                 | 100.0         | 1.5          | 2.0            |

## PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: MAY HOURS: 03-05 ...... WIND SPEED IN KNOTS DIRECTION 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) % WIND WIND (N) 350-010 15.0 2.9 3.0 020-040 2.8 1.7 4.4 4.1 4.0 050-070 2.2 2.2 1.5 1.0 (E) 080-100 .6 5.0 5.0 .6 110-130 .6 .6 2.0 2.0 140-160 .6 .6 1.0 1.0 (S) 170-190 5.0 1.7 6.7 3.1 2.5 200-220 8.9 2.2 11.1 2.9 2.5 230-250 3.3 1.1 4.4 2.6 2.0 (W) 260-280 .6 1.0 1.0 .6 290-310 320-340 6.1 2.5 ..... VARIABLE .6 8.0 8.0 ////////// 46.7 //////// CALM 100.0 1.6 2.0 TOTALS 42.9 10.7

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERJUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

TOTALS

47.7 7.8

.6

STATION NAME: CAMP CASFY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: MAY HOURS: 06-08

LET TO UTC: - 9

...... WIND SPEED IN KNOTS DIRECTION 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) WIND WIND % ...... (N) 350-010 9.4 1.7 11.1 3.1 3.0 020-040 3.3 1.1 4.4 3.3 3.5 050-070 .6 15.0 10.0 (E) 080-100 1.1 1.1 1.5 1.5 110-130 1.1 1.0 1.1 1.0 140-160 (S) 170-190 16.1 17.2 2.7 3.0 200-220 12.2 3.9 16.1 3.7 3.0 230-250 1.1 1.1 3.0 3.0 (W) 260-280 2.7 1.7 3.0 290-310 320-340 1.7 1.7 2.3 2.0 VARIABLE CALM

......

TOTAL NUMBER OF OBSERVATIONS 180

100.0

1.8

3.0

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

| L | ST TO UTC: - | 9 | MONTH: | MAY | HOURS: | 09-11 |
|---|--------------|---|--------|-----|--------|-------|
|   |              |   |        |     |        |       |

|                     |                         |        |        |             | WIND S  | SPEED IN | KNOTS       |         |         | • • • • • • • |         |            |              |                |
|---------------------|-------------------------|--------|--------|-------------|---------|----------|-------------|---------|---------|---------------|---------|------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4                     | 5-9    | 10-14  | 15-19       | 20-24   | 25-29    | 30-34       | 35-39   | 40-49   | 50-64         | GE 65   | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 3.3                     | 4.2    | .8     | • • • • • • | •••••   |          | • • • • • • | •••••   |         | • • • • • •   | •••••   | 8.3        | 5.1          | 5.0            |
| 020-040             | 5.0                     |        |        |             |         |          |             |         |         |               |         | 5.0        | 3.2          | 3.5            |
| 050-070             | 1.7                     | .8     |        |             |         |          |             |         |         |               |         | 2.5        | 3.7          | 4.0            |
| (E) 080-100         | .8                      |        |        |             |         |          |             |         |         |               |         | .8         | 1.0          | 1.0            |
| 110-130             | 1.7                     | .8     |        |             |         |          |             |         |         |               |         | 2.5        | 3.3          | 4.0            |
| 140-160             | 2.5                     | .8     |        |             |         |          |             |         |         |               |         | 3.3        | 3.8          | 3.5            |
| (S) 170-190         | 12.5                    | 7.5    |        |             |         |          |             |         |         |               |         | 20.0       | 3.9          | 4.0            |
| 200-220             | 14.2                    | 10.8   |        |             |         |          |             |         |         |               |         | 25.0       | 4.6          | 4.0            |
| 230-250             | 4.2                     | 4.2    |        |             |         |          |             |         |         |               |         | 8.3        | 4.1          | 4.5            |
| (W) 260-280         | 1.7                     |        |        |             |         |          |             |         |         |               |         | 1.7        | 3.0          | 3.0            |
| 290-310             | 2.5                     |        |        |             |         |          |             |         |         |               |         | 2.5        | 3.0          | 3.0            |
| 320 - 340           | 6.7                     |        |        |             |         |          |             |         |         |               |         | 6.7        | 2.4          | 2.0            |
|                     | <br>: • • • • • • • • • |        |        |             |         |          |             |         |         |               |         |            |              |                |
| VARIABLE            |                         | 3.3    | 1.7    |             |         |          |             |         |         |               |         | 5.0        | 8.5          | 8.0            |
| CALM                | 11111111                | ////// | ////// | //////      | 11/1/// | ///////  | //////      | 1:11111 | 1111111 | //////        | 1111111 | 8.3        | //////       | /////          |
| TOTALS              | 56.8                    | 32.4   | 2.5    |             |         |          |             |         |         |               |         | 100.0      | 3.9          | 4.0            |
|                     |                         |        |        |             |         |          |             |         |         |               |         |            |              |                |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAY HOURS: 12-14

| •••••               | • • • • • • • |        | • • • • • • • | • • • • • • | WIND S | SPEED IN | KNOTS  | • • • • • • | • • • • • • | • • • • • • | • • • • • • • |            | • • • • • •  | • • • • • • •  |
|---------------------|---------------|--------|---------------|-------------|--------|----------|--------|-------------|-------------|-------------|---------------|------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4           | 5~9    | 10-14         | 15-19       | 20-24  | 25-29    | 30-34  | 35-39       | 40-49       | 50-64       | GE 65         | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 5.6           | 1.1    | •••••         | • • • • • • |        |          | •••••  |             | •••••       |             | • • • • • • • | 6.7        | 3.3          | 3.0            |
| 020-040             | 1.1           | .6     |               |             |        |          |        |             |             |             |               | 1.7        | 4.0          | 4.0            |
| 050-070             | 4.4           |        |               |             |        |          |        |             |             |             |               | 4.4        | 3.4          | 3.5            |
| (E) 080-100         | .6            | .6     |               |             |        |          |        |             |             |             |               | 1.1        | 4.0          | 4.0            |
| 110-130             | 1.1           |        |               |             |        |          |        |             |             |             |               | 1.1        | 1.5          | 1.5            |
| 140-160             | 2.2           | .6     |               |             |        |          |        |             |             |             |               | 2.8        | 3.2          | 2.0            |
| (S) 170-190         | 6.1           | 7.2    | 1.1           |             |        |          |        |             |             |             |               | 14.4       | 5.4          | 5.0            |
| 200-220             | 13.9          | 13.3   | 2.8           | .6          |        |          |        |             |             |             |               | 30.6       | 5.3          | 5.0            |
| 230-250             | 6.1           | 2.8    |               |             |        |          |        |             |             |             |               | 8.9        | 3.8          | 4.0            |
| (W) 260-280         | 2.8           | 4.4    |               |             |        |          |        |             |             |             |               | 7.2        | 4.5          | 5.0            |
| 290-310             | 2.8           | 1.7    |               |             |        |          |        |             |             |             |               | 4.4        | 3.8          | 3.0            |
| 320-340             | 2.8           | 2.8    |               |             |        |          |        |             |             |             |               | 5.6        | 4.5          | 4.5            |
|                     |               |        |               |             |        |          |        |             |             |             |               |            |              |                |
| VARIABLE            |               | 3.3    | 2.2           |             |        |          |        |             |             |             |               | 5.6        | 8.5          | 8.0            |
| CALM                | 1111111       | ////// | ///////       | //////      | ////// | '//////  | ////// | ///////     | //////      | 1111111     | ///////       | 5.6        | /////        | /////          |
| TOTALS              | 49.5          | 38.4   | 6.1           | .6          |        |          |        |             |             |             |               | 100.0      | 4.5          | 4.0            |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY O'SERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: MA' HOURS: 15-17 WIND SPEED IN KNOTS 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN DIRECTION (DEGREES) WIND WIND B ...... (N) 350-010 3.4 5.6 .6 9.5 5.3 6.0 020-040 1.1 .6 1.7 3.7 4.0 050-070 1.7 1.1 2.8 4.6 5.0 (E) 080-100 1.7 1.7 2.3 3.0 110-130 2.8 140-160 .6 3.4 3.0 3.0 (S) 170-190 3.4 5.0 1.7 10.1 6.2 5.5 200-220 7.8 12.8 7.3 .6 28.5 7.0 6.0 230-250 2.8 11.2 .6 14.5 5.5 5.0 (W) 260-280 2.2 3.4 5.6 4.7 5.5 290-310 2.2 1.7 3.9 4.4 4.0 320-340 5.0 3.9 8.9 4.4 4.0 6.1 1.1 VARIABLE 7.3 8.6 8.0 CALM TOTALS 33.5 52.6 11.3 .6 100.0 5.7 6.0

TOTAL NUMBER OF OBSERVATIONS 179 ......

## PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: MAY HOURS: 18-20

|                     |                                       | LS          | T TO UI | c: - 9  |             |                   |         |         | MONTE         | : MAY       | HOUR          | s: 18-20   | )            |                |
|---------------------|---------------------------------------|-------------|---------|---------|-------------|-------------------|---------|---------|---------------|-------------|---------------|------------|--------------|----------------|
| •••••               |                                       | · · · · · · |         | • • •   | · · · ·     | DDDD TH           |         |         | • • • • • • • | • • • • • • | • • • • • • • |            |              | • • • • • • •  |
| DIRECTION (DEGREES) | 1-4                                   | 5-9         | 10-14   | 15-19   |             | SPEED IN<br>25-29 |         | 35-39   | 40-49         | 50-64       | GE 65         | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 3.3                                   | 3.9         |         | .6      | • • • • • • | ••••              | •••••   | •••••   | •••••         | • • • • • • | •••••         | 7.8        | 5.2          | 5.0            |
| 020-040             | 1.1                                   | 1.1         |         |         |             |                   |         |         |               |             |               | 2.2        | 5.0          | 4.5            |
| 050-070             | .6                                    | 2.2         |         |         |             |                   |         |         |               |             |               | 2.8        | 4.8          | 5.0            |
| (8) 080-100         |                                       |             |         |         |             |                   |         |         |               |             |               |            |              |                |
| 110-130             | .6                                    |             |         |         |             |                   |         |         |               |             |               | .6         | 1.0          | 1.0            |
| 140~160             | 1.1                                   |             |         |         |             |                   |         |         |               |             |               | 1.1        | 2.0          | 2.0            |
| (S) 170-190         | 3.3                                   | 1.7         | 1.7     |         |             |                   |         |         |               |             |               | 6.7        | 6.0          | 5.0            |
| 200-220             | 13.9                                  | 18.9        | .6      |         |             |                   |         |         |               |             |               | 33.3       | 4.6          | 5.0            |
| 230-250             | 10.6                                  | 4.4         | .6      |         |             |                   |         |         |               |             |               | 15.6       | 3.7          | 3.0            |
| (W) 260-280         | 4.4                                   | 2.2         |         |         |             |                   |         |         |               |             |               | 6.7        | 3.5          | 2.5            |
| 290-310             | 2.2                                   | 1.1         |         |         |             |                   |         |         |               |             |               | 3.3        | 2.7          | 1.5            |
| 320-340             | 4.4                                   |             |         |         |             |                   |         |         |               |             |               | 4.4        | 2.5          | 2.5            |
|                     | · · · · · · · · · · · · · · · · · · · |             |         |         |             |                   |         |         |               |             |               |            |              |                |
| VARIABLE            |                                       | 3.3         |         |         |             |                   |         |         |               |             |               | 3.3        | 7.3          | 7.5            |
| CALM                | 1111111                               | //////      | //////  | /////// | ///////     | ///////           | /////// | /////// | ///////       | 1111111     | 7//////       | 12.2       | /////        | /////          |
| TOTALS              | 45.5                                  | 38.8        | 2.9     | .6      |             |                   |         |         |               |             |               | 100.0      | 3.9          | 4.0            |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PFRIOD OF RECORD: JUL 80 - JUN 90

|                     |                   | LS     | TU OT T       | 'C: - 9       |             |                   |               |         | MONTH         | : MAY         | HOUR            | s: 21-23    | 3            |                |
|---------------------|-------------------|--------|---------------|---------------|-------------|-------------------|---------------|---------|---------------|---------------|-----------------|-------------|--------------|----------------|
| ••••                | • • • • • • • • • |        | • • • • • • • | • • • • • •   |             |                   |               |         | • • • • • • • | • • • • • •   | • • • • • • •   | • • • • • • | • • • • • •  | • • • • • • •  |
| DIRECTION (DEGREES) | 1-4               | 5-9    | 10-14         | 15-19         |             | SPEED IN<br>25-29 |               | 35-39   | 40-49         | 50-64         | GE 65           | TOTAL       | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 12.7              | 1.7    | • • • • • • • | · · · · · · · |             |                   | • • • • • • • | •••••   |               | • • • • • • • | • • • • • • • • | 14.4        | 2.3          | 2.0            |
| (4) 330-010         | 12.7              | 1.7    |               |               |             |                   |               |         |               |               |                 | 14.4        | 2.3          | 2.0            |
| 020-040             | 8.3               | 1.1    |               |               |             |                   |               |         |               |               |                 | 9.4         | 2.1          | 2.0            |
| 050-070             | 2.8               |        |               |               |             |                   |               |         |               |               |                 | 2.8         | 2.6          | 2.0            |
|                     |                   |        |               |               |             |                   |               |         |               |               |                 |             |              |                |
| (E) 080-100         |                   |        |               |               |             |                   |               |         |               |               |                 |             |              |                |
| 110-130             | 1.1               |        |               |               |             |                   |               |         |               |               |                 | 1.1         | 1.0          | 1.0            |
| 140-160             | 3.3               |        |               |               |             |                   |               |         |               |               |                 | 3.3         | 2.3          | 2.5            |
| (S) 170-190         | 5.0               | 1.1    | .6            |               |             |                   |               |         |               |               |                 | 6.6         | 3.5          | 2.0            |
| (2) 2:0             |                   |        |               |               |             |                   |               |         |               |               |                 | 0.0         | 3.3          | 2.0            |
| 200-220             | 8.3               | 2.2    | .6            | .6            |             |                   |               |         |               |               |                 | 11.6        | 4.0          | 2.0            |
| 230-250             | 3.9               |        |               |               |             |                   |               |         |               |               |                 | 3.9         | 2.4          | 3.0            |
| (W) 260-280         |                   |        |               |               |             |                   |               |         |               |               |                 |             |              |                |
| 290-310             | .6                |        |               |               |             |                   |               |         |               |               |                 | .6          | 2.0          | 2.0            |
| 320-340             | 5.0               |        |               |               |             |                   |               |         |               |               |                 | 5.0         | 2.0          | 2.0            |
|                     |                   |        |               |               |             |                   |               |         |               |               |                 |             |              |                |
| VARIABLE            |                   | .6     | • • • • • • • | • • • • • •   | • • • • • • | • • • • • • •     |               | ••••    |               |               |                 | .6          | 8.0          | 8.0            |
| CALM                | 11111111          | ////// | ///////       | //////        | ///////     | ///////           | ///////       | /////// | //////        | //////        | ///////         | 40.9        | //////       | 111111         |
| TOTALS              | 51.0              | 6.7    | 1.2           | .6            |             |                   |               |         |               |               |                 | 100.0       | 1.6          | 2.0            |
|                     |                   |        | TO            | TAL NUM       | BER OF      | OBSERVA           | TIONS         | 181     |               |               |                 |             |              |                |

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC USAFETAC, ASHEVILLE NC

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

| LST TO UTC: - 9 | ) |
|-----------------|---|
|-----------------|---|

| STATION NUMBER                          |                 | LS    | T TO UT     | rc: - 9 |        | Y/TONGD       |        |        | MONTH           | : MAY       |             | S: ALL      |             | 0           |
|---|-----------------|-------|-------------|---------|--------|---------------|--------|--------|-----------------|-------------|-------------|-------------|-------------|-------------|
| • | • • • • • • • • |       | • • • • • • |         |        | PEED IN       |        |        |                 | • • • • • • | •••••       | • • • • • • | • • • • • • | • • • • • • |
| DIRECTION                               | 1-4             | 5-9   | 10-14       | 15-19   |        | 25-29         |        | 35~39  | 40-49           | 50-64       | GE 65       | TOTAL       | MEAN        | MEDIAN      |
| (DEGREES)                               | <br>            |       | •••••       |         | •••••  |               | •••••  |        | · • • • • • • • |             | • • • • • • |             | WIND        | WIND        |
| (N) 350-010                             | 8.3             | 3.1   | .1          | .1      | •••••  | • • • • • • • |        |        |                 | ,           |             | 11.7        | 3.5         | 3.0         |
| 020-040                                 | 3.2             | 1.0   |             |         |        |               |        |        |                 |             |             | 4.2         | 3.3         | 3.0         |
| 050-070                                 | 1.8             | .7    | .1          |         |        |               |        |        |                 |             |             | 2.5         | 3.5         | 4.0         |
| (E) 030-100                             | .5              | .2    |             |         |        |               |        |        |                 |             |             | .7          | 3.0         | 2.5         |
| 110-130                                 | .7              | .1    |             |         |        |               |        |        |                 |             |             | .8          | 1.8         | 1.0         |
| 140-160                                 | 1.6             | .2    |             |         |        |               |        |        |                 |             |             | 1.8         | 2.8         | 3.0         |
| (S) 170-190                             | 6.7             | 3.0   | .7          |         |        |               |        |        |                 |             |             | 10.4        | 4.2         | 4.0         |
| 200-220                                 | 10.6            | 8.0   | 1.4         | .2      |        |               |        |        |                 |             |             | 20.3        | 4.8         | 4.0         |
| 230-250                                 | 4.1             | 3.0   | .1          |         |        |               |        |        |                 |             |             | 7.3         | 4.0         | 4.0         |
| (W) 260-280                             | 1.7             | 1.4   |             |         |        |               |        |        |                 |             |             | 3.1         | 3.9         | 4.0         |
| 290-310                                 | 1.3             | .6    |             |         |        |               |        |        |                 |             |             | 1.9         | 3.5         | 3.5         |
| 320-340                                 | 4.0             | .9    | .1          |         |        |               |        |        |                 |             |             | 5.0         | 3.3         | 3.0         |
| VARIABLE                                | <u>.</u>        | 2.2   | 6           |         | •••••  |               | •••••  |        | • • • • • •     |             |             | 2.8         | 8.3         | 8.0         |
| CALM                                    | 111111111       | ///// | //////      | //////  | ////// | ///////       | ////// | ////// | ///////         | ///////     | 1111111     | 27.5        | /////       | /////       |
| TOTALS                                  | 44.5            | 24.4  | 3.1         | .3      |        |               |        |        |                 |             |             | 100.0       | 3.0         | 4.0         |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

MONTH: MAY HOURS: ALL

.....

WIND SPEED IN KNOTS

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

DIRECTION | 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN ...... % WIND WIND (DEGREES) (N) 350-010 3.0 020-040 1.3 .8 2.1 3.8 3.0 050-070 2.5 . 4 3.0 3.3 2.0 (E) 080-100 2.3 1.3 1.3 2.0 110-130 .8 .8 1.0 1.0 140-160 ۰, .8 2.0 2.0 (S) 170-190 9.7 3.0 2.5 15.3 4.9 4.0 17.4 27.5 4.5 200-220 4.0 8.1 1.3 .8 230-250 5.5 1.7 7.2 2.9 2.0 (W) 260-280 3.1 3.0 2.5 .8 290-310 .8 .8 2.0 2.0 320-340 2.1 2.1 2.0 2.0 CALM TOTALS 47.7 14.4 4.2 100.0 2.7 3.0 . 8

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: JUN HOURS: 00-02

LST TO UTC: - 9

|                     | • • • • • • • • | • • • • • •   | · · · · · · · | • • • • • • | WIND S      | PEED IN                                 | KNOTS         | • • • • • •   | • • • • • • • |         |             | • • • • • • • | • • • • • •  | • • • • • •    |
|---------------------|-----------------|---------------|---------------|-------------|-------------|---|---------------|---------------|---------------|---------|-------------|---------------|--------------|----------------|
| DIRECTION (DEGRFES) | 1-4             | 5 -9          | 10-14         | 15 -19      |             | 25-29                                   |               | 35-39         | 40-49         | 50-64   | GE 65       | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
|                     | • • • • • • • • | • • • • • •   | · · · · · · · | • • • • • • | • • • • • • | • • • • • • •                           | • • • • • • • | • • • • • •   | • • • • • • • |         | · · · · · · | • • • • • • • |              | • • • • • • •  |
| (N) 350-010         | 14.4            | 1.1           |               |             | .6          |   |               |               |               |         |             | 16.1          | 2.9          | 2.0            |
| 020-040             | 5.6             |               |               |             |             |   |               |               |               |         |             | 5.6           | 1.9          | 2.0            |
| 050-070             | 2.2             | .6            |               |             |             |   |               |               |               |         |             | 2.8           | 2.4          | 2.0            |
| (E) 080-100         | .6              |               |               |             |             |   |               |               |               |         |             | .5            | 1.0          | 1.0            |
| 110-130             | .6              | .6            |               |             |             |   |               |               |               |         |             | 1.1           | 4.5          | 4.5            |
| 140-160             | .6              | .6            |               |             |             |   |               |               |               |         |             | 1.1           | 4.5          | 4.5            |
| (S) 170-190         | 4.4             | 1.7           | 1.1           |             |             |   |               |               |               |         |             | 7.2           | 4.7          | 4.0            |
| 200-270             | 3.9             | 2.8           |               |             |             |   |               |               |               |         |             | 6.7           | 4.7          | 4.0            |
| 230-250             | 1.7             |               |               |             |             |   |               |               |               |         |             | 1.7           | 2.3          | 2.0            |
| (W) 260-280         | ъ.              |               |               |             |             |   |               |               |               |         |             | .6            | 4.0          | 4.0            |
| 290-310             | 1.7             | 1.7           |               |             |             |   |               |               |               |         |             | 3.3           | 4.7          | 4.5            |
| 320-340             | 11.7            |               |               |             |             |   |               |               |               |         |             | 11.7          | 2.0          | 2.0            |
| VARIABLE            | :<br>           | • • • • • • • |               | • • • • • • |             | • |               | • • • • • • • |               |         | •••••       | ••••••        | •••••        | • • • • • •    |
| CALM                | 11111111        | (111111       | ///////       | //////      | //////      | 1111111                                 | //////        | 1111111       | 1111111       | 1111111 | ///////     | 41.7          | /////        | /////          |
| TOTALS              | 48.0            | 9.1           | 1.1           |             | .6          |   |               |               |               |         |             | 100.0         | 1.8          | 2.0            |
|                     |                 |               | TΩ            | тат. мим    | BEB OF      | OBSERVA                                 | TTONS         | 180           |               |         |             |               |              |                |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

|                        |          | LS     | T TO UI       | 'C: ~ 9         |        |                   |         |   | MONTH   | : JUN  | HOUR                                    | s: 03-05 | 5            | •              |
|------------------------|----------|--------|---------------|-----------------|--------|-------------------|---------|---|---------|--------|---|----------|--------------|----------------|
| DIRECTION<br>(DEGREES) | 1-4      | 5-9    | 10-14         | 15-19           |        | SPEED IN<br>25-29 |         | 35-39                                   | 40-49   | 50-64  | GE 65                                   | TOTAL    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010            | 18.3     | 1.1    | • • • • • • • | • • • • • • • • |        | • • • • • • •     |         | • • • • • • •                           |         |        | • • • • • • •                           | 19.4     | 2.1          | 2.0            |
| 020-040                | 2.2      |        |               |                 |        |                   |         |   |         |        |   | 2.2      | 1.8          | 2.0            |
| 050-070                | 1.7      |        |               |                 |        |                   |         |   |         |        |   | 1.7      | 2.3          | 2.0            |
| (E) 080-100            |          |        |               |                 |        |                   |         |   |         |        |   |          |              |                |
| 110-130                | .6       | 1.1    |               |                 |        |                   |         |   |         |        |   | 1.7      | 4.7          | 5.0            |
| 140-160                |          |        |               |                 |        |                   |         |   |         |        |   |          |              |                |
| (S) 170-190            | 1.1      |        |               |                 |        |                   |         |   |         |        |   | 1.1      | 1.0          | 1.0            |
| 200-220                | 6.7      | 2.2    | 1.1           |                 |        |                   |         |   |         |        |   | 10.0     | 4.3          | 3.5            |
| 230-250                | 1.1      |        |               |                 |        |                   |         |   |         |        |   | 1.1      | 2.5          | 2.5            |
| (W) 260-280            | 1.7      |        |               |                 |        |                   |         |   |         |        |   | 1.7      | 1.3          | 1.0            |
| 290-310                | 1.7      |        |               |                 |        |                   |         |   |         |        |   | 1.7      | 1.7          | 2.0            |
| 320-340                | 9.4      | 1.7    |               |                 |        |                   |         |   |         |        |   | 11.1     | 2.8          | 2.5            |
| ማስግግ ABOR              |          |        |               | • • • • • • •   |        |                   |         | • |         |        | • |          | • • • • • •  |                |
| CALM                   | //////// | 1///// | ///////       | //////          | ////// | ///////           | /////// | ////////                                | 1111111 | ////// | 1111111                                 | 48.3     | //////       | /////          |
| TOTALS                 | 44.5     | 6.1    | 1.1           |                 |        |                   |         |   |         |        |   | 100.0    | 1.4          | 2.0            |
|                        |          |        | -             |                 |        |                   |         |   |         |        |   |          |              |                |

TOTAL NUMBER OF OBSERVATIONS 180 ......

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: JUN HOURS: 06-08 LST TO UTC: - 3 WIND SPEED IN KNOTS DIRECTION 1 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 CE 65 TOTAL MEAN MEDIAN 1 - 4 (DEGREES) \* WIND WIND ....... 10.6 (N) 350-010 1.7 1.1 3.3 2.0 020-040 2.2 2.2 1.3 1.0 050-070 3.3 .6 2.4 2.0 (E) 080-100 .6 .6 6.0 6.0 110-130 4.0 . 6 .6 4.0 140-160 1.1 1.1 2.0 2.0 (S) 170-190 10.0 11.1 2.6 2.0 1.1 200-220 7.2 3.9 11.7 4.0 3.0 230-250 .6 2.0 2.0 (W) 260-280 290 -313 1.1 1.0 1.0 1.1 320-340 8.9 . 6 2.0 2.0 VARIABLE CALM TOTALS 45.6 8.5 1.7 100.0 1.6 2.0

## PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 4/1066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: JUN HOURS: 09-11

|                     |                     | 2,74. |         |         |        |          |         |         | PROPERTY.     |        |        | 100. 00-1  | •            |               |
|---------------------|---------------------|-------|---------|---------|--------|----------|---------|---------|---------------|--------|--------|------------|--------------|---------------|
|                     |                     |       |         |         |        | SPEED IN | KNOTS   |         |               |        |        |            |              |               |
| DIFECTION (DEGREES) | ;                   |       |         |         |        | 25-29    |         |         |               | 50-64  | GE 65  | TOTAL<br>% | MEAN<br>WIND | MEDIA<br>WIND |
| N) 350-010          | 10.8                | 1.7   |         |         |        |          |         | •••••   | • • • • • • • | •••••  |        | 12.5       | 3.1          | 4.0           |
| 070-040             | .8                  | 1.7   |         |         |        |          |         |         |               |        |        | 2.5        | 4.3          | 5.0           |
| 050-070             |                     | 1.7   |         |         |        |          |         |         |               |        |        | 1.7        | 5.5          | 5.5           |
| E) 080-100          | .8                  |       |         |         |        |          |         |         |               |        |        | .8         | 2.0          | 2.0           |
| 110-110             | 1                   | 1.7   |         |         |        |          |         |         |               |        |        | 3.3        | 4.8          | 4.0           |
| 140-150             | 6.7                 | 2.5   |         |         |        |          |         |         |               |        |        | 9.2        | 3.9          | 4.0           |
| 3) 170-190          | 14.2                | 2.5   |         |         |        |          |         |         |               |        |        | 16.7       | 3.4          | 3.0           |
| 200 220             | 17.5                | 7.5   |         |         |        |          |         |         |               |        |        | 25.0       | 4.0          | 4.0           |
| 230-250             | 3.3                 | 1.7   |         |         |        |          |         |         |               |        |        | 5.0        | 3.3          | 2.0           |
| v) 260-280          | 2.5                 |       |         |         |        |          |         |         |               |        |        | 2.5        | 3.3          | 4.0           |
| 290-310             | 1.7                 |       |         |         |        |          |         |         |               |        |        | 1.7        | 2.0          | 2.0           |
| 320 - 340           | 5.0                 | .я    |         |         |        |          |         |         |               |        |        | 5.8        | 2.4          | 2.0           |
| VARIABLE            | <br>!               | à     |         |         |        |          |         |         |               |        |        | .8         | 8.0          | 8.0           |
| nAbM                | :<br>:////////<br>: | 17797 | (111111 | 1/1//// | 7/1/// | 1111111  | /////// | /////// | 1111111       | 111111 | 1///// | / 12.5     | //////       | 111111        |
| TOTALS              | 65.0                | 22.6  |         |         |        |          |         |         |               |        |        | 100.0      | 3.2          | 4.0           |

USAFETAC, ASHEVILLE NO

### OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATI: N NUMBER: 471966 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

|                        |   | LS   | т ю пт | rc: - 9  |         |                   |          |         | MONTY    | H: JUN   | HOUR  | S: 12-14   | :            |                |
|------------------------|---|------|--------|----------|---------|-------------------|----------|---------|----------|----------|-------|------------|--------------|----------------|
| DIRROTION<br>(DRURRER) |   | 5-9  | 10-14  | 15 19    |         | SPEED IN<br>25-29 |          | 35-39   | 40-49    | 50-64    | GE 65 | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010            | 5.ñ                                       | 5.6  | 1.7    |          |         |                   |          |         |          |          |       | 12.8       | 5.6          | 5.0            |
| 120-140                | . 2.8                                     | . 6  | .6     |          |         |                   |          |         |          |          |       | 3.9        | 4.3          | 3.0            |
| 040-079                | . 1.3                                     | 1.1  |        |          |         |                   |          |         |          |          |       | 4.4        | 3.1          | 3.0            |
| (E) (980-100           | !   |      |        |          |         |                   |          |         |          |          |       |            |              |                |
| 110-130                | 1.1                                       | 2.2  |        |          |         |                   |          |         |          |          |       | 3.3        | 5.0          | 6.0            |
| 140~160                | 6.1                                       |      |        |          |         |                   |          |         |          |          |       | 6.1        | 3.0          | 3.0            |
| (3) 170-190            | 3.9                                       | 7.2  |        |          |         |                   |          |         |          |          |       | 11.1       | 5.0          | 5.0            |
| 200-120                | 20.0                                      | 7.2  | 1.7    |          |         |                   |          |         |          |          |       | 28.9       | 4.3          | 4.0            |
| 230-250                | 6.1                                       | 7.8  | 1.1    |          |         |                   |          |         |          |          |       | 15.0       | 4.9          | 5.0            |
| (W) 260-280            | 3.3                                       |      |        |          |         |                   |          |         |          |          |       | 3.3        | 2.8          | 3.0            |
| 290=410                | .6  | 1.1  |        |          |         |                   |          |         |          |          |       | 1.7        | 5.0          | 6.0            |
| 320-340                | 2.2                                       | 1.1  |        |          |         |                   |          |         |          |          |       | 3.3        | 3.3          | 2.0            |
| VAPIABLE               | <br>• • • • • • • • • • • • • • • • • • • | 1.1  |        |          |         | <i>.</i>          |          |         |          |          |       | 1.7        | 8.7          | 7.0            |
|                        | ///////                                   |      |        | 111111   |         | ////////          |          |         |          |          |       |            |              |                |
|                        | 55.0                                      |      | 5.7    | ,,,,,,,, | ,,,,,,, | .,,,,,,,,         | ,,,,,,,, | ,,,,,,, | ,,,,,,,, | ,,,,,,,, |       |            |              |                |
| TYYALS                 | 1 55-0                                    | 35.0 | 5.7    |          |         |                   |          |         |          |          |       | 100.0      | 4.3          | 4.0            |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURTLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: JUN HOURS: 15-17

|   |          | LS      | T TO UI | C: - 9 |         |               |               |               | MONTE         | i: JUN      | HOUR    | S: 15-17   | ′            |                |
|---|----------|---------|---------|--------|---------|---------------|---------------|---------------|---------------|-------------|---------|------------|--------------|----------------|
| • |          |         |         |        | WIND S  | PEED IN       | KNOTS         |               |               |             |         |            | •••••        | • • • • • • •  |
| DIRECTION (DEGREES)                     | 1-4      | 5-9     | 10-14   | 15-19  | 20-24   | 25-29         | 30-34         | 35-39         | 40-49         | 50-64       | GE 65   | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 5.0      | 5.0     | .6      |        | •••••   | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • •   | • • • • • • |         | 10.6       | 4.5          | 5.0            |
| 020-040                                 | 3.9      | 3.3     |         |        |         |               |               |               |               |             |         | 7.2        | 4.3          | 4.0            |
| 050-070                                 | 2.8      | 1.1     |         |        |         |               |               |               |               |             |         | 3.9        | 4.3          | 4.0            |
| (E) 080-100                             | 2.8      |         |         |        |         |               |               |               |               |             |         | 2.8        | 3.2          | 3.0            |
| 110-130                                 | 2.8      |         |         |        |         |               |               |               |               |             |         | 2.8        | 2.6          | 2.0            |
| 140-160                                 | 1.7      |         | .5      |        |         |               |               |               |               |             |         | 2.2        | 5.0          | 4.0            |
| (S) 170-190                             | 2.8      | 2.2     |         |        |         |               |               |               |               |             |         | 5.0        | 4.2          | 4.0            |
| 200-220                                 | 13.3     | 15.0    | 1.1     |        |         |               |               |               |               |             |         | 29.4       | 5.1          | 5.0            |
| 230-250                                 | 7.2      | 4.4     | .6      |        |         |               |               |               |               |             |         | 12.2       | 4.4          | 4.0            |
| (W) 260-280                             | 4.4      | 3.3     |         |        |         |               |               |               |               |             |         | 7.8        | 4.6          | 4.0            |
| 290-310                                 | 2.8      | 1.7     | .6      |        |         |               |               |               |               |             |         | 5.0        | 5.0          | 4.0            |
| 320-340                                 | 4.4      | 1.7     |         |        |         |               |               |               |               |             |         | 6.1        | 3.8          | 4.0            |
| VARIABLE                                | '<br>    | 1.7     |         |        |         |               |               |               | · · · · · · · |             |         | 1.7        | 7.7          | 8.0            |
|   |          |         |         |        |         |               |               |               |               |             |         |            |              |                |
| CALM                                    | 11111111 | (1/1/// | /////// | ////// | 1////// | 11/1///       | 7//////       | 11/////       | '//////       | (//////     | '////// | 3.3        | //////       | /////          |
| TOTALS                                  | 53.9     | 39.4    | 3.5     |        |         |               |               |               |               |             |         | 100.0      | 4.4          | 4.0            |
|   |          |         |         | m = 7  |         |               |               |               |               |             |         |            |              |                |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUN HOURS: 18-20

|                     |                   |        |         |               |         | <b></b>  |         | . <b></b>     |         |               |               |            | -<br>        |                |
|---------------------|-------------------|--------|---------|---------------|---------|----------|---------|---------------|---------|---------------|---------------|------------|--------------|----------------|
|                     |                   |        |         |               | WIND S  | SPEED IN | KNOTS   |               |         |               |               |            |              |                |
| DIRECTION (DEGREES) | 1-4               | 5-9    | 10-14   | 15-19         | 20-24   | 25-29    | 30-34   | 35-39         | 40-49   | 50-64         | GE 65         | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 6.1               | 4.4    | 1.1     | • • • • • • • | •••••   |          |         | • • • • • • • |         | • • • • • • • | • • • • • • • | 11.7       | 4.8          | 4.0            |
| 020-040             | 3.9               | 2.8    |         |               |         |          |         |               |         |               |               | 6.7        | 4.1          | 3.0            |
| 050-070             | 3.9               | 2.2    |         |               |         |          |         |               |         |               |               | 6.1        | 3.8          | 3.0            |
| (E) 080-100         | .6                |        |         |               |         |          |         |               |         |               |               | .6         | 2.0          | 2.0            |
| 110-130             | 1.1               | .6     |         |               |         |          |         |               |         |               |               | 1.7        | 3.3          | 4.0            |
| 140-160             | 1.1               |        |         |               |         |          |         |               |         |               |               | 1.1        | 1.5          | 1.5            |
| (S) 170-190         | 3.3               | 3.3    |         |               |         |          |         |               |         |               |               | 6.7        | 4.5          | 4.5            |
| 200-220             | 10.6              | 7.8    |         |               |         |          |         |               |         |               |               | 18.3       | 4.2          | 4.0            |
| 230-250             | 8.3               | 3.3    | .6      |               |         |          |         |               |         |               |               | 12.2       | 4.1          | 3.0            |
| (W) 260-280         | 5.0               | 2.8    |         |               |         |          |         |               |         |               |               | 7.8        | 3.6          | 4.0            |
| 290-310             | 2.8               |        |         |               |         |          |         |               |         |               |               | 2.8        | 2.0          | 2.0            |
| 320~340             | 4.4               |        |         |               |         |          |         |               |         |               |               | 4.4        | 2.1          | 2.0            |
|                     | · · · · · · · · · |        |         |               |         |          |         |               |         |               |               |            |              |                |
| VARIABLE            |                   | 1.7    |         |               |         |          |         |               |         |               |               | 1.7        | 7.7          | 8.0            |
| CALM                | 11111111          | ////// | /////// | //////        | 11/1/// | ///////  | /////// | '//////       | /////// | (//////       | ///////       | 18.3       | /////        | 111111         |
| TOTALS              | 51.1              | 28.9   | 1.7     |               |         |          |         |               |         |               |               | 100.0      | 3.3          | 3.0            |
|                     |                   |        |         | <b></b>       |         |          |         |               |         |               |               |            |              |                |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

52.P

9.1 2.3

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

|                     |                        | LS        | T TO UT | C: - 9      |               |               | -             |               |               | : JUN         | HOUR          | S: 21-23      | 1            |                |
|---------------------|------------------------|-----------|---------|-------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|--------------|----------------|
|                     | • • • • • • • •        | • • • • • |         | • • • • • • |               | SPEED IN      |               | • • • • • • • |               | • • • • • • • | • • • • • • • | • • • • • • • | •••••        |                |
| DIRECTION (DEGREES) | 1-4                    | 5-9       | 10-14   | 15-19       | 20-24         | 25-29         | 30-34         | 35-39         | 40-49         | 50-64         | GE 65         | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | <br>  18.9             | 2.2       |         | • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • |               | • • • • • • • | 21.1          | 2.4          | 2.0            |
| (11) 330-010        | 10.5                   | 2.2       |         |             |               |               |               |               |               |               |               | 21.1          | 2.4          | 2.0            |
| 020-040             | 7.2                    | .6        |         |             |               |               |               |               |               |               |               | 7.8           | 2.1          | 2.0            |
|                     |                        |           |         |             |               |               |               |               |               |               |               |               |              |                |
| 050-070             | 1.7                    |           |         |             |               |               |               |               |               |               |               | 1.7           | 2.0          | 1.0            |
| (E) 080-100         | .6                     |           | .6      |             |               |               |               |               |               |               |               | 1.1           | 6.5          | 6.5            |
| (1) 000 100         | •                      |           | ••      |             |               |               |               |               |               |               |               | 1.1           | 0.5          | 0.3            |
| 110-130             | :                      |           |         |             |               |               |               |               |               |               |               |               |              |                |
|                     | _                      |           |         |             |               |               |               |               |               |               |               |               |              |                |
| 140-160             | .6                     |           |         |             |               |               |               |               |               |               |               | .6            | 2.0          | 2.0            |
| (S) 170-190         | 2.2                    | 1.7       |         |             |               |               |               |               |               |               |               | 3.9           | 3.9          | 4.0            |
| (3) 2:0 230         |                        |           |         |             |               |               |               |               |               |               |               | 3.7           | 3.5          | 4.0            |
| 200-∠20             | 11.1                   | 2.8       | 1.1     |             |               |               |               |               |               |               |               | 15.0          | 3.7          | 3.0            |
|                     |                        | _         | _       |             |               |               |               |               |               |               |               |               |              |                |
| 230-250             | 3.3                    | .6        | .6      |             |               |               |               |               |               |               |               | 4.4           | 3.6          | 2.0            |
| (W) 260-280         |                        |           |         |             |               |               |               |               |               |               |               |               |              |                |
| ` ,                 |                        |           |         |             |               |               |               |               |               |               |               |               |              |                |
| 290-310             | 1.1                    |           |         |             |               |               |               |               |               |               |               | 1.1           | 1.0          | 1.0            |
| 300 340             |                        | _         |         |             |               |               |               |               |               |               |               |               |              |                |
| 320-340             | 6.1                    | .6        |         |             |               |               |               |               |               |               |               | 6.7           | 2.3          | 2.0            |
|                     | !<br>• • • • • • • • • |           |         |             |               |               |               |               |               |               |               |               |              |                |
| VARIABLE            | 1                      | .6        |         |             |               |               |               |               |               |               |               | .6            | 7.0          | 7.0            |
|                     | <b> </b>               |           |         |             |               |               |               |               |               |               |               |               |              |                |
| CALM                | 11/1////               | 111111    | //////  | //////      | //////        | 1111111       | //////        | //////        | 11/1///       | //////        | 1111111       | 36.1          | /////        | /////          |
|                     | •                      |           |         |             |               |               |               |               |               |               |               |               |              |                |

TOTAL NUMBER OF OBSERVATIONS 180 ......

100.0

2.0

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO
LST TO UTC: - 9

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: JUN HOURS: ALL

|             |          | ПО          | 1 10 01       | C 9           |        |             |             |         | PONT          |               | noon    | 3. KUL |             |        |
|-------------|----------|-------------|---------------|---------------|--------|-------------|-------------|---------|---------------|---------------|---------|--------|-------------|--------|
| •••••       |          | • • • • • • | • • • • • • • |               | WIND S | SPEED IN    | KNOTS       |         |               |               | •••••   |        | • • • • • • |        |
| DIRECTION   | 1-4      | 5-9         | 10-14         | 15-19         | 20-24  | 25-29       | 30-34       | 35-39   | 40-49         | 50-64         | GE 65   | TOTAL  | MEAN        | MEDIAN |
| (DEGREES)   |          |             | •••••         | • • • • • •   |        | •••••       |             |         | •••••         | • • • • • • • | •••••   | *      | WIND        | WIND   |
| (N) 350-010 | 11.2     | 2.9         | .6            | • • • • • •   | .1     | • • • • • • | •••••       |         | •••••         |               | •••••   | 14.8   | 3.4         | 2.0    |
| 020-040     | 3.7      | 1.1         | .1            |               |        |             |             |         |               |               |         | 4.9    | 3.1         | 2.0    |
| 050-070     | 2.5      | .9          |               |               |        |             |             |         |               |               |         | 3.3    | 3.3         | 3.0    |
| (E) 080-100 | .7       | .1          | .1            |               |        |             |             |         |               |               |         | .8     | 3.6         | 3.0    |
| 110-130     | 1.0      | .7          |               |               |        |             |             |         |               |               |         | 1.7    | 4.1         | 4.0    |
| 140-160     | 2.0      | .3          | .1            |               |        |             |             |         |               |               |         | 2.4    | 3.5         | 3.0    |
| (S) 170-190 | 4.9      | 2.5         | .1            |               |        |             |             |         |               |               |         | 7.5    | 3.9         | 4.0    |
| 200-220     | 11.0     | 6.1         | .7            |               |        |             |             |         |               |               |         | 17.8   | 4.4         | 4.0    |
| 230-250     | 4.0      | 2.2         | .4            |               |        |             |             |         |               |               |         | 6.6    | 4.2         | 4.0    |
| (W) 260-280 | 2.2      | .8          |               |               |        |             |             |         |               |               |         | 3.0    | 3.7         | 4.0    |
| 290-310     | 1.7      | .6          | .1            |               |        |             |             |         |               |               |         | 2.3    | 3.5         | 2.5    |
| 320-340     | 6.6      | .8          |               |               |        |             |             |         |               |               |         | 7.4    | 2.5         | 2.0    |
|             | <br>     |             |               | · · · · · · · |        |             | • • • • • • |         | • • • • • • • |               |         |        |             |        |
| VARIABLE    |          | .7          | -1            |               |        |             |             |         |               |               |         | .8     | 7.9         | 8.0    |
| CALM        | 11111111 | (111111     | //////        | //////        | ////// | '///////    | //////      | (////// | ///////       | 7//////       | /////// | 26.7   | //////      | 111111 |
| TOTALS      | 51.5     | 19.7        | 2.3           |               | .1     |             |             |         |               |               |         | 100.0  | 2.7         | 3.0    |

TOTAL NUMBER OF OBSERVATIONS 1380

......

USAFETAC, ASHEVILLE NC

### OPERATING LOCATION "A" PERCENTAGE FREQUENCY OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED USAFETAC. ASHEVILLE NO. FROM HOURLY OBSERVATIONS

FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUN HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

|       | DIRECTION | 1-4     |         | 10 14  | 15 10         |             | PEED IN<br>25-29 |        | 35 30         | 40-49         | E0 64         | OF SE         | TOTAL         | MEAN   | MEDIAN |
|-------|-----------|---------|---------|--------|---------------|-------------|------------------|--------|---------------|---------------|---------------|---------------|---------------|--------|--------|
|       | DIRECTION | 1-4     | o-9     | 10-14  | 15-19         | 20-24       | 23-29            |        | 33-39         | 40-49         | 30-64         | GE 05         | TOTAL         | PLEAN  | MEDIAN |
|       | (DEGREES) |         |         |        |               |             |                  |        |               |               |               |               | *             | WIND   | WIND   |
| (N)   | 350-010   | 7.6     | 2.0     | 1.2    | • • • • • • • |             |                  |        | • • • • • • • | •••••         | • • • • • • • | • • • • • • • | 10.8          | 3.9    | 3.0    |
|       | 020-040   | 2.0     | .6      |        |               |             |                  |        |               |               |               |               | 2.6           | 2.8    | 2.0    |
|       | 050-070   | 1.7     |         |        |               |             |                  |        |               |               |               |               | 1.7           | 1.3    | 1.0    |
| (E)   | 080-100   | .3      |         |        |               |             |                  |        |               |               |               |               | .3            | 1.0    | 1.0    |
|       | 110-130   | .3      | .3      |        |               |             |                  |        |               |               |               |               | .6            | 3.0    | 3.0    |
|       | 140-160   | .6      |         |        |               |             |                  |        |               |               |               |               | .6            | 1.5    | 1.5    |
| (S)   | 170-190   | 9.6     | 4.4     | .6     |               |             |                  |        |               |               |               |               | 14.5          | 4.1    | 4.0    |
|       | 200-220   | 16.0    | 4.9     | 1.5    |               |             |                  |        |               |               |               |               | 22.4          | 4.2    | 4.0    |
|       | 230-250   | 3.5     | 1.5     | .3     |               |             |                  |        |               |               |               |               | 5.2           | 3.8    | 3.0    |
| (W)   | 260-280   | 1.2     |         |        |               |             |                  |        |               |               |               |               | 1.2           | 2.0    | 1.5    |
|       | 290-310   | 2.0     |         |        |               |             |                  |        |               |               |               |               | 2.0           | 2.0    | 2.0    |
|       | 320-340   | 2.6     | .3      |        |               |             |                  |        |               |               |               |               | 2.9           | 2.9    | 3.0    |
| • • • | VARIABLE  |         |         |        | • • • • • •   | • • • • • • | • • • • • • •    |        |               | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • |        | •••••  |
|       | AULINDRE  |         |         |        |               |             |                  |        |               |               |               |               |               |        |        |
|       | CALM      | 1111111 | /////// | ////// | //////        | //////      | ////////         | ////// | //////        | 11/1///       | //////        | ///////       | 35.2          | ////// | ////// |
|       | TOTALS    | 47.4    | 14.0    | 3.6    |               |             |                  |        |               |               |               |               | 100.0         | 2.4    | 3.0    |

TOTAL NUMBER OF OBSERVATIONS 344

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90
MONTH: JUI HOURS: 00-02

|                     |                 | LS          | r to ut | 'C: - 9       |               |               |         |               | MONTH         | i: Ju       | HOUR          | s: 00-02      | 2            |                |
|---------------------|-----------------|-------------|---------|---------------|---------------|---------------|---------|---------------|---------------|-------------|---------------|---------------|--------------|----------------|
| •••••               | • • • • • • • • | • • • • • • |         | • • • • • • • | WIND S        | SPEED IN      | KNOTS   | • • • • • • • | - • • • • • • | • • • • • • | • • • • • • • | • • • • • • • |              | • • • • • • •  |
| DIRECTION (DEGREES) | 1-4             | 5-9         | 10-14   | 15-19         |               | 25-29         |         | 35-39         | 40-49         | 50-64       | GE 65         | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 12.2            | 3.3         | 1.1     | • • • • • •   | • • • • • • • | • • • • • • • | •••••   |               |               | •••••       | •••••         | 16.7          | 3.7          | 2.0            |
| 020-040             | 4.4             |             |         |               |               |               |         |               |               |             |               | 4.4           | 1.3          | 1.0            |
| 050-070             | 2.2             |             |         |               |               |               |         |               |               |             |               | 2.2           | 2.0          | 2.0            |
| (E) 080-100         |                 |             |         |               |               |               |         |               |               |             |               |               |              |                |
| 110-130             |                 |             |         |               |               |               |         |               |               |             |               |               |              |                |
| 140-160             |                 |             |         |               |               |               |         |               |               |             |               |               |              |                |
| (S) 170-190         | 1.1             | 2.2         | 1.1     |               |               |               |         |               |               |             |               | 4.4           | 7.3          | 6.5            |
| 200-220             | 7.8             |             |         |               |               |               |         |               |               |             |               | 7.8           | 1.7          | 1.0            |
| 230-250             |                 |             |         |               |               |               |         |               |               |             |               |               |              |                |
| (W) 260-280         |                 |             |         |               |               |               |         |               |               |             |               |               |              |                |
| 290-310             |                 |             |         |               |               |               |         |               |               |             |               |               |              |                |
| 320-340             | 11.1            | 1.1         |         |               |               |               |         |               |               |             |               | 12.2          | 2.4          | 2.0            |
| VARIABLE            | !<br>           | •••••       |         |               | ••••••        | · • • • • • • | •••••   |               |               |             | •••••         | • • • • • • • | · • • • • •  |                |
| CALM                | 11111111        | 111111      | //////  | //////        | 1/////        | ////////      | /////// | ///////       | ///////       | '//////     | //////        | 52.2          | /////        | /////          |
| TOTALS              | 38.8            | 6.6         | 2.2     |               |               |               |         |               |               |             |               | 100.0         | 1.5          | 2.0            |

TOTAL NUMBER OF OBSERVATIONS 90

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

| STATION NUMBER      | R: 4/1000       |             | r to ut |               | MP CASE | II/ IUNGD     | OCHON F     | NO .    |               | I: JUL        |                 | s: 03-05    |              | U              |
|---------------------|-----------------|-------------|---------|---------------|---------|---------------|-------------|---------|---------------|---------------|-----------------|-------------|--------------|----------------|
|                     | • • • • • • • • | • • • • • • |         | • • • • • • • | WIND S  | PEED IN       | KNOTS       | •••••   | • • • • • • • | • • • • • • • | • • • • • • •   | • • • • • • | • • • • • •  |                |
| DIRECTION (DEGREES) | 1-4             | 5-9         | 10-14   | 15-19         | 20-24   | 25-29         | 30-34       | 35-39   | 40-49         | 50-64         | GE 65           | TOTAL<br>%  | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 11.1            | 4.4         |         | •••••         |         | • • • • • • • | ••••••      | •••••   | • • • • • •   | •••••         | • • • • • • • • | 15.6        | 3.3          | 2.0            |
| 020-040             | 3.3             |             | 1.1     |               |         |               |             |         |               |               |                 | 4.4         | 4.0          | 2.5            |
| 050-070             |                 |             |         |               |         |               |             |         |               |               |                 |             |              |                |
| (E) 080-100         |                 |             |         |               |         |               |             |         |               |               |                 |             |              |                |
| 110-130             |                 |             |         |               |         |               |             |         |               |               |                 |             |              |                |
| 140-160             | İ               |             |         |               |         |               |             |         |               |               |                 |             |              |                |
| (S) 170-190         | 2.2             | 4.4         | 1.1     |               |         |               |             |         |               |               |                 | 7.8         | 5.6          | 5.0            |
| 200-220             | 10.0            |             |         |               |         |               |             |         |               |               |                 | 10.0        | 1.8          | 1.0            |
| 230-250             | <u> </u>        |             |         |               |         |               |             |         |               |               |                 |             |              |                |
| (W) 260-280         |                 |             |         |               |         |               |             |         |               |               |                 |             |              |                |
| 290-310             | 1.1             |             |         |               |         |               |             |         |               |               |                 | 1.1         | 1.0          | 1.0            |
| 320-340             | 6.7             | 2.2         |         |               |         |               |             |         |               |               |                 | 8.9         | 3.6          | 2.5            |
| VARIABLE            | :<br>           | • • • • • • |         |               |         | •••••         | • • • • • • | •••••   | •••••         | •••••         |                 | •••••       | • • • • • •  | •••••          |
| CALM                | 11111111        | //////      | //////  | //////        | //////  | ///////       | //////      | /////// | ///////       | //////        | ///////         | 52.2        | /////        | /////          |
| TOTALS              | 34.4            | 11.0        | 2.2     |               |         |               |             |         |               |               |                 | 100.0       | 1.6          | 2.0            |
|                     |                 |             | m-      | mat mum       | DED OF  | ODCEDUS       | TONC        | 00      |               |               |                 |             |              |                |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 80-

| LST TO UTC | : - 9 | MONTH: | JUL | HOURS: | 06-0 |
|------------|-------|--------|-----|--------|------|
|            |       |        |     |        |      |

|                        |          | 20            |        |             |             |                   |               |               | 1101111     |         | 110010      |             | •             |                |
|------------------------|----------|---------------|--------|-------------|-------------|-------------------|---------------|---------------|-------------|---------|-------------|-------------|---------------|----------------|
| DIRECTION<br>(DEGREES) | 1-4      | 5~9           | 10-14  | 15-19       |             | SPEED IN<br>25-29 |               | 35-39         | 40-49       | 50-64   | GE 65       | TOTAL       | MEAN<br>WIND  | MEDIAN<br>WIND |
| (N) 350-010            | 7.8      | 3.3           | 1.1    |             | •••••       |                   | • • • • • •   | • • • • • • • | •••••       |         |             | 12.2        | 4.2           | 3.0            |
| 020-040                | 6.7      | 1.1           |        |             |             |                   |               |               |             |         |             | 7.8         | 2.3           | 2.0            |
| 050-070                | 1.1      | 2.2           |        |             |             |                   |               |               |             |         |             | 3.3         | 4.7           | 5.0            |
| (E) 080-100            | 1.1      |               |        |             |             |                   |               |               |             |         |             | 1.1         | 4.0           | 4.0            |
| 110-130                |          |               |        |             |             |                   |               |               |             |         |             |             |               |                |
| 140-160                |          |               |        |             |             |                   |               |               |             |         |             |             |               |                |
| (S) 170-190            | 5.6      | 3.3           | 1.1    |             |             |                   |               |               |             |         |             | 10.0        | 4.6           | 3.0            |
| 200-220                | 7.8      | 2.2           |        |             |             |                   |               |               |             |         |             | 10.0        | 2.8           | 2.0            |
| 230-250                | 1.1      |               |        |             |             |                   |               |               |             |         |             | 1.1         | 1.0           | 1.0            |
| (W) 260-280            |          |               |        |             |             |                   |               |               |             |         |             |             |               |                |
| 290-310                |          |               |        |             |             |                   |               |               |             |         |             |             |               |                |
| 320-340                | 4.4      | 1.1           | 1.1    |             |             |                   |               |               |             |         |             | 6.7         | 4.2           | 2.5            |
| VARIABLE               |          | • • • • • • • | •••••• | • • • • • • | • • • • • • |                   | • • • • • • • | : • • • • •   | • • • • • • |         | • • • • • • | • • • • • • | · • • • • • • | •••••          |
| CALM                   | 11111111 | //////        | ////// | //////      | //////      | ////////          | //////        | //////        | ///////     | 1111111 | ///////     | 47.8        | /////         | /////          |
| TOTALS                 | 35.6     | 13.2          | 3.3    |             |             |                   |               |               |             |         |             | 100.0       | 1.9           | 3.0            |
|                        |          |               | Tr.C   | erat aue    | DED OF      | ODGERUA           | TTONE         | 00            |             |         |             |             |               |                |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90
MONTH: JUL HOURS: 09-11

| LST TO UTC: - 9 | MONTH: | Jί |
|-----------------|--------|----|
| LST TO OTC: - 9 | MUNTH: | J  |

|                     |          | гэ     | 1 10 01       | C: - 9  |             |          |        |        | MONTH       | : 001         | יות יות       | (S: U9-1.  | L            |                |
|---------------------|----------|--------|---------------|---------|-------------|----------|--------|--------|-------------|---------------|---------------|------------|--------------|----------------|
| D.T.D.P.COD.T.C.    |          |        |               |         |             | SPEED IN |        | 25 25  | 40.40       |               | an er         |            |              |                |
| DIRECTION (DEGREES) | 1-4      | 5-9    | 10-14         | 15-19   | 20-24       | 25-29    | 30-34  | 35-39  | 40-49       | 50-64         | GE 65         | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 6.9      | 6.9    | 3.4           | •••••   | •••••       |          | •••••  | •••••  | •••••       | • • • • • • • | • • • • • • • | 17.2       | 5.9          | 6.0            |
| 020-040             | 1.7      | 3.4    |               |         |             |          |        |        |             |               |               | 5.2        | 4.7          | 5.0            |
| 050-070             |          |        |               |         |             |          |        |        |             |               |               |            |              |                |
| (E) 080-100         |          |        |               |         |             |          |        |        |             |               |               |            |              |                |
| 110-130             |          |        |               |         |             |          |        |        |             |               |               |            |              |                |
| 140-160             | 3.4      |        |               |         |             |          |        |        |             |               |               | 3.4        | 3.0          | 3.0            |
| (S) 170-190         | 5.2      | 8.6    |               |         |             |          |        |        |             |               |               | 13.8       | 5.3          | 5.5            |
| 200-220             | 24.1     | 8.6    | 1.7           |         |             |          |        |        |             |               |               | 34.5       | 3.9          | 3.0            |
| 230-250             | 3.4      | 1.7    |               |         |             |          |        |        |             |               |               | 5.2        | 3.3          | 2.0            |
| (W) 260-280         |          |        |               |         |             |          |        |        |             |               |               |            |              |                |
| 290-310             |          |        |               |         |             |          |        |        |             |               |               |            |              |                |
| 320-340             | 3.4      | 1.7    |               |         |             |          |        |        |             |               |               | 5.2        | 3.7          | 3.0            |
| VARIABLE            | [        |        | • • • • • • • | •••••   | • • • • • • |          | •••••  | •••••  | • • • • • • | •••••         | • • • • • • • | •••••      | • • • • • •  |                |
| CALM                | 11111111 | ////// | //////        | //////  | //////      | '//////  | ////// | ////// | ///////     | //////        | ///////       | 15.5       | /////        | /////          |
| TOTALS              | 48.1     | 30.9   | 5.1           |         |             |          |        |        |             |               |               | 100.0      | 3.8          | 4.0            |
|                     |          |        | TO            | TAL NUM | BER OF      | OBSERVA  | TIONS  | 58     |             |               |               |            |              |                |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

|                     |          | LS.         | T TO UT | 'C: - 9       |         |         |         |   | MONTH         | : JUL  | HOUE          | RS: 12-14 | ı            |                |
|---------------------|----------|-------------|---------|---------------|---------|---------|---------|---|---------------|--------|---------------|-----------|--------------|----------------|
|                     |          | • • • • • • |         | • • • • • • • | ייייי פ | PEED IN | KNOTS   |   | • • • • • • • |        | • • • • • • • |           |              | • • • • • • •  |
| DIRECTION (DEGREES) | 1-4      | 5-9         | 10-14   | 15-19         |         | 25-29   |         | 35-39                                   | 40-49         | 50-64  | GE 65         | TOTAL     | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 4.6      | 5.7         | 3.4     | •••••         | •••••   | •••••   | •••••   | •••••                                   | •••••         |        | •••••         | 13.8      | 6.5          | 6.0            |
| 020-040             | 3.4      | 2 3         |         |               |         |         |         |   |               |        |               | 5.7       | 4.6          | 4.0            |
| 050-070             |          |             |         |               |         |         |         |   |               |        |               |           |              |                |
| (E) 080-100         | 1.1      |             |         |               |         |         |         |   |               |        |               | 1.1       | 4.0          | 4.0            |
| 110-130             |          |             |         |               |         |         |         |   |               |        |               |           |              |                |
| 140-160             |          | 1.1         |         |               |         |         |         |   |               |        |               | 1.1       | 5.0          | 5.0            |
| (S) 170-190         | 6.9      | 9.2         |         |               |         |         |         |   |               |        |               | 16.1      | 4.8          | 5.0            |
| 200-220             | 13.8     | 5.7         | 2.3     |               |         |         |         |   |               |        |               | 21.8      | 4.6          | 4.0            |
| 230-250             | 6.9      | 4.6         |         |               |         |         |         |   |               |        |               | 11.5      | 4.7          | 4.0            |
| (W) 260-280         | 9.2      | 1.1         |         |               |         |         |         |   |               |        |               | 1(.3      | 3.2          | 4.0            |
| 290-310             | 2.3      | 1.1         |         |               |         |         |         |   |               |        |               | 3.4       | 4.7          | 4.0            |
| 320-340             | 8.0      |             |         |               |         |         |         |   |               |        |               | 8.0       | 2.3          | 2.0            |
| VARIABLE            | <br>     |             |         | · · · · · ·   |         |         |         | • |               |        | •••••         |           |              |                |
| marine a consultat  |          |             |         |               |         |         |         |   |               |        |               |           |              |                |
| CALM                | 11111111 | //////      | //////  | //////        | 1111111 | 1/////  | 11/1/1/ | ///////                                 | //////        | ////// | 1/////        | 6.9       | //////       | /////          |
| TOTALS              | 56.2     | 30.8        | 5.7     |               |         |         |         |   |               |        |               | 100.0     | 4.3          | 4.0            |

TOTAL NUMBER OF OBSERVATIONS 87

### OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED USAFETAC, ASHEVILLE NC FROM HOURLY OBSERVATIONS FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO NGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: JUL HOURS: 15-17 LST TO UTC: - 9

|                     |         |        |        |        | WIND S | SPEED IN | KNOTS  |         |         |        |        |             |              |                |
|---------------------|---------|--------|--------|--------|--------|----------|--------|---------|---------|--------|--------|-------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4     | 5-9    | 10-14  | 15-19  | 20-24  | 25-29    | 30-34  | 35-39   | 40-49   | 50-64  | GF 65  | ТОТАТ,<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
|                     |         |        |        |        |        |          |        |         |         |        |        | <i></i>     |              |                |
| (N) 350-010         | 2.3     | 6.9    | 2.3    |        |        |          |        |         |         |        |        | 11.5        | 7.4          | 7.5            |
| 020-040             | 1.1     |        |        |        |        |          |        |         |         |        |        | 1.1         | 4.0          | 4.0            |
| 050-070             | 1.1     |        |        |        |        |          |        |         |         |        |        | 1.1         | 2.0          | 2.0            |
| (E) 080-100         |         |        |        |        |        |          |        |         |         |        |        |             |              |                |
| 110-130             | 1.1     |        |        |        |        |          |        |         |         |        |        | 1.1         | 3.0          | 3.0            |
| 140-160             | 1.1     | 1.1    |        |        |        |          |        |         |         |        |        | 2.3         | 5.0          | 5.0            |
| (S) 170-190         | 2.3     | 1.1    |        |        |        |          |        |         |         |        |        | 3.4         | 3.0          | 2.0            |
| 200-220             | 6.9     | 18.4   | 3.4    |        |        |          |        |         |         |        |        | 28.7        | 6.2          | 6.0            |
| 230-250             | 9.2     | 3.4    |        |        |        |          |        |         |         |        |        | 12.6        | 3.3          | 3.0            |
| (W) 260-280         | 1.1     | 5.7    |        |        |        |          |        |         |         |        |        | 6.9         | 6.0          | 6.0            |
| 290-310             | 6.9     | 3.4    |        |        |        |          |        |         |         |        |        | 10.3        | 3.6          | 4.0            |
| 320-340             | 6.9     | 2.3    |        |        |        |          |        |         |         |        |        | 9.2         | 3.4          | 3.5            |
|                     | ¦<br>   |        |        |        |        |          |        |         |         |        |        |             |              |                |
| VARIABLE            |         |        |        |        |        |          |        |         |         | ,      |        |             |              | •              |
| CALM                | 1111111 | ////// | ////// | ////// | ////// | ///////  | ////// | /////// | /////// | ////// | 111111 | // 11.5     | /////        | /////          |
| TOTALS              | 40.0    | 42.3   | 5.7    |        |        |          |        |         |         |        |        | 100.0       | 4.4          | 5.0            |

TOTAL NUMBER OF OBSERVATIONS 87 ......

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL HOURS: 18-20

|                     |                 | LS     | T TO UT       | °C: - 9       |         |         |        |               | MONTH  | ։ յսւ   | HOUR    | S: 18-20        | )            |                |
|---------------------|-----------------|--------|---------------|---------------|---------|---------|--------|---------------|--------|---------|---------|-----------------|--------------|----------------|
|                     | • • • • • • • • |        | • • • • • • • |               |         | PEED IN | WNOTE  | • • • • • • • |        |         | •••••   |                 | • • • • • •  |                |
| DIRECTION (DEGREES) | 1-4             | 5-9    | 10-14         | 15-19         |         | 25-29   |        | 35-39         | 40-49  | 50-64   | GE 65   | TOTAL<br>%      | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 1.1             | 8.0    |               | • • • • • • • | •••••   | •••••   |        |               | •••••  |         | •••••   | 9.2             | 7.0          | 7.5            |
| 020-040             | 2.3             |        |               |               |         |         |        |               |        |         |         | 2.3             | 3.0          | 3.0            |
| 050-070             | 2.3             |        |               |               |         |         |        |               |        |         |         | 2.3             | 2.0          | 2.0            |
| (E) 080-100         |                 |        |               |               |         |         |        |               |        |         |         |                 |              |                |
| 110-130             | 2.3             |        |               |               |         |         |        |               |        |         |         | 2.3             | 1.5          | 1.5            |
| 140-160             | 1.1             |        |               |               |         |         |        |               |        |         |         | 1.1             | 3.0          | 3.0            |
| (S) 170-190         | 3.4             |        |               |               |         |         |        |               |        |         |         | 3.4             | 1.7          | 2.0            |
| 200-220             | 14.9            | 5.7    |               |               |         |         |        |               |        |         |         | 20.7            | 3.2          | 2.5            |
| 230-250             | 13.8            | 9.2    |               |               |         |         |        |               |        |         |         | 23.0            | 3.6          | 3.0            |
| (W) 260-280         | 6.9             | 1.1    |               |               |         |         |        |               |        |         |         | 8.0             | 2.9          | 2.0            |
| 290-310             | 3.4             |        |               |               |         |         |        |               |        |         |         | 3.4             | 2.0          | 1.0            |
| 320-340             | 6.9             | 1.1    |               |               |         |         |        |               |        |         |         | 8.0             | 2.6          | 2.0            |
| VARIABLE            | !<br><br>       |        | · · · · · · · |               |         |         |        |               |        |         |         | • • • • • • • • |              | •••••          |
| CALM                | 11111111        | ////// | //////        | ////////      | 11/1/// | /////// | ////// | ////////      | ////// | /////// | 1111111 | 16.1            | /////        | /////          |
| TOTALS              | 58.4            | 25.1   |               |               |         |         |        |               |        |         |         | 100.0           | 2.9          | 2.0            |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LCT TO UTC: 9 MONTH: JUL HOURS: 21-23

| DIRECTION (DEGREES) (N) 350-010 020-040 050-070 | 1-4      |       |               | 15-19         | WIND S | SPEED IN<br>25-29 |               | 35-39  | 40-49       | 50-64  | GE 65                                   | TOTAL | MFAN<br>WIND | MEDIAN<br>WIND |
|---|----------|-------|---------------|---------------|--------|-------------------|---------------|--------|-------------|--------|---|-------|--------------|----------------|
| (N) 350-010   020-040                           | 6.9      |       | 1.1           |               |        |                   | <i>.</i>      |        |             |        |   | 8     | WIND         | WIND           |
| 020-040   | 6.9      |       | 1.1           | • • • • • • • |        |                   | • • • • • • • |        |             |        |   |       |              | MIND           |
|   |          | 1.1   | 1.1           |               |        |                   |               |        | • • • • • • |        | • | 11.5  | 2.2          | 1.5            |
| 050-070   | 1.1      |       |               |               |        |                   |               |        |             |        |   | 9.2   | 4.1          | 3.0            |
|   |          |       |               |               |        |                   |               |        |             |        |   | 1.1   | 2.0          | 2.0            |
| (E) 080-100                                     |          |       |               |               |        |                   |               |        |             |        |   |       |              |                |
| 110-130   | 1.1      |       |               |               |        |                   |               |        |             |        |   | 1.1   | 3.0          | 3.0            |
| 140-160   |          |       |               |               |        |                   |               |        |             |        |   |       |              |                |
| (S) 170-190                                     | 3.4      |       |               |               |        |                   |               |        |             |        |   | 3.4   | 2.3          | 2.0            |
| 200-220   | 12.5     |       |               |               |        |                   |               |        |             |        |   | 12.6  | 1.7          | 1.0            |
| 230-250   | 1.1      |       |               |               |        |                   |               |        |             |        |   | 1.1   | 2.0          | 2.0            |
| (W) 260-280                                     | 1.1      |       |               |               |        |                   |               |        |             |        |   | 1.1   | 3.0          | 3.0            |
| 290-310   |          |       |               |               |        |                   |               |        |             |        |   |       |              |                |
| 320-340   | 5.7      | 1.1   |               |               |        |                   |               |        |             |        |   | 6.9   | 3.7          | 4.0            |
| VARIABLE  |          |       | • • • • • • • |               |        |                   | • • • • • • • |        | • • • • • • |        |   |       | • • • • • •  |                |
| CALM /  | //////// | ///// | //////        | //////        | ////// | 1//////           | //////        | ////// | //////      | ////// | 7//////                                 | 51.7  | /////        | /////          |
| TOTALS  | 43.3     | 3.3   | 1.1           |               |        |                   |               |        |             |        |   | 100.0 | 1.3          | 2.0            |
|   |          |       | <b>'TY</b> C  | TAL NUM       |        |                   |               |        |             |        |   |       |              |                |

### FERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL HOURS: ALL

|             |                                       | LS      | T TO UT | 'C: - 9       |        |          |         |                 | MONTE       | i: JUL      | HOUR            | S: ALL        |        |               |
|-------------|---------------------------------------|---------|---------|---------------|--------|----------|---------|-----------------|-------------|-------------|-----------------|---------------|--------|---------------|
|             |                                       |         |         | • • • • • • • |        | SPEED IN |         | · · · · · · · · |             | • • • • • • |                 |               |        | • • • • • • • |
| DIRECTION   | '                                     |         |         |               | 20-24  | 25-29    | 30-34   | 35-39           | 40-49       | 50-64       | GE 65           | TOTAL         | MEAN   | MEDIAN        |
| (DEGREES)   |                                       |         |         |               |        |          |         |                 | •••••       |             |                 | 8             | WIND   | WIND          |
| (N) 350-010 | /.1                                   | 4.º     | 1,3     | • • • • • • • |        |          |         |                 | • • • • • • |             | • • • • • • • • | 13.3          | 4.8    | 4.0           |
| ,           |                                       | • • •   |         |               |        |          |         |                 |             |             |                 | 13.3          | 4.0    | 4.0           |
| 27()=1:4:1  | 1.8                                   | .9      | . 3     |               |        |          |         |                 |             |             |                 | 5.0           | 3.4    | 3.0           |
| 950-079     | 1.0                                   | .3      |         |               |        |          |         |                 |             |             |                 | 1.3           | 2.9    | 2.0           |
| (E) 080-100 | .3                                    |         |         |               |        |          |         |                 |             |             |                 | .3            | 4.0    | 4.0           |
| 110-130     | .6                                    |         |         |               |        |          |         |                 |             |             |                 | .6            | 2.3    | 2.5           |
| 140-160     | .6                                    | . 3     |         |               |        |          |         |                 |             |             |                 | .9            | 4.0    | 4.0           |
| (S) 170-190 | 3.7                                   | 3.4     | .4      |               |        |          |         |                 |             |             |                 | 7.5           | 4.7    | 5.0           |
| 200-220     | 11.7                                  | 4.9     | .9      |               |        |          |         |                 |             |             |                 | 17.5          | 3.8    | 3.0           |
| 230-250     | 4.4                                   | 2.4     |         |               |        |          |         |                 |             |             |                 | 6.8           | 3.7    | 3.5           |
| (W) 260-280 | 2.4                                   | 1.0     |         |               |        |          |         |                 |             |             |                 | 3.4           | 3.8    | 4.0           |
| 290-310     | 1.8                                   | .6      |         |               |        |          |         |                 |             |             |                 | 2.4           | 3.3    | 3.5           |
| 320-340     | 6.8                                   | 1.3     | . 1     |               |        |          |         |                 |             |             |                 | 8.3           | 3.1    | 2.0           |
|             | · · · · · · · · · · · · · · · · · · · |         |         |               |        |          |         |                 |             |             |                 | • • • • • • • |        |               |
| VARIABLE    | 1                                     |         |         |               |        |          |         |                 |             |             |                 |               |        |               |
| MIAD        | 1//////                               | (1/1/1/ | /////// | 7//////       | ////// | (/////// | 11/1/// | ////////        | '//////     | ///////     | ////////        | 32.7          | ////// | /////         |
| TOTALS      | 44.2                                  | 20.0    | 3.0     |               |        |          |         |                 |             |             |                 | 100.0         | 2.7    | 3.0           |
|             |                                       |         | TO      | YEAL NUM      | BER OF | OBSERVA  | TIONS   | 676             |             |             |                 |               |        |               |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

MONTH: JUL HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS). AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

......

|             |          |           |             |         |         | PEED IN |               |         |               |         |         |           |       |        |        |
|-------------|----------|-----------|-------------|---------|---------|---------|---------------|---------|---------------|---------|---------|-----------|-------|--------|--------|
| DIRECTION   | 1-4      | 5-9       | 10-14       | 15-19   | 20-24   | 25-29   | 30-34         | 35-39   | 40-49         | 50-64   | GE      | 65        | TOTAL | MEAN   | MEDIAN |
| (DEGREES)   | <br>     |           |             |         |         |         | •••••         |         |               | •••••   | • • • • |           | 8     | WIND   | WIND   |
| (N) 350-010 | 5.4      | 4.3       | 1.1         |         |         | •••••   | • • • • • • • |         | • • • • • •   | •••••   | • • • • | • • • • • | 10.9  | 5.0    | 5.0    |
| 020-040     | 3.3      | 2.2       |             |         |         |         |               |         |               |         |         |           | 5.4   | 4.0    | 4.0    |
| 050-070     | 1.1      |           |             |         |         |         |               |         |               |         |         |           | 1.1   | 2.0    | 2.0    |
| (E) 080-100 | 1.1      |           |             |         |         |         |               |         |               |         |         |           | 1.1   | 4.0    | 4.0    |
| 110-130     | 2.2      |           |             |         |         |         |               |         |               |         |         |           | 2.2   | 2.5    | 2.5    |
| 140-160     | 1.1      | 1.1       |             |         |         |         |               |         |               |         |         |           | 2.2   | 4.5    | 4.5    |
| (S) 170-190 | 2.2      | 2.2       |             |         |         |         |               |         |               |         |         |           | 4.3   | 3.8    | 4.0    |
| 200-220     | 17.4     | 5.4       |             |         |         |         |               |         |               |         |         |           | 22.8  | 3.0    | 2.0    |
| 230-250     | 1.1      |           |             |         |         |         |               |         |               |         |         |           | 1.1   | 1.0    | 1.0    |
| (W) 260-280 | 1.1      |           |             |         |         |         |               |         |               |         |         |           | 1.1   | 3.0    | 3.0    |
| 290-310     | 2.2      |           |             |         |         |         |               |         |               |         |         |           | 2.2   | 2.5    | 2.5    |
| 320-340     | 6.5      | 1.1       |             |         |         |         |               |         |               |         |         |           | 7.6   | 2.7    | 3.0    |
| VARIABLE    | :        | • • • • • | • • • • • • | •••••   | •••••   | •••••   | •••••         |         | • • • • • • • | ******  |         |           |       | •••••  |        |
| CALM        | 11111111 | /////     | //////      | /////// | /////// | /////// | 1111111       | /////// | //////        | /////// | ////    | ////      | 38.0  | ////// | /////  |
| TOTALS      | 44.7     | 16.3      | 1.1         |         |         |         |               |         |               |         |         |           | 100.0 | 2.1    | 3.0    |

TOTAL NUMBER OF OBSERVATIONS 92

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

TOTALS

48.5

8.6

STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9

PERIOD OF RECORD: JUL 80 - JUN 90 HOURS: 00-02 MONTH: AUG

WIND SPEED IN KNOTS DIRECTION 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) WIND WIND 8 ...... (N) 350-010 18.3 020-040 10.8 10.8 1.7 1.5 050-070 2.2 1.1 3.2 4.0 4.0 (E) 080-100 110-130 140-160 (S) 170-190 200-220 230-250 (W) 260-280 290~310 17.2 17.2 2.6 2.0 320-340 VARIABLE CALM

> TOTAL NUMBER OF OBSERVATIONS 93

100.0

1.6

2.0

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

| ornaron nonzo                           |                   | LS    | T TO UT     | C: - 9  | 0           | ,,, 101,02 |               | .0                                      | MONTH       | : AUG                                   | HOUR          | s: 03-05      | 5            | •              |
|---|-------------------|-------|-------------|---------|-------------|------------|---------------|---|-------------|---|---------------|---------------|--------------|----------------|
| • | • • • • • • • • • |       | • • • • • • | •••••   | WIND S      | SPEED IN   | KNOTS         | •••••                                   |             | • • • • • • •                           | • • • • • • • | • • • • • • • |              | •••••          |
| DIRECTION (DEGREES)                     | 1-4               | 5-9   | 10-14       | 15-19   | 20-24       | 25-29      | 30-34         | 35-39                                   | 40-49       | 50-64                                   | GE 65         | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 18.3              |       | 1.1         | 1.1     | • • • • • • | •••••      | • • • • • • • | •••••                                   | • • • • • • | •••••                                   | • • • • • •   | 20.4          | 3.4          | 2.0            |
| 020-040                                 | 6.5               | 1.1   |             | 1.1     |             |            |               |   |             |   |               | 8.6           | 3.9          | 2.0            |
| 050-070                                 | 4.3               |       |             |         |             |            |               |   |             |   |               | 4.3           | 2.3          | 2.0            |
| (E) 080-100                             |                   |       |             |         |             |            |               |   |             |   |               |               |              |                |
| 110-130                                 | 1.1               |       |             |         |             |            |               |   |             |   |               | 1.1           | 2.0          | 2.0            |
| 140-160                                 |                   |       |             |         |             |            |               |   |             |   |               |               |              |                |
| (S) 170-190                             |                   |       |             |         |             |            |               |   |             |   |               |               |              |                |
| 200-220                                 | 4.3               | 1.1   |             |         |             |            |               |   |             |   |               | 5.4           | 2.4          | 2.0            |
| 230-250                                 |                   |       |             |         |             |            |               |   |             |   |               |               |              |                |
| (W) 260-280                             |                   |       |             |         |             |            |               |   |             |   |               |               |              |                |
| 290-310                                 |                   |       |             |         |             |            |               |   |             |   |               |               |              |                |
| 320-340                                 | 22.6              | 2.2   |             |         |             |            |               |   |             |   |               | 24.7          | 2.7          | 3.0            |
| VARIABLE                                | )<br>             |       |             |         |             |            |               | • |             | • |               | • • • • • • • |              | •••••          |
| CALM                                    | <br> /////////    | ///// | ///////     | 1111111 | ///////     | '///////   | 1111111       | 1111111                                 | 1111111     | 1111111                                 | 1111111       | 35.5          | //////       | /////          |
| TOTALS                                  | 57.1              | 4.4   | 1.1         | 2.2     |             |            |               |   |             |   |               | 100.0         | 1.9          | 2.0            |
|   | 1                 |       |             |         | men oe      | ODGEDUA    | m tone        | 03                                      |             |   |               |               |              |                |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO
LST TO UTC: - 9

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: AUG HOURS: 06-08

|                     |  | LS     | T TO UT       | C: - 9 |             |               |               |         | MONTE         | I: AUG  | HOUR    | S: 06-08      | 3            |                |
|---------------------|--|--------|---------------|--------|-------------|---------------|---------------|---------|---------------|---------|---------|---------------|--------------|----------------|
| ***********         | • • • • • • • • •                          | •••••  | • • • • • • • |        | WIND S      | SPEED IN      | KNOTS         |         |               | •••••   | •••••   | • • • • • •   |              | • • • • • •    |
| DIRECTION (DEGREES) | 1-4  | 5-9    | 10-14         | 15-19  |             | 25-29         |               | 35-39   | 40-49         | 50-64   | GE 65   | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 22.6                                       | 1.1    | 3.2           | 1.1    | • • • • • • | • • • • • • • | • • • • • • • |         | • • • • • • • | •••••   | •••••   | 28.0          | 4.1          | 2.5            |
| 020-040             | 3.2  | 1.1    |               |        |             |               |               |         |               |         |         | 4.3           | 3.3          | 3.0            |
| 050-070             | 1.1  |        |               |        |             |               |               |         |               |         |         | 1.1           | 1.0          | 1.0            |
| (E) 080-100         |  |        |               |        |             |               |               |         |               |         |         |               |              |                |
| 110-130             |  |        |               |        |             |               |               |         |               |         |         |               |              |                |
| 140-160             | 1.1  |        |               |        |             |               |               |         |               |         |         | 1.1           | 1.0          | 1.0            |
| (S) 170-190         | 4.3  |        | 1.1           |        |             |               |               |         |               |         |         | 5.4           | 4.0          | 3.0            |
| 200-220             | 3.2  |        | 1.1           |        |             |               |               |         |               |         |         | 4.3           | 4.3          | 3.0            |
| 230-250             |  |        |               |        |             |               |               |         |               |         |         |               |              |                |
| (W) 260-280         | 1.1  |        |               |        |             |               |               |         |               |         |         | 1.1           | 1.0          | 1.0            |
| 290-310             |  |        |               |        |             |               |               |         |               |         |         |               |              |                |
| 320-340             | 19.4                                       |        |               |        |             |               |               |         |               |         |         | 19.4          | 2.2          | 2.0            |
| VARIABLE            | 1<br>• • • • • • • • • • • • • • • • • • • |        | • • • • • •   |        | • • • • • • |               |               |         |               |         | •••••   | • • • • • • • |              | • • • • • • •  |
| VARIABLE            |  |        |               |        |             |               |               |         |               |         |         |               |              |                |
| CALM                | 11111111                                   | '///// | //////        | ////// | //////      | ///////       | ///////       | '////// | 1111111       | '////// | /////// | 35.5          | /////        | /////          |
| TOTALS              | 56.0                                       | 2.2    | 5.4           | 1.1    |             |               |               |         |               |         |         | 100.0         | 2.1          | 2.0            |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9 PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: AUG HOURS: 09-11

|   |                 |             |        | -                                       |        |               |               |             |         |        |               |            | •            |                |
|---|-----------------|-------------|--------|---|--------|---------------|---------------|-------------|---------|--------|---------------|------------|--------------|----------------|
| • | • • • • • • • • | • • • • • • | •••••  | •••••                                   | WIND S | SPEED IN      | KNOTS         |             |         | *****  |               |            |              |                |
| DIRECTION (DEGREES)                     | 1-4             | 5-9         | 10-14  | 15-19                                   | 20-24  | 25-29         | 30-34         | 35-39       | 40-49   | 50-64  | GE 65         | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 6.5             | 8.1         | 1.6    | •••••                                   |        |               | • • • • • • • | • • • • • • |         |        | • • • • • • • | 16.1       | 5.6          | 6.0            |
| 020-040                                 | 1.6             | 6.5         |        |   |        |               |               |             |         |        |               | 8.1        | 6.4          | 8.0            |
| 050-070                                 |                 | 4.8         | 1.6    |   |        |               |               |             |         |        |               | 6.5        | 8.0          | 7.0            |
| (E) 080-100                             | 3.2             | 1.6         |        |   |        |               |               |             |         |        |               | 4.8        | 4.0          | 4.0            |
| 110-130                                 |                 |             |        |   |        |               |               |             |         |        |               |            |              |                |
| 140-160                                 | 1.6             |             |        |   |        | •             |               |             |         |        |               | 1.6        | 4.0          | 4.0            |
| (S) 170-190                             | 4.8             | 1.6         |        |   |        |               |               |             |         |        |               | 6.5        | 4.0          | 4.0            |
| 200-220                                 | 16.1            | 3.2         |        |   |        |               |               |             |         |        |               | 19.4       | 3.1          | 3.0            |
| 230-250                                 | 1.6             | 1.6         |        |   |        |               |               |             |         |        |               | 3.2        | 3.5          | 3.5            |
| (W) 260-280                             | 1.6             |             |        |   |        |               |               |             |         |        |               | 1.6        | 2.0          | 2.0            |
| 290-310                                 | 4.8             |             |        |   |        |               |               |             |         |        |               | 4.8        | 2.3          | 2.0            |
| 320-340                                 | 12.9            |             |        |   |        |               |               |             |         |        |               | 12.9       | 2.9          | 3.0            |
| VARIABLE                                | `<br>           | 1.6         | 1.6    | • | •••••  | • • • • • • • |               | • • • • • • |         | •••••  |               | 3.2        | 9.0          | 9.0            |
| CALM                                    | 1111111         | //////      | ////// | ///////                                 | ////// | ////////      | 1111111       | ///////     | /////// | ////// | ////////      | 11.3       | /////        | /////          |
| TOTALS                                  | 54.7            | 29.0        | 4.8    |   |        |               |               |             |         |        |               | 100.0      | 4.0          | 4.0            |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

|                     |          | LS          | TU OT         | 'C: - 9     |        |          |         |         | MONTH   | : AUG         | HOUR    | s: 12-14   | 1            |                |
|---------------------|----------|-------------|---------------|-------------|--------|----------|---------|---------|---------|---------------|---------|------------|--------------|----------------|
|                     |          | • • • • • • | • • • • • • • | • • • • • • | WIND S | SPEED IN | KNOTS   |         | •••••   | • • • • • • • | •••••   |            | • • • • • •  | • • • • • • •  |
| DIRECTION (DEGREES) | 1-4      | 5-9         | 10-14         | 15-19       | 20-24  | 25-29    | 30-34   | 35-39   | 40-49   | 50-64         | GE 65   | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 3.2      | 4.3         | •••••         |             | •••••  | •••••    | •••••   |         | •••••   | • • • • • • • | •••••   | 7.5        | 5.3          | 6.0            |
| 020-040             | 3.2      | 4.3         | 1.1           |             |        |          |         |         |         |               |         | 8.6        | 6.6          | 6.5            |
| 050-070             | 1.1      | 4.3         |               |             |        |          |         |         |         |               |         | 5.4        | 6.4          | 7.0            |
| (E) 080-100         | 3.2      | 1.1         | 2.2           |             |        |          |         |         |         |               |         | 6.5        | 5.2          | 3.5            |
| 110-130             | 4.3      |             |               |             |        |          |         |         |         |               |         | 4.3        | 3.0          | 3.0            |
| 140-160             | į<br>j   | 3.2         | 1.1           |             |        |          |         |         |         |               |         | 4.3        | 7.8          | 8.0            |
| (S) 170-190         | 2.2      | 3.2         |               |             |        |          |         |         |         |               |         | 5.4        | 4.4          | 5.0            |
| 200-220             | 8.6      | 6.5         |               |             |        |          |         |         |         |               |         | 15.1       | 4.1          | 4.0            |
| 230-250             | 5.4      | 2.2         |               |             |        |          |         |         |         |               |         | 7.5        | 3.6          | 4.0            |
| (W) 260-280         | 4.3      |             |               |             |        |          |         |         |         |               |         | 4.3        | 2.0          | 1.5            |
| 290-310             | 3.2      |             |               |             |        |          |         |         |         |               |         | 3.2        | 2.3          | 2.0            |
| 320-340             | 10.8     | 1.1         |               |             |        |          |         |         |         |               |         | 11.8       | 3.4          | 4.0            |
|                     | !<br>    |             |               |             |        |          |         |         |         |               |         |            | . <b></b>    |                |
| VARIABLE            |          | 3.2         | 3.2           |             |        |          |         |         |         |               |         | 6.5        | 8.8          | 9.0            |
| CALM                | 11111111 | //////      | //////        | //////      | ////// | ///////  | /////// | /////// | 1111111 | 1111111       | /////// | 9.7        | /////        | /////          |
| TOTALS              | 49.5     | 33.4        | 7.6           |             |        |          |         |         |         |               |         | 100.0      | 4.4          | 4.0            |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERTOD OF RECORD: JUL 80 - JUN 90 MONTH: AUG HOURS: 15-17

LST TO UTC: - 9

|                     |                      |        | • • • • • • |             | WIND S | PEED IN | KNOTS   | • • • • • • |               | •••••   | • • • • • •   | • • • • • • | • • • • • •  | • • • • • • •  |
|---------------------|----------------------|--------|-------------|-------------|--------|---------|---------|-------------|---------------|---------|---------------|-------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4                  | 5-9    | 10-14       | 15~19       |        | 25-29   |         | 35-39       | 40-49         | 50-64   | GE 65         | TOTAL<br>%  | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 6.5                  | 6.5    | • • • • • • | • • • • • • | •••••  |         |         | •••••       | • • • • • • • | •••••   | • • • • • • • | 12.9        | 5.3          | 4.5            |
| 020-040             | 3.2                  | 7.5    |             |             |        |         |         |             |               |         |               | 10.8        | 5.0          | 5.5            |
| 050-670             | 2.2                  | 1.1    |             |             |        |         |         |             |               |         |               | 3.2         | 4.0          | 4.0            |
| (E) 080-100         | 1.1                  | 2.2    | 1.1         |             |        | •       |         |             |               |         |               | 4.3         | 6.5          | 5.5            |
| 110-130             | 2.2                  |        |             |             |        |         |         |             |               |         |               | 2.2         | 3.0          | 3.0            |
| 140-160             | 1.1                  | 1.1    |             |             |        |         |         |             |               |         |               | 2.2         | 5.0          | 5.0            |
| (S) 170-190         | 3.2                  | 3.2    |             |             |        |         |         |             |               |         |               | 6.5         | 4.2          | 4.5            |
| 200-220             | 5.4                  | 11.8   | 1.1         |             |        |         |         |             |               |         |               | 18.3        | 5.4          | 5.0            |
| 230-250             | 6.5                  | 2.2    |             |             |        |         |         |             |               |         |               | 8.6         | 3.6          | 3.0            |
| (W) 260-280         | 4.3                  |        |             |             |        |         |         |             |               |         |               | 4.3         | 2.5          | 2.5            |
| 290-310             | 6.5                  |        |             |             |        |         |         |             |               |         |               | 6.5         | 2.0          | 2.0            |
| 320-340             | 2.2                  | 4.3    |             |             |        |         |         |             |               |         |               | 6.5         | 4.5          | 5.0            |
|                     | ;<br>: • • • • • • • |        |             |             |        |         |         |             |               |         |               |             |              |                |
| VARIABLE            | ĺ                    | 4.3    | 3.2         |             |        |         |         |             |               |         |               | 7.5         | 8.9          | 9.0            |
| CATM                | 11111111             | ////// | ///////     | //////      | 7///// | /////// | /////// | ///////     | ///////       | /////// | ///////       | 6.5         | /////        | 111111         |
| TOTALS              | 44.4                 | 44.2   | 5.4         |             |        |         |         |             |               |         |               | 100.0       | 4.5          | 5.0            |
|                     |                      |        |             |             |        |         |         |             |               |         |               |             |              |                |

TOTAL NUMBER OF OBSERVATIONS 93 ......

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471055

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: AUG HOURS: 18-20

| LST TO | OUTC: | _ | 9 | MONTH: | ΑU |
|--------|-------|---|---|--------|----|

|                     |                   | ь       | 1 10 01 | C 3           |        |          |        |         | PONTE   | i. Aug  | noon    | w. 10-20   | ,            |                |
|---------------------|-------------------|---------|---------|---------------|--------|----------|--------|---------|---------|---------|---------|------------|--------------|----------------|
| •••••               | • • • • • • • • • |         | •••••   | • • • • • • • | WIND S | SPEED IN | KNOTS  |         |         |         | •••••   |            |              | • • • • • • •  |
| DIRECTION (DEGREES) | 1-4               | 5-9     | 10-14   |               |        | 25-29    |        |         |         | 50-64   | GE 65   | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 7.5               | 15.1    | 1.1     | • • • · • •   |        |          | •••••  | •••••   | •••••   |         | •••••   | 23.7       | 5.5          | 6.0            |
| 020-040             | 2.2               | 4.3     |         |               |        |          |        |         |         |         |         | 6.5        | 4.3          | 5.5            |
| 050-070             | 2.2               |         |         |               |        |          |        |         |         |         |         | 2.2        | 2.0          | 2.0            |
| (E) 080-100         | 2.2               |         |         |               |        |          |        |         |         |         |         | 2.2        | 3.0          | 3.0            |
| 110-130             | 2.2               |         |         |               |        |          |        |         |         |         |         | 2.2        | 1.5          | 1.5            |
| 140-160             | 3.2               |         |         |               |        |          |        |         |         |         |         | 3.2        | 2.0          | 2.0            |
| (S) 170-190         | 2.2               |         |         |               |        |          |        |         |         |         |         | 2.2        | 4.0          | 4.0            |
| 200-220             | 9.7               | 2.2     |         |               |        |          |        |         |         |         |         | 11.8       | 2.9          | 3.0            |
| 230-250             | 7.5               | 2.2     |         |               |        |          |        |         |         |         |         | 9.7        | 3.1          | 3.0            |
| (W) 260-280         | 1.1               |         |         |               |        |          |        |         |         |         |         | 1.1        | 4.0          | 4.0            |
| 290-310             | 2.2               |         |         |               |        |          |        |         |         |         |         | 2.2        | 2.5          | 2.5            |
| 320-340             | 12.9              | 2.2     |         |               |        |          |        |         |         |         |         | 15.1       | 2.9          | 3.0            |
|                     | ,<br>             |         |         |               |        |          |        |         |         |         |         |            |              |                |
| VARIABLE            |                   | 1.1     |         |               |        |          |        |         |         |         |         | 1.1        | 7.0          | 7.0            |
| CALM                | 11111111          | 11/1/// | 1111111 | //////        | ////// | '//////  | ////// | /////// | 11/1/// | /////// | '////// | 17.2       | /////        | /////          |
| TOTALS              | 55.1              | 27.1    | 1.1     |               |        |          |        |         |         |         |         | 100.0      | 3.1          | 3.0            |
|                     |                   |         | Tro     | אוווא זמיז    | DED OF | ODGEDUA  | TTONE  | 0.2     |         |         |         |            |              |                |

TOTAL NUMBER OF OBSERVATIONS 93

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: AUG HOURS: 21-23

|   |                   | LS    | т то от     | 'C: - 9       |        |                   |             |               | HTYSOM      | : AUG       | HOUR    | s: 21-23      | 3            |                |
|---|-------------------|-------|-------------|---------------|--------|-------------------|-------------|---------------|-------------|-------------|---------|---------------|--------------|----------------|
| • | • • • • • • • • • |       | • • • • • • | • • • • • • • |        |                   | • • • • • • | • • • • • • • | • • • • • • | • • • • • • |         | • • • • • • • | • • • • • •  | • • • • • • •  |
| DIRECTION (DEGREES)                     | 1-4               | 5-9   | 10-14       | 15-19         |        | SPEED IN<br>25-29 |             | 35-39         | 40-49       | 50-64       | GE 65   | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 19.4              | 4.3   |             | •••••         | •••••• | •••••             | • • • • • • |               |             | •••••       |         | 23.7          | 3.1          | 3.0            |
| 020-040                                 | 9.7               | 1.1   |             |               |        |                   |             |               |             |             |         | 10.8          | 2.3          | 2.0            |
| 050-070                                 |                   | 1.1   |             |               |        |                   |             |               |             |             |         | 1.1           | 9.0          | 9.0            |
| (E) 080-100                             |                   |       |             |               |        |                   |             |               |             |             |         |               |              |                |
| 110-130                                 | 1.1               |       |             |               |        |                   |             |               |             |             |         | 1.1           | 1.0          | 1.0            |
| 140-160                                 | 2.2               |       |             |               |        |                   |             |               |             |             |         | 2.2           | 1.5          | 1.5            |
| (S) 170-190                             | 1.1               |       |             |               |        |                   |             |               |             |             |         | 1.1           | 1.0          | 1.0            |
| 200-220                                 | 5.4               |       |             |               |        | •                 |             |               |             |             |         | 5.4           | 2.4          | 2.0            |
| 230-250                                 | 1.1               |       |             |               |        |                   |             |               |             |             |         | 1.1           | 1.0          | 1.0            |
| (W) 260-280                             | 1.1               |       |             |               |        |                   |             |               |             |             |         | 1.1           | 1.0          | 1.0            |
| 290-310                                 |                   |       |             |               |        |                   |             |               |             |             |         |               |              |                |
| 320-340                                 | 11.8              |       |             |               |        |                   |             |               |             |             |         | 11.8          | 2.4          | 2.0            |
|   | 1                 |       |             |               |        |                   |             |               |             |             |         |               |              |                |
| VARIABLE                                |                   |       |             |               |        |                   |             |               |             |             |         |               |              |                |
| CALM                                    | 111111111         | ///// | //////      | '//////       | 111111 | ////////          | 1111111     | //////        | '//////     | //////      | '////// | 40.9          | /////        | /////          |
| TOTALS                                  | 52.9              | 6.5   |             |               |        |                   |             |               |             |             |         | 100.0         | 1.6          | 2.0            |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: AUG HOURS: ALL

LST TO UTC: - 9

WIND SPEED IN KNOTS DIRECTION | 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) (N) 350-010 13.0 5.8 .8 .3 19.9 4.2 3.0 020-040 5.2 3.1 4.0 4.0 .1 .1 8.6 050-070 .1 4.8 1.7 1.4 3.2 4.0 (E) 080-100 1.1 .6 . 4 2.1 5.0 110-130 1.4 1.4 2.4 2.0 140-160 1.1 .6 .1 1.8 4.2 3.0 (S) 170-190 2.1 4.0 1.0 3.2 4.0 .1 200-220 6.2 3.1 .3 9.5 3.8 4.0 230-250 2.8 1.0 3.8 3.3 3.0 (W) 260-280 1.7 1.7 2.2 2.0 290-310 2.0 2.0 2.2 2.0 320-340 15.0 3.0 VARIABLE 1.3 1.0 2.2 8.8 8.5 CALM TOTALS 52.0 19.2 2.9 100.0 2.9

TOTAL NUMBER OF OBSERVATIONS 713

USAFETAC, ASHEVILLE NC

#### OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

............

MONTH: AUG HOURS: ALL LST TO UTC: ~ 9

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS). AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

|             |           |           |               |         |             | PEED IN |             |         |               |         |                   |       |       |        |
|-------------|-----------|-----------|---------------|---------|-------------|---------|-------------|---------|---------------|---------|-------------------|-------|-------|--------|
| DIRECTION   | 1-4       | 5-9       | 10-14         | 15-19   | 20-24       | 25-29   | 30-34       | 35-39   | 40-49         | 50-64   | GE 65             | TOTAL | MEAN  | MEDIAN |
| (DEGREES)   |           |           | • • • • • •   |         | • • • • • • | •••••   | • • • • • • | •••••   | • • • • • • • | •••••   |                   | *     | WIND  | WIND   |
| (N) 350-010 | 4.3       | .9        | • • • • • • • |         | •••••       | •••••   | • • • • • • | •••••   | •••••         | •••••   | • • • • • • •     | 5.1   | 3.5   | 3.5    |
| 020-040     | 1.7       | .9        |               |         |             |         |             |         |               |         |                   | 2.6   | 3.3   | 2.0    |
| 050-070     | .9        |           |               |         |             |         |             |         |               |         |                   | .9    | 4.0   | 4.0    |
| (E) 080-100 | l<br>     |           |               |         |             |         |             |         |               |         |                   |       |       |        |
| 110-130     | 1.7       |           |               |         |             |         |             |         |               |         |                   | 1.7   | 3.0   | 3.0    |
| 140-160     | 2.6       |           |               |         |             |         |             |         |               |         |                   | 2.6   | 2.7   | 2.0    |
| (S) 170-190 | 6.0       | 2.6       |               |         |             |         |             |         |               |         |                   | 8.5   | 3.8   | 4.0    |
| 200-220     | 16.2      | .9        |               |         |             |         |             |         |               |         |                   | 17.1  | 2.5   | 2.0    |
| 230-250     | 2.6       |           |               |         |             |         |             |         |               |         |                   | 2.6   | 2.0   | 2.0    |
| (W) 260-280 | .9        |           |               |         |             |         |             |         |               |         |                   | .9    | 1.0   | 1.0    |
| 290-310     | .9        |           |               |         |             |         |             |         |               |         |                   | .9    | 3.0   | 3.0    |
| 320-340     | 8.5       |           |               |         |             |         |             |         |               |         |                   | 8.5   | 1.9   | 2.0    |
| VARIABLE    | <br>      | · • • • • | •••••         |         |             | •••••   |             | •••••   | • • • • • • • | •••••   | · · · · · · · · · | ••••• | ••••• | •••••  |
| CALM        | 111111111 | /////     | //////        | 1111111 | ///////     | 1111111 | //////      | 1111111 | //////        | 1111111 | ///////           | 48.7  | ///// | /////  |
| TOTALS      | 46.3      | 5.3       |               |         |             |         |             |         |               |         |                   | 100.0 | 1.4   | 2.0    |

TOTAL NUMBER OF OBSERVATIONS 117

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: SEP HOURS: 00-02

LST TO UTC: - 9

|   |          | PS     | T 10 01       | C: - 9  |             |             |             |               | MONTE         | i: SEP  | HOUR    | s: 00-02   | :            |                |
|---|----------|--------|---------------|---------|-------------|-------------|-------------|---------------|---------------|---------|---------|------------|--------------|----------------|
| • |          | • •••• | • • • • • •   |         | WIND S      | PEED IN     | KNOTS       | • • • • • •   | • • • • • • • |         |         |            | • • • • • •  | • • • • • • •  |
| DIRECTION (DEGREES)                     | 1-4      | 5~9    | 10-14         | 15-19   |             | 25-29       |             | 35-39         | 40-49         | 50-64   | GE 65   | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 26.7     | 4.4    | • • • • • • • |         | • • • • • • | • • • • • • | • • • • • • | • • • • • • • | • • • • • • • |         |         | 31.1       | 2.6          | 2.0            |
| ()                                      |          |        |               |         |             |             |             |               |               |         |         | 31.1       |              | 2.00           |
| 020-040                                 | 3.3      |        |               |         |             |             |             |               |               |         |         | 3.3        | 2.7          | 3.0            |
| 050-070                                 |          |        |               |         |             |             |             |               |               |         |         |            |              |                |
|   |          |        |               |         |             |             |             |               |               |         |         |            |              |                |
| (E) 080-100                             |          |        |               |         |             |             |             |               |               |         |         |            |              |                |
| 110-130                                 |          |        |               |         |             |             |             |               |               |         |         |            |              |                |
| 140-160                                 | 1.1      |        |               |         |             |             |             |               |               |         |         | 1.1        | 1.0          | 1.0            |
| 140-100                                 | 1        |        |               |         |             |             |             |               |               |         |         | 1.1        | 1.0          | 1.0            |
| (S) 170-190                             | 1.1      |        |               |         |             |             |             |               |               |         |         | 1.1        | 2.0          | 2.0            |
| 200-220                                 | 4.4      |        |               |         |             |             |             |               |               |         |         | 4.4        | 1.5          | 1.0            |
|   | l        |        |               |         |             |             |             | •             |               |         |         |            |              |                |
| 230-250                                 | 1.1      |        |               |         |             |             |             |               |               |         |         | 1.1        | 2.0          | 2.0            |
| (W) 260~280                             | 1.1      |        |               |         |             |             |             |               |               |         |         | 1.1        | 2.0          | 2.0            |
| 290-310                                 | 1.1      |        |               |         |             |             |             |               |               |         |         | 1.1        | 1.0          | 1.0            |
|   | }        |        |               |         |             |             |             |               |               |         |         | 1.1        | 1.0          |                |
| 320-340                                 | 11.1     | 1.1    |               |         |             |             |             |               |               |         |         | 12.2       | 2.6          | 2.0            |
|   |          |        |               |         |             |             |             |               |               |         |         |            |              |                |
| VARIABLE                                | [        |        |               |         |             |             |             |               |               |         |         |            |              |                |
| CALM                                    | 11111111 | ////// | //////        | /////// | //////      | ///////     | //////      | ///////       | ///////       | /////// | /////// | 43.3       | /////        | /////          |
| TOTALS                                  | 51.0     | 5.5    |               |         |             |             |             |               |               |         |         | 100.0      | 1.4          | 2.0            |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9 PERIOD OF RECORD: JUL 80 - JUN 90
MONTH: SEP HOURS: 03-05

|   |   | ь           | 1 10 01     | C: - 9  |             |               |               |               | MONTE         | : SEP   | HOOR     | S: U3~U3    | 1            |                |
|---|---|-------------|-------------|---------|-------------|---------------|---------------|---------------|---------------|---------|----------|-------------|--------------|----------------|
| • |   |             |             |         | WIND S      | PEED IN       | KNOTS         | • • • • • • • | • • • • • • • |         |          |             | • • • • • •  | •••••          |
| DIRECTION (DEGREES)                     | 1-4                                     | 5-9         | 10-14       | 15-19   |             | 25-29         |               | 35-39         | 40-49         | 50-64   | GE 65    | TATCT<br>\$ | MEAN<br>WIND | MEDIAN<br>WIND |
|   |   | • • • • • • | • • • • • • |         | • • • • • • | • • • • • • • | • • • • • • • | • • • • • •   | • • • • • •   |         |          |             | • • • • •    | • • • • • •    |
| (N) 350-010                             | 22.2                                    | 6.7         |             |         |             |               |               |               |               |         |          | 28.9        | 2.5          | 2.0            |
| 020-040                                 | 2.2                                     |             |             |         |             |               |               |               |               |         |          | 2.2         | 2.0          | 2.0            |
| 050-070                                 |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
|   |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
| (E) 080-100                             |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
| 110-130                                 |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
| 140-160                                 | 1.1                                     |             |             |         |             |               |               |               |               |         |          | 1.1         | 4.0          | 4.0            |
|   |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
| (S) 170-190                             | 3.3                                     |             |             |         |             |               |               |               |               |         |          | 3.3         | 1.7          | 2.0            |
| 200 220                                 |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
| 200-220                                 | 3.3                                     |             |             |         |             |               |               |               |               |         |          | 3.3         | 1.7          | 1.0            |
| 230-250                                 | 3.3                                     |             |             |         |             |               |               |               |               |         |          | 3.3         | 2.0          | 2.0            |
|   |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
| (W) 260-280                             |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
| 200 210                                 |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
| 290-310                                 |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
| 320-340                                 | 14.4                                    | 1.1         |             |         |             |               |               |               |               |         |          | 15.6        | 2.7          | 2.5            |
|   |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
|   |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
| VARIABLE                                |   |             |             |         |             |               |               |               |               |         |          |             |              |                |
| CALM                                    | 11111111                                | ,,,,,,      | ,,,,,,,     | ,,,,,,, |             | 1111111       | 1111111       | 1111111       |               |         |          | 42.2        | ,,,,,,       | 111111         |
| CMINI                                   | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | ,,,,,,      |             | ,,,,,,, | ,,,,,,,     | ,,,,,,,       | ,,,,,,,       | ,,,,,,,       | 111111        | 1711111 | ,,,,,,,, | 46.6        | ,,,,,,       | ,,,,,,         |
| TOTALS                                  | 49.8                                    | 7.8         |             |         |             |               |               |               |               |         |          | 100.0       | 1.4          | 2.0            |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90
MONTH: SEP HOURS: 06-08

|                     |                   | LS          | רט טד די      | rc: - 9       |         |          |        |             | MONTH         | l: SEP        | HOUR        | s: 06-0       | 3            |                |
|---------------------|-------------------|-------------|---------------|---------------|---------|----------|--------|-------------|---------------|---------------|-------------|---------------|--------------|----------------|
|                     | • • • • • • • • • | • • • • • • | • • • • • • • |               | WIND S  | SPEED IN | KNOTS  | • • • • • • | • • • • • • • | • • • • • • • | • • • • • • | • • • • • •   | • • • • • •  |                |
| DIRECTION (DEGREES) | 1-4               | 5-9         | 10-14         | 15-19         |         | 25-29    |        | 35-39       | 40-49         | 50-64         | GE 65       | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 21.1              | 4.4         |               |               |         |          |        |             |               | • • • • • • • |             | 25.6          | 3.0          | 2.0            |
| 020-040             | 3.3               | 1.1         |               |               |         |          |        |             |               |               |             | 4.4           | 2.8          | 2.0            |
| 050-070             |                   |             |               |               |         |          |        |             |               |               |             |               |              |                |
| (E) 080-100         |                   |             |               |               |         |          |        |             |               |               |             |               |              |                |
| 110-130             |                   |             |               |               |         |          |        |             |               |               |             |               |              |                |
| 140-160             |                   |             |               |               |         |          |        |             |               |               |             |               |              |                |
| (S) 170-190         | 3.3               |             |               |               |         |          |        |             |               |               |             | 3.3           | 2.3          | 2.0            |
| 200-220             | 2.2               |             |               |               |         |          |        |             |               |               |             | 2.2           | 1.5          | 1.5            |
| 230-250             |                   |             |               |               |         |          |        |             |               |               |             |               |              |                |
| (W) 260-280         |                   |             |               |               |         |          |        |             |               |               |             |               |              |                |
| 290-310             |                   |             |               |               |         |          |        |             |               |               |             |               |              |                |
| 320-340             | 17.8              |             |               |               |         |          |        |             |               |               |             | 17.8          | 1.9          | 2.0            |
| VARIABLE            | ¦<br>             |             |               | · • • • • • • | •••••   |          |        |             |               |               | •••••       | • • • • • • • |              | ••••           |
| CALM                | 11111111          | //////      | //////        | ////////      | /////// | //////// | 1///// | ////////    | ///////       | ///////       | ///////     | 46.7          | /////        | /////          |
| TOTALS              | 47.7              | 5.5         |               |               |         |          |        |             |               |               |             | 100.0         | 1.3          | 2.0            |
|                     |                   |             | то            | YTAL NUN      | IBER OF | OBSERVA  | TIONS  | 90          |               |               |             |               |              |                |
|                     |                   |             |               |               |         |          |        |             |               |               |             |               |              |                |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9 PERIOD OF RECORD: JUL 80 - JUN 90
MONTH: SEP HOURS: 09-11

|   |          | LS          | T TO UT       | C: - 9      |        |               |               |               | MONTH       | : SEP         | HOUL          | RS: 09-1      | L            |                |
|---|----------|-------------|---------------|-------------|--------|---------------|---------------|---------------|-------------|---------------|---------------|---------------|--------------|----------------|
| • |          | • • • • • • |               |             | WIND S | SPEED IN      | KNOTS         |               |             | • • • • • •   | • • • • • •   | • • • • • • • |              | •••••          |
| DIRECTION (DEGREES)                     | 1-4      | 5-9         | 10-14         | 15-19       |        | 25-29         |               | 35-39         | 40-49       | 50-64         | GE 65         | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 15.0     | 11.7        | • • • • • •   | • • • • • • |        | •••••         | • • • • • • • | • • • • • • • | • • • • • • | •••••         | • • • • • • • | 26.7          | 4.6          | 4.0            |
| (11) 330 310                            | *3.0     | ,           |               |             |        |               |               |               |             |               |               | 2017          | ***          | 4.0            |
| 020-040                                 | 5.0      | 3.3         |               |             |        |               |               |               |             |               |               | 8.3           | 3.0          | 2.0            |
| 050-070                                 | 6.7      | 1.7         |               |             |        |               |               |               |             |               |               | 8.3           | 2.8          | 2.0            |
|   |          |             |               |             |        |               |               |               |             |               |               |               |              |                |
| (E) 080-100                             |          |             |               |             |        |               |               |               |             |               |               |               |              |                |
| 110-130                                 | ļ        |             |               |             |        |               |               |               |             |               |               |               |              |                |
|   | İ        |             |               |             |        |               |               |               |             |               |               |               |              |                |
| 140-160                                 | 1.7      |             |               |             |        |               |               |               |             |               |               | 1.7           | 1.0          | 1.0            |
| (S) 170-190                             | 5.0      | 6.7         |               |             |        |               |               |               |             |               |               | 11.7          | 4.7          | 5.0            |
| 202 222                                 |          |             |               |             |        |               |               |               |             |               |               |               | 2.0          |                |
| 200-220                                 | 11.7     |             |               |             |        |               |               |               |             |               |               | 11.7          | 2.9          | 3.0            |
| 230-250                                 | 5.0      |             |               |             |        |               |               |               |             |               |               | 5.0           | 2.7          | 3.0            |
| (W) 260-280                             |          |             |               |             |        |               |               |               |             |               |               |               |              |                |
| (", 200 200                             |          |             |               |             |        |               |               |               |             |               |               |               |              |                |
| 290-310                                 | ļ        |             |               |             |        |               |               |               |             |               |               |               |              |                |
| 320-340                                 | 10.0     |             |               |             |        |               |               |               |             |               |               | 10.0          | 1.8          | 1.5            |
|   |          |             |               |             |        |               |               |               |             |               |               |               |              |                |
| VARIABLE                                | 1.7      | • • • • • • | • • • • • • • | • • • • • • | •••••  | • • • • • • • | • • • • • • • |               |             | • • • • • • • | • • • • • • • | 1.7           | 1.0          | 1.0            |
| AWINDE                                  | 1        |             |               |             |        |               |               |               |             |               |               | 1.7           | 1.0          | 1.0            |
| CALM                                    | 11111111 | //////      | //////        | //////      | ////// | ////////      | '//////       | ////////      | '//////     | ///////       | ///////       | 15.0          | /////        | /////          |
| TOTALS                                  | 61.8     | 23.4        |               |             |        |               |               |               |             |               |               | 100.0         | 2.9          | 3.0            |
|   | ,        |             |               |             |        |               |               |               |             |               |               | 2             |              |                |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

|                     |                     | LS          | TU OT T       | c: - 9   |         | _       |         |         | MONTH   | : SEP         | HOUR    | s: 12-14      |              |                |
|---------------------|---------------------|-------------|---------------|----------|---------|---------|---------|---------|---------|---------------|---------|---------------|--------------|----------------|
| •••••               | • • • • • • • •     | • • • • • • | • • • • • • • |          | WIND S  | PEED IN | KNOTS   |         |         | • • • • • •   | •••••   | • • • • • • • | • • • • •    | • • • • • • •  |
| DIRECTION (DEGREES) | 1-4                 | 5-9         | 10-14         | 15-19    |         |         |         | 35-39   | 40-49   | 50-64         | GE 65   | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 8.9                 | 8.9         | 2.2           |          | •••••   | •••••   |         |         |         | • • • • • • • | •••••   | 20.0          | 5.1          | 5.5            |
| 020-040             | 2.2                 | 2.2         |               |          |         |         |         |         |         |               |         | 4.4           | 4.8          | 4.5            |
| 050-070             | ĺ                   | 3.3         |               |          |         |         |         |         |         |               |         | 3.3           | 6.7          | 6.0            |
| (E) 080-100         | 1.1                 | 1.1         |               |          |         |         |         |         |         |               |         | 2.2           | 3.5          | 3.5            |
| 110-130             | 1.1                 | 1.1         |               |          |         |         |         |         |         |               |         | 2.2           | 3.5          | 3.5            |
| 140-160             | 4.4                 |             |               |          |         |         |         |         |         |               |         | 4.4           | 2.3          | 2.0            |
| (S) 170-190         | 6.7                 | 2.2         | 1.1           |          |         |         |         |         |         |               |         | 10.0          | 4.6          | 3.0            |
| 200-220             | 10.0                | 5.6         | 1.1           |          |         |         |         |         |         |               |         | 16.7          | 4.5          | 4.0            |
| 230-250             | 4.4                 | 3.3         |               |          |         |         |         |         |         |               |         | 7.8           | 4.3          | 4.0            |
| (W) 260-280         | 3.3                 | 1.1         |               |          |         |         |         |         |         |               |         | 4.4           | 2.5          | 1.5            |
| 290-310             | 2.2                 | 1.1         | 2.2           |          |         |         |         |         |         |               |         | 5.6           | 6.2          | 6.0            |
| 320-340             | 5.6                 | 3.3         |               |          |         |         |         |         |         |               |         | 8.9           | 3.8          | 3.0            |
|                     | · · · · · · · · · · |             |               |          |         |         |         |         |         |               |         |               |              |                |
| VARIABLE            | 4.4                 | 1.1         |               |          |         |         |         |         |         |               |         | 5.6           | 2.2          | 1.0            |
| CALM                | 1111111             | //////      | //////        | 11/1///  | /////// | '////// | /////// | /////// | 1111111 | '//////       | '////// | 4.4           | /////        | /////          |
| TOTALS              | 54.3                | 34.3        | 6.6           |          |         |         |         |         |         |               |         | 100.0         | 4.1          | 4.0            |
|                     |                     |             | mo.           | MAT 1111 |         | 000000  | TTONG.  | 00      |         |               |         |               |              |                |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: SEP HOURS: 15-17

| LST | то | UTC: | _ | 9 |  |
|-----|----|------|---|---|--|
|     |    |      |   |   |  |

WIND SPEED IN KNOTS DIRECTION 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) WIND WIND \* (N) 350-010 18.9 5.8 5.0 020-040 2.2 4.4 6.7 4.7 5.0 050-070 4.4 4.4 1.8 1.0 (E) 080-100 110-130 1.1 1.1 5.0 5.0 140-160 2.8 2.5 (S) 170-190 4.4 2.2 6.7 4.0 3.0 200-220 5.6 3.3 3.3 12.2 5.8 5.0 230-250 8.9 4.4 13.3 3.8 4.0 (W) 260-280 5.6 3.2 3.0 290-310 8.9 2.2 3.3 3.5 320-340 7.8 3.3 11.1 3.7 3.0 VARIABLE CALM TOTALS 59.9 30.9 5.5 100.0 4.1 4.0

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: SEP HOURS: 18-20

|                     |                                       | LS        | T TO UI     | :C: - 9     |             |                  |               |        | MONTH         | : SEP       | HOUR        | S: 18-20      | )            |                |
|---------------------|---------------------------------------|-----------|-------------|-------------|-------------|------------------|---------------|--------|---------------|-------------|-------------|---------------|--------------|----------------|
| •••••               | • • • • • • • • • • • • • • • • • • • | • • • • • | • • • • • • | • • • • • • | • • • • • • | • • • • • • •    | · · · · · · · |        | • • • • • • • | • • • • • • | • • • • • • | • • • • • • • | • • • • • •  | • • • • • • •  |
| DIRECTION (DEGREES) | 1-4                                   | 5-9       | 10-14       | 15-19       |             | PEED IN<br>25-29 |               | 35-39  | 40-49         | 50-64       | GE 65       | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 27.8                                  | 1.1       | •••••       | •••••       | 1.1         | •••••            | •••••         |        | •••••         | •••••       | •••••       | 30.0          | 3.1          | 2.0            |
| 020-040             | 5.6                                   | 1.1       |             |             | 1.1         |                  |               |        |               |             |             | 7.8           | 5.3          | 2.0            |
| 050-070             |                                       |           |             |             |             |                  |               |        |               |             |             |               |              |                |
| (E) 080-100         | 2.2                                   |           |             |             |             |                  |               |        |               |             |             | 2.2           | 2.0          | 2.0            |
| 110-130             |                                       |           |             |             |             |                  |               |        |               |             |             |               |              |                |
| 140-160             | 1.1                                   |           |             |             |             |                  |               |        |               |             |             | 1.1           | 3.0          | 3.0            |
| (S) 170-190         | 1.1                                   | 3.3       |             |             |             |                  |               |        |               |             |             | 4.4           | 5.8          | 7.0            |
| 200-220             | 4.4                                   |           |             |             |             |                  |               |        |               |             |             | 4.4           | 2.3          | 2.0            |
| 230-250             | 4.4                                   |           |             |             |             |                  |               |        |               |             |             | 4.4           | 2.5          | 3.0            |
| (W) 260-280         | 2.2                                   |           |             |             |             |                  |               |        |               |             |             | 2.2           | 1.5          | 1.5            |
| 290-310             |                                       | 1.1       |             |             |             |                  |               |        |               |             |             | 1.1           | 7.0          | 7.0            |
| 320-340             | 20.0                                  | 2.2       |             |             |             |                  |               |        |               |             |             | 22.2          | 2.7          | 2.0            |
| VARIABLE            | !<br>                                 | •••••     |             | •••••       | ••••••      | • • • • • • •    |               |        | •••••         |             | •••••       | •••••         | •••••        | •••••          |
| CALM                | 11111111                              | /////     | //////      | //////      | //////      | ///////          | //////        | ////// | //////        | //////      | ///////     | 20.0          | /////        | /////          |
| TOTALS              | 68.8                                  | 8.8       |             |             | 2.2         |                  |               |        |               |             |             | 100.0         | 2.6          | 2.0            |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

|                     |              | LS    | T TO UT     | C: - 9      |        |         |               |         | MONTH       | : SEP  | HOUR    | s: 21-23      |              | •              |
|---------------------|--------------|-------|-------------|-------------|--------|---------|---------------|---------|-------------|--------|---------|---------------|--------------|----------------|
|                     |              |       |             |             |        | PEED IN |               |         |             |        |         |               |              |                |
| DIRECTION (DEGREES) | 1-4          | 5-9   | 10-14       | 15~19       | 20-24  | 25-29   | 30-34         | 35-39   | 40-49       | 50-64  | GE 65   | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 37.8         | 1.1   | • • • • • • | • • • • • • |        | •••••   | • • • • • •   | •••••   | • • • • • • | •••••  | •••••   | 38.9          | 2.3          | 2.0            |
| 020-040             | 3.3          | 1.1   |             |             |        |         |               |         |             |        |         | 4.4           | 3.5          | 2.5            |
| 050-070             | 2.2          |       |             |             |        |         |               |         |             |        |         | 2.2           | 1.5          | 1.5            |
| (E) 080-100         |              |       |             |             |        |         |               |         |             |        |         |               |              |                |
| 110-130             |              |       |             |             |        |         |               |         |             |        |         |               |              |                |
| 140-160             |              |       |             |             |        |         |               |         |             |        |         |               |              |                |
| (S) 170-190         |              | 1.1   |             |             |        |         |               |         |             |        |         | 1.1           | 7.0          | 7.0            |
| 200-220             | 4.4          | 1.1   |             |             |        |         |               |         |             |        |         | 5.6           | 2.6          | 2.0            |
| 230-250             |              |       |             |             |        |         |               |         |             |        |         |               |              |                |
| (W) 260-280         |              |       |             |             |        |         |               |         |             |        |         |               |              |                |
| 290-310             |              |       |             |             |        |         |               |         |             |        |         |               |              |                |
| 320-340             | 10.0         |       |             |             |        |         |               |         |             |        |         | 10.0          | 2.4          | 2.0            |
| VARIABLE            | <u>.</u><br> | ••••• |             |             |        | •••••   | • • • • • • • | •••••   |             |        | •••••   | • • • • • • • | •••••        | •••••          |
| CALM                | 111111111    | '//// | //////      | //////      | ////// | /////// | //////        | /////// | //////      | ////// | '////// | 37.8          | /////        | //////         |
| TOTALS              | 57.7         | 4.4   |             |             |        |         |               |         |             |        |         | 100.0         | 1.5          | 2.0            |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

TOTALS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: SEP HOURS: ALL

LST TO UTC: - 9

56.0 14.7 1.6

WIND SPEED IN KNOTS DIRECTION | 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) % WIND WIND (N) 350-010 21.2 5.7 .6 .1 27.5 3.3 2.0 020-040 3.3 1.6 .1 5.1 3.9 3.0 050-070 1.4 .6 2.0 3.1 2.0 (E) 080-100 . 4 . 1 .6 2.8 2.0 110-130 . 1 .3 . 4 4.0 5.0 140-160 1.7 1.7 2.4 2.0 (S) 170-190 3.0 1.7 4.9 4.2 3.0 .1 200-220 5.5 1.3 .6 3.7 3.0 230-250 3.3 1.0 4.3 3.4 3.0 (W) 260-280 .3 1.4 1.7 2.6 2.0 290-310 1.6 .6 .3 2.5 4.2 4.0 320-340 13.6 2.0 VARIABLE 1.0 2.0 1.0 CALM 

TOTAL NUMBER OF OBSERVATIONS 690

.2

100.0 2.4

2.0

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: SEP HOURS: ALL

.....

.....

| CATEGORY A: | CEILING GE 200 BUT LESS THAN 1500 | FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS). |
|-------------|-----------------------------------|---|
|             | AND/OR                            |   |

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

| WIND SPEED IN KNOTS DIRECTION   1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN |         |        |         |         |               |         |             |         |               |         |     |           |            |       |        |
|---|---------|--------|---------|---------|---------------|---------|-------------|---------|---------------|---------|-----|-----------|------------|-------|--------|
| DIRECTION   | 1-4     | 5-9    | 10-14   | 15-19   | 20-24         | 25-29   | 30-34       | 35-39   | 40-49         | 50-64   | GE  | 65        | TOTAL      | MEAN  | MEDIAN |
| (DEGREES)   |         |        |         | •••••   | • • • • • •   | •••••   | •••••       |         | • • • • • •   | •••••   | ••• | ••••      | *          | WIND  | WIND   |
| (N) 350-010   | 7.4     | 16.0   | 3.7     | •••••   | 1.2           | •••••   | •••••       | •••••   | •••••         | •••••   | ••• | • • • • • | 28.4       | 6.4   | 6.0    |
| 020-040   |         |        |         |         |               |         |             |         |               |         |     |           |            |       |        |
| 050-070   |         |        |         |         |               |         |             |         |               |         |     |           |            |       |        |
| (E) 080-100   |         |        |         |         |               |         |             |         |               |         |     |           |            |       |        |
| 110-130   |         |        |         |         |               |         |             |         |               |         |     |           |            |       |        |
| 140-160   | 1.2     |        |         |         |               |         |             |         |               |         |     |           | 1.2        | 4.0   | 4.0    |
| (S) 170-190   | 4.9     | 3.7    |         |         |               |         |             |         |               |         |     |           | 8.6        | 4.0   | 2.0    |
| 200-220<br>230-250  | 1.2     |        |         |         |               |         |             |         |               |         |     |           | 4.9<br>1.2 | 1.8   | 2.0    |
| (W) 260-280   | 1.2     |        |         |         |               |         |             |         |               |         |     |           | 1.2        | 2.0   | 2.0    |
| 290-310   |         |        |         |         |               |         |             |         |               |         |     |           |            |       |        |
| 320-340   | 6.2     |        |         |         |               |         |             |         |               |         |     |           | 6.2        | 2.4   | 2.0    |
| VARIABLE  |         |        | •••••   | •••••   | • • • • • • • | •••••   | • • • • • • | •••••   | • • • • • • • | •••••   | ••• | • • • • • |            |       | •••••  |
| CALM  | 1111111 | ////// | /////// | /////// | ///////       | /////// | //////      | /////// | 1111111       | /////// | /// | ////      | 49.4       | ///// | /////  |
| TOTALS  | 25.8    | 19.7   | 3.7     |         | 1.2           |         |             |         |               |         |     |           | 100.0      | 2.5   | 4.0    |

TOTAL NUMBER OF OBSERVATIONS 81

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: OCT HOURS: 00-02 WIND SPEED IN KNOTS DIRECTION 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) 8 WIND WIND (N) 350-010 21.5 21.5 2.4 2.0 020-040 5.4 5.4 2.0 1.8 050-070 (E) 080-100 110-130 140-160 (S) 170-190 6.5 6.5 1.0 1.2 200-220 4.3 2.0 230-250 1.1 1.1 2.0 2.0 (W) 260-280 290-310 320-340 4.3 4.3 2.3 2.0 VARIABLE CALM TOTALS 43.1 100.0 .9 2.0

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED

FROM HOURLY OBSERVATIONS STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: OCT HOURS: 03-05 LST TO UTC: - 9 WIND SPEED IN KNOTS DIRECTION 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) WIND WIND (N) 350-010 20.4 20.4 2.0 2.0 020-040 7.5 7.5 1.6 2.0 050-070 (E) 080-100 110-130 2.2 2.2 1.0 1.0 140-160 1.1 1.1 3.0 3.0 (S) 170-190 12.9 12.9 2.3 2.0 200-220 2.1 8.6 8.6 2.0 230-250 (W) 260-280 290-310 2.2 2.2 3.0 3.0 320-340 8.6 1.1 9.7 3.3 4.0 ..... VARIABLE CALM TOTALS 63.5 1.1 100.0 1.4 2.0

TOTAL NUMBER OF OBSERVATIONS 93 .....

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

TOTALS

51.7

8.7

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: OCT HOURS: 06-08

LST TO UTC: - 9

WIND SPEED IN KNOTS DIRECTION 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) WIND WIND ₽. (N) 350-010 16.1 3.2 19.4 020-040 2.2 2.2 1.0 1.0 050-070 2.2 2.2 1.5 1.5 (E) 080-100 110-130 140-160 1.1 1.1 2.0 2.0 (S) 170-190 11.8 1.1 12.9 2.9 3.0 200-220 4.3 1.1 5.4 2.2 1.0 230-250 1.1 2.2 3.5 3.5 (W) 260-280 290-310 320-340 12.9 2.2 15.1 3.4 3.0 ...... VARIABLE /////// 39.8 //////// CALM

TOTAL NUMBER OF OBSERVATIONS 93

100.0 1.7

2.0

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: OCT HOURS: 09-11

| LST TO UTC: - 9 | MONTH: OCT | HOURS: 09-11 |
|-----------------|------------|--------------|
|                 |            |              |

|                     |   | LS          | T TO UI     | :C: - 9 |             |               |         |         | MONTH         | : OCT     | HOUR          | S: 09-11   | L            |                |
|---------------------|---|-------------|-------------|---------|-------------|---------------|---------|---------|---------------|-----------|---------------|------------|--------------|----------------|
|                     | • | · · · · · · |             |         | WIND        | SPEED IN      | KNOTS   | •••••   |               | •••••     |               |            |              | •••••          |
| DIRECTION (DEGREES) | 1-4                                     | 5-9         | 10-14       | 15-19   |             | 25-29         | 30-34   |         |               | 50-64     | GE 65         | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 8.1                                     | 14.5        | 1.6         |         | •••••       | • • • • • • • | •••••   | •••••   | • • • • • • • |           | • • • • • • • | 24.2       | 5.7          | 6.0            |
| 020-040             | 1.6                                     | 3.2         |             |         |             |               |         |         |               |           |               | 4.8        | 6.3          | 7.0            |
| 050-070             |   | 3.2         |             |         |             |               |         |         |               |           |               | 3.2        | 5.5          | 5.5            |
| (E) 080-100         |   |             |             |         |             |               |         |         |               |           |               |            |              |                |
| 110-130             |   |             |             |         |             |               |         |         |               |           |               |            |              |                |
| 140-160             | 1.6                                     |             |             |         |             |               |         |         |               |           |               | 1.6        | 2.0          | 2.0            |
| (S) 170-190         | 17.7                                    | 4.8         |             |         |             |               |         |         |               |           |               | 22.6       | 3.6          | 3.5            |
| 200-220             | 11.3                                    | 6.5         |             |         |             |               |         |         |               |           |               | 17.7       | 3.6          | 3.0            |
| 230-250             | 1.6                                     |             |             |         |             |               |         |         |               |           |               | 1.6        | 4.0          | 4.0            |
| (W) 260-280         |   |             |             |         |             |               |         |         |               |           |               |            |              |                |
| 290-310             | 3.2                                     |             |             |         |             |               |         |         |               |           |               | 3.2        | 3.0          | 3.0            |
| 320-340             | 1.6                                     | 3.2         |             |         |             |               |         |         |               |           |               | 4.8        | 6.7          | 8.0            |
| VARIABLE            |   |             | • • • • • • |         | • • • • • • | • • • • • • • |         | •••••   |               | • • • • • | • • • • • • • | •••••      | · • • • • •  | •••••          |
| CALM                | 1111111                                 | //////      | //////      | //////  | //////      | ///////       | /////// | /////// | ///////       | //////    | ////////      | 16.1       | /////        | /////          |
| TOTALS              | 46.7                                    | 35.4        | 1.6         |         |             |               |         |         |               |           |               | 100.0      | 3.8          | 4.0            |
|                     |   |             | TC          | TAL NUM | BER OF      | OBSERVA       | TIONS   | 62      |               |           |               |            |              |                |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

|                     |               | LS          | TU OT T       | rc: - 9 |        |   |        |   | MONTH   | : OCT         | HOUR          | S: 12-14      | l            |   |
|---------------------|---------------|-------------|---------------|---------|--------|---|--------|---|---------|---------------|---------------|---------------|--------------|---|
| •••••               | • • • • • • • | • • • • • • | • • • • • • • |         | WIND S | PEED IN                                 | KNOTS  |   |         | •••••         |               | • • • • • • • |              | • • • • • •                             |
| DIRECTION (DEGREES) | 1-4           | 5-9         | 10-14         | 15-19   |        | 25-29                                   |        | 35-39                                   | 40-49   | 50-64         | GE 65         | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND                          |
| (N) 350-010         | 8.6           | 8.6         | 2.2           |         | •••••  | • • • • • • •                           | •••••  | · • • • • • • • • • • • • • • • • • • • | •••••   | • • • • • • • | •••••         | 19.4          | 5.7          | 5.5                                     |
| 020-040             | 1.1           | 4.3         |               |         |        |   |        |   |         |               |               | 5.4           | 6.0          | 6.0                                     |
| 050-070             | 1.1           | 1.1         |               |         |        |   |        |   |         |               |               | 2.2           | 3.0          | 3.0                                     |
| (E) 080-100         |               |             |               |         |        |   |        |   |         |               |               |               |              |   |
| 110-130             |               |             |               |         |        |   |        |   |         |               |               |               |              |   |
| 140-160             | 3.2           |             |               |         |        |   |        |   |         |               |               | 3.2           | 3.0          | 3.0                                     |
| (S) 170-190         | 11.8          | 4.3         |               |         |        |   |        |   |         |               |               | 16.1          | 3.7          | 4.0                                     |
| 200-220             | 12.9          | 6.5         | 1.1           |         |        |   |        |   |         |               |               | 20.4          | 4.0          | 3.0                                     |
| 230-250             | 1.1           | 3.2         |               |         |        |   |        |   |         |               |               | 4.3           | 5.3          | 5.5                                     |
| (W) 260-280         | 1.1           | 1.1         | 1.1           |         |        |   |        |   |         |               |               | 3.2           | 7.0          | 8.0                                     |
| 290-310             | 2.2           | 1.1         | 3.2           |         |        |   |        |   |         |               |               | 6.5           | 7.5          | 8.0                                     |
| 320-340             | 5.4           | 3.2         |               | 1.1     |        |   |        |   |         |               |               | 9.7           | 6.1          | 4.0                                     |
| VARIABLE            | i<br>         |             |               |         |        | · • • • • • • • • • • • • • • • • • • • |        | · · · · · · · ·                         |         |               | · • • • • • • |               |              | • |
| AUVIUDE             |               |             |               |         |        |   |        |   |         |               |               |               |              |   |
| CALM                | 1111111       | //////      | ///////       | //////  | 11:111 | '//////                                 | ////// | ///////                                 | '////// | '//////       | '//////       | 9.7           | /////        | //////                                  |
| TOTALS              | 48.5          | 33.4        | 7.6           | 1.1     |        |   |        |   |         |               |               | 100.0         | 4.5          | 4.0                                     |
|                     |               |             | TO            | TAL NUM | BER OF | OBSERVA                                 | RNOIT  | 93                                      |         |               |               |               |              |   |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

MONTH: OCT HOURS: 15-17

|   |          | LS          | T TO UT       | C: - 9        |             |          |             |               | MONTH   | : OCT  | HOUR    | S: 15-17   | 7            |                |
|---|----------|-------------|---------------|---------------|-------------|----------|-------------|---------------|---------|--------|---------|------------|--------------|----------------|
| • |          | • • • • • • | • • • • • • • | • • • • • • • | WIND S      | SPEED IN | KNOTS       | • • • • • • • |         | •••••  |         | •••••      |              | •••••          |
| DIRECTION (DEGREES)                     | 1-4      | 5-9         | 10-14         | 15-19         |             | 25-29    |             | 35-39         | 40-49   | 50-64  | GE 65   | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             |          | 6.5         | • • • • • • • | • • • • • • • | • • • • • • |          | • • • • • • | • • • • • • • |         | •••••  |         | 6.5        | 5.3          | 5.0            |
| 020-040                                 | 3.2      | 2.2         |               |               |             |          |             |               |         |        |         | 5.4        | 3.6          | 2.0            |
| 050-070                                 | 1.1      | 1.1         |               |               |             |          |             |               |         |        |         | 2.2        | 4.5          | 4.5            |
| (E) 080-100                             | 1.1      | 1.1         |               |               |             | ٠        |             |               |         |        |         | 2.2        | 5.0          | 5.0            |
| 110-130                                 |          |             |               |               |             |          |             |               |         |        |         |            |              |                |
| 140-160                                 | 1.1      |             |               |               |             |          |             |               |         |        |         | 1.1        | 2.0          | 2.0            |
| (S) 170-190                             | 2.2      | 1.1         | 1.1           |               |             |          |             |               |         |        |         | 4.3        | 6.0          | 4.5            |
| 200-220                                 | 7.5      | 11.8        |               |               |             |          |             |               |         |        |         | 19.4       | 4.9          | 5.0            |
| 230-250                                 | 6.5      | 8.6         |               |               |             |          |             |               |         |        |         | 15.1       | 4.8          | 5.0            |
| (W) 260-280                             | 8.6      |             |               |               |             |          |             |               |         |        |         | 8.6        | 2.6          | 2.5            |
| 290-310                                 | 4.3      | 6.5         | 2.2           |               |             |          |             |               |         |        |         | 12.9       | 5.8          | 5.5            |
| 320-340                                 | 4.3      | 6.5         | 1.1           |               |             |          |             |               |         |        |         | 11.8       | 5.3          | 5.0            |
| VARIABLE                                | !<br>    | • • • • • • | • • • • • •   | •••••         | •••••       |          | •••••       | • • • • • • • |         | •••••  |         |            | . <b></b>    |                |
| CALM                                    | 11111111 | //////      | //////        | //////        | //////      | //////// | ///////     | ///////       | /////// | ////// | /////// | 10.8       | //////       | /////          |
| TOTALS                                  | 39.9     | 45.4        | 4.4           |               |             |          |             |               |         |        |         | 100.0      | 4.3          | 5.0            |
|   |          |             | TO            | TAI. NIIM     | BER OF      | OBSERVA  | TIONS       | 93            |         |        |         |            |              |                |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: OCT HOURS: 18-20

LST TO UTC: - 9

|                     | • • • • • • • • |        |        | • • • • • • • | wind s | SPEED IN                                | KNOTS  | · · · · · · · | • • • • • • |        | •••••       | • • • • • • • |              | • • • • • • •  |
|---------------------|-----------------|--------|--------|---------------|--------|---|--------|---------------|-------------|--------|-------------|---------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4             | 5-9    | 10-14  | 15-19         | 20-24  | 25-29                                   | 30-34  | 35-39         | 40-49       | 50-64  | GE 65       | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 15.1            | 1.1    |        | • • • • • • • |        | • • • • • • •                           |        |               |             |        | • • • • • • | 16.1          | 2.2          | 2.0            |
| 020-040             | 11.8            |        |        |               |        |   |        |               |             |        |             | 11.8          | 1.5          | 2.0            |
| 050-070             | 4.3             |        |        |               |        |   |        |               |             |        |             | 4.3           | 2.0          | 2.0            |
| (E) 080-100         |                 | 2.2    |        |               |        |   |        |               |             |        |             | 2.2           | 6.0          | 6.0            |
| 110-130             |                 |        |        |               |        |   |        |               |             |        |             |               |              |                |
| 140-160             | 1.1             |        |        |               |        |   |        |               |             |        |             | 1.1           | 2.0          | 2.0            |
| (S) 170-190         | 2.2             |        |        |               |        |   |        |               |             |        |             | 2.2           | 3.0          | 3.0            |
| 200-220             | 1.1             | 1.1    |        |               |        |   |        |               |             |        |             | 2.2           | 4.5          | 4.5            |
| 230~250             | 4.3             |        |        |               |        |   |        |               |             |        |             | 4.3           | 2.3          | 2.5            |
| (W) 260-280         | 1.1             |        |        |               |        |   |        |               |             |        |             | 1.1           | 3.0          | 3.0            |
| 290-310             | 3.2             |        |        |               |        |   |        |               |             |        |             | 3.2           | 3.3          | 3.0            |
| 320-340             | 10.8            | 4.3    | 1.1    |               |        |   |        |               |             |        |             | 16.1          | 4.3          | 3.0            |
| VARIABLE            | :<br>:<br>      |        |        | • • • • • • • |        | • |        | •••••         | •••••       |        |             | •••••         | • • • • • •  | •••••          |
| CALM                | 11111111        | 7///// | ////// | ///////       | ////// | 11/1///                                 | ////// | //////        | //////      | ////// | (111111     | / 35.5        | /////        | /////          |
| TOTALS              | 55.0            | 8.7    | 1.1    |               |        |   |        |               |             |        |             | 100.0         | 1.9          | 2.0            |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

|             |           | LS    | т то ит     | :C: - 9   |         |                  |         |         | MONTH   | : OCT  | HOUR        | s: 21-23 | 3           |        |
|-------------|-----------|-------|-------------|-----------|---------|------------------|---------|---------|---------|--------|-------------|----------|-------------|--------|
| DIRECTION   | 1-4       | 5-9   | 10-14       | 15-19     |         | PEED IN<br>25-29 |         | 35~39   | 40-49   | 50-64  | GE 65       | TOTAL    | MEAN        | MEDIAN |
| (DEGREES)   |           | ,     |             |           |         |                  |         |         |         | 50 01  | 02 03       | 8        | WIND        | WIND   |
| (N) 350-010 | 29.0      | 4.3   | • • • • • • | •••••     | •••••   | •••••            | •••••   | •••••   | •••••   | •••••  | •••••       | 33.3     | 2.6         | 2.0    |
| 020-040     | 10.8      |       |             |           |         |                  |         |         |         |        |             | 10.8     | 2.2         | 2.0    |
| 050-070     | 5.4       |       |             |           |         |                  |         |         |         |        |             | 5.4      | 2.4         | 2.0    |
| (E) 080-100 |           |       |             |           |         |                  |         |         |         |        |             |          |             |        |
| 110-130     | ĺ         |       |             |           |         |                  |         |         |         |        |             |          |             |        |
| 140-160     |           |       |             |           |         |                  |         |         |         |        |             |          |             |        |
| (S) 170-190 | 2.2       |       |             |           |         |                  |         |         |         |        |             | 2.2      | 1.0         | 1.0    |
| 200-220     | 1.1       |       |             |           |         |                  |         |         |         |        |             | 1.1      | 4.0         | 4.0    |
| 230-250     | <u> </u>  |       |             |           |         |                  |         |         |         |        |             |          |             |        |
| (W) 260-280 |           |       |             |           |         |                  |         |         |         |        |             |          |             |        |
| 290-310     | į<br>Į    |       |             |           |         |                  |         |         |         |        |             |          |             |        |
| 320-340     | 4.3       | 1.1   |             |           |         |                  |         |         |         |        |             | 5.4      | 3.0         | 3.0    |
| VARIABLE    | :<br>     |       |             |           |         |                  |         |         |         | •••••  | • • • • • • |          | • • • • • • | •••••  |
| CALM        | 111111111 | ///// | //////      | ///////   | 1111111 | ///////          | /////// | /////// | /////// | ////// | ///////     | 41.9     | //////      | /////  |
| TOTALS      | 52.8      | 5.4   |             |           |         |                  |         |         |         |        |             | 100.0    | 1.5         | 2.0    |
|             |           |       | TTC:        | ATT ATTIE | 90 ggm  | ODGEDUA          | TTONG.  | 0.2     |         |        |             |          |             |        |

TOTAL NUMBER OF OBSERVATIONS 93

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

TC: - 9 MONTH: OCT HOURS: ALL

| • | • • • • • • • | • • • • • • | • • • • • • • | • • • • • • • | WIND S | SPEED IN      | KNOTS   | • • • • • • | • • • • • • | • • • • • • • | •••••   | • • • • • •   | • • • • • • |        |
|---|---------------|-------------|---------------|---------------|--------|---------------|---------|-------------|-------------|---------------|---------|---------------|-------------|--------|
| DIRECTION                               | 1-4           | 5-9         | 10-14         | 15-19         |        | 25-29         |         | 35~39       | 40-49       | 50-64         | GE 65   | TOTAL         | MEAN        | MEDIAN |
| (DEGREES)                               |               | • • • • • • | •••••         |               | •••••  |               |         |             |             | • • • • • • • | •••••   | 8             | WIND        | WIND   |
| (N) 350-010                             | 15.1          | 4.3         | .4            | •••••         |        | • • • • • • • |         | •••••       |             | •••••         | •••••   | 19.9          | 3.3         | 2.0    |
| 020-040                                 | 5.6           | 1.1         |               |               |        |               |         |             |             |               |         | 6.7           | 2.7         | 2.0    |
| 050-070                                 | 1.8           | .6          |               |               |        |               |         |             |             |               |         | 2.4           | 2.9         | 2.0    |
| (E) 080-100                             | -1            | . 4         |               |               |        |               |         |             |             |               |         | .6            | 5.5         | 5.5    |
| 110-130                                 | .3            |             |               |               |        |               |         |             |             |               |         | .3            | 1.0         | 1.0    |
| 140-160                                 | 1.1           |             |               |               |        |               |         |             |             |               |         | 1.1           | 2.5         | 2.0    |
| (S) 170-190                             | 8.0           | 1.3         | .1            |               |        |               |         |             |             |               |         | 9.4           | 3.1         | 3.0    |
| 200-220                                 | 6.2           | 3.2         | .1            |               |        |               |         |             |             |               |         | 9.5           | 3.7         | 3.0    |
| 230-250                                 | 2.0           | 1.7         |               |               |        |               |         |             |             |               |         | 3.6           | 4.2         | 4.0    |
| (W) 260-280                             | 1.4           | .1          | .1            |               |        |               |         |             |             |               |         | 1.7           | 3.8         | 3.0    |
| 290-310                                 | 1.8           | 1.0         | .7            |               |        |               |         |             |             |               |         | 3.5           | 5.4         | 4.0    |
| 320-340                                 | 6.7           | 2.7         | .3            | .1            |        |               |         |             |             |               |         | 9.8           | 4.3         | 4.0    |
| VARIABLE                                | :             |             | •••••         | •••••         | •••••  |               |         |             |             |               | •••••   | • • • • • • • |             | •••••  |
| CALM                                    | 11111111      | //////      | //////        | 1111111       | ////// | ///////       | /////// | ///////     | 1111111     | '//////       | /////// | 31.4          | //////      | ////// |
| TOTALS                                  | 50.1          | 16.4        | 1.7           | .1            |        |               |         |             |             |               |         | 100.0         | 2.4         | 3.0    |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: OCT HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS DIRECTION | 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) & WIND WIND (N) 350-010 11.4 11.4 1.8 2.0 020-040 3.4 3.4 2.0 2.0 050-070 (E) 080-100 110-130 140-160 3.4 3.4 2.3 2.0 (S) 170-190 17.0 1.1 18.2 2.9 3.0 200-220 6.8 2.2 2.0 6.8 230-250 4.0 4.0 (W) 260-280 290-310 2.3 1.1 3.4 3.7 4.0 320-340 3.3 3.0 VARIABLE /////// 48.9 //////// CALM TOTALS 48.8 2.2 100.0 1.3 2.0

# OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED USAFFTAC, ASHEVILLE NC FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORDS JUL. 80 - JUN 90

| STATION NUMBER                          | R: 471066         |        | ATION N<br>T TO UT |             | MP CASE                                 | Y/TONGD     | uchon k | 0             | PERIO<br>MONTH |             |               | JUL 80 -<br>s: 00-02 |              | 0              |
|---|-------------------|--------|--------------------|-------------|---|-------------|---------|---------------|----------------|-------------|---------------|----------------------|--------------|----------------|
| • |                   | •••••  | •••••              | • • • • • • | WIND S                                  | PEED IN     | KNOTS   | • • • • • • • | •••••          |             |               |                      |              | • • • • • • •  |
| DIRECTION<br>(DEGREES)                  | 1-4               | 5-9    | 10-14              | 15-19       |   | 25-29       |         | 35-39         | 40-49          | 50-64       | GE 65         | TOTAL<br>%           | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 20.2              | 8.3    | • • • • • • •      | •••••       |   | • • • • • • | •••••   | •••••         | •••••          | • • • • • • | • • • • • • • | 28.6                 | 3.6          | 3.0            |
| 020-040                                 | 2.4               |        |                    |             |   |             |         |               |                |             |               | 2.4                  | 1.5          | 1.5            |
| 050-070                                 |                   |        |                    |             |   |             |         |               |                |             |               |                      |              |                |
| (E) 080-100                             |                   |        |                    |             |   |             |         |               |                |             |               |                      |              |                |
| 110-130                                 |                   |        |                    |             |   |             |         |               |                |             |               |                      |              |                |
| 140-160                                 |                   |        |                    |             |   |             |         |               |                |             |               |                      |              |                |
| (S) 170-190                             | 3.6               |        |                    |             |   |             |         |               |                |             |               | 3.6                  | 1.0          | 1.0            |
| 200-220                                 | 4.8               | 1.2    |                    |             |   |             |         |               |                |             |               | 6.0                  | 2.6          | 2.0            |
| 230-250                                 |                   |        |                    |             |   |             |         |               |                |             |               |                      |              |                |
| (W) 260-280                             |                   | 3.6    |                    |             |   |             |         |               |                |             |               | 3.6                  | 5.3          | 5.0            |
| 290-310                                 | 3.6               | 1.2    |                    |             |   |             |         |               |                |             |               | 4.8                  | 3.3          | 2.5            |
| 320-340                                 | 9.5               |        |                    |             |   |             |         |               |                |             |               | 9.5                  | 2.9          | 3.0            |
| VARIABLE                                | <u>'</u><br> <br> | •••••  | •••••              |             | • | •••••       | •••••   | • • • • • •   | •••••          | • • • • • • |               | • • • • • • •        | •••••        |                |
| CALM                                    | ///////           | ////// | ///////            | ///////     | //////                                  | //////      | //////  | ///////       | ///////        | //////      | ///////       | 41.7                 | /////        | /////          |
| TOTALS                                  | 44.1              | 14.3   |                    |             |   |             |         |               |                |             |               | 100.0                | 1.9          | 3.0            |
|   |                   |        |                    |             |   |             |         |               |                |             |               |                      |              |                |

TOTAL NUMBER OF OBSERVATIONS 84 .....

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: NOV HOURS: 03-05

LST TO UTC: - 9

...... WIND SPEED IN KNOTS 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (DEGREES) % WIND WIND ...... (N) 350-010 16.7 11.9 2.4 31.0 4.1 3.5

050-070 (E) 080-100

020-040

110-130

140-160

(S) 170-190 3.6 3.6 200-220 6.0 2.4 8.3

230-250

(W) 260-280 3.6 3.6 2.7 2.0

290-310

320-340 13.1 13.1 2.6 3.0

VARIABLE

CALM

43.0 14.3 2.4 TOTALS

TOTAL NUMBER OF OBSERVATIONS 84

C - 4 - 102

2.0

2.6

100.0 2.0 2.5

2.0

2.0

USAFETAC, ASHEVILLE NC

#### OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED USAFETAC, ASHEVILLE NO FROM HOURLY OBSERVATIONS FROM HOURLY OBSERVATIONS

| STATION NUMBE       | R: 471066                               |             | ATION N<br>T TO UT |   | MP CASE | Y/TONGD       | UCHON K | Ю       |             | D OF RE       |         | JUL 80 -<br>S: 06-08 |              | 0              |
|---------------------|---|-------------|--------------------|---|---------|---------------|---------|---------|-------------|---------------|---------|----------------------|--------------|----------------|
| •••••               | • | • • • • • • | • • • • • • •      |   |         | PEED IN       |         |         | • • • • • • | • • • • • • • |         | • • • • • •          | • • • • • •  |                |
| DIRECTION (DEGREES) | 1-4                                     | 5-9         | 10-14              |   | 20-24   | 25-29         | 30-34   | 35-39   | 40-49       | 50-64         | GE 65   | TOTAL<br>%           | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 14.3                                    | 3.6         | 2.4                | • |         | • • • • • • • |         |         |             |               | •••••   | 20.2                 | 4.1          | 3.0            |
| 020-040             | 1.2                                     |             |                    |   |         |               |         |         |             |               |         | 1.2                  | 2.0          | 2.0            |
| 050-070             |   |             |                    |   |         |               |         |         |             |               |         |                      |              |                |
| (E) 080-100         |   |             |                    |   |         |               |         |         |             |               |         |                      |              |                |
| 110-130             |   |             |                    |   |         |               |         |         |             |               |         |                      |              |                |
| 140-160             | <u> </u>                                |             |                    |   |         |               |         |         |             |               |         |                      |              |                |
| (S) 170-190         | 6.0                                     | 2.4         |                    |   |         |               |         |         |             |               |         | 8.3                  | 2.9          | 3.0            |
| 200-220             | 8.3                                     |             |                    |   |         |               |         |         |             |               |         | 8.3                  | 1.9          | 2.0            |
| 230-250             | 2.4                                     |             |                    |   |         |               |         |         |             |               |         | 2.4                  | 2.0          | 2.0            |
| (W) 260-280         | 1.2                                     |             |                    |   |         |               |         |         |             |               |         | 1.2                  | 4.0          | 4.0            |
| 290-310             | 3.6                                     |             |                    |   |         |               |         |         |             |               |         | 3,6                  | 2.3          | 2.0            |
| 320-340             | 7.1                                     | 2.4         | 1.2                |   |         |               |         |         |             |               |         | 10.7                 | 3.8          | 3.0            |
| VARIABLE            | :<br>                                   | • • • • •   | • • • • • • •      |   | •••••   | •••••         |         |         |             | • • • • • •   | •••••   | • • • • • • •        | •••••        | •••••          |
| CALM                | 11111111                                | //////      | //////             | ///////                                 | /////// | //////        | //////  | /////// | ///////     | //////        | /////// | 44.0                 | /////        | /////          |
| TOTALS              | 44.1                                    | 8.4         | 3.6                |   |         |               |         |         |             |               |         | 100.0                | 1.8          | 2.0            |
|                     |   |             |                    |   |         |               |         |         |             |               |         |                      |              |                |

TOTAL NUMBER OF OBSERVATIONS 84

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: NOV HOURS: 09-11

| STRITON NOTIFIE     | R: 4/100          |             | T TO UT                                 |               | une CASI    | II TONGL | OCHON P       | W       |               | i: NOV | HOUR          | S: 09-1     |              | O              |
|---------------------|-------------------|-------------|---|---------------|-------------|----------|---------------|---------|---------------|--------|---------------|-------------|--------------|----------------|
|                     | • • • • • • • • • | • • • • • • | • • • • • •                             | • • • • • • • | WIND S      | SPEED IN | KNOTS         | •••••   | • • • • • • • | •••••  | • • • • • •   | • • • • • • | • • • • • •  | •••••          |
| DIRECTION (DEGREES) | 1-4               | 5-9         | 10-14                                   | 15-19         | 20-24       | 25-29    | 30-34         | 35-39   | 40-49         | 50-64  | GE 65         | TOTAL<br>%  | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 10.7              | 14.3        | • | •••••         | •••••       | •••••    | • • • • • • • |         | • • • • • • • | •••••  | • • • • • • • | 25.0        | 4.3          | 5.0            |
| 020-040             |                   |             |   |               |             |          |               |         |               |        |               |             |              |                |
| 050-070             |                   |             |   |               |             |          |               |         |               |        |               |             |              |                |
| (E) 080-100         |                   |             |   |               |             |          |               |         |               |        |               |             |              |                |
| 119-130             |                   |             |   |               |             |          |               |         |               |        |               |             |              |                |
| 140-160             |                   |             |   |               |             |          |               |         |               |        |               |             |              |                |
| (S) 170-190         | 17.9              | 3.6         |   |               |             |          |               |         |               |        |               | 21.4        | 3.0          | 3.0            |
| 200-220             | 8.9               | 1.8         |   |               |             |          |               |         |               |        |               | 10.7        | 2.7          | 2.0            |
| 230-250             | 5.4               |             |   |               |             |          |               |         |               |        |               | 5.4         | 2.7          | 3.0            |
| (W) 260-280         |                   |             |   |               |             |          |               |         |               |        |               |             |              |                |
| 290-310             | 1.8               | 5.4         |   |               |             |          |               |         |               |        |               | 7.1         | 5.3          | 5.0            |
| 320-340             | 8.9               | 1.8         |   |               |             |          |               |         |               |        |               | 10.7        | 3.3          | 3.0            |
| VARIABLE            | <u>.</u>          | 1.8         | 1.8                                     |               | • • • • • • | •••••    | • • • • • •   |         | • • • • • • • | •••••  |               | 3.6         | 10.0         | 10.0           |
| CALM                | 1111111           | //////      | //////                                  | //////        | //////      | ///////  | //////        | /////// | ///////       | ////// | ///////       | 16.1        | /////        | /////          |
| TOTALS              | 53.6              | 28.7        | 1.8                                     |               |             |          |               |         |               |        |               | 100.0       | 3.2          | 3.0            |
|                     |                   |             | ďΌ                                      | TAL NUM       | BER OF      | OBSERVA  | TIONS         | 56      |               |        |               |             |              |                |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION N

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: NOV HOURS: 12-14

| • | · · · · · · · · · | • • • • • • | • • • • • • | • • • • • • • | WIND S | SPEED IN | KNOTS   | • • • • • • | • • • • • • | • • • • • • • | •••••   | • • • • • • • | • • • • • •  | • • • • • •    |
|---|-------------------|-------------|-------------|---------------|--------|----------|---------|-------------|-------------|---------------|---------|---------------|--------------|----------------|
| DIRECTION (DEGREES)                     | 1-4               | 5-9         | 10-14       | 15-19         |        | 25-29    |         | 35-39       | 40-49       | 50-64         | GE 65   | TOTAL<br>\$   | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 16.7              | 13.1        | 2.4         | • • • • • • • | •••••  | •••••    | •••••   |             |             | • • • • • • • | •••••   | 32.1          | 4.6          | 4.0            |
| 020-040                                 |                   |             |             |               |        |          |         |             |             |               |         |               |              |                |
| 050-070                                 |                   |             |             |               |        |          |         |             |             |               |         |               |              |                |
| (E) 080-100                             |                   |             |             |               |        |          |         |             |             |               |         |               |              |                |
| 110-130                                 | 2.4               |             |             |               |        |          |         |             |             |               |         | 2.4           | 3.5          | 3.5            |
| 140-160                                 | 1.2               | 1.2         |             |               |        |          |         |             |             |               |         | 2.4           | 5.0          | 5.0            |
| (S) 170-190                             | 9.5               |             |             |               |        |          |         |             |             |               |         | 9.5           | 2.6          | 2.5            |
| 200-220                                 | 4.8               | 2.4         |             |               |        |          |         |             |             |               |         | 7.1           | 4.0          | 3.5            |
| 230-250                                 | 3.6               | 4.8         |             |               |        |          |         |             |             |               |         | 8.3           | 4.6          | 6.0            |
| (W) 260-280                             | 3.6               |             |             |               |        |          |         |             |             |               |         | 3.6           | 4.0          | 4.0            |
| 290-310                                 | 7.1               | 3.6         |             |               |        |          |         |             |             |               |         | 10.7          | 3.8          | 3.0            |
| 320-340                                 | 1.2               | 7.1         |             |               |        |          |         |             |             |               |         | 8.3           | 5.6          | 6.0            |
|   | !<br>             |             | • • • • • • |               |        |          |         |             |             |               |         | • • • • • •   |              |                |
| VARIABLE                                | 1.2               | 2.4         |             |               |        |          |         |             |             |               |         | 3.6           | 7.0          | 8.0            |
| CALM                                    | 1111111           | //////      | 1111111     | //////        | ////// | '//////  | //////  | ///////     | ///////     | //////        | '////// | 11.9          | /////        | /////          |
| TOTALS                                  | 51.3              | 34.6        | 2.4         |               |        |          |         |             |             |               |         | 100.0         | 3.8          | 4.0            |
|   |                   |             |             | <b></b>       | 222 22 | ~~~~     | m= 0110 |             |             |               |         |               |              |                |

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: NOV HOURS: 15-17

| • | • • • • • • • • | • • • • • |         | • • • • • • | WIND S | PEED IN | KNOTS    | • • • • • • | • • • • • •   | • • • • • • | • • • • • | • • • • • • • • • | • • • • • •  | •••••          |
|---|-----------------|-----------|---------|-------------|--------|---------|----------|-------------|---------------|-------------|-----------|-------------------|--------------|----------------|
| DIRECTION<br>(DEGREES)                  | 1-4             | 5-9       | 10-14   | 15-19       | 20-24  | 25-29   | 30-34    | 35-39       | 40-49         | 50-64       | GE 6      | 5 TOTAL<br>%      | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 9.5             | 6.0       |         |             | •••••  | •••••   |          | •••••       | •••••         | •••••       |           | 15.5              | 4.0          | 4.0            |
| 020-040                                 | <br>            | 1.2       |         |             |        |         |          |             |               |             |           | 1.2               | 5.0          | 5.0            |
| 050-070                                 |                 |           |         |             |        |         |          |             |               |             |           |                   |              |                |
| (E) 080-100                             |                 |           |         |             |        |         |          |             |               |             |           |                   |              |                |
| 110-130                                 |                 |           |         |             |        |         |          |             |               |             |           |                   |              |                |
| 140-160                                 |                 |           |         |             |        |         |          |             |               |             |           |                   |              |                |
| (S) 170-190                             | 3.6             |           |         |             |        |         |          |             |               |             |           | 3.6               | 1.7          | 1.0            |
| 200-220                                 | 2.4             | 8.3       |         |             |        |         |          |             |               |             |           | 10.7              | 5.7          | 6.0            |
| 230-250                                 | 8.3             | 3.6       |         |             |        |         |          |             |               |             |           | 11.9              | 3.6          | 3.5            |
| (W) 260-280                             | 6.0             |           |         |             |        | •       |          |             |               |             |           | 6.0               | 2.2          | 2.0            |
| 290-310                                 | 8.3             | 6.0       |         |             |        |         |          |             |               |             |           | 14.3              | 4.1          | 4.0            |
| 320-340                                 | 10.7            | 6.0       |         |             |        |         |          |             |               |             |           | 16.7              | 3.8          | 3.0            |
|   | !<br>           |           |         |             |        |         | <i>.</i> |             | • • • • • • • |             | <i>.</i>  |                   |              |                |
| VARIABLE                                | 1               | 3.6       |         |             |        |         |          |             |               |             |           | 3.6               | 7.7          | 8.0            |
| CALM                                    | ///////         | '/////    | /////// | ///////     | 111111 | '////// | 7/////   | '//////     | '//////       | '//////     | /////     | // 16.7           | /////        | '/////         |
| TOTALS                                  | 48.8            | 34.7      |         |             |        |         |          |             |               |             |           | 100.0             | 3.4          | 4.0            |
|   |                 |           |         |             |        |         |          |             |               |             |           |                   |              |                |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: NOV HOURS: 18-20

LST TO UTC: - 9

| • • • • • • • • • • • • • | • • • • • • • • | • • • • • • | • • • • • •   | • • • • • • | WIND S | PEED IN       | KNOTS  |         | • • • • • • | • • • • • • • |               | • • • • • • |              |                |
|---------------------------|-----------------|-------------|---------------|-------------|--------|---------------|--------|---------|-------------|---------------|---------------|-------------|--------------|----------------|
| DIRECTION (DEGREES)       | 1-4             | 5-9         | 10-14         | 15-19       |        | 25-29         |        | 35-39   | 40-49       | 50-64         | GE 65         | TOTAL<br>%  | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010               | 13.1            | 1.2         | • • • • • • • |             |        | • • • • • • • |        | •••••   | •••••       | •••••         | • • • • • • • | 14.3        | 2.9          | 2.0            |
| 020-040                   | 6.0             |             |               |             |        |               |        |         |             |               |               | 6.0         | 2.0          | 2.0            |
| 050-070                   |                 |             |               |             |        |               |        |         |             |               |               |             |              |                |
| (E) 080-100               |                 |             |               |             |        |               |        |         |             |               |               |             |              |                |
| 110-130                   | 1.2             |             |               |             |        |               |        |         |             |               |               | 1.2         | 4.0          | 4.0            |
| 140-160                   |                 |             |               |             |        |               |        |         |             |               |               |             |              |                |
| (S) 170-190               | 1.2             |             |               |             |        |               |        |         |             |               |               | 1.2         | 1.0          | 1.0            |
| 200-220                   | 4.8             |             |               |             |        |               |        |         |             |               |               | 4.8         | 1.5          | 1.5            |
| 230-250                   | 2.4             | 1.2         |               |             |        |               |        |         |             |               |               | 3.6         | 3.0          | 2.0            |
| (W) 260-280               | 3.6             | 1.2         |               |             |        |               |        |         |             |               |               | 4.8         | 3.0          | 3.0            |
| 290-310                   | 4.8             |             |               |             |        |               |        |         |             |               |               | 4.8         | 3.3          | 3.5            |
| 320-340                   | 4.8             | 4.8         |               |             |        |               |        |         |             |               |               | 9.5         | 4.0          | 4.5            |
| **********                | !<br>           |             |               |             |        |               |        |         |             |               |               |             |              |                |
| VARIABLE                  |                 | 2.4         |               |             |        |               |        |         |             |               |               | 2.4         | 8.5          | 8.5            |
| CALM                      | 11111111        | '/////      | //////        | ///////     | ////// | ///////       | ////// | 7////// | //////      | ///////       | '///////      | 47.6        | /////        | /////          |
| TOTALS                    | 41.9            | 10.8        |               |             |        |               |        |         |             |               |               | 100.0       | 1.7          | 2.0            |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

37.1

TOTALS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

|                     |  | LS     | T TO UT       | C: - 9        |        |               |               |               | MONTH         | : NOV         | HOUR    | s: 21-23   | 1            |                |
|---------------------|--|--------|---------------|---------------|--------|---------------|---------------|---------------|---------------|---------------|---------|------------|--------------|----------------|
|                     | • • • • • • • • •                          |        | • • • • • •   | •••••         | WIND S | PEED IN       | KNOTS         |               | • • • • • • • | • • • • • • • |         |            | •••••        |                |
| DIRECTION (DEGREES) | 1-4  | 5-9    | 10-14         | 15-19         | 20-24  | 25-29         | 30-34         | 35-39         | 40-49         | 50-64         | GE 65   | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 14.3                                       | 6.0    | • • • • • • • | • • • • • • • |        | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • |         | 20.2       | 3.4          | 2.0            |
| 020-040             | 6.0  |        |               |               |        |               |               |               |               |               |         | 6.0        | 1.4          | 1.0            |
| 050-070             | 1.2  |        |               |               |        |               |               |               |               |               |         | 1.2        | 2.0          | 2.0            |
| (E) 080-100         |  |        |               |               |        |               |               |               |               |               |         |            |              |                |
| 110-130             |  |        |               |               |        |               |               |               |               |               |         |            |              |                |
| 140-160             | 2.4  |        |               |               |        |               |               |               |               |               |         | 2.4        | 2.5          | 2.5            |
| (S) 170-190         |  |        |               |               |        |               |               |               |               |               |         |            |              |                |
| 200-220             |  |        |               |               |        |               |               |               |               |               |         |            |              |                |
| 230-250             | 2.4  |        |               |               |        |               |               |               |               |               |         | 2.4        | 2.0          | 2.0            |
| (W) 260-280         | 2.4  | 1.2    |               |               |        |               |               |               |               |               |         | 3.6        | 3.3          | 3.0            |
| 290-310             | 3.6  | 1.2    |               |               |        |               |               |               |               |               |         | 4.8        | 3.0          | 2.0            |
| 320-340             | 4.8  |        |               |               |        |               |               |               |               |               |         | 4.8        | 2.8          | 2.5            |
|                     | '<br>• • • • • • • • • • • • • • • • • • • |        |               |               |        |               |               |               |               | • • • • • •   |         |            |              |                |
| VARIABLE            | }  |        |               |               |        |               |               |               |               |               |         |            |              |                |
| CALM                | 11111111                                   | ////// | //////        | //////        | 1///// | ///////       | ///////       | 1111111       | 7/////        | //////        | '////// | 54.8       | /////        | //////         |

.....

TOTAL NUMBER OF OBSERVATIONS 84

100.0 1.3 2.0

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: NOV HOURS: ALL

LST TO UTC: - 9 MONTH: NOV

|             |         | 200     |         |             |        |                   |         |         | 1101111         |           | 11001   | <b>.</b> .шп |       |        |
|-------------|---------|---------|---------|-------------|--------|-------------------|---------|---------|-----------------|-----------|---------|--------------|-------|--------|
| DIRECTION   |         |         | 10.14   | 15 10       |        | SPEED IN<br>25-29 |         | 25 70   | 40.40           | <br>E0 64 | GD 65   | momax.       |       |        |
| DIRECTION   | 1-4     | 5-9     | 10-14   |             |        | 23-29             |         |         | 40-49           | 30-64     | GE 03   | TOTAL        | MEAN  | MEDIAN |
| (DEGREES)   |         |         |         |             |        |                   |         |         |                 |           |         | *            | WIND  | WIND   |
| (N) 350-010 | 14.6    | 7.8     | .9      |             |        | • • • • • • •     | •••••   |         |                 |           | •••••   | 23.3         | 3.9   | 4.0    |
| 020-040     | 2.0     | .2      |         |             |        |                   |         |         |                 |           |         | 2.2          | 1.9   | 2.0    |
| 050-070     | .2      |         |         |             |        |                   |         |         |                 |           |         | .2           | 2.0   | 2.0    |
| (E) 080-100 |         |         |         |             |        |                   |         |         |                 |           |         |              |       |        |
| 110-130     | .5      |         |         |             |        |                   |         |         |                 |           |         | .5           | 3.7   | 4.0    |
| 140-160     | .5      | .2      |         |             |        |                   |         |         |                 |           |         | .6           | 3.8   | 2.5    |
| (S) 170-190 | 5.1     | .6      |         |             |        |                   |         |         |                 |           |         | 5.7          | 2.5   | 2.0    |
| 200-220     | 4.8     | 2.0     |         |             |        |                   |         |         |                 |           |         | 6.8          | 3.2   | 2.0    |
| 230-250     | 3.0     | 1.2     |         |             |        |                   |         |         |                 |           |         | 4.2          | 3.4   | 3.0    |
| (W) 260-280 | 2.6     | .8      |         |             |        |                   |         |         |                 |           |         | 3.4          | 3.3   | 4.0    |
| 290-310     | 4.2     | 2.0     |         |             |        |                   |         |         |                 |           |         | 6.2          | 3.7   | 3.0    |
| 320-340     | 7.5     | 2.8     | .2      |             |        |                   |         |         |                 |           |         | 10.4         | 3.6   | 3.0    |
| VARIABLE    | .2      | 1.2     | 2       | • • • • • • | •••••  |                   |         |         | · • • • • • • • |           |         | 1.6          | 8.1   | 8.0    |
| CALM        | 1111111 | /////// | /////// | ///////     | ////// | (//////           | /////// | /////// | (11/:11)        | ///////   | /////// | 34.9         | ///// | ////// |
| TOTALS      | 45.2    | 18.8    | 1.3     |             |        |                   |         |         |                 |           |         | 100.0        | 2.4   | 3.0    |
|             |         |         |         |             |        |                   |         |         |                 |           |         |              |       |        |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: NOV HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS). AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

|   |          |             |         |        |             | ·             |             |         |        |        |         |               |        |               |
|---|----------|-------------|---------|--------|-------------|---------------|-------------|---------|--------|--------|---------|---------------|--------|---------------|
| D. I. D. D. G. T. C. L. |          |             | 10.14   |        |             | SPEED IN      |             | 25 20   | 40.40  |        |         |               |        |               |
| DIRECTION   | 1-4      | 5-9         | 10-14   | 15-19  | 20-24       | 25-29         | 30-34       | 35-39   | 40-49  | 50-64  | GE 65   | TOTAL         | MEAN   | MEDIAN        |
| (DEGREES)   | 1        |             |         |        |             |               |             |         | •••••  |        | •••••   | 8             | WIND   | WIND          |
| (N) 350-010   | 16.8     | 6.3         | 2.1     |        | • • • • • • | • • • • • • • |             | ******  | •••••  | •••••  | •••••   | 25.3          | 3.9    | 3.5           |
| 020-040   |          | 1.1         |         |        |             |               |             |         |        |        |         | 1.1           | 5.0    | 5.0           |
| 050-070   |          |             |         |        |             |               |             |         |        |        |         |               |        |               |
| (E) 080-100   |          |             |         |        |             |               |             |         |        |        |         |               |        |               |
| 110-130   |          |             |         |        |             |               |             |         |        |        |         |               |        |               |
| 140-160   | Ī        |             |         |        |             |               |             |         |        |        |         |               |        |               |
| (S) 170-190   | 9.5      | 1.1         |         |        |             |               |             |         |        |        |         | 10.5          | 2.1    | 2.0           |
| 200-220   | 12.6     |             |         |        |             |               |             |         |        |        |         | 12.6          | 1.6    | 2.0           |
| 230-250   |          |             |         |        |             |               |             |         |        |        |         |               |        |               |
| (W) 260-280   | 1.1      |             |         |        |             |               |             |         |        |        |         | 1.1           | 4.0    | 4.0           |
| 290-310   |          |             |         |        |             |               |             |         |        |        |         |               |        |               |
| 320~340   | 3.2      |             |         |        |             |               |             |         |        |        |         | 3.2           | 2.7    | 2.0           |
| VARIABLE  | <br>     | • • • • • • |         |        | • • • • • • |               | • • • • • • | •••••   |        |        | •••••   | • • • • • • • | •••••  | • • • • • • • |
| CALM  | 11111111 | /////       | 1111111 | ////// | //////      | ///////       | ///////     | 1111111 | ////// | ////// | /////// | 46.3          | ////// | /////         |
| TOTALS  | 43.2     | 8.5         | 2.1     |        |             |               |             |         |        |        |         | 100.0         | 1.6    | 2.0           |
|   |          |             |         |        |             |               |             |         |        |        |         |               |        |               |

TOTAL NUMBER OF OBSERVATIONS 95

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471065

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: DEC HOURS: 00-02

LST TO UTC: - 9

| ••••••              |          | • • • • • • | •••••         |               | WIND S | SPEED IN      | KNOTS       | • • • • • •   | •••••         | • • • • • • |         | • • • • • •   | • • • • • •  |                |
|---------------------|----------|-------------|---------------|---------------|--------|---------------|-------------|---------------|---------------|-------------|---------|---------------|--------------|----------------|
| DIRECTION (DEGREES) | 1-4      | 5-9         | 10-14         | 15-19         | 20-24  | 25-29         | 30-34       | 35-39         | 40-49         | 50-64       | GE 65   | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 12.4     | • • • • • • | • • • • • • • | • • • • • • • | •••••  | • • • • • • • |             | • • • • • • • | • • • • • • • |             |         | 12.4          | 2.3          | 2.0            |
| 020-040             | 3.4      |             |               |               |        |               |             |               |               |             |         | 3.4           | 2.0          | 2.0            |
| 050-070             |          |             |               |               |        |               |             |               |               |             |         |               |              |                |
| (E) 080-100         |          |             |               |               |        |               |             |               |               |             |         |               |              |                |
| 110-130             |          |             |               |               |        |               |             |               |               |             |         |               |              |                |
| 140-160             |          |             |               |               |        |               |             |               |               |             |         |               |              |                |
| (S) 170-190         | 3.4      |             |               |               |        |               |             |               |               |             |         | 3.4           | 1.7          | 2.0            |
| 200-220             | 2.2      | 3.4         |               |               |        |               |             |               |               |             |         | 5.6           | 5.2          | 6.0            |
| 230-250             |          |             |               |               |        |               |             |               |               |             |         |               |              |                |
| (W) 260-280         |          |             |               |               |        |               |             |               |               |             |         |               |              |                |
| 290-310             | 1.1      |             |               |               |        |               |             |               |               |             |         | 1.1           | 2.0          | 2.0            |
| 320-340             | 6.7      | 2.2         |               |               |        |               |             |               |               |             |         | 9.0           | 3.8          | 3.0            |
| VARIABLE            | <u>.</u> | •••••       | • • • • • •   |               |        |               | • • • • • • | • • • • • • • |               | • • • • • • |         | • • • • • • • |              |                |
| CALM                | 11111111 | '/////      | //////        | //////        | ////// | ///////       | //////      | ////////      | ///////       | ///////     | /////// | 65.2          | /////        | //////         |
| TOTALS              | 29.2     | 5.6         |               |               |        |               |             |               |               |             |         | 100.0         | 1.1          | 2.0            |
|                     |          |             | TC            | TAL NUM       | BER OF | OBSERVA       | TIONS       | 89            |               |             |         |               |              |                |

......

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90
MONTH: DEC HOURS: 03-05

LST TO UTC: - 9

| • |         |             | • • • • • • •                           | • • • • • • • | WIND S  | PEED IN | KNOTS       | • • • • • • | • • • • • • • |               | • • • • • • | • • • • • • •     | • • • • • •  | • • • • • • •  |
|---|---------|-------------|---|---------------|---------|---------|-------------|-------------|---------------|---------------|-------------|-------------------|--------------|----------------|
| DIRECTION (DEGREES)                     | 1-4     | 5-9         | 10-14                                   | 15-19         | 20-24   | 25-29   | 30-34       | 35-39       | 40-49         | 50-64         | GE 65       | TOTAL<br>%        | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010                             | 12.2    | 1.1         |   | •••••         |         |         | • • • • • • |             |               | • • • • • • • |             | 13.3              | 2.2          | 2.0            |
| 020-040                                 | 6.7     |             |   |               |         |         |             |             |               |               |             | 6.7               | 1.5          | 1.5            |
| 050-070                                 | İ       |             |   |               |         |         |             |             |               |               |             |                   |              |                |
| (E) 080-100                             |         |             |   |               |         |         |             |             |               |               |             |                   |              |                |
| 110-130                                 |         |             |   |               |         |         |             |             |               |               |             |                   |              |                |
| 140-160                                 | ١.١     |             |   |               |         |         |             |             |               |               |             | 1.1               | 3.0          | 3.0            |
| (S) 170-190                             | 3.3     |             |   |               |         |         |             |             |               |               |             | 3.3               | 1.7          | 1.0            |
| 200-220                                 | 6.7     | 1.1         |   |               |         |         |             |             |               |               |             | 7.8               | 2.3          | 2.0            |
| 230-250                                 |         |             |   |               |         |         |             |             |               |               |             |                   |              |                |
| (W) 260-280                             |         | 1.1         |   |               |         |         |             |             |               |               |             | 1.1               | 5.0          | 5.0            |
| 290-310                                 | 1.1     |             |   |               |         |         |             |             |               |               |             | 1.1               | 4.0          | 4.0            |
| 320-340                                 | 6.7     | 3.3         |   |               |         |         |             |             |               |               |             | 10.0              | 4.2          | 3.0            |
| VARIABLE                                |         | • • • • • • | • | •••••         |         |         |             |             | • • • • • • • |               |             | • • • • • • • • • |              | •••••          |
| CALM                                    | /////// | //////      | ///////                                 | //////        | 11/1/// | //////  | //////      | //////      | ///////       | //////        | //////      | / 55.6            | //////       | 7/////         |
| TOTALS                                  | 37.8    | 6.6         |   |               |         |         |             |             |               |               |             | 100.0             | 1.2          | 2.0            |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: DEC HOURS: 06-08 LST TO UTC: - 9 WIND SPEED IN KNOTS DIRECTION 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN (N) 350-010 11.1 3.3 14.4 2.9 3.0 020-040 050-070 (E) 080-100 110-130 140-160 (S) 170-190 7.8 1.1 8.9 2.6 2.0 200-220 1.1 1.1 3.0 3.0 230-250 1.1 1.1 5.0 5.0 (W) 260-280 2.2 1.1 3.3 4.0 3.0 290-310 1.1 1.1 1.0 1.0 320-340 15.6 1.1 16.7 2.5 2.0 VARIABLE CALM TOTALS 38.9 7.7 100.0 1.3 2.5 TOTAL NUMBER OF OBSERVATIONS 90

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: DEC HOURS: 09-11

|                        |         |        |             | •••••         |               | PEED IN |               | •••••       | •••••       | •••••       | • • • • • • • |            |              | •••••          |
|------------------------|---------|--------|-------------|---------------|---------------|---------|---------------|-------------|-------------|-------------|---------------|------------|--------------|----------------|
| DIRECTION<br>(DEGREES) | 1-4     | 5-9    | 10-14       | 15-19         | 20-24         | 25-29   | 30-34         | 35-39       | 40-49       | 50-64       | GE 65         | TOTAL<br>% | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010            | 6.7     | 5.0    | 1.7         | •••••         |               |         |               |             | •••••       | •••••       | ••••••        | 13.3       | 5.0          | 4.5            |
| 020-040                | 1.7     |        |             |               |               |         |               |             |             |             |               | 1.7        | 4.0          | 4.0            |
| 050-070                |         |        |             |               |               |         |               |             |             |             |               |            |              |                |
| (E) 080-100            |         |        |             |               |               |         |               |             |             |             |               |            |              |                |
| 110-130                |         |        |             |               |               |         |               |             |             |             |               |            |              |                |
| 140-160                | 1.7     |        |             |               |               |         |               |             |             |             |               | 1.7        | 4.0          | 4.0            |
| (S) 170-190            | 18.3    |        |             |               |               |         |               |             |             |             |               | 18.3       | 2.1          | 2.0            |
| 200-220                | 6.7     | 1.7    |             |               |               |         |               |             |             |             |               | 8.3        | 3.2          | 3.0            |
| 230-250                |         |        |             |               |               |         |               |             |             |             |               |            |              |                |
| (W) 260-280            |         |        |             |               |               |         |               |             |             |             |               |            |              |                |
| 290-310                | 1.7     | 3.3    |             |               |               |         |               |             |             |             |               | 5.0        | 5.7          | 5.0            |
| 320-340                | 6.7     | 3.3    |             |               |               |         |               |             |             |             |               | 10.0       | 4.0          | 3.0            |
| VARIABLE               | <br>    | 1.7    | • • • • • • | · · · · · · · | • • • • • • • |         | • • • • • • • | • • • • • • | • • • • • • | • • • • • • | • • • • • •   | 1.7        | 8.0          | 8.0            |
| CALM                   | 1111111 | ////// | //////      | //////        | //////        | /////// | //////        | ///////     | //////      | //////      | //////        | 40.0       | /////        | //////         |
| TOTALS                 | 43.5    | 15.0   | 1.7         |               |               |         |               |             |             |             |               | 100.0      | 2.3          | 3.0            |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

|                     |   | LS          | T TO UT  | 'C: - 9       |               |   |               |               | MONTE         | : DEC         | HOUR        | s: 12-1       | 4            |                |
|---------------------|---|-------------|----------|---------------|---------------|---|---------------|---------------|---------------|---------------|-------------|---------------|--------------|----------------|
| •••••               | • | • • • • • • |          | • • • • • • • | WIND S        | SPEED IN                                | KNOTS         |               | •••••         | •••••         | • • • • • • | • • • • • • • | • • • • • •  | • • • • • • •  |
| DIRECTION (DEGREES) | 1-4                                     | 5-9         | 10-14    | 15-19         |               | 25-29                                   |               | 35-39         | 40-49         | 50-64         | GE 65       | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 15.6                                    | 10.0        |          | • • • • • •   | •••••         | • • • • • • •                           |               |               | • • • • • •   |               | ••••••      | 25.6          | 3.7          | 4.0            |
| 020-040             |   |             |          |               |               |   |               |               |               |               |             |               |              |                |
| 050-070             | }                                       |             |          |               |               |   |               |               |               |               |             |               |              |                |
| (E) 080-100         | 1.1                                     |             |          |               |               |   |               |               |               |               |             | 1.1           | 2.0          | 2.0            |
| 110-130             |   |             |          |               |               |   |               |               |               |               |             |               |              |                |
| 140-160             |   | 1.1         |          |               |               |   |               |               |               |               |             | 1.1           | 6.0          | 6.0            |
| (S) 170-190         | 10.0                                    | 3.3         | 1.1      |               |               |   |               |               |               |               |             | 14.4          | 4.5          | 4.0            |
| 200-220             | 14.4                                    | 2.2         |          |               |               |   |               |               |               |               |             | 16.7          | 3.3          | 3.0            |
| 230-250             |   |             |          |               |               |   |               |               |               |               |             |               |              |                |
| (W) 260-280         | 1.1                                     |             |          |               |               |   |               |               |               |               |             | 1.1           | 3.0          | 3.0            |
| 290-310             | 4.4                                     | 1.1         |          |               |               |   |               |               |               |               |             | 5.6           | 4.0          | 4.0            |
| 320-340             | 13.3                                    | 4.4         | 1.1      |               |               |   |               |               |               |               |             | 18.9          | 3.9          | 3.0            |
| VARIABLE            |   |             | <i>.</i> | • • • • • •   | • • • • • • • | • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • |             | • • • • • • • |              | • • • • • • •  |
| CALM                |   | ,,,,,,,     | ,,,,,,,  | ,,,,,,,       |               | ,,,,,,,,                                |               |               |               |               |             |               | ,,,,,,       | ,,,,,,         |
| CALM                | ///////                                 | 11/1///     | ///////  | ///////       | ///////       | 777777                                  | ///////       | 7717777       | //////        | ///////       | ///////     | 15.6          | //////       | /////          |
| TOTALS              | 59.9                                    | 22.1        | 2.2      |               |               |   |               |               |               |               |             | 100.0         | 3.2          | 3.5            |
|                     |   |             | TO       | TAL NUM       | BER OF        | OBSERVA                                 | TIONS         | 90            |               |               |             |               |              |                |

.....

# PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: DEC HOURS: 15-17

|                        |         |        |         | •••••  |        | SPEED IN |         |         | • • • • • • • | •••••   | • • • • • • | • • • • • • • |              | •••••          |
|------------------------|---------|--------|---------|--------|--------|----------|---------|---------|---------------|---------|-------------|---------------|--------------|----------------|
| DIRECTION<br>(DEGREES) | 1-4     | 5-9    | 10-14   | 15-19  | 20-24  | 25-29    | 30-34   | 35-39   | 40-49         | 50-64   | GE 65       | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010            | 12.2    | 4.4    |         | •••••  | •••••  | •••••    | ••••••  | •••••   | •••••         | •••••   |             | 16.7          | 3.7          | 3.0            |
| 020-040                | 1.1     |        |         |        |        |          |         |         |               |         |             | 1.1           | 2.0          | 2.0            |
| 050-070                |         |        |         |        |        |          |         |         |               |         |             |               |              |                |
| (E) 080-100            |         |        |         |        |        |          |         |         |               |         |             |               |              |                |
| 110-130                |         |        |         |        |        |          |         |         |               |         |             |               |              |                |
| 140-160                | 1.1     |        |         |        |        |          |         |         |               |         |             | 1.1           | 1.0          | 1.0            |
| (S) 170-190            | 1.1     |        |         |        |        |          |         |         |               |         |             | 1.1           | 4.0          | 4.0            |
| 200-220                | 10.0    | 5.6    |         |        |        |          |         |         |               |         |             | 15.6          | 3.6          | 3.5            |
| 230-250                | 8.9     | 5.6    |         |        |        |          |         |         |               |         |             | 14.4          | 3.8          | 4.0            |
| (W) 260-280            | 4.4     |        |         |        |        |          |         |         |               |         |             | 4.4           | 1.8          | 1.5            |
| 290-310                | 6.7     | 6.7    |         |        |        | ·        |         |         |               |         |             | 13.3          | 3.9          | 4.5            |
| 320-340                | 8.9     | 3.3    |         |        |        |          |         |         |               |         |             | 12.2          | 3.5          | 3.0            |
|                        |         |        |         |        |        |          |         |         |               |         |             |               | <b></b>      |                |
| VARIABLE               |         | 3.3    |         |        |        |          |         |         |               |         |             | 3.3           | 8.0          | 8.0            |
| CALM                   | 1////// | ////// | 1111111 | ////// | ////// | '//////  | /////// | /////// | ///////       | /////// | 111111      | / 16.7        | /////        | 111111         |
| TOTALS                 | 54.4    | 28.9   |         |        |        |          |         |         |               |         |             | 100.0         | 3.1          | 3.0            |
|                        |         |        |         |        |        |          |         |         |               |         |             |               |              |                |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

| LST TO | วบ | TC: | - 1 | 9 |
|--------|----|-----|-----|---|
|--------|----|-----|-----|---|

MONTH: DEC HOURS: 18-20

|                     |                            | rs        | r ro ur | :C: - 9       |         |               |             |               | MONTE  | : DEC       | HOUR    | S: 18-20      | )            |                |
|---------------------|----------------------------|-----------|---------|---------------|---------|---------------|-------------|---------------|--------|-------------|---------|---------------|--------------|----------------|
|                     | • • • • • • • •            | • • • • • | •••••   | • • • • • • • | WIND S  | PEED IN       | KNOTS       | • • • • • • • |        | • • • • • • | •••••   | • • • • • • • | • • • • • •  |                |
| DIRECTION (DEGREES) | 1-4                        | 5-9       | 10-14   | 15-19         |         | 25-29         |             | 35-39         | 40-49  | 50-64       | GE 65   | TOTAL<br>%    | MEAN<br>WIND | MEDIAN<br>WIND |
| (N) 350-010         | 11.6                       | 1.2       |         | •••••         |         | • • • • • • • | • • • • • • | • • • • • • • | •••••  | • • • • • • | •••••   | 12.8          | 2.5          | 2.0            |
| 020-040             | 3.5                        |           |         |               |         |               |             |               |        |             |         | 3.5           | 1.7          | 2.0            |
| 050-070             |                            |           |         |               |         |               |             |               |        |             |         |               |              |                |
| (E) 080-100         |                            |           |         |               |         |               |             |               |        |             |         |               |              |                |
| 110-130             |                            |           |         |               |         |               |             |               |        |             |         |               |              |                |
| 140-160             |                            |           |         |               |         |               |             |               |        |             |         |               |              |                |
| (S) 170-190         | 1.2                        | 1.2       |         |               |         |               |             |               |        |             |         | 2.3           | 3.0          | 3.0            |
| 200-220             | 5.8                        | 2.3       |         |               |         |               |             |               |        |             |         | 8.1           | 3.3          | 3.0            |
| 230-250             | 3.5                        | 1.2       |         |               |         |               |             |               |        |             |         | 4.7           | 2.8          | 2.0            |
| (W) 260-280         | 2.3                        |           |         |               |         |               |             |               |        |             |         | 2.3           | 1.5          | 1.5            |
| 290-310             | 5.8                        |           |         |               |         |               |             |               |        |             |         | 5.8           | 2.8          | 2.0            |
| 320-340             | 8.1                        |           |         |               |         |               |             |               |        |             |         | 8.1           | 2.3          | 2.0            |
| •••••               | †<br>- • • • • • • • • • • |           |         |               |         |               |             |               |        |             |         | • • • • • • • |              |                |
| VARIABLE            | ļ                          |           |         |               |         |               |             |               |        |             |         |               |              |                |
| CALM                | /////////                  | /////     | //////  | ///////       | //// // | ///////       | //////      | //////        | ////// | //////      | /////// | 52.3          | /////        | /////          |
| TOTALS              | 41.8                       | 5.9       |         |               |         |               |             |               |        |             |         | 100.0         | 1.2          | 2.0            |

### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: DEC HOURS: 21-23

|                        |          | LS        | T TO UI | :C: - 9     |               |                   |        |         | MONTH   | : DEC   | HOUR        | s: 21-2 | 3             |                |
|------------------------|----------|-----------|---------|-------------|---------------|-------------------|--------|---------|---------|---------|-------------|---------|---------------|----------------|
| DIRECTION<br>(DEGREES) | 1-4      | 5-9       | 10-14   | 15-19       |               | SPEED IN<br>25-29 |        | 35-39   | 40-49   | 50-64   | GE 65       | TOTAL   | MEAN<br>WIND  | MEDIAN<br>WIND |
| (N) 350-010            | 16.7     | • • • • • |         |             |               | •••••             |        | •••••   |         | •••••   | • • • • • • | 16.7    | 1.8           | 2.0            |
| 020-040                | 10.7     |           |         |             |               |                   |        |         |         |         |             | 10.7    | 1.6           | 2.0            |
| 050-070                | 1.2      |           |         |             |               |                   |        |         |         |         |             | 1.2     | 1.0           | 1.0            |
| (E) 080-100            |          |           |         |             |               |                   |        |         |         |         |             |         |               |                |
| 110-130                |          |           |         |             |               |                   |        |         |         |         |             |         |               |                |
| 140-160                |          |           |         |             |               |                   |        |         |         |         |             |         |               |                |
| (S) 170-190            | 4.8      |           |         |             |               |                   |        |         |         |         |             | 4.8     | 2.3           | 2.0            |
| 200-220                | 1.2      | 2.4       |         |             |               |                   |        |         |         |         |             | 3.6     | 5.0           | 5.0            |
| 230-250                | 3.6      |           |         |             |               |                   |        |         |         |         |             | 3.6     | 2.3           | 2.0            |
| (W) 260-280            | 1.2      |           |         |             |               |                   |        |         |         |         |             | 1.2     | 3.0           | 3.0            |
| 290-310                |          |           |         |             |               |                   |        |         |         |         |             |         |               |                |
| 320-340                | 6.0      |           |         |             |               |                   |        |         |         |         |             | 6.0     | 3.0           | 4.0            |
| VARIABLE               | <u>.</u> |           |         | • • • • • • | • • • • • • • | •••••             |        |         |         | •••••   |             | •••••   | • • • • • • • | •••••          |
| CALM                   | 11111111 | /////     | /////// | ///////     | ///////       | ///////           | ////// | '////// | /////// | /////// | ///////     | 52.4    | /////         | 111111         |
| TOTALS                 | 45.4     | 2.4       |         |             |               |                   |        |         |         |         |             | 100.0   | 1.1           | 2.0            |
|                        |          |           |         |             |               | 00455             | mroug  | 0.4     |         |         |             |         |               |                |

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: DEC HOURS: ALL

LST TO UTC: - 9

43.7 11.7 .3

TOTALS

...... WIND SPEED IN KNOTS DIRECTION | 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN ......

| (DEGREES)   | Ī                       |          |         | *8       | MIND   | WIND  |
|-------------|-------------------------|----------|---------|----------|--------|-------|
| (N) 350-010 | 12.5                    | 3.1      | .1      | <br>15.8 | 3.0    | 3.0   |
| 020-040     | 3.4                     |          |         | 3.4      | 1.7    | 2.0   |
| 050-070     | .1                      |          |         | .1       | 1.0    | 1.0   |
| (E) 080-100 | .1                      |          |         | .1       | 2.0    | 2.0   |
| 110-130     |                         |          |         |          |        |       |
| 140-160     | .4                      | -1       |         | .6       | 3.5    | 3.5   |
| (S) 170-190 | 5.7                     | .7       | .1      | 6.6      | 2.9    | 2.0   |
| 200-220     | 6.0                     | 2.4      |         | 8.4      | 3.5    | 3.0   |
| 230-250     | 2.1                     | 1.0      |         | 3.1      | 3.5    | 3.0   |
| (W) 260-280 | 1.5                     | .3       |         | 1.8      | 2.8    | 2.5   |
| 290-310     | 2.8                     | 1.3      |         | 4.1      | 3.8    | 4.0   |
| 320-340     | 9.1                     | 2.2      | .1      | 11.5     | 3.4    | 3.0   |
|             | · · · · · · · · · · · · |          |         | <br>     |        |       |
| VARIABLE    | -                       | .6       |         | .6       | 8.0    | 8.0   |
| CALM        | 1111111                 | //////// | /////// | 43.9     | ////// | ///// |

TOTAL NUMBER OF OBSERVATIONS 679

100.0 1.8 3.0

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: DEC HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS). AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

|                        |       |      |           |               |               |               | PEED IN       |        |         |         |        |               |       |       |        |
|------------------------|-------|------|-----------|---------------|---------------|---------------|---------------|--------|---------|---------|--------|---------------|-------|-------|--------|
| DIRECTION              | 1-    | - 4  | 5-9       | 10-14         | 15-19         | 20-24         | 25-29         | 30-34  | 35-39   | 40-49   | 50-64  | GE 65         | TOTAL | MEAN  | MEDIAN |
| (DEGREES)              |       | •••• | • • • • • |               | • • • • • • • | • • • • • • • | • • • • • • • |        | •••••   | •••••   |        |               | 8     | WIND  | WIND   |
| (N) 350-010            | 9.    | 4    | 2.4       | • • • • • • • | • • • • • •   | •••••         | • • • • • • • |        | •••••   | •••••   | •••••  | • • • • • • • | 12.8  | 2.8   | 3.0    |
| 020-040                | 2.    | 7    |           |               |               |               |               |        |         |         |        |               | 2.7   | 1.5   | 1.5    |
| 050-070                |       | .7   |           |               |               |               |               |        |         |         |        |               | .7    | 1.0   | 1.0    |
| (E) 080-100            |       |      |           |               |               |               |               |        |         |         |        |               |       |       |        |
| 110-130                |       |      |           |               |               |               |               |        |         |         |        |               |       |       |        |
| 140-160                |       | 7    |           |               |               |               |               |        |         |         |        |               | .7    | 3.0   | 3.0    |
| (S) 170-190            | 8.    |      | 2.0       | .7            |               |               |               |        |         |         |        |               | 11.4  | 3.6   | 3.0    |
| 200-220                | 3.    |      | .7        |               |               |               |               |        |         |         |        |               | 4.0   | 2.3   | 2.0    |
| 230-250<br>(W) 260-280 | 1.    | . 3  |           |               |               |               |               |        |         |         |        |               | 1.3   | 2.0   | 2.0    |
| 290-310                |       |      |           |               |               |               |               |        |         |         |        |               |       |       |        |
| 320-340                | 8.    | 7    |           |               |               |               |               |        |         |         |        |               | 8.7   | 2.2   | 2.0    |
|                        | <br>  |      |           |               |               |               |               |        |         |         |        |               |       |       |        |
| VARIABLE               |       |      |           |               |               |               |               | . ,    |         |         | - / •  |               |       |       |        |
| CALM                   | 11111 | 1111 | '////     | 1/////        | ///////       | ///////       | 1//////       | ////// | 11/1/1/ | 1111111 | 1///// | '//////       | 57.7  | ///// | /////  |
| TOTALS                 | 35.   | 6    | 6.1       | .7            |               |               |               |        |         |         |        |               | 100.0 | 1.2   | 2.0    |

TOTAL NUMBER OF OBSERVATIONS 149

#### PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: ALL HOURS: ALL

LST TO UTC: - 9

WIND SPEED IN KNOTS DIRECTION | 1-4 5-9 10-14 15-19 20-24 25-29 30-34 35-39 40-49 50-64 GE 65 TOTAL MEAN MEDIAN

| DIRECTION   | 1-4     | 5-9         | 10-14  | 15~19       | 20-24         | 25-29         | 30-34  | 35-39       | 40-49         | 50-64       | GE 65   | TOTAL | MEAN  | MEDIAN |
|-------------|---------|-------------|--------|-------------|---------------|---------------|--------|-------------|---------------|-------------|---------|-------|-------|--------|
| (DEGREES)   | l       | • • • • • • | •••••  | • • • • • • | • • • • • • • |               | *****  | • • • • • • | • • • • • • • | • • • • • • |         | 8     | WIND  | WIND   |
| (N) 350-010 | 12.4    | 5.3         | .7     | .0          | .0            | • • • • • • • |        | • • • • • • | • • • • • • • | • • • • • • |         | 18.4  | 3.8   | 3.0    |
| 020-040     | 4.3     | 1.4         | .1     | .0          | .0            |               |        |             |               |             |         | 5.8   | 3.3   | 2.0    |
| 050-070     | 1.4     | .5          | .0     |             |               |               |        |             |               |             |         | 1.9   | 3.4   | 3.0    |
| (E) 080-100 | .4      | .2          | .0     |             |               |               |        |             |               |             |         | .7    | 4.0   | 4.0    |
| 110-130     | .5      | .2          |        |             |               |               |        |             |               |             |         | .7    | 3.2   | 2.5    |
| 140-160     | 1.0     | .2          | .0     |             |               |               |        |             |               |             |         | 1.2   | 3.2   | 3.0    |
| (S) 170-190 | 4.5     | 1.5         | .2     |             |               |               |        |             |               |             |         | 6.1   | 3.7   | 3.0    |
| 200-220     | 7.9     | 4.0         | .7     | .1          | .0            |               |        |             |               |             |         | 12.7  | 4.3   | 4.0    |
| 230-250     | 3.2     | 1.8         | .1     | .0          |               |               |        |             |               |             |         | 5.1   | 3.9   | 4.0    |
| (W) 260-280 | 1.8     | .6          | .0     |             |               |               |        |             |               |             |         | 2.4   | 3.4   | 3.0    |
| 290-310     | 2.2     | .9          | .1     |             |               |               |        |             |               |             |         | 3.2   | 3.7   | 3.0    |
| 320-340     | 7.2     | 1.7         | .1     | .0          |               |               |        |             |               |             |         | 9.0   | 3.3   | 3.0    |
| VARIABLE    | .1      | 7           | 3      | .0          | • • • • • • • |               | •••••  | • • • • • • | • • • • • • • | • • • • • • |         | 1.1   | 8.5   | 8.0    |
| CALM        | 1111111 | //////      | ////// | ///////     | ///////       | ///////       | ////// | //////      | ///////       | //////      | (////// | 31.7  | ///// | /////  |
| TOTALS      | 46.9    | 19.0        | 2.3    | .1          |               |               |        |             |               |             |         | 100.0 | 2.6   | 3.0    |

TOTAL NUMBER OF OBSERVATIONS: 12237 ...... USAFETAC, ASHEVILLE NC

#### OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

MONTH: ALL HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS). AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

| WIND SPEED IN KNOTS |             |             |               |   |        |               |               |   |   |                 |                 |               |       |        |
|---------------------|-------------|-------------|---------------|---|--------|---------------|---------------|---|---|-----------------|-----------------|---------------|-------|--------|
| DIRECTION           | 1-4         | 5-9         | 10-14         | 15-19                                   | 20-24  | 25-29         | 30-34         | 35-39                                   | 40-49                                   | 50-64           | GE 65           | TOTAL         | MEAN  | MEDIAN |
| (DEGREES)           |             | • • • • • • |               |   |        | •••••         | • • • • • • • | • | • | • • • • • • • • | • • • • • • •   | *             | WIND  | WIND   |
| (N) 350-010         | 9.4         | 5.5         | .8            |   | .1     |               |               | ••••                                    | • • • • • •                             | •••••           | • • • • • • • • | 15.8          | 4. ŝ  | 4.0    |
| 020-040             | 1.9         | .9          |               |   |        |               |               |   |   |                 |                 | 2.9           | 3.2   | 2.0    |
| 050-070             | 1.0         | .1          | .1            |   |        |               |               |   |   |                 |                 | 1.2           | 2.7   | 2.0    |
| (E) 080-100         | .3          | .1          |               |   |        |               |               |   |   |                 |                 | .4            | 3.4   | 2.5    |
| 110-130             | .4          | -1          |               |   |        |               |               |   |   |                 |                 | .4            | 2.4   | 2.0    |
| 140-160             | .8          | •1          |               |   |        |               |               |   |   |                 |                 | .8            | 2.6   | 2.0    |
| (S) 170-190         | 7.3         | 1.9         | .5            |   |        |               |               |   |   |                 |                 | 9.7           | 3.7   | 3.0    |
| 200-220<br>230-250  | 12.7<br>2.8 | 3.5<br>1.0  | .5            | .1                                      |        |               |               |   |   |                 |                 | 16.8<br>3.8   | 3.6   | 3.0    |
| (W) 260-280         | .8          | .2          | ••            |   |        |               |               |   |   |                 |                 | 1.0           | 3.0   | 3.0    |
| 290-310             | 1.1         | .3          |               |   |        |               |               |   |   |                 |                 | 1.4           | 3.1   | 3.0    |
| 320-340             | 6.1         | .6          |               |   |        |               |               |   |   |                 |                 | 6.7           | 2.6   | 2.0    |
| VARIABLE            | :<br>       | • • • • • • | • • • • • • • | • |        | • • • • • • • | •••••         | • • • • • • •                           | • • • • • • •                           | •••••           | •••••           | • • • • • • • | ••••• |        |
| CALM                | ////////    | '/////      | //////        | //////                                  | ////// | ///////       | //////        | //////                                  | //////                                  | ///////         | (///////        | 39.1          | ///// | /////  |
| TOTALS              | 44.6        | 14.3        | 2.0           | .1                                      | .1     |               |               |   |   |                 |                 | 100.0         | 2.2   | 3.0    |
|                     |             |             |               |   |        |               |               |   |   |                 |                 |               |       |        |

TOTAL NUMBER OF OBSERVATIONS: 1957 ......

| PPPPPPPP  | AAA   | AAA   | RRRR | RRRR  | TTTTTTTTT | DDDDDDDD<br>DDDDDDDDD |     |  |
|-----------|-------|-------|------|-------|-----------|-----------------------|-----|--|
| PPPPPPPPP | AAAA  | AAAA  | RRRR | RRRRR | TTTTTTTTT |                       |     |  |
| PP PP     | AA    | AA    | RR   | RR    | TT        | DD                    | DD  |  |
| PP PP     | AA    | AA    | RR   | RR    | TT        | DD                    | DD  |  |
| PPPPPPPPP | AA    | AA    | RRRR | RRRRR | TT        | DD                    | DD  |  |
| PPPPPPPP  | AAAAA | AAAAA | RRRR | RRRR  | TT        | DD                    | DD  |  |
| PP        | AAAAA | AAAAA | RR   | RR    | TT        | DD                    | DD  |  |
| PP        | AA    | AA    | RR   | RR    | TT        | DD                    | DD  |  |
| PP        | AA    | AA    | RR   | RR    | TT        | DDDDDD                | DDD |  |
| PP        | AA    | AA    | RR   | RR    | TT        | DDDDDDD               | DDD |  |

#### PART D

#### CEILING VERSUS VISIBILITY AND SKY COVER SUMMARIES

CEILING VS VISIBILITY--PERCENT OCCURRENCE FREQUENCY (POF).

CREATED FROM HOURLY OBSERVATIONS, THIS SUMMARY IS A BIVARIATE DISTRIBUTION
OF PERCENTAGE FREQUENCY BY CLASSES OF CEILING (FROM ZERO FEET TO 20,000 FEET"NO CEILINC" IS A SEPARATE CLASS) VERSUS VISIBILITY CLASSES (FROM ZERO MILES
(METERS) TO GREATER THAN OR EQUAL TO 7 STATUTE MILES (11,200 METERS)). THE
TABLES SUMMARIZE THE DATA AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

BECAUSE OF THE CUMULATIVE NATURE OF THESE SUMMARIES, IT IS POSSIBLE TO DETERMINE THE PERCENTAGE OCCURRENCE FREQUENCY (POF) FOR ANY GIVEN CEILING AND/OR VISIBILITY LIMIT(S), EITHER SEPARATELY OR IN ANY COMBINATION. TOTALS PROGRESS FROM RIGHT TO LEFT AND FROM BOTTOM TO TOP. TO DETERMINE CEILING ALONE, REFER TO THE EXTREME RIGHT-HAND COLUMN (ZERO VISIBILITY). TO DETERMINE VISIBILITY ALONE, REFER TO THE BOTTOM ROW (ZERO CEILINGS). DETERMINE THE POF THAT MEETS OR EXCEEDS ANY GIVEN SET OF MAXIMA BY READING THE VALUE AT THE INTERSECTION OF THE APPROPRIATE CEILING ROW AND VISIBILITY COLUMN.

- NOTE 1: IN JANUARY 1968, METAR STATIONS BEGAN REPORTING VISIBILITIES TO 6 STATUTE MILES OR 9000 METERS. VALUES EXCEEDING 9000 METERS ARE REPORTED AS "9999."
- NOTE 2: FOR OVERSEAS CIVILIAN STATIONS REPORTING "CAVOK", ALL CEILINGS GREATER THAN 5000 FEET APPEAR IN THE 5000 FEET CLASS.
- CONVERSIONS: 1 STATUTE MILE = 1,609.344 METERS = .868391 NAUTICAL MILES.
  FOR CONVENIENCE, THE CONVERSION OFTEN USED IS 1 STATUTE MILE = 1,600 METERS.
- SKY COVER--PERCENT OCCURRENCE FREQUENCY.

ALSO CREATED FROM HOURLY OBSERVATIONS, THIS SUMMARY GIVES PERCENTAGE OCCURRENCE FREQUENCY (POF) OF SKY COVER IN EIGHTHS FOR SYNOPTIC STATIONS, BUT AS CLEAR, SCATTERED, BROKEN, OVERCAST, PARTIALLY OBSCURRED, OR TOTALLY OBSCURRED FOR AIRWAYS STATIONS. FOR AIRWAYS STATIONS, THIS SUMMARY ALSO GIVES POF FOR SKY COVER GREATER THAN ONE-HALF (I.E., 6/10). DATA IS SUMMARIZED THE SAME AS FOR PREVIOUS TABLE.

NOTE 1. THESE SUMMARIES ARE NOT AVAILABLE FOR METAR REPORTING STATIONS.

NOTE 2. AIRWAYS STATIONS THAT HAVE REPORTED IN SYNOPTIC CODE HAVE HAD THEIR SYNOPTIC SKY COVER REPORTS CONVERTED AS FOLLOWS:

NOTE 3. "PAPTIAL OBSCURATION" IS A SEPARATE CATEGORY NOT INCLUDED IN COMPUTATION OF "GREATER THAN 1/2" PERCENTAGES. "TOTAL OBSCURATIONS," HOWEVER, ARE INCLUDED.

#### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: JAN HOURS: 00-02 LST TO UTC: - 9 VISIBILITY IN METERS CEILING IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GF CE FEET 112 60 48 40 32 20 16 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 7000 GE GE 6000 63.7 70.4 71.5 71.5 71.5 71.5 71.5 71.5 71.5 71.5 GE 5000 36.9 39.1 53.6 53.6 63.7 71.5 GE 4500 36.9 39.1 55.3 55.3 65.4 65.4 72.1 73.2 73.2 73.2 73.2 73.2 73.2 73.2 73.2 73.2 77.1 77.1 77.1 77.7 77.7 77.7 4000 36.9 39.1 58.1 68.7 68.7 75.4 76.5 76.5 77.7 GE 58.1 GE 3500 38.0 40.2 63.1 63.1 74.3 74.3 81.0 82.1 82.1 92.7 82.7 82.7 83.2 83.2 83.2 83.2 GE 3000 39.7 41.9 65.4 65.4 79.3 79.3 86.0 87.2 87.2 87.7 88.8 88.8 89.4 89.4 89.4 89.4 GE 2500 39.7 41.9 65.9 65.9 80.4 80.4 89.8 89.9 91.6 92.2 93.3 93.3 93.9 93.9 93.9 93.9 GE 2000 39.7 41.9 65.9 65.9 81.6 81.6 89.9 91.1 92.7 93.3 95.5 95.5 96.6 96.6 93.3 95.5 96.6 96.6 96.6 GE 1800 19 7 41.9 65.9 65.9 81.6 81.6 89.9 91.1 92.7 95.5 96.6 GE 1500 39.7 41.9 65.9 65.9 81.6 81.6 89.9 91.1 92.7 93.3 95.5 95.5 96.6 96.6 96.6 96.6 1200 94.4 96.6 96.6 97.8 97.8 97.8 97.8 GE 39.7 41.9 67.0 67.0 82.7 82.7 91.1 92.2 93.0 GE 1000 39.7 41.9 67.0 67.0 83.2 83.2 91.6 92.7 94.4 95.0 97.2 97.2 98.3 98.3 98.3 98.3 95.0 97.2 97.2 98.3 98.3 98.3 GE 900 39.7 41.9 67.0 67.0 83.2 83.2 91.6 92.7 94.4 98.3 GE 800 39.7 41.9 67.0 67.0 83.2 83.2 91.6 92.7 94.4 95.0 97.2 97.2 98.3 98.3 98.3 98.3 98.9 100.0 100.0 100.0 100.0 700 39.7 41.9 67.0 67.0 91.6 92.7 95.5 96.1 98.9 GE 83.2 83.2 600 39.7 41.9 67.0 67.0 83.2 83.2 91.6 92.7 95.5 96.1 98.9 98.9 100.0 100.0 100.0 100.0 GE GE 500 39.7 41.9 67.0 67.0 83.2 83.2 91.6 92.7 95.5 96.1 98.9 98.9 100.0 100.0 100.0 100.0 GE 400 39.7 41.9 67.0 67.0 83.2 83.2 91.6 92.7 95.5 96.1 98.9 98.9 100.0 100.0 100.0 100.0 GE 300 39.7 41.9 67.0 67.0 83.2 83.2 91.6 92.7 95.5 96.1 98.9 98.9 100.0 100.0 100.0 100.0 91.6 95.5 96.1 98.9 98.9 100.0 100.0 100.0 GE 200 39.7 41.9 67.0 67.0 83.2 83.2 92.7 100.0 GE 100 39.7 41.9 67.0 67.0 83.2 83.2 91.6 92.7 95.5 96.1 98.9 98.9 100.0 100.0 100.0 100.0

TOTAL NUMBER OF OBSERVATIONS 179

41.9 67.0 67.0

000 39.7

CF

95.5

92.7

91.6

83.2 83.2

96.1 98.9

98.9 100.0 100.0 100.0 100.0

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN HOURS: 03-05

| CEI                                       | LING         | • • • • • •  | • • • • • •  | • • • • • •  | · • • • • •  | · · · · · · · , | VISIBIL       | ITY IN I     | METERS        | • • • • • •   | • • • • • •   | • • • • • •   | • • • • • •  | • • • • • •   | • • • • • • • | • • • • • •   | • • • • • •  |
|---|--------------|--------------|--------------|--------------|--------------|-----------------|---------------|--------------|---------------|---------------|---------------|---------------|--------------|---------------|---------------|---------------|--------------|
| IN GE GE GE GE GE GE GE GE GE GE GE GE GE |              |              |              |              |              |                 |               |              |               |               |               |               |              | GE            |               |               |              |
| FF  | ET           | 112          | 90           | 80           | 60           | 48              | 40            | 32           | 24            | 20            | 16            | 12            | 10           | 08            | 06            | 04            | 00           |
|   |              |              | • • • • • •  | • • • • • •  | • • • • • •  | • • • • • •     | • • • • • • • |              | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • •  | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • •  |
| NO  | CEIL         |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
|   |              |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
| GE  | 20000        |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
| GE  | 18000        |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
|   | 16000        |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
|   | 14000        |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
| GE  | 12000        |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
| GF.                                       | 10000        |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
| GE  | 9000         |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
| GE  | 8000         |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
| GE  | 7000         |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
| GE  | 6000         |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
|   |              |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
| GE  | 5000         | 33.3         | 33.3         | 47.8         | 47.8         | 64.4            | 64.4          | 70.0         | 72.8          | 73.3          | 73.3          | 73.3          | 73.3         | 73.3          | 73.3          | 73.3          | 73.9         |
| GE<br>GE                                  | 4500<br>4000 | 33.3         | 33.3<br>33.3 | 48.9         | 48.9<br>50.0 | 65.6<br>66.7    | 65.6          | 71.1<br>72.2 | 73.9<br>75.0  | 74.4<br>75.6  | 74.4<br>75.6  | 74.4<br>75.6  | 74.4<br>75.6 | 74.4<br>75.6  | 74.4<br>75.6  | 74.4<br>75.6  | 75.0<br>76.1 |
| GE  | 3500         | 33.3         | 33.3         | 50.0<br>55.6 | 55.6         | 72.2            | 66.7<br>72.2  | 77.8         | 80.6          | 81.1          | 81.1          | 81.1          | 81.1         | 81.1          | 81.1          | 81.1          | 81.7         |
| GE  | 3000         | 33.3         | 33.3         | 57.2         | 57.2         | 76.1            | 75.1          | 81.7         | 84.4          | 85.0          | 85.0          | 85.0          | 85.0         | 85.0          | 85.0          | 85.0          | 85.6         |
|   |              | 1            |              |              | 0.10         |                 |               |              |               |               |               |               | 40           |               |               |               |              |
| GΕ  | 2500         | 33.3         | 33.3         | 57.8         | 57.8         | 76.7            | 76.7          | 83.9         | 86.7          | 87.2          | 87.2          | 87.2          | 87.2         | 87.2          | 87.2          | 87.2          | 87.8         |
| GE  | 2000         | 33.9         | 33.9         | 60.0         | 60.0         | 79.4            | 79.4          | 86.7         | 89.4          | 90.0          | 90.0          | 91.1          | 91.7         | 91.7          | 91.7          | 91.7          | 92.2         |
| GE  | 1800         | 33.9         | 33.9         | 60.0         | 60.0         | 79.4            | 79.4          | 86.7         | 89.4          | 90.0          | 90.0          | 91.1          | 91.7         | 91.7          | 91.7          | 91.7          | 92.2         |
| GE  | 1500         | 33.9         | 33.9         | 60.0         | 60.0         | 80.0            | 80.0          | 88.3         | 91.1          | 91.7          | 91.7          | 92.8          | 93.3         | 93.3          | 93.3          | 93.3          | 93.9         |
| GE  | 1200         | 33.9         | 33.9         | 60.0         | 60.0         | 80.0            | 80.0          | 88.3         | 91.1          | 91.7          | 91.7          | 92.8          | 93.3         | 93.3          | 93.3          | 93.3          | 93.9         |
| GE  | 1000         | 33.9         | 33.9         | 60.0         | 60.0         | 80.0            | 80.0          | 88.3         | 91.7          | 92.2          | 92.2          | 93.3          | 93.9         | 93.9          | 93.9          | 93.9          | 94.4         |
| GE  | 900          | 33.9         | 33.9         | 60.0         | 60.0         | 80.0            | 80.0          | 88.3         | 91.7          | 92.2          | 92.2          | 93.3          | 93.9         | 93.9          | 93.9          | 93.9          | 94.4         |
| GE  | 800          | 31.9         | 33.9         | 60.0         | 60.0         | 80.0            | 80.0          | 88.3         | 91.7          | 92.2          | 92.2          | 93.3          | 93.9         | 93.9          | 93.9          | 93.9          | 94.4         |
| GE  | 700          | 33.9         | 33.9         | 60.0         | 60.0         | 80.0            | 80.0          | 88.3         | 91.7          | 92.2          | 92.2          | 95.0          | 95.6         | 95.6          | 95.6          | 95.6          | 96.1         |
| GE  | 600          | 33.9         | 33.9         | 60.0         | 60.0         | 80.0            | 80.0          | 88.3         | 91.7          | 92.2          | 92.2          | 95.0          | 95.6         | 95.6          | 95.6          | 95.6          | 96.1         |
|   |              |              |              |              |              |                 |               |              |               |               |               |               |              |               |               |               |              |
| GE  | 500          | 33.9         | 33.9         | 60.0         | 60.0         | 80.0            | 80.0          | 88.3         | 91.7          | 92.2          | 93.3          | 96.1          | 96.7         | 96.7          | 96.7          | 96.7          | 97.2         |
| GE  | 400          | 33.9         | 33.9         | 60.0         | 60.0         | 80.0            | 80.0          | 88.3         | 91.7          | 92.2          | 93.3          | 96.1          | 96.7         | 96.7          | 96.7          | 96.7          | 97.2         |
| GE  | 300<br>200   | 33.9<br>33.9 | 33.9         | 60.0         | 60.0<br>60.0 | 80.0            | 80.0<br>80.0  | 88.3<br>88.3 | 91.7<br>91.7  | 92.2<br>92.2  | 93.3<br>93.3  | 96.1<br>96.1  | 96.7<br>96.7 | 96.7<br>96.7  | 96.7<br>96.7  | 96.7<br>96.7  | 97.2<br>97.2 |
| GE<br>GE                                  | 100          | 33.9         | 33.9<br>33.9 | 60.0<br>60.0 | 60.0         | 80.0<br>80.0    | 80.0          | 88.3         | 91.7          | 92.2          | 93.3          | 96.1          | 96.7         | 96.7          | 97.2          | 97.2          | 98.3         |
| VID                                       | 100          | 22.7         | 13.07        | 00.0         | 00.0         | 00.0            | 00.0          | 00.3         | 31.1          | Ja C          | /3.3          | JU-1          | JU . 1       | 50.7          | 21.06         | 37.2          | 20.3         |
| GE  | 000          | 33.9         | 33.9         | 60.0         | 60.0         | 80.0            | 80.0          | 88.3         | 91.7          | 92.2          | 93.3          | 96.1          | 96.7         | 96.7          | 97.2          | 97.2          | 100.0        |
|   |              |              |              |              |              |                 |               |              |               |               |               |               |              |               | <i></i> .     |               | • • • • • •  |
|   |              |              |              |              | • • • • • •  |                 |               |              |               |               |               | • • • • • • • |              |               |               |               | ••••         |

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN HOURS: 06-08

| CEI   | <br>LING  |             | • • • • • • | • • • • • •   | • • • • • •   | • | VISIBIL       | <br>TTY IN I  | METERS        | • • • • • • | • • • • • • | • • • • • • | • • • • • • • | • • • • • •   |               |             | • • • • • • |
|-------|-----------|-------------|-------------|---------------|---------------|---|---------------|---------------|---------------|-------------|-------------|-------------|---------------|---------------|---------------|-------------|-------------|
| I     |           | GE          | GE          | GE            | GE            | GE                                      | GE            | GE            | GE            | GE          | GE          | GE          | GE            | GE            | GE            | GE          | GE          |
| FE    |           | 112         | 90          | 80            | 60            | 48                                      | 40            | 32            | 24            | 20          | 16          | 12          | 10            | 08            | 06            | 04          | 00          |
|       |           |             |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
|       |           |             |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| NO    | CEIL      |             |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| GE    | 20000     |             |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| GE    | 18000     | }           |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| GE    | 16000     |             |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| GE    | 14000     |             |             |               |               |   |               |               | *             |             |             |             |               |               |               |             |             |
| GE    | 12000     | Ì           |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
|       |           |             |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
|       | 10000     | !<br>!      |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| GE    | 9000      |             |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| GE    | 8000      |             |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| GE    | 7000      |             |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| GE    | 6000      | Ì           |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| GE    | 5000      | 24.4        | 25.0        | 43.9          | 43.9          | 60.0                                    | 61.1          | 63.3          | 65.6          | 67.2        | 67.8        | 68.3        | 68.3          | 68.9          | 68.9          | 68.9        | 68.9        |
| GE    | 4500      | 24.4        | 25.0        | 43.9          | 43.9          | 60.0                                    | 61.1          | 63.3          | 65.6          | 67.2        | 67.8        | 68.3        | 68.3          | 68.9          | 68.9          | 68.9        | 68.9        |
| GE    | 4000      | 24.4        | 25.0        | 43.9          | 43.9          | 60.0                                    | 61.1          | 63.9          | 66.1          | 67.8        | 68.3        | 68.9        | 68.9          | 69.4          | 69.4          | 69.4        | 69.4        |
| GE    | 3500      | 25.6        | 26.1        | 46.7          | 46.7          | 65.0                                    | 66.1          | 68.9          | 71.1          | 72.8        | 73.3        | 73.9        | 73.9          | 74.4          | 74.4          | 74.4        | 74.4        |
| GE    | 3000      | 25.6        | 26.1        | 48.3          | 48.3          | 69.4                                    | 71.1          | 74.4          | 76.7          | 78.9        | 73.4        | 80.6        | 80.6          | 81.7          | 81.7          | 81.7        | 81.7        |
| 01.7  | 3000      |             | 2071        |               | .0.5          | 03                                      | ,             |               |               |             |             | 0010        | 00.0          | 0.2.7         | 01.7          | 01.7        | 01.7        |
| GE    | 2500      | 25.6        | 26.1        | 48.3          | 48.3          | 71.1                                    | 72.8          | 76.1          | 78.3          | 80.6        | 81.1        | 82.2        | 82.2          | 83.3          | 83.3          | 83.3        | 83.3        |
| GE    | 2000      | 25.6        | 26.1        | 49.4          | 49.4          | 72.8                                    | 74.4          | 77.8          | 80.0          | 82.2        | 82.8        | 85.0        | 86.1          | 87.2          | 87.2          | 87.2        | 87.2        |
| GE    | 1800      | 25.6        | 26.1        | 49.4          | 49.4          | 72.8                                    | 74.4          | 77.8          | 80.0          | 82.2        | 82.8        | 85 0        | 86.1          | 87.2          | 87.2          | 87.2        | 87.2        |
| GE    | 1500      | 25.6        | 26.1        | 49.4          | 49.4          | 72.8                                    | 74.4          | 77.8          | 81.1          | 83.3        | 83.9        | 86.7        | 87.8          | 88.9          | 88.9          | 88.9        | 88.9        |
| GE    | 1200      | 25.6        | 26.1        | 49.4          | 49.4          | 72.8                                    | 74.4          | 78.3          | 81.7          | 83.9        | 84.4        | 87.2        | 88.3          | 89.4          | 89.4          | 89.4        | 89.4        |
|       |           |             |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| GE    | 1000      | 25.6        | 26.1        | 49.4          | 49.4          | 73.3                                    | 75.0          | 78.9          | 82.8          | 85.0        | 86.1        | 88.9        | 90.0          | 91.1          | 91.1          | 91.1        | 91.1        |
| GE    | 900       | 25.5        | 26.1        | 49.4          | 49.4          | 73.3                                    | 75.0          | 78.9          | 82.8          | 85.0        | 87.2        | 90.0        | 91.1          | 92.2          | 92.2          | 92.2        | 92.2        |
| GE    | 800       | 25.6        | 26.1        | 49.4          | 49.4          | 73.3                                    | 75.0          | 78.9          | 82.8          | 85.0        | 87.2        | 90.6        | 91.7          | 92.8          | 92.8          | 92.8        | 92.8        |
| GE    | 700       | 25.6        | 26.1        | 49.4          | 49.4          | 73.3                                    | 75.0          | 78.9          | 83.9          | 86.1        | 88.9        | 92.8        | 93.9          | 95.0          | 95.0          | 95.0        | 95.0        |
| GE    | 600       | 25.6        | 26.1        | 49.4          | 49.4          | 72.3                                    | 75.0          | 78.9          | 83.9          | 86.1        | 88.9        | 92.8        | 93.9          | 95.0          | 95.0          | 95.0        | 95.0        |
|       |           | ì           |             |               |               |   |               |               |               |             |             |             |               |               |               |             |             |
| GE    | 500       | 25.6        | 26.1        | 49.4          | 49.4          | 73.3                                    | 75.0          | 78.9          | 83.9          | 86.1        | 89.4        | 93.3        | 94 4          | 95.6          | 95.6          | 95.6        | 95.6        |
| GE    | 400       | 25.6        | 26.1        | 49.4          | 49.4          | 73.3                                    | 75.0          | 78.9          | 83.9          | 86.1        | 89.4        | 93.3        | 94.4          | 95.6          | 95.6          | 95.6        | 95.6        |
| GE    | 300       | 25.6        | 26.1        | 49.4          | 49.4          | 73.3                                    | 75.0          | 78.9          | 83.9          | 86.1        | 89.4        | 93.3        | 94.4          | 95.6          | 95.6          | 95.6        | 95.6        |
| GE    | 200       | 25.6        | 26.1        | 49.4          | 49.4          | 73.3                                    | 75.0          | 78.9          | 83.9          | 86.1        | 89.4        | 93.3        | 94.4          | 95.6          | 95.6          | 95.6        | 95.6        |
| GE    | 100       | 25.6        | 26.1        | 49.4          | 49.4          | 73.3                                    | 75.0          | 78.9          | 83.9          | 86.1        | 89.4        | 93.3        | 94.4          | 96.1          | 96.1          | 96.1        | 98.3        |
|       |           | 25.6        | 26.         | 40.4          | 40.4          | 22.5                                    | 75.0          | 70.0          | 03.0          | 06.1        |             | 02.3        | 04.6          | 06.1          | ac 1          |             |             |
| GE    | 000       | 25.6        | 26.1        | 49.4          | 49.4          | 73.3                                    | 75.0          | 78.9          | 83.9          | 86.1        | 89.4        | 93.3        | 94.4          | 96.1          | 96.1          | 96.1        | 100.0       |
| • • • | • • • • • | • • • • • • |             | • • • • • • • | • • • • • • • | • • • • • • •                           | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • | • • • • • • | • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • | • • • • • • |

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: JAN HOURS: 09-11 LST TO UTC: - 9 VISIBILITY IN METERS CEILING TN CF CF GE GE GE GE GE GF. GE GE GE GE. GE. GF. CF GE 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 65.0 65.8 66.7 66.7 66.7 67.5 67.5 68.3 58.3 22.5 39.2 39.2 55.0 58.3 61.7 GE 5000 21.7 GΕ 4500 21.7 22.5 40.8 40.8 56.7 60.0 63.3 66.7 67.5 68.3 68.3 68.3 69.2 69.2 70.0 70.0 23.3 57.5 64.2 67.5 68.3 69.2 69.2 69.2 70.0 70.0 70.8 70.8 4000 22.5 41.7 41.7 60.8 GE 67.5 68.3 69.2 69.2 70.0 70.0 70.8 70.8 GE 3500 22.5 23.3 41.7 41.7 57.5 60.8 64.2 69.2 GE 3000 25.8 26.7 46.7 46.7 65.0 68.3 72.5 75.8 78.3 79.2 79.2 79.2 81.7 81.7 82.5 82.5 GE 2500 25.8 26.7 46.7 46.7 65.0 68.3 72.5 75.8 78.3 79.2 79.2 79.2 81.7 81.7 82.5 82.5 2000 25.8 26.7 46.7 46.7 70.0 74.2 78.3 80.8 81.7 81.7 81.7 84.2 84.2 85.0 85.1 GE 66.7 GΕ 1800 25.8 26.7 46.7 46.7 66.7 70.0 74.2 78.3 80.8 81.7 81.7 81.7 84.2 84.2 85.0 85.0 GE 1500 25.8 26.7 46.7 46.7 68.3 71.7 78.3 82.5 85.0 85.8 85.8 85.8 88.3 88.3 89.2 89.2 87.5 90.8 91.7 91.7 25.8 26.7 72.5 80.0 85.0 88.3 88.3 88.3 90.8 GE 1200 46.7 46.7 69.2 25.8 26.7 46.7 46.7 70.0 74.2 82.5 87.5 90.0 90.8 91.7 91.7 95.0 95.8 96.7 96.7 GE 1000 90.0 90.8 96.7 GE 900 25.8 26.7 46.7 46.7 70.0 74.2 82.5 87.5 91.7 91.7 95.0 95.8 96.7 GE 800 25.8 26.7 46.7 46.7 70.0 74.2 82.5 89.2 91.7 92.5 93.3 93.3 96.7 97.5 98.3 98.3 74.2 91.7 25.8 26.7 46.7 92.5 93.3 93.3 96.7 97.5 98.3 98.3 GE 700 46.7 70.0 82.5 89.2 25.8 70.0 74.2 82.5 89.2 91.7 92.5 93.3 93.3 96.7 97.5 98.3 98.3 600 26.7 46.7 46.7 GE 500 25.8 26.7 46.7 46.7 70.0 74.2 82.5 89.2 91.7 92.5 93.3 93.3 96.7 97.5 98.3 98.3 GE 400 25.8 26.7 46.7 46.7 70.0 74.2 82.5 89.2 91.7 92.5 93.3 93.3 96.7 97.5 98.3 98.3 91.7 97.5 98.3 25.8 74.2 89.2 92.5 93.3 93.3 96.7 98.3 GE 300 26.7 46.7 46.7 70.0 82.5 98.3 GE 200 25.8 26.1 46.7 46.7 70.0 74.2 82.5 89.2 91.7 92.5 93.3 93.3 96.7 97.5 98.3 93.3 99 2 100.0 100.0 91.7 92.5 96.7 GE 100 25.8 26.7 46.7 46.7 70.0 74.2 82.5 89.2 93.3 GE 000 25.8 26.7 46.7 46.7 70.0 74.2 82.5 89.2 91.7 92.5 93.3 93.3 96.7 99.2 100.0 100.0 ......

TOTAL NUMBER OF OBSERVATIONS 120

D - 2 - 4

#### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN HOURS: 12-14 CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE FEET 112 80 60 48 20 40 32 24 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 9000 GE GE 8000 GE 7000 GE 6000 CF 5000 31.1 31.1 55.0 55.0 62.8 63.3 63.9 65.0 65.0 65.0 65.0 65.0 65.0 65.0 65.0 65.0 GE. 4500 55.6 55.6 63.3 63.9 65.6 65.6 65.6 31.1 31.1 64 A 65.6 65.6 65.6 65.6 65.6 65.6 GE 4000 33.3 33.3 58.3 58.3 67.2 67.8 68.3 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 GE 3500 34.4 60.6 60.6 69.4 70.0 70.6 71.7 71.7 34.4 71.7 71.7 71.7 71.7 71.7 71.7 71.7 GE 3000 37.2 37.2 63.9 63.9 76.1 77.2 79.4 80.6 81.1 81.1 81.1 81.1 81.7 81.7 81.7 81.7 2500 37.2 77.8 GE 37.2 63.9 63.9 78.9 81.1 82.2 82.8 82.8 82.8 82.8 83.3 83.3 83.3 83.3 GE 2000 37 B 37.8 64.4 64.4 78.3 79.4 81.7 82.8 83.9 84.4 83.3 83.3 83.9 84.4 GE 1800 37.8 37.8 64.4 64.4 78.9 80.6 82.8 83.9 84.4 84.4 85.0 85.0 85.6 85.6 85.6 85.6 GE 1500 38.3 38.3 65.6 65.6 80.6 84.: 87.2 88.3 88.9 88.9 90.6 90.6 91.1 91.1 91.1 91.1 GE 1200 38.3 38.3 65.6 65.6 80.6 85.0 88.3 89.4 90.0 90.0 91.7 91.7 92.2 92.2 92.2 92.2 90.6 GE 1000 38.3 38.3 65.6 65.6 80.6 85.0 88.3 89.4 90.6 95.6 95.6 97.2 97.2 97.2 97.2 GE 900 38.3 38.3 65.6 65.6 80.6 85.0 88.9 90.0 91.1 97.8 97.8 97.8 97.8 91.1 96.1 96.1 GE 800 38.3 38.3 65.6 65.6 80.6 85.0 89.4 90.6 93.3 93.3 98.3 98.3 100.0 100.0 100.0 100.0 38.3 89.4 700 65.6 65.6 85.0 90.6 GE 38.3 80.6 93.3 93.3 98.3 98.3 100.0 100.0 100.0 100.0 65.6 90.6 GE 600 38.3 38.3 65.6 80.6 85.0 89.4 93.3 93.3 98.3 98.3 100.0 100.0 100.0 100.0 GE 500 38.3 38.3 65.6 65.6 80.6 89.4 90.6 85.0 93.3 93.3 98.3 98.3 100.0 100.0 100.0 100.0 GE 400 38.3 38.3 65.6 65.6 80.6 85.0 89.4 90.6 93.3 93.3 98.3 98.3 100.0 100.0 100.0 100.0 GE 300 38.3 38.3 65.6 65.6 80.6 85.0 89.4 90.6 93.3 93.3 98.3 98.3 100.0 100.0 100.0 100.0 200 38.3 38.3 65.6 65.6 80.6 85.0 89.4 90.6 GΕ 93.3 93.3 98.3 98.3 100.0 100.0 100.0 100.0 GE 100 38.3 38.3 65.6 65.6 80.6 85.0 89.4 90.6 98.3 100.0 93.3 93.3 98.3 100.0 100.0 100.0 GE 000 38.3 38.3 65.6 65.6 80.6 85.0 89.4 90.6 93.3 93.3 98.3 98.3 100.0 100.0 100.0 100.0 ......

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN HOURS: 15-17 CEILING VISIBILITY IN METERS GE GE GE GE. TN GE GE GE GE GE GE GE GE GE GE GE GE 90 80 60 48 40 32 24 20 16 12 10 80 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 55.6 61.7 GE 5000 43.3 46.1 55.6 64.4 64.4 64.4 64.4 64.4 64.4 64.4 64.4 64.4 64.4 64.4 GE 4500 43.3 46.1 55.6 55.6 61.7 64.4 64.4 64.4 64.4 64.4 64.4 64.4 64.4 64.4 64.4 64.4 GE 4000 46.7 49.4 61.1 61.1 67.2 70.0 70.0 70.0 70.0 70.0 70.0 70.0 70.0 70.0 70.0 70.0 3500 GE 48.3 51.1 62.8 62.8 68.9 71.7 71.7 71.7 71.7 71.7 71.7 71.7 71.7 71.7 71.7 71.7 GE 3000 51.7 70.6 70.6 79.4 82.2 83.3 83.9 54.4 83.9 83.9 83.9 83.9 83.9 83.9 83.9 GΕ 2500 52.2 55.0 72.8 72.8 82.8 85.6 86.7 87.2 87.2 87.2 87.2 87.2 87.2 87.2 87.2 87.2 GE 2000 52.2 55.0 72.8 72.8 83.9 86.7 88.3 88.9 88.9 88.9 88.9 88.9 88.9 88.9 88.9 88.9 GE 1800 52.2 55.0 72.8 72.8 83.9 87.8 90.0 90.6 90.6 90.6 90.6 90.6 90.6 90.6 90.6 90.6 1500 85.0 89.4 91.7 92.2 GE 52.2 55.0 73.3 73.3 92.2 92.2 93.9 93.9 93.9 93.9 93.9 CE 1200 52.2 55.0 73.3 73.3 85.6 90.6 92.8 93.3 93.3 93.3 95.0 95.0 95.0 95.0 95.0 95.0 97.8 GE 1000 52.2 55.0 73.3 73.3 85.6 91.1 93.3 93.9 93.9 93.9 97.2 97.8 97.8 97.8 97 A GE 900 52.2 55.0 73.3 73.3 85.6 91.1 93.3 93.9 93.9 93.9 97.2 97.8 97.8 97.8 97.8 97.8 73.3 85.6 93.3 97.8 98.3 GE 800 52.2 55.0 73.3 91.1 94.4 94.4 94.4 98.3 98.3 98.3 98.3 700 93.3 94.4 99.4 99.4 GE 52.2 55.0 73.3 73.3 85.6 91.1 94.4 94.4 98.9 99.4 99.4 99.4 GE 600 52.2 55.0 73.3 73.3 85.6 91.1 93.3 94.4 94.4 98.9 99.4 99.4 99.4 99.4 55.0 73.3 73.3 85.6 91.1 93.3 94.4 94.4 94.4 98.9 99.4 99.4 99.4 99.4 99.4 GE 500 52.2 400 52.2 55.0 73.3 73.3 85.6 91.1 93.3 94.4 94.4 99.4 99.4 99.4 99.4 99.4 GE 94.4 98.9 GΕ 300 52.2 55.0 73.3 73.3 85.6 91.1 93.3 94.4 95.0 95.0 99.4 100.0 100.0 100.0 100.0 100.0 94.4 GE 200 52.2 55.0 73.3 73.3 85.6 91.1 93.3 95.0 95.0 99.4 100.0 100.0 100.0 100.0 100.0 GE 100 52.2 55.0 73.3 73.3 85.6 91.1 93.3 94.4 95.0 95.0 99.4 100.0 100.0 100.0 100.0 100.0 000 52.2 55.0 73.3 73.3 91.1 93.3 94.4 95.0 95.0 99.4 100.0 100.0 100.0 100.0 100.0 GE 85.6

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN HOURS: 18-20

| ··· |       | • • • • • • | • • • • • • • |      |               | • • • • • • • • |                |      |      | • • • • • • • • | • • • • • • |      |      | • • • • • • | • • • • • • • | • • • • • • • | • • • • • • |
|-----|-------|-------------|---------------|------|---------------|-----------------|----------------|------|------|-----------------|-------------|------|------|-------------|---------------|---------------|-------------|
|     | LING  | GE          | GE            | GE   | GE            | GE              | VISIBILI<br>GE | GE   | GE   | GE              | GE          | GE   | GE   | GE          | GE            | GE            | GE          |
|     | ET    | 112         | 90            | 80   | 60            | 48              | 40             | 32   | 24   | 20              | 16          | 12   | 10   | 08          | 06            | 04            | 00          |
|     | EI    | 1112        | 90            | 80   | 00            | 40              | 40             | 32   | 24   | 20              | 10          | 12   |      |             |               | 0.4           |             |
| ••• |       |             |               |      | • • • • • • • |                 | • • • • • • •  |      |      | • • • • • • • • |             |      |      |             |               |               |             |
| NO  | CEIL  |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
|     |       |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
|     | 20000 |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
|     | 18000 |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
|     | 16000 |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
|     | 14000 |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
| GE  | 12000 |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
| GE  | 10000 |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
| GE  | 9000  |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
| GΕ  | 8000  |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
| GE  | 7000  |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
| GE  | 6000  |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
| GE  | 5000  | 43.9        | 45.0          | 57.2 | 57.2          | 67.8            | 68.9           | 71.1 | 71.1 | 71.1            | 71.1        | 71.1 | 71.1 | 71.1        | 71.1          | 71.1          | 71.1        |
| GE  | 4500  | 43.9        | 45.0          | 57.2 | 57.2          | 67.8            | 68.9           | 71.1 | 71.1 | 71.1            | 71.1        | 71.1 | 71.1 | 71.1        | 71.1          | 71.1          | 71.1        |
| GE  | 4000  | 45.0        | 46.1          | 60.0 | 60.0          | 71.1            | 72.2           | 74.4 | 74.4 | 74.4            | 74.4        | 74.4 | 74.4 | 74.4        | 74.4          | 74.4          | 74.4        |
| GE  | 3500  | 47.8        | 48.9          | 62.8 | 62.8          | 74.4            | 75.6           | 77.8 | 77.8 | 77.8            | 77.8        | 77.8 | 77.8 | 77.8        | 77.8          | 77.8          | 77.8        |
| GE  | 3000  | 47.8        | 48.9          | 63.3 | 63.3          | 78.3            | 80.0           | 83.9 | 83.9 | 83.9            | 83.9        | 83.9 | 83.9 | 9. د8       | 83.9          | 83.9          | 83.9        |
|     |       |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
| GE  | 2500  | 47.8        | 48.9          | 63.3 | 63.3          | 78.3            | 81.1           | 85.6 | 85.6 | 85.6            | 85.6        | 85.6 | 85.6 | 85.6        | 85.6          | 85.6          | 85.6        |
| GE  | 2000  | 48.3        | 49.4          | 63.9 | 63.9          | 79.4            | 82.2           | 88.3 | 88.3 | 88.3            | 88.3        | 88.3 | 88.3 | 88.3        | 88.3          | 88.3          | 88.3        |
| GE  | 1800  | 48.9        | 50.0          | 64.4 | 64.4          | 80.0            | 82.8           | 88.9 | 88.9 | 88.9            | 88.9        | 88.9 | 88.9 | 88.9        | 88.9          | 88.9          | 88.9        |
| GE  | 1500  | 48.9        | 50.0          | 64.4 | 64.4          | 81.1            | 83.9           | 91.7 | 92.2 | 92.2            | 92.2        | 93.3 | 93.3 | 93.3        | 93.3          | 93.3          | 93.3        |
| GE  | 1200  | 48.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 92.8 | 93.3 | 94.4            | 94.4        | 95.6 | 95.6 | 95.6        | 95.6          | 95.6          | 95.6        |
| GE  | 1000  | 48.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 93.9 | 94.4 | 95.6            | 95.6        | 96.7 | 96.7 | 96.7        | 96.7          | 96.7          | 96.7        |
| GΕ  | 900   | 48.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 93.9 | 94.4 | 95.6            | 95.6        | 96.7 | 96.7 | 96.7        | 96.7          | 96.7          | 96.7        |
| CE  | 800   | 48.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 93 9 | 94.4 | 95.6            | 95.6        | 96.7 | 96.7 | 96.7        | 96.7          | 96.7          | 96.7        |
| GE  | 700   | 18.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 93.9 | 94.4 | 95.6            | 95.6        | 96.7 | 98.3 | 98.3        | 98.3          | 98.3          | 98.3        |
| GE  | 600   | 48.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 93.9 | 94.4 | 95.6            | 95.6        | 96.7 | 98.3 | 98.3        | 98.3          | 98.3          | 98.3        |
| GE  | 500   | 48.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 93.9 | 94.4 | 95.6            | 95.6        | 96.7 | 98.3 | 98.3        | 98.3          | 98.3          | 98.3        |
| GE  | 400   | 48.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 93.9 | 94.4 | 95.6            | 95.6        | 96.7 | 98.3 | 100.0       | 100.0         | 100.0         | 100.0       |
| GE  | 300   | 48.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 93.9 | 94.4 | 95.6            | 95.6        | 96.7 | 98.3 | 100.0       | 100.0         | 100.0         | 100.0       |
| GE  | 200   | 48.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 93.9 | 94.4 | 95.6            | 95.6        | 96.7 | 98.3 | 100.0       | 100.0         | 100.0         | 100.0       |
| GE  | 100   | 48.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 93.9 | 94.4 | 95.6            | 95.6        | 96.7 | 98.3 | 100.0       | 100.0         | 100.0         | 100.0       |
| 36  | 100   | 40.9        | .,0.0         | 04.4 | 04.4          | 02.2            | 03.0           | 23.3 | 74.4 | 93.0            | 93.0        | 30.7 | 20.3 | 100.0       | 100.0         | 100.0         | 100.0       |
| GE  | 000   | 48.9        | 50.0          | 64.4 | 64.4          | 82.2            | 85.0           | 93.9 | 94.4 | 95.6            | 95.6        | 96.7 | 98.3 | 100.0       | 100.0         | 100.0         | 100.0       |
|     |       |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |
|     |       |             |               |      |               |                 |                |      |      |                 |             |      |      |             |               |               |             |

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NAME: CAMP CASEY/TONGDUCHON KO STATION NUMBER: 471066 PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN HOURS: 21-23 CETLING VISIBILITY IN METERS GE GE GE GE GE GE GE GE GE GE GE GE GE GE 112 90 60 FEET 80 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 6000 GE 40.0 61.7 61.7 GE 5000 38.3 51.1 51.1 64.4 66.1 66.7 66.7 66.7 66.7 66.7 66.7 66.7 66.7 GE 4500 38.3 40.0 52.2 52.2 62.8 62.8 65.6 67.2 67.8 67.8 67.8 67.8 67.8 67.8 67.8 67.8 GE 4000 38.9 40.6 55.6 55.6 67.2 67.2 70.0 72.8 73.3 73.3 73.3 73.3 73.3 73.3 73.3 73.3 3500 59.4 59.4 73.9 GE 41.7 43.3 71.1 76.7 77.2 77.2 77.2 77.2 77.2 77.2 77.2 71.1 77.2 GE 3000 42.2 43.9 61.7 61.7 76.1 77.2 81.1 83.9 84.4 84.4 85.6 85.6 85.6 85.6 85.6 85.6 87.2 89.4 42.2 43.9 62.8 77.2 78.3 87.8 GE 2500 52.8 84.4 87.8 89.4 89.4 89.4 89.4 89.4 GE 2000 42.2 43.9 63.3 63.3 78.3 80.0 86.1 89.4 90.0 90.0 92.2 92.2 92.2 92.2 92.2 92.2 GE 1800 42.2 63.3 63.3 78.3 80.0 87.2 90.6 43.9 91.1 91.1 93.3 93.3 93.3 93.3 93.3 93.3 GE 1500 42.2 43.9 63.9 63.9 78.9 80.6 87.8 91.1 91.7 91.7 93.9 93.9 93.9 93.9 93.9 93.9 GE 1200 42.2 43.9 65.0 65.0 80.6 82.2 90.0 93.3 93.9 93.9 96.1 96.1 96.1 96.1 96.1 96.1 GE 1000 42.2 43.9 65.0 65.0 80.6 82.2 90.0 93.3 93.9 93.9 96.1 96.1 96.1 96.1 96.1 96.1 900 65.0 65.0 80.6 90.0 GE 42.2 43.9 82.2 93.3 93.9 96.1 96.1 96.1 93.9 96.1 96.1 96.1 96.1 GE 800 42.2 43.9 65.0 65.0 80.6 82.2 90.0 93.3 93.9 93.9 96.1 96.1 96.1 96.1 96.1 GE 700 42.2 43.9 65.0 65.0 81.1 82.8 90.6 93.9 94.4 94.4 97.8 98.3 98.3 98.3 98.3 98.3 GE 600 42.2 43.9 65.0 65.0 81.1 82.8 90.6 93.9 94.4 94.4 97.8 98.3 98.3 98.3 98.3 98.3 500 42.2 43.9 65.0 65.0 GE 81.1 82.8 90.6 93.9 94.4 94.4 97.8 98.3 98.3 98.3 98.3 98.3 GE 400 42.2 43.9 65.0 65.0 81.1 82.8 90.6 93.9 94.4 94.4 98.3 100.0 100.0 100.0 100.0 100.0 GE 300 42.2 43.9 65.0 65.0 81.1 82.8 90.6 93.9 94.4 94.4 98.3 100.0 100.0 100.0 100.0 100.0 65.0 GE 200 42.2 43.9 65.0 81.1 82.8 90.6 93.9 94.4 94.4 98.3 100.0 100.0 100.0 100.0 100.0 GΕ 42.2 43.9 65.0 65.0 81.1 82.8 90.6 93.9 94.4 94.4 98.3 100.0 100.0 100.0 100.0 100.0 GE 000 42.2 43.9 65.0 65.0 81.1 82.8 90.6 93.9 94.4 94.4 98.3 100.0 100.0 100.0 100.0 100.0 ------

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: JAN HOURS: ALL

| CEI  | LING       | • • • • • •  |              | • • • • • •  |              | ,            | VISIBIL      | TTY IN I     | METERS       | • • • • • •  | • • • • • •  | • • • • • •  |              | • • • • • • • |              | • • • • • •  | • • • • • •  |
|------|------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|---------------|--------------|--------------|--------------|
|      | N          | GE            | GE           | GE           | GE           |
| FE   | ET         | 112          | 90           | 80           | 60           | 48           | 40           | 32           | 24           | 20           | 16           | 12           | 10           | 08            | 06           | 04           | 00           |
|      | :          |              | <i>.</i>     |              |              |              | • • • • • •  |              | • • • • • •  |              | • • • • • •  | • • • • • •  | • • • • • •  | • • • • • •   | • • • • • •  | • • • • • •  | • • • • •    |
|      |            |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
| NO   | CEIL       |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
| O.P. | 20000      |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
|      | 18000      |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
|      | 16000      |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
|      | 14000      |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
|      | 12000      |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
|      |            |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
| GE   | 10000      |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
| GE   | 9000       |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
| GE   | 8000       |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
| GΕ   | 7000       |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
| GE   | 6000       |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
| GΕ   | 5000       | 34.7         | 35.8         | 50.9         | 50.9         | 62.4         | 63.5         | 66.4         | 67.8         | 68.2         | 68.4         | 68.5         | 68.5         | 68.6          | 68.6         | 68.7         | 68.7         |
| GE   | 4500       | 34.7         | 35.8         | 51.6         | 51.6         | 63.2         | 64.2         | 67.1         | 68.5         | 69.0         | 69.1         | 69.2         | 69.2         | 69.3          | 69.3         | 69.4         | 69.5         |
| 3E   | 4000       | 35.7         | 36.8         | 54.1         | 54.1         | 66.1         | 67.1         | 70.1         | 71.6         | 72.1         | 72.3         | 72.4         | 72.4         | 72.6          | 72.6         | 72.7         | 72.7         |
| 3E   | 3500       | 37 1         | 38.2         | 57.2         | 57.2         | 69.6         | 70.6         | 73.6         | 75.2         | 75.6         | 75.9         | 75.9         | 75.9         | 76.1          | 76.1         | 76.2         | 75.3         |
| 3E   | 3000       | 38.4         | 39.6         | 60.2         | 60.2         | 75.4         | 76.8         | 80.6         | 82.3         | 83.0         | 83.2         | 83.7         | 83.7         | 84.2          | 84.2         | 84.3         | 84.3         |
|      | ľ          |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
| ЗΕ   | 2500       | 38.5         | 39.7         | 60.8         | 60.8         | 76.6         | 78.2         | 82.8         | 84.5         | 85.4         | 85.6         | 86.1         | 86.1         | 86.7          | 86.7         | 86.7         | 86.8         |
| 7E   | 2000       | 38.7         | 39.9         | 61.4         | 61.4         | 78.0         | 79.6         | 84.6         | 86.4         | 87.3         | 87.5         | 88.6         | 88.8         | 89.4          | 89.4         | 89.5         | 89.6         |
| 3E   | 1800       | 38.8         | 40.0         | 61.5         | 61.5         | 78.2         | 80.0         | 85.1         | 86.9         | 87.9         | 88.1         | 89.2         | 89.4         | 90.0          | 90.0         | 90.1         | 90.1         |
| ЗΕ   | 1500       | 38.9         | 49.0         | 61.8         | 61.8         | 79.0         | 81.1         | 86.9         | 89.0         | 89.9         | 90.1         | 91.8         | 92.0         | 92.6          | 92.6         | 92.7         | 92.7         |
| Œ    | 1200       | 38.9         | 40.0         | 62.1         | 62.1         | 79.6         | 81.9         | 0.88         | 90.1         | 91.2         | 91.4         | 93.1         | 93.3         | 93.9          | 93.9         | 94.0         | 94.1         |
|      |            |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
| ₹E   | 1000       | 38.9         | 40.0         | 62.1         | 62.1         | 79.8         | 82.3         | 88.6         | 90.9         | 92.0         | 92.3         | 94.7         | 95.0         | 95.8          | 95.9         | 95.9         | 96.0         |
| Œ    | 900        | 38.9         | 40.0         | 62.1         | 62.1         | 79.8         | 82.3         | 88.7         | 90.9         | 92.1         | 92.5         | 94.9         | 95.2         | 96.0          | 96.1         | 96.2         | 96.2         |
| 3E   | 800<br>700 | 38.9<br>38.9 | 40.0         | 62.1         | 62.1         | 79.8<br>79.9 | 82.3         | 88.8         | 91.2         | 92.6         | 93.0<br>93.5 | 95.5<br>96.6 | 95.8<br>97.2 | 96.6<br>98.0  | 96.7<br>98.0 | 96.7<br>98.1 | 96.8<br>98.2 |
| Æ    | 600        | 38.9         | 40.0<br>40.0 | 62.1<br>62.1 | 62.1<br>62.1 | 79.9<br>79.9 | 82.4<br>82.4 | 88.8<br>88.8 | 91.4<br>91.4 | 93.0<br>93.0 | 93.5         | 96.6         | 97.2         | 98.0          | 98.0         | 98.1         | 98.2         |
| 715  | 1,00       | 30.9         | 40.0         | 02.1         | 02.1         | 79.9         | 02.4         | 00.0         | 91.4         | 93.0         | 93.3         | 50.0         | 31.2         | 90.0          | 30.0         | 30.1         | 50.2         |
| Æ    | 500        | 38.9         | 40.0         | 62.1         | 62.1         | 79.9         | 82.4         | 88.8         | 91.4         | 93.0         | 93.7         | 96.8         | 97.4         | 98.2          | 98.3         | 98.3         | 98.4         |
| ŧΕ   | 400        | 38.9         | 40.0         | 62.1         | 62.1         | 79.9         | 82.4         | 88.8         | 91.4         | 93.0         | 93.7         | 96.9         | 97.6         | 98.6          | 98.7         | 98.8         | 98.8         |
| ŧΕ   | 300        | 38.9         | 40.0         | 62.1         | 62.1         | 79.9         | 82.4         | 88.8         | 91.4         | 93.0         | 93.8         | 97.0         | 97.7         | 98.7          | 98.8         | 98.8         | 98.9         |
| 3E   | 200        | 38.9         | 40.0         | 62.1         | 62.1         | 79.9         | 82.4         | 88.8         | 91.4         | 93.0         | 93.8         | 97.0         | 97.7         | 98.1          | 98.8         | 98.8         | 98.9         |
| Æ    | 100        | 38.9         | 40.0         | 62.1         | 62.1         | 79.9         | 82.4         | 88.8         | 91.4         | 93.0         | 93.8         | 97.0         | 97.7         | 98.8          | 99.1         | 99.1         | 99.6         |
|      |            |              |              |              |              |              |              |              |              |              |              |              |              |               |              |              |              |
| Æ    | 000        | 38.9         | 40.0         | 62.1         | 62.1         | 79.9         | 82.4         | 88.88        | 91.4         | 93.0         | 93.8         | 97.0         | 97.7         | 98.8          | 99.1         | 99.1         | 100.0        |
|      |            |              |              |              |              |              | <i>.</i>     |              |              |              |              |              |              |               |              |              |              |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO
LST TO UTC: - 9 PERIOD OF RECORD: JUL 80 - JUN 90
MONTH: FEB HOURS: 00-02

CEILING VISIBILITY IN METERS

| CEI      | LING  |              |               |      |      | 7             | VISIBIL:     | I NI YTI | METERS        |               |              |               |               |              |               |              |             |
|----------|-------|--------------|---------------|------|------|---------------|--------------|----------|---------------|---------------|--------------|---------------|---------------|--------------|---------------|--------------|-------------|
| I        | N     | GE           | CE            | GE   | GE   | GE            | GE           | GE       | GE            | GE            | GE           | GE            | GE            | GE           | GE            | GE           | GE          |
| FE       | ET    | 112          | 90            | 80   | 60   | 48            | 40           | 32       | 24            | 20            | 16           | 12            | 10            | 08           | 06            | 04           | 00          |
|          |       |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
|          |       |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| NO       | CEIL  |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
|          |       |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| GE       | 20000 |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
|          | 18000 |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
|          | 16000 |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
|          | 14000 |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
|          | 12000 |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| GL       | 12000 |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| CF       | 10000 |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| GE       | 9000  |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| GE       | 8000  |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| GE       | 7000  |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| GE       | 6000  |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| GE       | 8000  |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| GE       | 5000  | 27.9         | 27.9          | 43.0 | 43.0 | 58.2          | 61.2         | 70.3     | 71.5          | 72.1          | 72.1         | 72.1          | 72.1          | 72.1         | 72.1          | 72.1         | 72.1        |
| GE       | 4500  | 27.9         | 27.9          | 43.0 | 43.0 | 58.2          | 61.2         | 70.3     | 71.5          | 72.1          | 72.1         | 72.1          | 72.1          | 72.1         | 72.1          | 72.1         | 72.1        |
|          | 4000  | 1            |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| GE       |       | 29.1         | 29.1          | 46.1 | 46.1 | 63.0          | 66.7         | 75.8     | 77.6          | 78.2          | 78.2         | 78.2          | 78.2          | 78.2         | 78.2          | 78.2         | 78.2        |
| GE       | 3500  | 29.7         | 29.7          | 46.7 | 46.7 | 64.2          | 67.9         | 77.6     | 80.6          | 81.8          | 81.8         | 82.4          | 82.4          | 82.4         | 82.4          | 82.4         | 82.4        |
| GE       | 3000  | 32.7         | 32.7          | 49.7 | 49.7 | 70.9          | 74.5         | 85.5     | 89.7          | 90.9          | 90.9         | 91.5          | 91.5          | 91.5         | 91.5          | 91.5         | 91.5        |
| ar       | 2500  | 22.7         | 12 7          | 49.7 | 49.7 | 70.0          | 74 6         | 85.5     | 00.7          | 00.0          | 00 0         | 01 5          | 91.5          | 01 5         | 01 5          | 01 5         | 91.5        |
| GE<br>GE | 2000  | 32.7<br>32.7 | 32.7<br>32.7  | 49.7 | 49.7 | 70.9<br>71.5  | 74.5<br>75.8 | 87.3     | 89.7<br>91.5  | 90.9<br>92.7  | 90.9<br>93.9 | 91.5<br>94.5  | 94.5          | 91.5<br>94.5 | 91.5<br>94.5  | 91.5<br>94.5 | 94.5        |
|          |       |              |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| GE       | 1800  | 32.7         | 32.7          | 49.7 | 49.7 | 71.5          | 75.8         | 87.3     | 91.5          | 92.7          | 93.9         | 94.5          | 94.5          | 94.5         | 94.5          | 94.5         | 94.5        |
| GE       | 1500  | 32.7         | 32.7          | 49.7 | 49.7 | 71.5          | 75.8         | 87.9     | 92.1          | 93.9          | 95.2         | 96.4          | 96.4          | 96.4         | 96.4          | 96.4         | 96.4        |
| GE       | 1200  | 32.7         | 32.7          | 49.7 | 49.7 | 72.1          | 76.4         | 88.5     | 92.7          | 94.5          | 95.8         | 97.0          | 97.0          | 97.0         | 97.0          | 97.0         | 97.0        |
| GE       | 1000; | 32.7         | 32.7          | 49.7 | 49.7 | 72.1          | 77.0         | 89.1     | 93.3          | 95.2          | 97.6         | 98.8          | 98.8          | 98.8         | 98.8          | 98.8         | 98.8        |
| GE       | 900   | 32.7         | 32.7          | 49.7 | 49.7 | 72.1          | 77.0         | 89.1     | 93.3          | 95.2          | 97.6         | 98.8          | 98.8          | 98.8         | 98.8          | 98.8         | 98.8        |
|          |       | 1            |               |      |      |               |              |          |               |               |              |               |               |              |               |              |             |
| GF.      | 800   | 32.7         | 32.7          | 49.7 | 49.7 | 72.1          | 77.0         | 89.1     | 93.3          | 95.2          | 97.6         | 98.8          | 98.8          | 98.8         | 98.8          | 98.8         | 98.8        |
| GE       | 700   | 32.7         | 32.7          | 49.7 | 49.7 | 72.1          | 77.0         | 89.1     | 93.3          | 95.2          | 97.6         | 98.8          | 98.8          | 98.8         | 98.8          | 98.8         | 98.8        |
| GE       | 600   | 32.7         | 32.7          | 49.7 | 49.7 | 72.1          | 77.0         | 89.1     | 93.3          | 95.2          | 97.6         | 98.8          | 98.8          | 98.8         | 98.8          | 98.8         | 98.8        |
| ar.      | 500   | 32.7         | 12 7          | 40.7 | 49.7 | 70 1          | 77.0         | 89.1     | 02.1          | 05.2          | 07.6         | 00.0          | 98.8          | 00.0         | 98.8          | 98.8         | 98.8        |
| GE       | 400   | 32.7         | 32.7          | 49.7 | 49.7 | 72.1          | 77.0<br>77.0 |          | 93.3          | 95.2          | 97.6<br>97.6 | 98.8<br>100.0 |               | 98.8         |               | 100.0        | 100.0       |
| GE       |       | ľ            | 32.7          | 49.7 |      | 72.1          |              | 89.1     | 93.3          | 95.2          |              |               | 100.0         | 100.0        | 100.0         |              |             |
| GE       | 300   | 32.7         | 32.7          | 49.7 | 49.7 | 72.1          | 77.0         | 89.1     | 93.3          | 95.2          | 97.6         | 100.0         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0       |
| GE       | 200   | 32.7         | 32.7          | 49.7 | 49.7 | 72.1          | 77.0         | 89.1     | 93.3          | 95.2          | 97.6         | 100.0         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0       |
| GE       | 100   | 32.7         | 32.7          | 49.7 | 49.7 | 72.1          | 77.0         | 89.1     | 93.3          | 95.2          | 97.6         | 100.0         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0       |
| 0.5      | 000   | 32.7         | 22.7          | 40.7 | 40.7 | 72 1          | 77.6         | 00.1     | 03.3          | 05.2          | 07.6         | 100.0         | 100.0         | 100 0        | 100.0         | 100.0        | 100.0       |
| GE       | 000   | 32.7         | 32.7          | 49.7 | 49.7 | 72.1          | 77.0         | 89.1     | 93.3          | 95.2          | 97.6         | 100.0         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0       |
|          |       |              | • • • • • • • |      |      | • • • • • • • |              |          | • • • • • • • | • • • • • • • |              | • • • • • •   | • • • • • • • | • • • • • •  | • • • • • • • |              | • • • • • • |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

'ATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: FEB HOURS: 03-05

| ILING |      |      |      |      |      | VISIBIL |      |      |      |      |      |          |      |        |      |      |
|-------|------|------|------|------|------|---------|------|------|------|------|------|----------|------|--------|------|------|
| IN    | GE   | GE   | GE   | GE   | GE   | GE      | GE   | GE   | GE   | GE   | GE   | GE<br>10 | GE   | GE     | GE   | GE   |
| EET   | 112  | 90   | 80   | 60   | 48   | 40      | 32   | 24   | 20   | 16   | 12   | 10       | 08   | 06<br> | 04   | 00   |
| CEIL  |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| CELL  |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| 20000 |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| 18000 |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| 16000 |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| 14000 |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| 12000 |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| 10000 |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| 9000  |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| 8000  |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| 7000  |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| 6000  |      |      |      |      |      |         |      |      |      |      |      |          |      |        |      |      |
| 5000  | 27.3 | 27.9 | 39.4 | 39.4 | 53.9 | 56.4    | 64.8 | 65.5 | 66.1 | 66.7 | 67.9 | 67.9     | 69.1 | 69.1   | 69.1 | 70.  |
| 4500  | 27.3 | 27.9 | 39.4 | 39.4 | 53.9 | 56.4    | 64.8 | 65.5 | 66.1 | 66.7 | 67.9 | 67.9     | 69.1 | 69.1   | 69.1 | 70.  |
| 4000  | 27.9 | 28.5 | 42.4 | 42.4 | 60.0 | 62.4    | 71.5 | 72.1 | 72.7 | 73.3 | 74.5 | 74.5     | 75.8 | 75.8   | 75.8 | 77.  |
| 3500  | 28.5 | 29.1 | 43.0 | 43.0 | 62.4 | 64.8    | 73.9 | 74.5 | 75.2 | 76.4 | 79.4 | 79.4     | 80.6 | 80.6   | 80.6 | 82.  |
| 3000  | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 67.3    | 77.6 | 78.2 | 79.4 | 80.6 | 83.6 | 83.6     | 84.8 | 84.8   | 84.8 | 86.  |
| 2500  | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 67.3    | 77.6 | 78.2 | 79.4 | 80.6 | 83.6 | 84.8     | 86.1 | 86.1   | 86.1 | 87.  |
| 2000  | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 79.4 | 80.0 | 81.2 | 84.2 | 87.9 | 89.1     | 90.3 | 90.3   | 90.3 | 92.  |
| 1800  | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 80.0 | 81.8 | 83.0 | 86.1 | 89.7 | 90.9     | 92.1 | 92.1   | 92.1 | 93.  |
| 1500  | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 80.0 | 81.8 | 84.8 | 87.9 | 91.5 | 93.3     | 95.2 | 95.2   | 95.2 | 97.  |
| 1200  | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 80.0 | 81.8 | 84.8 | 87.9 | 91.5 | 93.3     | 95.2 | 95.2   | 95.2 | 97.  |
| 1000  | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 80.0 | 81.8 | 84.8 | 87.9 | 91.5 | 93.3     | 95.2 | 95.2   | 95.2 | 97.  |
| 900   | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 80.0 | 81.8 | 84.8 | 87.9 | 91.5 | 93.3     | 95.2 | 95.2   | 95.2 | 97.  |
| 800   | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 80.0 | 81.8 | 84.8 | 87.9 | 91.5 | 93.3     | 95.2 | 95.2   | 95.2 | 97.  |
| 700   | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 81.8 | 83.6 | 86.7 | 89.7 | 93.3 | 95.2     | 97.0 | 97.0   | 97.0 | 98.  |
| 600   | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 81.8 | 83.6 | 86.7 | 89.7 | 93.3 | 95.2     | 97.0 | 97.0   | 97.0 | 98.  |
| 500   | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 81.8 | 83.6 | 86.7 | 89.7 | 93.3 | 96.4     | 98.2 | 98.2   | 98.2 | 100. |
| 400   | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 81.8 | 83.6 | 86.7 | 89.7 | 93.3 | 96.4     | 98.2 | 98.2   | 98.2 | 100. |
| 300   | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 81.8 | 83.6 | 86.7 | 89.7 | 93.3 | 96.4     | 98.2 | 98.2   | 98.2 | 100. |
| 200   | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 81.8 | 83.6 | 86.7 | 89.7 | 93.3 | 96.4     | 98.2 | 98.2   | 98.2 | 100. |
| 100   | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 81.8 | 83.6 | 86.7 | 89.7 | 93.3 | 96.4     | 98.2 | 98.2   | 98.2 | 100. |
| 000   | 30.9 | 31.5 | 45.5 | 45.5 | 64.8 | 69.1    | 81.8 | 83.6 | 86.7 | 89.7 | 93.3 | 96.4     | 98.2 | 98.2   | 98.2 | 100. |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: FEB HOURS: 06-08

| CEI      | LING  |               | • • • • • • • |              |              | · · · · · · <sub>·</sub> | VISIBIL      | יייייי       | METERS       |              | • • • • • •  |              |              | • • • • • •  | • • • • • • • |              | • • • • • •  |
|----------|-------|---------------|---------------|--------------|--------------|--------------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|---------------|--------------|--------------|
|          | N     | GE            | GE            | GE           | GE           | GE                       | GE           | GE           | GE           | GE           | GE           | GE           | GE           | GE           | GE            | GE           | GE           |
|          | ET    | 112           | 90            | 80           | 60           | 48                       | 40           | 32           | 24           | 20           | 16           | 12           | 10           | 08           | 06            | 04           | 00           |
|          |       |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
|          |       |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
| NO       | CEIL  |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
| GE       | 20000 |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
|          | 18000 |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
|          | 16000 |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
| GE       | 14000 |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
| GE       | 12000 |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
|          |       |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
|          | 10000 |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
| GE       | 9000  |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
| GE       | 8000  | i<br>I        |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
| GE       | 7000  |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
| GE       | 6000  |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
| GE       | 5000  | 22.3          | 22.3          | 34.3         | 34.3         | 53.6                     | 57.8         | 59.6         | 63.3         | 63.9         | 63.9         | 66.3         | 66.3         | 66.9         | 66.9          | 66.9         | 68.1         |
| GE       | 4500  | 22.9          | 22.9          | 34.9         | 34.9         | 54.2                     | 58.4         | 60.2         | 63.9         | 64.5         | 64.5         | 66.9         | 66.9         | 67.5         | 67.5          | 67.5         | 68.7         |
| GE       | 4000  | 22.9          | 22.9          | 36.1         | 36.1         | 55.4                     | 59.6         | 62.0         | 66.3         | 68.1         | 68.1         | 70.5         | 70.5         | 71.1         | 71.1          | 71.1         | 72.3         |
| GE       | 3500  | 22.9          | 22.9          | 37.3         | 37.3         | 58.4                     | 63.9         | 66.3         | 70.5         | 72.9         | 72.9         | 75.3         | 75.9         | 76.5         | 76.5          | 77.1         | 78.3         |
| GE       | 3000  | 24.7          | 24.7          | 39.8         | 39.8         | 60.8                     | 66.3         | 68.7         | 72.9         | 75.3         | 75.3         | 79.5         | 80.1         | 80.7         | 80.7          | 81.3         | 82.5         |
|          |       |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
| GE       | 2500  | 24.7          | 24.7          | 39.8         | 39.8         | 61.4                     | 66.9         | 69.3         | 73.5         | 75.9         | 75.9         | 80.7         | 81.3         | 82.5         | 82.5          | 83.1         | 84.3         |
| GE       | 2000  | 24.7          | 24.7          | 39.8         | 39.8         | 62.0                     | 68.7         | 71.7         | 75.9         | 78.9         | 79.5         | 85.5         | 86.1         | 87.3         | 87.3          | 88.0         | 89.2         |
| GE       | 1800  | 24.7          | 24.7          | 39.8         | 39.8         | 62.0                     | 68.7         | 71.7         | 75.9         | 78.9         | 79.5         | 85.5         | 86.1         | 87.3         | 87.3          | 88.0         | 89.2         |
| GE       | 1500  | 24.7          | 24.7          | 39.8         | 39.8         | 62.0                     | 68.7         | 71.7         | 75.9         | 78.9         | 79.5         | 85.7         | 88.0         | 89.8         | 89.8          | 90.4         | 91.6         |
| GE       | 1200  | 24.7          | 24.7          | 39.8         | 39.8         | 62.0                     | 68.7         | 71.7         | 75.9         | 78.9         | 79.5         | 86.7         | 88.0         | 90.4         | 90.4          | 91.0         | 92.2         |
| an       | 1000  | 24.7          | 25. )         | 40.4         | 40.4         | 62.7                     | 60.0         | 72.5         | ~~ ~         | 20.2         | 01 2         | 00.6         | aa <b>a</b>  | 00.0         | 00.0          | 03.4         | 24.6         |
| GE<br>GE | 1000  | 24.7<br>24.7  | 25.3<br>25.3  | 40.4<br>40.4 | 40.4         | 62.7                     | 69.9<br>69.9 | 73.5<br>73.5 | 77.7<br>77.7 | 80.7<br>80.7 | 81.3<br>81.3 | 88.6<br>88.6 | 89.8<br>89.8 | 92.2<br>92.2 | 92.2<br>92.2  | 93.4<br>93.4 | 94.6<br>94.6 |
| GE       | 800   | 24.7          | 25.3          | 40.4         | 40.4<br>40.4 | 62.7<br>62.7             | 69.9         | 73.5         | 77.7         | 80.7         | 81.3         | 88.6         | 89.8         | 92.2         | 92.2          | 93.4         | 94.6         |
| GE.      | 700   | 24.7          | 25.3          | 40.4         | 40.4         | 62.7                     | 69.9         | 73.5         | 77.7         | 80.7         | 81.3         | 88.6         | 89.8         | 92.2         | 92.2          | 93.4         | 94.6         |
| GE       | 600   | 24.7          | 25.3          | 40.4         | 40.4         | 62.7                     | 69.9         | 73.5         | 77.7         | 80.7         | 81.3         | 88.6         | 89.8         | 92.2         | 92.2          | 93.4         | 94.6         |
| GE.      | 900   | 64.7          | 23.3          | 40.4         | 40.4         | 02.7                     | 09.9         | 13.3         | //./         | 00.7         | 01.5         | 00.0         | 07.0         | 72.2         | 76.2          | 93.4         | 94.0         |
| GE       | 500   | 24.7          | 25.3          | 40.4         | 40.4         | 62.7                     | 69.9         | 73.5         | 78.3         | 81.3         | 81.9         | 89.2         | 90.4         | 93.4         | 93.4          | 94.6         | 95.8         |
| GE       | 400   | 24.7          | 25.3          | 40.4         | 40.4         | 62.7                     | 69.9         | 73.5         | 78.3         | 81.3         | 81.9         | 89.8         | 91.6         | 94.6         | 94.6          | 96.4         | 97.6         |
| GE       | 300   | 24.7          | 25.3          | 40.4         | 40.4         | 62.7                     | 69.9         | 73.5         | 78.3         | 81.3         | 81.9         | 89.8         | 91.6         | 94.6         | 94.6          | 96.4         | 97.6         |
| GE       | 200   | 24.7          | 25.3          | 40.4         | 40.4         | 62.7                     | 69.9         | 73.5         | 78.3         | 81.3         | 81.9         | 89.8         | 91.6         | 94.6         | 94.6          | 96.4         | 98.8         |
| GE       | 100   | 24.7          | 25.3          | 40.4         | 40.4         | 62.7                     | 69.9         | 73.5         | 78.3         | 81.3         | 81.9         | 89.8         | 91.6         | 94.6         | 94.6          | 96.4         | 98.8         |
|          | Ì     |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |
| GE       | 000   | 24.7          | 25 - 3        | 40.4         | 40.4         | 62.7                     | 69.9         | 73.5         | 78.3         | 81.3         | 81.9         | 89.8         | 91.6         | 94.6         | 94.6          | 96.4         | 100.0        |
|          |       | · · · · · · · |               |              |              |                          |              | <b></b> .    |              |              | • • • • • •  |              |              |              | • • • • • •   |              |              |
|          |       |               |               |              |              |                          |              |              |              |              |              |              |              |              |               |              |              |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

TATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: FEB HOURS: 09-11

| :E1 | LING      | • • • • • • |      | • • • • • • |      | • • • • • • • • | VISIBIL | ITY IN | METERS   | • • • • • • | • • • • • • • | • • • • • • |               |      |              | • • • • • • | • • • • • • |
|-----|-----------|-------------|------|-------------|------|-----------------|---------|--------|----------|-------------|---------------|-------------|---------------|------|--------------|-------------|-------------|
|     | N         | GE          | GE   | GE          | GE   | GE              | GE      | GE     | GE       | GE          | GE            | GE          | GE            | GE   | GE           | GE          | GE          |
|     | ET        | 112         | 90   | 80          | 60   | 48              | 40      | 32     | 24       | 20          | 16            | 12          | 10            | 08   | 06           | 04          | 00          |
| ٠.  |           | ,<br>       |      |             |      |                 |         |        | <i>.</i> |             |               |             |               |      |              |             |             |
|     |           | <b>\</b>    |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| Ю   | CEIL      |             |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
|     |           | 1           |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| ŀΕ  | 20000     |             |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| F.  | 18000     |             |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| F.  | 16000     |             |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| Æ   | 14000     | ļ           |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| ïΕ  | 12000     |             |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
|     |           | ļ           |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| żΕ  | 10000     | l           |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| żΕ  | 9000      | į           |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| ;E  | 8000      | -           |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| ;E; | 7000      | ļ           |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| Æ   | 6000      |             |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
|     |           | <b>!</b>    |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| ìΕ  | 5000      | 19.6        | 21.4 | 36.6        | 36.6 | 54.5            | 57.1    | 61.6   | 62.5     | 64.3        | 65.2          | 66.1        | 66.1          | 67.0 | 67.0         | 67.0        | 67.9        |
| æ   | 4500      | 19.6        | 21.4 | 36.6        | 36.6 | 54.5            | 57.1    | 61.6   | 62.5     | 64.3        | 65.2          | 66.1        | 66.1          | 67.0 | 67.0         | 67.0        | 67.9        |
| E   | 4000      | 21.4        | 23.2 | 39.3        | 39.3 | 58.9            | 62.5    | 67.0   | 68.8     | 71.4        | 72.3          | 73.2        | 73.2          | 74.1 | 74.1         | 74.1        | 75.0        |
| ŀΕ  | 3500      | 21.4        | 23.2 | 39.3        | 39.3 | 59.8            | 63.4    | 67.9   | 70.5     | 73.2        | 75.0          | 76.8        | 76.8          | 77.7 | 77 <b>.7</b> | 77.7        | 78.6        |
| Œ   | 3000      | 23.2        | 25.0 | 44.6        | 44.6 | 67.9            | 72.3    | 76.8   | 80.4     | 83.0        | 84.8          | 87.5        | 87.5          | 88.4 | 88.4         | 88.4        | 89.3        |
|     |           | ļ           |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| Œ   | 2500      | 23.2        | 25.0 | 44.6        | 44.6 | 67.9            | 73.2    | 77.7   | 81.3     | 83.9        | 85.7          | 88.4        | 88.4          | 89.3 | 89.3         | 89.3        | 90.2        |
| H.  | 2000      | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 90.2        | 90.2          | 92.9 | 92.9         | 92.9        | 93.8        |
| Œ   | 1800      | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 90.2        | 90.2          | 92.9 | 92.9         | 92.9        | 93.8        |
| Œ   | 1500      | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 90.2        | 90.2          | 92.9 | 92.9         | 92.9        | 93.8        |
| E   | 1200      | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 90.2        | 90.2          | 92.9 | 92.9         | 92.9        | 93.8        |
|     |           |             |      |             |      |                 |         |        |          |             |               |             |               |      |              |             |             |
| Е   | 1000      | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 90.2        | 90.2          | 92.9 | 92.9         | 92.9        | 93.8        |
| E   | 900       | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 90.2        | 90.2          | 93.8 | 93.8         | 93.8        | 94.6        |
| F.  | 800       | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 90.2        | 90.2          | 93.8 | 93.8         | 93.8        | 94.6        |
| E   | 700       | 21.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 90.2        | 90.2          | 93.8 | 93.8         | 93.8        | 94.6        |
| F.  | 600       | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 90.2        | 90.2          | 93.8 | 93.8         | 93.8        | 94.6        |
| _   |           |             | 25 0 |             |      |                 | 75.0    | 70.5   |          |             |               |             |               |      |              |             |             |
| Ε   | 500       | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 91.1        | 92.0          | 95.5 | 95.5         | 95.5        | 96.4        |
| E   | 400       | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 91.1        | 92.0          | 96.4 | 96.4         | 96.4        | 97.3        |
| E   | 300       | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 91.1        | 92.0          | 96.4 | 96.4         | 96.4        | 97.3        |
| F.  | 200       | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 91.1        | 92.0          | 96.4 | 96.4         | 96.4        | 98.2        |
| E   | 100       | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | 79.5   | 83.0     | 85.7        | 87.5          | 91.1        | 92.0          | 96.4 | 96.4         | 96.4        | 98.2        |
|     | 000       | ,,,         | 25.0 |             | 44.6 | 60.6            | 75.0    | 10.5   | 0.2.0    | 05 7        | 07.5          | 01.         | 02.6          | 06.4 | 06.4         | 06.4        | 100.0       |
| E   | 000       | 23.2        | 25.0 | 44.6        | 44.6 | 69.6            | 75.0    | /9.5   | 83.0     | 85.7        | 87.5          | 91.1        | 92.0          | 96.4 | 96.4         | 96.4        | 100.0       |
|     | • • • • • |             |      |             |      | · · · · · · ·   |         |        |          |             |               |             | • • • • • • • |      | • • • • • •  |             | • • • • • • |

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 LST TO UTC: - 9 MONTH: FEB HOURS: 12-14 CEILING VISIBILITY IN METERS IN GE GE GΞ GE GE GE GE GE GE GE GΕ GE GE GE GE FEEC 112 90 80 60 48 40 32 20 16 12 24 10 86 06 04 00 NO CETT. GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GΕ 6000 GE 5000 29.8 29.8 57.1 57.1 71.4 72.0 72.5 72.6 73.2 73.8 74.4 74.4 74.4 74.4 74.4 74.4 GΕ 4500 31.5 si.5 58.9 58.9 73.2 73.8 74:4 74.4 75.0 75.6 76.2 76.2 76.2 76.2 76.2 76.2 77.4 78.0 78.6 GE 4000 33.9 33.9 63.1 63.1 78.6 79.2 79.8 80.4 80.4 80.4 80.4 80.4 80.4 80.4 GE. 3500 33.9 33.9 63.7 63.7 79.2 79.8 80.4 81.0 81.5 82.1 82.1 82.1 82.1 82.1 82.1 GΕ 3000 35.7 35.7 70.2 70.2 87.5 88.1 88.7 90.5 91.1 91.7 92.3 92.3 92.3 92.3 92.3 92.3 35.7 70.2 GE 2500 35.7 70.2 87.5 88.1 88.7 90.5 91.1 91.7 92.3 92.3 92.3 92.3 92.3 92.3 GE 2000 35.7 35.7 70.3 70.2 89.3 89.9 91.1 92.9 93.5 94.0 95.2 95.2 95.2 95.2 95.2 95.2 GE 1800 35.7 70.2 70.2 91.1 95.2 95.2 95.2 95.2 95.2 35.7 89.3 89.9 92.9 93.5 94.0 95.2 GE. 1500 35.7 35.7 70.2 70.2 90.5 91.1 92.3 94.0 94.6 95.2 96.4 96.4 97.0 97.6 97.6 97.6 GE 1200 35.7 35.7 70.2 70.2 90.5 91.1 92.3 94.0 94.6 95.2 96.4 96.4 97.0 97.6 97.6 97.6 GE 1000 35.7 35.7 70.2 70.2 90.5 91.1 92.3 94.0 94.6 95.2 96.4 96.4 97.0 97.6 97.6 97.6 GE 900 35.7 35.7 70.2 70.2 90.5 91.1 92.3 94.0 94.6 95.2 96.4 96.4 97.0 97.6 97.6 97.6 35.7 35.7 70.2 92.3 GE 800 70.2 90.5 91.1 94.0 94.6 95.2 96.4 97.0 97.6 98.2 98.2 98.2 GΕ 700 35.7 35.7 70.2 70.2 90.5 91.1 92.3 94.0 94.6 95.2 96.4 97.0 97.6 98.2 98.2 98.2 GE 35.7 70.2 600 35.7 70.2 90.5 92.3 94.0 95.2 96.4 97.0 97.6 98.2 91.1 94.6 98.2 98.2 GE 500 35.7 35.7 70.2 70.2 90.5 91.1 92.3 94.0 94.6 95.8 97.6 98.2 98.8 99.4 99.4 GE 400 35.7 35.7 90.5 91.1 92.3 95.8 97.6 98.8 100.0 100.0 100.0 70.2 70.2 94.0 94.6 98.2 GE 300 35.7 35.7 70.2 70.2 90.5 91.1 92.3 94.0 94.6 95.8 97.6 98.2 98.8 100.0 100.0 100.0 GE 200 35.7 90.5 91.1 92.3 95.8 97.6 35.7 70.2 70.2 94.0 94.6 98.2 98.8 100.0 100.0 100.0 GE 100 35.7 35.7 70.2 70.2 90.5 91.1 92.3 94.0 94.6 95.8 97.6 98.2 98.8 100.0 100.0 100.0 GE 70.2 92.3 95.8 97.6 000 35.7 35.7 70.2 90.5 91.1 94.0 94.6 98.2 93.8 100.0 100.0 100.0

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY CBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9 MONTH: FEB HOURS: 15-17 CEILING VISIBILITY IN METERS GE GE GE IN GE GE GE GE GE GE GE GE GE GE GE 112 48 32 20 16 12 10 08 06 90 82 60 40 24 04 00 FEET NO CELL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 7000 GE GE 6000 72.0 72.0 39.3 67.9 67.9 72.0 72.0 72.0 72.0 72.0 72.0 72.0 72.0 72.0 GE 5000 38.7 72.0 GE 4500 40.5 41.1 69.6 69.6 73.8 73.8 73.8 73.8 73.8 73.8 73.8 73.8 73 B 73.8 73 A 73.8 4000 42.9 43.5 73.2 73.2 78.0 78.0 78.0 78.0 78.0 78.0 78.0 78.0 78.0 78.0 78.0 78.0 GΕ 79.2 79.2 79.2 3500 79.2 79.2 79.2 79.2 79.2 79.2 79.2 79.2 79.2 GE 42.9 43.5 73.2 73.2 GE 3000 47.6 48.2 79.8 79.8 89.9 90.5 91.1 91.1 91.1 91.1 91.1 91.1 91.1 91.1 91.1 91.1 48.2 79.8 79.8 91.7 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 GE 2500 47.6 92.9 94.0 GE 2000 47.6 48.2 79.8 79.8 92.3 94.6 97.0 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 1800 47.6 48.2 79.8 79.8 92.3 94.6 97.0 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 GE 1500 47.6 48.2 19.8 97.6 98.2 98.2 98.2 98.2 98.2 98.2 98.2 98.2 GE 79.8 92.9 95.2 98.2 GE 1200 47.6 48.2 79.8 79.8 92.9 95.2 97.6 98.2 98.2 98.2 98.2 98.2 98.2 98.2 98.2 98.2 GE 1000 47.6 48.2 79.8 79.8 94.0 96.4 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 900 47.6 48.2 79.8 79.8 94.0 96.4 98.8 100.0 100.0 100.C 100.0 100.0 100.0 100.0 100.0 47 5 48.2 79.8 96.4 100.0 100.0 100.0 100.0 100.0 100.0 800 79.8 94.0 98.8 100.0 100.0 GE GΕ 700 47.6 48.2 79.8 79.8 94.0 96.4 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 600 47.6 48.2 79.8 79.8 94.0 96.4 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE. 500 47.6 48.2 79.8 79.8 94.0 96.4 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 47.6 48.2 79.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 79.8 94.0 96.4 98.8 GE 300 47.6 48.2 79.8 79.8 94.0 96.4 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 47.6 48.2 79.8 79.8 94.0 96.4 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100 47.6 48.2 79.8 GE 79.8 94.0 96.4 000 47.6 48.2 79.8 79.8 94.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 96.4

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CE'LING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: FEB HOURS: 18-20 CEILING VISIBILITY IN METERS TN GE GE GE GΕ GE GE GE GE GE GE GE GΕ GE GE GE GE FEET 90 80 60 48 32 24 20 16 12 10 08 00 ....... NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GΕ 7000 GE 6000 GF 35.5 5000 35.5 64.5 64.5 79.5 79.5 79.5 79.5 79.5 79.5 79.5 79.5 79.5 79.5 79.5 79.5 GE 4500 36.7 36.7 65.7 65.7 80.7 80.7 80.7 80.7 80.7 80.7 80.7 80.7 80.7 80.7 80.7 80.7 GΕ 4000 36.7 36.7 67.5 67.5 82.5 82.5 82.5 82.5 82.5 82.5 82.5 82.5 82.5 82.5 82.5 82.5 GE 3500 36.7 36.7 67.5 82.5 67.5 82.5 82.5 82.5 82.5 82.5 82.5 82.5 82.5 82.5 82.5 82.5 GΕ 3000 38.0 38.0 69.3 69.3 89.2 89.2 89.2 89.2 99.2 89.2 89.2 89.2 89.2 89.2 89.2 89.2 38.0 GE 2500 38.0 69.3 69.3 91.6 91.6 93.4 93.4 93.4 93.4 93.4 93.4 93.4 93.4 93.4 93.4 91.6 GE 2000 38.0 38.0 69.3 69.3 91.6 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 GE 69.3 96.4 1800 38.0 38.0 69.3 91.6 91.6 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 GE 1500 38.0 38.0 69.3 69.3 91.6 91.6 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 GE 1200 38.0 38.0 69.3 69.3 91.6 91.6 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 GE 1000 38.0 38.0 69.3 69.3 92.8 94.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE. 900 38.0 38.0 69.3 69.3 92.8 94.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 800 38.0 38.0 69.3 69.3 92.8 94.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GF. 700 38.0 38.0 69.3 69.3 92.8 94.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 600 38.0 92.8 100.0 100.0 100.0 38.0 69.3 69.3 94.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 38.0 38.0 69.3 69.3 92.8 94.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GF. 38.0 38.0 69.3 94.0 100.0 100.0 100.0 100.0 100.0 400 69.3 92.8 100.0 100.0 100.0 100.0 100.0 GE 300 38.0 38.0 69.3 69.3 92.8 94.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 38.0 200 38.0 69.3 69.3 92.8 94.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 38.0 38.0 69.3 د. 69 92.8 94.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 000 38.0 69.3 38.0 69.3 92.8 94.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: FEB HOURS: 21-23

| CEL     | <br>LING | • • • • • • | • • • • • • |               | • • • • • •   |      | <br>/ISIBIL   | יייייייייייייייייייייייייייייייייייייי |                 | • • • • • • | · · · · · ·   | • • • • • •   | • • • • • •   | • • • • • • | • • • • • • •   | • • • • • • | • • • • • • |
|---------|----------|-------------|-------------|---------------|---------------|------|---------------|--|-----------------|-------------|---------------|---------------|---------------|-------------|-----------------|-------------|-------------|
| I       |          | GE          | GE          | GE            | GE            | GE   | GE            | GE .                                   | GE              | GE          | GE            | GE            | GE            | GE          | GE              | GE          | GE          |
| FE      |          | 112         | 90          | 80            | 60            | 48   | 40            | 32                                     | 24              | 20          | 16            | 12            | 10            | 08          | 06              | 04          | 00          |
| r E     | er 1     | 112         | 90          | 80            | 60            | 40   | 40            | 32                                     | 24              | 20          | 10            | 12            | 10            | 08          | 00              | 04          | 00          |
| • • • • |          | •••••       |             | • • • • • • • | • • • • • • • |      | • • • • • • • |  |                 | • • • • • • | • • • • • • • | • • • • • • • |               |             | • • • • • • •   |             | • • • • • • |
| NO :    | CEIL     |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
|         |          |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 20000    |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 18000    |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 16000    |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 14000    |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 12000    |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
|         |          |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
|         | 10000    |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 9000     |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 8000     |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 7000     |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 6000     |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 5000     | 36.8        | 37.4        | 54.0          | 54.0          | 71.2 | 73.6          | 77.3                                   | 77.9            | 77.9        | 77.9          | 77.9          | 77.9          | 77.9        | 77.9            | 77.9        | 77.9        |
| GE      | 4500     | 36.8        | 37.4        | 54.0          | 54.0          | 71.2 | 73.6          | 77.3                                   | 77.9            | 77.9        | 77.9          | 77.9          | 77.9          | 77.9        | 77.9            | 77.9        | 77.9        |
| GE      | 4000     | 38.7        | 39.3        | 57.7          | 57.7          | 75.5 | 77.9          | 81.6                                   | 82.2            | 82.2        | 82.2          | 82.2          | 82.2          | 82.2        | 82.2            | 82.2        | 82.2        |
| GE      | 3500     | 38.7        | 39.3        | 57.7          | 57.7          | 75.5 | 77.9          | 82.2                                   | 82.8            | 82.8        | 82.8          | 82.8          | 82.8          | 82.8        | 82.8            | 82.8        | 82.8        |
| GE      | 3000     | 38.7        | 39.3        | 60.1          | 60.1          | 82.2 | 85.3          | 90.2                                   | 90.8            | 90.8        | 90.8          | 90.8          | 90.8          | 90.8        | 90.8            | 90.8        | 90.8        |
|         |          |             | -212        |               |               |      | 0010          |  |                 |             |               |               |               |             | • • • • •       |             |             |
| GE      | 2500     | 38.7        | 39.3        | 60.1          | 60.1          | 84.0 | 87.1          | 92.6                                   | 93.3            | 93.3        | 93.3          | 93.3          | 93.3          | 93.3        | 93.3            | 93.3        | 93.3        |
| GE      | 2000     | 38.7        | 39.3        | 60.1          | 60.1          | 84.0 | 87.7          | 95.7                                   | 96.3            | 96.3        | 96.3          | 96.3          | 96.3          | 96.3        | 96.3            | 96.3        | 96.3        |
| CE      | 1800     | 38.7        | 39.3        | 60.1          | 60.1          | 84.0 | 87.7          | 95.7                                   | 96.3            | 96.3        | 96.3          | 96.3          | 96.3          | 96.3        | 96.3            | 96.3        | 96.3        |
| GE      | 1500     | 38.7        | 39.3        | 60.1          | 60.1          | 84.0 | 87.7          | 95.7                                   | 96.3            | 96.3        | 96.3          | 96.3          | 96.3          | 96.3        | 96.3            | 96.3        | 96.3        |
| GE      | 1200     | 38.7        | 39.3        | 60.1          | 60.1          | 84.7 | 88.3          | 96.3                                   | 97.5            | 97.5        | 97.5          | 97.5          | 97.5          | 97.5        | 97.5            | 97.5        | 97.5        |
|         |          |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 1000     | 38.7        | 39.3        | 60.1          | 60.1          | 84.7 | 89.0          | 98.2                                   | 99.4            | 99.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
| Œ       | 900      | 38.7        | 39.3        | 60.1          | 60.1          | 84.7 | 89.0          | 98.2                                   | 99.4            | 99.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
| GE      | 800      | 38.7        | 39.3        | 60.1          | 60.1          | 84.7 | 89.0          | 98.2                                   | 99.4            | 99.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
| GE      | 700      | 38.7        | 39.3        | 60.1          | 60.1          | 84.7 | 89.0          | 98.2                                   | 99.4            | 99.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
| GE      | 600      | 38.7        | 39.3        | 60.1          | 60.1          | 84.7 | 89.0          | 98.2                                   | 99.4            | 99.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
|         |          |             |             |               |               |      |               |  |                 |             |               |               |               |             |                 |             |             |
| GE      | 500      | 38.7        | 39.3        | 60.1          | 60.1          | 84.7 | 89.0          | 98.2                                   | 99.4            | 99.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
| GE      | 400      | 38.7        | 39.3        | 60.1          | 60.1          | 84.7 | 89.0          | 98.2                                   | 99.4            | 99.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
| GE      | 300      | 38.7        | 39.3        | 60.1          | 60.1          | 84.7 | 89.0          | 98.2                                   | 99.4            | 99.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
| GE      | 200      | 38.7        | 39.3        | 60.1          | 60.1          | 84.7 | 89.0          | 98.2                                   | 99.4            | 99.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
| αE      | 100      | ₹8.7        | 39.3        | 60.1          | 60.1          | 84.7 | 89.0          | 98.2                                   | 99.4            | 99.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
| a=      | 000      | 30.7        | 30.3        | 60.4          | 60.1          | 04.7 | 0. 2          | 00.0                                   | 00.4            | 00.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
| GE      | 000      | 38.7        | 39.3        | 60.1          | 60.1          | 84.7 | 89.0          | us S                                   | 99.4            | 99.4        | 100.0         | 100.0         | 100.0         | 100.0       | 100.0           | 100.0       | 100.0       |
| • • •   |          |             |             | • • • • • • • | • • • • • •   |      |               | • • • • • •                            | • • • • • • • • | • • • • •   | • • • • • • • |               | • • • • • • • |             | • • • • • • • • |             | • • • • • • |

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSTRVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: FEB HOURS: ALL

| CEILI |           | • • • • • • |      | • • • • • • | • • • • • • • |               |             | TY İN I       | APPERE        | • • • • • • • | • • • • • • | • • • • • • |         | • • • • • • • | • • • • • • | · · · · · · · | • • • • • • |
|-------|-----------|-------------|------|-------------|---------------|---------------|-------------|---------------|---------------|---------------|-------------|-------------|---------|---------------|-------------|---------------|-------------|
| IN    | 1         | GE          | GE   | GE          | GE            | GE,           | GE          | GE            | GE            | GE            | GE          | GE          | GE      | GE            | GE          | GE            | GE          |
| FEET  | ,         | 112         | 90   | 80          | 60            | 48            | 40          | 32            | 24            | 20            | 16          | 12          | 10      | 08            | 06          | 04            | 00          |
| FEEI  | . 1       | 112         | 30   | 80          | 00            | 40            | 40          | 32            | 24            | 20            | 10          | 12          | 10      | 00            | 00          | 0.9           | 00          |
|       | · · · · i |             |      |             |               | • • • • • •   | • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • | • • • • • • |         | • • • • • • • | • • • • • • |               | •••••       |
| NO CE | BIL       |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
| GE 20 | 000       |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
| GE 18 | 1000      |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
| GE 16 | 000       |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
| GE 14 | 1000      |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
| GE 12 | 000       |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
|       |           |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
| GE 10 | 1         |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
|       | 0000      |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
|       | 0000      |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
|       | 000       |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
| GE O  | 0000      |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
| GE 5  | 000       | 30.2        | 30.6 | 50.2        | 50.2          | 64.7          | 66.6        | 70.1          | 70.9          | 71.4          | 71.6        | 72.3        | 72.3    | 72.6          | 72.6        | 72.6          | 73.0        |
|       | 500       | 30.9        | 31.3 | 50.9        | 50.9          | 65.4          | 67.3        | 70.8          | 71.5          | 72.1          | 72.3        | 73.0        | 73.0    | 73.3          | 73.3        | 73.3          | 73.7        |
|       | 000       | 32.1        | 32.5 | 53.8        | 53.8          | 69.3          | 71.3        | 74.9          | 76.0          | 76.7          | 77.0        | 77.6        | 77.6    | 77.9          | 77.9        | 77.9          | 78.3        |
|       | 500       | 32.3        | 32.7 | 54.2        | 54.2          | 70.6          | 72.8        | 76.6          | 77.9          | 78.8          | 79.2        | 80.2        | 80.3    | 80.6          | 80.6        | 80.7          | 81.1        |
|       | 1000      | 34.4        | 34.8 | 58.0        | 58.0          | 77.1          | 79.5        | 83.7          | 85.5          | 86.5          | 86.9        | 88.2        | 88.3    | 88.6          | 88.6        | 88.7          | 89.2        |
|       |           |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
| GE 2  | 2500      | 34.4        | 34.8 | 58.0        | 58.0          | 77.9          | 80.5        | 85.2          | 87.0          | 87.9          | 88.3        | 89.7        | 89.9    | 90.3          | 90.3        | 90.4          | 90.9        |
| GE 2  | 000       | 34.4        | 34.8 | 58.0        | 58.0          | 78.6          | 81.9        | 87.6          | 89.5          | 90.5          | 91.4        | 93.1        | 93.3    | 93.9          | 93.9        | 94.0          | 94.4        |
| GE 1  | 1800      | 34.4        | 34.8 | 58.0        | 58.0          | 78.6          | 81.9        | 87.7          | 89.7          | 90.7          | 91.6        | 93.3        | 93.6    | 94.1          | 94.1        | 94.2          | 94.7        |
| GE 1  | 1500      | 34.4        | 34.8 | 58.0        | 58.0          | 78.8          | 82.1        | 88.0          | 90.0          | 91.4          | 92.2        | 94.2        | 94.6    | 95.4          | 95.4        | 95.5          | 96.0        |
| GE 1  | 200       | 34.4        | 34.8 | 58.0        | 58.0          | 78.9          | 82.2        | 88.1          | 90.3          | 91.6          | 92.5        | 94.4        | 94.8    | 95.7          | 95.8        | 95.8          | 96.3        |
|       | 1         |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
| GE 1  | 1000      | 34.4        | 34.9 | 58.1        | 58.1          | 79.3          | 83.0        | 89.3          | 91.5          | 92.9          | 94.0        | 95.9        | 96.3    | 97.2          | 97.3        | 97.4          | 97.9        |
| GE    | 900       | 34.4        | 34.9 | 58.1        | 58.1          | 79.3          | 83.0        | 89.3          | 91.5          | 92.9          | 94.0        | 95.9        | 96.3    | 97.3          | 97.3        | 97.5          | 98.0        |
| GE    | 800       | 34.4        | 34.9 | 58.1        | 50.1          | 79.3          | 83.0        | 89.3          | 91.5          | 92.9          | 94.0        | 95.9        | 96.4    | 97.3          | 97.4        | 97.6          | 98.0        |
|       | 700       | 34.4        | 34.9 | 58.1        | 58.1          | 79.3          | 83.0        | 89.6          | 91.8          | 93.1          | 94.2        | 96.2        | 96.6    | 97.6          | 97.6        | 97.8          | 98.3        |
| GE    | 600       | 34.4        | 34.9 | 58.1        | 58.1          | 79.3          | 83.0        | 89.6          | 91.8          | 93.1          | 94.2        | 96.2        | 96.6    | 97.6          | 97.6        | 97.8          | 98.3        |
|       |           |             |      |             |               |               |             |               |               |               |             |             |         |               |             |               |             |
|       | 500       | 34.4        | 34.9 | 58.1        | 58.1          | 79.3          | 83.0        | 89.6          | 91.8          | 93.2          | 94.3        | 96.5        | 97.2    | 98.2          | 98.3        | 98.4          | 98.9        |
|       | 400       | 34.4        | 34.9 | 58.1        | 58.1          | 79.3          | 83.0        | 89.6          | 91.8          | 93.2          | 94.3        | 96.7        | 97.5    | 98.6          | 98.7        | 99.0          | 99.5        |
|       | 300       | 34.4        | 34.9 | 58.1        | 58.1          | 79.3          | 83.0        | 89.6          | 91.8          | 93.2          | 94.3        | 96.7        | 97.5    | 98.6          | 98.7        | 99.0          | 99.5        |
|       | 200       | 34.4        | 34.9 | 58.1        | 58.1          | 79.3          | 83.0        | 89.6          | 91.8          | 93.2          | 94.3        | 96.7        | 97.5    | 98.6          | 98.7        | 99.0          | 99.7        |
| GE    | 100       | 34.4        | 34.9 | 58.1        | 58.1          | 79.3          | 83.0        | 89.6          | 91.8          | 93.2          | 94.3        | 96.7        | 97.5    | 98.6          | 98.7        | 99.0          | 99.7        |
| GE    | 000       | 34.4        | 34.9 | 58.1        | 58.1          | 79.3          | 83.0        | 89.6          | 91.8          | 93.2          | 94.3        | 96.7        | 97.5    | 98.6          | 98.7        | 99.0          | 100.0       |
| (34)  | 2001      | 34.4        | 34.9 | 30.1        | 20.1          | 19.3          | 03.0        | 09.0          | 91.0          | 93.2          | 74.3        | 90.7        | 31.0    | 30.0          | 70./        | 99.U          | 100.0       |
|       |           |             |      |             |               | · · · · · · · |             |               |               |               |             |             | · · · · |               | · · · ·     |               |             |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

| NO | CEIL  |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
|----|-------|------|------|------|-----------|------|------|------|------|------|------|------|------|------------------|------|------|-------|
| GE | 20000 |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 18000 |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 16000 |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 14000 |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 12000 |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
|    |       |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 10000 |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 9000  |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 8000  |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GΕ | 7000  |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 6000  |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
|    |       |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 5000  | 44.6 | 45.2 | 59.7 | 59.7      | 74.2 | 74.2 | 74.7 | 75.3 | 75.3 | 75.3 | 75.3 | 75.3 | 75.3             | 75.3 | 75.3 | 75.8  |
| GE | 4500  | 44.6 | 45.2 | 59.7 | 59.7      | 74.2 | 74.2 | 74.7 | 75.3 | 75.3 | 75.3 | 75.3 | 75.3 | 75.3             | 75.3 | 75.3 | 75.8  |
| GE | 4000  | 44.6 | 45.2 | 62.4 | 62.4      | 76.9 | 76.9 | 77.4 | 78.0 | 78.0 | 78.0 | 78.0 | 78.0 | 78.0             | 78.0 | 78.0 | 78.5  |
| GE | 3500  | 44.6 | 45.2 | 62.9 | 62.9      | 77.4 | 77.4 | 78.5 | 79.0 | 79.0 | 79.0 | 79.0 | 79.0 | 79.0             | 79.0 | 79.0 | 79.6  |
| GE | 3000  | 47.3 | 47.8 | 71.0 | 71.0      | 87.1 | 87.1 | 88.7 | 89.2 | 89.2 | 89.2 | 89.2 | 89.2 | 89.2             | 89.2 | 89.2 | 89.8  |
|    |       |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 2500  | 47.8 | 48.4 | 71.5 | 71.5      | 88.2 | 88.2 | 89.8 | 90.3 | 90.3 | 90.3 | 90.3 | 90.3 | 90.3             | 90.3 | 90.3 | 90.9  |
| GE | 2000  | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.1 | 94.6 | 94.6 | 95.7 | 96.2 | 96.2 | 96.2             | 96.2 | 96.2 | 96.8  |
| GE | 1800  | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.1 | 94.6 | 94.6 | 95.7 | 96.2 | 96.2 | 96.2             | 96.2 | 96.2 | 96.8  |
| GE | 1500  | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.1 | 94.6 | 94.6 | 95.7 | 96.8 | 97.3 | 97.3             | 97.3 | 97.3 | 97.8  |
| GE | 1200  | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.1 | 94.6 | 94.6 | 95.7 | 96.8 | 97.3 | 97.3             | 97.3 | 97.3 | 97.8  |
|    |       |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 1000  | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.1 | 94.6 | 95.2 | 96.2 | 97.3 | 97.8 | 97.8             | 97.8 | 97.8 | 98.4  |
| GE | 900   | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.1 | 94.6 | 95.2 | 96.2 | 97.3 | 97.8 | 97.8             | 97.8 | 97.8 | 98.4  |
| GΕ | 800   | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.1 | 95.7 | 96.2 | 97.3 | 98.4 | 98.9 | 98.9             | 98.9 | 98.9 | 99.5  |
| GE | 700   | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.1 | 95.7 | 96.2 | 97.3 | 98.4 | 98.9 | 98. <del>9</del> | 98.9 | 98.9 | 99.5  |
| GE | 600   | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.1 | 95.7 | 96.2 | 97.3 | 98.4 | 98.9 | 98.9             | 98.9 | 98.9 | 99.5  |
|    |       |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 500   | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.1 | 95.7 | 96.2 | 97.3 | 98.4 | 98.9 | 98.9             | 98.9 | 98.9 | 99.5  |
| GE | 400   | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.1 | 95.7 | 96.2 | 97.3 | 98.4 | 98.9 | 98.9             | 98.9 | 98.9 | 99.5  |
| GE | 300   | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.6 | 96.2 | 96.8 | 97.8 | 98.9 | 99.5 | 99.5             | 99.5 | 99.5 | 100.0 |
| GE | 200   | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.6 | 96.2 | 96.8 | 97.8 | 98.9 | 99.5 | 99.5             | 99.5 | 99.5 | 100.0 |
| GE | 100   | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.6 | 96.2 | 96.8 | 97.8 | 98.9 | 99.5 | 99.5             | 99.5 | 99.5 | 100.0 |
|    | İ     |      |      |      |           |      |      |      |      |      |      |      |      |                  |      |      |       |
| GE | 000   | 48.4 | 48.9 | 73.1 | 73.1      | 90.9 | 91.4 | 94.5 | 96.2 | 96.8 | 97.8 | 98.9 | 99.5 | 99.5             | 99.5 | 99.5 | 100.0 |
|    |       |      |      |      | . <b></b> |      |      |      |      |      |      |      |      |                  |      |      |       |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 47:066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAR HOURS: 03-05

| CEI | LING  |      |      |      |      |      | <br>/ISIBIL | TY IN | METERS |      |      | • • • • • • |      | • • • • • •   |         |      | • • • • • |
|-----|-------|------|------|------|------|------|-------------|-------|--------|------|------|-------------|------|---------------|---------|------|-----------|
|     | N     | GE   | GE   | GE   | GE   | GE   | GE          | GE    | GE     | GE   | GE   | GE          | GE   | GE            | GE      | GE   | GE        |
| FE  |       | 112  | 90   | 80   | 60   | 48   | 40          | 32    | 24     | 20   | 16   | 12          | 10   | 08            | 06      | 04   | 00        |
|     |       |      |      |      |      |      | <b></b> .   |       |        |      | - ·  |             |      |               | <i></i> |      |           |
|     | 1     |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| NO  | CEIL  |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 20000 |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 18000 |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 16000 |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 14000 |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 12000 |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| an. | 10000 |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 9000  |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 8000  |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 7000  |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 6000  |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| 013 | 0000  |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 5000  | 27.4 | 28.5 | 51.6 | 51.6 | 64.5 | 64.5        | 65.1  | 65.1   | 65.1 | 65.1 | 65.1        | 65.1 | 65.1          | 65.1    | 65.6 | 65.6      |
| GE  | 4500  | 27.1 | 28.5 | 51.6 | 51.6 | 64.5 | 64.5        | 65:1  | 65.1   | 65.1 | 65.1 | 65.1        | 65.1 | 65.1          | 65.1    | 65.6 | 65.6      |
| GE  | 4000  | 27.4 | 28.5 | 54.3 | 54.3 | 68.3 | 68.3        | 69.4  | 69.4   | 69.4 | 69.4 | 69.4        | 69.4 | 69.4          | 69.4    | 69.9 | 69.9      |
| GE  | 3500  | 29.0 | 30.1 | 56.5 | 56.5 | 70.4 | 70.4        | 71.5  | 71.5   | 71.5 | 71.5 | 71.5        | 71.5 | 71.5          | 71.5    | 72.0 | 72.0      |
| GE  | 3000  | 33.3 | 34.4 | 64.5 | 64.5 | 79.0 | 79.0        | 81.7  | 82.8   | 82.8 | 82.8 | 83.3        | 83.3 | 83.3          | 83.3    | 83.9 | 83.9      |
|     |       |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 2500  | 33.3 | 34.4 | 64.5 | 64.5 | 80.1 | 80.1        | 83.3  | 84.4   | 86.0 | 86.0 | 86.6        | 86.6 | 86.6          | 86.6    | 87.1 | 87.1      |
| GE  | 2000  | 33.9 | 34.9 | 66.7 | 66.7 | 83.9 | 84.4        | 87.6  | 88.7   | 90.3 | 90.3 | 90.9        | 90.9 | 90.9          | 90.9    | 91.4 | 91.4      |
| GE  | 1800  | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 85.5        | 88.7  | 89.8   | 91.4 | 91.4 | 91.9        | 91.9 | 91.9          | 91.9    | 92.5 | 92.5      |
| GE  | 1500  | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 85.5        | 88.7  | 89.8   | 91.4 | 91.4 | 91.9        | 91.9 | 91.9          | 91.9    | 92.5 | 92.5      |
| GE  | 1200  | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 86.6        | 89.8  | 90.9   | 92.5 | 92.5 | 93.0        | 93.0 | 93.0          | 93.0    | 93.5 | 93.5      |
| GE  | 1000  | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 86.6        | 89.8  | 91.4   | 94.1 | 94.1 | 94.6        | 94.6 | 94.6          | 94.6    | 95.2 | 95.2      |
| GE  | 900   | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 86.6        | 89.8  | 91.4   | 94.1 | 94.1 | 94.6        | 94.6 | 94.6          | 94.6    | 95.2 | 95.2      |
| GΕ  | 800   | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 86.6        | 89.8  | 91.4   | 94.1 | 94.1 | 94.6        | 94.6 | 94.6          | 94.6    | 95.2 | 95.2      |
| GE  | 700   | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 86.6        | 89.8  | 91.4   | 94.1 | 94.1 | 94.6        | 94.6 | 94.6          | 94.6    | 95.2 | 95.2      |
| GE  | 600   | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 86.6        | 89.8  | 91.4   | 94.1 | 94.1 | 94.6        | 94.6 | 94.6          | 94.6    | 95.2 | 95.2      |
|     |       |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |
| GE  | 500   | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 86.6        | 90.3  | 91.9   | 94.6 | 94.6 | 95.2        | 95.2 | 95.2          | 95.2    | 95.7 | 95.7      |
| GE  | 400   | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 86.6        | 90.3  | 91.9   | 95.2 | 95.2 | 95.7        | 95.7 | 95.7          | 95.7    | 96.2 | 96.2      |
| GE  | 300   | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 86.6        | 90.3  | 91.9   | 95.2 | 95.2 | 95.7        | 95.7 | 96.2          | 96.8    | 97.3 | 97.3      |
| GE  | 200   | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 86.6        | 90.3  | 91.9   | 95.2 | 95.2 | 95.7        | 95.7 | 96.2          | 96.8    | 97.3 | 97.3      |
| GE  | 100   | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 86.6        | 90.3  | 91.9   | 95.2 | 95.7 | 96.2        | 96.2 | 96.8          | 97.3    | 97.8 | 100.0     |
| GE  | იიი   | 33.9 | 34.9 | 66.7 | 66.7 | 84.9 | 96.6        | 90.3  | 91.9   | 95.2 | 95.7 | 96.2        | 96.2 | 96.8          | 97.3    | 97.8 | 100.0     |
| 35  | 330   |      |      |      |      |      |             |       |        |      |      |             |      | • • • • • • • |         |      |           |
| •   |       |      |      |      |      |      |             |       |        |      |      |             |      |               |         |      |           |

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 30 - JUN 90 MONTH: MAR HOURS: 06-08 LST TO UTC: - 9 VISIBILITY IN METERS CEILING GE GE GE GE GE GE GE GE TN GE GE GE GE GE GE GE GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 GE 5000 15.6 16.7 36.0 36.0 55.4 56.5 61.3 66.1 66.1 66.1 66.1 67.2 67.7 67.7 67.7 67.7 4500 15.5 16.7 36.0 36.0 55.4 56.5 61.3 66.1 66.1 66.1 66.1 67.2 67.7 GE 36.0 36.0 57.0 67.7 67.7 67.7 68.8 69.4 69.4 69.4 GE 4000 15.6 16.7 58.1 62.9 67.7 69.4 GE 3500 16.1 17.2 37.6 37.6 58.6 60.2 65.6 70.4 70.4 70.4 70.4 71.5 72.0 72.0 72.0 72.0 79.6 79.6 80.1 81.2 81.7 17.7 18.8 40.3 40.3 67.2 74.2 79.6 81.7 81.7 81.7 GE 3000 65.6 GE 2500 18.3 20.4 41.9 41.9 67.2 68.8 76.9 82.8 84.4 84.4 84.9 86.0 86.6 86.6 86.6 86.6 87.6 88.7 89.2 20.4 42.5 69.9 79.6 85.5 87.1 87.1 89.2 89.2 89.2 2000 18.3 42.5 71.5 GE GE 1800 18.3 20.4 42.5 42.5 70.4 72.0 80.1 86.0 87.6 87.6 88.7 90.3 90.9 90.9 90.9 90.9 90.9 GE 1500 18.3 20.4 42.5 42.5 70.4 72.0 80.1 86.0 87.6 87.6 88.7 90.3 90.9 90.9 90.9 GE 1200 18.3 20.4 43.0 43.0 71.0 74.2 82.3 88.2 89.8 89.8 90.9 92.5 93.0 93.0 93.0 93.0 88.2 89.8 90.9 92.5 93.0 93.0 93.0 93.0 GE 18.3 20.4 43.0 43.0 71.0 74.2 82.3 89.8 1000 GE 900 18.3 20.4 43.0 43.0 71.0 74.2 82.3 88.2 89.8 89.8 90.9 92.5 93.0 93.0 93.0 93.0 GE 800 18.3 20.4 43.0 43.0 71.0 74.2 82.3 88.2 89.8 89.8 90.9 92.5 93.0 93.0 93.0 93.0 20.4 90.9 91.9 93.5 94.1 94.1 94.1 94.1 700 18.3 43.0 43.0 71.0 74.2 82.3 88.2 89.8 GE GE 600 18.3 20.4 43.0 43.0 71.0 74.2 82.3 88.2 89.8 90.9 91.9 93.5 94.1 94.1 94.1 94.1 90.3 92.5 94.1 20.4 43.0 43.0 71.0 74.2 82.8 88.7 91.4 94.6 94.6 94.6 94.6 GE 500 18.3 GE 400 18.3 20.4 43.0 43.0 71.0 74.2 82.8 88.7 91.4 92.5 93.5 95.2 96.2 96.2 96.2 96.2 97.8 97.8 97.8 97.8 20.4 43.0 43.0 74.2 82.8 88.7 92.5 94.1 96.2 GE 300 18.3 71.0 91.4 97.8 GE 200 18.3 20.4 43.0 43.0 71.0 74.2 82.8 88.7 91.4 92.5 94.1 96.2 97.8 97.8 97.8 97.8 GE 100 18.3 20.4 43.0 43.0 71.0 74.2 82.8 88.7 91.4 92.5 94.1 96.2 97.8 97.8 99.5

TOTAL NUMBER OF OBSERVATIONS 186

000 18.3 20.4 43.0

43.0

71.0 74.2

82.8

91.4 92.5

94.1 96.2

88.7

......

97.8 97.8 97.8 100.0

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY. TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAR HOURS: 09-11 ...... CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE 112 48 90 60 32 20 12 FEET 80 40 24 16 10 08 06 04 0.0 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 9000 GE GE 8000 GE 7000 GE 6000 GE 5000 20.2 20.2 37.9 37.9 61.3 62.9 66.1 66.9 67.7 67.7 69.4 69.4 69.4 69.4 69.4 69.4 GE 4500 20.2 20.2 37.9 37.9 62.1 63.7 66.9 67.7 68.5 68.5 70.2 70.2 70.2 70.2 70.2 70.2 71.0 72.6 72.6 GE. 4000 20.2 20.2 39.5 39.5 64.5 66.1 69.4 70.2 71.0 72.6 72.6 72 6 72.6 3500 20.2 20.2 40.3 40.3 67.7 70.2 73.4 74.2 75.0 75.0 76.6 76.6 76.6 76.6 76.6 76.6 GE GΕ 3000 20.2 20.2 41.9 77.4 82.3 86.3 87.9 88.7 88.7 90.3 90.3 90.3 90.3 90.3 90.3 41.9 79.0 83.9 87.9 91.1 91.1 92.7 92.7 92.7 92.7 GE 2500 21.8 43.5 43.5 90.3 92.7 92.7 21.8 43.5 80.6 85.5 89.5 91.9 92.7 94.4 94.4 94.4 94.4 94.4 94.4 CE 2000 43.5 92.7 21.8 GE 1800 21.8 21.8 43.5 43.5 80.6 85.5 89.5 91.9 92.7 92.7 94.4 94.4 94.4 95.2 95.2 95.2 GF 1500 21.8 21.8 43.5 43.5 80.6 86.3 90.3 93.5 94.4 94.4 96.0 96.0 96.0 96.8 96.8 90.3 96.0 96.0 96.0 96.8 96.8 95.8 GE 1200 21.8 21.8 43.5 43.5 80.6 86.3 93.5 94.4 94.4 GE 1000 21.3 21.8 43.5 43.5 80.6 86.3 90.3 93.5 94.4 94.4 96.0 96.0 96.0 96.8 96.8 96.8 GE 900 21.8 21.8 43.5 43.5 80.6 86.3 90.3 94.4 95.2 95.2 96.8 96.8 96.8 97.6 97.6 97.6 21.8 80.6 90.3 95.2 95.2 97.6 97.6 98.4 99.2 99.2 99.2 GE 800 21.8 43.5 43.5 86.3 94.4 97.6 97.6 98.4 99.2 700 21.8 86.3 90.3 94.4 95.2 95.2 99.2 99.2 GE 21.8 43.5 43.5 80.6 600 21.8 21.8 43.5 43.5 80.6 86.3 90.3 94.4 95.2 95.2 97.6 97.6 98.4 99.2 99.2 99.2 GE GE 500 21.8 21.8 43.5 43.5 80.6 86.3 90.3 94.4 95.2 95.2 97.6 97.6 98.4 99.2 99.2 99.2 400 21.8 43.5 43.5 86.3 90.3 94.4 95.2 95.2 97.6 97.6 98.4 99.2 99.2 99.2 GE 21.8 80.6 GE 300 21.8 21.8 43.5 43.5 80.6 86.3 90.3 94.4 95.2 95.2 97.6 97.6 98.4 99.2 99.2 99.2 GE 200 21.8 21.8 43.5 43.5 80.6 86.3 90.3 94.4 95.2 95.2 97.6 97.6 99.2 100.0 100.0 100.0 GE21.8 21.8 43.5 43.5 80.6 86.3 90.3 94.4 95.2 95.2 97.6 97.6 99.2 100.0 100.0 100.0 000 21.8 21.8 43.5 43.5 80.6 86.3 90.3 94.4 95.2 95.2 97.6 97.6 99.2 100.0 100.0 100.0 GE ....

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECUED: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAR HOURS: 12-14 CEILING VISIBILITY IN METERS GE IN GE GE GE GE GE GE GE GE GE GE GΕ GE GE GE GE FEET 112 32 20 90 80 60 48 40 24 16 12 10 08 Üΰ 04 00 NO CELL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 34.4 GE 5000 33.3 52.2 52.2 61.8 72.4 63.4 63.4 63.4 63.4 63.4 63.4 63.4 53.4 63.4 63.4 GE 4500 53.3 34.4 52.2 52.2 61.8 62.4 63.4 63.4 63.4 63.4 63.4 63.4 63.4 63.4 63.4 63.4 33.9 34.9 53.8 53.8 64.5 65.1 66.1 GE 4000 66.1 66.1 66.1 66.1 66.1 66.1 66.1 66.1 66.1 57.5 57.5 71.5 72.0 73.1 73.1 73.1 GE 3500 35.5 36.6 73.1 73.1 73.1 73.1 73.1 73.1 73.1 GE 3000 39.8 40.9 66.7 66.7 87.1 89.2 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 2500 89.2 94.6 66.7 66.7 95.7 GE 39.8 40.9 91.4 95.7 95.7 95.7 95.7 95.7 95.7 95.7 95.7 97.3 97.3 GE 2000 39.8 40.9 66.7 66.7 90.9 93.0 96.2 97.3 97.3 97.3 97.3 97.3 97.3 97.3 GE 1800 39.8 40.9 66.7 66.7 90.9 93.0 96.2 97.3 97.3 97.3 97.3 97.3 97.3 97.3 97.3 97.3 GE 1500 39.9 40.9 66.7 66.7 90.9 93.0 96.2 97.3 97.3 97.3 97.3 97.3 97.3 97.8 98.4 98.4 GE 1200 39.8 40.9 66.7 66.7 90.9 93.0 96.2 97.3 97.3 97.3 97.3 97.3 97.3 97.8 98.4 98.4 GE 1000 39.8 40.9 66.7 66.7 90.9 93.0 96.8 97.8 97.8 97.8 97.8 98.4 98.4 98.9 99.5 99.5 GE 900 39.8 40.9 66.7 66.7 90.9 93.0 96.8 97.6 97.8 97. 97.8 98.4 98.4 98.9 99.5 99.5 19.8 40.9 66.7 66.7 90.9 93.0 96.8 97.8 99.5 100.0 GE 800 97.8 97.8 97.8 98.4 98.4 100.0 GE700 39.8 40.9 65.7 66.7 90.9 93.0 96.8 97.8 97.8 97.8 97.8 98.4 98.4 99.5 100.0 100.0 39.8 90.9 93.0 96.8 97.6 98.4 99.5 100.0 GE 600 40.9 66.7 66.7 97.8 97.8 97.8 98.4 100.0 GE 5001 39.8 40.9 66.7 66.7 90.9 93.0 96.8 97.8 97.8 97.8 97.8 98.4 98.4 99.5 100.0 100.0 66.7 98.4 98.4 GE 400 39.8 40.9 66.7 90.9 93.0 96.8 97.8 97.R 99.5 100.0 100.0 97.3 97.8 GE300 39.8 40.9 66.7 66.7 90.9 93.0 96.8 97.8 97.8 97.8 97.8 98.4 98.4 99.5 100.0 100.0 200 39.8 40.9 66.7 66.7 90.9 93.0 GΕ 96.A 97.8 97.8 97.8 97.8 98.4 99.5 100.0 100.0 98.4 GE 100 39.8 40.9 66.7 66.7 90.9 93.0 96.8 97.8 97.8 97.8 97.8 98.4 98.4 99.5 100.0 100.0 66.7 93.0 000 39.8 40.9 66.7 90.9 97.8 97.8 97.8 GE 96.8 97.8 98.4 98.4 99.5 100.0 100.0

#### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAR HOURS: 15 -17 CEILING VISIBILITY IN METERS ! GE IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE ξE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 20 NO CEIL GE 20000 GE 19000 GF 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 Œ 7000 GE 6000 GE 5000 46.2 64.0 64.0 69.4 69.4 69.4 69.4 69.4 69.4 46.2 69.4 69.4 69.4 69.4 69.4 67.4 69 4 CE 4500 46.2 46.2 64 D 64.0 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 GE 4000 47.3 47.3 67.2 67.2 74.2 74.7 74.7 74 7 74.7 74.7 74.7 74.7 74.7 74.7 74.7 GE 3500 49.5 49.5 70.4 70.4 77.4 78.0 78.0 78.U 78.0 78.0 78.0 78.0 78.0 78.0 78.0 16 0 GE 3000 53.8 53.8 80.1 80.1 87.6 88.7 90.9 90.9 90.9 90.9 90.9 90.9 90.9 90.9 90.9 90.9 80.1 91.4 93.5 GE 2500 53.8 53.8 80.1 90.3 93.5 93.5 93.5 93.5 93.5 93.5 93.5 93.5 93.5 GE 2000 53.A 53.8 81.7 81.7 92.5 93.5 96.2 97.8 97.8 97.8 98.9 98.9 98.9 98.9 98.9 98.9 GF 1800 53.8 53.8 81.7 81.7 92.5 93.5 96.2 97.8 97.8 97.8 98.9 98.9 98.9 98.9 98.9 98.9 GE 1500 53.8 53.8 81.7 81.7 92.5 93.5 96.2 97.8 97 8 97 A 98.9 98 9 98.9 98.9 QR Q 98 9 GE 1200 53.8 53.8 81.7 81.7 92.5 93.5 97.3 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 CE 1000 53.8 53.8 81.7 81.7 92.5 9".5 97.3 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 900 53.8 53.R 81.7 R1 7 92.5 93.5 97.3 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 800 53.8 97.3 GE 53.8 81.7 81.7 92.5 93.5 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 7001 53.8 53.8 81.7 81.7 92.5 93.5 97.3 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 51.8 53.8 81.7 81.7 92.5 93.5 97.3 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 53.8 53.8 81.7 81.7 92.5 93.5 97.3 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 GE 400 53.8 81.7 81.7 92.5 93.5 27.3 98.9 100.0 100.0 100.0 100.0 100.0 53.8 98.9 98.9 CF 300 53.8 53.A 81.7 81.7 92.5 9:.5 97.3 98.9 98.9 98.9 100.0 100.0 100.) 100.0 100.C 100.0 GE 200 53.8 52.A 81.7 81.7 92.5 93.5 97.3 98.9 98.9 98.9 100.0 100.) 100.( 100.0 100.0 100.0 CE 100 53.8 53.8 81.7 81.7 92.5 93.5 97.3 98.9 98.9 \_8.9 100.0 100.0 100.0 100.0 100.0 000 53.8 53.8 81.7 81.7 92.5 93.5 97.3 98.9 GE 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0

TOTAL NUMBER OF OBSERVATIONS 186

D - 2 - 24

## PEPCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOUDLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO MONTH: MAR HOURS: 18-20 LST TO UTC: - 9 CELLING VISIBILITY IN METERS IN GE GE GE GE GE 48 40 32 GE GE ĴΕ GE GE GE GE GE GE GE GE FEET | 112 90 30 48 16 12 60 24 20 10 08 06 00 04 NO CELL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 100001 9000 GE GE 8000 i GE 7000 GE 6000 GE 3000 48.4 48.4 68.3 68.3 71.5 71.5 71.5 71.5 71.5 71.5 71.5 71.5 71.5 71.5 71.5 4500 j 50.5 50.5 70.4 73.7 73.7 73.7 73.7 GE 70.4 73.7 73.7 73.7 73.7 73.7 73.7 73.7 51.1 51.1 4000 i 72.0 72.0 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 GE GE 3500 53.2 53.2 75.9 76.9 83.3 83.9 83.9 83.9 83.9 83.9 83.9 83.9 83.9 83.9 83.9 83.9 92.5 GE 3000 54.8 54.8 82.3 82.3 88.7 90.3 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 OF. 2500; 54.8 54.8 92.3 82.3 88.7 90.3 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 Gā. 20001 54.8 54.8 83.9 83.9 91.4 94.6 96.8 97.3 97.3 97.3 97.3 97.3 97.3 97.3 97.3 97.3 1800: 54.8 97 3 4E 54.8 83.0 83.9 91.4 94.6 96.8 97.3 97.3 97.3 97.3 97.3 97.3 97.3 97.3  $C_{i}^{\alpha}$ 1900 54.8 83.9 91.4 95.2 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 54.9 83.9 1200 54.8 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE. 54.8 83.9 83.9 91.4 95.2 GE 1000 54.8 98.9 100.0 100.0 100.0 54.8 83.9 83.9 91.4 95.2 100.0 100.0 100.0 100.0 100.0 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 900 54.8 54 8 95.2 :F 83.9 83.0 91.4 (1<u>F</u>) 54.8 5 .R 83.9 83.9 91.4 95.2 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GB. 700 54.A 54.8 83.9 83.9 91.4 95.2 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 500 54.8 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 54.8 83.9 83.9 91.4 95.2 500 54.8 Œ 54.8 83.9 83.9 91.4 95.2 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 400 54.8 CF 54.8 83.9 83.9 91.4 95.2 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100 54.8 91.4 CF 54.8 83.9 83.9 95.2 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 CF. 200 54.8 54.8 83.9 83.9 91.4 95.2 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 300 54.8 Œ. 54.8 83.9 83.9 91.4 95.2 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 ara 54.8 83.9 7.5 83.9 91.4 91.2 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9 MONTH: MAR HOURS: 21-23 ...... CELLING VISIBILITY IN METERS GE GE GE GÈ GE GE GΕ GE GE GE GE GE IN GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 11000 GE 12000 GE 10000 GE 9000 8000 GE 7000 GE GΕ 6000 46.2 66.7 75.3 75.8 75.8 75.8 75.8 75.8 75.8 75.8 75.8 75.8 75.8 5000 46.2 66.7 75.8 GE GE 4500 47.3 47.3 68.8 68.8 77.4 78.0 78.0 78.0 78.0 78.0 78.0 78.0 78.0 78.0 78.0 78.0 GE 4000 47.3 47.3 69.4 69.4 78.0 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 48.9 85.5 85.5 3500 48.9 73.7 73.7 83.3 84.9 95.5 85.5 85.5 85.5 85.5 85.5 85.5 85.5 GE GE 3000 51.1 51.1 77.4 77.4 87.1 88.7 89.8 89.8 89.8 91.4 91.4 91.4 91.4 91.4 91.4 91.4 91.4 GE 51.1 77.4 87.1 88.7 89.8 89.8 89.8 91.4 91.4 91.4 91.4 91.4 91.4 2500 51.1 77.4 GE 2000 51.1 51.1 80.6 80.6 91.4 93.5 94.6 94.6 94.6 97.3 97.3 97.3 97.3 97.3 97.3 97.3 GE 1800 51.1 51.1 80.6 80.6 91.4 93.5 94.6 94.6 94.6 97.3 97.3 97.3 97.3 97.3 97.3 97.3 GE 1500 51.1 51.1 80.6 80.6 92.5 94.6 96.8 96.8 96.8 99.5 99.5 99.5 99.5 99.5 99.5 99.5 GE1200 51.1 51.1 80.6 80.6 92.5 94.6 96.8 96.8 96.8 99.5 99.5 99.5 99.5 99.5 99.5 99.5 99.5 CE 1000 51.1 51.1 80.6 80.5 92.5 94.6 96.8 96.8 96.8 99.5 99.5 99.5 99.5 99.5 99.5 99.5 GE 900 51.1 51.1 80.6 80.6 92.5 94.6 96.8 96.8 96.8 99.5 99.5 99.5 99.5 99.5 99.5 51.1 51.1 800 80.6 92.5 94.6 96.8 97.3 97.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 80.6 CE 200 51.1 51.1 80.5 80.6 92.5 94.6 96.8 97.3 97.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 600 51.1 51.1 80.6 80.6 92.5 94.6 96.8 97.3 97.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 51.1 51.1 80.6 80.6 92.5 94.6 96.8 97.3 97.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 51.1 51.1 80.5 80.6 92.5 94.5 96.8 97.3 97.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 300 51.1 51.1 80.6 80.6 92.5 94.6 96.8 97.3 97.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 CE. 200 51.1 51.1 80.6 80.5 92.5 94.6 96.8 97.3 97.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE. 100 51.1 51.1 80.6 BO. 6 92.5 94.6 96.8 97.3 97.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 000 51.1 51.1 80.6 80.6 92.5 94.6 96.8 97.3 97.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAR HOURS: ALL

|             |        |               | • • • • • • • |               |             |               |             |               | • • • • • •   | • • • • • •   | • • • • • • |               | • • • • • •   | • • • • • • • | • • • • • •   | • • • • • • |
|-------------|--------|---------------|---------------|---------------|-------------|---------------|-------------|---------------|---------------|---------------|-------------|---------------|---------------|---------------|---------------|-------------|
| CEILING     | 1      |               |               | ~~            |             | VISIBIL       |             |               | <b>an</b>     | an            | an          | an            | <b>a</b> n    | an            | <b>an</b>     |             |
| IN          | GE     | GE            | GE            | GE            | GE          | GE            | GE          | GE            | GE            | GE            | GE          | GE            | GE            | GE            | GE            | GE          |
| FEET        | 112    | 90            | 80            | 60            | 48          | 40            | 32          | 24            | 20            | 16            | 12          | 10            | 08            | 06            | 04            | 00          |
| • • • • • • |        | • • • • • •   | • • • • • • • | • • • • • •   | • • • • • • | • • • • • •   | • • • • • • |               | • • • • • • • | • • • • • • • |             |               | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • |
| NO CEIL     |        |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 2000     |        |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 1800     | ı      |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 1600     | i i    |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 1400     |        |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 1200     | 1      |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
|             |        |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 1000     |        |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 900      |        |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 800      |        |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 700      | 1      |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 600      | 9      |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 500      | 35.9   | 36.4          | 55.3          | 55.3          | 66.9        | 67.3          | 68.5        | 69.3          | 69.4          | 69.4          | 69.5        | 69.6          | 69.7          | 69.7          | 69.8          | 69.8        |
| GE 450      | 1      | 36.8          | 55.8          | 55.8          | 67.5        | 68.0          | 69.1        | 69.9          | 70.0          | 70.0          | 70.1        | 70.3          | 70.3          | 70.3          | 70.4          | 70.5        |
| GE 400      | l l    | 37.1          | 57.6          | 57.6          | 70.5        | 71.0          | 72.2        | 73.0          | 73.1          | 73.1          | 73.2        | 73.4          | 73.4          | 73.4          | 73.5          | 73.6        |
| GE 350      | 1      | 38.4          | 60.3          | 60.3          | 74.0        | 74.8          | 76.3        | 77.1          | 77.1          | 77.1          | 77.3        | 77.4          | 77.5          | 77.5          | 77.6          | 77.6        |
| GE 300      | 1      | 41.1          | 66.5          | 66.5          | 82.7        | 84.2          | 87.1        | 88.1          | 88.2          | 88.4          | 88.7        | 88.8          | 88.9          | 88.9          | 89.0          | 89.1        |
| GL 300      | 7 40.0 | 41.1          | 00.5          | 00.3          | 02.7        | 04.2          | 07.1        | 00.1          | 00.2          | 00.4          | 00.7        | 00.0          | 00.5          | 00.5          | 03.0          | 03.1        |
| GE 250      | 40.9   | 41.5          | 67.0          | 67.0          | 83.9        | 85.4          | 88.6        | 89.9          | 90.4          | 90.6          | 90.9        | 91.0          | 91.1          | 91.1          | 91.2          | 91.2        |
| GE 200      | 1      | 41.7          | 68.4          | 68.4          | 86.7        | 88.6          | 51.9        | 93.5          | 94.0          | 94.5          | 95.0        | 95.2          | 95.2          | 95.2          | 95.3          | 95.4        |
| GE 180      | 1      | 41.7          | 68.4          | 68.4          | 86.9        | 88.8          | 92.1        | 93.8          | 94.2          | 94.7          | 95.3        | 95.5          | 95.6          | 95.7          | 95.7          | 95.8        |
| GE 150      | 0 41.0 | 41.7          | 68.4          | 68.4          | 87.0        | 89.1          | 92.8        | 94.5          | 95.0          | 95.5          | 96.1        | 96.4          | 96.5          | 96.6          | 96.8          | 96.8        |
| GE 120      | 0 41.0 | 41.7          | 68.4          | 68.4          | 87.1        | 89.5          | 93.3        | 95.1          | 95.6          | 96.1          | 96.7        | 97.0          | 97.1          | 97.2          | 97.3          | 97.4        |
|             | 1      |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 100      | 41.0   | 41.7          | 68.4          | 68.4          | 87.1        | 89.5          | 93.4        | 95.2          | 95.9          | 96.4          | 97.1        | 97.4          | 97.5          | 97.6          | 97.8          | 97.8        |
| GE 90       | 41.0   | 41.7          | 68.4          | 68.4          | 87.1        | 89.5          | 93.4        | 95.3          | 96.0          | 96.5          | 97.1        | 97.5          | 97.5          | 97.7          | 97.8          | 97.9        |
| GE 80       | 0 41.0 | 41.7          | 68.4          | 68.4          | 87.1        | 89.5          | 93.4        | 95.5          | 96.2          | 96.7          | 97.4        | 97.8          | 97.9          | 98.1          | 98.2          | 98.3        |
| GE 70       | 41.0   | 41.7          | 68.4          | 68.4          | 87.1        | 89.5          | 93.4        | 95.5          | 96.2          | 96.8          | 97.5        | 97.9          | 98.0          | 98.2          | 98.4          | 98.5        |
| GE 60       | 41.0   | 41.7          | 68.4          | 68.4          | 87.1        | 89.5          | 93.4        | 95.5          | 96.2          | 96.8          | 97.5        | 97.9          | 98.0          | 98.2          | 98.4          | 98.5        |
|             | 1      |               |               |               |             |               |             |               |               |               |             |               |               |               |               |             |
| GE 50       | 1      | 41.7          | 68.4          | 68.4          | 87.1        | 89.5          | 93.5        | 95.7          | 96.4          | 97.0          | 97.7        | 98.0          | 98.2          | 98.4          | 98.5          | 98.6        |
| GE 40       | 1      | 41.7          | 68.4          | 68.4          | 87.1        | 89.5          | 93.5        | 95.7          | 96.6          | 97.2          | 97.9        | 98.2          | 98.5          | 98.7          | 98.8          | 98.9        |
| GE 30       | ı      | 41 7          | 68.4          | 68.4          | 87.1        | 89.5          | 93.6        | 95.7          | 96.6          | 97.3          | 98.0        | 98.5          | 98.8          | 99.1          | 99.2          | 99.3        |
| GE 20       | 1      | 41            | 68.4          | 68.4          | 87.1        | 89.5          | 93.6        | 95.7          | 96.6          | 97.3          | 98.0        | 98.5          | 98.9          | 99.2          | 99.3          | 99.4        |
| GE 10       | 41.0   | 41.7          | 68.4          | 68.4          | 87.1        | 89.5          | 93.6        | 95.7          | 96.6          | 97.3          | 98.1        | 98.5          | 98.9          | 99.2          | 99.4          | 99.9        |
|             |        |               |               | -a ·          |             |               |             |               |               |               |             |               |               |               | ••            | 400.0       |
| GE 00       | 0 41.0 | 41.7          | 68.4          | 68.4          | 87.1        | 89.5          | 93.6        | 95.7          | 96.6          | 97.3          | 98.1        | 98.5          | 98.9          | 99.2          | 99.4          | 100.0       |
| • • • • • • |        | • • • • • • • | • • • • • •   | • • • • • • • | • • • • • • | • • • • • • • | • • • • • • | • • • • • • • | • • • • • •   |               | • • • • • • | • • • • • • • | • • • • • • • | • • • • • •   | • • • • • •   | • • • • • • |

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: APR HOURS: 00-02

| CEILING            | • • • • • • |              | • • • • • •   |              |              | VISIBIL      |              |               |               | • • • • •    | · • • • ·    | • • • • •    | • • • • • •  |               | • • • • •     |              |
|--------------------|-------------|--------------|---------------|--------------|--------------|--------------|--------------|---------------|---------------|--------------|--------------|--------------|--------------|---------------|---------------|--------------|
| IN                 | GE          | GE           | GE            | GE           | GE           | GE           | GE           | GE            | GE            | GE           | GE           | GE           | GE           | GE            | GE            | GE           |
| FEET               | 112         | 90           | 80            | 60           | 48           | 40           | 32           | 24            | 20            | 16           | 12           | 10           | 08           | 06            | 04            | 00           |
| FEET               | 112         | 30           | 80            | 00           | 40           | 40           | 32           | 24            | 20            | 10           | 12           | 10           | Vo           | 00            | 04            | 00           |
|                    |             |              | • • • • • • • |              |              |              |              | • • • • • • • | • • • • • • • |              |              |              |              | • • • • • • • | • • • • • • • |              |
| NO CEIL            |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 20000           |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 18000           |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 15000           | }           |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 14000           |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 12000           |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
|                    |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 10000           |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 9000            |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 8000            |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 7000            |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 6000            |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| an 5000            |             |              |               |              | 70.          |              |              |               |               |              |              |              |              |               |               |              |
| GE 5000            | 1           | 41.2         | 60.6          | 60.6         | 78.8         | 79.4         | 84.1         | 84.1          | 84.1          | 84.1         | 84.1         | 84.1         | 84.1         | 84.1          | 84.1          | 84.1         |
| GE 4500            | 40.6        | 41.2         | 60.6          | 60.6         | 78.8         | 79.4         | 84.1         | 84.1          | 84.1          | 84.1         | 84.1         | 84.1         | 84.1         | 84.1          | 84.1          | 84.1         |
| GE 4000<br>GE 3500 | 40.6        | 41.2<br>41.2 | 60.6          | 60.6         | 78.8<br>82.4 | 79.4         | 84.1         | 84.1<br>87.6  | 84.1<br>87.6  | 84.1<br>87.6 | 84.1<br>87.6 | 84.1<br>87.6 | 84.1<br>87.6 | 84.1<br>87.6  | 84.1<br>87.6  | 84.1<br>87.6 |
| GE 3500<br>GE 3000 | 40.6        | 43.5         | 60.6<br>64.7  | 60.6<br>64.7 | 90.0         | 82.9<br>90.6 | 87.6<br>95.3 | 95.3          | 95.3          | 95.3         | 95.3         | 95.3         | 95.3         | 95.3          | 95.3          | 95.3         |
| GE 3000            | 42.9        | 43.3         | 04.7          | 04.7         | 90.0         | 90.6         | 93.3         | 95.3          | 90.0          | 93.3         | 93.3         | 93.3         | 93.3         | 93.3          | 95.5          | 93.3         |
| GE 2500            | 43.5        | 44.1         | 65.3          | 65.3         | 90.6         | 91.2         | 95.9         | 95.9          | 95.9          | 95.9         | 95.9         | 95.9         | 95.9         | 95.9          | 95.9          | 95.9         |
| GE 2000            | 43.5        | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.2         | 98.2         | 98.2         | 98.2         | 98.2          | 98.2          | 98.2         |
| GE 1800            | 1           | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.2         | 98.2         | 98.2         | 98.2         | 98.2          | 98.2          | 98.2         |
| GE 1500            | 43.5        | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.2         | 98.2         | 98.2         | 98.2         | 98.2          | 98.2          | 98.2         |
| GE 1200            | 43.5        | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.2         | 98.2         | 98.2         | 98.2         | 98.2          | 98.2          | 98.2         |
|                    | ŀ           |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 1000            | 43.5        | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.2         | 98.2         | 98.2         | 98.2         | 98.2          | 98.2          | 98.2         |
| GE 900             | 43.5        | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.2         | 98.2         | 98.2         | 98.2         | 98.2          | 98.2          | 98.2         |
| GE 800             | 43.5        | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.2         | 98.2         | 98.2         | 98.2         | 98.2          | 98.2          | 98.2         |
| GE 700             | 43.5        | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.2         | 98.2         | 98.2         | 98.2         | 98.2          | 98.2          | 98.2         |
| GE 600             | 43.5        | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.2         | 98.2         | 98.2         | 98.2         | 98.2          | 98.2          | 98.2         |
|                    | 1           |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
| GE 500             |             | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.8         | 98.8         | 98.8         | 98.8         | 98.8          | 98.8          | 98.8         |
| GE 400             | ł           | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.8         | 98.8         | 98.8         | 98.8         | 98.8          | 98.8          | 98.8         |
| GE 300             | Į.          | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.8         | 98.8         | 98.8         | 98.8         | 98.8          | 98.8          | 98.8         |
| GE 200             | ı           | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.8         | 98.8         | 98.8         | 98.8         | 98.8          | 98.8          | 98.8         |
| GE 100             | 43.5        | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.8         | 98.8         | 98.8         | 99.4         | 100.0         | 100.0         | 100.0        |
| GE 000             | 43.5        | 44.1         | 65.9          | 65.9         | 92.4         | 92.9         | 98.2         | 98.2          | 98.2          | 98.8         | 98.8         | 98.8         | 99.4         | 100.0         | 100.0         | 100.0        |
|                    |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |
|                    |             |              |               |              |              |              |              |               |               |              |              |              |              |               |               |              |

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: APR HOURS: 03-05 VISIBILITY IN METERS CEILING GE GE GE GE GE GE GE GE GE GE GE GΕ GE IN GE GE ĢΕ 112 FEET 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 ..... NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 GE 5000 36.3 38.0 56.7 56.7 70.2 71.9 77.2 78.4 78.9 79.5 80.1 80.1 80.7 80.7 81.3 82.5 79.5 80.1 80.7 GE 4500 36.3 38.0 56.7 56.7 70.2 71.9 77.2 78.4 78.9 80.1 80.7 81.3 82.5 57.9 57.9 73.1 80.7 81.3 81.3 81.9 81.9 82.5 83.6 GE 4000 36.8 38.6 71.3 78.4 79.5 80.1 GE 3500 37.4 39.2 58.5 58.5 71.9 73.7 78.9 80.1 80.7 81.3 81.9 81.9 82.5 82.5 83.0 84.2 GE 3000 37.4 39.2 61.4 61.4 76.0 77.8 83.0 84.2 84.8 85.4 86.0 86.0 86.5 86.5 87.1 88.3 90.6 37.4 39.2 61.4 61.4 78.4 80.1 85.4 86.5 87.1 87.7 88.3 88.3 88.9 88.9 89.5 GE 2500 GE 2000 37.4 39.2 61.4 61.4 78.9 80.7 86.0 87.1 87.7 88.3 88.9 88.9 89.5 89.5 90.1 91.2 GE 1800 37.4 39.2 61.4 61.4 79.5 81.3 86.5 87.7 88.3 88.9 89.5 89.5 90.1 90.1 90.6 91.8 89.5 90.1 90.1 90.6 GE 1500 37.4 39.2 61.4 61.4 79.5 81.3 86.5 87.7 88.3 90.6 91.2 92.4 GΕ 1200 37.4 39.2 61.4 61.4 79.5 81.3 86.5 87.7 88.3 89.5 90.1 90.1 90.6 90.6 91.2 92.4 90.6 90.6 91.2 GE 1000 37.4 39.2 61.4 61.4 79.5 81.3 87.1 88.3 88.9 90.1 91.2 91.8 93.0 90.1 90.6 90.6 91.2 91.2 91.8 900 37.4 39.2 61.4 61.4 79.5 81.3 87.1 88.3 88.9 93.0 GE GE 800 37.4 39.2 61.4 61.4 79.5 81.3 87.1 88.3 88.9 90.1 90.6 90.6 91.2 91.2 91.8 93.0 GE 700 37.4 39.2 61.4 61.4 79.5 81.3 87.1 88.3 88.9 90.1 90.6 90.6 91.2 91.2 91.8 93.0 91.2 91.8 93.0 90.1 90.6 90.6 91.2 GΕ 600 37.4 39.2 61.4 61.4 79.5 81.3 87.1 88.3 88.9 91.8 91.8 92.4 92.4 93.0 37.4 39.2 61.4 61.4 79.5 81.3 87.1 88.3 89.5 91.2 96.5 GE 500 GE 400 37.4 39.2 61.4 61.4 79.5 81.3 87.1 88.3 89.5 91.2 91.8 91.8 93.0 93.0 93.6 97.1 GE 300 37.4 39.2 61.4 61.4 79.5 81.3 87.1 88.3 89.5 91.2 91.8 91.8 93.0 93.0 93.6 97.1 93.0 91.8 91.8 93.0 93.6 98.2 GE 200 37.4 39.2 61.4 61.4 79.5 81.3 87.1 88.3 89.5 91.2 91.8 91.8 93.0 93.0 93.6 100.0 GE 61.4 61.4 79.5 81.3 87.1 88.3 89.5 91.2 000 37.4 39.2 61.4 61.4 79.5 81.3 87.1 88.3 89.5 91.2 91.8 91.8 93.0 93.0 93.6 100.0 GE

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: APR HOURS: 06-08

| CEILING VISIBILITY IN METERS |           |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
|------------------------------|-----------|-------|------|-------------|---------------|-------------|------|---------------|-----------|-------------|---------------|---------------|---------------|---------------|------|------|-------------|
| I                            |           | GE    | GE   | GE          | GE            | GE          | GE   | GE            | GE        | GE          | GE            | GE            | GE            | GE            | GE   | GE   | GE          |
| FE                           |           | 112   | 90   | 80          | 60            | 48          | 40   | 32            | 24        | 20          | 16            | 12            | 10            | 08            | 06   | 04   | 00          |
|                              | 1         | 112   | 50   | 00          | 00            | 40          | 40   |               |           | 20          |               |               |               |               |      |      |             |
| • • • •                      |           | ••••• |      |             | • • • • • • • | • • • • • • |      | • • • • • • • |           |             | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • |      |      | •••••       |
| NO                           | CEIL      |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 20000     |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 18000     |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 16000     |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 14000     |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 12000     |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 10000     |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 9000      |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 8000      |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 7000      |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 5000      |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
|                              |           |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 5000      | 29.0  | 31.4 | 55.6        | 55.6          | 69.8        | 70.4 | 72.2          | 72.8      | 72.8        | 74.0          | 74.0          | 74.0          | 74.6          | 74.6 | 75.1 | 77.5        |
| GE                           | 4500      | 29.0  | 31.4 | 55.6        | 55.6          | 69.8        | 70.4 | 72.2          | 72.8      | 72.8        | 74.0          | 74.0          | 74.0          | 74.6          | 74.6 | 75.1 | 77.5        |
| GE                           | 4000      | 30.2  | 32.5 | 57.4        | 57.4          | 72.2        | 72.8 | 74.6          | 75.1      | 75.1        | 76.3          | 76.3          | 76.3          | 76.9          | 76.9 | 77.5 | 79.9        |
| GE                           | 3500      | 30.2  | 32.5 | 57.4        | 57.4          | 72.2        | 72.8 | 74.6          | 75.1      | 75.1        | 76.3          | 76.3          | 76.3          | 76.9          | 76.9 | 77.5 | 79.9        |
| GE                           | 3000      | 31.4  | 33.7 | 58.6        | 58.6          | 76.3        | 76.9 | 78.7          | 79.3      | 79.3        | 80.5          | 80.5          | 80.5          | 81.1          | 81.1 | 81.7 | 84.0        |
| GE                           | 2500      | 31.4  | 33.7 | 58.6        | 58.6          | 76.9        | 77.5 | 79.3          | 79.9      | 79.9        | 81.1          | 81.1          | 81.1          | 81.7          | 81.7 | 82.2 | 84.6        |
| GE                           | 2000      | 31.4  | 33.7 | 58.6        | 58.6          | 76.9        | 77.5 | 79.9          | 80.5      | 80.5        | 81.7          | 81.7          | 81.7          | 82.2          | 82.2 | 82.8 | 85.2        |
| GE                           | 1800      | 31.4  | 33.7 | 58.6        | 58.6          | 76.9        | 77.5 | 79.9          | 80.5      | 80.5        | 81.7          | 81.7          | 81.7          | 82.2          | 82.2 | 82.8 | 85.2        |
| GE                           | 1500      | 31.4  | 33.7 | 59.8        | 59.8          | 78.1        | 78.7 | 81.1          | 81.7      | 81.7        | 82.8          | 82.8          | 82.8          | 83.4          | 83.4 | 84.0 | 86.4        |
| GE                           | 1200      | 31.4  | 33.7 | 39.8        | 59.8          | 78.1        | 79.3 | 81.7          | 82.2      | 82.2        | 83.4          | 83.4          | 83.4          | 84.0          | 84.0 | 84.6 | 87.0        |
|                              |           |       |      |             |               |             |      |               |           |             |               |               |               |               |      |      |             |
| GE                           | 1000      | 32.0  | 34.3 | 60.4        | 60.4          | 79.3        | 80.5 | 82.8          | 84.0      | 84.0        | 85.2          | 85.2          | 85.2          | 85.8          | 85.8 | 86.4 | 88.8        |
| GE                           | 900       | 32.0  | 34.3 | 60.4        | 60.4          | 79.3        | 80.5 | 82.8          | 84.0      | 84.0        | 85.2          | 85.2          | 85.2          | 85.8          | 85.8 | 86.4 | 88.8        |
| GE                           | 800       | 32.0  | 34.3 | 60.4        | 60.4          | 79.3        | 80.5 | 82.8          | 84.0      | 84.0        | 85.2          | 85.2          | 85.8          | 87.0          | 87.0 | 88.2 | 90.5        |
| GE                           | 700       | 32.0  | 34.3 | 60.4        | 60.4          | 79.3        | 80.5 | 82.8          | 84.0      | 84.0        | 85.2          | 85.2          | 85.8          | 87.0          | 87.0 | 88.2 | 90.5        |
| GΕ                           | 600       | 32.0  | 34.3 | 60.4        | 60.4          | 79.3        | 80.5 | 82.8          | 84.0      | 84.0        | 85.2          | 85.2          | 85.8          | 87.0          | 87.0 | 88.2 | 90.5        |
| GE                           | 500       | 32.0  | 34.3 | 6U.4        | 60.4          | 79.3        | 80.5 | 82.8          | 84.0      | 84.0        | 85.2          | 85.8          | 86.4          | 87.6          | 87.6 | 88.8 | 91.7        |
| GE                           | 400       | 32.0  | 34.3 | 60.4        | 60.4          | 79.3        | 80.5 | 82.8          | 84.0      | 84.0        | 85.2          | 85.8          | 86.4          | 87.6          | 87.6 | 88.8 | 91.7        |
| GE                           | 300       | 32.0  | 34.3 | 60.4        | 60.4          | 79.3        | 80.5 | 82.8          | 84.6      | 84.6        | 85.8          | 86.4          | 87.0          | 88.2          | 88.2 | 89.3 | 92.3        |
| GE                           | 200       | 32.0  | 34.3 | 60.4        | 60.4          | 79.3        | 80.5 | 82.8          | 84.6      | 84.6        | 85.8          | 86.4          | 87.0          | 88.2          | 88.2 | 89.9 | 94.1        |
| GE                           | 100       | 32.0  | 34.3 | 60.4        | 60.4          | 79.3        | 80.5 | 82.8          | 84.6      | 84.6        | 85.8          | 86.4          | 87.0          | 88.2          | 88.2 | 89.9 | 96.4        |
|                              |           | 22.0  | 3    | ••••        |               | ,,,,,       |      | 52.5          | · · · · · |             | 3             | ••••          | •             |               |      |      | •           |
| GE                           | 000       | 32.0  | 34.3 | 60.4        | 60.4          | 79.3        | 80.5 | 82.8          | 84.6      | 84.6        | 85.8          | 86.4          | 87.0          | 88.2          | 88.2 | 89.9 | 100.0       |
| • • •                        | • • • • • |       |      | • • • • • • | • • • • • •   |             |      |               |           | • • • • • • | • • • • • • • | • • • • • •   | • • • • • •   | • • • • • • • |      |      | • • • • • • |

TOTAL NUMBER OF OBSERVATIONS 169

· D - 2 - 30

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: APR HOURS: 09-11

|                              |             |      | LST         | TO UTC | MONTH:      | APR      | HOURS:      | 09-11 |      |           |              |       |                |               |               |       |
|------------------------------|-------------|------|-------------|--------|-------------|----------|-------------|-------|------|-----------|--------------|-------|----------------|---------------|---------------|-------|
| • • • • • • • •              |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| CEILING VISIBILITY IN METERS |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| IN                           | GE          | GE   | GE          | GE     | GE          | GE       | GE          | GE    | GĒ   | GE        | GE           | GE    | GE             | GE            | GE            | GE    |
| FEET                         | 112         | 90   | 80          | 60     | 48          | 40       | 32          | 24    | 20   | 16        | 12           | 10    | 08             | 06            | 04            | 00    |
|                              |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
|                              |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| NO CEIL                      |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 20000                     | l l         |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 18000                     |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 16000                     | 1           |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 14000                     |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 12000                     |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 10000                     |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 9000                      | 1           |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 8000                      | <b>†</b>    |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 7000                      |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 6000                      |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 5000                      | 44.6        | 47.3 | 65.2        | 65.2   | 78.6        | 79.5     | 83.0        | 84.8  | 84.8 | 84.8      | 84.8         | 84.8  | 84.8           | 84.8          | 84.8          | 84.8  |
| GE 4500                      | 1           | 47.3 | 65.2        | 65.2   | 78.5        | 79.5     | 83.0        | 84.8  | 84.8 | 84.8      | 84.8         | 84.8  | 84.8           | 84.8          | 84.8          | 84.8  |
| GE 4000                      | 45.5        | 48.2 | 66.1        | 66.1   | 79.5        | 81.3     | 86.6        | 88.4  | 80.4 | 88.4      | 88.4         | 88.4  | 88.4           | 88.4          | 88.4          | 88.4  |
| GE 3500                      | l l         | 48.2 | 67.0        | 67.0   | 80.4        | 82.1     | 87.5        | 89.3  | 89.3 | 89.3      | 89.3         | 89.3  | 89.3           | 89.3          | 89.3          | 89.3  |
| ⊌E 3000                      | 46.4        | 49.1 | 67.9        | 67.9   | 83.0        | 84.8     | 90.2        | 92.0  | 92.0 | 92.0      | 92.0         | 92.0  | 92.0           | 92.0          | 92.0          | 92.0  |
|                              |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 2500                      | 46.4        | 49.1 | 67.9        | 67.9   | 83.0        | 84.8     | 90.2        | 92.0  | 92.0 | 92.0      | 92.0         | 92.0  | 92.0           | 92.0          | 92.0          | 92.0  |
| GE 2000                      | 46.4        | 49.1 | 67.9        | 67.9   | 83.0        | 84.8     | 90.2        | 92.0  | 92.0 | 92.0      | 92.0         | 92.0  | 92.0           | 92.0          | 92.0          | 92.0  |
| GE 1800                      | 46.4        | 49.1 | 67.9        | 67.9   | 83.0        | 84.8     | 90.2        | 92.0  | 92.0 | 92.0      | 92.0         | 92.0  | 92.0           | 92.0          | 92.0          | 92.0  |
| GE 1500                      | 46.4        | 49.1 | 69.6        | 69.6   | 84.8        | 86.6     | 92.0        | 93.8  | 93.8 | 93.8      | 93.8         | 93.8  | 93.8           | 93.8          | 93.8          | 93.8  |
| GE 1200                      | 46.4        | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 95.5      | 95.5         | 95.5  | 95.5           | 95.5          | 95.5          | 95.5  |
|                              |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |
| GE 1000                      | 1           | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 95.5      | 95.5         | 95.5  | 95.5           | 95.5          | 95.5          | 95.5  |
| GE 900                       | l .         | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 95.5      | 95.5         | 95.5  | 95.5           | 95.5          | 95.5          | 95.5  |
| GE 800                       | l .         | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 96.4      | 97.3         | 97.3  | 97.3           | 97.3          | 97.3          | 97.3  |
| GE 700                       |             | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 96.4      | 97.3         | 97.3  | 97.3           | 97.3          | 97.3          | 97.3  |
| GE 500                       | 46.4        | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 96.4      | 97.3         | 97.3  | 97.3           | 97.3          | 97.3          | 97.3  |
| GE 500                       | 46.4        | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 96.4      | 97.3         | 97.3  | 97.3           | 97.3          | 97.3          | 97.3  |
| GE 400                       | 46.4        | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 96.4      | 98.2         | 99.1  | 99.1           | 99.1          | 99.1          | 99.1  |
| GE 300                       | 46.4        | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 96.4      | 98.2         | 99.1  | 99.1           | 99.1          | 99.1          | 99.1  |
| GE 200                       | 46.4        | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 96.4      | 99.1         | 100.0 | 100.0          | 100.0         | 100.0         | 100.0 |
| GE 100                       | l .         | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 96.4      | 99.1         | 100.0 | 100.0          | 100.0         | 100.0         | 100.0 |
|                              |             |      | •           |        |             |          |             |       |      |           | <del>-</del> |       | · <del>-</del> | <del>-</del>  | · · · · · · · |       |
| GE 000                       | 46.4        | 49.1 | 69.6        | 69.6   | 84.8        | 88.4     | 93.8        | 95.5  | 95.5 | 96.4      | 99.1         | 100.0 | 100.0          | 100.0         | 100.0         | 100.0 |
| • • • • • • • •              | • • • • • • |      | • • • • • • |        | • • • • • • | <i>.</i> | • • • • • • |       |      | <b></b> . |              |       |                | • • • • • • • |               |       |
|                              |             |      |             |        |             |          |             |       |      |           |              |       |                |               |               |       |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: APR HOURS: 12-14

| CEI     | <br>LING  | •••••       |               | • • • • • •   | • • • • • •   |             | VISIBIL     | <br>FTY TN 9 | METERS        | • • • • • •   |       | • • • • • •   |             | • • • • • •   | • • • • • • • | • • • • • •   | •••••       |
|---------|-----------|-------------|---------------|---------------|---------------|-------------|-------------|--------------|---------------|---------------|-------|---------------|-------------|---------------|---------------|---------------|-------------|
| II      |           | GE          | GE            | GE            | GE            | GE          | GE          | GE           | GE            | GE            | GE    | GE            | GE          | GE            | GE            | GE            | GE          |
| FE      | ı         | 112         | 90            | 80            | 60            | 48          | 40          | 32           | 24            | 20            | 16    | 12            | 10          | 08            | 06            | 04            | 00          |
| 10.     |           |             |               |               |               | 40          |             |              |               |               |       |               |             |               |               |               |             |
| • • • • |           | •••••       | • • • • • • • | • • • • • • • | • • • • • •   |             | • • • • • • |              | • • • • • • • |               |       |               |             |               |               |               |             |
| NO (    | CEIL      |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
| GF 1    | 20000     |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
|         | 18000     |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
|         | 16000     |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
|         | 14000     |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
|         | 12000     |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
|         |           |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
| GE :    | 10000     |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
| GE      | 9000      |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
| GE      | 8000      |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
| GE      | 7000      |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
| GE      | 6000      |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
|         |           |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
| GE      | 5000      | 56.4        | 57.0          | 69.7          | 69.7          | 84.2        | 84.8        | 86.1         | 86.7          | 86.7          | 86.7  | 87.3          | 87.3        | 87.3          | 87.3          | 87.3          | 87.3        |
| GE      | 4500      | 56.4        | 57.0          | 69.7          | 69.7          | 84.2        | 84.8        | 86.1         | 86.7          | 86.7          | 86.7  | 87.3          | 87.3        | 87.3          | 87.3          | 87.3          | 87.3        |
| GE      | 4000      | 57.0        | 57.6          | 70.9          | 70.9          | 85.5        | 86.1        | 87.9         | 88.5          | 88.5          | 88.5  | 89.1          | 89.1        | 89.1          | 89.1          | 89.1          | 89.1        |
| GE      | 3500      | 57.0        | 57.6          | 70.9          | 70.9          | 85.5        | 86.1        | 87.9         | 88.5          | 88.5          | 88.5  | 89.1          | 89.1        | 89.1          | 89.1          | 89.1          | 89.1        |
| GE      | 3000      | 57.0        | 57.6          | 70,9          | 70.9          | 86.1        | 86.7        | 88.5         | 89.1          | 89.1          | 89.1  | 89.7          | 89.7        | 89.7          | 89.7          | 89.7          | 89.7        |
| GE      | 2500      | 57.0        | 57.6          | 70.9          | 70.9          | 87.3        | 87.9        | 89.7         | 90.3          | 90.3          | 90.3  | 90.9          | 90.9        | 90.9          | 90.9          | 90.9          | 90.9        |
| GE      | 2000      | 58.2        | 58.8          | 72.7          | 70.9          | 89.7        | 90.3        | 93.3         | 93.9          | 93.9          | 93.9  | 94.5          | 94.5        | 94.5          | 94.5          | 94.5          | 94.5        |
| GE      | 1800      | 58.2        | 58.8          | 72.7          | 72.7          | 89.7        | 90.3        | 93.3         | 93.9          | 93.9          | 93.9  | 94.5          | 94.5        | 94.5          | 94.5          | 94.5          | 94.5        |
| GE      | 1500      | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 96.4         | 97.0          | 97.0          | 97.0  | 97.6          | 97.6        | 97.6          | 97.6          | 97.6          | 97.6        |
| GE      | 1200      | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 96.4         | 97.0          | 97.0          | 97.0  | 97.6          | 97.6        | 97.6          | 97.6          | 97.6          | 97.6        |
| OL.     | 1200      | 00.0        | 00.0          | , 3.0         | 73.0          | ,,,,        | 33.3        | ,,,,,        | 37.00         | 3.40          | 37.00 | 3.00          | 3, 10       | 3,            | 3, 10         | 3,            | 3, 10       |
| GE      | 1000      | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 97.6         | 98.8          | 98.8          | 98.8  | 99.4          | 99.4        | 99.4          | 99.4          | 99.4          | 99.4        |
| GE      | 900       | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 97.6         | 98.8          | 98.8          | 98.8  | 99.4          | 99.4        | 99.4          | 99.4          | 99.4          | 99.4        |
| GE      | 800       | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 97.6         | 98.8          | 99.4          | 99.4  | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE      | 700       | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 97.6         | 98.8          | 99.4          | 99.4  | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GΕ      | 600       | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 97.6         | 98.8          | 99.4          | 99.4  | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
|         |           |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
| GE      | 500       | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 97.6         | 98.8          | 99.4          | 99.4  | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE      | 400       | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 97.6         | 98.8          | 99.4          | 99.4  | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE      | 300       | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 97.6         | 98.8          | 99.4          | 99.4  | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE      | 200       | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 97.6         | 98.8          | 99.4          | 99.4  | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE      | 100       | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 97.6         | 98.8          | 99.4          | 99.4  | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
|         |           |             |               |               |               |             |             |              |               |               |       |               |             |               |               |               |             |
| GE      | 000       | 60.0        | 60.6          | 75.8          | 75.8          | 92.7        | 93.3        | 97.6         | 98.8          | 99.4          | 99.4  | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| • • •   | • • • • • | • • • • • • | • • • • • •   |               | • • • • • • • | • • • • • • | • • • • • • | • • • • • •  | • • • • • •   | • • • • • • • |       | • • • • • • • | • • • • • • | • • • • • • • | • • • • • •   | • • • • • • • | • • • • • • |

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: APR HOURS: 15-17 CEILING VISIBILITY IN METERS IN GE GΕ GE GE GE GE GE GE GE GE GE GE GE GE GE GE FEET 112 80 60 48 32 24 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 82.4 GE 5000 57.6 60.0 73.3 73.3 81.8 81.8 81.8 81.8 81.8 81.8 82.4 82.4 82.4 82.4 82.4 GE 4500 58.8 61.2 74.5 74.5 83.0 83.0 83.0 83.0 83.0 83.0 83.6 83.6 83.6 83.6 83.6 83.6 GE 4000 60.0 62.4 75.8 75.8 84.2 84.2 84.2 84.2 84.2 84.2 84.8 84.8 84.8 84.8 84.8 84.8 GE 3500 75.8 60.0 62.4 75.8 85.5 85.5 85.5 85.5 85.5 85.5 86.1 86.1 86.1 86.1 86.1 85.1 GE 3000 62.4 64.8 78.2 78.2 90.3 90.3 90.3 90.3 90.3 90.3 90.9 90.9 90.9 90.9 90.9 90.9 78.2 78.2 90.3 90.3 90.9 90.9 90.9 90.9 90.9 GE 2500 62.4 64.8 90.3 90.3 90.3 90.3 90.9 GE 2000 62.4 64.8 80.0 80.0 92.1 92.1 92.7 92.7 93.3 93.3 93.9 93.9 93.9 93.9 93.9 93.9 1800 64.8 80.0 92.1 92.7 92.7 93.3 93.3 93.9 93.9 93.9 93.9 93.9 GE 62.4 80.0 92.1 93.9 1500 95.8 95.8 95.8 GE 64.2 66.7 81.8 81.8 93.9 93.9 94.5 94.5 95.2 95.2 95.8 95.8 95. R GE 1200 64.2 66.7 81.8 81.8 95.8 95.8 96.4 96.4 97.0 97.0 97.6 97.6 97.6 97.6 97.6 97.6 GE 1000 64.2 66.7 81.8 81.8 95.8 95.8 96.4 98.2 98.8 98.8 99.4 99.4 99.4 99.4 99.4 99.4 GF. 900 64.2 66.7 81.8 81.8 95.8 95.8 96.4 98.2 98.8 98.8 99.4 99.4 99.4 99.4 99.4 99.4 97.0 99.4 100.0 100.0 100.0 100.0 100.0 100.0 800 64.2 66.7 81.8 81.8 95.8 96.4 98.8 99.4 GE GE 700 64.2 66.7 81.8 81.8 95.8 96.4 97.0 98.8 99.4 99.4 100.0 100.0 100.0 100.C 100.O 100.0 GE 600 64.2 66.7 81.8 81.8 95.8 96.4 97.0 98.8 99.4 99.4 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 64.2 66.7 81.8 81.8 95.8 96.4 97.0 98.8 99.4 99.4 100.0 100.0 100.0 100.0 100.0 100.0 GE 64.2 95.8 96.4 97.0 98.8 99.4 99.4 100.0 100.0 100.0 100.0 100.0 100.0 400 66.7 81.8 81.8 GE 300 64.2 66.7 81.8 81.8 95.8 96.4 97.0 98.8 99.4 99.4 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 64.2 66.7 81.8 81.8 95.8 96.4 97.0 98.8 99.4 99.4 100.0 100.0 100.0 100.0 100.0 97.0 100-0 100-0 100-0 95.8 96.4 98.8 99.4 99.4 100.0 100.0 100.0 GE 100 64.2 66.7 81.8 81.8

TOTAL NUMBER OF OBSERVATIONS 165

GE

000 64.2

66.7

81.8

81.8

99.4

98.8

96.4

95.8

97.0

99.4 100.0 100.0 100.0 100.0 100.0 100.0

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: APR HOURS: 18-20

|            |           |             |             | 201           | 10 010      | . ,                                     |               |             |               |               |               |               |             | 10 00         |               |               |             |
|------------|-----------|-------------|-------------|---------------|-------------|---|---------------|-------------|---------------|---------------|---------------|---------------|-------------|---------------|---------------|---------------|-------------|
| CEI        | LING      |             | • • • • • • | • • • • • • • | • • • • • • | • | /ISIBIL       | <br>ITY IN  | METERS        | - • • • • • • | • • • • • •   | • • • • • • • |             |               | •••••         |               |             |
|            | N I       | GE          | GE          | GE            | GE          | GE                                      | GE            | GE          | GE            | GE            | GE            | GE            | GE          | GE            | GE            | GÉ            | GE          |
|            | ET        | 112         | 90          | 80            | 60          | 48                                      | 40            | 32          | 24            | 20            | 16            | 12            | 10          | 08            | 06            | 04            | 00          |
|            | D1        | ***         | 30          | 00            | 00          | 40                                      | 40            | 55          |               | 20            |               |               |             |               | 00            | •             |             |
| • • •      |           |             | • • • • • • | • • • • • • • |             | • • • • • •                             | • • • • • • • |             |               |               | • • • • • • • |               |             |               | •••••         | • • • • • • • | •••••       |
| NO         | CE 11     |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
| NO         | CEIL      |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
|            |           |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
|            | 20000     |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
|            | 18000     |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
|            | 16000     |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
|            | 14000     |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
| GE         | 12000     |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
|            |           |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
| GE         | 10000     |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
| GE         | 9000      |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
| GΕ         | 8000      |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
| GE         | 7000      |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
| GE         | 6000      |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
|            | į         |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
| GE         | 5000      | 60.0        | 61.2        | 73.9          | 73.9        | 82.4                                    | 82.4          | 82:4        | 82.4          | 82.4          | 82.4          | 82.4          | 82.4        | b2.4          | 82.4          | 82.4          | 82.4        |
| GE         | 4500      | 60.6        | 61.8        | 74.5          | 74.5        | 83.0                                    | 83.0          | 83.0        | 83.0          | 83.0          | 83.0          | 83.0          | 83.0        | 83.0          | 83.0          | 83.0          | 83.0        |
| GE         | 4000      | 62.4        | 63.6        | 77.0          | 77.0        | 86.1                                    | 86.1          | 86.1        | 86.1          | 86.1          | 86.1          | 86.1          | 86.1        | 86.1          | 85.1          | 86.1          | 86.1        |
| GE         | 3500      | 62.4        | 63.6        | 77.0          | 77.0        | 87.9                                    | 87.9          | 87.9        | 87.9          | 87.9          | 87.9          | 87.9          | 87.9        | 87.9          | 87.9          | 87.9          | 87.9        |
| GE         | 3000      | 64.2        | 65.5        | 80.0          | 80.0        | 90.9                                    | 90.9          | 90.9        | 90.9          | 90.9          | 90.9          | 90.9          | 90.9        | 90.9          | 90.9          | 90.9          | 90.9        |
|            |           |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
| GE         | 2500      | 64.2        | 65.5        | 80.0          | 80.0        | 92.1                                    | 92.1          | 92.1        | 92.1          | 92.1          | 92.1          | 92.1          | 92.1        | 92.1          | 92.1          | 92.1          | 92.1        |
| GE         | 2000      | 65.5        | 66.7        | 81.8          | 81.8        | 94.5                                    | 95.8          | 95.8        | 96.4          | 96.4          | 96.4          | 96.4          | 96.4        | 96.4          | 96.4          | 96.4          | 96.4        |
| GE         | 1800      | 65.5        | 66.7        | 81.8          | 81.8        | 94.5                                    | 95.8          | 95.8        | 96.4          | 96.4          | 96.4          | 96.4          | 96.4        | 96.4          | 96.4          | 96.4          | 96.4        |
| GE         | 1500      | 66.7        | 67.9        | 83.0          | 83.0        | 95.8                                    | 97.0          | 97.0        | 97.6          | 97.6          | 97.6          | 97.6          | 97.6        | 97.6          | 97.6          | 97.6          | 97.6        |
| GE         | 1200      | 66.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| 0.5        | 1200      | 00.7        | 0,13        | 03.0          | 03.0        | 30.2                                    | ,,,,          | ,,,,        | 100.0         | 100.0         | 10010         | 10010         | 10000       | 100.0         | 100.0         | 10010         | 100.0       |
| GE         | 1900      | 66.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE         | 900       | 66.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE         | 800       | 66.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE         | 700       | 66.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE         |           | 66.7        | 67.9        |               |             |   |               |             | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE         | 600       | 00.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| <b>a</b> n | 500       | 66.7        | c7 0        | 02.0          | 03.0        | 00.0                                    | 00.4          | 00.4        | 100.0         | 100 0         | 100.0         | 100 0         | 100 0       | 100.0         | 100.0         | 100.0         | 100 0       |
| GE         | 500       | 66.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE         | 400       | 66.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE         | 300       | 66.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE         | 200       | 66.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| GE         | 100       | 66.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
|            |           |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |
| GE         | 000       | 66.7        | 67.9        | 83.0          | 83.0        | 98.2                                    | 99.4          | 99.4        | 100.0         | 100.0         | 100.0         | 100.0         | 100.0       | 100.0         | 100.0         | 100.0         | 100.0       |
| • • •      | • • • • • | • • • • • • | • • • • • • | • • • • • •   | • • • • • • | • • • • • •                             | • • • • • •   | • • • • • • | • • • • • • • | • • • • • •   | • • • • • • • | • • • • • • • | • • • • • • | • • • • • • • | • • • • • • • | • • • • • •   | • • • • • • |
|            |           |             |             |               |             |   |               |             |               |               |               |               |             |               |               |               |             |

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBITITY FROM HOURLY OBSERVATIONS

STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 LST TO UTC: - 9 MONTH: APR HOURS: 21-23 CEILING VISIBILITY IN METERS IN GÉ GΕ GE GE GE GE GE GE GE GE GE GE GE GE 60 48 40 32 24 20 16 12 10 80 06 04 112 90 80 00 FEET NO CELL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GΕ 9000 GE 8000 GE 7000 GE 6000 70.7 86.2 50.3 70.7 83.8 86.2 86.2 86.2 86.2 86.2 86.2 86.2 86.2 GE 5000 48.5 86.2 86.2 GΕ 4500 48.5 50.3 70.7 70.7 83.8 86.2 86.2 86.2 86.2 86.2 86.2 86.2 86.2 86.2 86.2 86.2 50.3 71.9 71.9 85.6 88.0 88.0 88.0 88.0 88.0 88.0 88.0 88.0 GE 4000 48.5 88.0 88.0 3500 89.8 89.8 89.8 87.4 89.8 89.8 89.8 89.8 89.8 89.8 89.8 GE 48.5 50.3 71.9 71.9 89.8 GE 3000 49.7 51.5 74.3 74.3 89.8 92.2 92.2 92.2 92.2 92.2 92.2 92.2 92.2 92.2 92.2 92.2 51.5 76.0 76.0 91.6 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 GE 2500 53.3 94.0 94.0 94.0 GE 2000 51.5 53.3 79.6 79.6 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 51.5 53.3 79.6 GE 1800 79.6 GE 1500 51.5 53.3 79.6 79.6 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 1200 51.5 53.3 79.6 79.6 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 1000 51.5 53.3 79.6 79.6 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 900 53.3 79.6 79.6 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 51.5 GE 800 51.5 53.3 79.6 79.6 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GΕ 700 51.5 53.3 79.6 79.6 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 79.6 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 600 51.5 53.3 79.6 GE 500 51.5 53.3 79.6 79.6 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 51.5 53.3 79.6 79.6 100.0 Œ 300 51.5 53.3 79.6 79.6 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 51.5 100.0 100.0 100.0 100.0 100.0 100.0 200 53.3 79.6 79.6 96.4 100.0 100.0 100.0 100.0 GΕ 100 51.5 53.3 79.6 79.6 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 96.4 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 000 51.5 53.3 79.6 79.6

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: APR HOURS: ALL

|               | · • • • • • • • |               | • • • • • •   |               |             |             |          |               |             |             | • • • • • •   |             |             | • • • • • • |               | • • • • • • |
|---------------|-----------------|---------------|---------------|---------------|-------------|-------------|----------|---------------|-------------|-------------|---------------|-------------|-------------|-------------|---------------|-------------|
| CEILING       | l an            |               |               | an            |             |             | ITY IN I |               | <b>CP</b>   | an          | an            | an.         | an.         | <b>a</b> n  | <b>an</b>     | 20          |
| IN            | GE              | GE            | GE            | GE            | GE          | GE          | GE       | GE            | GE          | GE          | GE            | GE          | GE          | GE          | GE            | GE          |
| FEET          | 112             | 90            | 80            | 60            | 48          | 40          | 32       | 24            | 20          | 16          | 12            | 10          | 80          | 06          | 04            | 00          |
| • • • • • • • | • • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • | • • • • • • |          | • • • • • • • | • • • • • • | • • • • • • | • • • • • • • | • • • • • • | • • • • • • | • • • • • • | • • • • • • • | • • • • • • |
| NO CEIL       |                 |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 2000       | ,               |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 1800       | 1               |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 1600       |                 |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 1400       | i i             |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 1200       | 1               |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
|               |                 |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 1000       | )               |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 900        |                 |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 800        |                 |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 700        | )               |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 600        |                 |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
|               |                 |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 500        | 46.6            | 48.2          | 65.7          | 65.7          | 78.7        | 79.5        | 81.5     | 82.0          | 82.1        | 82.3        | 82.6          | 82.6        | 82.7        | 82.7        | 82.9          | 83.3        |
| GE 450        | 46.8            | 48.4          | 65.9          | 65.9          | 78.9        | 79.8        | 81.8     | 82.2          | 82.3        | 82.6        | 82.8          | 82.8        | 82.9        | 82.9        | 83.1          | 83.6        |
| GE 400        | 47.6            | 49.2          | 67.1          | 67.1          | 80.4        | 81.3        | 83.6     | 84.0          | 84.1        | 84.3        | 84.6          | 84.6        | 84.7        | 84.7        | 84.9          | 85.4        |
| GE 350        | 47.7            | 49.3          | 67.3          | 67.3          | 81.6        | 82.6        | 84.8     | 85.3          | 85.4        | 85.6        | 85.8          | 85.8        | 86.0        | 86.0        | 86.1          | 86.6        |
| GE 300        | 48.9            | 50.5          | 69.5          | 69.5          | 85.4        | 86.3        | 88.6     | 89.0          | 89.1        | 89.3        | 89.6          | 89.6        | 89.7        | 89.7        | 89.9          | 90.3        |
|               | 1               |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 250        | 49.2            | 50.9          | 69.8          | 69.8          | 86.4        | 87.3        | 89.6     | 90.0          | 90.1        | 90.3        | 90.6          | 90.6        | 90.7        | 90.7        | 90.9          | 91.4        |
| GE 200        | 49.5            | 51.2          | 71.0          | 71.0          | 88.2        | 89.4        | 92.1     | 92.6          | 92.8        | 93.0        | 93.2          | 93.2        | 93.4        | 93.4        | 93.5          | 94.0        |
| GE 180        | 49.5            | 51.2          | 71.0          | 71.0          | 88.2        | 89.5        | 92.1     | 92.7          | 92.8        | 93.1        | 93.3          | 93.3        | 93.5        | 93.5        | 93.6          | 94.1        |
| GE 150        | 50.2            | 51.8          | 72.1          | 72.1          | 89.3        | 90.5        | 93.2     | 93.8          | 93.9        | 94.2        | 94.5          | 94.5        | 94.6        | 94.6        | 94.8          | 95.2        |
| GE 120        | 50.2            | 51.8          | 72.1          | 72.1          | 89.9        | 91.4        | 94.0     | 94.5          | 94.7        | 95.0        | 95.2          | 95.2        | 95.4        | 95.4        | 95.6          | 96.0        |
|               |                 |               |               |               |             |             |          |               |             |             |               |             |             |             |               |             |
| GE 100        | 1               | 51.9          | 72.2          | 72.2          | 90.0        | 91.5        | 94.4     | 95.3          | 95.5        | 95.8        | 96.0          | 96.0        | 96.2        | 96.2        | 96.3          | 96.8        |
| GE 90         | 1               | 51.9          | 72.2          | 72.2          | 90.0        | 91.5        | 94.4     | 95.3          | 95.5        | 95.8        | 96.0          | 96.0        | 96.2        | 96.2        | 96.3          | 96.8        |
| GE 80         | 1               | 51.9          | 72.2          | 72.2          | 90.0        | 91.6        | 94.5     | 95.4          | 95.6        | 96.0        | 96.3          | 96.4        | 96.7        | 96.7        | 96.9          | 97.4        |
| GE 70         | Ł               | 51.9          | 72.2          | 72.2          | 90.0        | 91.6        | 94.5     | 95.4          | 95.6        | 96.0        | 96.3          | 96.4        | 96.7        | 96.7        | 96.9          | 97.4        |
| GE 60         | 50.2            | 51.9          | 72.2          | 72.2          | 90.0        | 91.6        | 94.5     | 95.4          | 95.6        | 96.0        | 96.3          | 96.4        | 96.7        | 96.7        | 96.9          | 97.4        |
| AR F0         |                 | 51.0          | 72.2          | 72.2          | 00.0        | 01.6        | 04.5     | 05.4          | 05.7        | 06.1        | 06.7          | 06.7        | 07.0        | 07.0        | 07.3          | 00 1        |
| GE 50         | 1               | 51.9          | 72.2          | 72.2          | 90.0        | 91.6        | 94.5     | 95.4          | 95.7        | 96.3        | 96.7          | 96.7        | 97.0        | 97.0        | 97.2          | 98.1        |
| GE 40         | _               | 51.9          | 72.2          | 72.2          | 90.0        | 91.6        | 94.5     | 95.4          | 95.7        | 96.3        | 96.7          | 96.9        | 97.2        | 97.2        | 97.4          | 98.3        |
| GE 30         | 1               | 51.9          | 72.2          | 72.2          | 90.0        | 91.6        | 94.5     | 95.5          | 95.8        | 96.3        | 96.8          | 97.0        | 97.3        | 97.3        | 97.5          | 98.4        |
| GE 20         | 1               | 51.9          | 72.2          | 72.2          | 90.0        | 91.6        | 94:5     | 95.5          | 95.8        | 96.3        | 96.9          | 97.0        | 97.4        | 97.4        | 97.7          | 98.8        |
| GE 10         | 50.2            | 51.9          | 72.2          | 72.2          | 90.0        | 91.6        | 94.5     | 95.5          | 95.8        | 96.3        | 96.9          | 97.0        | 97.4        | 97.5        | 97.8          | 99.5        |
| GE 00         | 50.2            | 51.9          | 72.2          | 72.2          | 90.0        | 91.6        | 94.5     | 95.5          | 95.8        | 96.3        | 96.9          | 97.0        | 97.4        | 97.5        | 97.8          | 100.0       |
| GE 00         | 1 30.2          | 31.9          | 12.2          | 16.2          | 90.0        | 91.0        | 34.3     | 90.0          | 33.0        | 30.3        | 30.3          | 97.0        | 21.4        | 91.3        | 31.0          | 100.0       |
|               |                 |               |               | · · · · · ·   |             |             |          |               |             | · · · · ·   |               |             |             |             |               |             |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAY HOURS: 00-02

| CEII     | <br>LING | • • • • • • |      | • • • • • •   | • • • • • •   | ,           | /ISIBIL:      | ITY IN I | METERS       | • • • • • • |         |      |         | • • • • • •   | • • • • • • |         |       |
|----------|----------|-------------|------|---------------|---------------|-------------|---------------|----------|--------------|-------------|---------|------|---------|---------------|-------------|---------|-------|
| II       |          | GE          | GE   | GE            | GE            | GE          | GE            | GE       | GE           | GE          | GE      | GE   | GE      | GE            | GE          | GE      | GE    |
| FE       | - 1      | 112         | 90   | 80            | 60            | 48          | 40            | 32       | 24           | 20          | 16      | 12   | 10      | 08            | 06          | 04      | 00    |
|          |          |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| • • • •  | 1        |             |      | • • • • • •   | • • • • • • • | • • • • • • | • • • • • • • |          |              |             |         |      |         |               |             |         |       |
| NO (     | CEIL     |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
|          |          |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE 2     | 20000    |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE :     | 18000    |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE 1     | 16000    |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE :     | 14000    |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE :     | 12000    |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
|          |          |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE :     | 10000    |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE       | 9000     |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE       | 8000     |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE       | 7000     |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE       | 6000     |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
|          |          |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE       | 5000     | 25.6        | 26.7 | 48.9          | 48.9          | 54.4        | 57.8          | 57.8     | 57.8         | 57.8        | 58.9    | 58.9 | 58.9    | 59.4          | 59.4        | 59.4    | 59.4  |
| GE       | 4500     | 27.2        | 28.3 | 50.6          | 50.6          | 56.1        | 59.4          | 59.4     | 59.4         | 59.4        | 60.6    | 60.6 | 60.6    | 61.1          | 51.1        | 61.1    | 61.1  |
| GE       | 4000     | 28.3        | 29.4 | 54.4          | 54.4          | 61.7        | 65.0          | 65.0     | 65.0         | 65.0        | 66.1    | 66.1 | 66.1    | 66.7          | 66.7        | 66.7    | 66.7  |
| GE       | 3500     | 28.3        | 29.4 | 56.7          | 56.7          | 66.7        | 70.0          | 70.0     | 70.0         | 70.0        | 71.1    | 71.1 | 71.1    | 71.7          | 71.7        | 71.7    | 71.7  |
| GE       | 3000     | 33.3        | 34.4 | 62.2          | 62.2          | 73.9        | 77.2          | 77.2     | 77.2         | 77.2        | 78.3    | 78.9 | 78.9    | 79.4          | 79.4        | 79.4    | 79.4  |
|          |          |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         |       |
| GE       | 2500     | 33.3        | 34.4 | 63.3          | 63.3          | 76.7        | 80.0          | 80.0     | 80.0         | 80.0        | 81.1    | 81.7 | 81.7    | 82.2          | 82.2        | 82.2    | 82.2  |
| GE       | 2000     | 33.3        | 34.4 | 63.3          | 63.3          | 77.2        | 80.6          | 80.6     | 80.6         | 80.6        | 81.7    | 82.2 | 82.2    | 82.8          | 82.8        | 82.8    | 82.8  |
| GE       | 1800     | 33.3        | 34.4 | 63.9          | 63.9          | 79.4        | 82.8          | 82.8     | 82.8         | 82.8        | 83.9    | 84.4 | 84.4    | 85.0          | 85.0        | 85.0    | 85.0  |
| GE       | 1500     | 33.9        | 35.0 | 66.1          | 66.1          | 82.8        | 86.1          | 87.2     | 87.2         | 87.2        | 88.3    | 88.9 | 88.9    | 89.4          | 89.4        | 89.4    | 89.4  |
| GE       | 1200     | 33.9        | 35.0 | 66.1          | 66.1          | 86.1        | 89.4          | 90.6     | 90.6         | 91.7        | 92.8    | 93.3 | 93.3    | 93.9          | 93.9        | 93.9    | 93.9  |
| CE       | 1000     | 33.9        | 35.0 | 66.1          | 56.1          | 86.7        | 90.0          | 92.2     | 92.2         | 93.3        | 94.4    | 95.0 | 95.0    | 95.6          | 95.6        | 95.6    | 95.6  |
| GE<br>GE | 900      | 33.9        | 35.0 | 66.1          | 66.1          | 86.7        | 90.6          | 92.2     | 92.2         | 94.4        | 95.6    | 96.1 | 96.1    | 96.7          | 96.7        | 96.7    | 96.7  |
|          | 800      |             |      |               | 66.1          | 86.7        |               |          | 92.8         | 94.4        | 95.6    | 96.1 | 96.1    | 96.7          | 96.7        | 96.7    | 96.7  |
| GE       | 700      | 33.9        | 35.0 | 66.1          |               | 86.7        | 90.6          | 92.8     |              |             | 95.6    | 96.1 | 96.1    | 96.7          | 96.7        | 96.7    | 96.7  |
| GE       |          | 33.9        | 35.0 | 66.1          | 66.1          |             | 90.6          | 92.8     | 92.8<br>92.8 | 94.4        | 95.6    | 96.1 | 96.1    | 96.7          | 96.7        | 96.7    | 96.7  |
| GE       | 600      | 33.9        | 35.0 | 66.1          | 56.1          | 86.7        | 90.6          | 92.8     | 92.0         | 94.4        | 90.0    | 90.1 | 90.1    | 90.7          | 90.7        | 90.7    | 90.7  |
| GE       | 500      | 33.9        | 35.0 | 66.1          | 66.1          | 86.7        | 90.6          | 92.8     | 92.8         | 94.4        | 95.6    | 96.7 | 96.7    | 97.2          | 97.2        | 97.2    | 97.2  |
| GE       | 400      | 33.9        | 35.0 | 65.1          | 66.1          | 86.7        | 90.6          | 93.3     | 93.9         | 95.6        | 96.7    | 97.8 | 97.8    | 98.3          | 98.3        | 98.3    | 98.3  |
| GE       | 300      | 33.9        | 35.0 | 66.1          | 66.1          | 86.7        | 90.6          | 93.3     | 93.9         | 95.6        | 96.7    | 97.8 | 97.8    | 98.3          | 98.3        | 98.3    | 98.3  |
| GE.      | 200      | 33.9        | 35.0 | 66.1          | 66.1          | 86.7        | 90.6          | 93.3     | 93.9         | 95.6        | 97.2    | 98.3 | 98.3    | 98.9          | 98.9        | 98.9    | 98.9  |
|          | 100      | 33.9        | 35.0 | 66.1          | 66.1          | 86.7        | 90.6          | 93.3     | 93.9         | 95.6        | 97.2    | 98.3 | 98.3    | 98.9          | 98.9        | 99.4    | 100.0 |
| GE       | 100      | )J.9        | 33.9 | 99.1          | 99.1          | 00.7        | 90.0          | 93.3     | 73.7         | 90.0        | 91.2    | 30.3 | 30.3    | 30.3          | 70.7        | 22.4    | 100.0 |
| GE       | 000      | 33.9        | 35.0 | 66.1          | 66.1          | 86.7        | 90.6          | 93.3     | 93.9         | 95.6        | 97.2    | 98.3 | 98.3    | 98.9          | 98.9        | 99.4    | 100.0 |
| 96       |          |             |      |               |               |             |               |          |              |             |         |      |         |               |             |         | 100.0 |
|          |          |             |      | · · · · · · · | <b></b>       |             |               |          |              | <b></b>     | · · · · |      | <b></b> | - · · · · · · | <b></b>     | <b></b> |       |

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 LST TO UTC: - 9 MONTH: MAY HOURS: 03-05 CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GE GE GE GE FEET 112 90 80 48 40 32 24 20 16 12 10 08 06 00 60 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 8000 GE GE 7000  $_{\rm GE}$ 6000 56.1 56.1 56.1 56.1 56.1 56.1 56.1 56.7 GF. 5000 22.2 22.8 34.4 34.4 50.6 53.3 55.5 56.1 GE 4500 23.9 24.4 36.1 36.1 52.8 55.6 57.8 50.3 58.3 58.3 58.3 58.3 58.3 58.3 58.3 58.9 GE4000 23.9 24.4 36.7 36.7 58.9 61.1 61.7 61.7 61.7 61.7 61.7 61.7 61.7 61.7 62.2 56.1 GE 25.6 38.3 38.3 58.3 61.1 63.3 63.9 63.9 63.9 63.9 63.9 63.9 63.9 63.9 64.4 3500 25.0 GE 3000 26.7 21.2 41.7 41.7 63.9 66.7 68.9 69.4 69.4 69.4 69.4 69.4 69.4 69.4 69.4 70.0 GE 65.6 72.2 72.8 72.8 72.8 72.8 72.8 72.8 7...8 72.8 73.3 25001 26.7 27.2 41.7 41.7 69.4 GE 2000 26.7 27.2 42.2 42.2 66.1 70.0 72.8 73.3 73.3 73.3 73.3 73.3 73.3 73.3 73.3 73.9 75.0 75.0 75.0 75.0 75.0 75.0 75.0 75.6 GE 1800 26.7 27.2 42.2 42.2 67.2 71.7 74.4 75.0 85.0 85.0 85.0 85.0 85.0 GE 1500 27.2 27.8 42.8 42.8 70.6 75.0 83.9 84.4 85.0 85.0 85.6 89.4 89.4 89.4 89.4 89.4 89.4 90.0 GE 1200 27.2 27.8 42.8 73.3 78.3 88.3 88.9 89.4 GE 1000 27.2 27.8 42.8 42.8 73.9 78.9 98.9 89.4 90.0 90.6 90.6 90.6 90.6 90.6 90.€ 91.1 GF. 300 27.2 27.8 42.8 73.9 78.9 48.9 89.4 90.0 90.6 90.6 90.6 90.6 90.6 90.6 91.1 42.8 91.1 91.1 92.2 GE 800 27.2 27.B 42.8 42.8 73.9 78.9 88.9 80.4 90.0 90.6 92.2 92.2 92.8 GE700 27.2 27.8 42.8 42.8 73.9 78.9 88.9 89.4 90.0 90.6 91.1 91.1 92.2 92.2 92.2 92.8 600 27.2 73.9 89.4 90.0 90.6 91.1 91.1 92.2 92.2 92.2 92.8 GE 27.9 42.8 42.8 78.9 88.9 90.0 90.6 91.1 92.2 92.2 92.2 92.8 GE 27.2 27.8 42.8 42.8 73.9 78.9 88.9 89.4 91.1 92.2 92.8 93.3 94.4 95.0 95.0 GE 4001 27.2 27.8 42.8 42.8 73.9 78.9 90.6 91.1 91.7 95.6 GE 300 27.2 27.8 42.8 42.F 73.9 78.9 90.6 91.1 91.7 92.2 92.8 9..3 96.1 96.7 96.7 97.8 98.3 SE 200 27.2 27.8 42.8 42.8 73.9 78.9 90.6 91.7 92.2 92.8 93.3 96.1 96.7 96.7 91.1 91.7 92.2 92.8 100.0 GE 190 27.2 27.8 42.8 42.8 73.9 78.9 90.6 91.1 93.3 96.1 96.7 96.7 92.8 93.3 96.7 96.7 100.0 GE 000 27.2 27.8 42.8 42.8 73.9 78.9 90.6 91.1 91.7 92.2 96.1

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAY HOURS: 06-08 CEILING VISIBILITY IN METERS GE IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE 112 60 FEET 90 80 48 32 24 20 40 16 12 10 08 06 04 00 NO CELL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE9000 GE. 8000 GE 7000 6000 GEGE 5000 15.6 16.1 25.6 25.6 36.7 37.8 40.6 41.7 42.2 43.3 45.0 45.0 46.1 46.1 46.7 48.9 27.8 GE 38.9 4500 17.2 17.8 27.8 40.0 42.8 43.9 44.4 45.6 47.2 47.2 48.3 48.3 48.9 51.1 GE 4000 17.2 17.8 27.8 27.8 40.6 41.7 44.4 45.6 46.1 47.2 48.9 48.9 50.0 50.0 50.6 52.8 GE3500 19.4 20.0 30.6 30.6 43.3 44.4 47.2 48.3 48.9 50.6 52.2 52.2 53.3 53.3 53.9 56.1 GE 3000 21.7 22.8 33.9 33.9 48.3 49.4 52.8 54.4 55.0 56.7 58.3 58.3 59.4 59.4 60.0 62.2 GE 2500 21.7 22.8 33.9 33.9 48.3 49.4 54.4 56.1 60.0 60.0 56.7 58.3 61.1 GE 2000 21.7 22.8 33.9 33.9 50.0 51.1 56.1 57.8 61.7 62.8 63.3 58.3 60.0 61.7 62.8 65.6 SE 1800 21.7 22.8 33.9 33.9 50.0 51.7 56.7 58.3 59.4 61.7 63.3 63.3 65.0 65.0 65.6 67.8 GE 1500 21.7 22.8 34.4 34.4 54.4 56.1 62.8 64.4 66.1 68.9 70.6 71.1 72.8 72.8 73.3 GE 1200 24.4 37.2 37.2 57.2 60.6 67.8 70.0 79.4 23.3 72.2 75.6 77.2 77.8 79.4 80.0 82.2 1000 GE 23.3 24.4 37.2 37.2 57.2 60.6 68.3 71.7 73.9 77.2 80.0 81.1 82.8 82.8 93.3 85.6 900 68.3 GE 23.3 24.4 37.2 37.2 57.2 60.6 71.7 73.9 77.2 80.0 81.7 83.3 83.3 83.9 86.1 GE 300 24.4 37.2 37.2 57.2 60.6 68.3 71.7 73.9 8€.1 23.3 78.9 81.7 83.3 85.6 85.6 88.3 GE 700 23.3 24.4 37.2 37.2 57.2 68.3 60.6 72.2 74.4 79.4 83.5 86.1 86.1 86.7 88.9 82.2 GE 600 23.3 24.4 37.2 37.2 57.2 60.6 68.3 72.2 75.0 82.2 85.6 87.2 90.6 90.6 91.1 93.3 500! 57.2 GE 23.3 24.4 37.2 37.2 60.6 68.3 72.2 75.0 82.2 85.6 87.2 90.6 90.6 91.1 93.3 GE 400 23.3 24.4 37.2 37.2 57.2 60.6 68.3 72.2 75.0 82.2 86.1 87.8 91.7 91.7 92.2 GE 300 23.3 24.4 37.2 37.2 57.2 60.6 68.3 72.8 75.6 82.8 86.7 88.3 95.0 95.0 95.6 97.8 57.2 200 37.2 GF 23.3 24.4 37.2 60.6 68.3 72.8 75.6 82.8 86.7 88.3 95.6 95.6 96.1 99.4 37.2 57.2 100 | 23.3 24.4 37.2 60.6 68.3 72.8 75.6 82.0 86.7 P8.3 95.6 95.6 96.1 100.0 57.2 60.6 GE 000, 21.1 24.4 37.2 37.2 68.3 72.8 75.6 82.8 86.7 88.3 95.6 95.6 96.1 100.0 

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90 STATION NAME: CAMP CASEY/TONGDUCHON KO STATION NUMBER: 471066 LST TO JTC: - 9 MONTH: MAY HOURS: 09-11 CEILING VISIBILITY IN METERS GE GE GE GE GE GΕ GE GE GE GE GE TN GE GE GE 112 90 80 40 32 24 20 16 12 10 08 06 04 00 FEET 60 48 NO CELL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 8000 GE 700C GE 6000 59.2 59.2 59.2 59.2 59.2 59.2 59.2 GE 5000 25.8 25.8 42.5 42.5 54.2 56.7 56.3 59.2 59.2 GE 4500 27.5 28.3 45.8 45.8 57.5 60.0 61.7 62.5 62.5 62.5 62.5 62.5 62.5 62.5 62.5 62.5 GE 4000 27.5 28.3 45.8 45.8 60.8 63.3 65.0 66.7 66.7 66.7 66.7 66.7 66.7 66.7 66.7 66.7 68.3 68.3 68.3 68.3 GE 3500 46.7 62.5 66.7 68.3 68.3 68.3 68.3 68.3 27.5 28.3 46.7 65.0 GE 3000 33.3 34.2 54.2 54.2 72.5 75.0 76.7 79.2 79.2 79.2 79.2 79.2 79.2 79.2 79.2 79.2 81.7 GF. 34.2 55.0 55.0 75.0 77.5 79.2 81.7 81.7 81.7 81.7 81.7 81.7 81.7 81.7 2500 33.3 GE 2000 33.3 34.2 55.8 55.8 76.7 80.8 82.5 85.0 85.0 85.0 85.0 85.0 85.0 85.0 85.0 85.0 GE 1800 33.3 34.2 55.8 55.8 76.7 81.7 83.3 85.8 85.8 85.8 85.8 85.8 85.8 90.8 90.8 90.8 GE 1500 34.2 56.7 56.7 80.0 85.0 86.7 90.8 90.8 90.8 90.8 90.8 90.8 33.3 GE 1200 33.3 34.2 56.7 56.7 81.7 87.5 90.0 94.2 94.2 95.0 95.0 95.0 95.0 95.0 95.0 95.0 56.7 56.7 90.8 95.0 95.0 95.8 95.8 95.8 95.8 95.8 95.8 GE 1000 33.3 34.2 82.5 88.3 95.8 GE 900 33.3 34.2 56.7 56.7 82.5 88.3 90.8 95.0 95.0 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 800 33.3 34.2 56.7 90.8 95.0 95.0 97.5 97.5 97.5 97.5 97.5 97.5 56.7 88.3 82. 97.5 95.0 95.0 97.5 97.5 97.5 97.5 97.5 97.5 GE 700 33.3 34.2 56.7 56.7 82.5 88.3 90.8 GE 600 33.3 34.2 56.7 56.7 82.5 88.3 90.8 95.0 95.0 97.5 97.5 97.5 97.5 97.5 97.5 97.5 97.5 GE 500 33.3 34.2 56.7 56.7 82.5 88.3 90.8 95.0 95.0 98.3 98.3 98.3 98.3 98.3 98.3 GE 400 33.3 34.2 56.7 ...7 82.5 88.3 90.8 95.0 95.0 97.5 98.3 98.3 100.0 100.0 100.0 95.0 97.5 56.7 95.0 98.3 98.3 100.0 100.0 100.0 100.0 GE 300 33.3 34.2 56.7 82.5 88.3 90.8 GE 200 33.3 34.2 56.7 56.7 82.5 88.3 90.8 95.0 95.0 97.5 98.3 98.3 100.0 100.0 100.0 100.0 GE 100 33.3 34.2 56.7 56.7 82.5 88.3 90.8 95.0 95.0 97.5 98.3 98.3 100.0 100.0 100.0 100.0 000 33.3 34.2 56.7 56.7 82.5 90.8 95.0 95.0 97.5 98.3 98.3 100.0 100.0 100.0 100.0

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAY HOURS: 12-14

| CEI      | LING           | • • • • • • • |              |              | • • • • • • • | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | VISIBIL:     | TY IN I      | METERS        |              |              | •••••         | • • • • • •  | •••••        | • • • • • • • | • • • • • •  | •••••        |
|----------|----------------|---------------|--------------|--------------|---------------|---|--------------|--------------|---------------|--------------|--------------|---------------|--------------|--------------|---------------|--------------|--------------|
| 1        | N.             | GE            | GE           | GE           | GE            | GE                                      | GE           | GE           | GE            | GE           | GE           | GE            | GE           | GE           | GE            | GE           | GE           |
| FE       | ET             | 112           | 90           | 80           | 60            | 48                                      | 40           | 32           | 24            | 20           | 16           | 12            | 10           | 08           | 06            | 04           | 00           |
| • • •    |                |               |              | • • • • • •  | • • • • • • • |   |              |              | • • • • • • • |              |              | • • • • • • • |              | • • • • • •  | •••••         |              | • • • • • •  |
| NO       | CEIL           |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
|          |                |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
|          | 20000          |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
|          | 18000          |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
|          | 16000          |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
|          | 14000<br>12000 |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
| GE       | 12000          |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
| GE       | 10000          |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
| GE       | 9000           |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
| GE       | 8000           |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
| GE       | 7000           |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
| GE       | 6000           |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
| GE       | 5000           | 35.0          | 36.1         | 51.1         | 51.1          | 60.0                                    | 62.2         | 63.3         | 63.3          | 63.3         | 63.3         | 63.3          | 63.3         | 63.3         | 63.3          | 63.3         | 63.3         |
| GE       | 4500           | 38.3          | 39.4         | 54.4         | 54.4          | 63.3                                    | 65.6         | 66.7         | 66.7          | 66.7         | 66.7         | 66.7          | 66.7         | 66.7         | 66.7          | 66.7         | 66.7         |
| GE       | 4000           | 40.0          | 41.1         | 57.8         | 57.8          | 67.2                                    | 69.4         | 70.6         | 70.6          | 70.6         | 70.6         | 70.6          | 70.6         | 70.6         | 70.6          | 70.6         | 70.6         |
| GE       | 3500           | 43.3          | 44.4         | 63.3         | 63.3          | 73.3                                    | 75.6         | 77.2         | 77.2          | 77.2         | 77.2         | 77.2          | 77.2         | 77.2         | 77.2          | 77.2         | 77.2         |
| GE       | 3000           | 48.3          | 51.1         | 71.7         | 71.7          | 82.8                                    | 85.0         | 86.7         | 86.7          | 86.7         | 86.7         | 86.7          | 86.7         | 86.7         | 86.7          | 86.7         | 86.7         |
|          |                |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
| GE       | 2500           | 48.3          | 51.1         | 71.7         | 71.7          | 83.3                                    | 85.6         | 87.2         | 87.2          | 87.2         | 87.2         | 87.2          | 87.2         | 87.2         | 87.2          | 87.2         | 87.2         |
| GE<br>GE | 2000<br>1800   | 48.3<br>48.3  | 51.1<br>51.1 | 71.7<br>71.7 | 71.7<br>71.7  | 84.4<br>84.4                            | 86.7<br>86.7 | 88.3<br>88.3 | 88.3<br>88.3  | 88.3<br>88.3 | 88.3<br>88.3 | 88.3<br>88.3  | 88.3<br>88.3 | 88.3<br>88.3 | 88.3<br>88.3  | 88.3<br>88.3 | 88.3<br>88.3 |
| GE       | 1500           | 49.4          | 52.8         | 73.9         | 73.9          | 87.8                                    | 90.0         | 92.2         | 92.2          | 92.2         | 92.2         | 92.2          | 92.2         | 92.2         | 92.2          | 92.2         | 92.2         |
| GE       | 1200           | 50.6          | 53.9         | 75.0         | 75.0          | 89.4                                    | 92.2         | 94.4         | 94.4          | 94.4         | 95.6         | 95.6          | 95.6         | 95.6         | 95.6          | 95.6         | 95.6         |
|          |                |               |              |              |               |   |              |              |               |              |              |               |              |              |               |              |              |
| GE       | 1000           | 50.6          | 53.9         | 75.0         | 75.0          | 90.6                                    | 93.3         | 96.1         | 96.7          | 97.2         | 98.3         | 98.9          | 98.9         | 98.9         | 98.9          | 98.9         | 98.9         |
| GE       | 900            | 50.6          | 53.9         | 75.0         | 75.0          | 90.6                                    | 93.3         | 96.1         | 97.2          | 97.8         | 98.9         | 99.4          | 99.4         | 99.4         | 99.4          | 99.4         | 99.4         |
| GE       | 800            | 50.6          | 53.9         | 75.0         | 75.0          | 90.6                                    | 93.3         | 96.1         | 97.2          | 97.8         | 98.9         | 99.4          | 99.4         | 99.4         | 99.4          | 99.4         | 99.4         |
| GE       | 700            | 50.6          | 53.9         | 75.0         | 75.0          | 90.6                                    | 93.3         | 96.1         | 97.2          | 97.8         | 98.9         | 99.4          | 99.4         | 99.4         | 99.4          | 99.4         | 99.4         |
| GE       | 600            | 50.6          | 53.9         | 75.0         | 75.0          | 90.6                                    | 93.3         | 96.1         | 97.2          | 97.8         | 99.4         | 100.0         | 100.0        | 100.0        | 100.0         | 100.0        | 100.0        |
| GE       | 500            | 50.6          | 53.9         | 75.0         | 75.0          | 90.6                                    | 93.3         | 96.1         | 97.2          | 97.8         | 99.4         | 100.0         | 100.0        | 100.0        | 100.0         | 100.0        | 100.0        |
| GE       | 400            | 50.6          | 53.9         | 75.0         | 75.0          | 90.6                                    | 93.3         | 96.1         | 97.2          | 97.8         | 99.4         | 100.0         | 100.0        | 100.0        | 100.0         | 100.0        | 100.0        |
| GE       | 300            | 50.6          | 53.9         | 75.0         | 75.0          | 90.6                                    | 93.3         | 96.1         | 97.2          | 97.8         | 99.4         | 100.0         | 100.0        | 100.0        | 100.0         | 100.0        | 100.0        |
| GE       | 200            | 50.6          | 53.9         | 75.0         | 75.0          | 90.6                                    | 93.3         | 96.1         | 97.2          | 97.8         | 99.4         | 100.0         | 100.0        | 100.0        | 100.0         | 100.0        | 100.0        |
| GE       | 100            | 50.6          | 53.9         | 75.0         | 75.0          | 90.6                                    | 93.3         | 96.1         | 97.2          | 97.8         | 99.4         | 100.0         | 100.0        | 100.0        | 100.0         | 100.0        | 100.0        |
| ar.      | 000            | 50.5          | 53.6         | 75.0         | 7.5           | 00.6                                    | 0.1.1        | 05.          | 07.0          | 07.6         |              | 100.0         | 100.0        | 100.0        |               | 100.5        | 100 -        |
| GE       | 000            | 50.6          | 53.9         | 75.0         | 75.0          | 90.6                                    | 93.3         | 96.1         | 97.2          | 97.8         | 99.4         | 100.0         | 100.0        | 100.0        | 100.0         | 100.0        | 100.0        |
| • • •    |                |               |              |              | • • • • • • • |   |              |              | • • • • • • • |              |              | • • • • • • • |              |              |               |              |              |

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAY HOURS: 15-17 VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 GE 5000 44.1 46.4 65.9 65.9 68.2 68.7 68.7 68.7 68.7 68.7 68.7 68.7 68.7 68.7 68.7 68.7 GΕ 4500 47.5 57.0 67.0 69.3 69.8 69.8 69.8 45.3 69.8 69.8 69.8 69.8 69.8 69.8 69.8 69.8 GE 4000 48.6 51.4 71.5 71.5 74.3 74.9 74.9 74.9 74.9 74.9 74.9 74.9 74.9 74.9 74.9 74.9 GΕ 3500 49.2 52.0 73.2 76.0 76.5 76.5 73.2 76.5 76.5 76.5 76.5 76.5 76.5 76.5 76.5 76.5 GE 3000 55.3 79.3 85.5 52.5 79.3 84.9 85.5 87.2 87.2 87.2 87.7 87.7 87.7 87.7 87.7 27.7 79.3 GE 2500 52.5 55.3 79.3 84.9 85.5 85.5 87.2 87.2 87.2 88.3 88.3 88.3 88.3 88.3 88.3 2000 58.1 82.1 87.7 88.3 88.8 GE 55.3 82.1 90.5 90.5 90.5 91.6 91.6 91.6 91.6 91.6 91.6 GE 1800 55.3 58.1 82.1 82.1 87.7 88.3 88.8 90.5 90.5 90.5 91.6 91.6 91.6 91.6 91.6 91.6 GE 1500 57.0 59.8 83.8 83.8 89.4 89.9 91.6 93.3 93.3 93.3 94.4 94.4 94.4 94.4 94.4 94.4 GE 1200 57.0 59.8 83.8 83.8 89.4 89.9 91.6 93.3 93.3 93.3 94.4 94.4 94.4 94.4 94.4 94.4 GE 1000 58.1 60.9 84.9 92.7 93.3 96.6 99.4 84.9 98.3 98.3 98.3 99.4 100.0 100.0 100.0 100.0 GE 900 58.1 60.9 84.9 84.9 92.7 93.3 96.6 98.3 98.3 98.3 99.4 99.4 100.0 100.0 100.0 100.0 60.9 GE 800 58.1 84.9 84.9 92.7 93.3 96.6 98.3 98.3 98.3 99.4 99.4 100.0 100.0 100.0 100.0 GE 700 58.1 60.9 84.9 84.9 92.7 93.3 96.6 98.3 98.3 98.3 99.4 99.4 100.0 100.0 100.0 100.0 GΕ 600 58.1 60.9 84.9 84.9 92.7 93.3 96.6 98.3 98.3 98.3 99.4 99.4 100.0 100.0 100.0 100.0 GE 500 58.1 60.9 84.9 84.9 92.7 93.3 96.6 98.3 98.3 98.3 99.4 99.4 100.0 100.0 100.0 100.0 GΕ 58.1 60.9 84.9 92.7 93.3 96.6 99.4 400 84.9 98.3 98.3 98.3 99.4 100.0 100.0 100.0 100.0 GE 60.9 84.9 93.3 96.6 300 58.1 84.9 92.7 98.3 99.4 99.4 100.0 100.0 98.3 98.3 100.0 100.0 GE 200 58.1 60.9 84.9 84.9 92.7 93.3 96.6 98.3 98.3 98.3 99.4 99.4 100.0 100.0 100.0 100.0 100 58.1 60.9 84.9 92.7 93.3 96.6 98.3 99.4 100.0 100.0 98.3 98.3 99.4 100.0 100.0 GΕ 000 58.1 60.9 84.9 84.9 92.7 93.3 96.6 98.3 98.3 98.3 99.4 99.4 100.0 100.0 100.0 100.0

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAY HOURS: 18-20

|               |        |               | LST           | TO UTC        | : - 9 |                   |             |               |               | MONTH: | MAY   | HOURS:    | 18-20 |               |       |             |
|---------------|--------|---------------|---------------|---------------|-------|-------------------|-------------|---------------|---------------|--------|-------|-----------|-------|---------------|-------|-------------|
| CEILING       |        | • • • • • • • | • • • • • •   | • • • • • • • |       | ······<br>VISIBIL |             |               | • • • • • • • |        |       | • • • • • |       |               | ••••• | • • • • • • |
| IN            | ( GE   | GE            | GE            | GE            | GE    | GE<br>GE          | GE          | GE            | GE            | GE     | GE    | GE        | GE    | GE            | GE    | GE          |
| FEET          | 112    | 90            | 80            | 60            | 48    | 40                | 32          | 24            | 20            | 16     | 12    | 10        | 08    | 06            | 04    | 00          |
| L DE 1        | 112    | 90            | 80            | 00            | 40    | 40                | 32          | 24            | 20            | 10     | 12    | 10        | 00    | 00            | 04    | 00          |
| •••••         |        |               | • • • • • • • | · • · • · • • |       | • • • • • •       | • • • • • • | • • • • • • • | • • • • • •   |        |       |           |       | • • • • • • • |       | • • • • • • |
| NO CEIL       |        |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| NO CELE       |        |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 2000       | ,      |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 1800       | l l    |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 1600       | l l    |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 1400       |        |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 1200       | 1      |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
|               |        |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 1000       |        |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 900        | o      |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 800        | o      |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 700        | o      |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 600        | o      |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
|               | ļ      |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 500        | 45.0   | 46.7          | 66.1          | 66.1          | 70.0  | 71.1              | 71.1        | 71.1          | 71.1          | 71.1   | 71.1  | 71.1      | 71.1  | 71.1          | 71.1  | 71.1        |
| GE 450        | 45.6   | 47.8          | 67.2          | 67.2          | 71.1  | 72.2              | 72.2        | 72.2          | 72.2          | 72.2   | 72.2  | 72.2      | 72.2  | 72.2          | 72.2  | 72.2        |
| GE 400        | 46.1   | 48.3          | 68.3          | 68.3          | 72.2  | 73.3              | 73.3        | 73.3          | 73.3          | 73.3   | 73.3  | 73.3      | 73.3  | 73.3          | 73.3  | 73.3        |
| GE 350        | 47.2   | 49.4          | 71.7          | 71.7          | 77.2  | 78.3              | 78.3        | 78.3          | 78.3          | 78.3   | 78.3  | 78.3      | 78.3  | 78.3          | 78.3  | 78.3        |
| GE 300        | 52.2   | 54.4          | 77.8          | 77.8          | 83.3  | 84.4              | 84.4        | 85.6          | 86.1          | 86.1   | 86.1  | 86.1      | 86.1  | 86.1          | 86.1  | 86.1        |
|               |        |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 250        |        | 54.4          | 78.3          | 78.3          | 83.9  | 86.1              | 86.7        | 87.8          | 88.3          | 88.3   | 88.3  | 88.3      | 88.3  | 88.3          | 88.3  | 88.3        |
| GE 200        |        | 56.7          | 81.7          | 81.7          | 87.8  | 90.0              | 91.1        | 92.2          | 92.8          | 92.8   | 92.8  | 92.8      | 92.8  | 92.8          | 92.8  | 92.8        |
| GE 180        |        | 56.7          | 81.7          | 81.7          | 87.8  | 90.0              | 91.1        | 92.2          | 92.8          | 92.8   | 92.8  | 92.8      | 92.8  | 92.8          | 92.8  | 92.8        |
| GE 150        | 1      | 56.7          | 81.7          | 81.7          | 88.3  | 90.6              | 91.7        | 92.8          | 93.3          | 93.3   | 93.3  | 93.3      | 93.3  | 93.3          | 93.3  | 93.3        |
| GE 120        | 54.4   | 56.7          | 81.7          | 81.7          | 90.0  | 92.2              | 93.3        | 94.4          | 95.0          | 95.0   | 95.0  | 95.0      | 95.0  | 95.0          | 95.0  | 95.0        |
|               |        |               |               |               |       |                   |             |               |               |        |       |           |       |               |       |             |
| GE 100        |        | 56.7          | 82.2          | 82.2          | 92.2  | 95.0              | 96.1        | 97.2          | 97.8          | 97.8   | 97.8  | 97.8      | 97.8  | 97.8          | 97.8  | 97.8        |
| GE 90         | 1      | 56.7          | 82.2          | 82.2          | 92.2  | 95.0              | 96          | 98.3          | 98.9          | 98.9   | 98.9  | 98.9      | 98.9  | 98.9          | 98.9  | 98.9        |
| GE 80         | 1      | 56.7          | 82.2          | 82.2          | 92.2  | 95.0              | 96.1        | 98.3          | 98.9          | 98.9   | 98.9  | 98.9      | 98.9  | 98.9          | 98.9  | 98.9        |
| GE 70         | ł      | 56.7          | 82.2          | 82.2          | 92.2  | 95.0              | 96.1        | 98.3          | 98.9          | 98.9   | 98.9  | 98.9      | 98.9  | 98.9          | 98.9  | 98.9        |
| GE 60         | 54.4   | 56.7          | 82.2          | 82.2          | 92.2  | 95.0              | 96.1        | 98.3          | 99.4          | 99.4   | 100.0 | 100.0     | 100.0 | 100.0         | 100.0 | 100.0       |
| an 60         |        |               |               |               |       |                   |             |               |               |        |       |           | 400 0 |               |       |             |
| GE 50         |        | 56.7          | 82.2          | 82.2          | 92.2  | 95.0              | 96.1        | 98.3          | 99.4          | 99.4   | 100.0 | 100.0     | 100.0 | 100.0         | 100.0 | 100.0       |
| GE 40         |        | 56.7          | 82.2          | 82.2          | 92.2  | 95.0              | 96.1        | 98.3          | 99.4          | 99.4   | 100.0 | 100.0     | 100.0 | 100.0         | 100.0 | 100.0       |
| GE 30         | 1      | 56.7<br>56.7  | 82.2          | 82.2          | 92.2  | 95.0              | 96.1        | 98.3          | 99.4          | 99.4   | 100.0 | 100.0     | 100.0 | 100.0         | 100.0 | 100.0       |
| GE 201        | 1      |               | 82.2          | 82.2          | 92.2  | 95.0              | 96.1        | 98.3          | 99.4          | 99.4   | 100.0 | 100.0     | 100.0 | 100.0         | 100.0 | 100.0       |
| GE 10         | 54.4   | 56.7          | 82.2          | 82.2          | 92.2  | 95.0              | 96.1        | 98.3          | 99.4          | 99.4   | 100.0 | 100.0     | 100.0 | 100.0         | 100.0 | 100.0       |
| GE 00         | 54.4   | 56.7          | 82.2          | 82.2          | 92.2  | 95.0              | 96.1        | 98.3          | 99.4          | 99.4   | 100.0 | 100.0     | 100.0 | 100 0         | 100.0 | 100.0       |
| GE 001        | 1 34.4 | 30.7          | 02.2          | 02.2          | 72.2  | 95.0              | 90.1        | 90.3          | 99.4          | 99.4   | 100.0 | 100.0     | 100.0 | 100.0         | 100.0 | 100.0       |
| • • • • • • • |        | • • • • • • • |               | • • • • • •   |       | • • • • • • •     |             | • • • • • • • | • • • • • • • |        |       |           |       | • • • • • • • |       | • • • • • • |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAY HOURS: 21-23

| CEL      | <br>LING  | • • • • • • • | • • • • • •  |              | • • • • • •  | ,            | VISIBIL      | TTY IN       | METERS       | • • • • • •  |              |       | • • • • • • |              | • • • • • • • | • • • • • • • | • • • • • •  |
|----------|-----------|---------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|-------|-------------|--------------|---------------|---------------|--------------|
| I        |           | GE            | GE           | GE           | GE           | GE           | GE           | GE           | GE           | GE           | GE           | GE    | GE          | GE           | GE            | GE            | GE           |
| FE       |           | 112           | 90           | 80           | 60           | 48           | 40           | 32           | 24           | 20           | 16           | 12    | 10          | 08           | 06            | 04            | 00           |
|          |           |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| •••      |           |               |              |              |              |              |              |              |              |              |              | ••••• |             |              |               |               |              |
| NO I     | CEIL      |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
|          |           |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| GE :     | 20000     |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| GE       | 18000     |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| GE       | 16000     |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| GE .     | 14000     |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| GE       | 12000     |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
|          |           |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
|          | 10000     |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| GE       | 9000      |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| GĒ       | 8000      |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| GE       | 7000      |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| GE       | 6000      |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| an       | 5000      | 24.0          | 35.0         | 56.0         | 56.0         | 63 E         |              | 65.2         | <i>cc</i> 0  | 66.0         | 56.0         | 66.9  | 66.9        | 66.0         | 66.0          | <i>ce</i> 0   | 66.0         |
| GE<br>GE | 4500      | 34.8<br>35.9  | 35.9<br>37.6 | 56.9<br>58.6 | 56.9<br>58.6 | 63.5<br>65.2 | 64.6<br>66.3 | 65.2<br>66.9 | 66.9<br>68.5 | 66.9<br>68.5 | 66.9<br>68.5 | 68.5  | 68.5        | 66.9<br>68.5 | 66.9<br>68.5  | 66.9<br>68.5  | 66.9<br>68.5 |
| GE       | 4000      | 37.6          | 39.2         | 61.9         | 61.9         | 68.5         | 69.6         | 70.2         | 71.8         | 71.8         | 71.8         | 71.8  | 71.8        | 71.8         | 71.8          | 71.8          | 71.8         |
| GE       | 3500      | 37.6          | 39.2         | 63.0         | 63.0         | 74.0         | 75.1         | 75.7         | 77.3         | 77.3         | 77.3         | 77.3  | 77.3        | 77.3         | 77.3          | 77.3          | 77.3         |
| GE       | 3000      | 40.9          | 42.5         | 66.3         | 66.3         | 80.1         | 81.2         | 81.8         | 84.5         | 84.5         | 85.1         | 85.1  | 85.1        | 85.1         | 85.1          | 85.1          | 85.1         |
|          |           |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| GE       | 2500      | 42.0          | 43.6         | 67.4         | 67.4         | 81.2         | 84.0         | 85.1         | 87.8         | 87.8         | 88.4         | 88.4  | 88.4        | 88.4         | 88.4          | 88.4          | 88.4         |
| GE       | 2000      | 42.5          | 44.2         | 68.5         | 68.5         | 84.0         | 86.7         | 87.8         | 90.6         | 90.6         | 91.2         | 91.2  | 91.2        | 91.2         | 91.2          | 91.2          | 91.2         |
| GE       | 1800      | 42.5          | 44.2         | 68.5         | 68.5         | 84.0         | 86.7         | 87.8         | 91.7         | 91.7         | 92.3         | 92.3  | 92.3        | 92.3         | 92.3          | 92.3          | 92.3         |
| GE       | 1500      | 42.5          | 44.2         | 69.1         | 69.1         | 84.5         | 87.3         | 88.4         | 92.3         | 92.3         | 92.8         | 92.8  | 92.8        | 92.8         | 92.8          | 92.8          | 92.8         |
| GE       | 1200      | 42.5          | 44.2         | 69.1         | 69.1         | 86.7         | 89.5         | 90.6         | 94.5         | 94.5         | 95.0         | 95.0  | 95.0        | 95.0         | 95.0          | 95.0          | 95.0         |
|          |           |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
| GE       | 1000      | 42.5          | 44.2         | 69.1         | 69.1         | 89.0         | 91.7         | 93.9         | 97.8         | 97.8         | 98.3         | 98.3  | 98.3        | 98.3         | 98.3          | 98.3          | 98.3         |
| GE       | 900       | 42.5          | 44.2         | 69.1         | 69.1         | 89.0         | 91.7         | 93.9         | 98.9         | 99.4         | 100.0        | 100.0 | 100.0       | 100.0        | 100.0         | 100.0         | 100.0        |
| GE       | 800       | 42.5          | 44.2         | 69.1         | 69.1         | 89.0         | 91.7         | 93.9         | 98.9         | 99.4         | 100.0        | 100.0 | 100.0       | 100.0        | 100.0         | 100.0         | 100.0        |
| GE       | 700       | 42.5          | 44.2         | 69.1         | 69.1         | 89.0         | 91.7         | 93.9         | 98.9         | 99.4         | 100.0        | 100.0 | 100.0       | 100.0        | 100.0         | 100.0         | 100.0        |
| GE       | 600       | 42.5          | 44.2         | 69.1         | 69.1         | 89.0         | 91.7         | 93.9         | 98.9         | 99.4         | 100.0        | 100.0 | 100.0       | 100.0        | 100.0         | 100.0         | 100.0        |
| GE       | 500       | 42.5          | 44.2         | 69.1         | 69.1         | 89.0         | 91.7         | 93.9         | 98.9         | 99.4         | 100.0        | 100.0 | 100.0       | 100.0        | 100.0         | 100.0         | 100.0        |
| GE       | 400       | 42.5          | 44.2         | 69.1         | 69.1         | 89.0         | 91.7         | 93.9         | 98.9         | 99.4         | 100.0        | 100.0 | 100.0       | 100.0        | 100.0         | 100.0         | 100.0        |
| GE       | 300       | 42.5          | 44.2         | 69.1         | 69.1         | 89.0         | 91.7         | 93.9         | 98.9         | 99.4         | 100.0        | 100.0 | 100.0       | 100.0        | 100.0         | 100.0         | 100.0        |
| GE       | 200       | 42.5          | 44.2         | 69.1         | 69.1         | 89.0         | 91.7         | 93.9         | 98.9         | 99.4         | 100.0        | 100.0 | 100.0       | 100.0        | 100.0         | 100.0         | 100.0        |
| GE       | 100       | 42.5          | 44.2         | 69.1         | 69.1         | 89.0         | 91.7         | 93.9         | 98.9         | 99.4         | 100.0        | 100.0 | 100.0       | 100.0        | 100.0         | 100.0         | 100.0        |
| 35       | 100       | 42.3          | 77.6         | 02.1         | 05.1         | 05.0         | 32.47        | 23.3         | ,0.,         | 22.4         | 100.0        | 100.0 | 100.0       | 100.0        | 100.0         | 100.0         | 100.0        |
| GE       | 000       | 42.5          | 44.2         | 69.1         | 69.1         | 89.0         | 91.7         | 93.9         | 98.9         | 99.4         | 100.0        | 100.0 | 100.0       | 100.0        | 100.0         | 100.0         | 100.0        |
|          | • • • • • |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |
|          |           |               |              |              |              |              |              |              |              |              |              |       |             |              |               |               |              |

#### PERCENTAGE PREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: MAY HOURS: ALL

| CET   | <br>LING  | • • • • • •   | • • • • • • |      | • • • • • • • |       | <br>VISIBILI | TV IN 1 |               | • • • • • • |      | • • • • • • |      | • • • • • • |      | • • • • • • | • • • • • |
|-------|-----------|---------------|-------------|------|---------------|-------|--------------|---------|---------------|-------------|------|-------------|------|-------------|------|-------------|-----------|
| I     |           | GE            | GE          | GE   | GE            | GE    | GE           | GE .    | GE            | GE          | GE   | GE          | GE   | GE          | GE   | GE          | GE        |
| FE    |           | 112           | 90          | 80   | ر ر           | 48    | 40           | 32      | 24            | 20          | 16   | 12          | 10   | 08          | 06   | 04          | 00        |
|       |           |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
|       |           |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| NO    | CEIL      |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE :  | 20000     |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE    | 18000     |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE    | 16000     |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE    | 14000     |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE    | 12000     |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
|       |           |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
|       | 10000     |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE    | 9000      |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE    | 8000      |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE    | 7000      |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE    | 6000      |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE    | 5000      | 31.2          | 32.3        | 49.2 | 49.2          | 57.3  | 59.1         | 60.1    | 60.7          | 60.7        | 61.0 | 61.2        | 61.2 | 61.4        | 61.4 | 61.5        | 61.9      |
| GE    | 4500      | 32.8          | 34.1        | 51.2 | 51.2          | 59.3  | 61.2         | 62.2    | 62.7          | 62.8        | 63.0 | 63.3        | 63.3 | 63.5        | 63.5 | 63.6        | 63.9      |
| GE    | 4000      | 33.9          | 35.3        | 53.3 | 53.3          | 62.8  | 64.6         | 65.6    | 66.2          | 66.2        | 66.5 | 66.7        | 66.7 | 67.0        | 67.0 | 67.0        | 67.4      |
| GE    | 3500      | 35.0          | 36.4        | 55.8 | 55.8          | 66.6  | 68.4         | 69.5    | 70.1          | 70.1        | 70.5 | 70.7        | 70.7 | 70.9        | 70.9 | 71.0        | 71.4      |
| GE    | 3000      | 38.8          | 40.5        | 61.2 | 61.2          | 73.8  | 75.6         | 76.7    | 78.0          | 78.1        | 78.6 | 78.9        | 78.9 | 79.1        | 79.1 | 79.2        | 79.6      |
|       | 3000      |               |             |      | -2.0          | , , , | , , , ,      |         |               |             |      |             |      |             |      |             |           |
| GE    | 2500      | 39.0          | 40.7        | 61.6 | 61.6          | 74.9  | 77.2         | 78.8    | 80.0          | 80.1        | 80.6 | 81.0        | 81.3 | 81.2        | 81.2 | 81.3        | 81.7      |
| GE    | 2000      | 39.7          | 41.4        | 62.7 | 62.7          | 76.7  | 79.2         | 80.9    | 82.2          | 82.3        | 82.8 | 83.2        | 83.2 | 83.4        | 83.4 | 83.5        | 83.8      |
| GE    | 1800      | 39.7          | 41.4        | 62.8 | 62.8          | 77.2  | 79.9         | 81.6    | 83.0          | 83.2        | 83.7 | 84.1        | 84.1 | 84.4        | 84.4 | 84.5        | 84.9      |
| GE    | 1500      | 40.2          | 42.0        | 63.8 | 63.8          | 79.7  | 82.4         | 85.5    | 87.0          | 87.4        | 88.0 | 38.4        | 88.5 | 88.8        | 88.8 | 88.8        | 89.2      |
| GE    | 1200      | 40.6          | 42.3        | 64.3 | 64.3          | 81.7  | 84.9         | 88.3    | 89.9          | 90.4        | 91.3 | 91.7        | 91.8 | 92.1        | 92.1 | 92.2        | 92.5      |
|       |           |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE    | 1000      | 40.7          | 42.5        | 64.6 | 64.6          | 83.1  | 86.3         | 90.4    | 92.2          | 92.8        | 93.8 | 94.4        | 94.6 | 94.9        | 94.9 | 95.0        | 95.4      |
| GE    | 900       | 40.7          | 42.5        | 64.6 | 64.6          | 83.1  | 86.4         | 90.4    | 92.6          | 93.4        | 94.4 | 95.1        | 95.3 | 95.7        | 95.7 | 95.7        | 96.1      |
| GE    | 800       | 40.7          | 42.5        | 64.6 | 64.6          | 83.1  | 86.4         | 90.4    | 92.6          | 93.4        | 94.7 | 95.4        | 95.7 | 96.2        | 96.2 | 96.3        | 96.7      |
| GE    | 700       | 40.7          | 42.5        | 64.6 | 64.6          | 83.1  | 86.4         | 90.4    | 92.7          | 93.5        | 94.8 | 95.5        | 95.7 | 96.3        | 96.3 | 96.4        | 96.7      |
| GΕ    | 600       | 40.7          | 42.5        | 64.6 | 64.6          | 83.1  | 86.4         | 90.4    | 92.7          | 93.6        | 95.3 | 96.2        | 96.4 | 97.1        | 97.1 | 97.2        | 97.5      |
|       |           |               |             |      |               |       |              |         |               |             |      |             |      |             |      |             |           |
| GE    | 500       | 40.7          | 42.5        | 64.6 | 64.6          | 83.1  | 86.4         | 90.4    | 92.7          | 93.6        | 95.3 | 96.3        | 96.5 | 97.2        | 97.2 | 97.3        | 97.7      |
| GE    | 400       | 40.7          | 42.5        | 64.6 | 64.6          | 83.1  | 86.4         | 90.7    | 93.0          | 94.0        | 95.7 | 96.7        | 97.0 | 98.0        | 98.0 | 98.1        | 98.5      |
| GE    | 300       | 40.7          | 42.5        | 64.6 | 64.6          | 83.1  | 86.4         | 90.7    | 93.1          | 94.1        | 95.7 | 96.8        | 97.1 | 98.6        | 98.7 | 98.8        | 99.2      |
| GE    | 200       | 40.7          | 42.5        | 64.6 | 64.6          | 83.1  | 86.4         | 90.7    | 93.1          | 94.1        | 95.8 | 96.9        | 97.2 | 98.8        | 98.8 | 98.9        | 99.6      |
| GE    | 100       | 40.7          | 42.5        | 64.6 | 64.6          | 83.1  | 86.4         | 90.7    | 93.1          | 94.1        | 95.8 | 96.9        | 97.2 | 98.8        | 98.8 | 99.0        | 100.0     |
| GE    | 000       | 40.7          | 42.5        | 64.6 | 64.6          | 83.1  | 86.4         | ĵ₀.7    | 93.1          | 94.1        | 95.8 | 96.9        | 97.2 | 98.8        | 98.8 | 99.0        | 100.0     |
| GE    | 000       | 40.7          | 42.0        | 04.0 | 04.0          | 03.1  | 50.4         | 50.7    | 93.1          | 34.1        | 33.0 | 30.3        | 31.4 | 30.0        | 30.0 | 33.0        | 100.0     |
| • • • | • • • • • | • • • • • • • |             |      | • • • • • • • |       |              |         | • • • • • • • |             |      |             |      |             |      |             |           |

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUN HOURS: 00-02 ....... VISIBILITY IN METERS IN GE GE GΕ GE GE GE GE GE GE GE GE GE GΕ GE GE GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GΕ 6000 GE 5000 22.2 22.2 37.8 37.8 51.1 52.2 54.4 55.6 56.7 58.9 60.0 60.0 60.0 60.0 60.0 60.0 GE 22.2 22.2 38.9 38.9 52.2 53.3 55.6 56.7 57.8 60.0 61.1 61.1 61.1 61.1 61.1 61.1 4500 67.8 68.9 68.9 68.9 GE 4000 26.1 26.7 43.3 43.3 57.8 60.6 63.3 64.4 65.6 68.9 68.9 68.9 72.2 72.2 72.2 72.2 72.2 72.2 GE 3500 26.1 26.7 43.3 43.3 57.8 63.3 66.7 67.8 68.9 71.1 3000 27.2 27.8 62.8 69.4 73.9 75.6 77.2 79.4 80.6 80.6 80.6 80.6 80.6 80.6 GE 44.4 44.4 GE 2500 27.2 27.8 44.4 44.4 62.8 69.4 73.9 75.6 77.2 80.0 81.1 81.1 81.1 81.1 81.1 81.1 GE 2000 27.2 27.8 45.6 45.6 64.4 71.1 78.3 0.08 81.7 84.4 85.6 85.6 85.6 85.6 85.6 85.6 85.0 86.1 86.1 86.1 86.1 86.1 86.1 27.2 27.8 45.6 45.6 64.4 71.1 78.9 82.2 ЗE 1800 80.6 GΕ 1500 27.2 27.8 45.6 45.6 64.4 72.8 81.7 85.0 86.7 89.4 90.6 90.6 90.6 90.6 90.6 90.6 GE 1200 27.2 27.8 45.6 45.6 66.1 74.4 83.3 86.7 88.3 92.8 94.4 94.4 94.4 94.4 94.4 94.4 1000 27.2 27.8 45.6 45.6 66.1 74.4 83.3 87.2 90.6 95.0 96.7 96.7 96.7 96.7 96.7 96.7 GΕ 900 27.2 27.9 74.4 83.3 87.2 90.6 95.0 96.7 96.7 96.7 96.7 96.7 96.7 GE 45.6 45.6 66.1 GE 800 27.2 27.8 45.6 45.6 66.1 74.4 83.3 88.3 91.7 96.1 98.3 98.3 98.3 98.3 98.3 98.3 GE 700 27.2 27.8 45.6 45.6 66.1 74.4 83.3 88.3 91.7 96.1 98.3 98.3 98.3 98.3 98.3 98.3 91.7 98.3 98.3 98.3 98.3 74.4 83.3 88.3 96.1 98.3 98.3 GE 600 27.2 27.8 45.6 45.6 66.1 500 27.2 27.8 45.6 74.4 83.3 91.7 100.0 100.0 100.0 100.0 100.0 100.0 GE 45.6 66.1 88.3 96.1 96.1 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 27.2 27.8 45.6 45.6 66.1 74.4 83.3 88.3 91.7 45.6 GΕ 300 27.2 27.8 45.6 66.1 74.4 83.3 88.3 91.7 96.1 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 27.2 27.8 45.6 45.6 66.1 74.4 83.3 88.3 91.7 96.1 88.3 GE 100 27.2 27.8 45.6 45.6 66.1 74.4 83.3 91.7 96.1 100.0 100.0 100.0 100.0 100.0 100.0 000 27.2 27.8 45.6 74.4 GE 45.6 66.1 83.3 88.3 91.7 96.1 100.0 100.0 100.0 100.0 100.0 100.0

### FERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: JUN HOURS: 03-05 LST TO UTC: - 9 VISIDILITY IN METERS CEILING IN GE GE GE GE GE GE' GE GE GE GE GE GE CE GE GE GE 48 32 24 20 12 10 08 06 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 20.0 37.2 37.2 47.8 49.4 52.8 59.4 59.4 59.4 60.0 60.0 GΕ 5000 20.0 51.1 52.8 60.0 60.0 GE 4500 21.1 21.1 39.4 39.4 50.0 51.7 53.3 55.0 55.0 61.7 61.7 61.7 62.2 62.2 62.2 62.2 GE 4000 22.2 22.2 41.7 41.7 52.2 55.6 57.2 58.9 58.9 66.1 66.1 66.1 66.7 66.7 66.7 66.7 GE 3500 22.2 57.2 60.6 67.8 67.8 67.8 68.3 22.2 41.7 52.2 58.9 60.6 68.3 68.3 68.3 41.7 GE 3000 23.3 23.3 42.8 42.8 53.9 60.6 63.9 67.2 67.8 75.0 75.0 75.0 75.6 75.6 75.6 75.6 78.3 23.3 69.4 70.0 77.2 77.8 77.8 78.3 78.3 GE 2500 23.3 42.8 42.8 53.9 60.6 64.4 78.3 GE 2000 23.3 23.3 42.8 42.8 54.4 61.7 66.1 71.1 71.7 80.0 80.6 80.6 81.1 81.1 81.1 81.1 GE 1800 23.3 23.3 54.4 66.1 71.1 71.7 80.0 80.6 80.6 81.1 81.1 81.1 42.8 42.8 61.7 81.1 GE 1500 67.8 82.8 83.3 83.3 83.9 83.9 23.3 23.3 42.8 42.8 55.0 62.2 73.3 74.4 83.9 83.9 GΕ 1200 23.3 23.3 42.8 42.8 55.0 62.8 68.9 75.6 76.7 85.6 86.7 86.7 87.8 87.8 87.8 87.8 GE 1000 23.3 23.3 42.8 42.8 56.1 63.9 72.2 79.4 82.2 91.7 92.8 92.8 93.9 93.9 93.9 93.9 GE 900 23.3 23.3 42.8 42.8 56.1 63.9 72.2 79.4 82.2 91.7 92.8 92.8 93.9 93.9 93.9 93.9 93.3 94.4 94.4 95.6 95.6 95.6 95.6 GE 800 23.3 23.3 42.R 42.8 56.1 63.9 72.2 80.0 83.3 GE 700 23.3 23.3 42.8 42.8 56.1 63.9 72.2 80.0 83.3 93.3 94.4 94.4 95.6 95.6 95.6 95.6 Œ 600 23.3 23.3 42.8 56.1 63.9 72.2 80.0 83.3 93.3 94.4 94.4 95.6 95.6 96.1 96.7 42.8 GE 500 23.3 23.3 42.8 42.8 56.1 63.9 72.2 80.6 83.9 93.9 96.1 96.1 98.3 98.3 98.9 99.4 GE 400 23.3 93.9 96.1 96.1 98.3 98.3 98.9 23.3 42.8 42.8 56.1 63.9 72.2 80.6 83.9 99.4 GE 300 23.3 23.3 42.8 42.8 56.1 63.9 72.2 80.6 83.9 93.9 96.1 96.1 98.3 98.3 98.9 99.4 GE 200 23.3 23.3 42.8 42.8 56.1 63.9 72.2 80.6 83.9 93.9 96.1 96.1 98.9 98.9 23.3 100 93.9 96.1 96.1 98.9 98.9 99.4 100.0 GE 21.3 42.8 42.8 56.1 63.9 72.2 80.6 83.9 000 23.3 23.3 42.8 56.1 63.9 72.2 80.6 83.9 93.9 96.1 96.1 98.9 98.9 99.4 100.0 42.8

STATION NUMBER: 471066

#### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: JUN HOURS: 06-08

CEILING VISIBILITY IN METERS GE TN GE GE GE GE GE GE GE GE GE GE CE GF. GE GE GE 112 90 80 60 48 40 32 24 20 16 12 10 08 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GΕ 7000 GE 6000 GΕ 5000 25.6 26.7 40.0 40.0 45.6 47.2 49.4 50.0 50.6 53.9 55.0 55.0 56.1 56.1 56.1 56.7 4500 27.2 28.3 41.7 41.7 47.2 GE 48.9 51.1 51.7 52.2 55.6 56.7 56.7 57.8 57.8 57.8 58.3 GE 4000 27.2 28.3 41.7 41.7 48.3 50.0 52.2 52.8 53.3 56.7 57.8 57.8 58.9 59.4 59.4 60.0 GE 3500 28.3 29.4 43.3 43.3 50.0 51.7 53.9 54.4 55.0 58.3 59.4 59.4 60.6 61.1 61.1 61.7 GE 3000 28.3 29.4 43.3 43.3 51.7 54.4 57.2 57.8 58.3 63.3 67.2 67.2 68.9 69.4 69.4 70.0 GE 2500 28.3 29.4 43.3 43.3 52.8 58.3 59.4 68.3 68.3 70.0 70.6 70.6 55.6 58.9 64.4 71.1 GE 2000 28.3 29.4 43.9 43.9 53.9 57.2 61.7 62.2 63.3 68.3 72.2 72.2 73.9 74.4 74.4 75.0 GE 1800 28.3 29.4 43.9 43.9 54.4 57.8 62.2 62.8 63.9 68.9 72.8 72.8 74.4 75.0 75.0 75.6 GE 1500 28.3 29.4 43.9 43.9 55.0 58.3 62.8 63.3 65.6 70.6 74.4 74.4 76.1 76.7 76.7 77.2 GΕ 1200 28.3 29.4 43.9 43.9 56.7 60.0 68.3 70.6 72.8 77.8 81.7 81.7 83.3 83.9 83.9 84.4 GE 1000 28.3 29.4 13.9 43.9 58.3 61.7 72.2 74.4 76.7 81.7 85.6 85.6 87.2 87.8 87.8 88.3 GE 900 28.3 29.4 43.9 43.9 58.3 61.7 72.2 74.4 76.7 81.7 85.6 85.6 87.2 87.8 87.8 88.3 GE 800 28.3 29.4 43.9 43.9 58.3 72.2 75.0 77.2 86.1 86.1 88.3

STATION NAME: CAMP CASEY/TONGDUCHON KO

61.7

61.7

61.7

61.7

61.7

61.7

61.7

61.7

58.3 61.7

72.2

72.2

72.2

72.2

72.2

72.2

72.2

75.0

75.6

75.6

75.6

75.6

75.6

75.6

72.2 75.6

77.2

78.3

78.3

78.3

78.3

78.3

78.3

78.3

LST TO UTC: - 9

TOTAL NUMBER OF OBSERVATIONS 180

000 28.3 29.4 43.9

GE

GE

GE

GE

GE

GE

GE

GE

700

600

500

400

300

200

100

28.3

28.3

28.3

28.3

28.3

28.3

28.3

29.4

29.4

29.4

29.4

29.4

29.4

29.4

43.9

43.9

43.9

43.9

43.9

43.9

43.9

43.9

43.9

43.9

43.9

43.9

43.9

43.9

43.9

58.3

58.3

58.3

58.3

58.3

58.3

58.3

82.2

82.2

83.3

83.3

84.4

84.4

84.4

84.4

84.4

86.1

87.2

87.8

89.4

90.0

90.0

90.0

86.1

87.2

87.8

90.0

91.1

91.1

91.1

90.0 91.1

88.3

90.6

91.7

93.9

95.6

96.1

96.1

88.9

88.9

92.8

93.9

96.1

97.8

98.3

98.3

96.1 98.3

88.9

88.9

92.8

96.1

97.8

98.3 100.0

98.3 100.0

98.3 100.0

89.4

89.4

93.3

97.8

99.4

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUN HOURS: 09-11 CEILING VISIBILITY IN METERS GE GE GE GE GΕ GE GΕ GE IN GE GE GE GΕ GE GE GΕ 112 90 30 60 48 40 32 24 20 16 12 10 08 06 04 00 FEET NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 59.2 59.2 59.2 59.2 39.2 39.2 48.3 50.8 53.3 56.7 58.3 59.2 59.2 59.2 GE 5000 20.8 21.7 59.2 GΕ 4500 20.8 21.7 39.2 39.2 48.3 50.8 53.3 56.7 58.3 59.2 59.2 59.2 59.2 59.2 59.2 GE 4000 24.2 25.0 42.5 42.5 51.7 54.2 56.7 60.0 61.7 62.5 62.5 62.5 62.5 62.5 65.0 65.0 65.0 26.7 59.2 62.5 64.2 65.0 65.0 65.0 65.0 3500 25.8 44.2 44.2 54.2 56.7 GE. GE 3000 30.0 31.7 50.0 50.0 64.2 67.5 71.7 75.8 77.5 78.3 78.3 78.3 78.3 78.3 78.3 78.3 80.0 80.0 80.0 80.0 31.7 77.5 80.0 80.0 80.0 GE 2500 30.0 50.0 50.0 65.0 69.2 73.3 79.2 GE 2000 30.0 31.7 50.8 50.8 66.7 71.7 75.8 80.0 81.7 82.5 83.3 84.2 84.2 84.2 84.2 84.2 66.7 75.8 82.5 83.3 84.2 84.2 84.2 84.2 1800 30.0 31.7 50.8 50.8 71.7 80.0 81.7 GE 90.0 90.8 90.8 90.8 90.8 90.8 GE 1500 31.7 33.3 52.5 52.5 69.2 75.8 80.0 86.7 88.3 89.2 GE 1200 31.7 52.5 52.5 69.2 80.0 86.7 88.3 89.2 90.0 90.8 90.8 90.8 90.8 90.8 GE 1000 31.7 33.3 52.5 52.5 70.8 77.5 81.7 90.8 93.3 94.2 95.0 95.8 95.8 95.8 95.8 95.8 GE 900 31.7 33.3 52.5 52.5 70.8 77.5 81.7 91.7 94.2 95.0 96.7 97.5 97.5 97.5 97.5 97.5 70.8 95.0 99.2 99.2 99.2 33.3 77.5 81.7 95.8 97.5 99.2 99.2 GE 800 31.7 52.5 52.5 92.5 GE 700 31.7 33.3 52.5 52.5 70.8 77.5 81.7 92.5 95.0 95.8 97.5 99.2 99.2 99.2 99.2 99.2 GE 600 31.7 33.3 52.5 52.5 70.8 77.5 81.7 93.3 95.8 96.7 98.3 100.0 100.0 100.0 100.0 100.0 GE 500 31.7 33.3 52.5 52.5 70.8 77.5 81.7 93.3 95.8 96.7 98.3 100.0 100.0 100.0 100.0 98.3 100.0 100.0 100.0 100.0 400 52.5 52.5 70.8 77.5 81.7 93.3 95.8 96.7 100.0 GE 31.7 33.3 GE 300 31.7 33.3 52.5 52.5 70.8 77.5 81.7 93.3 95.8 96.7 98.3 100.0 100.0 100.0 100.0 100.0 200 31.7 52.5 52.5 70.8 77.5 81.7 93.3 95.8 96.7 98.3 100.0 100.0 100.0 100.0 GΕ 33.3 98.3 100.0 100.0 100.0 100.0 100.0 GE 100 31.7 33.3 52.5 52.5 70.8 77.5 81.7 93.3 95.8 96.7 70.8 77.5 81.7 93.3 000 31.7 33.3 52.5 52.5 95.8 96.7 98.3 100.0 100.0 100.0 100.0 100.0

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUN HOURS: 12-14 ........... CELLING VISIBILITY IN METERS GE IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE 48 32 12 10 FEET 112 90 80 60 40 24 20 16 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 6000 GE GE 5000 18.9 19.4 36.7 36.7 48.9 50.6 52.8 52.8 52.8 52.8 52.8 52.8 52.8 52.8 52.8 52.8 48.9 50.6 52.8 GΕ 4500 18.9 19.4 36.7 36.7 52.8 52.8 52.8 52.8 52.8 52.8 52.8 52.8 52.8 GE 4000 20.6 21.7 42.2 42.2 55.6 57.2 59.4 59.4 59.4 59.4 59.4 59.4 59.4 59.4 59.4 59.4 GE 3500 21.7 22.8 44.4 44.4 57.8 59.4 61.7 61.7 61.7 61.7 61.7 61.7 61.7 61.7 61.7 61.7 GE 3000 78.3 30.6 32.2 57.2 57.2 76.7 80.6 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 84.4 GE 2500 31.1 32.8 57.8 57.8 77.8 80.0 82.2 84.4 84.4 84.4 84.4 84.4 84.4 GE 2000 31.1 32.8 58.9 58.9 79.4 81.7 83.9 87.2 88.3 88.3 28.3 88.3 88.3 88.3 88.3 88.3 GE 1800 31.1 32.8 58.9 58.9 79.4 81.7 83.9 87.8 88.9 88.9 88.9 88.9 88.9 88.9 88.9 88.9 GE 1500 32.8 60.0 60.0 84.4 31.1 87.2 91.1 95.0 96.1 96.1 96.1 96.1 96.1 96.1 96.1 96.1 GE 1200 60.0 31.1 32.8 60.0 84.4 87.2 91.1 96.7 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 GE 1000 60.0 87.8 91.7 31.1 32.8 60.0 85.0 97.8 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 900 GE 32.8 60.0 60.0 87.8 98.9 85.0 91.7 97.8 98.9 98.9 98.9 98.9 98.9 98.9 98.9 31.1 GE 800 31.1 32.8 60.0 60.0 85.0 87.8 91.7 97.8 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GE 700 31.1 32.8 60.0 60.0 85.0 87.8 91.7 97.8 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 600 31.1 32.8 60.0 60.0 85.0 87.8 91.7 97.8 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 31.1 32.8 60.0 60.0 85.0 87.8 91.7 97.8 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 31.1 32.8 60.0 60.0 85.0 87.8 91.7 97.8 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 300 31.1 32.8 60.0 60.0 85.0 87.8 91.7 97.8 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 31.1 32.8 60.0 60.0 85.0 87.8 91.7 97.8 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 100.0 100.0 31.1 32.8 60.0 60.0 85.0 87.8 91.7 97.8 98.9 98.9 100.0 100.0 100.0 100.0 GE 000 31.1 32.8 60.0 60.0 85.0 87.8 91.7 97.8 98.9 98.9 100.0 100.0 100.0 100.0 100.0 

OPERATING LOCATION "A"

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

USAFETAC, ASHEVILLE NC

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUN HOURS: 15-17

| I<br>FE |       | GE<br>112 | GE<br>90 | GE<br>80 | GE<br>60 | GE<br>48 | GE<br>40 | GE<br>32 | GE<br>24 | GE<br>20    | GE<br>16 | GE<br>12 | GE<br>10 | GE<br>08 | GE<br>06 | GE<br>04      | 00    |
|---------|-------|-----------|----------|----------|----------|----------|----------|----------|----------|-------------|----------|----------|----------|----------|----------|---------------|-------|
|         |       |           |          |          |          |          |          |          |          | • • • • • • |          |          |          |          |          | • • • • • • • |       |
| 110     | 0777  |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| NO      | CEIL  |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| GE      | 20000 |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| GE      | 18000 |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| GE      | 16000 |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| GE      | 14000 |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| GE      | 12000 |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| GE      | 10000 |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| GE      | 9000  |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| GE      | 8000  |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| GE      | 7000  |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| GE      | 6000  |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |
| GE      | 5000  | 23.9      | 23.9     | 41.7     | 41.7     | 51.7     | 51.7     | 52.2     | 52.2     | 52.2        | 52.2     | 52.2     | 52.2     | 52.2     | 52.2     | 52.2          | 52.2  |
| GE      | 4500  | 24.4      | 24.4     | 42.2     | 42.2     | 52.2     | 52.2     | 52.8     | 52.8     | 52.8        | 52.8     | 52.8     | 52.8     | 52.8     | 52.8     | 52.8          | 52.8  |
| GE      | 4000  | 31.7      | 31.7     | 51.1     | 51.1     | 61.7     | 61.7     | 62.8     | 62.8     | 62.8        | 62.8     | 62.8     | 62.8     | 62.8     | 62.8     | 62.8          | 62.8  |
| GE      | 3500  | 36.7      | 37.2     | 57.2     | 57.2     | 67.8     | 67.8     | 68.9     | 68.9     | 68.9        | 68.9     | 68.9     | 68.9     | 68.9     | 68.9     | 68.9          | 68.9  |
| GE      | 3000  | 42.2      | 43.3     | 65.6     | 65.6     | 81.1     | 81.1     | 82.2     | 82.2     | 82.2        | 82.2     | 82.2     | 82.2     | 82.2     | 82.2     | 82.2          | 82.2  |
| GE      | 2500  | 43.3      | 44.4     | 67.2     | 67.2     | 85.6     | 85.6     | 86.7     | 86.7     | 86.7        | 86.7     | 86.7     | 86.7     | 86.7     | 86.7     | 86.7          | 86.7  |
| GE      | 2000  | 43.3      | 44.4     | 67.2     | 67.2     | 86.1     | 86.7     | 89.4     | 92.2     | 92.2        | 92.2     | 92.2     | 92.2     | 92.2     | 92.2     | 92.2          | 92.2  |
| GE      | 1800  | 43.3      | 44.4     | 67.2     | 67.2     | 86.1     | 86.7     | 89.4     | 92.2     | 92.2        | 92.2     | 92.2     | 92.2     | 92.2     | 92.2     | 92.2          | 92.2  |
| GE      | 1500  | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.1     | 95.0     | 99.4     | 99.4        | 99.4     | 99.4     | 99.4     | 99.4     | 99.4     | 99.4          | 99.4  |
| GE      | 1200  | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
| GE      | 1000  | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
| GE      | 900   | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
| GE      | 800   | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
| GE      | 700   | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
| GE      | 600   | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
| GE      | 500   | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
| GE      | 400   | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
| GE      | 300   | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
| GE      | 200   | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
| GE      | 100   | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
| GE      | 000   | 43.3      | 44.4     | 67.8     | 67.8     | 90.0     | 91.7     | 95.6     | 100.0    | 100.0       | 100.0    | 100.0    | 100.0    | 100.0    | 100.0    | 100.0         | 100.0 |
|         |       |           |          |          |          |          |          |          |          |             |          |          |          |          |          |               |       |

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 LST TO UTC: - 9 MONTH: JUN HOURS: 18-20 CEILING VISIBILITY IN METERS GE GE GE GE GE GE GE GE GE GE GE GE GE GE 112 FEET 32 20 16 12 10 08 06 04 00 90 80 60 48 40 24 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 59.4 59.4 59.4 59.4 59.4 59.4 59.4 59.4 GE 5000 35.0 36.7 48.9 48.9 56.7 57.2 58.9 59.4 60.6 60.6 60.6 GΕ 4500 36.1 37.8 50.0 50.0 57.8 58.3 60.0 60.6 60.6 60.6 60.6 60.6 60.6 4000 57.8 69.4 70.0 70.0 70.0 70.0 70.0 70.0 70.0 70.0 70 0 GE 38.9 40.6 57.8 67.2 67.8 75.6 76.1 76.1 76.1 76.1 76.1 76.1 76.1 76.1 GE 3500 41.1 43.9 62.8 62.8 73.3 73.9 76.1 GE 3000 43.3 46.1 68.3 68.3 82.2 82.8 84.4 85.0 85.0 35.0 85.0 85.0 85.0 85.0 85.0 85.0 GE 68.9 89.4 90.0 90.0 90.0 90.0 90.0 90.0 90.0 90.0 90.0 2500 43.9 46.7 68.9 84.4 86.1 GE 2000 43.9 46.7 68.9 68.9 85.0 86.7 90.6 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 1800 68.9 86.7 90.6 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 GE 43.9 46.7 68.9 35.0 1500 43.9 92.8 95.6 95.6 95.6 95.6 95.6 95.6 95.6 95.6 GE 46.7 68.9 68.9 86.7 88.9 95.6 GE 12' 46.7 68.9 68.9 86.7 89.4 93.9 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 43.9 GE 1000 43.9 46.7 68.9 68.9 86.7 89.4 93.9 97.8 97.8 98.9 98.9 98.9 99.4 99.4 99.4 99.4 97.3 97.8 98.9 98.9 99.4 99.4 99.4 GE 900 43.9 46.7 68.9 68.9 86.7 89.4 93.9 98.9 99.4 46.7 68.9 87.2 94.4 98.3 99.4 99.4 99.4 100.0 100.0 100.0 100.0 GE 800 43.9 68.9 90.0 98.3 100.0 GE 700 43.9 46.7 68.9 68.9 87.2 90.0 94.4 98.3 98.3 99.4 99.4 99.4 100.0 100.0 100.0 98.3 98.3 99.4 99.4 99.4 100.0 100.0 100.0 100.0 GΕ 600 43.9 46.7 68.9 68.9 87.2 90.0 94.4 99.4 GE 500 43.9 46.7 68.9 68.9 87.2 90.0 94.4 98.3 98.3 99.4 99.4 100.0 100.0 100.0 99.4 100.0 100.0 400 46.7 68.9 68.9 87.2 90.0 94.4 98.3 98.3 99.4 99.4 100.0 100.0 GE 43.9 GE 300 43.9 46.7 68.9 68.9 87.2 90.0 94.4 98.3 98.3 99.4 99.4 99.4 100.0 100.0 100.0 100.0 200 43.9 46.7 98.3 99.4 99.4 99.4 100.0 100.0 100.0 100.0 GE 68.9 68.9 87.2 90.0 94.4 98.3 99.4 100.0 100.0 100.0 100.0 GE 100 43.9 46.7 68.9 68.9 87.2 90.0 94.4 98.3 98.3 99.4 99.4 000 43.9 68.9 68.9 87.2 90.0 94.4 98.3 98.3 99.4 99.4 99.4 100.0 100.0 100.0 100.0 GE 46.7

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

|     | EET   | 112   | 90      | 80   | 60   | 48   | 40   | 32   | 24      | 20               | 16            | 12            | 10    | 08    | 06     | 04    | 00    |
|-----|-------|-------|---------|------|------|------|------|------|---------|------------------|---------------|---------------|-------|-------|--------|-------|-------|
|     |       |       |         |      |      |      |      |      |         | · • • • • • •    | · • • • • • • | . <b></b> .   |       |       |        |       |       |
|     |       |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| NO  | CEIL  |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
|     |       |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| GE  | 20000 |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| GE  | 18000 |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
|     | 16000 |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
|     | 14000 |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| GE  | 12000 |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| CF  | 10000 |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| GE  | 9000  | l     |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| GE  | 8000  |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| GE, | 7000  |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| GE  | 6000  |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| GE  | 0000  |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| GE  | 5000  | 31.7  | 32.2    | 47.8 | 47.8 | 56.7 | 57.2 | 58.9 | 63.3    | 63.3             | 63.3          | 63.3          | 63.3  | 63.3  | 63.3   | 63.3  | 63.3  |
| GE  | 4500  | 31.7  | 32.2    | 47.8 | 47.8 | 56.7 | 57.2 | 58.9 | 63.3    | 63.3             | 63.3          | 63.3          | 63.3  | 63.3  | 63.3   | 63.3  | 63.3  |
| GE  | 4000  | 35.0  | 36.1    | 53.3 | E2 2 | 65.6 | 66.1 | 68.3 | 73.3    | 73.3             | 73.3          | 73.3          | 73.3  | 73.3  | 73.3   | 73.3  | 73.3  |
| GE  | 3500  | 36.1  | 37.2    | 5.5  | 55.6 | 69.4 | 70.0 | 72.8 | 77.8    | 77.8             | 77.8          | 77.8          | 77.8  | 77.8  | 77.8   | 77.8  | 77.8  |
| GE  | 3000  | 36.7  | 37.8    | 5 8  | 57.8 | 75.0 | 75.6 | 80.0 | 85.0    | 85.0             | 85.0          | 85.0          | 85.0  | 85.0  | 85.0   | 85.0  | 85.0  |
|     |       |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| GE  | 2500  | 37.2  | 38.3    | 58.3 | 58.3 | 75.6 | 77.2 | 82.2 | 87.2    | 87.2             | 87.2          | 87.2          | 87.2  | 87.2  | 87.2   | 87.2  | 87.2  |
| GE  | 2000  | 38.3  | 39.4    | 59.4 | 59.4 | 76.7 | 78.3 | 85.0 | 90.0    | 90.0             | 90.0          | 90.0          | 90.0  | 90.0  | 90.0   | 90.0  | 90.0  |
| GE  | 1800  | 30.3  | 39.4    | 59.4 | 59.4 | 76.7 | 78.3 | 85.0 | 90.0    | 90.0             | 90.0          | 90.0          | 90.0  | 90.0  | 90.0   | 90.0  | 90.0  |
| GE  | 1500  | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 93.3    | 93.3             | 93.3          | 93.3          | 93.3  | 93.3  | 93.3   | 93.3  | 93.3  |
| GE  | 1200  | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 94.4    | 95.0             | 95.0          | 95.0          | 95.0  | 95.0  | 95.0   | 95.0  | 95.0  |
|     |       |       |         |      |      |      |      |      |         |                  |               |               |       |       |        |       |       |
| GE  | 1000  | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 94.4    | 95. <del>6</del> | 96.7          | 96.7          | 96.7  | 96.7  | 96.7   | 96.7  | 96.7  |
| GE  | 900   | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 94.4    | 95.6             | 96.7          | 96.7          | 96.7  | 96.7  | 96.7   | 96.7  | 96.7  |
| GE  | 800   | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 94.4    | 95.6             | 97.2          | 98.3          | 98.3  | 98.9  | 98.9   | 98.9  | 98.9  |
| GE  | 700   | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 94.4    | 95.6             | 97.2          | 98.3          | 98.3  | 98.9  | 98.9   | 98.9  | 98.9  |
| GE  | 600   | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 94.4    | 95.6             | 97.2          | 98.3          | 98.3  | 98.9  | 98.9   | 98.9  | 98.9  |
| GE  | 500   | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 94.4    | 95.6             | 97.2          | 99.4          | 99.4  | 100.0 | 100.0  | 100.0 | 100.0 |
| GE  | 400   | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 94.4    | 95.6             | 97.2          | 99.4          | 99.4  | 100.0 | 100.0  | 100.0 | 100.0 |
| GE  | 300   | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 4.4د    | 95.6             | 97.2          | 99.4          | 99.4  | 100.0 | 100.0  | 100.0 | 100.0 |
| GE  | 200   | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 94.4    | 95.6             | 97.2          | 99.4          | 99.4  | 100.0 | 100.0  | 100.0 | 100.0 |
| GE  | 100   | 38.3  | 39.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 94.4    | 95.6             | 97.2          | 99.4          | 99.4  | 100.0 | 100.0  | 100.0 | 100.0 |
|     |       | 30.00 |         |      |      |      | 30.0 |      | ,       | 33.0             | J. • • •      | JJ • ¥        | JJ. 4 | _00.0 | - 40.0 |       | 200.0 |
| GE  | 000   | 38.3  | 19.4    | 59.4 | 59.4 | 77.8 | 80.0 | 86.7 | 94.4    | 95.6             | 97.2          | 99.4          | 99.4  | 100.0 | 100.0  | 100.0 | 100.0 |
|     |       |       | <i></i> |      |      |      |      |      | <b></b> |                  | · • • • • • • | · • • • • • • |       |       |        |       |       |

STATION NUMBER: 471066

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: JUN HOURS: ALL

95.6

95.7

96.6

96.7

97.0

97.6

97.8

97.9

97.9

97.9

95.8 97.9

94.6

94.7

95.4

95.4

95.6

95.7

95.8

95.8

95.8

95.8

95.7

95.8

96.7

96.9

97.1

97.8

98.0

98.2

98.2

98.2

96.1

96.2

97.3

97.5

97.8

98.7

99.0

99.2

99.3

99.3

96.2

96.3

97.4

97.5

98.1

99.0

99.3

99.5

99.6

99.6

98.2 99.3 99.6 99.7 100.0

96.2

96.3

97.4

97.5

98.2

99.1

99.3

99.6

99.7

99.7 100.0

96.2

96.4

97.5

97.6

98.3

99.2

99.6

99.9

100.0

CEILING VISIBILITY IN METERS GE GE GE GE GE GE GE GE GE GE GE TN GE GE GE GE. GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 ...... NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 6000 GE GE 50001 24.9 25.5 41.2 41.2 50.9 52.1 53.9 55.3 55.7 57.3 57.6 57.6 57.8 57.8 57.8 57.9 GE 4500 25.5 26.1 42.1 42.1 51.8 53.0 54.8 56.2 56.5 58.2 58.5 58.5 58.7 58.7 58.7 58.8 63.2 65.2 65.2 65.4 65.5 65.5 GE 4000 28.4 29.2 46.9 46.9 57.8 59.3 61.4 62.8 64.9 65.6 GΕ 3500 29.9 30.9 49.3 49.3 60.6 62.8 64.9 66.4 66.7 68.5 68.8 68.8 69.0 69.1 69.1 69.1 77.0 78.9 79.6 79.6 79.9 79.9 79.9 80.0 3000 32.8 34.1 53.8 53.8 68.6 71.4 74.3 76.4 GΕ GE 2500 33.2 34.4 54.3 54.3 69.9 73.1 76.4 78.8 79.3 81.3 82.0 82.0 82.3 82.4 82.4 82.5 34.6 54.9 74.5 81.9 82.6 84.8 .5.6 85.7 85.9 86.0 86.0 86.1 GE 2000 33.3 54.9 71.0 79.0 GΕ 1800 33.3 34.6 54.9 54.9 71.1 74.6 79.1 82.1 82.8 85.0 85.8 85.9 86.2 86.2 86.2 86.3 90.7 GΕ 1500 33.5 34.7 55.2 55.2 73.0 77.1 82.3 86.4 87.4 89.6 90.4 90.4 90.8 90.8 90.9 GE 1200 33.5 34.7 55.2 55.2 73.4 77.8 83.6 88.6 89.6 92.1 93.0 93.1 93.5 93.6 93.6 93.6

90.2

90.3

90.7

90.7

90.9

90.9

90.9

90.9

90.9

90.9

90.9

......

84.8

84.8

84.9

84.9

84.9

84.9

84.9

84.9

84.9

84.9

91.8

91.9

92.4

92.4

92.6

92.7

92.7

92.7

92.7

92.7

92.7

STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: - 9

TOTAL NUMBER OF OBSERVATIONS 1380

34.7

34.7

34.7

34.7

34.7

34.7

34.7

34.7

34.7

34.7

GE

GE

GΕ

GE GE

GE

GE

GE

GE

GE

GE

1000

900

700

600

500

400

300

200

100

33.5

33.5

33.5

33.5

33.5

33.5

33.5

33.5

33.5

33.5

55.2

55.2

55.2

55.2

55.2

55.2

55.2

55.2

55.2

55.2

000 33.5 34.7 55.2 55.2 74.1

55.2

55.2

55.2

55.2

55.2

55.2

55.2

55.2

55.2

55.2

74.0

74.0

74.1

74.1

74.1

74.1

74.1

74.1

74.1

74.1

78.3

78.3

78.4

78.4

78.4

78.4

78.4

78.4

78.4

78.4

78.4 84.9

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90 STATION NAME: CAMP CASEY/TONGDUCHON KO STATION NUMBER: 471066 LST TO UTC: - 9 MONTH: JUL HOURS: 00-02 CEILING VISIBILITY IN METERS GE GE GE GE GE GE GE GE GE GE GE IN GE GE GE GΕ GE 112 60 48 40 32 24 20 16 12 10 80 06 00 FEET 90 80 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 7000 GΕ GE 6000 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 5000 15.6 16.7 34.4 34.4 65.6 65.6 GE 65.6 65.6 65.6 GE 4500 15.6 16.7 34.4 34.4 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 65.6 GE 4000 18.9 20.0 37.8 37.8 70.0 70.0 73.3 73.3 73.3 73.3 73.3 73.3 73.3 73.3 73.3 73.3 76.7 76.7 76.7 76.7 76.7 76.7 76.7 73.3 76.7 76.7 76.7 3500 21.1 22.2 40.0 40.0 73.3 GE GE 3000 26.7 27.8 47.8 47.8 82.2 82.2 86.7 86.7 86.7 86.7 86.7 86.7 86.7 86.7 86.7 86.7 90.0 90.0 90.0 85.6 90.0 90.0 90.0 90.0 26.7 27.8 47.8 47.8 85.6 90.0 90.0 90.0 GE 2500 GΕ 2000 26.7 27.8 47.8 47.8 86.7 86.7 91.1 91.1 91.1 93.3 93.3 93.3 93.3 93.3 93.3 93.3 47.8 47.8 87.8 92.2 94.4 94.4 94.4 94.4 94.4 94.4 94.4 26.7 27.8 87.0 92.2 92.2 GE 1800 94.4 94.4 94.4 94.4 94.4 94.4 94.4 GE 1500 26.7 27.8 47.8 47.8 87.8 87.8 92.2 92.2 92.2 GE 1200 26.7 27.8 47.8 47.8 88.9 88.9 93.3 93.3 93.3 95.6 95.6 95.6 95.6 95.6 95.6 95.6 GE 1000 26.7 27.8 47.8 47.8 88.9 90.0 94.4 94.4 94.4 96.7 96.7 96.7 96.7 96.7 96.7 96.7 900 26.7 27.8 47.8 47.8 88.9 90.0 94.4 94.4 94.4 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 98.9 98.9 98.9 98.9 98.9 GE 800 26.7 27.8 47.8 47.8 88.9 90.0 95.6 96.7 96.7 98.9 98.9 47.8 GE 700 26.7 27.8 47.8 88.9 90.0 95.6 96.7 96.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 27.8 98.9 98.9 26.7 88.9 95.6 96.7 98.9 98.9 98.9 98.9 98.9 GE 600 47.8 47.8 90.0 96.7 98.9 98.9 98.9 98.9 27.8 47.8 47.8 88.9 90.0 95.6 96.7 98.9 98.9 98.9 GE 500 26.7 96.7 GE 400 26.7 27.8 47.8 47.8 88.9 90.0 95.6 96.7 96.7 98.9 98.9 98.9 100.0 100.0 100.0 100.0 GE 300 26.7 27.8 47.8 47.8 88.9 90.0 95.6 96.7 96.7 98.9 98.9 98.9 100.0 100.0 100.0 100.0 GE 200 26.7 27.8 47.8 47.8 88.9 90.0 95.6 96.7 96.7 98.9 98.9 98.9 100.0 100.0 100.0 100.0 GE 100 26.7 27.8 47.8 47.8 88.9 90.0 95.6 96.7 96.7 98.9 98.9 100.0 100.0 100.0 100.0 000 26.7 27.8 47.8 88.9 90.0 95.6 96.7 96.7 98.9 98.9 98.9 100.0 100.0 100.0 100.0 GE 47.8

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL HOURS: 03-05 CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GΕ GE GE GE GE GE GE GE FEET 112 90 80 60 48 40 32 24 20 10 16 12 08 06 04 00 NO CETT. GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 8000 GE GE 7000 GE 6000 47.8 50.0 GE 5000 10.0 10.0 18.9 18.9 50.0 50.0 50.0 51.1 52.2 52.2 52.2 52.2 52.2 52.2 GE 4500 10.0 10.0 18.9 18.9 48.9 51.1 52.2 52.2 52.2 53.3 54.4 54.4 54.4 54.4 54.4 54.4 GE 4000 13.3 13.3 22.2 22.2 53.3 55.6 56.7 56.7 56.7 57.8 58.9 58.9 58.9 58.9 58.9 58.9 3500 GE 13.3 13.3 22.2 22.2 54.4 56.7 57.8 57.8 57.8 58.9 60.0 60.0 60.0 60.0 60.0 60.0 GE 3000 20.0 20.0 32.2 68.9 71.1 72.2 74.4 74.4 32.2 72.2 72.2 73.3 74.4 74.4 74.4 81.1 GE 2500 21.1 21.1 33.3 33.3 73.3 75.6 76.7 77.8 77.8 80.0 81.1 81.1 81.1 81.1 81.1 GE 2000 23.3 24.4 36.7 36.7 78.9 81.1 82.2 83.3 83.3 88.9 90.0 90.0 90.0 90.0 90.0 90.0 GE 1800 23.3 24.4 36.7 36.7 78.9 81.1 82.2 83.3 83.3 88.9 90.0 90.0 90.0 90.0 90.0 90.0 GE 1500 23.3 24.4 36.7 36.7 78.9 81.1 90.0 91.1 91.1 91.1 82.2 84.4 84.4 91.1 91.1 1200 23.3 24.4 78.9 81.1 GE 36.7 36.7 82.2 84.4 84.4 90.0 91.1 91.1 91.1 91.1 91.1 91.1 GE 1000 24.4 36.7 36.7 78.9 81.1 90.0 92.2 23.3 82.2 84.4 84.4 92.2 92.2 92.2 92.2 92.2 GE 900 23.3 24.4 36.7 36.7 78.9 81.1 82.2 84.4 84.4 90.0 92.2 92.2 92.2 92.2 92.2 92.2 GE 800 23.3 24.4 36.7 36.7 78.9 81.1 82.2 87.8 87.8 93.3 95.6 95.6 95.6 95.6 95.6 95.6 GΕ 700 23.3 24.4 36.7 36.7 78.9 81.1 83.3 88.9 88.9 94.4 96.7 96.7 96.7 96.7 96.7 96.7 600 23.3 24.4 36.7 78.9 GE 36.7 81.1 83.3 88.9 88.9 94.4 96.7 96.7 96.7 96.7 96.7 96.7 500 23.3 36.7 36.7 78.9 81.1 GE 24.4 83.3 88.9 94.4 96.7 96.7 96.7 96.7 88.9 96.7 96.7 GE 400 23.3 24.4 36.7 36.7 78.9 81.1 83.3 88.9 88.9 94.4 96.7 96.7 98.9 98.9 100.0 100.0 24.4 78.9 GΕ 300 23.3 36.7 36.7 81.1 83.3 88.9 88.9 94.4 96.7 96.7 98.9 98.9 100.0 100.0 23.3 GE 200 24.4 36.7 36.7 78.9 83.3 81.1 88.9 88.9 94.4 96.7 96.7 98.9 98.9 100.0 100.0 GE 100 23.3 24.4 36.7 36.7 78.9 83.3 96.7 96.7 81.1 94.4 98.9 98.9 100.0 100.0 000 23.3 36.7 GE 24.4 36.7 78.9 81.1 83.3 88.9 88.9 94.4 96.7 96.7 98.9 98.9 100.0 100.0

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL HOURS: 06-08 CEILING VISIBILITY IN METERS IN GE GΕ GE GE GË GE GE GE GE GE GE GE GE GE GE GΕ 32 112 90 FEET 80 60 48 40 24 20 16 12 10 08 06 04 00 NO CELL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GΕ 6000 GE 5000 3.3 3.3 16.7 16.7 42.2 43.3 44.4 45.6 45.6 45.6 46.7 46.7 47.8 47.8 48.9 50.0 GΕ 4500 16.7 16.7 42.2 43.3 44.4 45.6 45.6 48.9 50.0 3.3 3.3 45.6 46.7 46.7 47.8 47.8 GE 4000 3.3 3.3 16.7 16.7 44.4 45.6 46.7 47.8 47.8 47.8 48.9 48.9 50.0 50.0 51.1 52.2 GE 3500 3.3 3.3 16.7 16.7 45.6 46.7 47.8 48.9 48.9 48.9 50.0 50.0 51.1 51.1 52.2 53.3 GE 3000 20.0 20.0 52.2 55.6 6.7 6.7 53.3 54.4 55.6 55.6 56.7 56.7 57.8 57.8 58.9 60.0 GE 2500 12.2 12.2 26.7 26.7 60.0 62.2 63.3 64.4 64.4 64.4 65.6 65.6 66.7 66.7 67.8 68.9 GE 2000 16.7 16.7 31.1 31.1 64.4 66.7 67.8 68.9 68.9 68.9 71.1 71.1 74.4 74.4 75.6 76.7 16.7 66.7 67.8 68.9 GE 1800 16.7 31.1 31.1 64.4 68.9 68.9 71.1 71.1 74.4 74.4 75.6 76.7 GE 1500 16.7 16.7 31.1 31.1 64.4 66.7 72.2 74.4 74.4 74.4 77.8 77.8 81.1 81.1 82.2 83.3 GE 1200 64.4 66.7 72.2 74.4 16.7 16.7 31.1 31.1 74.4 74.4 77.8 77.8 81.1 81.1 82.2 83.3 16.7 65.6 67.8 73.3 75.6 GE 1000 16.7 31.1 31.1 76.7 77.8 81.1 81.1 84.4 84.4 85.6 86.7 16.7 65.6 67.8 84.4 900 16.7 31.1 31.1 73.3 75.6 85.6 86.7 GE 76.7 77.8 81.1 81.1 84.4 GE 800 16.7 16.7 31.1 31.1 65.6 67.8 73.3 75.6 76.7 77.8 81.1 81.1 84.4 84.4 85.6 86.7 GE 700 16.7 16.7 31.1 31.1 65.6 67.8 73.3 75.6 76.7 77.8 81.1 81.1 86.7 86.7 87.8 88.9 GE 600 16.7 16.7 31.1 31.1 65.6 67.8 73.3 76.7 77.8 78.9 82.2 84.4 90.0 90.0 91.1 92.2 67.8 75.6 78.9 16.7 16.7 31.1 31.1 65.6 GE 500 80.0 81.1 85.6 87.8 93.3 93.3 94.4 95.6 GE 400 16.7 16.7 31.1 31.1 65.6 67.8 75.6 78.9 80.0 82.2 86.7 90.0 96.7 96.7 98.9 100.0 GE 300 16.7 16.7 31.1 31.1 65.6 67.8 75.6 78.9 80.0 82.2 86.7 90.0 96.7 96.7 98.9 100.0 75.6 GE 200 16.7 16.7 31.1 31.1 65.6 67.8 78.9 80.0 82.2 86.7 90.0 96.7 96.7 98.9 100.0 75.6 78.9 GE 16.7 16.7 31.1 31.1 65.6 67.8 80.0 82.2 86.7 90.0 96.7 96.7 98.9 100.0 000 16.7 16.7 31.1 31.1 65.6 67.8 75.6 78.9 80.0 82.2 86.7 90.0 96.7 96.7 98.9 100.0 GE

#### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONODUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL HOURS: 09-11 CEILING VISIBILITY IN METERS GE GE GE GE GΕ GE GE IN GE GE GE GE GΕ GE GΕ 32 90 20 12 10 06 04 FEET 112 80 60 48 40 24 16 08 00 ...... NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 55.2 GΕ 5000 17.2 17.2 24.1 24.1 46.6 50.0 55.2 55.2 55.2 55.2 55.2 55.2 55.2 55.2 55.2 4500 GE 17.2 17.2 24.1 24.1 46.6 50.0 55.2 55.2 55.2 55.2 55.2 55.2 55.2 55.2 55.2 17.2 56.9 GE 4000 56.9 56.9 56.9 56.9 56.9 56.9 17.2 24.1 24.1 48.3 51.7 56.9 56.9 56.9 GE 350C 17.2 17.2 27.6 27.6 51.7 55.2 60.3 60.3 60.3 60.3 60.3 60.3 60.3 60.3 60.3 60.3 67.2 34.5 67.2 67.2 67.2 67.2 67.2 67.2 67.2 GE 3000 17.2 17.2 34.5 58.6 62.1 67.2 67.2 GE 2500 25.9 25.9 43.1 43.1 69.0 72.4 77.6 77.6 77.6 77.6 77.6 77.6 77.6 77.6 77.6 77.6 27.6 79.3 79.3 79.3 79.3 79.3 79.3 2000 27.6 44.8 70.7 74.1 79.3 79.3 79.3 79.3 GE 44.8 GE 1800 27.6 27.6 44.8 44.8 70.7 74.1 79.3 79.3 79.3 79.3 79.3 79.3 79.3 79.3 79.3 79.3 GΕ 1500 29.3 29.3 46.6 46.6 74.1 77.6 84.5 86.2 86.2 86.2 87.9 87.9 87.9 87.9 87.9 87.9 GE 1200 29.3 29.3 46.6 46.6 74.1 77.6 84.5 86.2 86.2 86.2 87.9 87.9 87.9 87.9 87.9 87.9 89.7 89.7 29.3 29.3 46.6 77.6 86.2 89.7 91.4 91.4 91.4 91.4 91.4 GE 1000 46.6 74.1 91.4 GE 900 29.3 29.3 46.6 46.6 74.1 77.6 86.2 89.7 89.7 89.7 91.4 91.4 91.4 91.4 91.4 91.4 GE 800 29.3 29.3 48.3 48.3 75.9 79.3 89.7 93.1 93.1 94.8 96.6 96.6 96.6 96.6 96.6 96.6 96.6 700 29.3 29.3 48.3 48.3 75.9 79.3 89.7 93.1 94.8 96.6 96.6 96.6 96.6 96.6 GE 93.1 GΕ 600 29.3 29.3 48.3 48.3 75.9 79.3 89.7 93.1 93.1 94.8 96.6 96.6 96.6 96.6 96.6 96.6 79.3 29.3 75.9 89.7 94.8 96.6 100.0 100.0 100.0 100.0 100.0 GE 500 29.3 48.3 48.3 94.8 GE 400 29.3 29.3 48.3 48.3 75.9 79.3 89.7 94.8 94.8 96.6 100.0 100.0 100.0 100.0 100.0 29.3 48.3 75.9 94.8 94.8 96.6 100.0 100.0 100.0 100.0 100.0 GE 300 29.3 48.3 79.3 89.7 GE 2001 29.3 29.3 48.3 48.3 75.9 79.3 89.7 94.8 94.8 96.6 100.0 100.0 100.0 100.0 100.0 GE 100 29.3 29.3 48.3 48.3 75.9 79.3 89.7 94.8 94.8 96.6 100.0 100.0 100.0 100.0 100.0 100.0 000 29.3 29.3 48.3 48.3 75.9 79.3 89.7 94.8 94.8 96.6 100.9 100.0 100.0 100.0 100.0 100.0

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL HOURS: 12-14 CEILING VISIBILITY IN METERS IN GE GE GΕ GE GE GE GE GE GE GE GE GE GE GΕ GE GΕ 112 60 48 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 8000 GE GΕ 7000 GE 6000 GE 29.9 29.9 42.5 42.5 44.8 46.0 5000 13.8 13.8 46.0 46.0 46.0 46.0 46.0 46.0 46.0 46.0 GE 4500 13.8 13.8 31.0 31.0 43.7 43.7 46.0 47.1 47.1 47.1 47.1 47.1 47.1 47.1 47.1 47.1 GΕ 4000 16.1 16.1 34.5 34.5 47.1 47.1 49.4 50.6 50.6 50.6 50.6 50.6 50.6 50.6 50.6 50.6 16.1 3500 16.1 37.9 37.9 50.6 50.6 54.0 55.2 GE 55.2 55.2 55.2 55.2 55.2 55.2 55.2 55.2 GΕ 3000 24.1 24.1 56.3 56.3 70.1 71.3 74.7 77.0 77.0 77.0 77.0 77.0 77.0 77.0 77.0 77.0 79.3 GE 2500 32.2 32.2 64.4 64.4 78.2 82.8 85.1 85.1 85.1 85.1 85.1 85.1 85.1 85.1 85.1 GΕ 2000 33.3 33.3 66.7 66.7 82.8 83.9 87.4 89.7 89.7 89.7 89.7 89.7 89.7 89.7 89.7 89.7 33.3 66.7 87.4 GΞ 1800 33.3 66.7 82.8 83.9 89.7 89.7 89.7 89.7 89.7 89.7 89.7 89.7 89.7 GE 1500 33.3 33.3 66.7 66.7 82.8 85.1 88.5 92.0 92.0 93.1 93.1 93.1 93.1 93.1 93.1 GE 1200 33.3 33.3 66.7 66.7 82.8 85.1 88.5 92.0 92.0 93.1 93.1 93.1 93.1 93.1 93.1 93.1 GΕ 1000 33.3 33.3 67.8 67.8 83.9 86.2 92.0 95.4 95.4 96.6 96.6 96.6 96.6 96.6 96.6 900 33.3 67.8 67.8 83.9 86.2 GΕ 33.3 92.0 95.4 96.6 96.6 95.4 96.6 96.6 96.6 96.6 96.6 GE 800 33.3 33.3 69.0 69.0 85.1 87.4 93.1 96.6 96.6 100.0 100.0 100.0 100.0 100.6 100.0 100.0 GE 700 33.3 33.3 69.0 69.0 85.1 87.4 93.1 96.6 96.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 600 69.0 69.0 85.1 87.4 33.3 33.3 93.1 96.6 96.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 33.3 33.3 69.0 69.0 85.1 87.4 93.1 96.6 96.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 33.3 33.3 69.0 69.0 85.1 87.4 93.1 96.6 96.6 100.0 100.0 100.0 100.0 100.0 100.0 87.4 GE 300 33.3 33.3 69.0 69.0 85.1 93.1 96.6 96.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 33.3 GE 200 33.3 69.0 69.0 85.1 87.4 93.1 96.6 96.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 85.1 GE 100 33.3 33.3 69.0 69.0 87.4 93.1 96.6 96.6 100.0 100.0 100.0 100.0 100.0 100.0 GE 000 | 33.3 33.3 69.0 69.0 85.1 87.4 93.1 96.6 96.6 100.0 100.0 100.0 100.0 100.0 100.0

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL HOURS: 15-17

| • • • • • • | • • • • • • •  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
|-------------|--|---|--|---|---|---|---|--|--|---|--|---|---|---|---|
|             |  |   |  | , ,   | VISIBIL   | ITY IN  | METERS  | • • • • • •  | •••••  | •••••   | •••••  | •••••   | •••••   | • • • • • • •   | • • • • •   |
| GE          | GE   | GE  | GE   | GE  | GE  | GE  | GE  | GE   | GE   | GE  | GE   | Œ   | GΕ  | GE  | GI  |
| 112         | 90   | 80  | 60   | 48  | 40  | 32  | 24  | 20   | 16   | 12  | 10   | 08  | 06  | 04  | 00  |
|             | • • • • • •  | • • • • • • •   | • • • • • •  |   | · · · · · · ·   |   | • • • • • • •   | • • • • • • •  | • • • • • • •  |   | • • • • • • •  | • • • • • • •   |   | • • • • • • •   | ••••  |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   |   |
| 34.5        | 34.5   | 46.0  | 46.0   | 51.7  | 51.7  | 51.7  | 51.7  | 51.7   | 51.7   | 51.7  | 51.7   | 51.7  | 51.7  | 51.7  | 51  |
| 35.6        | 36.8   | 49.4  | 49.4   | 55.2  | 55.2  | 55.2  | 55.2  | 55.2   | 55.2   | 55.2  | 55.2   | 55.2  | 55.2  | 55.2  | 55  |
|             | 42.5   | 58.6  |  |   |   |   | 70.1  |  |  |   |  |   |   | 70.1  | 70  |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   | 77  |
| 47.1        | 48.3   | 67.8  | 67.8   | 82.8  | 83.9  | 85.1  | 85.1  | 85.1   | 85.1   | 85.1  | 85.1   | 85.1  | 85.1  | 85.1  | 85  |
| 51.7        | 52.9   | 72.4  | 72.4   | 88.5  | 89.7  | 90.8  | 90.8  | 90.8   | 90.8   | 90.3  | 90.8   | 90.8  | 90.8  | 90.8  | 90  |
| 51.7        | 52.9   | 75.9  | 75.9   | 92.0  | 93.1  | 94.3  | 94.3  | 94.3   | 94.3   | 94.3  | 94.3   | 94.3  | 94.3  | 94.3  | 94  |
| 51.7        | 52.9   | 77.0  | 77.0   | 93.1  | 94.3  | 95.4  | 95.4  | 95.4   | 95.4   |   |  | 95.4  | 95.4  | 95.4  | 95  |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   | 98  |
| 54.0        | 55.2   | 80.5  | 80.5   | 96.6  | 97.7  | 98.9  | 98.9  | 98.9   | 98.9   | 98.9  | 98.9   | 98.9  | 98.9  | 98.9  | 98  |
| 54.0        | 55.2   | 81.6  | 81.6   | 97.7  | 98.9  | 100.0   | 100.0   | 100.0  | 100.0  | 100.0   | 100.0  | 100.0   | 100.0   | 100.0   | 100   |
| 54.0        | 55.2   | 81.6  | 81.6   | 97.7  | 98.9  | 100.0   | 100.0   | 100.0  | 100.0  | 100.0   | 100.0  | 100.0   | 100.0   | 100.0   | 100   |
| 54.0        | 55.2   | 81.6  | 81.6   | 97.7  | 98.9  | 100.0   | 100.0   | 100.0  | 100.0  | 100.0   | 100.0  | 100.0   | 100.0   | 100.0   | 100   |
|             |  |   |  |   |   |   |   |  |  |   |  |   |   |   | 100   |
| 54.0        | 55.2   | 81.6  | 81.6   | 97.7  | 98.9  | 100.0   | 100.0   | 100.0  | 100.0  | 100.0   | 100.0  | 100.0   | 100.0   | 100.0   | 100   |
| 54.0        | 55.2   | 81.6  | 81.6   | 97.7  | 98.9  | 100.0   | 100.0   | 100.0  | 100.0  | 100.0   | 100.0  | 100.0   | 100.0   | 100.0   | 100   |
| 54.0        | 55.2   | 81.6  | 81.6   | 97.7  | 98.9  | 100.0   | 100.0   | 100.0  | 100.0  | 100.0   | 100.0  | 100.0   | 100.0   | 100.0   | 100   |
| 54.0        | 55.2   | 81.6  | 81.6   | 97.7  | 98.9  | 100.0   | 100.0   | 100.0  | 100.0  | 100.0   | 100.0  | 100.0   | 100.0   | 100.0   | 100   |
| 54.0        | 55.2   | 81.6  | 81.6   | 97.7  | 98.9  | 100.0   | 100.0   | 100.0  | 100.0  | 100.0   | 100.0  | 100.0   | 100.0   | 100.0   | 100   |
| 54.0        | 55.2   | 81.6  | 81.6   | 97.7  | 98.9  | 100.0   | 100.0   | 100.0  | 100.0  | 100.0   | 100.0  | 100.0   | 100.0   | 100.0   | 100   |
| 54.0        | 55.2   | 81.6  | 81.6   | 97.7  | 98.9  | 100.0   | 100.0   | 100.0  | 100.0  | 100.0   | 100.0  | 100.0   | 100.0   | 100.0   | 100   |
|             | 34.5<br>35.6<br>41.4<br>43.7<br>47.1<br>51.7<br>51.7<br>54.0<br>54.0<br>54.0<br>54.0<br>54.0<br>54.0<br>54.0<br>54.0 | 34.5 34.5<br>35.6 36.8<br>41.4 42.5<br>43.7 44.8<br>47.1 48.3<br>51.7 52.9<br>51.7 52.9<br>54.0 55.2<br>54.0 55.2<br>54.0 55.2<br>54.0 55.2<br>54.0 55.2<br>54.0 55.2<br>54.0 55.2<br>54.0 55.2<br>54.0 55.2<br>54.0 55.2 | 34.5 34.5 46.0<br>35.6 36.8 49.4<br>41.4 42.5 58.6<br>43.7 44.8 64.4<br>47.1 48.3 67.8<br>51.7 52.9 72.4<br>51.7 52.9 77.0<br>54.0 55.2 80.5<br>54.0 55.2 81.6<br>54.0 55.2 81.6 | 34.5 34.5 46.0 46.0<br>35.6 36.8 49.4 49.4<br>41.4 42.5 58.6 58.6<br>43.7 44.8 64.4 64.4<br>47.1 48.3 67.8 67.8<br>51.7 52.9 72.4 72.4<br>51.7 52.9 77.0 77.0<br>54.0 55.2 80.5 80.5<br>54.0 55.2 81.6 81.6<br>54.0 55.2 81.6 81.6 | 34.5 34.5 46.0 46.0 51.7 35.6 36.8 49.4 49.4 55.2 41.4 42.5 58.6 58.6 69.0 43.7 44.8 64.4 64.4 74.7 47.1 48.3 67.8 67.8 82.8 51.7 52.9 72.4 72.4 88.5 51.7 52.9 75.9 75.9 92.0 51.7 52.9 77.0 77.0 93.1 54.0 55.2 80.5 80.5 96.6 54.0 55.2 80.5 80.5 96.6 54.0 55.2 81.6 81.6 97.7 | 34.5 34.5 46.0 46.0 51.7 51.7 35.6 36.8 49.4 49.4 55.2 55.2 41.4 42.5 58.6 58.6 69.0 69.0 43.7 44.8 64.4 64.4 74.7 75.9 47.1 48.3 67.8 67.8 82.8 83.9 51.7 52.9 72.4 72.4 88.5 89.7 51.7 52.9 75.9 75.9 92.0 93.1 51.7 52.9 75.9 75.9 92.0 93.1 51.7 52.9 77.0 77.0 93.1 94.3 54.0 55.2 80.5 80.5 96.6 97.7 54.0 55.2 80.5 80.5 96.6 97.7 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 | 34.5 34.5 46.0 46.0 51.7 51.7 51.7 35.6 36.8 49.4 49.4 55.2 55.2 55.2 41.4 42.5 58.6 58.6 69.0 69.0 70.1 43.7 44.8 64.4 64.4 74.7 75.9 77.0 47.1 48.3 67.8 67.8 82.8 83.9 85.1 51.7 52.9 75.9 75.9 92.0 93.1 94.3 51.7 52.9 75.9 75.9 92.0 93.1 94.3 51.7 52.9 75.9 75.9 92.0 93.1 94.3 51.7 52.9 77.0 77.0 93.1 94.3 95.4 54.0 55.2 80.5 80.5 96.6 97.7 98.9 54.0 55.2 80.5 80.5 96.6 97.7 98.9 54.0 55.2 81.6 81.6 97.7 98.9 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 55.0 | 34.5 34.5 46.0 46.0 51.7 51.7 51.7 51.7 35.6 36.8 49.4 49.4 55.2 55.2 55.2 55.2 41.4 42.5 58.6 58.6 69.0 69.0 70.1 70.1 43.7 44.8 64.4 64.4 74.7 75.9 77.0 77.0 47.1 48.3 67.8 67.8 82.8 83.9 85.1 85.1 51.7 52.9 75.9 75.9 92.0 93.1 94.3 94.3 51.7 52.9 75.9 75.9 92.0 93.1 94.3 94.3 51.7 52.9 77.0 77.0 93.1 94.3 95.4 95.4 54.0 55.2 80.5 80.5 96.6 97.7 98.9 98.9 54.0 55.2 80.5 80.5 96.6 97.7 98.9 98.9 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 55.0 55.2 81.6 81.6 81.6 97.7 98.9 100.0 100.0 55. | 34.5 34.5 46.0 46.0 51.7 51.7 51.7 51.7 51.7 35.6 36.8 49.4 49.4 55.2 55.2 55.2 55.2 55.2 55.2 41.4 42.5 58.6 58.6 69.0 69.0 70.1 70.1 70.1 70.1 43.7 44.8 64.4 64.4 74.7 75.9 77.0 77.0 77.0 47.1 48.3 67.8 67.8 82.8 83.9 85.1 85.1 85.1 51.7 52.9 75.9 75.9 92.0 93.1 94.3 94.3 94.3 94.3 51.7 52.9 75.9 75.9 92.0 93.1 94.3 94.3 94.3 94.3 51.7 52.9 75.9 82.0 93.1 94.3 95.4 95.4 54.0 55.2 80.5 80.5 96.6 97.7 98.9 98.9 98.9 98.9 54.0 55.2 80.5 80.5 96.6 97.7 98.9 98.9 98.9 98.9 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 54.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 100.0 100.0 100.0 55.0 55.2 81.6 81.6 97.7 98.9 100.0 | 34.5 34.5 46.0 46.0 51.7 51.7 51.7 51.7 51.7 51.7 35.6 36.8 49.4 49.4 55.2 55.2 55.2 55.2 55.2 55.2 41.4 42.5 58.6 58.6 69.0 69.0 70.1 70.1 70.1 70.1 43.7 44.8 64.4 64.4 74.7 75.9 77.0 77.0 77.0 77.0 77.0 47.1 48.3 67.8 67.8 82.8 83.9 85.1 85.1 85.1 85.1 85.1 51.7 52.9 75.9 75.9 92.0 93.1 94.3 94.3 94.3 94.3 51.7 52.9 75.9 75.9 92.0 93.1 94.3 94.3 94.3 94.3 51.7 52.9 77.0 77.0 93.1 94.3 95.4 95.4 95.4 95.4 95.4 95.4 95.4 95.4 | 34.5 34.5 46.0 46.0 51.7 51.7 51.7 51.7 51.7 51.7 51.7 35.6 36.8 49.4 49.4 55.2 55.2 55.2 55.2 55.2 55.2 55.2 41.4 42.5 58.6 58.6 69.0 69.0 70.1 70.1 70.1 70.1 70.1 70.1 43.3 67.8 67.8 82.8 83.9 85.1 85.1 85.1 85.1 85.1 85.1 85.1 85.1 | 34.5 34.5 46.0 46.0 51.7 51.7 51.7 51.7 51.7 51.7 51.7 51.7 | 34.5 34.5 46.0 46.0 51.7 51.7 51.7 51.7 51.7 51.7 51.7 51.7 | 34.5 34.5 46.0 46.0 51.7 51.7 51.7 51.7 51.7 51.7 51.7 51.7 | 34.5 34.5 46.0 46.0 51.7 51.7 51.7 51.7 51.7 51.7 51.7 51.7 |

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 LST TO UTC: - 9 MONTH: JUL HOURS: 18-20 CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GE GE GE GE GΕ GE GE GE FEET 112 90 80 60 48 40 32 20 16 12 10 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 8000 GE 7000 GE GE 6000 62.1 62.1 GE 5000 40.2 41.4 60.9 60.9 62.1 62.1 62.1 62.1 62.1 62.1 62.1 62.1 62.1 62.1 GE 4500 41.4 42.5 62.1 62.1 63.2 63.2 63.2 63.2 63.2 63.2 63.2 63.2 63.2 63.2 63.2 63.2 GΕ 4000 47.1 48.3 69.0 69.0 73.6 73.6 73.6 73.6 73.6 73.6 73.6 73.6 73.6 73.6 73.6 73.6 77.0 77.0 77.0 77.0 77.0 77.0 49.4 50.6 72.4 77.0 77.0 77.0 77.0 77.0 GE 3500 72.4 77.0 GE 3000 52.9 54.0 77.0 77.0 81.6 81.6 81.6 81.6 81.6 81.6 81.6 81.6 81.6 81.6 81.6 81.6 88.5 GE 56.3 82.8 88.5 88.5 88.5 88.5 88.5 88.5 88.5 88.5 88.5 88.5 88.5 2500 55.2 82.8 GE 2000 57.5 58.6 85.1 85.1 92.0 92.0 92.0 92.0 92.0 92.0 92.0 92.0 92.0 92.0 92.0 92.0 57.5 58.6 85.1 85.1 92.0 92.0 92.0 92.0 92.0 92.0 92.0 92.0 92.0 92.0 GE 1800 92.0 92.0 GE 1500 58.6 59.8 87.4 87.4 97.7 97.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GE 1200 58.6 59.8 87.4 87.4 97.7 97.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GE 1000 58.6 59.8 87.4 87.4 97.7 97.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 97.7 GΕ 900 58.6 59.8 87.4 87.4 97.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 87.4 59.8 87.4 97.7 97.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GE 800 58.6 98.9 98.9 GE 700 58.6 59.8 87.4 87.4 97.7 97.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GE 58.6 87.4 87.4 97.7 97.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 600 59.8 GE 500 58.6 59.8 87.4 87.4 97.7 97.7 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 87.4 100.0 100.0 100.0 GE 400 58.6 59.8 87.4 97.7 97.7 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 300 58.6 59.8 87.4 87.4 97.7 97.7 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 58.6 59.8 87.4 97.7 97.7 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 58.6 87.4 87.4 97.7 97.7 98.9 100.0 100.0 GE 100 59.8 87.4 97.7 97.7 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 000 58.6 59.8 87.4 GE

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: JUL HOURS: 21-23 LST TO UTC: - 9 CEILING VISIBILITY IN METERS GE GE GE GE GE GE GE IN GE GE GE GE GE GE GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GΕ 7000 GE 5000 GE 5000 23.0 23.0 56.3 36.3 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 GE 56.3 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 4500 23.0 23.0 56.3 69.0 GE 4000 23.0 23.0 57.5 57.5 72.4 72.4 73.6 73.6 73.6 73.6 73.6 73.6 73.6 73.6 73.6 73.6 GE 3500 23.0 23.0 57.5 57.5 72.4 72.4 73.6 73.6 73.6 73.6 73.6 73.6 73.6 73.6 73.6 73.6 GE 3000 26.4 26.4 62.1 62.1 80.5 80.5 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 GE 2500 27.6 27.6 63.2 63.2 82.8 82.8 85.1 85.1 85.1 85.1 85.1 85.1 85.1 85.1 85.1 85.1 87.4 87.4 87.4 87.4 87.4 87.4 87.4 87.4 GE 2000 27.6 27.6 63.2 63.2 85.1 85.1 87.4 87.4 GE 1800 27.6 27.6 63.2 63.2 85.1 87.4 89.7 89.7 89.7 89.7 89.7 89.7 89.7 89.7 GE 1500 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 27.6 27.6 63.2 63.2 90.8 94.3 GE 1200 27.6 27.6 63.2 63.2 90.8 94.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 27.6 63.2 90.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 1000 27.6 63.2 94.3 100.0 GE 900 27.6 27.6 63.2 63.2 90.8 94.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 800 27.6 27.6 63.2 63.2 90.8 94.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 94.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 700 27.6 27.6 63.2 90.8 63.2 GE 600 27.6 27.6 63.2 63.2 90.8 94.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 27.6 27.6 63.2 63.2 90.8 94.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 27.6 27.6 63.2 63.2 90.8 94.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 90.8 GΕ 300 27.6 27.6 63.2 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 63.2 94.3 GE 200 27.6 27.6 63.2 63.2 90.8 94.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 27.6 27.6 63.2 63.2 90.8 94.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 000 27.6 27.6 63.2 63.2 90.8 94.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL HOURS: ALL VISIBILITY IN METERS CEILING IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GΕ GE 24 112 FEET 90 80 60 48 40 32 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 9000 GE 8000 GE GE 7000 GΕ 6000 GE 5000 19.7 20.0 36.2 36.2 53.7 54.4 55.3 55.6 55.6 55.8 56.1 56.1 56.2 56.2 56.4 56.5 20.0 37.0 37.0 54.6 55.3 56.4 56.7 56.7 56.8 57.1 57.1 57.2 57.2 57.4 57.5 GE 4500 20.4 GE 4000 22.6 23.1 40.5 40.5 60.2 60.9 62.7 63.0 63.0 63.2 63.5 63.5 63.6 63.6 63.8 63.9 GE 3500 23.5 24.0 42.8 42.8 62.9 63.8 65.7 66.0 66.0 66.1 66.4 66.4 66.6 66.6 66.7 66.9 GE 3000 28.0 50.1 50.1 72.6 73.7 75.9 76.3 76.3 76.5 76.8 76.8 76.9 76.9 77.1 77.2 28.4 GE 2500 31.7 32.1 54.4 54.4 78.6 79.7 82.0 82.5 82.5 82.8 83.1 83.1 83.3 83.3 83.4 83.6 85.9 87.4 87.4 GE 2000 33.1 33.7 56.7 56.7 82.0 83.1 85.4 85.9 87.0 87.9 87.9 88.0 88.2 88.6 33.7 56.8 56.8 82.2 83.7 85.9 86.5 86.5 87.6 88.0 88.0 88.5 88.5 88.8 GE 1800 33.1 CZ 1500 33.7 34.3 57.7 57.7 84.5 86.2 89.8 91.0 91.0 92.2 92.9 92.9 93.3 93.3 93.5 93.6 GE 1200 33.7 34.3 57.7 57.7 84.6 86.4 89.9 91.1 91.1 92.3 93.0 93.0 93.5 93.5 93.6 93.8 GE 1000 33.7 34.3 58.0 58.0 85.1 87.0 91.0 92.3 92.5 93.8 94.7 94.7 95.1 95.1 95.3 95.4 900 33.7 34.3 58.0 58.0 85.1 87.0 91.0 92.3 92.5 93.8 94.7 94.7 95.1 95.1 95.3 95.4 GE 97.0 GE 800 33.7 34.3 58.3 58.3 85.4 87.3 91.6 93.5 93.6 95.4 96.3 96.3 96.7 96.7 96.9 33.7 85.4 GΕ 700 34.3 58.3 58.3 87.3 91.7 93.6 93.8 95.6 96.4 96.4 97.2 97.2 97.3 97.5 97.8 97.9 58.3 85.4 87.3 91.7 93.8 95.7 96.6 96.9 97.6 97.6 GE 600 33.7 34.3 58.3 93.9 500 33.7 34.3 58.3 58.3 85.4 87.3 92.0 94.4 94.5 96.3 97.5 97.8 98.5 98.5 98.7 98.8 GE 58.3 85.4 87.3 92.0 96.4 97.6 98.1 99.4 99.4 99.9 100.0 GE 400 33.7 34.3 58.3 94.4 94.5 GE 300 33.7 34.3 58.3 58.3 85.4 87.3 92.0 94.4 94.5 96.4 97.6 98.1 99.4 99.4 99.9 100.0 87.3 97.6 33.7 85.4 92.0 94.4 96.4 98.1 99.4 99.4 99.9 100.0 GE 200 34.3 58.3 58.3 94.5

TOTAL NUMBER OF OBSERVATIONS 676

34.3

34.3

58.3

58.3

58.3

58.3

85.4

85.4

87.3

87.3

92.0

92.0

GE

GE

100

33.7

000 33.7

94.4

94.4

94.5

94.5

96.4

97.6

96.4 97.6

98.1

98.1

99.4

99.4

99.4

99.4

99.9

100.0

99.9 100.0

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: AUG HOURS: 00-02 CEILING VISIBIATTY IN METERS IN GE GE GE GE GE GE GE GE GE. GE GE GE GE GE GE GE 90 80 60 48 32 24 20 12 10 08 06 04 00 40 16 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 7000 GE GE 6000 GE 5000 37.6 44.1 63.4 63.4 69.9 72.0 75.3 75.3 75.3 75.3 75.3 75.3 75.3 75.3 75.3 75.3 GE 4500 37.6 44.1 63.4 63.4 69.9 72.0 75.3 75.3 75.3 75.3 75.3 75.3 75.3 75.3 75.3 75.3 GE 4000 37.6 44.1 63.4 63.4 73.1 75.3 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 3500 63.4 78.5 78.5 78.5 78.5 78.5 78.5 78.5 GE 37.6 44.1 63.4 73.1 75.3 78.5 78.5 78.5 GE 3000 37.6 44.1 63.4 74.2 76.3 79.6 79.6 79.6 79.6 79.6 79.6 79.6 79.6 79.6 79.6 63.4 GE 2500 37.6 44.1 63.4 63.4 77.4 79.6 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 GE 2000 37.6 44.1 63.4 63.4 77.4 79.6 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 GE 1800 37.6 44.1 63.4 63.4 77.4 79.6 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 82.8 GE 1500 38.7 45.2 65.6 79.6 81.7 84.9 84.9 84.9 84.9 65.6 84.9 84.9 84.9 84.9 GE 1200 38.7 65.6 79.6 86.0 88.2 91.4 91.4 91.4 91.4 45.2 65.6 81.7 86.0 86.0 91.4 91.4 94.6 GE 1000 41.9 48.4 68.8 68.8 82.8 84.9 89.2 89.2 89.2 91.4 94.6 94.6 94.6 94.6 94.6 89.2 GE 900 41.9 48.4 68.8 68.8 82.8 84.9 89.2 89.2 91.4 94.6 94.6 94.6 94.6 94.6 94.6 GE 800 41.9 48.4 68.8 68.8 82.8 84.9 89.2 90.3 92.5 94.6 97.8 97.8 97.8 97.8 97.8 97.8 700 41.9 48.4 68.8 92.5 94.6 97.8 97.8 97.8 97.8 97.8 97.8 GE 68.8 82.8 84.9 89.2 90.3 GE 600 41.9 48.4 68.8 68.8 82.8 84.9 89.2 90.3 92.5 95.7 98.9 98.9 98.9 98.9 98.9 98.9 92.5 GE 500 41.9 48.4 68.8 68.8 82.8 84.9 89.2 90.3 95.7 98.9 98.9 98.9 98.9 98.9 98.9 GE 400 41.9 48.4 68.8 68.8 82.8 84.9 89.2 90.3 92.5 95.7 98.9 98.9 98.9 98.9 98.9 98.9 GE 300 41.9 48.4 68.8 68.8 82.8 84.9 89.2 90.3 92.5 95.7 98.9 98.9 98.9 98.9 98.9 98.9 GE 200 41.9 48.4 68.8 68.8 82.8 84.9 89.2 90.3 92.5 95.7 98.9 98.9 98.9 98.9 98.9 98.9 GE 100 41.9 48.4 68.8 68.8 82.8 84.9 89.2 90.3 92.5 95.7 98.9 98.9 98.9 98.9 98.9 100.0 000 41.9 48.4 68.8 68.8 82.8 84.9 89.2 90.3 92.5 95.7 98.9 98.9 98.9 98.9 98.9 100.0 GE

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: AUG HOURS: 03-05 CEILING VISIBILITY IN METERS GE TN GE CE GE GE GE GE GE GE GE GE GE GE GE GE GE 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 9000 GE GΕ 8000 GΕ 7000 GE 6000 GΕ 5000 39.8 45.2 54.8 54.8 63.4 63.4 65.6 66.7 66.7 67.7 69.9 69.9 69.9 69.9 69.9 69.9 4500 65.6 69.9 69.9 GE 39.8 45.2 54.8 54.8 63.4 63.4 66.7 66.7 67.7 69.9 69.9 69.9 69.9 GE 4000 39.8 45.2 54.8 54.8 63.4 63.4 65.6 66.7 66.7 67.7 69.9 69.9 69.9 69.9 69.9 69.9 GE 3500 39.8 45.2 54.8 54.8 63.4 65.6 66.7 66.7 67.7 69.9 69.9 69.9 69.9 69.9 63.4 69.9 GE 3000 39.8 45.2 54.8 54.8 68.8 68.8 72.0 73.1 73.1 74.2 76.3 76.3 76.3 76.3 76.3 76.3 2500 47.3 58.1 76.3 77.4 79.6 79.6 79.6 79.6 GE 41.9 58.1 72.0 72.0 75.3 76.3 79.6 79.6 GE 2000 41.9 47.3 58.1 58.1 74.2 74.2 77.4 78.5 78.5 79.6 81.7 81.7 81.7 81.7 81.7 81.7 GE 1800 41.9 47.3 58.1 58.1 74.2 74.2 77.4 78.5 78.5 79.6 81.7 81.7 81.7 81.7 81.7 GE 1500 78.5 79.6 41.9 47.3 58.1 58.1 75.3 75.3 79.6 80.6 82.8 82.8 82.8 82.8 82.8 82.8 GE 1200 41.9 47.3 58.1 58.1 75.3 75.3 80.6 81.7 81.7 82.8 87.1 88.2 88.2 88.2 88.2 88.2 76.3 GE 1000 41.9 47.3 58.1 58.1 75.3 81.7 82.8 82.8 83.9 88.2 89.2 89.2 89.2 89.2 89.2 GE 900 41.9 47.3 58.1 58.1 75.3 76.3 81.7 82.8 82.8 83.9 88.2 89.2 89.2 89.2 89.2 89.2 GE 47.3 58.1 75.3 83.9 90.3 91.4 91.4 800 41.9 58.1 76.3 81.7 83.9 86.0 91.4 91.4 91.4 GE 700 41.9 47.3 58.1 58.1 75.3 76.3 81.7 83.9 83.9 87.1 91.4 92.5 92.5 92.5 92.5 92.5 GE 600 41.9 47.3 58.1 58.1 75.3 76.3 81.7 83.9 83.9 90.3 94.6 95.7 95.7 95.7 95.7 95.7 GE 500 41.9 47.3 58.1 58.1 75.3 76.3 81.7 83.9 83.9 90.3 94.6 95.7 95.7 95.7 95.7 95.7 GΕ 400 41.9 47.3 58.1 58.1 75.3 76.3 81.7 83.9 83.9 90.3 94.6 95.7 95.7 95.7 95.7 95.7 GE 300 41.9 47.3 58.1 58.1 75.3 76.3 81.7 83.9 83.9 90.3 94.6 95.7 95.7 95.7 95.7 95.7 GE 200 41.9 47.3 58.1 58.1 75.3 76.3 81.7 83.9 83.9 90.3 94.6 97.8 97.8 98.9 98.9 98.9 GE 100 41.9 47.3 58.1 58.1 75.3 76.3 81.7 83.9 83.9 90.3 94.6 97.8 97.8 98.9 98.9 100.0

TOTAL NUMBER OF OBSERVATIONS 93

47.3

58.1

58.1

75.3

76.3

81.7

000 41.9

83.9

90.3

94.6

97.8

97.8

98.9

98.9 100.0

83.9

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: AUG HOURS: 06-08 CEILING VISIBILITY IN METERS GE TN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 GE 5000 44.1 45.2 55.9 55.9 58.1 58.1 58.1 58.1 58.1 58.1 59.1 59.1 59.1 59.1 59.1 59.1 GΕ 4500 44.1 45.2 55.9 55.9 58.1 58.1 58.1 58.1 58.1 58.1 59.1 59.1 59.1 59.1 59.1 59.1 4000 45.2 58.1 60.2 60.2 GE 46.2 58.1 60.2 60.2 60.2 60.2 61.3 61.3 61.3 61.3 61.3 61.3 GE 3500 46.2 47.3 60.2 60.2 62.4 62.4 52.4 62.4 62.4 62.4 63.4 63.4 63.4 63.4 63.4 63.4 74.2 GE 3000 49.5 50.5 65.6 65.6 69.9 71.0 72.0 72.0 74.2 72.0 72.0 74.2 74.2 74.2 74.2 GE 2500 49.5 50.5 65.6 65.6 69.9 73.1 74.2 74.2 74.2 74.2 76.3 76.3 76.3 76.3 76.3 76.3 2000 49.5 50.5 66.7 66.7 71.0 71.2 75.3 78.5 78.5 78.5 GE 76.3 76.3 76.3 78.5 78.5 78.5 50.5 66.7 GE 1800 49.5 66.7 71.0 74.2 75.3 76.3 76.3 76.3 78.5 78.5 78.5 78.5 78.5 78.5 GE 1500 49.5 50.5 67.7 67.7 72.0 75.3 76.3 77.4 78.5 78.5 81.7 81.7 81.7 81.7 81.7 81.7 50.5 67.7 67.7 75.3 88.2 1200 49.5 72.0 GE 76.3 77.4 78.5 80.6 88.2 88.2 88.2 88.2 88.2 GE 1000 50.5 51.6 69.9 69.9 74.2 77.4 78.5 79.5 33.9 91.4 91.4 91.4 91.4 91.4 80.6 91.4 50.5 51.6 69.9 69.9 77.4 GE 900 74.2 78.5 79.6 80.6 83.9 91.4 91.4 91.4 91.4 91.4 91.4 GE 800 50.5 51.6 69.9 69.9 74.2 77.4 78.5 79.6 80.6 83.9 91.4 92.5 92.5 92.5 92.5 92.5 GE 700 50.5 51.6 69.9 69.9 74.2 77.4 78.5 79.6 80.6 83.9 91.4 93.5 93.5 93.5 93.5 93.5 GE 600 50.5 51.6 69.9 69.9 74.2 77.4 78.5 79.6 80.6 84.9 92.5 94.6 94.6 94.6 94.6 94.6 500 50.5 69.9 74.2 77.4 GE 51.6 69.9 78.5 79.6 80.6 84.9 92.5 94.6 94.6 94.6 94.6 94.6 GE 400 50.5 51.6 69.9 69.9 74.2 77.4 78.5 79.6 80.6 84.9 94.6 96.8 98.9 98.9 98.9 98.9 300 50.5 51.6 69.9 69.9 74.2 77.4 GΕ 78.5 79.6 84.9 94.6 97.8 100.0 100.0 100.0 100.0 80.6 GE 200 50.5 51.6 69.9 69.9 74.2 77.4 78.5 79.6 80.6 84.9 94.6 97.8 100.0 100.0 100.0 100.0 GE 100 50.5 51.6 69.9 69.9 74.2 77.4 78.5 79.6 80.6 84.9 94.6 97.8 100.0 100.0 100.0 100.0 000 50.5 51.6 69.9 69.9 74.2 77.4 78.5 79.6 80.6 84.9 94.6 97.8 100.0 100.0 100.0 100.0 ......

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9 MONTH: AUG HOURS: 09-11 CEILING VISIBILITY IN METERS GE GE IN GE GE GE GE GE GE GE GE GE GΕ GE GE GE GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 64.5 GE. 5000 54.8 56.5 58.1 58.1 61.3 61.3 61.3 62.9 64.5 64.5 64.5 64.5 64.5 56.5 58.1 58.1 61.3 62.9 64.5 64.5 64.5 64.5 64.5 64.5 64.5 64.5 GE 4500 54.8 61.3 61.3 GE 4000 59.7 61.3 52.9 62.9 €5.1 66.1 66.1 67.7 69.4 71.0 71.0 71.0 71.0 71.0 71.0 71.0 GE 3500 64.5 66.1 21.7 67.7 71.0 71.0 71.0 75.8 77.4 79.0 79.0 79.0 79.0 79.0 79.0 79.0 85.5 3000 67.7 69.4 75.8 82.3 83.9 85.5 85.5 85.5 85.5 85.5 85.5 GE. 66.1 69.4 74.2 74.2 GF. 67.7 69.4 69.4 74.2 74.2 75.8 82.3 83.9 85.5 85.5 85.5 85.5 85.5 85.5 85.5 2500 66.1 GE 2000 66.1 67.7 69.4 69.4 74.2 75.8 80.6 88.7 90.3 91.9 91.9 91.9 91.9 91.9 91.9 91.9 67.7 69.4 74.2 75.8 80.6 88.7 90.3 91.9 91.9 91.9 91.9 91.9 91.9 GĒ 1800 66.1 69.4 91.9 67.7 69.4 69.4 75.8 82.3 90.3 ¢1.9 93.5 95.2 95.2 95.2 GE 1500 66.1 74.2 95.2 95.2 95.2 GE 1200 66.1 67.7 69.4 69.4 74.2 75.8 82.3 90.3 93.5 95.2 96.8 96.8 96.8 96.8 96.8 96.8 CE 67.7 69.4 74.2 75.8 90.3 93.5 95.2 96.8 96.8 1000 66.1 69.4 82.3 96.8 96.8 96.8 96.8 GE 900 66.1 67.7 69.4 69.4 74.2 75.8 82.3 90.3 93.5 95.2 96.8 96.8 96.8 96.8 96.8 96.8 GE 800 66.1 67.7 69.4 69.4 74.2 75.8 82.3 90.3 93.5 95.2 96.8 96.8 96.8 96.8 96.8 96.8 67.7 69.4 69.4 95.2 96.8 96.8 GE 700 56.1 74.2 75.8 82.3 90.3 93.5 96.8 96.8 96.8 96.8 67.7 69.4 77.4 79.0 98.4 100.0 100.0 100.0 100.0 100.0 100.0 GE 600 66.1 69.4 85.5 93.5 96.8 GE 500 66.1 67.7 69.4 69.4 77.4 79.0 85.5 93.5 96.8 98.4 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 66.1 67.7 69.4 69.4 77.4 79.0 85.5 93.5 96.8 98.4 100.0 100.0 100.0 100.0 100.0 100.0 98.4 100.0 100.0 100.0 100.0 100.0 300 56.1 67.7 69.4 69.1 77.4 79.0 85.5 93.5 GE 96.8 GE 200 65.1 67.7 69.4 69.4 77.4 79.0 85.5 93.5 96.8 98.4 100.0 100.0 100.0 100.0 100.0 100.0 67.7 77.4 79.0 93.5 98.4 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 66.1 69.4 69.4 85.5 96.8 GE 000 66.1 67.7 69.4 69.4 77.4 79.0 85.5 93.5 96.8 98.4 100.0 100.0 100.0 100.0 100.0

#### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: AUG HOURS: 12-14 VISIBILITY IN METERS CEILING IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE. GE GE 60 40 FEET 112 90 80 48 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE8000 7000 GE 6000 GE 5000 60.2 60.2 66.7 68.8 68.8 68.8 68.8 68.8 68.8 68.8 68.8 68.8 68.8 68.8 GE 54.8 GE 4500 51.6 54.8 60.2 60.2 66.7 68.8 68.8 68.8 68.8 68.8 68.8 68.8 69.8 68.8 68.8 68.8 71.0 71.0 71.0 71.0 71.0 GE 4000 53.8 57.0 62.4 62.4 68.8 71.0 71.0 71.0 71.0 71.0 71.0 3500 59.1 62.4 67.7 67.7 76.3 78.5 79:6 79.6 79.6 79.6 79.6 79.6 79.6 79.6 79.6 79.6 GE 87.1 87.1 87.1 87.1 87.1 87.1 87.1 GE 3000 63.4 66.7 72.0 72.0 80.6 82.8 87.1 87.1 87.1 GE 2500 63.4 66.7 73.1 73.1 84.9 88.2 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 92.5 GE 2000 63.4 66.7 73.1 73.1 87.1 90.3 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 87.1 73.1 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 GE 1800 63.4 66.7 73.1 90.3 94.6 94.6 1500 63.4 66.7 73.1 73.1 87.1 90.3 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 GE 66.7 73.1 73.1 87.1 90.3 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 GE 1200 63.4 GE 1000 63.4 66.7 73.1 73.1 87.1 90.3 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 900 63.4 66.7 73.1 73.1 87.1 90.3 94.6 94.6 94.6 96.8 96.8 96.8 96.8 96.8 96.8 96.8 GE 96.8 96.8 96.8 GE 800 63.4 66.7 73.1 73.1 87.1 90.3 94.6 94.6 94.6 96.8 96.8 96.8 96.8 GE 700 63.4 66.7 73.1 73.1 88.2 91.4 95.7 95.7 95.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 63.4 91.4 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 600 66.7 73.1 73.1 88.2 96.8 96.8 GE 500 63.4 66.7 73.1 73.1 88.2 91.4 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 63.4 73.1 88.2 91.4 96.8 96.8 96.8 100.0 GE 400 66.7 73.1 GE 300 63.4 66.7 73.1 73.1 88.2 91.4 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 63.4 66.7 73.1 73.1 88.2 91.4 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 63.4 66.7 73.1 73.1 88.2 91.4 96.8 96.8 GE 100 000 63.4 66.7 73.1 73.1 88.2 91.4 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: AUG HOURS: 15-17

| CEI        | LING           |               | • • • • • • • | • • • • • •   | • • • • • • • | ,             | /ISIBIL      | TY IN I      | 1ETERS        |              |               | •••••        | • • • • • • • |              | • • • • • • • |               | • • • • • •  |
|------------|----------------|---------------|---------------|---------------|---------------|---------------|--------------|--------------|---------------|--------------|---------------|--------------|---------------|--------------|---------------|---------------|--------------|
|            | N              | GE            | GE            | GE            | GE            | GE            | GE           | GÉ           | GE            | GE           | GE            | GE           | GE            | GE           | GE            | GE            | GE           |
| FE         | ET             | 112           | 90            | 80            | 60            | 48            | 40           | 32           | 24            | 20           | 16            | 12           | 10            | 08           | 06            | 04            | 00           |
|            |                |               |               |               |               |               |              |              |               | · • • • • •  |               |              |               |              |               |               |              |
|            |                |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
| NO         | CEIL           |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
|            |                |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
|            | 20000          |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
|            | 18000          |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
|            | 16000          |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
|            | 14000<br>12000 |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
| GE         | 12000          |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
| GE         | 10000          |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
| GE         | 9000           |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
| GE         | 8000           |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
| GE         | 7000           | 1             |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
| GE         | 6000           | ľ             |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
|            |                |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
| GE         | 5000           | 58.1          | 59.1          | 66.7          | 66.7          | 69.9          | 69.9         | 69.9         | 69.9          | 69.9         | 69.9          | 69.9         | 69.9          | 69.9         | 69.9          | 69.9          | 69.9         |
| GE         | 4500           | 59.1          | 60.2          | 67.7          | 67.7          | 72.0          | 72.0         | 72.0         | 72.0          | 72.0         | 72.0          | 72.0         | 72.0          | 72.0         | 72.0          | 72.0          | 72.0         |
| GΕ         | 4000           | 60.2          | 61.3          | 68.8          | 68.8          | 74.2          | 74.2         | 74.2         | 74.2          | 74.2         | 74.2          | 74.2         | 74.2          | 74.2         | 74.2          | 74.2          | 74.2         |
| GE         | 3500           | 64.5          | 65.6          | 74.2          | 74.2          | 80.6          | 80.6         | 80.6         | 80.6          | 80.6         | 80.6          | 80.6         | 80.6          | 80.6         | 80.6          | 80.6          | 80.6         |
| GE         | 3000           | 67.7          | 68.8          | 79.6          | 79.6          | 86.0          | 86.0         | 87.1         | 87.1          | 87.1         | 87.1          | 87.1         | 87.1          | 87.1         | 87.1          | 87.1          | 87.1         |
| <b>a</b> n | 25.00          | 67.7          | 60.0          | 70.6          | 70.6          | 00.0          | 00.0         | 02 5         | 00 5          | 00 5         | 02.5          | 03.5         | 03.5          | 03 E         | 03.5          | 03 5          | 03 5         |
| GE<br>GE   | 2500<br>2000   | 67.7<br>67.7  | 68.8<br>68.8  | 79.6<br>79.6  | 79.6<br>79.6  | 88.2<br>88.2  | 88.2<br>88.2 | 92.5<br>92.5 | 92.5<br>92.5  | 92.5<br>92.5 | 93.5<br>93.5  | 93.5<br>93.5 | 93.5<br>93.5  | 93.5<br>93.5 | 93.5<br>93.5  | 93.5<br>93.5  | 93.5<br>93.5 |
| GE         | 1800           | 69.9          | 71.0          | 81.7          | 81.7          | 90.3          | 90.3         | 94.6         | 94.6          | 94.6         | 95.7          | 95.7         | 95.7          | 95.7         | 95.7          | 95.7          | 95.7         |
| GE         | 1500           | 71.0          | 72.0          | 82.8          | 82.8          | 91.4          | 91.4         | 95.7         | 95.7          | 95.7         | 96.8          | 96.8         | 96.8          | 96.8         | 96.8          | 96.8          | 96.8         |
| GE         | 1200           | 71.0          | 72.0          | 82.8          | 82.8          | 91.4          | 91.4         | 95.7         | 95.7          | 95.7         | 96.8          | 96.8         | 96.8          | 96.8         | 96.8          | 96.8          | 96.8         |
| QD.        | 12.00          | '1.0          | ,,,,          | 02.0          | 02.0          | 21.4          | 31.4         | 3347         | 33.,          | 33.7         | 30.0          | ,,,,         | ,,,,          | 30.0         | 30.0          | 30.0          | 3000         |
| GE         | 1000           | 72.0          | 73.1          | 83.9          | 83.9          | 92.5          | 92.5         | 96.8         | 96.8          | 96.8         | 97.8          | 97.8         | 97.8          | 97.8         | 97.8          | 97.8          | 97.8         |
| GE         | 900            | 72.0          | 73.1          | 83.9          | 83.9          | 92.5          | 92.5         | 96.8         | 96.8          | 96.8         | 98.9          | 98.9         | 98.9          | 98.9         | 98.9          | 98.9          | 98.9         |
| GE         | 800            | 72.0          | 73.1          | 83.9          | 83.9          | 92.5          | 92.5         | 96.8         | 96.8          | 96.8         | 98.9          | 98.9         | 98.9          | 98.9         | 98.9          | 98.9          | 98.9         |
| GE         | 700            | 72.0          | 73.1          | 84.9          | 84.9          | 93.5          | 93.5         | 97.8         | 97.8          | 97.8         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0         | 100.0         | 100.0        |
| GE         | 600            | 72.0          | 73.1          | 84.9          | 84.9          | 93.5          | 93.5         | 97.8         | 97.8          | 97.8         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0         | 100.0         | 100.0        |
|            |                |               |               |               |               |               |              |              |               |              |               |              |               |              |               |               |              |
| GE         | 500            | 72.0          | 73.1          | 84.9          | 84.9          | 93.5          | 93.5         | 97.8         | 97.8          | 97.8         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0         | 100.0         | 100.0        |
| GE         | 400            | 72.0          | 73.1          | 84.9          | 84.9          | 93.5          | 93.5         | 97.8         | 97.8          | 97.8         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0         | 100.0         | 100.0        |
| GE         | 300            | 72.0          | 73.1          | 84.9          | 84.9          | 93.5          | 93.5         | 97.8         | 97.8          | 97.8         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0         | 100.0         | 100.0        |
| GE         | 200            | 72.0          | 73.1          | 84.9          | 84.9          | 93.5          | 93.5         | 97.8         | 97.8          | 97.8         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0         | 100.0         | 100.0        |
| GE         | 100            | 72.0          | 73.1          | 84.9          | 84.9          | 93.5          | 93.5         | 97.8         | 97.8          | 97.8         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0         | 100.0         | 100.0        |
| an.        | 000            | 72.6          | 73.1          | 04.6          | 04.0          | 03 F          | 02 5         | 07.0         | 07.0          | 07.0         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0         | 100.0         | 100.0        |
| GE         | 000            | 72.0          | 73.1          | 84.9          | 84.9          | 93.5          | 93.5         | 97.8         | 97.8          | 97.8         | 100.0         | 100.0        | 100.0         | 100.0        | 100.0         | 100.0         | 100.0        |
| • • •      | • • • • • •    | • • • • • • • | • • • • • • • | • • • • • • • |               | · · · · · · · |              |              | • • • • • • • |              | • • • • • • • |              |               |              | • • • • • • • | • • • • • • • | • • • • • •  |

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: AUG HOURS: 18-20 LST TO UTC: - 9 CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE. 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GΕ 7000 GE 6000 75.3 75.3 75.3 75.3 75.3 75.3 GE 5000 53.8 58.1 64.5 64.5 75.3 75.3 75.3 75.3 75.3 75.3 75.3 GE 4500 53.8 58.1 64.5 64.5 75.3 75.3 75.3 75.3 75.3 75.3 75.3 75.3 75.3 75.3 75.3 GΕ 4000 55.9 60.2 66.7 66.7 77.4 77.4 77.4 77.4 77.4 77.4 77.4 77.4 77.4 77.4 77.4 77.4 3500 80.6 80.6 80.6 80.6 80.6 80.6 80.6 80.6 80.6 GE 57.0 61.3 69.9 69.9 80.6 80.6 80.6 GE 3000 61.3 65.6 76.3 76.3 87.1 87.1 87.1 87.1 87.1 87.1 87.1 87.1 87.1 87.1 87.1 87.1 88.2 88.2 65.6 87.1 87.1 88.2 88.2 88.2 88.2 88.2 8.2 88.2 88.2 GE 2500 61.3 76.3 76.3 90.3 GE 2000 61.3 65.6 78.5 78.5 89.2 89.2 90.3 90.3 90.3 90.3 90.3 90.3 90.3 90.3 90.3 1800 61.3 65.6 78.5 78.5 89.2 89.2 90.3 90.3 90.3 90.3 90.3 90.3 90.3 90.3 90.3 90.3 GE 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 GE 1500 62.4 66.7 80.6 80.6 93.5 93.5 94.6 GE 1200 62.4 66.7 80.6 80.6 94.6 94.6 95.7 95.7 95.7 97.8 97.8 97.8 97.8 97.8 97.8 97.8 GE 1000 62.4 66.7 80.6 80.6 94.6 94.6 95.7 95.7 95.7 97.8 97.8 97.8 98.9 98.9 98.9 98.9 GE 900 62.4 66.7 80.6 80.6 94.6 94.6 95.7 95.7 95.7 97.8 97.8 97.8 98.9 98.9 98.9 98.9 62.4 66.7 80.6 95.7 95.7 96.8 96.8 96.8 98.9 98.9 98.9 100.0 100.0 100.0 100.0 GE. 800 80.6 GE 700 62.4 66.7 80.6 80.6 95.7 95.7 96.8 96.8 96.8 98.9 98.9 98.9 100.0 100.0 100.0 100.0 600 62.4 66.7 80.6 80.6 95.7 95.7 96.8 96.8 96.8 98.9 98.9 98.9 100.0 100.0 100.0 100.0 GE GE 500 62.4 66.7 80.6 80.6 95.7 95.7 96.8 96.8 96.8 98.9 98.9 98.9 100.0 100.0 100.0 100.0 96.8 98.9 98.9 98.9 100.0 100.0 100.0 100.0 400 62.4 66.7 80.6 95.7 95.7 96.8 96.8 GE 80.6 GE 300 62.4 66.7 80.6 80.6 95.7 95.7 96.8 96.8 96.8 98.9 98.9 98.9 100.0 100.0 100.0 100.0 200 62.4 66.7 80.6 80.6 95.7 95.7 96.8 96.8 96.8 98.9 98.9 98.9 100.0 100.0 100.0 100.0 GE 98.9 98.9 98.9 100.0 100.0 100.0 100.0 GE 100 62.4 66.7 80.6 80.6 95.7 95.7 96.8 96.8 96.8 000 62.4 66.7 95.7 95.7 96.8 96.8 98.9 98.9 98.9 100.0 100.0 100.0 100.0 GE 80.6 80.6 96.8

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: AUG HOURS: 21-23 VISIBILITY IN METERS CEILING IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 9000 GE 8000 GE GE 7000 6000 GΕ GE 5000 45.2 51.6 64.5 64.5 77.4 79.6 81.7 83.9 83.9 83.9 83.9 83.9 83.9 83.9 83.9 83.9 45.2 51.6 77.4 GE 4500 64.5 64.5 79.6 81.7 83.9 83.9 83.9 83.9 83.9 83.9 83.9 83.9 83.9 GE 4000 45.2 51.6 64.5 64.5 77.4 79.6 81.7 83.9 83.9 83.9 83.9 83.9 83.9 83.9 83.9 83.9 GE 3500 45.2 51.6 65.6 65.6 79.6 81.7 83.9 86.0 86.0 86.0 86.0 86.0 86.0 86.0 86.0 86.0 3000 45.2 87.1 GE 51.6 66.7 66.7 80.6 82.8 84.9 87.1 87.1 87.1 87.1 87.1 87.1 GE 2500 45.2 51.6 66.7 66.7 82.8 84.9 87.1 89.2 89.2 90.3 90.3 90.3 90.3 90.3 90.3 90.3 GE 2000 45.2 51.6 66.7 66.7 82.8 84.9 87.1 89.2 89.2 90.3 90.3 90.3 90.3 90.3 90.3 90.3 93.5 1800 90.3 93.5 93.5 93.5 GE 45.2 51.6 66.7 66.7 86.0 88.2 92.5 92.5 93.5 93.5 93.5 93.5 GE 1500 45.2 51.6 66.7 66.7 86.0 88.2 90.3 92.5 92.5 93.5 93.5 93.5 93.5 93.5 93.5 GE 1200 45.2 51.6 66.7 66.7 87.1 89.2 91.4 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 1000 45.2 51.6 66.7 66.7 87.1 89.2 91.4 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 GE 900 45.2 51.6 66.7 66.7 87.1 89.2 91.4 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 800 45.2 51.6 66.7 66.7 87.1 89.2 91.4 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 700 45.2 51.6 66.7 66.7 87.1 89.2 91.4 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 600 45.2 51.6 91.4 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 66.7 66.7 87.1 89.2 GE 500 45.2 51.6 66.7 66.7 87.1 89.2 91.4 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 98.9 100.0 100.0 100.0 93.5 400 45.2 51.6 66.7 66.7 87.1 89.2 91.4 93.5 100.0 100.0 100.0 GE GE 300 45.2 51.6 66.7 66.7 87.1 89.2 91.4 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 45.2 51.6 66.7 66.7 87.1 89.2 91.4 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 100 45.2 51.6 93.5 98.9 100.0 100.0 100.0 100.0 100.0 GE 66.7 66.7 87.1 89.2 91.4 93.5 000 45.2 51.6 66.7 66.7 87.1 89.2 91.4 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 GE

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATICN NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: AUG HOURS: ALL

|       |             |             |               | 551           | 10 010        | •             |               |               |               |               | non in.       | noo no        | orto. Hu      |               |             |             |             |
|-------|-------------|-------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|-------------|-------------|-------------|
| • • • | • • • • •   | • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • •   | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • •   | • • • • • •   |               |               | • • • • • • | • • • • • • | • • • • • • |
|       | LING        |             |               |               |               |               |               | ITY IN I      |               |               |               |               |               |               |             |             |             |
| I     | N           | GE          | GE            | GE            | GE            | GE            | GE            | GE            | GE            | GE            | GE            | GΕ            | GE            | GE            | GE          | Œ           | GE          |
| FE    | ET          | 112         | 90            | 80            | 60            | 48            | 40            | 32            | 24            | 20            | 16            | 12            | 10            | 80            | 06          | 04          | 00          |
|       |             |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
|       | - 1         |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
| NO    | CEIL        |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
|       |             |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
| GE    | 20000       |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
|       | 18000       |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
|       | 16000       |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
|       | 14000       |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
|       | 12000       |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
| GE    | 12000       |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
|       |             |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
|       | 10000       |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
| GE    | 9000        |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
| GE    | 8000        |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
| GE    | 7000        |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
| GE    | 6000        |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
|       |             | •           |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
| GE    | 5000        | 47.8        | 51.6          | 61.2          | 61.2          | 68.0          | 68.9          | 69.8          | 70.4          | 70.5          | 70.7          | 71.1          | 71.1          | 71.1          | 71.1        | 71.1        | 71.1        |
| GE    | 4500        | 48.0        | 51.8          | 61.3          | 61.3          | 68.3          | 69.1          | 70.1          | 70.7          | 70.8          | 71.0          | 71.4          | 71.4          | 71.4          | 71.4        | 71.4        | 71.4        |
| GE    | 4000        | 49.2        | 53.0          | 62.7          | 62.7          | 70.3          | 71.1          | 72.1          | 72.7          | 72.8          | 73.1          | 73.5          | 73.5          | 73.5          | 73.5        | 73.5        | 73.5        |
| GE    | 3500        | 51.2        | 55.0          | 65.4          | 65.4          | 73.5          | 74.3          | 75.5          | 76.3          | 76.4          | 76.7          | 77.1          | 77.1          | 77.1          | 77.1        | 77.1        | 77.1        |
| GE    | 3000        | 53.3        | 57.1          | 68.4          | 68.4          | 77.8          | 78.8          | 80.9          | 81.9          | 82.0          | 82.3          | 82.9          | 82.9          | 82.9          | 82.9        | 82.9        | 82.9        |
|       |             |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
| GE    | 2500        | 53.6        | 57.4          | 69.0          | 69.0          | 79.8          | 81.2          | 83.9          | 84.9          | 85            | 85.6          | 86.1          | 86.1          | 86.1          | 86.1        | 86.1        | 86.1        |
| GE    | 2000        | 53.6        | 57.4          | 69.4          | 69.4          | 80.8          | 82.3          | 85.3          | 86.5          | 86.           | 87.2          | 87.8          | 87.8          | 87.8          | 87.8        | 87.8        | 87.8        |
| GE    | 1800        | 53.9        | 57.6          | 69.7          | 69.7          | 81.5          | 83.0          | 86.0          | 87.2          | 87.4          | 87.9          | 88.5          | 88.5          | 88.5          | 88.5        | 88.5        | 88.5        |
| GE    | 1500        | 54.3        | 58.1          | 70.5          | 70.5          | 82.7          | 84.3          | 87.4          | 88.6          | 88.9          | 89.5          | 90.3          | 90.3          | 90.3          | 90.3        | 90.3        | 90.3        |
| GE    | 1200        | 54.3        | 58.1          | 70.5          | 70.5          | 83.0          | 84.6          | 88.1          | 89.3          | 89.8          | 91.7          | 94.0          | 94.1          | 94.1          | 94.1        | 94.1        | 94.1        |
| GE    | 1200        | 34.3        | 30.1          | /0.5          | 70.5          | 03.0          | 04.0          | 00.1          | 69.3          | 09.0          | 91./          | 94.0          | 94.1          | 94.1          | 94.1        | 94.1        | 94.1        |
| ~~    |             |             |               | 71 4          | ~4            | 03.0          | 05.6          | 00.1          |               | 00.7          |               | 05.1          | 05.0          | 05.4          | 05.4        | 05.4        |             |
| GE    | 1000        | 55.0        | 58.8          | 71.4          | 71.4          | 83.9          | 85.6          | 89.1          | 90.3          | 90.7          | 92.8          | 95.1          | 95.2          | 95.4          | 95.4        | 95.4        | 95.4        |
| GE    | 900         | 55.0        | 58.8          | 71.4          | 71.4          | 83.9          | 85.6          | 89.1          | 90.3          | 90.7          | 93.3          | 95.5          | 95.7          | 95.8          | 95.8        | 95.8        | 95.8        |
| GE    | 800         | 55.0        | 58.8          | 71.4          | 71.4          | 84.0          | 85.7          | 89.2          | 90.7          | 91.4          | 94.1          | 96.4          | 96.6          | 96.8          | 96.8        | 96.8        | 96.8        |
| GE    | 700         | 55.0        | 58.8          | 71.5          | 71.5          | 84.3          | 86.0          | 89.5          | 91.0          | 91.7          | 94.7          | 96.9          | 97.3          | 97.5          | 97.5        | 97.5        | 97.5        |
| GE    | 600         | 55.0        | 58.8          | 71.5          | 71.5          | 84.6          | 86.3          | 89.9          | 91.4          | 92.1          | 95.8          | 98.0          | 98.5          | 98.6          | 98.6        | 98.6        | 98.6        |
|       |             |             |               |               |               |               |               |               |               |               |               |               |               |               |             |             |             |
| GE    | 500         | 55.0        | 58.8          | 71.5          | 71.5          | 84.6          | 86.3          | 89.9          | 91.4          | 92.1          | 95.8          | 98.0          | 98.5          | 98.6          | 98.6        | 98.6        | 98.6        |
| GE    | 400         | 55.0        | 58.8          | 71.5          | 71.5          | 84.6          | 86.3          | 89.9          | 91.4          | 92.1          | 95.8          | 98.3          | 98.7          | 99.2          | 99.2        | 99.2        | 99.2        |
| GE    | 300         | 55.0        | 58.8          | 71.5          | 71.5          | 84.6          | 86.3          | 89.9          | 91.4          | 92.1          | 95.8          | 98.3          | 98.9          | 99.3          | 99.3        | 99.3        | 99.3        |
| GE    | 200         | 55.0        | 58.8          | 71.5          | 71.5          | 84.6          | 86.3          | 89.9          | 91.4          | 92.1          | 95.8          | 98.3          | 99.2          | 99.6          | 99.7        | 99.7        | 99.7        |
| GE    | 100         | 55.0        | 58.8          | 71.5          | 71.5          | 84.6          | 86.3          | 89.9          | 91.4          | 92.1          | 95.8          | 98.3          | 99.2          | 99.6          | 99.7        | 99.7        | 100.0       |
| QL.   | 100         | 33.3        | 50.5          |               |               | 0             |               | ~,,,          | 74.4          | ~ · · ·       | ,,,,,         | ,,,,          | ,, <b></b>    | ,,,,          |             |             | -00.0       |
| GE    | 000         | 55.0        | 58.8          | 71.5          | 71.5          | 84.6          | 86.3          | 89.9          | 91.4          | 92.1          | 95.8          | 98.3          | 99.2          | 99.6          | 99.7        | 99.7        | 100.0       |
| GE.   | 000         | 33.0        | 20.0          | /1.3          | /1.3          | 04.0          | 00.3          | 07.9          | 91.4          | 96.1          | 90.0          | 30.3          | 77.2          | 99.0          | 77./        | 39.7        | 100.0       |
| • • • | • • • • • • | •••••       | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • | • • • • • • | • • • • • • |

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: ~ 9 MONTH: SEP HOURS: 00-02 CEILING VISIBILITY IN METERS GE GE GE TN GE GE GE GE GE GE GE GE GE GE GE GE GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 80 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GΕ 7000 GE 6000 5000 25.6 27.8 40.0 40.0 75.6 76.7 77.8 78.9 78.9 78.9 78.9 78.9 GE 64.4 64.4 71.1 78.9 78.9 27.8 82.2 82.2 GE 4500 30.0 42.2 42.2 67.8 67.8 74.4 80.0 81.1 82.2 82.2 82.2 82.2 87.8 GE 4000 32.2 34.4 46.7 46.7 73.3 73.3 80.0 84.4 85.6 86.7 87.8 87.8 87.8 87.8 87.8 GΕ 3500 32.2 34.4 46.7 46.7 73.3 73.3 80.0 84.4 85.6 86.7 87.8 87.8 87.8 87.8 87.8 87.8 GE 3000 32.2 34.4 47.8 47.8 76.7 76.7 83.3 87.8 88.9 90.0 91.1 91.1 91.1 91.1 91.1 91.1 2500 48.9 48.9 78.9 78.9 85.6 90.0 91.1 92.2 93.3 93.3 93.3 GE 32.2 34.4 93.3 93.3 93.3 GE 2000 32.2 34.4 48.9 48.9 80.0 80.0 86.7 91.1 92.2 94.4 96.7 96.7 96.7 96.7 96.7 96.7 GE 1800 32.2 34.4 48.9 48.9 82.2 82.2 88.9 93.3 94.4 96.7 98.9 98.9 98.9 98.9 GE 1500 32.2 48.9 48.9 88.9 93.3 94.4 97.8 100.0 100.0 100.0 100.0 100.0 34.4 82.2 82.2 GΕ 1200 32.2 34.4 48.9 48.9 82.2 82.2 88.9 93.3 94.4 97.8 100.0 100.0 100.0 100.0 100.0 100.0 GE 1000 32.2 34.4 48.9 48.9 82.2 82.2 88.9 93.3 94.4 97.8 100.0 100.0 100.0 100.0 100.0 GE 900 32.2 34.4 48.9 48.9 82.2 82.2 88.9 93.3 94.4 97.8 100.0 100.0 100.0 100.0 100.0 100.0 97.8 100.0 100.0 100.0 100.0 100.0 48.9 GE 800 32.2 34.4 48.9 82.2 82.2 88.9 93.3 94.4 GE 700 32.2 34.4 48.9 48.9 82.2 82.2 88.9 93.3 94.4 97.8 100.0 100.0 100.0 100.0 100.0 GE 600 32.2 34.4 48.9 48.9 82.2 82.2 88.9 93.3 94.4 97.8 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 32.2 34.4 48.9 48.9 82.2 82.2 88.9 93.3 94.4 97.8 100.0 100.0 100.0 100.0 100.0 400 32.2 48.9 48.9 88.9 97.8 100.0 100.0 100.0 100.0 100.0 100.0 GE 34.4 82.2 82.2 93.3 94.4 GE 300 32.2 34.4 48.9 48.9 82.2 82.2 88.9 93.3 94.4 97.8 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 32.2 34.4 48.9 48.9 82.2 82.2 88.9 93.3 94.4 97.8 100.0 100.0 100.0 100.0 100.0 100.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 32.2 48.9 48.9 88.9 34.4 82.2 82.2 93.3 94.4 000 32.2 34.4 48.9 48.9 82.2 88.9 93.3 94.4 97.8 100.0 100.0 100.0 100.0 100.0 100.0 GE 82.2

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: SEP HOURS: 03-05 VISIBILITY IN METERS GΕ GE GE GE GE GE GE GE GE GE GE GE Œ GE GE GΕ IN FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 GE 5000 18.9 20.0 33.3 33.3 50.0 50.0 55.6 61.1 61.1 66.7 71.1 71.1 74.4 74.4 75.6 81.1 75.6 62.2 62.2 67.8 72.2 72.2 75.6 76.7 82.2 GΕ 4500 20.0 21.1 34.4 34.4 51.1 51.1 56.7 76.7 GE 4000 20.0 34.4 34.4 52.2 52.2 57.R 63.3 63.3 68.9 73.3 73.3 76.7 77.8 83.3 21.1 70.0 77.8 GE 3500 20.0 21.1 35.6 35.6 53.3 53.3 58.9 64.4 64.4 74.4 74.4 77.8 78.9 84.4 GE 3000 23.3 38.9 61.1 61.1 68.9 74.4 80.0 84.4 84.4 87.8 87.8 88.9 94.4 24.4 38.9 74.4 87.8 87.8 GE 2500 23.3 24.4 38.9 38.9 61.1 61.1 68.9 74.4 74.4 80.0 84.4 84.4 88.9 94.4 2000 68.9 GE 23.3 24.4 38.9 38.9 61.1 61.1 75.6 75.6 81.1 86.7 86.7 90.0 90.0 91.1 96.7 77.8 90.0 93.3 1800 23.3 71.1 77.8 83.3 90.0 93.3 94.4 100.0 GE 24.4 38.9 38.9 63.3 63.3 GΕ 1500 23.3 38.9 38.9 63.3 63.3 71.1 77.8 77.8 83.3 90.0 90.0 93.3 93.3 94.4 100.0 24.4 GE 1200 23.3 71.1 77.8 83.3 90.0 90.0 93.3 93.3 94.4 100.0 24.4 38.9 38.9 63.3 63.3 77.8 GE 1000 38.9 38.9 63.3 71.1 77.8 77.8 83.3 90.0 90.0 93.3 93.3 94.4 100.0 23.3 24.4 63.3 900 83.3 90.0 90.0 93.3 93.3 94.4 100.0 GE 23.3 38.9 38.9 63.3 63.3 71.1 77.8 77.8 24.4 GE 800 23.3 24.4 38.9 38.9 63.3 63.3 71.1 77.8 77.8 83.3 90.0 90.0 93.3 93.3 94.4 100.0 GE 700 23.3 24.4 38.9 38.9 63.3 63.3 71.1 77.8 77.8 83.3 90.0 90.0 93.3 93.3 94.4 100.0 100.0 90.0 93.3 93.3 94.4 23.3 71.1 77.8 77.8 83.3 90.0 GE 600 24.4 38.9 38.9 63.3 63.3 GΕ 500 23.3 38.9 38.9 63.3 63.3 71.1 77.8 77.8 83.3 90.0 90.0 93.3 93.3 24.4 93.3 94.4 100.0 400 90.0 93.3 GE 23.3 24.4 38.9 38.9 63.3 63.3 71.1 77.R 77.R 83.3 90.0 71.1 GΕ 300 23.3 24.4 38.9 38.9 63.3 63.3 77.8 77.8 83.3 90.0 90.0 93.3 93.3 94.4 100.0 93.3 94.4 100.0 23.3 77.8 77.8 83.3 90.0 90.0 93.3 GE 200 24.4 38.9 38.9 63.3 63.3 71.1 GΕ 100 23.3 24.4 38.9 38.9 63.3 63.3 71.1 77.8 77.8 83.3 90.0 90.0 93.3 93.3 94.4 100.0 000 23.3 63.3 94.4 100.0 71.1 77.8 77.8 83.3 90.0 90.0 93.3 93.3 GE 24.4 38.9 38.9 63.3

STATION NUMBER: 471066

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: SEP HOURS: 06-08 VISIBILITY IN METERS CEILING IN GŁ GE GE GE GE GE GE GE GE GE GE GE GE GF. GE GE 90 80 60 48 40 32 20 16 12 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 25.6 47.8 47.8 48.9 53.3 53.3 55.6 60.0 60.0 62.2 Œ 5000 24.4 31.1 31.1 62.2 62.2 71.1 GE 4500 24.4 25.6 31.1 31.1 47.8 47.8 48.9 53.3 53.3 55.6 60.0 60.0 62.2 62.2 62.2 71.1 GΕ 4000 26.7 27.8 33.3 33.3 51.1 51.1 52.2 56.7 56.7 58.9 63.3 63.3 65.6 65.6 65.6 74.4 3500 26.7 27.8 34.4 55.6 55.6 61.1 61.1 63.3 70.0 70.0 70.0 78.9 GΕ 34.4 56.7 67.8 67.8 GE 3000 26.7 27.8 34.4 34.4 57.8 57.8 58.9 63.3 63.3 65.6 70.0 70.0 72.2 72.2 72.2 81.1 27.8 57.8 57.8 66.7 71.1 71.1 73.3 73.3 GE 2500 26.7 34.4 34.4 58.9 64.4 64.4 73.3 82.2 GΕ 2000 26.7 27.8 34.4 34.4 57.8 58.9 60.0 66.7 66.7 68.9 76.7 76.7 78.9 78.9 78.9 87.8 1800 26.7 27.8 34.4 34.4 57.8 58.9 60.0 66.7 66.7 68.9 76.7 76.7 78.9 78.9 78.9 87.8 GE 78.9 1500 57.8 60.0 66.7 66.7 76.7 76.7 78.9 78.9 87.8 GE 26.7 27.8 34.4 34.4 58.9 68.9 GE 1200 26.7 27.8 34.4 34.4 57.8 58.9 60.0 66.7 66.7 68.9 76.7 76.7 78.9 78.9 78.9 87.8 GE 1000 40.7 27.8 34.4 34.4 57.8 50.9 60.0 66.7 66.7 68.9 76.7 76.7 78.9 78.9 78.9 87.8 GE 900 26.7 27.8 34.4 34.4 57.8 58.9 60.0 66.7 66.7 68.9 76.7 76.7 78.9 78.9 78.9 87.8 26.7 27.8 34.4 57.8 58.9 60.0 66.7 66.7 76.7 76.7 78.9 78.9 78.9 87.8 GE 800 34.4 68.9 GE 700 26.7 27.8 34.4 34.4 57.8 58.9 62.2 68.9 68.9 71.1 78.9 78.9 81.1 81.1 81.1 90.0 GE 600 26.7 27.8 34.4 34.4 57.8 58.9 62.2 68.9 68.9 71.1 78.9 78.9 81.1 81.1 81.1 90.0 GE 500 26.7 27.8 34.4 34.4 57.8 58.9 62.2 68.9 68.9 71.1 78.9 78.9 81.1 81.1 81.1 90.0 27.8 34.4 34.4 57.8 58.9 62.2 68.9 68.9 78.9 78.9 81.1 81.1 81.1 90.0 GE 400 26.7 71.1 GE 300 26.7 27.8 34 4 34.4 57.8 58.9 62.2 68.9 68.9 71.1 78.9 78.9 81.1 81.1 81.1 91.1

STATION NAME: CAMP CASEY/TONGDUCHON KO

TOTAL NUMBER OF OBSERVATIONS 90

27.8

27.8

27.8 34.4

34.4

34.4

34.4

34.4

34.4

57.8

57.8

57.8

58.9

58.9

58.9

62.2

62.2

62.2

GΕ

GE

GE

200

100

26.7

26.7

000 26.7

68.9

68.9

68.9

68.9

68.9

68.9

71.1

71.1

71.1

78.9

78.9

78.9

78.9

78.9

81.1

81.1

78.9 81.1 81.1

81.1

81.1

82.2 100.0

82.2 100.0

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: SEP HOURS: 09-11 CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GE GΕ GE GE GE GE GE GE 80 60 48 40 32 16 12 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 GE 5000 78.3 78.3 80.0 80.0 50.0 51.7 61.7 61.7 80.0 80.0 80.0 80.0 80.0 80.0 80.0 80.0 GE 4500 50.0 51.7 61.7 61.7 80.0 80.0 81.7 81.7 81.7 81.7 81.7 81.7 81.7 81.7 81.7 81.7 GE 4000 50.0 51.7 61.7 61.7 85.0 85.0 86.7 86.7 86.7 86.7 86.7 86.7 86.7 86.7 86.7 86.7 3500 88.3 GE 50.0 51.7 61 7 61.7 85.0 86.7 88.3 88.3 88.3 88.3 88.3 88.3 88.3 88.3 88.3 GE 3000 50.0 51.7 61.7 61.7 88.3 90.0 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 GE 2500 50.0 61.7 88.3 51.7 61.7 90.0 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 GE 2000 50.0 51.7 61.7 61.7 90.0 91.7 95:0 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 1800 50.0 GE 51.7 61.7 61.7 90.0 91.7 95.0 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 1500 50.0 51.7 61.7 61.7 90.0 91.7 95.0 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 1200 50.0 51.7 61.7 61.7 90.0 91.7 95.0 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 1000 50.0 51.7 61.7 61.7 90.0 91.7 95.0 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 900 50.0 51.7 61.7 61.7 90.0 91.7 95.0 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 800 50.0 51.7 61.7 90.0 91.7 95.0 GF 61.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 700 50.0 51.7 61.7 61.7 90.0 91.7 95.0 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 600 50.0 51.7 91.7 95.0 61.7 61.7 90.0 96.7 98.3 98.3 98.3 98.3 98.3 98.3 98.3 98.3 GE 500 50.0 51.7 61.7 61.7 90.0 91.7 95.0 96.7 98.3 98.3 98.3 98.3 98.3 98.3 98.3 98.3 GE 50.0 400 61.7 61.7 90.0 91.7 95.0 96.7 98.3 98.3 98.3 98.3 51.7 98.3 98.3 98.3 98.3 GE 300 50.0 51.7 61.7 61.7 90.0 91.7 95.0 96.7 98.3 98.3 98.3 98.3 98.3 98.3 98.3 98.3 GE 200 50.0 51.7 61.7 61.7 90.0 91.7 95.0 96.7 98.3 98.3 98.3 98.3 98.3 98.3 98.3 98.3 GE 100 50.0 51.7 61.7 61.7 90.0 91.7 95.0 96.7 98.3 98.3 98.3 98.3 98.3 98.3 98.3 100.0 GE 000 50.0 51.7 61.7 90.0 91.7 98.3 61.7 95.0 96.7 98.3 98.3 98.3 98.3 98.3 98.3 100.0

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 LST TO UTC: - 9 MONTH: SEP HOURS: 12-14 CETLING VISIBILITY IN METERS GE GE GE IN GE GE GΕ GE GE GE GE GE GE GΕ GE GE GE 112 48 40 32 24 20 16 12 10 08 06 00 FEET 90 80 60 04 NO CELL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 8000 GE 7000 GE GE 6000 85.6 85.6 85.6 85.6 85.6 85.6 85.6 85.6 85.6 85.6 85.6 GE 5000 64.4 66.7 81.1 81.1 85.6 GE 4500 64.4 66.7 81.1 81.1 85.6 85.6 85.6 85.6 85.6 85.6 85.6 85.6 85.6 85.6 85.6 85.6 GΕ 4000 67.8 70.0 84.4 84.4 93.3 93.3 93.3 93.3 93.3 93.3 93.3 93.3 93.3 93.3 93.3 93.3 93.3 93.3 93.3 93.3 93.3 3500 67.8 70.0 93.3 93.3 93.3 93.3 93.3 GE 84.4 84.4 93.3 93.3 GE 3000 67.8 70.0 84.4 84.4 93.3 93.3 94.4 94.4 94.4 94.4 94.4 94.4 94.4 94.4 94.4 94.4 97.8 97.8 97.8 70.0 84.4 95.6 95.6 96.7 96.7 96.7 97.8 97.8 97.8 97.8 GE 2500 67.8 84.4 GE 2000 67.8 70.0 84.4 84.4 95.6 95.6 96.7 96.7 96.7 97.8 97.8 97.8 97.8 97.8 97.8 97.8 67.8 95.6 96.7 97.8 97.8 97.8 97.8 97.8 97.8 97.8 GE 1800 70.0 84.4 95.6 96.7 96.7 84.4 97.8 97.R 97.8 97.8 GE 1500 67.8 70.0 84.4 84.4 95.6 95.6 96.7 96.7 96.7 97.8 97.8 97.8 GE 1200 67.8 70.0 84.4 84.4 95.6 95.6 96.7 96.7 96.7 97.8 97.8 97.8 97.8 97.8 97.8 97.8 GE 1000 67.8 70.0 84.4 84.4 96.7 96.7 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GΕ 900 67.8 70.0 84.4 84.4 96.7 96.7 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 800 67.8 70.0 96.7 96.7 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 84.4 84.4 98.9 GE 700 67.8 70.0 84.4 84.4 96.7 96.7 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GΕ 67.8 70.0 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 600 84.4 84.4 96.7 96.7 GΕ 500 67.8 70.0 84.4 84.4 96.7 96.7 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 67.8 100.0 70.0 96.7 96.7 98.9 100.0 100.0 100.0 100.0 100.0 GE 400 84.4 84.4 98.9 98.9 100.0 GE 300 67.8 70.0 84.4 84.4 96.7 96.7 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 67.8 70.0 96.7 96.7 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 84.4 84.4 100.0 100.0 100.0 100.0 100.0 GE 100 67.8 70.0 84.4 84.4 96.7 96.7 98.9 98.9 98.9 100.0 100.0 100.0 000 67.8 70.0 96.7 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 GE 84.4 84.4 96.7

STATION NUMBER: 471066

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: SEP HOURS: 15-17

CEILING VISIBILITY IN METERS GE TN GE CF GE GE GE GE GE GE GE GE GE GE GE GE GE FEET 112 90 80 60 48 40 32 20 16 12 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 GE 65.6 75.6 75.6 75.6 5000 64.4 75.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 GE 4500 64.4 65.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 75.6 83.3 GE 4000 71.1 72.2 83.3 83.3 83.3 83.3 83.3 83.3 83.3 83.3 83.3 83.3 83.3 83.3 83.3 GE 3500 74.4 86.7 86.7 73.3 86.7 86.7 86.7 86.7 86.7 86.7 86.7 86.7 86.7 86.7 86.7 86.7 GE 3000 76.7 77.8 90.0 90.0 90.0 91.1 91.1 91.1 91.1 91.1 91.1 91.1 91.1 91.1 91.1 91.1 77.8 GE 2500 76.7 90.0 90.0 90.0 91.1 91.1 91.1 91.1 92.2 92.2 92.2 92.2 92.2 92.2 92.2 94.4 GE 2000 76.7 77.8 90.0 90.0 90.0 91.1 91.1 93.3 93.3 94.4 94.4 94.4 94.4 94.4 94.4 GE 1800 76.7 77.8 90.0 90.0 90.0 91.1 91.1 93.3 93.3 94.4 94.4 94.4 94.4 94.4 94.4 94.4 GE 1500 76.7 77.8 90.0 90.0 90.0 91.1 91.1 95.6 95.6 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 1200 76.7 77.8 90.0 90.0 90.0 91.1 91.1 95.6 95.6 96.7 96.7 96.7 96.7 96.7 96.7 96.7 76.7 GE 1000 77.8 90.0 90.0 91.1 92.2 92.2 97.8 97.8 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GΕ 900 76.7 77.8 90.0 90.0 91.1 92.2 92.2 97.8 97.8 98.9 98.9 98.9 98.9 98.9 98.9 98.9

STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: - 9

TOTAL NUMBER OF OBSERVATIONS 90

77.8

77.8

77.8

77.8

77.8

77.8

77.8

77.8

90.0

90.0

90.0

90.0

90.0

90.0

90.0

90.0

77.8 90.0

90.0

90.0

90.0

90.0

90.0

90.0

90.0

90.0

90.0

91.1

91.1

92.2

92.2

92.2

92.2

92.2

92.2

92.2

92.2

93.3

93.3

93.3

93.3

93.3

93.3

92.2 93.3 93.3

92.2

92.2

93.3

93.3

93.3

93.3

93.3

93.3

97 . R

97.8

98.9

98.9

98.9

98.9

98.9

98.9

98.9

97.8

97.8

98.9

98.9

98.9

98.9

98.9

98.9

98.9

100.0

100.0

100.0

100.0

100.0

98.9 100.0

98.9

98.9

100.0

100.0

100.0

100.0

100.0

98.9

98.9

100.0 100.0

100.0 100.0

100.0 100.0

100.0

100.0

98.9

98.9

100.0

100.0

98.9

98.9

100.0

100.0

100.0

100.0

100.0 100.0 100.0 100.0

98.9 100.0 100.0 100.0 100.0 100.0 100.0

100.0

98.9

98.9

100.0 100.0

100.0 100.0

100.0 100.0

100.0 100.0

100.0 100.0

100.0 100.0

98.9

98.9

800

700

600

500

400

300

200

100

GE

GE

GΕ

GE

GE

GE

GE

GE

GE

76.7

76.7

76.7

76.7

76.7

76.7

76.7

76.7

000 76.7

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: SEP HOURS: 18-20 CEILING VISIBILITY IN METERS GE . IN GE GE GE GE GE GE GE GE GE GΕ GE GE GΕ GE GE FEET 112 80 60 48 40 32 20 16 12 10 08 06 04 00 NO CELL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 8000 GE GE 7000 GE 6000 GE 5000 63.3 63.3 83.3 83.3 84.4 84.4 84.4 84.4 84.4 84.4 84.4 84.4 84.4 84.4 84.4 84.4 GE 4500 63.3 63.3 83.3 83.3 84.4 84.4 84.4 84.4 84.4 84.4 84.4 84.4 84.4 84.4 84.4 84.4 GE 4000 67.8 67.8 87.8 87.8 88.9 88.9 88.9 88.9 88.9 88.9 88.9 88.9 88.9 88.9 GE 3500 67.8 67.8 87.8 87.8 88.9 88.9 88.9 88.9 88.9 88.9 88.9 88.9 88.9 88.9 88.9 88.9 GE 3000 70.0 70.0 93.3 93.3 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.R 97.8 GE 2500 70.0 70.0 93.3 93.3 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 98.9 GE 2000 71.1 71.1 94.4 94.4 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GE 1800 71.1 71.1 94.4 94.4 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GE 1500 71.1 71.1 94.4 94.4 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GE 1200 71.1 71.1 94.4 94.4 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 100.0 100.0 100.0 100.0 GE 1000 71.1 71.1 94.4 94.4 98.9 98.9 100.0 100.0 100.0 100.0 100.0 GE 900 71.1 71.1 94.4 94.4 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 800 71.1 71.1 94.4 94.4 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 94.4 700 GE 71.1 71.1 94.4 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 600 71.1 71.1 94.4 94.4 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 71.1 71.1 94.4 94.4 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 71.1 71.1 94.4 94.4 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 71.1 GE 300 71.1 94.4 94.4 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 71.1 71.1 94.4 94.4 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 71.1 71.1 94.4 94.4 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 000 71.1 71.1 94.4 94.4 98.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471366 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: SEP HOURS: 21-23

|         |            |           |             | • • • • • •  | • • • • • • • | • • • • • • • • |             |                |               | • • • • • •   | • • • • • • | • • • • • • | • • • • • • | • • • • • •   | • • • • • •    |                | •••••          |
|---------|------------|-----------|-------------|--------------|---------------|-----------------|-------------|----------------|---------------|---------------|-------------|-------------|-------------|---------------|----------------|----------------|----------------|
|         | LING       | 00        | an          | an           | <b>an</b>     |                 |             | ITY IN         |               | OT.           | an.         | an.         | <b>an</b>   | an.           | ar.            | ar.            | ar.            |
| II      | 1          | GE<br>112 | GE          | 80<br>GE     | 60<br>GE      | GE<br>40        | GE<br>40    | GE<br>32       | GE<br>24      | GE            | GE<br>16    | GE<br>12    | GE<br>10    | GE<br>08      | GE<br>06       | GE<br>04       | GE<br>OO       |
| FE.     | P. 1       | 112       | 90          | 80           | 60            | 48              | 40          | 32             | 24            | 20            | 10          | 12          | 10          | 08            | Vb             | 04             | 00             |
| • • • • |            |           | • • • • • • | • • • • • •  |               |                 | • • • • • • |                | • • • • • • • | • • • • • • • | • • • • • • | • • • • • • | ••••        | • • • • • • • | • • • • • • •  | • • • • • •    | • • • • • •    |
| МО      | CEIL       |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
| GE '    | 20000      |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
|         | 18000      |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
|         | 16000      |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
|         | 14000      |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
| GE      | 12000      |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
|         |            |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
|         | 10000      |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
| GE      | 9000       |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
| GE      | 8000       |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
| GE      | 7000       |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
| GE      | 6000       |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
| GE      | 5000       | 38.9      | 40.0        | 71.1         | 71.1          | 86.7            | 86.7        | 86.7           | 86.7          | 86.7          | 86.7        | 86.7        | 86.7        | b5.7          | 86.7           | 86.7           | 86.7           |
| GE      | 4500       | 38.9      | 40.0        | 71.1         | 71.1          | 86.7            | 86.7        | 86.7           | 86.7          | 86.7          | 86.7        | 86.7        | 86.7        | 86.7          | 86.7           | 86.7           | 86.7           |
| GE      | 4000       | 43.3      | 44.4        | 76.7         | 76.7          | 92.2            | 12.2        | 92.2           | 92.2          | 92.2          | 92.2        | 92.2        | 92.2        | 92.2          | 92.2           | 92.2           | 92.2           |
| GE      | 3500       | 43.3      | 44.4        | 76.7         | 76.7          | 92.2            | 92.2        | 92.2           | 92.2          | 92.2          | 92.2        | 92.2        | 92.2        | 92.2          | 92.2           | 92.2           | 92.2           |
| GE      | 3000       | 43.3      | 44.4        | 76.7         | 76.7          | 92.2            | 92.2        | 95.6           | 95.6          | 95.6          | 95.6        | 95.6        | 95.6        | 95.6          | 95.6           | 95.6           | 95.6           |
| 02      | 3000       |           | ****        | ,            | , , , ,       | JU.2            | 22.2        | 33.0           | ,,,,          |               |             | 2213        | ,,,,        |               | 33.00          | ,,,,           | 2010           |
| GE      | 2500       | 43.3      | 44.4        | 77.8         | 77.8          | 95.6            | 95.6        | 98.9           | 98.9          | 98.9          | 98.9        | 98.9        | 98.9        | 98.9          | 98.9           | 98.9           | 98.9           |
| GE      | 2000       | 43.3      | 44.4        | 77.8         | 77.8          | 95.6            | 95.6        | 98.9           | 98.9          | 98.9          | 98.9        | 98.9        | 98.9        | 98.9          | 98.9           | 98.9           | 98.9           |
| GE      | 1800       | 43.3      | 44.4        | 77.8         | 77.8          | 95.6            | 95.6        | 98.9           | 98.9          | 98.9          | 98.9        | 98.9        | 98.9        | 98.9          | 98.9           | 98.9           | 98.9           |
| GE      | 1500       | 43.3      | 44.4        | 77.8         | 77.8          | 96.7            | 96.7        | 100.0          | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0          | 100.0          | 100.0          |
| GE      | 1200       | 43.3      | 44.4        | 77.8         | 77.8          | 96.7            | 96.7        | 100.0          | 100.0         | 100.0         | 106.G       | 10(.0       | 100.0       | 100.0         | 100.0          | 100.3          | 100.0          |
|         |            |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |
| GE      | 1000       | 43.3      | 44.4        | 77.8         | 77.8          | 96.7            | 96.7        | 100.0          | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0          | 100.0          | 100.0          |
| GE      | 900        | 43.3      | 44.4        | 77.8         | 77.8          | 96.7            | 96.7        | 100.0          | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0          | 100.0          | 100.0          |
| GE      | 800        | 43.3      | 44.4        | 77.8         | 77.8          | 9F.7            | 96.7        | 100.0          | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0          | 100.0          | 100.0          |
| GE      | 700        | 43.3      | 44.4        | 77.8         | 77.8          | 96.7            | 96.7        | 100.0          | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0          | 100.0          | 100.0          |
| GE      | 600        | 43.3      | 44.4        | 77.8         | 77.8          | 96.7            | 96.7        | 100.0          | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0          | 100.0          | 100.0          |
| ar.     | E00        | 42.2      |             | 77.0         | 77.0          | 06.7            | 06.7        | 100.0          | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0          | 100.0          | 100.0          |
| GE      | 500        | 43.3      | 44.4        | 77.8         | 77.8          | 96.7            | 96.7        | 100.0          | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0          | 100.0          | 100.0          |
| GE      | 400        | 43.3      | 44.4        | 77.8         | 77.8          | 95.7            | 96.7        | 100.0          | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0          | 100.0          | 100.0          |
| GE      | 300<br>200 | 43.3      | 44.4        | 77.8<br>77.8 | 77.8<br>77.8  | 96.7<br>96.7    | 96.7        | 100.0<br>100.0 | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0<br>100.0 | 100.0<br>100.0 | 100.0<br>100.0 |
| GE      | 100        | 43.3      | 44.4        |              |               |                 | 96.7        |                |               |               | 100.0       |             | 100.0       | 100.0         |                |                |                |
| GE      | 100        | 43.3      | 44.4        | 77.8         | 77.8          | 96.7            | 96.7        | 100.0          | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0          | 100.0          | 100.0          |
| GE      | oon        | 43.3      | 44.4        | 77.8         | 77.8          | 96.7            | 96.7        | 100.0          | 100.0         | 100.0         | 100.0       | 100.0       | 100.0       | 100.0         | 100.0          | 100.0          | 100.0          |
|         |            |           | ****        |              |               |                 |             |                | 100.0         |               |             |             |             |               |                |                |                |
|         |            |           |             |              |               |                 |             |                |               |               |             |             |             |               |                |                |                |

STATION NUMBER: 471066

3500

3000

2000

1500

1200

1000

900

800

700

600

GE

GE

GE 2500

GE

GE 1800

GE

GE

GE

GE

GE

GE

GE

47.5

48.7

48.7

48.8

48.8

48.8

48.8

48.8

48.8

48.8

48.8

48.8

48.8

50.0

50.0

50.1

50.1

50.1

50.1

50.1

50.1

50.1

50.1

50.1

64.3

66.1

66.4

66.5

66.5

66.5

66.5

66.5

66.5

66.5

66.5

66.5

64.3

66.1

66.4

66.5

66.5

66.5

66.5

66.5

66.5

66.5

66.5

66.5

78.3

81.9

82.9

83.3

83.9

84.1

84.1

84.3

84.3

84.3

84.3

84.5

78.4

82.2

83.2

83.8

84.3

84.5

84.5

84.8

84.8

84.8

84.8

84.9

80.3

84.9

85.9

86.7

87.2

87.4

87.4

87.8

87.8

87.8

88.1

88.3

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: SEP HOURS: ALL

CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GE GE GE GΕ GΕ GE GE GE FEFT 112 90 80 60 40 32 10 48 24 20 04 16 12 08 06 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 8000 GE GE 7000 GE 6000 GE 59.6 59.6 71.3 73.2 77.7 77.7 5000 43.5 44.8 71.3 75.1 75.2 76.4 78.4 78.4 78.6 80.4 GE 4500 43.9 45.2 60.0 60.0 72.0 72.0 73.9 75.8 75.9 77.1 78.4 78.4 79.1 79.1 79.3 81.2 GE 4000 47.2 48.6 63.6 63.6 77.1 77.1 79.0 80.9 81.0 82.2 83.5 83.5 84.2 84.3 84.2 86.2

82.2

86.8

88.0

89.4

90.0

90.4

90.4

91.2

91.2

91.2

91.4

91.6

82.3

87.0

88.1

89.6

90.1

90.6

90 . .

91.3

91.3

91.3

91.6

91.9

83.5

88.1

89.6

91.2

^ <u>1</u>

92.

92 3

4. , 6

91.

93.0

93.3

93.6

84.8

89.4

90.9

93.2

93.9

21.5

^4.5

5.2

95.2

95.2

95.5

95.8

84.8

89.4

90.9

93.2

93.9

94.5

94.5

95.2

95.2

95.2

95.5

95.8

STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: - 9

GE 500 48.8 50.1 66.5 66.5 84.5 84.9 88.3 91.6 91.9 93.6 95.8 95.8 96.5 96.5 96.7 98.6 48.8 GE 400 50.1 66.5 66.5 84.5 84.9 88.3 91.6 91.9 93.6 95.8 95.8 96.5 96.5 96.7 98.6 GΕ 300 48.8 50.1 66.5 66.5 84.5 84.9 88.3 91.6 91.9 93.6 95.8 95.8 96.5 96.5 96.7 98.7 GE 200 48.8 50.1 66.5 66.5 84.9 88.3 91.6 84.5 91.9 93.6 95.8 95.8 96.5 96.5 96.8 98.8 GE 100 48.8 50.1 66.5 66.5 84.9 88.3 95.B 84.5 91.6 91.9 95.8 96.5 96.5 96.8 100.0 GE 000 48.8 50.1 66.5 36.5 84.5 84.9 88.3 91.6 91.9 93.6 95.8 95.8 96.5 96.5 96.8 100.0

TOTAL NUMBER OF OBSERVATIONS 690

85.5

90.1

91.6

93.9

94.6

95.2

95.2

95.9

95.9

95.9

96.2

96.5

85.5

90.1

91.6

93.9

94.6

95.2

95.2

95.9

95.9

95.9

96.2

96.5

85.7

90.3

91.7

94.1

94.8

95.4

95.4

96.1

96.1

96.1

96.4

96.7

87.5

92.2

93.6

95.9

96.7

97.2

97.2

98.0

98.0

98.0

98.3

98.6

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: OCT HOURS: 00-02 LST TO UTC: - 9 CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GΕ GE 112 FEET 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 13000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GΕ 8000 GE 7000 GE 6000 73.1 74.2 75.3 78.5 78.5 79.6 79.6 79.6 GE 5000 31.2 32.3 53.8 53.8 71.0 71.0 72.0 80.6 GΕ 4500 31.2 32.3 54.8 54.8 72.0 72.0 73.1 74.2 75.3 76.3 79.6 79.6 80.6 80.6 80.6 81.7 74.2 75.3 76.3 80.6 80.6 81.7 81.7 GE 4000 31.2 32.3 54.8 54.8 72.0 72.0 73.1 81.7 82.8 75.3 80.6 74.2 80.6 GE 3500 31.2 32.3 54.8 54.8 72.0 72.0 73.1 76.3 81.7 81.7 81.7 82.8 GE 3000 73.1 73.1 75.3 76.3 77.4 81.7 81.7 82.8 82.8 82.8 31.2 32.3 54.8 54.8 74.2 83.9 75.3 GE 2500 31.2 32.3 54.8 54.8 73.1 73.1 74.2 76.3 77.4 81.7 81.7 82.8 82.8 82.8 83.9 GΕ 2000 31.2 32.3 54.8 54.8 76.3 76.3 77.4 78.5 79.6 80.6 84.9 84.9 86.0 86.0 86.0 87.1 78.5 79.6 80.6 84.9 84.9 86.0 87.1 GE 1800 31.2 32.3 54.8 54.8 76.3 76.3 77.4 86.0 86.0 GE 1500 31.2 32.3 54.8 54.8 76.3 76.3 77.4 78.5 79.6 80.6 84.9 84.9 86.0 86.0 86.0 87.1 GE 1200 76.3 78.5 79.6 80.6 84.9 84.9 86.0 86.0 86.0 87.1 31.2 32.3 54.8 54.8 76.3 77.4 GE 1000 31.2 32.3 54.8 54.8 76.3 76.3 77.4 78.5 79.6 80.6 84.9 84.9 87.1 87.1 87.1 88.2 900 76.3 78.5 79.6 80.6 84.9 84.9 87.1 87.1 87.1 88.2 GE 31.2 32.3 54.8 54.8 76.3 77.4 78.5 GE 800 31.2 32.3 54.8 54.8 76.3 76.3 77.4 79.6 80.6 84.9 84.9 87.1 87.1 87.1 88.2 GE700 31.2 32.3 54.8 54.8 76.3 76.3 77.4 78.5 79.6 80.6 84.9 84.9 87.1 87.1 87.1 88.2 76.3 78.5 79.6 80.6 87.1 GE 600 77.4 84.9 84.9 87.1 87.1 88.2 31.2 32.3 54.8 54.8 76.3 GE 500 31.2 32.3 54.8 54.8 76.3 76.3 77.4 78.5 79.6 80.6 84.9 84.9 87.1 87.1 87.1 88.2 78.5 79.6 80.6 84.9 84.9 87.1 GE 400 31.2 32.3 54.8 54.8 76.3 76.3 77.4 87.1 87.1 88.2 76.3 GE 300 31.2 32.3 54.8 54.8 76.3 77.4 78.5 79.6 80.6 84.9 84.9 87.1 87.1 87.1 88.2 79.6 76.3 77.4 78.5 80.6 84.9 84.9 87.1 87.1 GE 200 31.2 32.3 54.8 54.8 76.3 87.1 88.2 GE, 100 31.2 32.3 54.8 54.8 76.3 76.3 77.4 78.5 79.6 80.6 84.9 84.9 87.1 87.1 88.2 100.0 79.6 78.5 000 31.2 80.6 84.9 84.9 87.1 GE 32.3 54.8 54.8 76.3 76.3 77.4 87.1 88.2 100.0

# PERCENTA; E FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: OCT HOURS: 03-05

| CE  | LING       |      | • • • • • • • | • • • • • • •                         |          | , , , , , , , | VISIBIL | ITY IN I | METERS       | • • • • • • |              |              |              | • • • • • • • | · · · · · · · |              |              |
|-----|------------|------|---------------|---------------------------------------|----------|---------------|---------|----------|--------------|-------------|--------------|--------------|--------------|---------------|---------------|--------------|--------------|
|     | (N         | GE   | GE            | GE                                    | GE       | GE            | GE      | GE       | GE           | GE          | GE           | GE           | GE           | GE            | GE            | GE           | GE           |
| F   | EET        | 112  | 90            | 80                                    | 60       | 48            | 40      | 32       | 24           | 20          | 16           | 12           | 10           | 80            | 06            | 04           | 00           |
|     |            |      | <b></b> .     | • • • • • • • • • • • • • • • • • • • |          |               |         |          |              |             |              |              |              |               |               |              |              |
|     |            |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
| NO  | CEIL       |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
|     |            |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
|     | 20000      |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
|     | 18000      |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
|     | 16000      |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
|     | 14000      |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
| GE  | 12000      |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
| GE  | 10000      |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
| GE  | 9000       |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
| GE  | 8000       |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
| GE  | 7000       |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
| GE  | 6000       |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
|     |            |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
| GE  | 5000       | 18.3 | 18.3          | 40.9                                  | 40.9     | 57.0          | 58.1    | 63.4     | 65.6         | 65.6        | 66.7         | 66.7         | 66.7         | 67.7          | 67.7          | 67.7         | 74.2         |
| GE  | 4500       | 18.3 | 18.3          | 40.9                                  | 40.9     | 58.1          | 59.1    | 64.5     | 66.7         | 66.7        | 67.7         | 67.7         | 67.7         | 68.8          | 68.8          | 68.8         | 75.3         |
| GE  | 4000       | 18.3 | 18.3          | 40.9                                  | 40.9     | 58.1          | 59.1    | 64.5     | 66.7         | 66.7        | 67.7         | 67.7         | 67.7         | 68.8          | 68.8          | 68.8         | 75.3         |
| GE  | 3500       | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 60.2    | 65.6     | 67.7         | 67.7        | 68.8         | 69.9         | 69.9         | 71.0          | 71.0          | 71.0         | 77.4         |
| GΕ  | 3000       | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 60.2    | 65.6     | 68.8         | 68.8        | 69.9         | 71.0         | 71.0         | 72.0          | 72.0          | 72.0         | 78.5         |
|     |            |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
| GE  | 2500       | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 60.2    | 65.6     | 68.8         | 68.8        | 71.0         | 72.0         | 72.0         | 73.1          | 73.1          | 73.1         | 79.6         |
| GE  | 2000       | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 62.4    | 67.7     | 71.0         | 71.0        | 73.1         | 74.2         | 74.2         | 75.3          | 75.3          | 75.3         | 81.7         |
| GE  | 1800       | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 62.4    | 67.7     | 71.0         | 71.0        | 73.1         | 74.2         | 74.2         | 75.3          | 75.3          | 75.3         | 81.7         |
| GE  | 1500       | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0         | 72.0        | 74.2         | 75.3         | 75.3         | 76.3          | 76.3          | 76.3         | 82.8         |
| GE  | 1200       | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0         | 72.0        | 74.2         | 75.3         | 75.3         | 76.3          | 76.3          | 76.3         | 82.8         |
|     |            |      |               |                                       |          |               |         |          |              |             |              |              |              |               |               |              |              |
| GE  | 1000       | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0         | 72.0        | 74.2         | 75.3         | 75.3         | 77.4          | 77.4          | 77.4         | 83.9         |
| GE  | 900        | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0         | 72.0        | 74.2         | 75.3         | 75.3         | 77.4          | 77.4          | 77.4         | 83.9         |
| GE  | 800        | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0         | 72.0        | 74.2         | 75.3         | 75.3         | 77.4          | 77.4          | 77.4         | 83.9         |
| GΞ  | 700        | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0         | 72.0        | 74.2         | 75.3         | 75.3         | 77.4          | 77.4          | 77.4         | 83.9         |
| GE  | 600        | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0         | 72.0        | 74.2         | 75.3         | 75.3         | 77.4          | 77.4          | 77.4         | 83.9         |
|     | <b>500</b> | 10.3 | 10.2          | 40.0                                  | 40.0     | 50.1          |         | co o     | 70.0         | 70.0        | 74.0         | 75.3         | 25.3         | 77 .          | 77.4          | 77.4         | 03.0         |
| GE  | 500        | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0         | 72.0        | 74.2         | 75.3         | 75.3         | 77.4          | 77.4          | 77.4         | 83.9         |
| GE  | 400        |      | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0         | 72.0        | 74.2         | 75.3         | 75.3         | 77.4          | 77.4          | 77.4         | 83.9         |
| GE  | 300        | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0         | 72.0        | 74.2         | 75.3<br>75.3 | 75.3<br>75.3 | 77.4          | 77.4          | 77.4         | 83.9<br>84.9 |
| GE  | 200        | 18.3 | 18.3<br>18.3  | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0<br>72.0 | 72.0        | 74.2<br>74.2 | 75.3<br>75.3 | 75.3         | 77.4<br>77.4  | 77.4<br>77.4  | 78.5<br>78.5 | 100.0        |
| GE  | 100        | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 12.0         | 72.0        | 14.2         | 15.3         | 15.3         | 11.4          | //.4          | /8.5         | 100.0        |
| GE  | 000        | 18.3 | 18.3          | 40.9                                  | 40.9     | 59.1          | 63.4    | 68.8     | 72.0         | 72.0        | 74.2         | 75.3         | 75.3         | 77.4          | 77.4          | 78.5         | 100.0        |
| Gr. | 000        | 19+3 | 10.3          | 40.3                                  | 40.9     | 33.1          | 03.4    | 00.0     | 12.0         | 12.0        | 14.2         |              |              |               |               |              | 100.0        |
|     | <b></b>    |      |               |                                       | <i>.</i> | <i></i>       |         |          |              |             |              |              |              |               |               |              |              |

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: OCT HOURS: 06-08 VISIBILITY IN METERS CEILING IN GE GE GΕ GE GE GE GE GE GΕ GE GE GE GE GE GE GE 112 80 60 48 40 32 24 20 16 12 10 08 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 GE 5000 12.9 12.9 25.8 25.8 40.9 41.9 43.0 49.5 49.5 50.5 55.9 55.9 55.9 55.9 57.0 59.1 12.9 25.8 40.9 44.1 50.5 50.5 51.6 57.0 57.0 57.0 57.0 58.1 60.2 GE 4500 12.9 25.8 41.9 GE 4000 12.9 12.9 25.8 25.8 40.9 41.9 44.1 50.5 51.6 52.7 58.1 58.1 58.1 58.1 59.1 61.3 GÉ 3500 12.9 12.9 28.0 28.0 43.0 44.1 47.3 54.8 55.9 57.0 63.4 63.4 63.4 63.4 64.5 66.7 67.7 68.8 GE 3000 12.9 12.9 28.0 28.0 43.0 44.1 48.4 57.0 58.1 59.1 67.7 67.7 67.7 71.0 GE 2500 12.9 12.9 28.0 28.0 43.0 44.1 48.4 57.0 58.1 59.1 67.7 67.7 67.7 67.7 68.8 71.0 59.1 69.9 29.0 45.2 60.2 61.3 69.9 69.9 69.9 71.0 73.1 GE 2000 12.9 12.9 29.0 46.2 50.5 73.1 GE 1800 12.9 12.9 29.0 29.0 45.2 46.2 50.5 59.1 60.2 61.3 69.9 69.9 69.9 69.9 71.0 GE 1500 31.2 49.5 50.5 63.4 64.5 65.6 74.2 74.2 74.2 74.2 75.3 77.4 15.1 15.1 31.2 54.8 GE 1200 15.1 15.1 31.2 31.2 49.5 50.5 54.8 63.4 64.5 65.6 74.2 74.2 74.2 74.2 75.3 77.4 49.5 50.5 63.4 64.5 65.6 74.2 74.2 74.2 74.2 75.3 77.4 GE 1000 15.1 15.1 31.2 31.2 54.8 GE 900 15.1 15.1 31.2 31.2 49.5 50.5 54.8 63.4 64.5 65.6 75.3 75.3 75.3 75.3 76.3 78.5 800 15.1 15.1 31.2 31.2 49.5 50.5 54.8 63.4 64.5 65.6 75.3 75.3 75.3 75.3 76.3 78.5 GE 15.1 15.1 49.5 64.5 700 50.5 65.6 75.3 75.3 75.3 75.3 76.3 GE 31.2 31.2 54.8 63.4 78.5 GE 600 15.1 15.1 31.2 31.2 49.5 50.5 54.8 63.4 64.5 65.6 75.3 75.3 75.3 75.3 76.3 78.5 75.3 75.3 GE 500 15.1 15.1 31.2 31.2 49.5 50.5 54.8 63.4 64.5 65.6 75.3 75.3 77.4 79.6 GΕ 400 15.1 15.1 31.2 31.2 49.5 50.5 54.8 63.4 64.5 65.6 75.3 75.3 75.3 75.3 77.4 79.6 75.3 75.3 75.3 75.3 GE 300 15.1 15.1 31.2 31.2 49.5 50.5 64.5 65.6 77.4 79.6 54.8 63.4 GE 200 15.1 15.1 31.2 31.2 49.5 50.5 54.8 63.4 64.5 65.6 75.3 75.3 75.3 75.3 77.4 82.8 GE 100 15.1 15.1 31.2 31.2 49.5 50.5 54.8 63.4 64.5 65.6 75.3 75.3 75.3 75.3 78.5 100.0 000 15.1 15.1 31.2 31.2 49.5 50.5 54.8 63.4 64.5 65.6 75.3 75.3 75.3 75.3 78.5 100.0

STATION NUMBER: 471066

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: OCT HOURS: 09-11

VISIBILITY IN METERS CEILING IN GE GE GE GE GE GE GE GE GE GE GE GE GE Œ GE GE 80 60 48 40 32 20 16 12 10 08 06 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GΕ 8000 GE 7000 GE 6000 GE 5000 50.0 50.0 56.5 56.5 71.0 71.0 74.2 75.8 77.4 80.6 80.6 82.3 82.3 82.3 82.3 82.3 GE 4500 50.0 50.0 56.5 56.5 71.0 71.0 74.2 75.8 77.4 80.6 80.6 82.3 82.3 82.3 82.3 82.3 GE 4000 50.0 50.0 58.1 58.1 72.6 72.6 75.8 77.4 79.0 83.9 83.9 85.5 85.5 85.5 85.5 85.5 3500 75.8 79.0 GE 50.0 50.0 61.3 61.3 75.8 80.6 82.3 87.1 87.1 88.7 88.7 88.7 88.7 88.7 GE 3000 50.0 50.0 62.9 62.9 77.4 79.0 82.3 83.9 85.5 90.3 90.3 91.9 91.2 91.9 91.9 91.9 50.0 77.4 79.0 82.3 90.3 GE 2500 50.0 62.9 62.9 83.9 85.5 90.3 91.9 91.9 91.9 91.9 91.9 GE 2000 50.0 50.0 62.9 62.9 77.4 80.6 83.9 85.5 87.1 91.9 91.9 93.5 93.5 93.5 93.5 93.5 GE 1800 50.0 50.0 62.9 62.9 77.4 80.6 83.9 85.5 87.1 91.9 91.9 93.5 93.5 93.5 93.5 93.5 1500 77.4 85.5 GE 50.0 50.0 62.9 62.9 80.6 83.9 87.1 91.9 91.9 93.5 93.5 93.5 93.5 93.5 GE 1200 50.0 50.0 62.9 62.9 77.4 80.6 83.9 87.1 88.7 93.5 93.5 95.2 95.2 95.2 95.2

STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: - 9

TOTAL NUMBER OF OBSERVATIONS 62

GE

GE

GE

GE

GE

GE

GE

GE

GE

GE

GE

1000

900

800

700

600

500

400

300

200

100

50.0

50.0

50.0

50.0

50.0

50.0

50.0

50.0

50.0

50.0

000 50.0

50.0

50.0

50.0

50.0

50.0

50.0

50.0

50.0

50.0

50.0

62.9

62.9

62.9

62.9

62.9

62.9

62.9

62.9

62.9

62.9

50.0 62.9

62.9

62.9

62.9

62.9

62.9

62.9

62.9

62.9

62.9

62.9

62.0

77.4

77.4

77.4

77.4

77.4

77.4

77.4

77.4

77.4

77.4

77.4

80.6

80.6

80.6

80.6

80.6

80.6

80.6

80.6

80.6

80.6

80.6

83.9

83.9

83.9

83.9

83.9

83.9

83.9

83.9

83.9

83.9

87.1

87.1

87.1

87.1

87.1

87.1

87.1

87.1

87.1

87.1

83.9 87.1

88.7

88.7

88.7

90.3

90.3

90.3

90.3

90.3

90.3

90.3

93.5

93.5

93.5

95.2

95.2

95.2

95.2

95.2

95.2

95.2

93.5

93.5

93.5

95.2

95.2

95.2

95.2

95.2

95.2

95.2

90.3 95.2 95.2 96.8

95.2

95.2

95.2

96.8

96.8

96.8

96.8

96.8

96.8

96.8

95.2

95.2

95.2

96.8

96.8

96.8

96.8

96.8

96.8

96.8

96.8

95.2

95.2

95.2

96.8

96.8

96.8

96.8

96.8

96.8

96.8

96.8

95.2

95.2

95.2

96.8

96.8

96.8

96.8

96.8

96.8

95.2

95.2

95.2

96.8

96.8

96.8

98.4

98.4

100.0

96.8 100.0

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: OCT HOURS: 12-14 VISIBILITY IN METERS CEILING IN GE GE GE GE GE GE GE GE GE GE GE GΕ GE GΕ GE GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 77.4 78.5 78.5 GE 5000 73.1 73.1 76.3 76.3 77.4 78.5 78.5 78.5 78.5 78.5 78.5 61.3 61.3 GE 4500 61.3 61.3 73.1 73.1 76.3 76.3 77.4 77.4 78.5 78.5 78.5 78.5 78.5 78.5 78.5 78.5 GE 4000 62.4 74.2 74.2 77.4 77.4 79.6 79.6 80.6 80.6 80.6 80.6 80.6 80.6 80.6 80.6 62.4 63.4 77.4 77.4 83.9 84.9 84.9 84.9 84.9 84.9 GΕ 3500 63.4 81.7 81.7 83.9 84.9 84.9 84.9 GE 3000 68.8 68.8 83.9 83.9 89.2 89.2 93.5 93.5 94.6 94.6 94.6 94.6 94.6 94.6 94.6 94.6 95.7 95.7 95.7 95.7 GE 2500 68.8 68.8 83.9 83.9 90.3 90.3 94.6 94.6 95.7 95.7 95.7 95.7 GE 2000 68.8 68.8 83.9 83.9 92.5 92.5 96.8 96.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 GE 1800 68.8 68.8 84.9 84.9 93.5 93.5 97.8 97.8 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GE 1560 68.8 68.8 93.5 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 84.9 84.9 93.5 98.9 GE 1200 68.8 68.8 84.9 84.9 93.5 93.5 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 1000 68.8 68.8 84.9 84.9 93.5 93.5 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GΕ 900 68.8 68.8 84.9 84.9 93.5 93.5 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 800 68.8 84.9 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 68.8 84.9 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 700 68.8 68.8 84.9 84.9 93.5 93.5 98.9 GE 600 68.8 68.8 84.9 84.9 93.5 93.5 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GΕ 500 68.8 68.8 84.9 84.9 93.5 93.5 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 68.8 68.8 84.9 84.9 93.5 93.5 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 300 68.8 68.8 84.9 84.9 93.5 93.5 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 98.9 GΕ 200 68.8 68.8 84.9 84.9 93.5 93.5 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 68.8 68.8 84.9 84.9 93.5 93.5 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0 000 68.8 68.8 84.9 84.9 93.5 93.5 98.9 98.9 100.0 100.0 100.0 100.0 100.0 100.0 100.0

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 LST TO UTC: - 9 MONTH: OCT HOURS: 15-17 CEILING VISIBILITY IN METERS GE GE GΕ GE GΕ GE GE GE GE IN GE GĖ GE GE GE GE 112 60 40 32 24 20 16 12 10 08 06 04 00 90 80 48 FEET NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GΕ 8000 7000 GE GE 6000 86.0 86.0 86.0 89.2 89.2 89.2 89.2 89.2 89.2 89.2 76.3 76.3 86.0 86.0 86.0 69.2 GE 5000 GΕ 4500 76.3 76.3 86.0 86.0 86.0 86.0 86.0 86.0 89.2 89.2 89.2 89.2 89.2 89.2 89.2 89.2 GE 4000 76.3 76.3 87.1 87.1 87.1 87.1 87.1 87.1 90.3 90.3 90.3 90.3 90.3 90.3 90.3 91.4 88.2 88.2 91.4 91.4 91.4 91.4 91.4 91.4 91.4 3500 77.4 77.4 88.2 88.2 88.2 88.2 GE GE 3000 81.7 81.7 94.6 94.6 94.6 94.6 94.6 94.6 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 97.8 GE 2500 81.7 81.7 94.6 94.6 94.6 94.6 94.6 94.6 GE 2000 81.7 81.7 94.6 94.6 95.7 95.7 95.7 95.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 95.7 95.7 98.9 98.9 98.9 98.9 98.9 1800 81.7 81.7 94.6 94.6 95.7 95.7 98.9 98.9 98.9 GE GΕ 1500 81.7 81.7 94.6 94.6 95.7 95.7 95.7 95.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GE 1200 81.7 81.7 94.6 94.6 95.7 95.7 95.7 95.7 98.9 98.9 98.9 98.9 98.9 98.9 98.9 GE 1000 81.7 81.7 94.6 94.6 95.7 95.7 95.7 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 900 81.7 81.7 94.6 94.6 95.7 95.7 95.7 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE GE 800 81.7 81.7 94.6 94.6 95.7 95.7 95.7 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 700 81.7 81.7 94.6 94.6 95.7 95.7 95.7 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 94.6 95.7 96.8 100.0 100.0 100.0 100.0 100.0 GE 600 81.7 81.7 94.6 95.7 95.7 500 81.7 81.7 94.6 94.6 95.7 95.7 95.7 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 81.7 81.7 94.6 95.7 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE. 400 94.6 95.7 95.7 GE 300 81.7 81.7 94.6 94.6 95.7 95.7 95.7 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 81.7 81.7 94.6 95.7 95.7 95.7 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 94.6 GE 100 81.7 81.7 94.6 94.6 95.7 95.7 95.7 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 81.7 000 81.7 94.6 94.6 95.7 95.7 95.7 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: OCT HOURS: 18-20 LST TO UTC: - 9 VISIBILITY IN METERS CEILING IN GE GE GE GE GE GE GE GE ĢΕ GE GE GE GE GE Œ GE 112 60 48 40 32 50 16 12 10 08 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 7000 GE GE 6000 77.4 87.1 88.2 91.4 91.4 GE 5000 63.4 77.4 88.2 88.2 91.4 91.4 91.4 91.4 91.4 91.4 63.4 88.2 GĒ 4500 63.4 63.4 77.4 77.4 87.1 88.2 88.2 91.4 91.4 91.4 91.4 91.4 91.4 91.4 91.4 GE 4000 63.4 63.4 77.4 77.4 87.1 88.2 88.2 91.4 91.4 91.4 91.4 91.4 91.4 91.4 91.4 88.2 3500 89.2 89.2 92.5 92.5 92.5 92.5 92.5 92.5 GE 64.5 64.5 78.5 78.5 88.2 89.2 92.5 92.5 GE 3000 68.8 68.8 86.0 95.7 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 86.0 96.8 GE 2500 68.8 68.8 86.0 86.0 95.7 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 2000 68.8 68.8 86.0 86.0 95.7 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 68.8 95.7 96.8 100.0 100.0 100.0 100.0 1800 68.8 86.0 86.0 96.8 96.8 GE 1500 68.8 68.8 86.0 86.0 95.7 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 1200 68.8 68.8 86.0 86.0 95.7 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GΕ 1000 68.8 68.8 86.0 86.0 95.7 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 900 68.8 95.7 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 68.8 86.0 86.0 96.8 GE 800 68.8 68.8 85.0 86.0 95.7 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 700 68.8 68.8 86.0 86.0 95.7 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 600 68.8 68.8 86.0 86.0 95.7 96.8 96.8 96.8 100.0 GE 500 68.8 68.8 86.0 95.7 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 86.0 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 68.8 68.8 86.0 86.0 95.7 96.8 96.8 96.8 GE 300 68.8 68.8 86.0 86.0 95.7 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 95.7 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 68.8 68.8 86.0 86.0 96.8 96.8 GE 100 68.8 68.8 86.0 86.0 95.7 96.8 96.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 000 68.8 96.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 68.8 86.0 86.0 95.7 96.8 96.8

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: OCT HOURS: 21-23 VISIBILITY IN METERS CEILING IN GE GE GE GE GE GE GE GE GE GE GE GE GΕ GE GE GE 112 FEET 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 ........... NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 8000 GΕ GE 7000 GΕ 6000 GE 5000 44.1 44.1 67.7 67.7 74.2 76.3 77.4 82.8 84.9 88.2 88.2 88.2 88.2 88.2 88.2 88.2 4500 44.1 44.1 67.7 67.7 74.2 76.3 77.4 82.8 84.9 88.2 88.2 88.2 88.2 88.2 88.2 88.2 GE GE 4000 44.1 44.1 67.7 67.7 74.2 76.3 77.4 82.8 84.9 88.2 90.3 90.3 90.3 90.3 90.3 90.3 GE: 3500 44.1 44.1 67.7 67.7 74.2 76.3 77.4 82.8 84.9 88.2 90.3 90.3 90.3 90.3 90.3 90.3 GE 3000 47.3 47.3 73.1 73.1 80.6 82.8 89.2 91.4 94.6 96.8 96.8 96.8 96.8 96.8 83.9 96.8 GE 2500 47.3 47.3 73.1 73.1 80.6 82.8 83.9 89.2 91.4 94.6 96.8 96.8 96.8 96.8 96.8 96.8 91.4 GE 2000 47.3 47.3 74.2 74.2 82.8 84.9 86.0 93.5 96.8 98.9 98.9 98.9 98.9 98.9 98.9 47.3 47.3 74.2 93.5 98.9 1800 74.2 82.8 84.9 86.0 91.4 96.8 98.9 98.9 98.9 98.9 98.9 GE GE 1500 47.3 47.3 74.2 74.2 82.8 84.9 86.0 91.4 93.5 96.8 98.9 98.9 98.9 98.9 98.9 98.9 GE 1200 47.3 47.3 74.2 74.2 82.8 84.9 86.0 91.4 93.5 96.8 98.9 98.9 98.9 98.9 98.9 98.9 GE 1000 47.3 47.3 74.2 74.2 82.8 84.9 86.0 91.4 93.5 96.8 98.9 98.9 98.9 98.9 98.9 98.9 900 47.3 47.3 74.2 82.8 84.9 91.4 93.5 96.8 98.9 98.9 98.9 98.9 98.9 98.9 GE 74.2 86.0 GE 800 47.3 47.3 74.2 74.2 82.8 84.9 86.0 91.4 93.5 96.8 98.9 98.9 98.9 98.9 98.9 98.9 GE 700 47.3 47.3 74.2 74.2 82.8 84.9 86.0 91.4 93.5 96.8 98.9 98.9 98.9 98.9 98.9 98.9 47.3 47.3 74.2 74.2 84.9 93.5 96.8 98.9 98.9 98.9 98.9 98.9 98.9 GE 600 82.8 86.0 91.4 GE 47.3 47.3 74.2 74.2 82.8 84.9 86.0 91.4 93.5 96.8 98.9 98.9 98.9 98.9 98.9 98.9 98.9 47.3 47.3 74.2 82.8 84.9 86.0 93.5 96.8 98.9 98.9 98.9 98.9 400 74.2 91.4 98.9 GE GE 300 47.3 47.3 74.2 74.2 82.8 84.9 86.0 91.4 93.5 96.8 98.9 98.9 98.9 98.9 98.9 98.9 200 47.3 47.3 74.2 74.2 84.9 86.0 91.4 93.5 96.8 98.9 98.9 98.9 98.9 98.9 98.9 GE 82.8 GE 100 47.3 47.3 74.2 74.2 82.8 84.9 86.0 91.4 93.5 96.8 98.9 98.9 98.9 98.9 98.9 100.0 91.4 93.5 98.9 47.3 74.2 98.9 98.9 98.9 100.0 000 47.3 74.2 82.8 84.9 86.0 96.8 98.9 GE

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: OCT HOURS: ALL

| CETTING            | IN GE GE GE GE GE GE GE GE GE GE GE |      |      |             |             |               |               |             |      |      |               |               |             |             | • • • • • •   |             |
|--------------------|-------------------------------------|------|------|-------------|-------------|---------------|---------------|-------------|------|------|---------------|---------------|-------------|-------------|---------------|-------------|
|                    | l ce                                | CP   | CE   | CE          |             |               |               |             | CF.  | CF   | CIF.          | GF.           | CE          | CF.         | CP            | GF.         |
| FEET               | 112                                 | 90   | 80   | 60          | 48          | 40            | 32            | 24          | 20   | 16   | 12            | 10            | 08          | 06          | 04            | 00          |
|                    | 1 112                               |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
|                    | i                                   |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| NO CEIL            |                                     |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 20000           |                                     |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 20000           | i                                   |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 16000           | )                                   |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 14000           | 1                                   |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 12000           | 1                                   |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
|                    | ł                                   |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 10000           |                                     |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 9000            |                                     |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 8000            |                                     |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 7000<br>GE 6000 | 1                                   |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 0000            | 1                                   |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 5000            | 44.5                                | 44.6 | 60.3 | 60.3        | 70.4        | 71.1          | 72.7          | 74.8        | 76.3 | 77.4 | 78.5          | 78.7          | 79.0        | 79.0        | 79.1          | 80.4        |
| GE 4500            | 44.5                                | 44.6 | 60.4 | 60.4        | 70.7        | 71.4          | 73.1          | 75.2        | 76.7 | 77.8 | 79.0          | 79.1          | 79.4        | 79.4        | 79.5          | 80.8        |
| GE 4000            | 44.6                                | 44.7 | 60.9 | 60.9        | 71.1        | 71.8          | 73.6          | 75.7        | 77.4 | 78.7 | 80.2          | 80.4          | 80.6        | 80.6        | 80.8          | 82.0        |
| GE 3500            | 45.0                                | 45.2 | 62.1 | 62.1        | 72.7        | 73.4          | 75.3          | 77.6        | 79.2 | 80.5 | 82.3          | 82.5          | 82.7        | 82.7        | 82.9          | 84.2        |
| GE 3000            | 17.3                                | 47.4 | 65.6 | 65.6        | 76.6        | 77.4          | 79.8          | 82.3        | 84.0 | 85.3 | 87.4          | 87.5          | 87.8        | 87.8        | 87.9          | 89.2        |
| GE 2500            | 47.3                                | 47.4 | 65.6 | 65.6        | 76.7        | 77.6          | 79.9          | 82.5        | 84.2 | 85.6 | 87.7          | 87.8          | 88.1        | 88.1        | 88.2          | 89.5        |
| GE 2000            | 1                                   | 47.4 | 65.9 | 65.9        | 78.1        | 79.4          | 81.8          | 84.3        | 86.0 | 87.4 | 89.5          | 89.6          | 89.9        | 89.9        | 90.0          | 91.3        |
| GE 1800            | 1                                   | 47.4 | 66.1 | 66.1        | 78.3        | 79.5          | 81.9          | 84.4        | 86.1 | 87.5 | 89.6          | 89.8          | 90.0        | 90.0        | 90.2          | 91.4        |
| GE 1500            | 1                                   | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.3        | 87.0 | 88.4 | 90.5          | 90.6          | 90.9        | 90.9        | 91.0          | 92.3        |
| GE 1200            | 1                                   | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.4        | 87.1 | 88.5 | 90.6          | 90.7          | 91.0        | 91.0        | 91.2          | 92.4        |
|                    | İ                                   |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 1000            | 47.5                                | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.6        | 87.2 | 88.6 | 90.7          | 90.9          | 91.4        | 91.4        | 91.6          | 92.8        |
| GE 900             | 1                                   | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.6        | 87.2 | 88.6 | 90.9          | 91.0          | 91.6        | 91.6        | 91.7          | 93.0        |
| GE 800             |                                     | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.6        | 87.2 | 88.6 | 90.9          | 91.0          | 91.6        | 91.6        | 91.7          | 93.0        |
| GE 700             | 1                                   | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.6        | 87.4 | 88.8 | 91.0          | 91.2          | 91.7        | 91.7        | 91.9          | 93.1        |
| GE 600             | 47.5                                | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.6        | 87.4 | 88.8 | 91.0          | 91.2          | 91.7        | 91.7        | 91.9          | 93.1        |
| GE 500             | 47.5                                | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.6        | 87.4 | 88.8 | 91.0          | 91.2          | 91.7        | 91.7        | 92.0          | 93.3        |
| GE 400             | 1                                   | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.6        | 87.4 | 88.8 | 91.0          | 91.2          | 91.7        | 91.7        | 92.0          | 93.3        |
| GE 300             | 1                                   | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.6        | 87.4 | 88.8 | 91.0          | 91.2          | 91.7        | 91.7        | 92.0          | 93.4        |
| GE 200             | 1                                   | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.6        | 87.4 | 88.8 | 91.0          | 91.2          | 91.7        | 91.7        | 92.1          | 94.0        |
| GE 100             | 47.5                                | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.6        | 87.4 | 88.8 | 91.0          | 91.2          | 91.7        | 91.7        | 92.4          | 100.0       |
|                    |                                     |      |      |             |             |               |               |             |      |      |               |               |             |             |               |             |
| GE 000             | 47.5                                | 47.7 | 66.3 | 66.3        | 78.8        | 80.2          | 82.7          | 85.6        | 87.4 | 88.8 | 91.0          | 91.2          | 91.7        | 91.7        | 92.4          | 100.0       |
|                    | • • • • • • •                       |      |      | • • • • • • | • • • • • • | • • • • • • • | • • • • • • • | • • • • • • |      |      | • • • • • • • | • • • • • • • | • • • • • • | • • • • • • | • • • • • • • | • • • • • • |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: NOV HOURS: 00-02 CEILING VISIBILITY IN METERS GE GE IN GE GE GE GE GE GE GΕ GE GE GE GE GE GΕ FEET 112 32 24 20 12 90 80 60 48 40 16 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 9000 GE GE 8000 GΕ 7000 GE 6000 5000 28.6 28.6 34.5 34.5 52.4 54.8 59.5 61.9 GΕ 61.9 61.9 61.9 61.9 61.9 61.9 61.9 61.9 59.5 4500 28.6 34.5 GE 28.6 34.5 52.4 54.8 61.9 61.9 61.9 61.9 61.9 61.9 61.9 61.9 61.9 GΕ 4000 33.3 33.3 39.3 39.3 59.5 61.9 66.7 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 GE 3500 35.7 35.7 41.7 41.7 61.9 64.3 69.0 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.4 GE 3000 38.1 38.1 44.0 44.0 67.9 71.4 76.2 78.6 78.6 78.6 78.6 78.6 78.6 78.6 78.6 78.6 GE 2500 38.1 38.1 44.0 44.0 69.0 72.6 77.4 79.8 79.8 79.8 79.8 79.8 79.8 79.8 79.8 79.8 2000 40.5 79.8 88.1 GE 41.7 53.6 53.6 83.3 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 GÈ 1800 40.5 41.7 53.6 53.6 79.8 83.3 88.1 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 40.5 GE 1500 41.7 53.6 53.6 81.0 85.7 94.0 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 96.4 40.5 GE 1200 41.7 53.6 53.6 83.3 88.1 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 53.6 GE 1000 10.5 41.7 53.6 A3.7 99.1 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 40.5 83.3 97.6 GE 900 41.7 53.6 53.6 88.1 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GΕ 800 40.5 41.7 53.6 53.6 83.3 88.1 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 40.5 GE 700 41.7 53.6 53.6 83.3 88.1 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 40.5 GE 600 41.7 53.6 53.6 83.3 88.1 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 40.5 41.7 53.6 53.6 83.3 88.1 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 97.6 GE 400 40.5 41.7 53.6 53.6 83.3 88.1 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 300 40.5 41.7 53.6 53.6 83.3 88.1 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 40.5 41.7 53.6 53.6 83.3 88.1 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 40.5 41.7 53.6 53.6 83.3 88.1 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 000 40.5 41.7 53.6 53.6 83.3 88.1 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: NOV HOURS: 03-05 VISIBILITY IN METERS GE GE GΕ GE GE GΕ GE GE GE GE GE GE GE GE GE GΕ IN 112 FEET 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 6000 GE GE 5000 23.8 23.8 32.1 32.1 42.9 44.0 52.4 56.0 59.5 61.9 63.1 63.1 63.1 63.1 63.1 65.5 GE 23.8 32.1 32.1 42.9 44.0 52.4 56.0 59.5 61.9 63.1 63.1 63.1 63.1 63.1 65.5 4500 23.8 GE 4000 25.0 25.0 39.3 39.3 52.4 53.6 64.3 67.9 71.4 73.8 75.0 75.0 75.0 75.0 75.0 77.4 GE 3500 25.0 25.0 39.3 39.3 54.8 56.0 66.7 70.2 73.8 76.2 77.4 77.4 77.4 77.4 77.4 79.8 GE 3000 25.0 39.3 39.3 54.8 56.0 70.2 73.8 76.2 77.4 77.4 77.4 77.4 77.4 79.8 25.0 66.7 GE 2500 25.0 25.0 39.3 39.3 57.1 58.3 69.0 72.6 76.2 78.6 79.8 79.8 79.8 79.8 79.8 82.1 42.9 GE 2000 27.4 27.4 42.9 64.3 65.5 76.2 79.8 83.3 85.7 86.9 86.9 86.9 86.9 86.9 89.3 86.9 27.4 27.4 42.9 42.9 64.3 65.5 76.2 79.8 83.3 85.7 86.9 86.9 86.9 86.9 89.3 GE 1800 GΕ 1500 27.4 27.4 42.9 42.9 65.5 71.4 84.5 88.1 91.7 94.0 95.2 95.2 95.2 95.2 95.2 97.6 1200 27.4 27.4 42.9 42.9 67.9 73.8 86.9 90.5 94.0 96.4 97.6 97.6 97.6 97.6 97.6 100.0 GE GE 1000 27.4 27.4 42.9 42.9 67.9 73.8 86.9 90.5 94.0 96.4 97.3 97.6 97.6 97.6 97.6 100.0 900 27.4 42.9 42.9 67.9 73.8 86.9 90.5 94.0 96.4 97.6 97.6 97.6 97.6 97.6 100.0 GE 27.4 97.6 97.6 97.6 100.0 GE 800 27.4 27.4 42.9 42.9 67.9 73.8 86.9 90.5 94.0 96.4 97.6 97.6 GE 700 27.4 27.4 42.9 42.9 67.9 73.8 86.9 90.5 94.0 96.4 97.6 97.6 97.6 97.6 97.6 100.0 97.6 97.6 97.6 97.6 100.0 27.4 27.4 67.9 73.8 86.9 90.5 94.0 96.4 97.6 GE 600 42.9 42.9 GΕ 500 27.4 27.4 42.9 42.9 67.9 73.8 86.9 94.0 96.4 97.6 97.6 97.6 97.6 97.6 100.0 97.6 97.6 97.6 97.6 97.6 100.0 42.9 86.9 90.5 94.0 96.4 GE 400 27.4 27.4 42.9 67.9 73.8 GE 300 27.4 27.4 42.9 42.9 67.9 73.8 86.9 90.5 94.0 96.4 97.6 97.6 97.6 97.6 97.6 100.0 97.6 97.6 97.6 97.6 97.6 100.0 27.4 27.4 42.9 67.9 73.8 90.5 96.4 GE 200 42.9 86.9 94.0 GE 100 27.4 27.4 42.9 42.9 67.9 73.8 86.9 90.5 94.0 96.4 97.6 97.6 97.6 97.6 97.6 100.0 97.6 97.6 97.6 97.6 97.6 100.0 73.8 GE 000 27.4 27.4 42.9 42.9 67.9 86.9 90.5 94.0 96.4

STATION NUMBER: 471066

GΕ

GE GE

GE

GE

5000

4500

4000

3500

3000

25.0

25.0

27.4

27.4

27.4

25.0

25.0

28.6

28.6

28.6

32.1

32.1

39.3

39.3

41.7

32.1

32.1

39.3

39.3

41.7

36.9

36.9

47.6

47.6

51.2

44.0

44.0

54.8

54.8

58.3

47.6

47.6

58.3

58.3

61.9

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: NOV HOURS: 06-08

CEILING VISIBILITY IN METERS GE GE GE GE GE GE GE GE GE GE GE GE IN GE GE GE GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GΕ 7000 6000 GE

48.8

48.8

59.5

59.5

63.1

48.8

48.8

59.5

59.5

63.1

51.2

51.2

61.9

61.9

65.5

56.0

56.0

66.7

66.7

70.2

59.5

59.5

71.4

71.4

75.0

60.7

60.7

72.6

72.6

76.2

60.7

60.7

72.6

72.6

76.2

61.9

61.9

73.8

73.8

77.4

67.9

67.9

79.8

79.8

83.3

STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: - 9

GE 2500 27.4 28.6 42.9 42.9 52.4 59.5 63.1 64.3 64.3 66.7 71.4 76.2 77.4 77.4 78.6 84.5 79.8 GE 2000 27.4 28.6 44.0 44.0 54.8 63.1 66.7 67.9 67.9 70.2 75.0 81.0 81.0 82.1 88.1 1800 27.4 28.6 44.9 44.0 54.8 63.1 66.7 67.9 67.9 70.2 75.0 79.8 81.0 81.0 82.1 88.1 79.8 86.9 GE 1500 29.8 31.0 47.6 47.6 58.3 67.9 71.4 72.6 72.6 75.0 84.5 85.7 85.7 92.9 GE 1200 29.8 31.0 47.6 47.6 58.3 69.0 75.0 76.2 76.2 78.6 83.3 88.1 89.3 89.3 90.5 96.4 31.0 76.2 89.3 GE 1000 29.8 47.6 47.6 58.3 69.0 75.0 76.2 78.6 83.3 88.1 89.3 90.5 96.4 89.3 GE 900 29.8 31.0 47.6 47.6 58.3 69.0 75.0 76.2 76.2 78.6 83.3 88.1 89.3 90.5 96.4 29.8 47.6 47.6 75.0 76.2 76.2 78.6 83.3 88.1 89.3 89.3 90.5 96.4 800 31.0 58.3 69.0 GE 97.6 GE 700 29.8 31.0 48.8 48.8 59.5 70.2 76.2 77.4 77.4 79.8 84.5 89.3 90.5 90.5 91.7 GE 600 29.8 31.0 48.8 48.8 59.5 70.2 76.2 77.4 77.4 79.8 84.5 89.3 90.5 90.5 91.7 97.6 GE 500 29.8 31.0 48.8 48.8 59.5 70.2 76.2 77.4 77.4 79.8 84.5 89.3 90.5 90.5 91.7 97.6 GE 400 29.8 31.0 48.8 48.8 59.5 70.2 76.2 77.4 77.4 79.8 84.5 89.3 90.5 90.5 91.7 97.6 77.4 29.8 59.5 76.2 77.4 79.8 84.5 89.3 90.5 90.5 91.7 97.6 GE 300 31.0 48.8 48.8 70.2 GE 200 29.8 31.0 48.8 48.8 59.5 70.2 16.2 77.4 77.4 79.8 84.5 89.3 90.5 90.5 91.7 97.6 GE 100 29.8 31.0 48.8 48.8 59.5 70.2 76.2 77.4 77.4 79.8 84.5 89.3 90.5 90.5 91.7 100.0 31.0 48.8 48.8 59.5 70.2 76.2 77.4 77.4 79.8 84.5 89.3 90.5 90.5 91.7 100.0

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: NOV HOURS: 09-11

|               |   |               | rea         | 10 010        | MONTH:        | NOV I         | HOURS:        | 39-11         |               |             |             |             |               |             |             |             |
|---------------|---|---------------|-------------|---------------|---------------|---------------|---------------|---------------|---------------|-------------|-------------|-------------|---------------|-------------|-------------|-------------|
| 0077770       | CEILING VISIBILITY IN METERS  IN GE GE GE GE GE GE GE GE GE GE GE GE GE |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
|               | 1 00  | an            | -           | an            |               |               |               |               |               |             |             |             |               |             |             |             |
|               | 1   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| FEET          | 112   | 90            | 80          | 60            | 48            | 40            | 32            | 24            | 20            | 16          | 12          | 10          | 08            | 06          | 04          | 00          |
| • • • • • • • |   | • • • • • • • | • • • • • • | • • • • • • • | • • • • • • • | • • • • • •   | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • • | • • • • • • | • • • • • • | • • • • • • • | • • • • • • | • • • • • • | • • • • • • |
| NO CELL       |   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| NO CEIL       | }   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 20000      |   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 18000      | 1   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 16000      | 1   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 14000      | 1   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 12000      | 1   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 12000      | <b>'</b>  |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 10000      | ,   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 9000       | 1   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 8000       |   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 7000       |   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 6000       |   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 0000       | 1   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 5000       | 33.9  | 35.7          | 41.1        | 41.1          | 60.7          | 64.3          | 64.3          | 67.9          | 67.9          | 67.9        | 71.4        | 73.2        | 73.2          | 73.2        | 73.2        | 75.0        |
| GE 4500       | 1   | 35.7          | 41.1        | 41.1          | 66.7          | 64.3          | 64.3          | 67.9          | 67.9          | 67.9        | 71.4        | 73.2        | 73.2          | 73.2        | 73.2        | 75.0        |
| GE 4000       | i   | 39.3          | 44.6        | 44.6          | 67.9          | 71.4          | 71.4          | 75.0          | 75.0          | 75.0        | 78.6        | 80.4        | 80.4          | 80.4        | 80.4        | 82.1        |
| GE 3500       | 1   | 41.1          | 46.4        | 46.4          | 69.6          | 73.2          | 73.2          | 76.8          | 76.8          | 76.8        | 80.4        | 82.1        | 62.1          | 82.1        | 82.1        | 83.9        |
| GE 3000       | 1   | 44.6          | 50.0        | 50.0          | 73.2          | 76.8          | 76.8          | 80.4          | 80.4          | 80.4        | 83.9        | 85.7        | 85.7          | 85.7        | 85.7        | 87.5        |
|               | ''''  |               |             |               |               |               | • •           |               |               |             |             | 02.         |               |             |             |             |
| GE 2500       | 42.9  | 44.6          | 50.0        | 50.0          | 73.2          | 76.8          | 76.8          | 80.4          | 80.4          | 80.4        | 83.9        | 85.7        | 85.7          | 85.7        | 85.7        | 87.5        |
| GE 2000       | 42.9  | 44.6          | 53.6        | 53.6          | 76.8          | 80.4          | 80.4          | 83.9          | 83.9          | 83.9        | 87.5        | 89.3        | 89.3          | 89.3        | 89.3        | 91.1        |
| GE 1800       | 42.9  | 44.6          | 53.6        | 53.6          | 76.8          | 80.4          | 80.4          | 83.9          | 83.9          | 83.9        | 87.5        | 89.3        | 89.3          | 89.3        | 89.         | 91.1        |
| GE 1500       | 44.6  | 46.4          | 55.4        | 55.4          | 78.6          | 82.1          | 82.1          | 85.7          | 85.7          | 85.7        | 89.3        | 91.1        | 91.1          | 91.1        | ∌1.1        | 92.9        |
| GE 1∠00       | 44.6  | 46.4          | 55.4        | 55.4          | 78.6          | 82.1          | 82.1          | 85.7          | 85.7          | 85.7        | 89.3        | 91.1        | 91.1          | 91.1        | 91.1        | 92.9        |
|               |   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 1000       | 44.6  | 46.4          | 55.4        | 55.4          | 78.6          | 82.1          | 82.1          | 85.7          | 85.7          | 85.7        | ₽9.3        | 91.1        | 91.1          | 91.1        | 91.1        | 92.9        |
| GE 900        | 44.6  | 46.4          | 55.4        | 55.4          | 80.4          | 83.9          | 83.9          | 87.5          | 87.5          | 87.5        | 91.1        | 92.3        | 92.9          | 92.9        | 92.9        | 94.6        |
| GE 800        | 44.6  | 46.4          | 55.4        | 55.4          | 80.4          | 03.9          | 83.9          | 87.5          | 87.5          | 87.5        | 91.1        | 97          | 92.9          | 92.9        | 92.9        | 94.6        |
| GE 700        | 44.6  | 46.4          | 55.4        | 55.4          | 80.4          | 83.9          | 87.5          | 91.1          | 91.1          | 91 1        | 94.6        | 9 '         | 96.4          | 96.4        | 96.4        | 98.2        |
| GE 600        | 14.6  | 46.4          | 55.4        | 55.4          | 80.4          | 83.9          | 87.5          | 91.1          | 91.1          | 91.1        | 94.6        | 90.4        | 96.4          | 96.4        | 96.4        | 98.2        |
|               |   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 500        | 1   | 46.4          | 55.4        | 55.4          | 80.4          | 83.9          | 87.5          | 91.1          | 91.1          | 91.1        | 94.6        | 96.4        | 36.4          | 96.4        | 96.4        | 98.2        |
| GE 400        | 44.6  | 46.4          | 55.4        | 55.4          | 80.4          | 83.9          | 87.5          | 91.1          | 91.1          | 91.1        | 94.6        | 96.4        | 96.4          | 96.4        | 96.4        | 98.2        |
| GE 300        | 44.6  | 46.4          | 55.4        | 55.4          | 80.4          | 83.9          | 87.5          | 91.1          | 91.1          | 91.1        | 94.6        | 96.4        | 96.4          | 96.4        | 96.4        | 98.2        |
| GE 200        | 44.6  | 46.4          | 55.4        | 55.4          | 80.4          | 83.9          | 87.5          | 91.1          | 91.1          | 91.1        | 94.6        | 96.4        | 96.4          | 96.4        | 96.4        | 98.2        |
| GE 100        | 44.6  | 46.4          | 55.4        | 55.4          | 80.4          | 83.9          | 87.5          | 91.1          | 91.1          | 91.1        | 91.0        | 96.4        | 96.4          | 96.4        | 96.4        | 100.0       |
|               |   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |
| GE 000        | 44.6  | 46.4          | 55.4        | 55.4          | 80.4          | 83.9          | 87.5          | 91.1          | 91.1          | 91.1        | 94.6        | 96.4        | 96.4          | 96.4        | 96.4        | 100.0       |
|               |   | • • • • • •   |             |               |               | · · · · · · · | · · · · · · · |               |               | • • • • • • |             | • • • • • • |               |             |             | • • • • • • |
|               |   |               |             |               |               |               |               |               |               |             |             |             |               |             |             |             |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: NOV HOURS: 12-14

| CEI | LING         |               |      |      | • • • • • • | ,    | <br>VISIBIL | ITY IN      | <br>METERS    | • • • • • • • |               | • • • • • • • |               | • • • • • • • |              | • • • • • •  | • • • • • •  |
|-----|--------------|---------------|------|------|-------------|------|-------------|-------------|---------------|---------------|---------------|---------------|---------------|---------------|--------------|--------------|--------------|
|     | N            | GE            | GE   | GE   | GE          | GE   | GE          | GE          | GE            | GE            | GE            | GE            | GE            | GE            | GE           | GE           | GE           |
|     | ET           | 112           | 90   | 80   | 60          | 48   | 40          | 32          | 24            | 20            | 16            | 12            | 10            | 08            | 06           | 04           | 00           |
|     | . <b></b>    |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
|     |              |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| NO  | CEIL         |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 20000        |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
|     | 18000        |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 16000        |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 14000        |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 12000        |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
|     |              | }             |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 10000        |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 9000         |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 8000         |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 7000         |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 6000         |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
|     |              |               |      |      |             |      |             |             |               |               | 20.0          | 70.0          |               | 70.6          |              | 70.6         | 70.6         |
| GE  | 5000         | 48.8          | 48.8 | 69.0 | 69.0        | 73.8 | 77.4        | 78.6        | 78.6          | 78.6          | 78.6          | 78.6          | 78.6          | 78.6          | 78.6         | 78.6         | 78.6         |
| GE  | 4500         | 48.8          | 48.F | 69.0 | 69.0        | 73.8 | 77 4        | 78.6        | 78.6          | 78.6          | 78.6          | 78.6          | 78.6          | 78.6          | 78.6         | 78.6         | 78.5         |
| GE  | 4000         | 53.6          | 53.6 | 76.2 | 76.2        | 81.0 | 84.5        | 85.7        | 85.7          | 85.7          | 85.7          | 85.7          | 85.7          | 85.7          | 85.7         | 85.7         | 85.7         |
| GE  | 3500<br>3000 | 56.0<br>57.1  | 56.0 | 78.6 | 78.6        | 83.3 | 86.9        | 88.1        | 88.1          | 88.1          | 88.1<br>89.3  | 88.1<br>89.3  | 88.1<br>89.3  | 88.1<br>89.3  | 88.1<br>89.3 | 88.1<br>89.3 | 88.1<br>89.3 |
| GE  | 3000         | 37.1          | 57.1 | 79.8 | 79.8        | 84.5 | 88.1        | 89.3        | 89.3          | 89.3          | 89.3          | 09.3          | 69.3          | 69.3          | 89.3         | 69.3         | 69.3         |
| GE  | 2500         | 59.5          | 59.5 | 82.1 | 82.1        | 36.9 | 90.5        | 91.7        | 91.7          | 91.7          | 91.7          | 91.7          | 91.7          | 91.7          | 91.7         | 91.7         | 91.7         |
| GE  | 2000         | 60.7          | 60.7 | 84.5 | 84.5        | 90.5 | 94.0        | 95.2        | 95.2          | 95.2          | 95.2          | 95.2          | 95.2          | 95.2          | 95.2         | 95.2         | 95.2         |
| GE  | 1800         | 60.7          | 60.7 | 84.5 | 84.5        | 90.5 | 94.0        | 95.2        | 95.2          | 95.2          | 95.2          | 95.2          | 95.2          | 95.2          | 95.2         | 95.2         | 95.2         |
| GE  | 1500         | 60.7          | 60.7 | 84.5 | 84.5        | 91.7 | 95.2        | 96.4        | 96.4          | 96.4          | 96.4          | 96.4          | 96.4          | 96.4          | 96.4         | 96.4         | 96.4         |
| GE  | 1200         | 60.7          | 60.7 | 84.5 | 84.5        | 92.9 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
|     |              |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 1000         | 60.7          | 60.7 | 84.5 | 84.5        | 92.9 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
| GE  | 900          | 60.7          | 60.7 | 84.5 | 84.5        | 92.9 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
| GE  | 800          | 60.7          | 60.7 | 84.5 | 84.5        | 92.9 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
| GE  | 700          | 60.7          | 60.7 | 84.5 | 84.5        | 92.9 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
| GE  | 600          | 60.7          | 60.7 | 84.5 | 84.5        | 92.9 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
|     |              | }             |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 500          | 60.7          | 60.7 | 84.5 | 84.5        | 92.7 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
| СE  | 400          | 60.7          | 60.7 | 84.5 | 84.5        | 92.0 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
| GE  | 300          | 50.7          | 60.7 | 84.5 | 84.5        | 92.9 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
| GE  | 260          | 60.7          | 60.7 | 84.5 | 84.5        | 92.9 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
| GE  | 100          | 50.7          | 60.7 | 84.5 | 84.5        | 92.9 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
|     |              |               |      |      |             |      |             |             |               |               |               |               |               |               |              |              |              |
| GE  | 600          | 60.7          | 60.7 | 84.5 | 84.5        | 92.9 | 97.6        | 100.0       | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0         | 100.0        | 100.0        | 100.0        |
|     |              | · · · · · · · |      |      |             |      |             | • • • • • • | • • • • • • • |               | • • • • • • • | • • • • • •   | • • • • • • • | · · · · · ·   | • • • • • •  | • • • • • •  | • • • • • •  |

TOTAL NUMBER OF CASERVATIONS 84

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: NOV HOURS: 15-17 CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE 112 FEET 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CELL GE 20000 GE 18000 CE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 GE 5000 46 4 48.8 58.3 58.3 61.9 61.9 61.9 61.9 61.9 61.9 61.9 61.9 61.9 61.9 61.9 61.9 GΕ 4500 46.4 48.8 58.3 58.3 61.9 61.9 61.9 61.9 61.9 61.9 61.9 61.9 61.9 61.9 F.1 . 61.9 GE 4000 51.2 53.6 66.7 66.7 70.2 70.2 70.2 70.2 70.2 70.2 70.2 70 2 70.2 70.2 70.2 70.2 GΕ 3500 56.0 59.5 77.4 77.4 81.0 81.0 81.0 81.0 81.0 81.0 81.0 81.0 81.0 81.0 81.0 81.0 3000 66.7 85.7 GE 63.1 85.7 89.3 89.3 89.3 89.3 89.3 89.3 89.3 89.3 89.3 89.3 89.3 89.3 GE 2500 66.7 70.2 89.3 89.3 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 89.3 GE 2000 66.7 70.2 89.3 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 89.3 94.0 GE 1800 66.7 70.2 89.3 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 1500 66.7 70.2 89.3 89.3 94.0 94.0 GE 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 89.3 89.3 GΕ 1200 66.7 70.2 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 94.0 GΕ 1000 66.7 70.2 90.5 90.5 95.2 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 900 66.7 70.2 90.5 90.5 95.2 97.6 97.6 GE 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 GE 800 36.7 70.2 90.5 90.5 95.2 97.6 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 97.6 GE 700 66.7 70.2 90.5 90.5 95.2 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 66.7 70.2 90.5 90.5 95.2 97.6 97.6 100.0 600 GE 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 5001 66.7 70.2 90.5 90.5 95.2 97.6 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 66.7 400 70.2 90.5 90.5 95.2 GE 97.6 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 97.6 GE 300 66.7 70.2 90.5 90.5 95.2 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 70.2 90.5 97.6 200 66.7 90.5 95.2 97.6 GE 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 66.7 70.2 90.5 90.5 95.2 97.6 97.6 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 90.5 000 66.7 70.2 90.5 GE 95.2 97.6 97.6 100.0 100.0 100.0 100.0 100.0 100.0 00.0 100.0

#### PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: NOV HOURS: 18-20 VISIBILITY IN METERS CEILING TN GE GE GE GE GE GE GE CE GE GE GE GE GE GE GE GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 70.2 5000 46.4 70.2 70.2 70.2 70.2 GE 44.0 59.5 59.5 70.2 70.2 70.2 70.2 70.2 70.2 70.2 GE 4500 44.0 46.4 59.5 59.5 70.2 70.2 70.2 70.2 70.2 70.2 70.2 70.2 70.2 70.2 70.2 70.2 GE 4000 46.4 48.8 63.1 63.1 73.8 73.8 73.8 73.8 73.8 73.8 73.8 73.8 73.8 73.8 73.8 73.8 GΕ 3500 47.6 50.0 78.6 78.6 66.7 66.7 78.6 78.6 78.6 78.6 78.6 78.6 78.6 78.6 78.6 78.6 GE 3000 54.8 57.1 77.4 77.4 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 GE 2500 54.8 57.1 77.4 77.4 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 91.7 2000 58.3 60.7 97.6 97.6 97.6 GE 81.0 81.0 96.4 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 GE 1800 58.3 60.7 81.0 81.0 96.4 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 GE 1500 58.3 60.7 81.0 81.0 96.4 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 GE 1200 58.3 60.7 81.0 81.0 96.4 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 GE 1000 58.3 60.7 81.0 81.0 96.4 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 97.6 900 58.3 60.7 97.6 97.6 97.6 97.6 GE 81.0 81.0 96.4 97.6 97.6 97.6 97.6 97.6 97.6 97.6 GE: 800 58.3 60.7 81.0 81.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.C 100.0 100.0 700 58.3 GE 60.7 81.0 81.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 60.7 GE 600 58.3 81.0 81.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 58.3 60.7 81.0 81.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 58.3 GE 400 60.7 81.0 81.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 300 58.3 60.7 81.0 81.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 58.3 60.7 81.0 81.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 58.3 60.7 81.0 81.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 000 58.3 60.7 81.0 81.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: NOV HOURS: 21-23 LST TO UTC: - 9 CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE 32 20 12 24 16 10 08 06 FEET 112 90 80 60 48 40 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 58.3 69.0 69.0 69.0 GE 5000 45.2 46.4 58.3 69.0 GE 4500 45.2 46.4 58.3 58.3 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 69.0 GE 4000 47.6 48.8 60.7 60.7 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.4 71.4 77.4 77.4 77.4 77.4 77.4 77.4 GE 3500 50.0 51.2 63.1 63.1 77.4 77.4 77.4 77.4 77.4 77.4 GE 3000 51.2 52.4 66.7 66.7 84.5 84.5 84.5 84.5 84.5 84.5 84.5 84.5 84.5 84.5 84.5 84.5 88.1 GE 2500 52.4 66.7 88.1 88.1 88.1 88.1 88.1 88.1 88.1 88.1 51.2 66.7 88.1 88.1 88.1 GE 2000 53.6 54.8 70.2 70.2 95.2 95.2 95.2 95.2 95.2 95.2 95.2 95.2 95.2 95.2 95.2 95.2 98.8 98.8 98.8 98.8 98.8 98.8 98.8 98.8 GE 1800 53.6 54.8 70.2 70.2 98.8 98.8 98.8 98.8 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GF. 1500 53.6 54.8 70.2 70.2 100.0 GE 1200 53.6 54.8 70.2 70.2 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 1000 53.6 54.8 70.2 70.2 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 900 53.6 54.8 70.2 70.2 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 53.6 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 800 54.8 70.2 70.2 GE GE 700 53.6 54.8 70.2 70.2 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 600 53.6 54.8 70.2 70.2 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE500 53.6 54.8 70.2 70.2 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 53.6 54.8 70.2 70.2 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 300 53.6 54.8 70.2 70.2 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 53.6 54.8 70.2 70.2 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 53.6 54.8 70.2 70.2 000 53.6 54.8 70.2 70.2 98.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: NOV HOURS: ALL

| CEI   | LING   |      |               | • • • • • • |               | • • • • • • | VISIBIL | ייייי<br>דיי איד אידו | METERS | • • • • • •   |      |      | • • • • • • | • • • • • •   | • • • • • • • | • • • • • • | • • • • • |
|-------|--------|------|---------------|-------------|---------------|-------------|---------|-----------------------|--------|---------------|------|------|-------------|---------------|---------------|-------------|-----------|
|       | in     | GE   | GE            | GE          | GE            | GE          | GE      | GE                    | GE     | GE            | GE   | GE   | GE          | GE            | GE            | GE          | GE        |
|       | EET    | 112  | 90            | 80          | 60            | 48          | 40      | 32                    | 24     | 20            | 16   | 12   | 10          | 08            | 06            | 04          | 00        |
|       | , L. L | 112  | 30            | 00          | 00            | 40          | 40      | 32                    | 24     | 20            | 10   | 12   | 10          | 00            | 00            | 04          | 00        |
|       |        |      | • • • • • • • | • • • • • • | • • • • • • • |             |         |                       |        | • • • • • • • |      |      |             |               |               |             |           |
| NO    | CEIL   |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
| 110   | CLID   |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
| GF.   | 20000  |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
|       | 18000  |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
|       | 16000  |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
|       | 14000  |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
|       | 12000  |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
| GE    | 12000  |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
| GF.   | 10000  |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
| GE    | 9000   |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
| GE    | 8000   |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
| GE    | 7000   |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
| GE    | 6000   |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
| GE    | 0000   |      |               |             |               |             |         |                       |        |               |      |      |             |               |               |             |           |
| GE    | 5000   | 37.1 | 38.0          | 48.4        | 48.4          | 58.4        | 60.6    | 62.9                  | 64.1   | 64.6          | 65.2 | 66.3 | 66.9        | 67.1          | 67.1          | 67.2        | 68.5      |
| GE    | 4500   | 37.1 | 38.0          | 48.4        | 48.4          | 58.4        | 60.6    | 62.9                  | 64.1   | 64.6          | 65.2 | 66.3 | 66.9        | 67.1          | 67.1          | 67.2        | 68.5      |
| GE    | 4000   | 40.4 | 41.5          | 54.0        | 54.0          | 65.4        | 67.5    | 70.2                  | 71.4   | 71.9          | 72.5 | 73.6 | 74.4        | 74.5          | 74.5          | 74.7        | 75.9      |
| GE    | 3500   | 42.2 | 43.5          | 57.0        | 57.0          | 69.3        | 71.4    | 74.1                  | 75.3   | 75.8          | 76.4 | 77.5 | 78.3        | 78.4          | 78.4          | 78.6        | 79.8      |
| GE    | 3000   | 45.0 | 46.3          | 61.0        | 61.0          | 74.7        | 77.0    | 79.7                  | 80.9   | 81.4          | 82.0 | 83.1 | 83.9        | 84.0          | 84.0          | 84.2        | 85.4      |
| GE    | 3000   | 43.0 | 40.5          | 01.0        | 01.0          | /4./        | 77.0    | 13.1                  | 00.9   | 01.4          | 02.0 | 03.1 | 03.9        | 04.0          | 04.0          | 04.2        | 63.4      |
| GE    | 2500   | 45.8 | 47.0          | 62.0        | 62.0          | 76.7        | 79.0    | 81.7                  | 82.9   | 83.4          | 84.0 | 85.1 | 85.9        | 86.0          | 86.0          | 86.2        | 87.4      |
| GE    | 2000   | 47.4 | 48.8          | 65.4        | 65.4          | 81.7        | 84.3    | 87.0                  | 88.2   | 88.7          | 89.3 | 90.4 | 91.1        | 91.3          | 91.3          | 91.5        | 92.7      |
| GE    | 1800   | 47.4 | 48.8          | 65.4        | 65.4          | 82.1        | 84.8    | 87.4                  | 88.7   | 89.1          | 89.8 | 90.8 | 91.6        | 91.8          | 91.8          | 91.9        | 93.2      |
| GE    | 1500   | 47.8 | 49.2          | 66.0        | 66.0          | 83.2        | 87.0    | 90.4                  | 91.6   | 92.1          | 92.7 | 93.8 | 94.6        | 94.7          | 94.7          | 94.9        | 96.1      |
| GE    | 1200   | 47.8 | 49.2          | 66.0        | 66.0          | 84.0        | 88.0    | 92.1                  | 93.3   | 93.8          | 94.4 | 95.5 | 96.3        | 96.4          | 96.4          | 96.6        | 97.8      |
| GE    | 1200   | 47.0 | 49.2          | 00.0        | 00.0          | 04.0        | 00.0    | 92.1                  | 93.3   | 93.0          | 74.4 | 90.0 | 30.3        | 30.4          | 30.4          | 30.0        | 37.0      |
| GE    | 1000   | 47.8 | 49.2          | 66.1        | 66.1          | 84.2        | 88.5    | 92.5                  | 93.8   | 94.3          | 94.9 | 96.0 | 96.7        | 96.9          | 96.9          | 97.0        | 98.3      |
| GE    | 900    | 47.8 | 49.2          | 66.1        | 66.1          | 84.3        | 88.7    | 92.7                  | 93.9   | 94.4          | 95.0 | 96.1 | 96.9        | 97.0          | 97.0          | 97.2        | 98.4      |
| GE    | 800    | 47.8 | 49.2          | 66.1        | 66.1          | 84.6        | 89.0    | 93.0                  | 94.6   | 95.0          | 95.7 | 96.7 | 97.5        | 97.7          | 97.7          | 97.8        | 99.1      |
| GE    | 700    | 47.8 | 19.2          | 66.3        | 66.3          | 94.8        | 89.1    | 93.5                  | 95.0   | 95.5          | 96.1 | 97.2 | 98.0        | 98.1          | 98.1          | 98.3        | 99.5      |
| GE    | 600    | 47.8 | 49.2          | 66.3        | 66.3          | 84.8        | 89.1    | 93.5                  | 95.0   | 95.5          | 96.1 | 97.2 | 98.0        | 98.1          | 98.1          | 98.3        | 99.5      |
| GE    | 000    | 47.0 | 49.6          | 00.5        | 00.3          | 04.0        | 09.1    | 73.3                  | 33.0   | 33.3          | 30.1 | 37.4 | 50.0        | 50.1          | 50.1          | 50.5        | 77.3      |
| GE    | 500    | 47.8 | 49.2          | 66.3        | 66.3          | 84.8        | 89.1    | 93.5                  | 95.0   | 95.5          | 96.1 | 97.2 | 98.0        | 98.1          | 98.1          | 98.3        | 99.5      |
| GE    | 400    | 47.8 | 49.2          | 66.3        | 66.3          | 84.8        | 89.1    | 93.5                  | 95.0   | 95.5          | 96.1 | 97.2 | 98.0        | 98.1          | 98.1          | 98.3        | 99.5      |
| GE    | 300    | 47.8 | 49.2          | 66.3        | 66.3          | 84.8        | 89.1    | 93.5                  | 95.0   | 95.5          | 96.1 | 97.2 | 98.0        | 98.1          | 98.1          | 98.3        | 99.5      |
|       | 200    | 47.8 | 49.2          | 66.3        | 66.3          | 84.8        | 89.1    | 93.5                  | 95.0   | 95.5          | 96.1 | 97.2 | 98.0        | 98.1          | 98.1          | 98.3        | 99.5      |
| GE    |        | 47.8 |               | 66.3        | 66.3          |             |         |                       | 95.0   | 95.5          | 96.1 |      | 98.0        |               | 98.1          | 98.3        |           |
| GE    | 100    | 47.8 | 49.2          | 6.00        | 50.3          | 84.8        | 89.1    | 93.5                  | 90.0   | 90.0          | 90.1 | 97.2 | 90.0        | 98.1          | 90.1          | 90.3        | 100.0     |
| GE    | 200    | 47.8 | 49.2          | 66.3        | 66.3          | 84.8        | 89.1    | 93.5                  | 95.0   | 95.5          | 96.1 | 97.2 | 98.0        | 98.1          | 98.1          | 98.3        | 100.0     |
| 9K    | 100    | 47.6 | 49.2          | 00.3        | 00.3          | 04.0        | 09.1    | 73.3                  | 90.0   | 90.0          | 90.1 | 71.4 | 90.0        | 30.1          | 30.1          | 70.3        | 100.0     |
| • • • |        |      |               |             |               |             |         |                       |        |               |      |      |             | • • • • • • • |               |             |           |

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 MONTH: DEC HOURS: 00-02 LST TO UTC: - 9 ............ VISIBILITY IN METERS CEILING IN GE GΕ GE GE GE GE GE GE GΕ GE GE GE GE GE GE GE 32 20 16 12 112 24 10 08 06 04 00 FEET 90 80 60 48 40 ...... NO CETT. GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10001 GE 9000 GE 8000 GE 7000 6000 GE GE 5000 36.0 36.0 41.6 41.6 56.2 60.7 67.4 71.9 71.9 71.9 71.9 71.9 71.9 71.9 71.9 71.9 36.0 41.6 60.7 67.4 71.9 71.9 71.9 71.9 71.9 71.9 71.9 71.9 71.9 GE 4500 36.0 41.6 56.2 74.2 74.2 74.2 74.2 74.2 GE 4000 38.2 38.2 43.8 43.8 58.4 62.9 69.7 74.2 74.2 74.2 74.2 75.3 75.3 75.3 75.3 75.3 75.3 75.3 GE 3500 38.2 38.2 43.8 43.8 59.6 64.0 70.8 75.3 75.3 39.3 82.0 82.0 83.1 83.1 83.1 83.1 83.1 83.1 GE 3000 39.3 44.9 44.9 65.2 69.7 77.5 83.1 GE 2500 39.3 39.3 44.9 44.9 65.2 69.7 77.5 82.0 82.0 83.1 83.1 83.1 83.1 83.1 83.1 83.1 GE 2000 39.3 39.3 44.9 44.9 66.0 70.8 79.8 84.3 84.3 85.4 86.5 87.6 88.8 88.8 88.8 84.3 84.3 85.4 86.5 87.6 88.8 88.8 88.8 GE 1800 39.3 39.3 44.9 44.9 66.3 70.8 79.8 88.8 39.3 39.3 44.9 44.9 70.8 79.8 84.3 84.3 85.4 88.8 89.9 91.0 91.0 91.0 91.0 1500 66.3 84.3 85.4 88.8 89.9 91.0 91.0 91.0 GE 1200 39.3 39.3 44.9 44.9 66.3 70.8 79.8 84.3 91.0 39.3 39.3 44.9 86.5 86.5 87.6 91.0 92.1 93.3 93.3 93.3 93.3 GE 1000 44.9 73.0 82.0 86.5 86.5 87.6 91.0 92.1 93.3 93.3 93.3 900 39.3 39.3 68.5 82.0 93.3 GE 44.9 44.9 73.0 GE 800 39.3 39.3 44.9 44.9 70.8 75.3 84.3 88.8 88.8 89.9 93.3 94.4 95.5 95.5 95.5 45.5 GE 700 39.3 39.3 44.9 44.9 70.8 75.3 84.3 88.88 88.8 89.9 93.3 94.4 95.5 95.5 95.5 95.5 89.9 91.3 94.4 95.5 95.5 95.5 95.5 70.8 88.8 88.8 GE 600 39.3 39.3 44.9 44.9 75.3 84.3 89.9 89.9 91.0 94.4 95.5 96.6 96.6 96.6 500 39.3 39.3 44.9 44.9 70.8 75.3 85.4 96.6 GE 89.9 95.5 96.6 96.6 GE 400 i 39.3 39.3 44.9 :4.9 70.8 75.3 85.4 89.9 91.0 94.4 96.6 96.6 GE 300 39.3 39.3 44.9 44.9 70.8 75.3 85.4 89.9 89.9 91.0 94.4 95.5 96.6 96.6 96.6 96.6 95.5 75.3 89.9 89.9 91.0 94.4 96.6 96.6 96.6 96.6 GE 200 33.3 39.3 44.9 44.9 70.8 85.4 96.6 75.3 89.9 89.9 91.0 94.4 95.5 96.6 96.6 96.6 39.3 39.3 44.9 85.4 000 39.3 39.3 44.9 44.9 70.8 75.3 85.4 89.9 89.9 91.0 94.4 95.5 96.6 96.6 96.6 100.0

TOTAL NUMBER OF OBSERVATIONS 89

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: DEC HOURS: 03-05

| CEILING VISIBILITY IN METERS |              |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
|------------------------------|--------------|--------------|---------------|---------------|---------------|--------------|---------------|---------------|---------------|---------------|---------------|-------------|---------------|--------------|---------------|-------------|-------------|
| OF I                         | ·····        | • • • • • •  | • • • • • • • | • • • • • • • | • • • • • • • |              |               |               |               | • • • • • • • | • • • • • • • | • • • • • • | • • • • • •   |              | • • • • • • • | • • • • • • | • • • • • • |
|                              |              | <b>~</b> ••• | <b>~</b>      |               | ~=            |              |               |               |               | <b>an</b>     |               | an.         | -             | 0.77         | an.           | <b>an</b>   | C.P.        |
| I                            | 1            | GE           | GE            | GE            | GE            | GE           | GE            | GE            | GE            | GE            | GE            | GE          | GE            | GE           | GE            | GE          | GE          |
| FE                           | ET           | 112          | 90            | 90            | 60            | 48           | 40            | 32            | 24            | 20            | 16            | 12          | 10            | 08           | 06            | 04          | 00          |
| • • •                        |              |              |               | • • • • • •   |               | • • • • • •  | • • • • • • • |               | • • • • • • • | • • • • • •   | • • • • • •   | • • • • • • | • • • • • • • | • • • • • •  | • • • • • • • | • • • • • • | • • • • • • |
|                              |              |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
| NO                           | CEIL         |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
| an.                          | 20000        |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
|                              | 20000        |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
|                              | 18000        |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
|                              | 16000        |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
|                              | 14000        |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
| GE                           | 12000        |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
| O.E.                         | 10000        |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
|                              | 9000         |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
| GE                           |              |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
| GE                           | 8000         |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
| GE                           | 7000         |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
| GE                           | 6000         |              |               |               |               |              |               |               |               |               |               |             |               |              |               |             |             |
| GE                           | 5000         | 32.2         | 34.4          | 47.8          | 47.8          | 56.7         | 63.3          | 70.0          | 71.1          | 71.1          | 71.1          | 72.2        | 72.2          | 72.2         | 72.2          | 72.2        | 72.2        |
|                              |              |              |               |               |               |              |               |               |               |               |               |             | 72.2          | 72.2         | 72.2          | 72.2        | 72.2        |
| GE                           | 4500         | 32.2         | 34.4          | 47.8          | 47.8          | 56.7         | 63.3          | 70.0          | 71.1          | 71.1          | 71.1          | 72.2        |               |              |               |             |             |
| GE                           | 4000         | 32.2         | 34.4          | 47.8          | 47.8          | 56.7         | 63.3          | 70.0          | 72.2          | 72.2          | 72.2          | 73.3        | 73.3          | 73.3         | 73.3          | 73.3        | 73.3        |
| GE                           | 3500         | 32.2         | 34.4          | 47.8          | 47.8          | 56.7         | 63.3          | 70.0          | 72.2          | 72.2          | 72.2          | 73.3        | 73.3          | 73.3         | 73.3          | 73.3        | 73.3        |
| GE                           | 3000         | 32.2         | 34.4          | 48.9          | 48.9          | 62.2         | 68.9          | 75.6          | 78.9          | 81.1          | 81.1          | 84.4        | 84.4          | 84.4         | 84.4          | 84.4        | 84.4        |
| O.F.                         | 25.00        | 33.0         | 24.4          | 40.0          | 40.0          | 63.3         | 70.0          | 76.7          | 00.0          | 02.2          | 02.2          | 85.6        | 85.6          | 85.6         | 85.6          | 85.6        | 85.6        |
| GE                           | 2500<br>2000 | 32.2         | 34.4          | 48.9          | 48.9          | 63.3<br>63.3 | 70.0<br>70.0  |               | 80.0          | 82.2          | 82.2          |             | 85.6          | 85.6         | 85.6          | 85.6        | 85.6        |
| GE                           | - 1          | 32.2         | 34.4          | 48.9          | 48.9          |              |               | 76.7          | 80.0          | 82.2          | 82.2          | 85.6        |               |              |               |             |             |
| GE                           | 1800         | 32.2         | 34.4          | 48.9          | 48.9          | 63.3         | 70.0          | 76.7          | 80.0          | 82.2          | 82.2          | 85.6        | 85.6          | 86.7         | 86.7          | 86.7        | 86.7        |
| G.                           | 1500         | 32.2         | 34.4          | 48.9          | 48.9          | 63.3         | 70.0          | 76.7          | 80.0          | 82.2          | 82.2          | 88.9        | 88.9          | 92.2         | 92.2          | 92.2        | 92.2        |
| GE                           | 1200         | 32.2         | 34.4          | 48.9          | 48.9          | 63.3         | 70.0          | 76.7          | 80.0          | 82.2          | 82.2          | 88.9        | 88.9          | 92.2         | 92.2          | 92.2        | 92.2        |
| O.F.                         | 1000         | 22.2         | 24.4          | 40.0          | 40.0          | 66.7         | 77.3          | 00 0          | 02.1          | 05.6          | 05.6          | 92.2        | 92.2          | 05.6         | 95.6          | 95.6        | 95.6        |
| GE<br>GE                     | 1000         | 32.2         | 34.4          | 48.9          | 48.9          | 66.7<br>66.7 | 73.3<br>73.3  | 80.0<br>80.0  | 83.3          | 85.6          | 85.6          | 92.2        | 92.2          | 95.6<br>95.6 |               |             | 95.6        |
|                              |              | 32.2         | 34.4          | 48.9          | 48.9          |              |               |               | 83.3          | 85.6          | 85.6          |             |               |              | 95.6          | 95.6        |             |
| GE                           | 800          | 32.2         | 34.4          | 48.9          | 48.9          | 67.8         | 74.4          | 81.1          | 84.4          | 86.7          | 86.7          | 93.3        | 93.3          | 96.7         | 96.7          | 96.7        | 96.7        |
| GE                           | 700          | 32.2         | 34.4          | 48.9          | 48.9          | 67.8         | 74.4          | 81.1          | 84.4          | 86.7          | 86.7          | 93.3        | 93.3          | 96.7         | 96.7          | 96.7        | 96.7        |
| GE                           | 600          | 32.2         | 34.4          | 48.9          | 48.9          | 67.8         | 74.4          | 81.1          | 84.4          | 86.7          | 86.7          | 93.3        | 93.3          | 96.7         | 96.7          | 96.7        | 96.7        |
| art                          | 500          | 10.0         | 24.4          | 40.0          | 40.0          | 67.6         | 74.4          | 01 1          | 04.4          | oc 7          | 06.7          | 01.3        | 03.3          | 05.7         | 06.3          | 06.3        | 06.7        |
| GE.                          | 500          | 32.2         | 34.4          | 48.9          | 48.9          | 67.8         | 74.4          | 81.1          | 84.4          | R6.7          | 86.7          | 93.3        | 93.3          | 96.7         | 96.7          | 96.7        | 96.7        |
| GE                           | 400          | 32.2         | 34.4          | 48.9          | 48.9          | 67.8         | 74.4          | 81.1          | 84.4          | 86.7          | 86.7          | 93.3        | 93.3          | 96.7         | 96.7          | 96.7        | 96.7        |
| GE                           | 300          | 32.2         | 34.4          | 48.9          | 48.9          | 67.8         | 74.4          | 81.1          | 84.4          | 86.7          | 86.7          | 93.3        | 93.3          | 96.7         | 96.7          | 96.7        | 96.7        |
| GE                           | 200          | 32.2         | 34.4          | 48.9          | 48.9          | 67.8         | 74.4          | 81.1          | 84.4          | 86.7          | 86.7          | 93.3        | 93.3          | 96.7         | 96.7          | 96.7        | 96.7        |
| GE                           | 100          | 32.2         | 34.4          | 48.9          | 48.9          | 67.8         | 74.4          | 81.1          | 84.4          | 86.7          | 86.7          | 93.3        | 93.3          | 96.7         | 96.7          | 96.7        | 97.8        |
|                              | 000          | 12.2         | 24.4          | 40.0          | 40.0          | 67.0         | 74.4          | 01.4          |               | 06.3          | 06.7          | 03.3        | 03.3          | 06.3         | 06.3          | 06.3        | 100.0       |
| GE                           | 000          | 32.2         | 34.4          | 48.9          | 48.9          | 67.8         | 74.4          | 81.1          | 84.4          | 86.7          | 86.7          | 93.3        | 93.3          | 96.7         | 96.7          | 96.7        | 100.0       |
| • • •                        | • • • • • •  |              | • • • • • •   | • • • • • • • | • • • • • •   |              | • • • • • • • | • • • • • • • | • • • • • • • | • • • • • •   | • • • • • •   | • • • • • • | • • • • • •   | • • • • • •  | • • • • • •   | • • • • • • | • • • • • • |

TOTAL NUMBER OF OBSERVATIONS 9

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: DEC HOURS: 06-08

| CEI       | LING        |              |              | • • • • • • • |               | • | VISIBIL      | ITY IN I      | METERS       |              | • • • • • • • | • • • • • • • | • • • • • •  | • • • • • • • | • • • • • • • | • • • • • •  | •••••        |
|-----------|-------------|--------------|--------------|---------------|---------------|---|--------------|---------------|--------------|--------------|---------------|---------------|--------------|---------------|---------------|--------------|--------------|
|           | N           | GE           | GE           | GE            | GE            | GE                                      | GE           | GE            | GE           | GE           | GE            | GE            | GE           | GE            | GE            | GE           | GE           |
| FE        | ET          | 112          | 90           | 80            | 60            | 48                                      | 40           | 32            | 24           | 20           | 16            | 12            | 10           | 08            | 06            | 04           | 00           |
| • • •     |             |              |              |               | • • • • • •   |   |              | • • • • • •   | • • • • • •  |              |               |               | • • • • • •  |               |               |              | • • • • • •  |
|           |             |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
| NO        | CEIL        |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
| O.F.      | 20000       |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
|           | 18000       |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
|           | 16000       |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
|           | 14000       |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
|           | 12000       |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
|           |             |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
| GE        | 10000       |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
| GE        | 9000        |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
| GE        | 8000        |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
| GE        | 7000        |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
| GE        | 6000        |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
| GE        | 5000        | 26.7         | 26.7         | 42.2          | 42.2          | 53.3                                    | 53.3         | 55.6          | 57.8         | 60.0         | 61.1          | 62.2          | 62.2         | 62.2          | 62.2          | 62.2         | 62.2         |
| GE        | 4500        | 26.7         | 26.7         | 42.2          | 42.2          | 53.3                                    | 53.3         | 55.5          | 57.8         | 60.0         | 61.1          | 62.2          | 62.2         | 62.2          | 62.2          | 62.2         | 63.3<br>63.3 |
| GE        | 4000        | 26.7         | 26.7         | 43.3          | 43.3          | 55.6                                    | 55.6         | 57.8          | 63.3         | 65.6         | 66.7          | 67.8          | 67.8         | 67.8          | 67.8          | 67.8         | 68.9         |
| GE        | 3500        | 26.7         | 26.7         | 43.3          | 43.3          | 56.7                                    | 56.7         | 58.9          | 64.4         | 66.7         | 67.8          | 68.9          | 68.9         | 68.9          | 68.9          | 68.9         | 70.0         |
| GE        | 3000        | 26.7         | 26.7         | 43.3          | 43.3          | 61.1                                    | 62.2         | 64.4          | 71.1         | 74.4         | 75.6          | 78.9          | 80.0         | 80.0          | 80.0          | 80.0         | 81.1         |
|           | 1           |              |              |               |               |   |              |               |              |              |               |               |              |               |               |              |              |
| GE        | 2500        | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 66.7          | 73.3         | 76.7         | 77.8          | 82.2          | 83.3         | 83.3          | 83.3          | 83.3         | 84.4         |
| GΕ        | 2000        | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 66.7          | 73.3         | 77.8         | 78.9          | 84.4          | 85.6         | 85.6          | 85.6          | 85.6         | 86.7         |
| GE        | 1800        | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 66.7          | 73.3         | 77.8         | 78.9          | 84.4          | 85.6         | 85.6          | 85.6          | 85.6         | 86.7         |
| GΕ        | 1500        | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 67.8          | 74.4         | 78.9         | 80.0          | 86.7          | 87.8         | 93.3          | 93.3          | 93.3         | 94.4         |
| GE        | 1200        | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 67.8          | 74.4         | 78.9         | 80.0          | 86.7          | 87.8         | 93.3          | 93.3          | 93.3         | 94.4         |
| ar        | 1000        | 26 7         | 26.7         | 42.2          | 43.3          | 62.2                                    | 64.4         | 67.0          | 74.4         | 70.0         | 01 1          | 07.0          | 00.0         |               |               | 04.4         | 05.6         |
| GE<br>GE  | 1000<br>900 | 26.7<br>26.7 | 26.7<br>26.7 | 43.3<br>43.3  | 43.3<br>43.3  | 63.3<br>63.3                            | 64.4<br>64.4 | 67.8<br>67.8  | 74.4<br>74.4 | 78.9<br>78.9 | 81.1<br>81.1  | 87.8<br>87.8  | 88.9<br>88.9 | 94.4<br>94.4  | 94.4<br>94.4  | 94.4<br>94.4 | 95.6<br>95.6 |
| GE        | 800         | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 68.9          | 75.6         | 80.0         | 82.2          | 90.0          | 92.2         | 97.8          | 94.4          | 97.8         | 98.9         |
| GE        | 700         | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 68.9          | 75.6         | 80.0         | 82.2          | 90.0          | 92.2         | 97.8          | 97.8          | 97.8         | 98.9         |
| GE        | 600         | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 68.9          | 75.6         | 80.0         | 82.2          | 90.0          | 92.2         | 97.8          | 97.8          | 97.8         | 98.9         |
|           |             |              |              |               |               |   |              |               |              |              |               |               |              |               | •             | *            | -0.0         |
| GE        | 500         | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 68.9          | 75.6         | 80.0         | 82.2          | 90.0          | 92.2         | 97.8          | 97.8          | 97.8         | 98.9         |
| GE        | 400         | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 68.9          | 75.6         | 80.0         | 82.2          | 90.0          | 92.2         | 97.8          | 97.8          | 97.8         | 98.9         |
| GE        | 300         | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 68.9          | 75.6         | 80.0         | 82.2          | 90.0          | 92.2         | 97.8          | 97.8          | 97.8         | 98.9         |
| GE        | 200         | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 68.9          | 75.6         | 80.0         | 82.2          | 90.0          | 92.2         | 97.8          | 97.8          | 97.8         | 98.9         |
| GE        | 100         | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 68.9          | 75.6         | 80.0         | 82.2          | 90.0          | 92.2         | 97.8          | 97.8          | 97.8         | 98.9         |
| <b>65</b> | 000         | 26.7         | 26.3         | 42.2          | 42.2          | 63.3                                    |              |               | 75.6         | 22.5         |               |               |              |               |               |              | ***          |
| GE        | 000         | 26.7         | 26.7         | 43.3          | 43.3          | 63.3                                    | 64.4         | 68.9          | 75.6         | 80.0         | 82.2          | 90.0          | 92.2         | 97.8          | 97.8          | 97.8         | 100.0        |
|           |             |              | • • • • • •  | • • • • • • • | • • • • • • • | • • • • • • •                           |              | • • • • • • • | • • • • • •  |              | • • • • • • • | • • • • • • • |              |               | • • • • • • • | <i>-</i>     | • · • • •    |

TOTAL NUMBER OF OBSERVATIONS 90

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9 MONTH: DEC HOURS: 09-11 CEILING VISIBILITY IN METERS GE GE GE IN GE GE GE GE GΕ GE GE GE GE GE GE GE GΕ 112 60 20 16 12 08 06 00 90 80 48 40 32 24 10 04 FEET NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 8000 GΕ GE 7000 GE 6000 23.3 41.7 41.7 55.0 55.0 55.0 55.0 56.7 60.0 61.7 61.7 61.7 61.7 61.7 63.3 GE 5000 18.3 GE. 4500 18.3 23.3 41.7 41.7 55.0 55.0 55.0 55.0 56.7 60.0 61.7 61.7 61.7 61.7 61.7 63.3 GE 4000 18.3 23.3 46.7 46.7 60.0 60.0 60.0 60.0 61.7 65.0 66.7 66.7 66.7 66.7 66.7 68.3 3500 18.3 46.7 46.7 61.7 63.3 63.3 70.0 70.0 70.0 70.0 70.0 GE 23.3 63.3 65.0 68.3 71.7 GE 3000 18.3 23.3 46.7 46.7 65.0 66.7 66.7 66.7 68.3 71.7 73.3 73.3 76.7 76.7 76.7 78.3 46.7 GE 2500 18.3 23.3 46.7 65.0 66.7 66.7 66.7 68.3 71.7 75.0 76.7 80.0 80.0 80.0 81.7 GE 2000 18.3 23.3 46.7 46.7 65.0 66.7 66.7 66.7 68.3 71.7 75.0 76.7 80.0 80.0 80.0 81.7 1800 18.3 23.3 46.7 46.7 65.0 66.7 66.7 68.3 75.0 76.7 80.0 80.0 80.0 GE 66.7 71.7 81.7 68.3 CF 1500 18.3 23.3 46.7 46.7 65.0 66.7 66.7 66.7 73.3 80.0 85.0 90.0 90.0 90.0 91.7 GE 1200 18.3 23.3 46.7 46.7 65.0 66.7 66.7 66.7 68.3 73.3 80.0 85.0 90.0 90.0 90.0 91.7 GE 1000 18.3 23.3 46.7 46.7 65.0 66.7 66.7 66.7 68.3 73.3 83.3 88.3 93.3 93.3 93.3 95.0 GE 900 18.3 23.3 46.7 46.7 65.0 66.7 66.7 66.7 68.3 73.3 83.3 88.3 93.3 93.3 93.3 65.0 91.3 93.3 GE 800 18.3 23.3 46.7 46.7 66.7 66.7 68.3 73.3 83.3 88.3 93.3 95.0 66.7 GE 700 18.3 23.3 46.7 46.7 65.0 66.7 66.7 66.7 68.3 73.3 83.3 88.3 93.3 93.3 93.3 95.0 GE 600 18.3 23.3 46.7 46.7 65.0 66.7 66.7 68.3 73.3 83.3 88.3 93.3 93.3 93.3 95.0 66.7 GE 500 18.3 23.3 46.7 46.7 65.0 66.7 66.7 66.7 68.3 73.3 83.3 88.3 93.3 93.3 93.3 400 18.3 46.7 46.7 65.0 66.7 88.3 93.3 93.3 93.3 GE 23.3 66.7 66.7 68.3 73.3 83.3 95.0 GE 300 18.3 23.3 46.7 46.7 65.0 66.7 66.7 66.7 68.3 73.3 83.3 88.3 93.3 93.3 93.3 95.0 GE 200 18.3 23.3 46.7 46.7 65.0 66.7 66.7 66.7 68.3 73.3 83.3 88.3 93.3 93.3 95.0 96.7 18.3 100 46.7 46.7 65.0 88.3 93.3 93.3 95.0 100.0 GE 23.3 66.7 66.7 66.7 68.3 73.3 83.3 46.7 68.3 73.3 83.3 88.3 93.3 93.3 95.0 100.0 000 18.3 23.3 46.7 65.0 66.7 66.7 66.7

STATION NUMBER: 471066

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: DEC HOURS: 12-14 CEILING VISIBILITY IN METERS IN GE GE GE GE GΕ GE GE GE GE GE GE GE GE GE Œ GE FEET 112 90 80 60 48 40 32 24 20 16 12 10 80 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 GE 5000 40.0 41.1 52.2 52.2 64.4 64.4 66.7 67.8 68.9 72.2 72.2 73.3 73.3 73.3 73.3 73.3 GE 4500 40.0 41.1 52.2 52.2 64.4 64.4 66.7 67.8 68.9 72.2 72.2 73.3 73.3 73.3 73.3 73.3 68.9 77.8 4000 54.4 68.9 71.1 72.2 73.3 76.7 76.7 77.8 77.8 77.8 GE 42.2 43.3 54.4 77.8 GE 3500 42.2 43.3 57.8 57.8 72.2 72.2 74.4 75.6 76.7 80.0 80.0 81.1 81.1 81.1 81.1 81.1 91.1 3000 42.2 43.3 61.1 61.1 77.8 77.8 82.2 85.6 86.7 90.0 90.0 91.1 91.1 91.1 GE 91.1 GE 2500 42.2 43.3 61.1 61.1 77.8 78.9 83.3 86.7 87.8 91.1 91.1 92.2 92.2 92.2 92.2 92.2 GE 2000 42.2 43.3 77.8 78.9 87.8 91.1 91.1 92.2 92.2 92.2 92.2 61.1 61.1 83.3 86.7 92.2 77.8 GE 1800 42.2 43.3 61.1 61.1 78.9 83.3 86.7 87.8 91.1 91.1 92.2 92.2 92.2 92.2 92.2 GE 1500 42.2 43.3 61.1 77.8 78.9 88.9 90.0 95.6 96.7 97.8 97.8 97.8 97.8 97.8 61.1 83.3 GE 1200 42.2 43.3 77.8 95.6 97.8 97.8 97.8 97.8 61.1 61.1 78.9 88.9 90.0 96.7 97.8 83.3 GΕ 1000 42.2 43.3 61.1 61.1 77.8 78.9 83.3 88.9 90.0 95.6 96.7 97.8 97.8 97.8 97.8 GE 900 42.2 43.3 77.8 78.9 96.7 98.9 61.1 61.1 83.3 88.9 90.0 97.8 98.9 38.9 98.9 98.9 GE 800 42.2 43.3 61.1 61.1 77.8 78.9 83.3 88.9 90.0 96.7 98.9 100.0 100.0 100.0 100.0 100.0 700 GΕ 42.2 43.3 61.1 61.1 77.8 78.9 83.3 88.9 90.0 96.7 98.9 100.0 100.0 100.0 100.0 100.0 600 GE 42.2 43.3 61.1 61.1 77.8 78.9 83.3 88.9 90.0 96.7 98.9 100.0 100.0 100.0 100.0 100.0

STATION NAME: CAMP CASEY/TONGDUCHON KO

77.8

77.8

77.8

77.8

77.8

61.1 77.8

61.1

61.1

61.1

61.1

61.1

78.9

78.9

78.9

78.9

78.9

78.9

83.3

83.3

83.3

83.3

83.3

83.3

88.9

88.9

88.9

88.9

88.9

88.9

90.0

90.0

90.0

90.0

90.0

90.0

96.7

96.7

96.7

96.7

96.7

96.7

98.9

98.9

98.9

98.9

98.9

100.0

100.0

100.0 100.0 100.0

100.0

100.0 100.0 100.0 100.0 100.0

100.0 100.0 100.0 100.0 100.0

100.0 100.0

98.9 100.0 100.0 100.0 100.0 100.0

100.0

100.0 100.0

100.0 100.0

100.0

100.0

TOTAL NUMBER OF OBSERVATIONS 90

43.3

43.3

43.3

43.3

43.3

43.3 61.1

61.1

61.1

61.1

61.1

61.1

GE

GE

GE

CE

GE

GE

500

400

300

200

100

42.2

42.2

42.2

42.2

42.2

000 42.2

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: DEC HOURS: 15-17 CEILING VISIBILITY IN METERS GE IN GE GE GE GE GE GE GE GE GE GE GE GE GE GE GE 112 80 60 48 40 32 20 16 12 10 08 06 04 00 NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 8000 GE 7000 GE GE 6000 58.9 76.7 76.7 76.7 GE 5000 46.7 46.7 58.9 76.7 76.7 76.7 76.7 76.7 76.7 76.7 76.7 76.7 GE 4500 46.7 46.7 58.9 58.9 76.7 76.7 76.7 76.7 76.7 76.7 76.7 76.7 76.7 76.7 76.7 76.7 GE 4000 47.8 47.8 61.1 61.1 80.0 81.1 81.1 81.1 81.1 81.1 81.1 81.1 81.1 81.1 81.1 81.1 3500 GE 47.8 47.8 83.3 84.4 84.4 84.4 62.2 62.2 84.4 84.4 84.4 84.4 84.4 84.4 84.4 84.4 GE 3000 52.2 53.3 70.0 70.0 94.4 96.7 96.7 96.7. 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 70.0 70.0 96.7 96.7 96.7 2500 52.2 53.3 94.4 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 2000 52.2 53.3 70.0 70.0 94.4 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 1800 96.7 GE 52.2 53.3 70.0 70.0 94.4 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 96.7 GE 1500 52.2 53.3 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 1200 52.2 50.3 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 1000 52.2 53.3 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 900 52.2 53.3 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 800 52.2 53.3 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 700 52.2 53.3 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 600 52.2 53.3 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 500 52.2 53.3 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 400 52.2 70.0 70.0 97.8 100.0 100.0 100.0 53.3 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 300 52.2 53.3 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 200 52.2 53.3 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 GE 100 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 52.2 53.3 000 52.2 53.3 70.0 70.0 97.8 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: DEC HOURS: 18-20

| CELLING VICIDILITY IN METTERS |              |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
|-------------------------------|--------------|--------------|--------------|--------------|--------------|--------------|---------------|--------------|-------|--------------|---------------|---------------|-------|---------------|---------------|-------|-------|
| CETI                          | CEILING      |              |              |              |              |              |               |              |       |              |               |               |       |               | • • • • • •   |       |       |
|                               |              | CF           | CF           | CP           | CE           |              |               |              |       | CF           | GF.           | CF            | GF.   | CF.           | GE            | GF.   | GF.   |
|                               |              | 112          | 90           | 80           | 60           | 48           | 40            | 32           | 24    | 20           | 16            | 12            | 10    | 08            | 06            | 04    | 00    |
| rEI                           | e. 1         | 112          | 90           | 80           | 00           | 40           | 40            | 32           | 24    | 20           | 10            | 12            | 10    | 00            | 00            | 04    | 00    |
| •••                           |              |              | • • • • • •  |              |              | • • • • • •  | • • • • • • • |              |       | • • • • • •  | • • • • • • • | • • • • • • • |       | • • • • • • • | • • • • • • • |       |       |
| NO (                          | CEIL         |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| .,,                           |              |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| GE 2                          | 20000        |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
|                               | 18000        |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
|                               | 16000        |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| GE :                          | 14000        |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| GE :                          | 12000        |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
|                               |              |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| GE :                          | 10000        |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| GE                            | 9000         |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| GE                            | 8000         |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| GE                            | 7000         |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| GE                            | 6000         |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
|                               |              |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| GE                            | 5000         | 44.2         | 45.3         | 54.7         | 54.7         | 70.9         | 72.1          | 74.4         | 75.6  | 75.6         | 75.6          | 75.6          | 75.6  | 75.6          | 75.6          | 75.6  | 75.6  |
| GE                            | 4500         | 44.2         | 45.3         | 54.7         | 54.7         | 70.9         | 72.1          | 74.4         | 75.6  | 75.6         | 75.6          | 75.6          | 75.6  | 75.6          | 75.6          | 75.6  | 75.6  |
| GE                            | 4000         | 44.2         | 45.3         | 54.7         | 54.7         | 72.1         | 73.3          | 75.6         | 76.7  | 76.7         | 76.7          | 76.7          | 76.7  | 76.7          | 76.7          | 76.7  | 76.7  |
| GE                            | 3500         | 44.2         | 45.3         | 54.7         | 54.7         | 75.6         | 77.9          | 80.2         | 83.7  | 83.7         | 83.7          | 83.7          | 83.7  | 83.7          | 83.7          | 83.7  | 83.7  |
| GE                            | 3000         | 45.3         | 46.5         | 59.3         | 59.3         | 83.7         | 87.2          | 93.0         | 96.5  | 96.5         | 96.5          | 96.5          | 96.5  | 96.5          | 96.5          | 96.5  | 96.5  |
| an.                           | 2500         | 45 3         | 46 5         | 50.3         | 50.3         | 03.7         | 87.2          | 03.0         | 96.5  | 05.5         | 96.5          | 0.0           | 96.5  | 96.5          | 96.5          | 96.5  | 96.5  |
| GE                            | 2500<br>2000 | 45.3         | 46.5<br>46.5 | 59.3<br>59.3 | 59.3<br>59.3 | 83.7<br>83.7 | 88.4          | 93.0<br>95.3 | 98.8  | 96.5<br>98.8 | 98.8          | 96.5<br>98.8  | 98.8  | 98.8          | 98.8          | 98.8  | 98.8  |
| GE<br>GE                      | 1800         | 45.3<br>45.3 | 46.5         | 59.3         | 59.3         | 83.7         | 88.4          | 95.3         | 98.8  | 98.8         | 98.8          | 98.8          | 98.8  | 98.8          | 98.8          | 98.8  | 98.8  |
| GE                            | 1500         | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
| GE                            | 1200         | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
| GE                            | 12.00        | 45.5         | 40.5         | 33.3         | 33.3         | 04.3         | 09.5          | 30.3         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
| GE                            | 1000         | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
| GE                            | 900          | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
| GE                            | 800          | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
| GE                            | 700          | 45.3         | 45.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
| GE                            | 600          | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
|                               |              |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| GE                            | 500          | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
| GE                            | 400          | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
| GE                            | 300          | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
| GE                            | 200          | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
| GE                            | 100          | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
|                               |              |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
| GE                            | 000          | 45.3         | 46.5         | 59.3         | 59.3         | 84.9         | 89.5          | 96.5         | 100.0 | 100.0        | 100.0         | 100.0         | 100.0 | 100.0         | 100.0         | 100.0 | 100.0 |
|                               |              |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |
|                               |              |              |              |              |              |              |               |              |       |              |               |               |       |               |               |       |       |

STATION NUMBER: 471066

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: DEC HOURS: 21-23

CEILING VISIBILITY IN METERS IN GE GE GE GE GE GE GE GΕ GE GE GE GΕ GΕ GE GΕ GΕ FEET 112 90 80 60 48 40 32 24 20 16 12 10 80 06 04 00 NO CELL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 GE 6000 77.4 GE 5000 39.3 45.2 45.2 61.9 61.9 71.4 77.4 77.4 77.4 77.4 77.4 77.4 77.4 78.6 36.9 77.4 GE4500 36.9 39.3 45.2 45.2 61.9 61.9 71.4 77.4 77.4 77.4 77.4 77.4 77.4 77.4 78.6 77.4 77.4 GE 4000 36.9 39.3 45.2 45.2 61.9 61.9 71.4 77.4 77.4 77.4 77.4 77.4 77.4 78.6 CE 2500 39.3 46.4 77.4 83.3 83.3 93.3 83.3 46.4 67.9 67.9 83.3 83.3 83.3 84.5 36.9 83.3 GE 3000 38.1 40.5 48.8 48.8 72.6 72.6 84.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 90.5 91.7 72.6 90.5 90.5 90.5 90.5 90.5 90.5 GE 2500 38.1 40.5 48.8 48.8 72.6 84.5 90.5 90.5 91.7 GE 2000 38.1 40.5 48.8 48.8 72.6 75.0 88.1 94.0 94.0 94.0 97.6 97.6 97.6 97.6 97.6 98.8 97.6 1800 38.1 40.5 48.8 48.8 72.6 75.0 88.1 94.0 94.0 94.0 97.6 97.6 97.6 97.6 98.8 GE 1500 38.1 40.5 48.8 48.8 72.6 75.0 88.1 94.0 94.0 94.0 97.6 97.6 97.6 97.6 97.6 98.8 GF GE 1200 38.1 40.5 48.8 48.8 72.6 75.0 88.1 94.0 94.0 94.0 97.6 97.6 97.6 97.6 97.6 98.8 75.0 97.6 97.6 GE 1000 38.1 40.5 48.8 48.8 72.6 88.1 94.0 94.0 94.0 97.6 97.6 97.6 98.8 GE 900 38.1 40.5 48.8 48.8 72.6 75.0 88.1 94.0 94.0 94.0 97.6 97.6 97.6 97.6 97.6 98.8 800 40.5 97.6 97.6 97.6 97.6 97.6 38.1 48.8 48.8 72.6 75.0 88.1 94.0 94.0 94.0 98.8 GE GE 700 38.1 40.5 48.8 48.8 72.6 75.0 88.1 94.0 94.0 94.0 97.6 97.6 97.6 97.6 97.6 98.8 GE600 38.1 40.5 48.8 48.8 72.6 75.0 88.1 94.0 94.0 94.0 97.6 97.6 97.6 97.6 97.6 98.8

STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: - 9

TOTAL NUMBER OF OBSERVATIONS 84

40.5

40.5

40.5

40.5

40.5

40.5 48.8

48.8

48.8

48.8

48.8

48.8

48.8

48.8

48.8

48.8

48.8

48.8

72.6

72.6

72.6

72.6

72.6

72.6

75.0

75.0

75.0

75.0

75.0

75.0

88.1

88.1

88.1

88.1

88.1

88.1

GE

GE

GE

GE

GE

GE

500

400

300

200

100

38.1

38.1

38.1

38.1

38.1

000 38.1

D - 2 - 107

94.0

94.0

94.0

94.0

94.0

94.0

94.0

94.0

94.0

94.0

94.0

94.0

94.0

94.0

94.0

94.0

94.0

94.0

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6

97.6 97.6

97.6

97.6

97.6

97.5

97.6

97.6 100.0

98.8

98.8

98.8

98.8

98.8

STATION NUMBER: 471066

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: DEC HOURS: ALL CELLING VISIBILITY IN METERS GE GE GÉ IN GE GE GE GE GE GE GE GE GE GE GE GE GE 60 48 24 112 90 80 40 32 20 16 12 10 08 06 04 00 FEET NO CEIL GE 20000 GE 18000 GE 16000 GE 14000 GE 12000 GE 10000 GE 9000 GE 8000 GE 7000 6000 GE GE 5000 35.8 37.1 48.3 48.3 62.2 63.8 67.6 69.7 70.3 71.1 71.6 71.7 71.7 71.7 71.7 72.2 37.1 48.3 48.3 62.2 63.8 67.6 69.7 70.3 71.1 71.6 71.7 71.7 71.7 71.7 72.2 GE 4500 35.8 4000 36.5 37.A 49.8 49.8 64.4 66.1 70.0 72.6 73.2 74.1 74.5 74.7 74.7 74.7 74.7 75.1 GE GE 3500 36.5 37.8 50.5 50.5 66.9 68.9 72.8 75.7 76.3 77.2 77.6 77.8 77.8 77.8 77.8 78.2 73.0 75.6 80.6 87.2 87.5 87.8 87.8 87.8 88.2 GE 3000 37.6 39.0 53.2 53.2 84.1 85.1 86.2 GE 2500 37.6 39.0 53.2 53.2 73.5 76.1 81.1 84.7 85.7 86.7 88.1 88.5 88.8 88.8 88.8 89.2 GE 2000 37.6 39.0 53.2 53.2 73.6 76.7 82.2 85.7 86.9 87.9 90.0 90.6 91.0 91.0 91.0 91.5 91.2 GE 1800 37.6 39.0 53.2 53.2 73.6 76.7 82.2 85.7 86.9 87.9 90.0 90.6 91.2 91.2 91.6 1500 37.6 39.0 53.2 53.2 74.2 77.3 82.9 86.7 87.9 89.4 92.8 93.7 95.4 95.4 95.4 95.9 GE 37.6 53.2 77.3 82.9 89.4 93.7 95.4 95.4 95.4 95.9 GE 1200 39.0 53.2 74.2 86.7 87.9 92.8 GE 1000 37.6 39.0 53.2 53.2 75.0 78.1 83.7 87.5 88.7 90.3 94.0 94.8 96.6 96.6 96.6 97.1 900 39.0 78.1 83.7 88.7 90.4 94.1 95.0 96.8 96.8 96.8 97.2 GE 37.6 53.2 53.2 75.0 87.5 GE 800 37.6 39.0 53.2 53.2 75.4 78.5 84.2 88.1 89.2 91.0 95.0 96.0 97.8 97.8 97.8 98.2 84.2 GE 700 37.6 39.0 53.2 53.2 75.4 78.5 88.1 89.2 91.0 95.0 96.0 97.8 97.8 97.8 98.2 37.6 75.4 78.5 95.0 97.8 39.0 53.2 53.2 84.2 89.2 91.0 96.0 97.8 97.8 98.2 GE 600 88.1

STATION NAME: CAMP CASEY/TONGDUCHON KO

TOTAL NUMBER OF OBSERVATIONS 679

39.0

39.0

39.0

39.0

39.0

39.0

53.2

53.2

53.2

53.2

53.2

53.2

53.2

53.2

53.2

53.2

53.2

75.4

75.4

75.4

75.4

75.4

53.2 75.4

78.5

78.5

78.5

78.5

78.5

78.5

84.4

84.4

84.4

84.4

84.4

88.2

88.2

88.2

88.2

88.2

84.4 88.2

500

400

300

200

100

GE

GE

GE

GE

GE

GE

37.6

37.6

37.6

37.6

37.6

000 37.6

89.4

89.4

89.4

89.4

89.4

89.4

91.2

91.2

91.2

91.2

91.2

91.2

95.1

95.1

95.1

95.1

95.1

95.1

96.2

96.2

96.2

96.2

96.2

96.2

97.9

97.9

97.9

97.9

97.9

97.9

97.9

97.9

97.9

97.9

97.9

97.9

97.9

97.9

98.1

98.1

98.1 100.0

98.4

98.4

98.4

98.5

99.0

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIGIL.TY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST '10 UTC: - 9 MONTH: ALL HOURS: ALL

| CEILI | NG    |              |              |              | • • • • • • • |       | <br>/ISIBIL | ייייייייייייייייייייייייייייייייייייי | TETERS       |              | · • • • • • • |      |      | • • • • • • | • • • • • • |      | • • • • • |
|-------|-------|--------------|--------------|--------------|---------------|-------|-------------|---------------------------------------|--------------|--------------|---------------|------|------|-------------|-------------|------|-----------|
| IN    |       | GE           | GE           | GE           | GE            | GE    | GE          | GE                                    | GE           | GE           | GE            | GZ   | GE   | GE          | GE          | GE   | GE        |
| FEET  |       | 112          | 90           | 80           | 60            | 48    | 40          | 32                                    | 24 .         | 20           | 16            | 12   | 10   | 08          | 06          | 04   | 00        |
|       |       |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
|       | 1     |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| NO CE | IL    |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| GE 20 | 000   |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| GE 18 | 1     |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| GE 16 | - 1   |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| GE 14 |       |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| GE 12 | 000   |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
|       |       |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| GE 10 | 000   |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| GE 9  | 000   |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| GE B  | 1000  |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| GE 7  | 000   |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| GE 6  | 000   |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
| CD E  | 000   | 25 2         | 26.1         | 52.2         | <b>E2</b> 2   | 63.6  | 64.7        | 66.7                                  | 67.0         | 60 1         | 68.6          | 69.1 | 6).1 | 69.3        | 69.3        | 69.4 | 69.8      |
|       | 500   | 35.3<br>35.7 | 36.3<br>36.8 | 52.2<br>52.8 | 52.2<br>52.8  | 64.3  | 65.4        | 67.4                                  | 67.8<br>68.5 | 68.1<br>68.8 | 69.3          | 59.8 | 69.8 | 70.0        | 70.0        | 70.1 | 70.5      |
|       | 000   | 37.2         | 38.3         | 55.4         | 55.4          | 67.8  | 69.0        | 71.2                                  | 72.3         | 72.7         | 73.2          | 73.7 | 73.8 | 74.0        | 74.0        | 74.1 | 74.5      |
|       | 500   | 38.1         | 39.2         | 57.2         | 57.2          | 70.5  | 71.8        | 74.1                                  | 75.3         | 75.7         | 76.3          | 76.8 | 76.8 | 77.1        | 77.1        | 77.1 | 77.6      |
|       | 000   | 40.5         | 41.7         | 61.3         | 61.3          | 76.8  | 78.4        | 81.3                                  | 82.8         | 83.3         | 83.9          | 84.6 | 61.7 | 85.0        | 85.0        | 85.1 | 85.5      |
| 31, 3 | ,,,,, | •0.5         |              | 01.5         | 0115          | , 0.0 | , , , .     | 0113                                  | 00.0         | 05.5         | 05.5          | 3    |      | 35.0        | 00.0        | 0011 |           |
| GE 2  | 500   | 40.9         | 42.1         | 61.9         | 61.9          | 78.2  | 80.0        | 83.1                                  | 84.7         | 85.3         | 86.0          | 86.7 | 86.8 | 87.1        | 87.1        | 87.2 | 87.6      |
| GE 2  | 1000  | 41.2         | 42.4         | 62.8         | 62.8          | 79.8  | 82.0        | 85.5                                  | 87.3         | 87.9         | 88.7          | 89.7 | 89.9 | 90.2        | 90.2        | 90.3 | 90.7      |
| GE 1  | 800   | 41.2         | 42.5         | 62.8         | 62.8          | 80.1  | 82.3        | 85.9                                  | 87.7         | 88.3         | 89.1          | 90.1 | 90.3 | 90.6        | 90.6        | 90.7 | 91.2      |
| GE 1  | 500   | 41.5         | 42.7         | 63.3         | 63.3          | 81.1  | 83.5        | 87.6                                  | 89.7         | 90.4         | 91.3          | 92.5 | 92.7 | 93.1        | 93.2        | 93.3 | 93.7      |
| GE 1  | 200   | 41.5         | 42.7         | 63.4         | 63.4          | 81.6  | 84.2        | 88.5                                  | 90.7         | 91.5         | 92.5          | 93.8 | 94.0 | 94.5        | 94.5        | 94.6 | 95.0      |
|       | İ     |              |              |              |               |       |             |                                       |              |              |               |      |      |             |             |      |           |
|       | 000   | 41.6         | 42.8         | 63.5         | 63.5          | 82.1  | 84.7        | 89.3                                  | 91.7         | 92.6         | 93.7          | 95.2 | 95.4 | 95.9        | 95.9        | 96.0 | 96.5      |
|       | 900   | 41.6         | 42.8         | 63.5         | 63.5          | 82.1  | 84.8        | 89.3                                  | 91.8         | 92.7         | 93.9          | 95.3 | 95.6 | 96.1        | 96 1        | 96.2 | 96.7      |
| GE    | 800   | 41.6         | 42.8         | 63.5         | 63.5          | 82.2  | 84.8        | 89.5                                  | 92.1         | 93.0         | 94.3          | 95.8 | 96.1 | 96.7        | 96.7        | 96.8 | 97.3      |
| GE    | 700   | 41.6         | 42.8         | 63.5         | 63.5          | 82.2  | 84.9        | 89.6                                  | 92.2         | 93.1         | 94.5          | 96.1 | 96.4 | 97.0        | 97.1        | 97.2 | 97.6      |
| GE    | 600 j | 41.6         | 42.8         | 63.5         | 63.5          | 82.2  | 84.9        | 89.6                                  | 92.2         | 93.2         | 94.6          | 96.3 | 96.6 | 97.3        | 97.3        | 9~.4 | 97.9      |
| GE    | 500   | 41.6         | 42.8         | 63.5         | 63.5          | 82.2  | 84.9        | 89.6                                  | 92.3         | 93.3         | 94.8          | 93.5 | 96.9 | 97.6        | 97.6        | 97.8 | 98.3      |
| **    | 400   | 41.6         | 42.8         | 63.5         | 63.5          | 82.2  | 84.9        | 89.7                                  | 92.4         | 93.4         | 94.9          | 96.7 | 97.1 | 97.9        | 98.0        | 98.1 | 98.7      |
| GE    | 100   | 41.6         | 42.8         | 03.5         | 63.5          | 82.2  | 84.9        | 89.7                                  | 92.4         | 93.4         | 94.9          | 96.7 | 97.2 | 98.1        | 98.2        | 98.3 | 98.8      |
| GE    | 200   | 41.6         | 42.8         | 63.5         | 63.5          | 82.2  | 84.9        | 89.7                                  | 92.4         | 93.4         | 94.9          | 96.8 | 97.2 | 98.1        | 98.2        | 98.4 | 99.1      |
| GE    | 100   | 41.6         | 42.8         | 63.5         | 63.5          | 82.2  | 84.9        | 89.7                                  | 92.4         | 93.4         | 94.9          | 96.8 | 97.2 | 98.2        | 98.3        | 98.5 | 99.8      |
|       |       | *1 ***       | 72           | .,,,,        | **.**         |       |             | 50 C .                                |              | ,,,,,        | ,,,,          | ,,,, |      | J•          | 20.3        | ,,,, | 22.0      |
| GE    | 000   | 41.6         | 42.B         | 63.5         | 63.5          | 82.2  | 84.9        | 89.7                                  | 92.4         | 93.4         | 94.9          | 96.8 | 97.2 | 98.2        | 98.7        | 98.5 | 110.0     |
|       |       |              |              |              |               |       |             |                                       |              |              | . <b></b> .   |      |      |             | <b></b>     |      |           |

TOTAL NUMBER OF OBSERVATIONS: 12237

| PPPPPI | PPP  | AAA   | AAA   | RRRRI | RRRR  | TTTTTTTTT | EEEEEEEEE |
|--------|------|-------|-------|-------|-------|-----------|-----------|
| PPPPPP | PPPP | AAAA  | AAAA  | RRRRI | RRRRR | TTTTTTTTT | EEEEEEEEE |
| PP     | PP   | AA    | AA    | RR    | RR    | TT        | EE        |
| PP     | PP   | AA    | AA    | RR    | RR    | TT        | EE        |
| PPPPPI | PPPP | AA    | AA    | RRRRI | RRRRR | TT        | EEEEEE    |
| PPPPPI | PPP  | AAAAA | AAAAA | RRRRI | RRRR  | TT        | EEEEEE    |
| PP     |      | AAAAA | AAAA  | RR    | RR    | TT        | EE        |
| PP     |      | AA    | AA    | RR    | RR    | TT        | EE        |
| PP     |      | AA    | AA    | RR    | RR    | TT        | EEEEEEEEE |
| PP     |      | AA    | AA    | RR    | RR    | TT        | EEEEEEEE  |

E - 1 - 1

#### PART E

#### TEMPERATURE AND RELATIVE HUMIDITY SUMMARIES

TEMPERATURE--CUMULATIVE PERCENT OCCURRENCE FREQUENCY (POF).

THESE TABLES ARE CREATED FROM SUMMARY OF DAY DATA AND GIVE CUMULATIVE
POF FOR MAXIMUM, MINIMUM, AND MEAN TEMPERATURES, RESPECTIVELY. DATA IS
SUMMARIZED BY MONTH FOR ALL YEARS COMBINED. TOTALS ARE GIVEN FOR THE WHOLE
YEAR. DATA IS DISPLAYED USING 5-DEGREE FAHRENHEIT INCREMENTS (GE 0, GE 5,
GE 10, ETC).. THERE IS ONE SPECIAL THRESHOLD FOR "GE 33" DEGREES. MEANS,
STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS ARE GIVEN.

NOTE 1. BEGINNING IN JANUARY 1946, DAILY MAXIMUM AND MINIMUM TEMPERATURES

CAME ROUTINELY FROM HOURLY OBSERVATIONS ON AWS FORMS 10/10A OR FROM AUTOMATED

DATA COLLECTION FROM ALL US"F-OPERATED STATIONS. REFER TO THE "STATION HISTORY"

PAGE FOR DETAILED INFORMATION ON REPORTING PRACTICES.

#### MONTHLY TEMPERATURES.

ALSO FROM SUMMARY OF DAY DATA, THE TABLES GIVE MONTHLY MAXIMUM AND MINIMUM TEMP-ERATURES BY MONTH AND BY YEAR. MONTHLY RECORD TEMPERATURES (MAX AND MIN) ARE GIVEN, ALONG WITH TOTAL OBSERVATIONS. AN ASTERISK (\*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS THAN 90% OF THE DATA ARE AVAILABLE. AN ASTERISK ALSO DENOTES A YEAR(S) WITH ONE OR MORE MISSING AND/OR INCOMPLETE MONTHS.

### MEAN MONTHLY TEMPERATURE.

ALSO FROM SUMMARY OF DAY DATA, GIVES MONTHLY MEAN TEMPERATURE BY MONTH, FOR ALL MONTHS, AND FOR ALL YEARS. AN ASTERISK (\*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS THAN 90% OF THE DATA ARE AVAILABLE. AN ASTERISK ALSO DENOTES A YEAR(S) WITH ONE OR MORE MISSING AND/OR INCOMPLETE MONTHS.

DRY BULB, WET BULB, AND DEW POINT TEMPERATURES.

THESE TABLES ARE CREATED FROM HOURLY OBSERVATIONS--DATA IS SUMMARIZED:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

MEANS, STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS ARE GIVEN.
THE MEAN NUMBER OF HOURS WITH TEMPERATURES FOR VARIOUS THRESHOLDS ALSO
APPEAR AS SPECIFIED IN EACH SUMMARY AND IN ACCORDANCE WITH AFM 88-29,
"ENGINEERING WEATHER DATA," AND AWSP 105-56, "METEOROLOGICAL TECHNIQUES."

NOTE 1. WINTER WET BULB AND DEW POINT MEAN TEMPERATURES FOR VERY COLD STATIONS MUST BE USED WITH CAUTION. WHEN THE DRY BULB TEMPERATURE IS BELOW -35 DEGREES F, DEW POINT TEMPERATURES ARE NOT REPORTED (FMH-LB). AS A RESULT, WINTER MEAN DEW POINTS (AND MORE FREQUENTLY, WINTER MEAN WET BULB TEMPERATURES) ARE ACTUALLY LOWER THAN SHOWN IN THE TABLES. IN SOME HOUR GROUPS, IN FACT, MEAN WET BULB TEMPERATURES MAY ACTUALLY BE SHOWN AS EXCEEDING THE MEAN DRY BULB TEMPERATURES.

SPECIAL CAVEAT: DURING PART TIME PERIODS, THESE SUMMARIES REPRESENT THE "HIGH" AND "LOW"
TEMPERATURES RECORDED AND NOT NECESSARILY THE ACTUAL MAXIMUM AND MINIMUM VALUES. THESE SUMMARIES
ARE INFLUENCED BY THE ABSENCE OF NIGHTTIME TEMPERATURE READINGS. THEREFORE, CERTAIN SUMMARIES
MAY DEPICT A SLIGHT "WARM" BAS.

TEMPERATURE CONVERS) ONS:

F = 1.8C + 32

C = K - 273.0 (BEFORE 5 APRIL 77) C = K - 273.2 (SINCE 5 APRIL 77)

RELATIVE HUMIDITY--CUMULATIVE PERCENT OCCURRENCE FREQUENCY (POF).

CREATED FROM HOURLY OBSERVATION. THESE TABLES GIVE POF OF RELATIVE

HUMIDITY FOR 10% INCREMENTS. MEANS AND TOTAL OBSERVATION COUNTS ARE ALSO PROVIDED.

THE DATA IS SUMMARIZED AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- 3Y YEAR (ALL YEARS AND ALL HOURS COMBINED).

E - 1 - 3

# CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF MAXIMUM TEMPERATURES IN FAHRENHEIT FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASET/TONGDUCTION KO

PERIOD OF RECORD: 5305-9006
MONTH: ALL HOURS: ALL

| OIAI     | 1011 1101 | BER: 4/1                                |                 | ST TO UT |       | r CABEI7        | TONGDUCIN | ON NO |          | MONT  | H: ALL          | HOURS:          |       |       |
|----------|-----------|---|-----------------|----------|-------|-----------------|-----------|-------|----------|-------|-----------------|-----------------|-------|-------|
|          | G-F)      | JAN                                     | PEB             | MMM      | AFK   | MAY             | NOC       | JUL   | AUG      | SEP   | OCT             | NOV             | DEC   | ANN   |
| GE       | 100       | • | • • • • • • • • |          |       | • • • • • • • • |           | .6    | .4       |       | • • • • • • • • | • • • • • • • • |       | .1    |
| GE       | 95        |   |                 |          |       |                 | .8        | 5.6   | 7.2      |       |                 |                 |       | 1.1   |
| GE       | 90        |   |                 |          |       | .5              | 8.6       | 23.6  | 29.8     | 1.0   |                 |                 |       | 5.4   |
| GE       | 85        |   |                 |          | .5    | 4.4             | 26.9      | 48.6  | 56.6     | 5.8   |                 |                 |       | 12.1  |
| GE       | 90        |   |                 |          | 2.7   | 22.9            | 63.6      | 76.3  | 81.0     | 44.7  | 3.4             |                 |       | 25.0  |
| GE       | 75        |   |                 |          | 10.6  | 48.4            | 86.0      | 95.0  | 94.0     | 73.3  | 15.0            | .2              |       | 35.9  |
| GE       | 70        |   |                 | .5       | 27.8  | 71.3            | 95.3      | 99.1  | 98.7     | 92.2  | 40.5            | 2.0             |       | 44.7  |
| GE       | 65        |   |                 | 3.1      | 45.6  | 84.7            | 99.0      | 99.8  | 99.8     | 98.4  | 61.7            | 7.1             |       | 50.7  |
| GE       | 60        |   | . 4             | 13.6     | 70.1  | 95.8            | 100.0     | 100.0 | 100.0    | 99.8  | 83.0            | 23.2            |       | 58.0  |
| GE       | 55        | .4                                      | 2.2             | 33.4     | 85.5  | 99.8            |           |       |          | 99.8  | 94.7            | 44.2            | 1.9   | 64.3  |
| GE       | 50        | 1.5                                     | 11.2            | 52.7     | 96.2  | 100.0           |           |       |          | 100.0 | 98.3            | 64.4            | 8.7   | 70.1  |
| GF       | 45        | 9.2                                     | 26.2            | 75.7     | 99.1  |                 |           |       |          |       | 99.1            | 78.4            | 26.3  | 76.7  |
| GE       | 40        | 20.0                                    | 45.2            | 87.1     | 99.5  |                 |           |       |          |       | 99.6            | 85.3            | 40.3  | 81.9  |
| CE       | 35        | 45.4                                    | 67.9            | 97.6     | 100.0 |                 |           |       |          |       | 100.0           | 95.2            | 67.0  | 89.7  |
| CE       | 33        | 52.8                                    | 74.6            | 98.5     |       |                 |           |       |          |       |                 | 97.2            | 73.6  | 91.6  |
| GE       | 30        | 56.7                                    | 84.7            | 99.1     |       |                 |           |       |          |       |                 | 98.8            | 81.7  | 94.4  |
| GE       | 25        | 84.3                                    | 93.0            | 99.5     |       |                 |           |       |          |       |                 | 100.0           | 94.4  | 97.6  |
| GE       | 20        | 94.0                                    | 97.8            | 100.0    |       |                 |           |       |          |       |                 |                 | 97.1  | 99.1  |
| GE       | 15        | 99.1                                    | 99.8            |          |       |                 |           |       |          |       |                 |                 | 99.4  | 99.9  |
| GE       | 10        | 100.C                                   | 100.0           |          |       |                 |           |       |          |       |                 |                 | 99.8  | 100.0 |
| GE       | 5         |   |                 |          |       |                 |           |       |          |       |                 |                 | 100.0 | 100.0 |
|          |           |   |                 |          |       |                 |           |       |          |       |                 |                 |       |       |
| <br>MEAN |           | 33.0                                    | 38.5            | 50.1     | 64.0  | 73.4            | 81.0      | 84.3  | <br>85.5 | 77.7  | <br>66.9        | <br>51.9        | 37.9  | 62.3  |
| SD<br>   |           | 8.12                                    | 8.79            | 8.36     | 8.60  | 7.4P            | 6.29      | 6.38  | 6.46     | 5.54  | 7.71            | 9.63            | 8.71  | 19.86 |
| TOTA     | L OBS     | 549                                     | 511             | 581      | 546   | 593             | 591       | 539   | 553      | 514   | 528             | 505             | 518   | 6528  |

.......

### CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF MINIMUM TEMPERATURES IN FAHRENHEIT FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASET TONGDUCHON KO PERIOD OF RECORD: 5305-9006 MONTH: ALL HOURS: ALL LST TO UTC: -09 TEMP JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV DEC ANN (DEG-F) .2 GE .0 85 GE 80 .6 .5 . 1 GE 75 .3 18.0 21.3 .2 3.3 GE 70 6.4 62.2 58.4 4.1 11.0 GE 65 .7 26.9 89.4 84.3 18.1 18.4 9.9 72.6 99.6 47.1 3.0 GE . 5 98.6 28.0 60 GE 55 4.8 35.1 94.1 100.0 99.8 70.6 15.5 1.0 35.7 GE 50 .2 15.9 65.6 99.2 100.0 88.7 33.3 6.7 43.2 97.7 GE 45 2.6 36.6 87.7 100.0 55.7 14.3 50.4 GE 40 2.2 8.6 55.5 98.3 99.2 73.9 26.3 2.1 56.3 100.0 89.2 44.0 GE 27.9 81.3 100.0 10.2 64.4 35 4.2 7.8 CE 33 6.9 13.3 36.7 89.7 92.8 52.7 15.8 68.0 GE 12.9 57.8 96.3 97.9 66.9 23.7 73.7 30 21.1 84.4 GE 25 21.7 37.8 80.3 99.8 100.0 38.8 80.8 GE 20 35.2 53.0 91.9 100.0 91.5 54.4 85.9 GE 98.6 74.5 15 51.4 70.8 99.1 91.4 GE 10 69.2 84.7 100.0 99.6 90.9 95.5 GΕ 5 82.7 92.2 100.0 96.9 97.7 GE Ú 94.4 98.8 99.4 99.4 GE -5 97.3 99.8 100.0 99.8 GE ~10 99.3 99.9 100.0 GE -15 100.0 100.0 70.1 MEAN 15.4 20.3 30.4 41.6 51.8 62.2 70.4 58.4 45.2 33.6 21.7 43.7 7.25 4.62 7.15 8.10 SD 11.00 10.24 6.96 6.03 4.79 4.08 9.51 9.63 20.09 TOTAL OBS 549 511 539 553 514 528 6528 546 591

## CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF MEAN TEMPERATURES IN FAHRENHEIT FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006 LST TO UTC: -09 MONTH: ALL HOURS: ALL TEMP JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NCV DEC (DEG-F) ...... - 0 GE 90 . 2 GE 85 5.0 6.5 1.0 GE 80 2.2 32.5 38.5 6.2 . 4 GE 75 . 5 28.9 78.5 79.6 9.9 16.7 GE 70 .2 9.4 71.4 97.8 96.6 42.8 27.0 10.8 .2 2.6 99.6 99.8 77.6 GE 65 39.5 95.3 36.1 GE 60 .2 16.5 72.5 99.5 99.8 100.0 95.1 33.7 44.0 GE 42 7 93.6 100.0 100.0 99.2 63.3 9.5 51.6 55 .7 GE 50 7.1 70.3 99.7 100.0 84.8 25.5 . 4 58.2 45 GE .9 2.2 30.1 89.9 100.0 93.6 46.3 4.1 64.7 3.6 58.5 98.2 30.5 GE 40 13.1 66-7 14.1 71.7 GE 35 14.4 33.3 81.9 99.8 99.8 81.6 32.6 79.2 GE 22.2 87.6 99.8 100.0 86.7 82.2 3.3 42.7 41.1 GE 30 30.2 54.6 93.8 100.0 91.5 53.5 85.7 GE 25 49.4 71.8 99.1 97.8 72.8 91.1 69.8 99.8 95.4 GE 20 85.1 99.7 0.98 GE 15 83.4 93.3 100.0 100.0 95.9 97.8 GE 10 96.4 99.4 99.0 99.6 99 9 GE 5 99.3 100.0 100.0 GE 0 100.0 100.0 24.5 29.7 40.5 53.1 MEAN 62.8 71.8 77.6 78.0 68.3 56.3 43.0 30.0 53.3 SD 8.99 8.80 6.65 6.47 5.18 4.13 4.22 4.43 5.14 6.87 8.87 19.57 8.56 TOTAL OBS 549 511 581 546 593 591 539 553 514 528 505 518 6528

### MONTHLY MAXIMUM TEMPERATURES IN FAHRENHEIT FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006 LST TO UTC: -09 MONTH: ALL HOURS: ALL

|      |     | LST | TO UTC:     | -09 |     |      |      |                 | MONTH:        | ALL H | DURS: ALI | L . |        |
|------|-----|-----|-------------|-----|-----|------|------|-----------------|---------------|-------|-----------|-----|--------|
| YEAR | JAN | FEB | MAR         | APR | MAY | JUN  | JUL  | AUG             | SEP           | ост   | NOV       | DEC | ANNUAL |
| 53   |     |     |             |     | 83  | 89   | 89*  | • • • • • • • • | • • • • • • • | 73*   | *         | *   | 89*    |
| 54   | •   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 55   |     | •   |             | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 1    |     |     |             |     |     |      |      |                 |               |       |           |     |        |
| 56   | *   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 57   | •   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 58   | *   | •   | •           | *   | *   | *    | *    | *               | *             |       | *         | *   | *      |
| 59   | *   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 60   | •   | •   | •           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 61   | •   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 62   | •   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 63   | •   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 64   | *   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 65   | *   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 66   | *   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 67   | *   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 68   | *   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| C3   | *   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 70   | *   | *   | *           | *   | *   | *    | *    | *               | *             | *     | *         | *   | *      |
| 71   | 50* | 55* | 64*         | 75* | 80* | 87*  | 87*  | 96*             | 84*           | 73*   | 71*       | 51* | 96*    |
| 72   | 57* | 46* | 62*         | 75* | 82* | 89*  | 98*  | 89*             | 82*           | 78*   | 66*       | 51* | 98*    |
| 73   | 51* | 55* | 69*         | 82* | 82* | 87*  | 96*  | 96*             | 86*           | 78*   | 60*       | 42* | 96*    |
| 74   | 48* | 42* | 59*         | 69* | 87* | 89*  | 89*  | 96*             | 86*           | 73*   | 66*       | 48* | 96*    |
| 75   | 44* | 51* | 57 <b>*</b> | 87* | 82* | 93*  | 93*  | 93*             | 87*           | 78*   | 68*       | 57* | 93*    |
| 76   | 44* | 55* | 60*         | 75* | 89* | 89   | 89*  | 89              | 84*           | 75*   | 66*       | 53* | 89*    |
| 77   | 37* | 59* | 71*         | 77  | 86* | 93*  | 100* | 91              | 86*           | 84*   | 66*       | 55* | 100*   |
| 78   | 46* | 48* | 64          | 77* | 87* | 87*  | 102* | 95              | 86*           | 82*   | 66*       | 55* | 102*   |
| 79   | 55* | 60* | 60          | 73* | 86* | 86   | 93*  | 95*             | 86*           | 81*   | 75*       | 52* | 95*    |
| 80   | 45* | 52  | 66          | 70  | 91  | 91   | 91   | 90              | 84            | 79    | 66        | 52  | 91*    |
| 81   | 36  | 52  | 72          | 79  | 84  | 91   | 97   | 93              | 86            | 75    | 55        | 48  | 97     |
| 82   | 45  | 54  | 63          | 82  |     | . 90 | 95   | 97              | 88            | 82    | 70        | 48  | 97     |
| 83   | 46  | 52  | 66          | 81  | 88  | 93   | 90   | 95              | 90            | 77    | 68        | 52  | 95     |
| 84   | 37  | 50  | 57          | 73  | 82  | 95   | 97   | 99              | 84            | 81    | 70        | 57  | 99     |
| 85   | 39  | 52  | 64          | 79  | 88  | 90   | 99   | 97              | 86            | 81    | 66*       | 46  | 99*    |
|      |     |     |             |     |     |      |      |                 |               |       |           |     |        |

## MONTHLY MAXIMUM TEMPERATURES IN FAHRENHEIT FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

BERIOD OF RECORD: 5305-9006

LST TO UTC: -09

MONTH: ALL HOURS: ALL

| YEAR     | JAN      | FEB      | MAR      | APR      | MAY      | JUN      | JUL      | AUG      | SEP      | oct      | NOA       | DEC      | ANNUAL     |
|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|-----------|----------|------------|
| 86<br>87 | 46<br>45 | 41<br>55 | 68<br>61 | 81<br>79 | 86<br>86 | 91<br>97 | 91<br>95 | 93<br>95 | 86<br>86 | 79<br>82 | 61<br>66* | 55<br>54 | 93<br>97*  |
| 88       | 46       | 54       | 63       | 81       | 91       | 97       | 95       | 100      | 91       | 81       | 64        | 57       | 100        |
| 89<br>90 | 52<br>46 | 61<br>55 | 66<br>68 | ชช<br>84 | 90<br>82 | 93<br>88 | 95       | 100      | 88       | 79       | 66        | 57       | 100<br>88* |

GREATFST 57 61 72 88 91 97 102 100 91 84 75 57 102

TOTAL OBS 549 511 581 546 593 591 539 553 514 528 505 518 6528

THE GREATEST VALUE OF 102 OCCURRED ON 07/26/78

NOTE: "THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

E - 3 - 1B

## MONTHLY MINIMUM TEMPERATURES IN FAHRENHEIT FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006
LST TO UTC: -09 MONTH: ALL HOURS: ALL

|      |                         | LST           | TO UTC: | -09           |     |      |     |               | MONTH:        | ALL H | OURS: AL | L   |        |
|------|-------------------------|---------------|---------|---------------|-----|------|-----|---------------|---------------|-------|----------|-----|--------|
| YEAR | JAN                     | FEB           | MAR     | APR           | MAY | JUN  | JUL | AUG           | SEP           | OCT   | NOV      | DEC | ANNUAL |
| 53   | • • • • • • • • • • • • | • • • • • • • |         | • • • • • • • | 36  | 53   | 60* | • • • • • • • | • • • • • • • | 42*   | *        |     | 36*    |
| 54   | *                       | *             | *       | *             |     |      | *   | *             | *             | 42 ·· | *        | *   | *      |
| 55   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | •   | *      |
| 33   |                         |               |         |               |     |      |     |               |               |       |          |     |        |
| 56   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | •        | *   | *      |
| 57   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 58   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 59   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 60   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 61   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 62   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 63   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 64   | *                       | *             | *       | *             | *   | *    | *   | <b>*</b>      | *             | *     | *        | *   | ×      |
| 65   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 66   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 67   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 68   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 69   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 70   | *                       | *             | *       | *             | *   | *    | *   | *             | *             | *     | *        | *   | *      |
| 71   | -7 <b>*</b>             | 1 *           | 14*     | 28*           | 39* | 55*  | 64* | 62*           | 46*           | 30*   | 15*      | 10* | -7*    |
| 72   | 8 *                     | 12*           | 15*     | 24 *          | 39* | 51*  | 62* | 59*           | 44*           | 30*   | 8*       | 10* | 8*     |
| 73   | 10*                     | 10*           | 19*     | 28*           | 46* | 53*  | 68* | 69*           | 39*           | 30*   | 5*       | 6*  | 5*     |
| 74   | ~5 <b>*</b>             | -2*           | 14*     | 28*           | 42* | 48*  | 64* | 59*           | 44*           | 28*   | 17*      | 12* | ~5*    |
| 75   | 6*                      | 10*           | 21*     | 28*           | 42* | 55*  | 64* | 62*           | 51*           | 35*   | 15*      | 5*  | 5*     |
| 76   | 1*                      | 16+           | 21*     | 26*           | 37* | 53   | 57* | 60            | 46*           | 30*   | 19*      | 0*  | 0*     |
| 77   | 0*                      | 0+            | 10*     | 30            | 42* | 55 * | 66+ | 25            | 29.           | 33*   | 17*      | 12* | 0*     |
| 78   | 3*                      | 0 *           | 10      | 28*           | 39* | 48*  | 62* | 66            | 48*           | 32*   | 19*      | 8*  | 0*     |
| 79   | 8 *                     | -2*           | 19      | 28*           | 41* | 55   | 60* | 53*           | 43*           | 30*   | 10*      | 0*  | -2*    |
| 80   | 0*                      | 0             | 23      | 30            | 41  | 52   | 61  | 61            | 39            | 25    | 25       | -2  | -2*    |
| 81   | -13                     | 3             | 19      | 28            | 37  | 45   | 64  | 61            | 43            | 28    | 18       | 7   | -13    |
| 82   | 3                       | 5             | 18      | 32            | 41  | 46   | 63  | 63            | 43            | 25    | 10       | 9   | 3      |
| 83   | 1                       | -2            | 18      | 28            | 4.3 | 50   | 63  | 64            | 48            | 30    | 18       | 0   | -2     |
| 94   | -4                      | -6            | 16      | 28            | 43  | 55   | 64  | 63            | 45            | 28    | 18       | 5   | -6     |
| 85   | -9                      | 9             | 16      | 27            | 46  | 54   | 66  | 63            | 46            | 34    | 23*      | 1   | -9*    |
| J    |                         |               |         |               |     |      |     |               |               |       |          |     |        |

### MONTHLY MINIMUM TEMPERATURES IN FAHRENHEIT FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: 5305-9006 MONTH: ALL HOURS: ALL

| LST | TO | UTC: | -09 |
|-----|----|------|-----|
|     |    |      |     |

| YEAR | JAN | FEB | MAR | APR | MAY | JUN | JUL | AUG | SEP | OCT | NOA | DEC | ANNUAL |
|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--------|
| 85   | -11 | -2  | 16  | 30  | 43  | 52  | 57  | 51  | 46  | 25  | 1 ห | 10  | -11    |
| 87   | -2  | 7   | 16  | 28  | 3.7 | 52  | 63  | 64  | 37  | 30  | 12* | 9   | -2.*   |
| 88 . | 7   | 5   | 16  | 32  | 41  | 55  | 64  | 66  | 50  | 30  | 18  | 7   | 5      |
| 89   | 7   | 10  | 18  | 32  | 41  | 50  | 63  | 59  | 46  | 28  | 14  | 10  | 7      |
| 90   | -8  | 18  | 2.3 | 28  | 41  | 54  |     |     |     |     |     |     | -8 •   |

LEAST -13 -6 10 24 36 45 57 53 37 25 5 -2 -13

TOTAL OBS 549 511 581 546 593 591 539 553 514 528 505 518 6528

THE LEAST VALUE OF -13 OCCURRED ON 01/04/81

NOTE: \*THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

### MONTHLY MEAN TEMPERATURES IN FAHRENHEIT FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006 LST TO UTC: -09 MONTH: ALL HOURS: ALL

|            |          | 1,471 | 10.010. | -09  |      |      |             |     | 765141211 | 71317        | 551417 AL | .,  |        |
|------------|----------|-------|---------|------|------|------|-------------|-----|-----------|--------------|-----------|-----|--------|
| YEAP       | JAN      | FEB   | MAR     | APR  | MAY  | JUN  | JUL         | AUG | SEP       | ост          | NOV       | DEC | ANNUAL |
| 53         |          |       |         |      | 63   | 69   | 75 <i>*</i> |     |           | 57*          | *         | *   | 67*    |
| 5.4        | •        |       | *       | •    | *    | *    | *           | *   | *         | •            | *         | •   | 0*     |
| 55         | •        | •     | *       | *    | *    | •    | *           | *   | *         | *            | *         | •   | 0.     |
| 5,6        |          | *     | *       | •    | *    | *    | *           | *   | *         | •            | *         | *   | 0.     |
| 5.7        | *        | •     | *       | *    | *    | *    | *           | *   | •         | *            | •         | •   | 0*     |
| 5.8        | •        | •     | •       | *    | *    | *    | *           | •   | •         | •            | •         | *   | 0*     |
| 5.0        |          | •     | •       | *    | *    | *    | *           | *   | •         | *            | •         | *   | 0*     |
| 60         | <u>.</u> | *     | *       | *    | *    | *    | *           | *   | *         | *            | *         | *   | 0*     |
| <b>5</b> ! | •        | •     |         | •    | •    | *    | *           | *   | *         | *            | *         | *   | 0*     |
| 45         | •        | •     | •       | •    | *    | *    | *           | *   | *         | *            | *         | •   | 0.*    |
| 63         |          | •     | •       | *    | *    | *    | *           | *   | *         | *            | *         | *   | 0*     |
| F. 4       | •        | *     | *       | •    | •    | *    | *           | *   | *         | •            | *         | *   | 0*     |
| 65         | •        | ٠     | *       | *    | *    | *    | *           | *   | *         | *            | *         | *   | C.+    |
| 66         |          | *     |         | *    | *    | *    | *           | *   | •         | *            | *         | *   | 0*     |
| 67         | •        | *     | *       | *    | •    | *    | *           | *   | *         | *            | *         | *   | >.     |
| 68         | •        | •     | *       | *    | *    | *    | •           | *   | *         | *            | *         | *   | 0*     |
| 69         | •        | *     | *       | *    | *    | *    | *           | *   | *         | *            | *         | *   | 0*     |
| 70         | •        | *     | *       | *    | •    | *    | *           | *   | *         | *            | *         | *   | 0*     |
| 7 1        | 26*      | 28+   | 36*     | 52*  | 61 * | 72*  | 77*         | 77* | 68*       | 5 <b>4</b> * | 46*       | 29* | 53*    |
| 12         | 12*      | 31 *  | 41*     | 53*  | 61*  | 71 * | 79 *        | 74* | 65 *      | 56 <i>*</i>  | 41*       | 31* | 53*    |
| * 4        | 31*      | 32 *  | 40 *    | 53+  | 63*  | 71 * | 82*         | 80* | 67*       | 54*          | 40*       | 25* | 54*    |
| 7.4        | 74.      | 26+   | 38+     | 50 * | 62 * | 68*  | 76*         | 77* | 68*       | 53*          | 41*       | 29* | 51*    |
| 75         | 25 *     | 30 *  | 39*     | 55*  | 62 * | 71*  | 77*         | 80* | 72*       | 58*          | 48*       | 28* | 54*    |
| 16         | 23*      | 37*   | 41*     | 51*  | 60+  | 71   | 74*         | 75  | 66*       | 56*          | 38*       | 32* | 52*    |
| * **       | 19*      | 25 *  | 41 *    | 55   | 64 * | 73*  | 80*         | 76  | 69*       | 59*          | 43*       | 34* | 54*    |
| 78         | 25 *     | 25 *  | 18      | 51 * | 63*  | 72.* | 80 *        | 79  | 68*       | 55*          | 43*       | 21* | 53*    |
| , 3        | 33+      | 32 *  | 4.1     | 52*  | 60*  | 72   | 76*         | 78* | 67*       | 58*          | 42*       | 33* | 54*    |
| an         | 23*      | 25    | 41      | 50   | 62   | 73   | 76          | 75  | 66        | 54           | 46        | 23  | 52*    |
| 81         | 15       | 29    | 42      | 54   | 61   | 72   | 79          | 77  | 68        | 54           | 37        | 29  | 52     |
| 82         | 24       | 12    | 4.3     | 54   | 64   | 72   | 78          | 78  | 67        | 59           | 45        | 30  | 54     |
| яз         | 2.7      | 2.7   | 42      | 56   | 65   | 73   | 75          | 80  | 72        | 57           | 43        | 28  | 54     |
| 8.1        | 18       | 25    | 3.7     | 54   | 66   | 74   | 79          | 81  | 69        | 56           | 46        | 31  | 53     |
| A5         | 19       | 32    | 40      | 5.3  | 64   | 73   | 80          | 81  | 69        | 58           | 44*       | 25  | 53*    |
| A5         | 19       | 32    | 40      | 5.3  | 64   | 73   | 80          | 81  | 69        | 58           | 44*       | 25  |        |

## MONTHLY MEAN TEMPERATURES IN FAHRENHEIT FROM SUMMARY OF DAY DATA

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: 5305-9006 LST TO UTC: -09 MONTH: ALL HOURS: ALL 25 32 40 52 63 74 77 78 69 55 42 35 53 28 29 39 52 64 74 77 78 69 60 47\* 32 54\* 32 36 44 58 65 71 78 79 69 55 44 32 55 24 36 44 51 62 70 MAR APR MAY JUL AUG SEP OCT NOV DEC ANNUAL YEAR JAN FEB 86 21 25 88 89 24 36

MEAN 24.5 29.7 40.5 53.1 62.8 71.8 77.6 78.0 68.3 56.3 43.0 30.0 53.3

TOTAL OBS 549 511 581 546 593 591 539 553 514 528 505 518 6528

NOTE: \*THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

## DRY BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN

|                                  |                                      | 20.                                       | r TO UTC: - 9                   | MONTH: JAN   |
|----------------------------------|--------------------------------------|---|---------------------------------|--|
| HOURS<br>LST                     | MEAN                                 | STANDARD<br>DEVIATION                     | TOTAL<br>OBS                    | MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F TOTAL<br>LE 0 LE 32 GE 65 GE 80 GE 93 HOURS   |
| 00-02                            | 24.5                                 | 11.121                                    | 179                             | 6 130 0 0 0 179  |
| 03-05                            | 22.7                                 | 12.212                                    | 180                             | 9 134 0 0 180  |
| 06-08                            | 21.5                                 | 12.451                                    | 180                             | 9 143 0 0 0 180  |
| 09-11                            | 27.3                                 | 9.946                                     | 120                             | 1 79 0 0 0 120   |
| 12-14                            | 33.6                                 | 8.107                                     | 180                             | 0 75 0 0 0 180   |
| 15-17                            | 35.3                                 | 7.790                                     | 180                             | 0 60 0 0 0 180   |
| 18-20                            | 30.1                                 | 8.923                                     | 180                             | 0 102 0 0 0 180  |
| 21-23                            | 26.9                                 | 10.002                                    | 180                             | 1 119 0 0 0 180  |
| ALL<br>HOURS                     | 27.8                                 | 11.237                                    | 1379                            | 26 842 0 0 0 1379  |
|                                  |                                      |   |                                 | MONTH: FEB   |
| 00-02                            | 30.5                                 |   |                                 |  |
| - 1                              | 30.5                                 | 7.341                                     | 165                             | 0 100 0 0 0 165  |
| 03-05                            | 28.7                                 | 7.341<br>7.988                            | 165<br>165                      | 0 100 0 0 0 165<br>0 106 0 0 0 165   |
| 03-05<br>06-08                   |                                      |   |                                 |  |
|                                  | 28.7                                 | 7.988                                     | 165                             | 0 106 0 0 0 165  |
| 06-08                            | 28.7<br>27.5                         | 7.988<br>8.317                            | 165<br>166                      | 0 106 0 0 0 165<br>0 113 0 0 0 166   |
| 06-08<br>09-11                   | 28.7<br>27.5<br>35.3                 | 7.988<br>8.317<br>7.101                   | 165<br>166<br>112               | 0     106     0     0     0     165       0     113     0     0     0     166       0     46     0     0     0     112   |
| 06-08<br>09-11<br>12-14          | 28.7<br>27.5<br>35.3<br>42.8         | 7.988<br>8.317<br>7.101<br>6.275          | 165<br>166<br>112<br>168        | 0       106       0       0       0       165         0       113       0       0       0       166         0       46       0       0       0       112         0       6       0       0       0       168   |
| 06-08<br>09-11<br>12-14<br>15-17 | 28.7<br>27.5<br>35.3<br>42.8<br>44.3 | 7.988<br>8.317<br>7.101<br>6.275<br>5.973 | 165<br>166<br>112<br>168<br>168 | 0       106       0       0       0       165         0       113       0       0       0       166         0       46       0       0       0       112         0       6       0       0       0       168         0       3       0       0       0       168 |

### DRY BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

PERIOD OF RECORD: JUL 80 - JUN 90

STATION NUMBER: 471066

HOURS

53.9

11.775

1283

STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: - 9 MONTH: MAR ....... HOURS MEAN STANDARD TOTAL MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F TOTAL LST DEVIATION OBS HOURS LE 0 LE 32 GE 65 GE 80 GE 93 37.7 6.202 186 0 00-02 41 0 0 0 186 03-05 35.4 6.805 186 0 68 0 0 0 186 06-08 34.7 7.110 186 0 83 0 0 0 186 09-11 44.1 5.432 124 0 1 0 0 0 124 50.8 6.589 186 n 186 12-14 0 1 0 0 7.244 0 7 15-17 53.1 186 0 0 186 0 18-20 47.2 6.090 186 0 3 0 0 0 186 21-23 41.6 5.590 186 14 0 0 0 186 HOURS 43.0 9.237 1426 210 1426 MONTH: APR 00-02 6.481 170 0 46.3 2 2 0 0 170 03-05 43.7 6.772 171 0 6 1 0 0 171 06-08 43.7 6.546 168 0 0 6 0 0 168 09-11 57.8 7.844 0 0 19 112 12-14 64.5 9.353 165 0 0 78 9 0 165 15-17 65.9 10.463 165 O 0 95 20 0 165 18-20 59.7 8,713 165 O 0 45 2 165 0 21-23 51.5 6.694 167 0 5 0 0 167 ALL

E - 5 - 1 - 2

0

14

245

32

0

1283

# DRY BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 I.ST TO UTC: - 9 MONTH: MAY

|              |      | I,ST                  | r to utc: -  | 9 MONTH: MAY   |     |
|--------------|------|-----------------------|--------------|--|-----|
| HOURS LST    | MEAN | STANDARD<br>DEVIATION | TOTAL<br>OBS | MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F TOT<br>LE 0 LE 32 GE 65 GE 80 GE 93 HOU |     |
| 00-02        | 56.0 | 4.651                 | 180          |  | 80  |
| 03-05        | 54.1 | 4.976                 | 180          | 0 0 0 0 0 1  | 80  |
| 06-08        | 55.1 | 5.172                 | 180          | 0 0 4 0 0 1  | 80  |
| 09-11        | 65.8 | 6.318                 | 120          | 0 0 67 0 0 1   | 20  |
| 12-14        | 71.8 | 7.511                 | 180          | 0 0 145 23 0 1   | .80 |
| 15-17        | 72.8 | 8.325                 | 179          | 0 0 145 40 0 1   | .79 |
| 18-20        | 66.5 | 7.024                 | 180          | 0 0 105 7 0 1  | 80  |
| 21-23        | 59.4 | 4.826                 | 181          | 0 0 20 0 0 1   | 81  |
| ALL<br>HOURS | 62.5 | 9.445                 | 1380         | 0 0 487 70 0 13  | 80  |
|              |      |                       |              | MONTH: JUN   |     |
| 00-02        | 64.1 | 4.639                 | 180          | 0 0 74 0 0 1   | 80  |
| 03-05        | 62.3 | 5.011                 | 180          | 0 0 44 0 0 1   | 80  |
| 06-08        | 63.5 | 4.922                 | 180          | 0 0 66 0 0 1   | 80  |
| 09-11        | 72.4 | 5.011                 | 120          | 0 0 106 8 0 1  | 20  |
| 12-14        | 76.4 | 6.614                 | 180          | 0 0 166 59 0 1   | 80  |
| 15-17        | 77.5 | 7.433                 | 180          | 0 0 168 75 3 1   | .80 |
| 18-20        | 73.3 | 6.127                 | 180          | 0 0 164 26 0 1   | .80 |
| 21-23        | 67.2 | 4.023                 | 180          | 0 0 123 0 0 1  | .80 |
| ALL<br>HOURS | 69.5 | 8.059                 | 1380         | 0 0 911 168 3 13   | 80  |

## DRY BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

LST TO UTC: - 9

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: JUL

|              |                       | LS.1                  | TO UTC:           | - 9   |       | M       | ONTH: | 2017  |                     |      |           |       |
|--------------|-----------------------|-----------------------|-------------------|-------|-------|---------|-------|-------|---------------------|------|-----------|-------|
| HOURS<br>LST | MEAN                  | STANDARD<br>DEVIATION | TOTAL<br>OBS      | MEAN  | LE O  | LE :    |       | GE 65 | TEMPERAT<br>GE 80   | GE   | 93        | HOURS |
| 00-02        | 71.5                  | 4.034                 | 90                |       | 0     | • • • • | 0     | 84    | 2                   | •••• | 0         | 90    |
| 03-05        | 70.1                  | 4.797                 | 90                |       | 0     |         | 0     | 76    | 2                   |      | 0         | 90    |
| 06-08        | 71.1                  | 4.652                 | 90                |       | 0     |         | 0     | 81    | 4                   |      | 0         | 90    |
| 09-11        | 78.2                  | 5.119                 | 58                |       | 0     |         | 0     | 58    | 23                  |      | 0         | 58    |
| 12-14        | 82.3                  | 6.018                 | 87                |       | 0     |         | 0     | 87    | 58                  |      | 0         | 87    |
| 15-17        | 83.8                  | 5.824                 | 87                |       | 0     |         | 0     | 87    | 64                  |      | 2         | 87    |
| 18-20        | 80.0                  | 5.253                 | 87                |       | 0     |         | 0     | 87    | 49                  |      | 0         | 87    |
| 21-23        | 74.4                  | 3.864                 | 87                |       | 0     |         | 0     | 85    | 4                   |      | 0         | 87    |
| ALL<br>HOURS | 76.3                  | 7.114                 | 676               |       | 0     |         | 0     | 645   | 206                 |      | 2         | 676   |
|              | • • • • • • • • • • • |                       | • • • • • • • • • | ••••• | ••••• | м       | ONTH: | AUG   | • • • • • • • •     |      | • • • • • | ••••• |
|              |                       |                       |                   |       |       |         |       |       | · · · · · · · · · · |      |           |       |
| 00-02        | 71.5                  | 3.911                 | 93                |       | 0     |         | 0     | 86    | 0                   |      | 0         | 93    |
| 03~05        | 69.9                  | 4.466                 | 93                |       | . 0   |         | 0     | 77    | 0                   |      | 0         | 93    |
| 06-08        | 70.5                  | 4.475                 | 93                |       | 0     |         | 0     | 80    | 0                   |      | 0         | 93    |
| 09-11        | 80.6                  | 4.127                 | 62                |       | 0     |         | 0     | 62    | 38                  |      | 0         | 62    |
| 12-14        | 85.6                  | 5.455                 | 93                |       | 0     |         | 0     | 93    | 82                  |      | 7         | 93    |
| 15-17        | 86.5                  | 6.779                 | 93                |       | 0     |         | 0     | 93    | 77                  |      | 17        | 93    |
| 18-20        | 80.6                  | 6.199                 | 93                |       | 0     |         | 0     | 92    | 51                  |      | 4         | 93    |
| 21-23        | 74.1                  | 3.999                 | 93                |       | 0     |         | 0     | 89    | 6                   |      | 0         | 93    |
| ALL<br>HOURS | 77.3                  | 8.203                 | 713               |       | 0     |         | 0     | 672   | 254                 |      | 28        | 713   |

## DRY BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: SEP

|              |      | LST                   | TO UTC: - 9  | MONTH: SEP   |            |
|--------------|------|-----------------------|--------------|--------------|------------|
| HOURS<br>LST | MEAN | STANDARD<br>DEVIATION | TOTAL<br>OBS |              | TAL<br>URS |
| 00-02        | 62.2 | 6.006                 | 90           | 0 0 33 0 0   | 90         |
| 03-05        | 60.2 | 6.505                 | 90           | 0 0 18 0 0   | 90         |
| 06-08        | 59.9 | 6.841                 | 90           | 0 0 21 0 0   | 90         |
| 09-11        | 71.2 | 5.957                 | 60           | 0 0 53 2 0   | 60         |
| 12-14        | 76.9 | 5.889                 | 90           | 0 0 87 32 0  | 90         |
| 15-17        | 77.0 | 5.955                 | 90           | 0 0 84 35 0  | 90         |
| 18-20        | 69.5 | 5.720                 | 90           | 0 0 69 1 0   | 90         |
| 21-23        | 64.2 | 5.330                 | 90           | 0 0 47 0 0   | 90         |
| ALL<br>HOURS | 67.5 | 8,970                 | 690          | 0 0 412 70 0 | 690        |
|              |      |                       |              | MONTH: OCT   |            |
| 00-02        | 46.6 | 6.606                 | 93           | 0 3 0 0 0    | 93         |
| 03-05        | 44.4 | 7.308                 | 93           | 0 4 0 0 0    | 93         |
| 06-08        | 43.8 | 7.351                 | 93           | 0 5 0 0 0    | 93         |
| 09-11        | 56.2 | 6.533                 | 62           | 0 0 4 0 0    | 62         |
| 12-14        | 64.7 | 6.765                 | 93           | 0 0 40 0 0   | 93         |
| 15-17        | 65.2 | 6.578                 | 93           | 0 0 43 0 0   | 93         |
| 18-20        | 55.6 | 5.763                 | 93           | 0 0 4 0 0    | 93         |
| 21-23        | 49.8 | 5.592                 | 93           | 0 0 0 0      | 93         |
| ALL<br>HOURS | 53.1 | 10.475                | 713          | 0 12 91 0 0  | 713        |

### DRY BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: NOV

|   |                                      | Lot                                       | TO UTC: -            | ,                   | MONT                       | H: NOV           |       |                  |                      |
|---|--------------------------------------|---|----------------------|---------------------|----------------------------|------------------|-------|------------------|----------------------|
| HOURS<br>LST                              | MEAN                                 | STANDARD<br>DEVIATION                     | TOTAL<br>OBS         | MEAN NUMBEF<br>LE O | LE 32                      | RS WITH<br>GE 65 | GE 80 | GE 93            | HOURS                |
| 00-02                                     | 39.0                                 | 10.177                                    | 84                   | 0                   | 27                         | 0                | 0     | 0                | 84                   |
| 03-05                                     | 37.5                                 | 10.581                                    | 84                   | 0                   | 28                         | 0                | 0     | 0                | 84                   |
| 06-08                                     | 36.3                                 | 11.195                                    | 84                   | 0                   | 37                         | 0                | 0     | o                | 84                   |
| 09-11                                     | 43.4                                 | 10.094                                    | 56                   | 0                   | 9                          | 0                | 0     | o                | 56                   |
| 12-14                                     | 50.4                                 | 9.222                                     | 84                   | 0                   | 5                          | 0                | 0     | o                | 84                   |
| 15-17                                     | 50.7                                 | 8.850                                     | 84                   | 0                   | 3                          | 1                | 0     | o                | 84                   |
| 18-20                                     | 43.4                                 | 9.299                                     | 84                   | 0                   | 14                         | 0                | 0     | o                | 84                   |
| 21-23                                     | 40.0                                 | 9.659                                     | 84                   | 0                   | 19                         | 0                | 0     | o                | 84                   |
| ALL<br>HOURS                              | 42.5                                 | 11.134                                    | 644                  | 0                   | 142                        | 1                | 0     | 0                | 644                  |
|   |                                      |   |                      |                     |                            |                  |       |                  |                      |
|   |                                      |   |                      |                     | MONT                       | H: DEC           |       |                  |                      |
| 00-02                                     | 27.3                                 | 7.319                                     | 89                   | 0                   | MONT:                      | H: DEC           | 0     | 0                | •••••<br>89          |
| 00-02                                     | 27.3<br>25.7                         | 7.319<br>8.217                            | 89<br>90             | 0                   |                            |                  | o     | 0                | <br>89<br>90         |
|   |                                      |   |                      |                     | 75                         | 0                |       |                  |                      |
| 03-05                                     | 25.7                                 | 8.217                                     | 90                   | 0                   | 75<br>78                   | o                | 0     | 0                | 90                   |
| 03-05<br>06-08                            | 25.7<br>25.2                         | 8.217                                     | 90<br>90             | 0                   | 75<br>78<br>78             | o<br>o<br>o      | 0     | 0                | 90<br>90             |
| 03-05<br>06-08<br>09-11                   | 25.7<br>25.2<br>32.0                 | 8.217<br>8.348<br>6.675                   | 90<br>90<br>60       | 0<br>0<br>0         | 75<br>78<br>78<br>31       | 0 0              | 0     | o<br>o<br>o      | 90<br>90<br>60       |
| 03-05<br>06-08<br>09-11<br>12-14          | 25.7<br>25.2<br>32.0<br>39.0         | 8.217<br>8.348<br>6.675<br>7.222          | 90<br>90<br>60<br>90 | 0<br>0<br>0         | 75<br>78<br>78<br>31<br>20 | 0 0 0            | 0 0   | o<br>o<br>o      | 90<br>90<br>60<br>90 |
| 03-05<br>06-08<br>09-11<br>12-14<br>15-17 | 25.7<br>25.2<br>32.0<br>39.0<br>39.6 | 8.217<br>8.348<br>6.675<br>7.222<br>7.219 | 90<br>90<br>60<br>90 | 0<br>0<br>0<br>0    | 75<br>78<br>78<br>31<br>20 | 0 0 0            | 0 0 0 | o<br>o<br>o<br>o | 90<br>90<br>60<br>90 |

## DRY BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: ALL

| HOURS        | MEAN | STANDARD  | TOTAL | ME    |      |       |       |       | PRES DEG F | TOTAL |
|--------------|------|-----------|-------|-------|------|-------|-------|-------|------------|-------|
| LST          |      | DEVIATION | OBS   |       | TE O | LE 32 | GE 65 | GE 80 | GE 93      | HOURS |
| 00-02        | 46.7 | 17.080    | 1599  | ••••• | 6    | 378   | 280   | 2     | 0          | 1599  |
| 03-05        | 44.7 | 17.366    | 1602  |       | 9    | 424   | 216   | 2     | 0          | 1603  |
| 06-08        | 44.5 | 18.165    | 1600  |       | 9    | 465   | 252   | 4     | o          | 1600  |
| 02-11        | 53.9 | 18.836    | 1066  |       | 1    | 166   | 369   | 72    | 0          | 1066  |
| 12-14        | 60.0 | 18.243    | 1596  |       | 0    | 106   | 697   | 263   | 7          | 1596  |
| 15-17        | 61.2 | 18.217    | 1595  |       | 0    | 83    | 723   | 311   | 22         | 1595  |
| 18-20        | 55.3 | 18.188    | 1590  |       | 0    | 200   | 566   | 136   | 4          | 1590  |
| 21-23        | 49.7 | 17.004    | 1588  |       | 1    | 293   | 369   | 10    | 0          | 1588  |
| ALL<br>HOURS | 51.9 | 18.930    | 12236 |       | 26   | 2115  | 3472  | 800   | 33         | 12236 |

#### WET BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JAN

MEAN STANDARD TOTAL MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F TOTAL HOURS LST DEVIATION OBS LE 32 GE 50 GE 67 GE 73 GE 80 HOURS ...... 00-02 23.4 10.714 179 21.8 11.743 03-05 06-08 20.7 11.931 09-11 25.7 9.642 12-14 30.3 7.773 15-17 31.3 7.189 27.8 8.439 18-20 25.5 21-23 9.545 ALL HOURS 25.8 10.416 MONTH: FEB 00-02 29.1 6.733 27.7 03-05 7.473 06~08 26.7 7.883 09-11 32.5 6.054 57.1 4.937 37.9 15-17 4.531 . 24 34.2 18-20 5.427 21-23 30.8 5.875 ALL HOURS 32 0 7.395 O 

......

## WET BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

|              |      | LST                   | TO UTC: - 9  | 9 MONTH: MAR  |        |
|--------------|------|-----------------------|--------------|---|--------|
| HOURS<br>LST | MEAN | STANDARD<br>DEVIATION | TOTAL<br>OBS | MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F TOTA<br>LE 32 GE 50 GE 67 GE 73 GE 80 HOUR | RS     |
| 00-02        | 35.6 | 5.879                 | 186          |   | <br>86 |
| 03-05        | 34.0 | 6.498                 | 186          | 78 0 0 0 0 16   | 86     |
| 06-08        | 33.4 | 6.790                 | 186          | 87 0 0 0 0 16   | 86     |
| 09-11        | 39.7 | 4.762                 | 124          | 8 2 0 0 0 12  | 24     |
| 12~14        | 43.4 | 4.529                 | 186          | 3 14 0 0 0 16   | 86     |
| 15~17        | 44.4 | 4.726                 | 186          | 4 19 0 0 0 16   | 86     |
| 18-20        | 41.4 | 4.881                 | 186          | 9 9 0 0 0 16  | 86     |
| 21-23        | 38.3 | 5.464                 | 186          | 20 4 0 0 0 18   | 86     |
| ALL<br>HOURS | 38.7 | 6.832                 | 1426         | . 261 51 0 0 0 142  | 26     |
|              |      |                       |              | MONTH: APR  | ••     |
| 00-02        | 42.9 | 5.266                 | 170          |   | <br>70 |
| 03-05        | 41.2 | 5.755                 | 171          |   | 71     |
| 06-08        | 41.2 | 5.804                 | 168          | 9 11 0 0 0 16   |        |
| 09-11        | 48.5 | 4.981                 | 111          |   | 11     |
| 12-14        | 51.4 | 4.643                 | 165          | 0 112 0 0 0 16  |        |
| 15-17        | 52.5 | 5.179                 | 165          |   | 65     |
| 18-20        | 49.9 | 5.285                 | 165          | 0 98 0 0 0 16   |        |
| 21-23        | 45.9 | 5.032                 | 167          |   | 67     |
| ALL          |      |                       |              | ·   |        |
| HOURS        | 46.5 | 6.803                 | 1282         | 22 464 1 0 0 128  | 32     |

# WET BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAY

|              |      | LST                   | TO UTC: - 9  | MONTH: MAY      |                |
|--------------|------|-----------------------|--------------|-----------------|----------------|
| HOURS<br>LST | MEAN | STANDARD<br>DEVIATION | TOTAL<br>OBS |                 | TOTAL<br>HOURS |
| 00-02        | 53.3 | 4.430                 | 180          | 0 144 0 0 0     | 180            |
| 03-05        | 52.1 | 4.691                 | 180          | 0 126 0 0 0     | 180            |
| 06-08        | 52.5 | 4.654                 | 180          | . 0 132 0 0 0   | 180            |
| 09-11        | 58.0 | 3.957                 | 120          | 0 116 2 0 0     | 120            |
| 12-14        | 60.5 | 3.912                 | 180          | 0 179 11 0 0    | 180            |
| 15-17        | 61.0 | 4.254                 | 179          | 0 178 17 0 0    | 179            |
| 18-20        | 58.4 | 4.447                 | 180          | 0 173 3 0 0     | 180            |
| 21-23        | 55.1 | 4.138                 | 181          | 0 165 0 0 0     | 181            |
| ALL<br>HOURS | 56.3 | 5.454                 | 1380         | 0 1213 33 0 0   | 1380           |
|              |      |                       |              | MONTH: JUN      |                |
| 00-02        | 61.4 | 4.277                 | 180          | 0 180 19 0 0    | 180            |
| 03-05        | 60.3 | 4.717                 | 180          | 0 177 16 0 0    | 180            |
| 06-08        | 60.8 | 4.511                 | 180          | 0 179 22 0 0    | 180            |
| 09-11        | 65.0 | 3.686                 | 120          | 0 120 46 0 0    | 120            |
| 12-14        | 66.8 | 3.542                 | 180          | 0 180 100 8 0   | 180            |
| 15-17        | 67.3 | 3.727                 | 180          | 0 180 113 11 0  | 180            |
| 18-20        | 65.9 | 4.241                 | 180          | 0 180 86 12 0   | 180            |
| 21-23        | 63.4 | 4.014                 | 180          | 0 180 37 1 0    | 180            |
| ALL<br>HOURS | 63.8 | 4.874                 | 1380         | 0 1376 439 32 0 | 1380           |

# WET BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL

|  |  | LST  | TO UTC: - 9                      | MONTH: JUL  |
|--|--|--|----------------------------------|---|
| HOURS<br>LST                                       | MEAN   | STANDARD<br>DEVIATION                              | TOTAL<br>OBS                     | MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F TOTAL LE 32 GE 50 GE 67 GE 73 GE 90 HOURS                          |
| 00-02  | 69.3   | 4.395  | 90                               | 0 90 65 25 0 90   |
| 03-05  | 68.4   | 4.577  | 90                               | 0 90 53 19 0 90   |
| 06-08  | 68.8   | 4.453  | 90                               | 0 90 62 23 0 90   |
| 09-11  | 72.2   | 3.780  | 58                               | 0 58 54 24 0 58   |
| 12-14  | 73.8   | 3.355  | 87                               | 0 87 86 51 2 87   |
| 15-17  | 74.3   | 3.322  | 87                               | 0 87 87 56 0 87   |
| 18-20  | 73.2   | 3.799  | 87                               | 0 87 82 49 0 87   |
| 21-23  | 71.4   | 4.134  | 87                               | 0 87 80 37 0 87   |
| ALL  |  |  |                                  |   |
| HOURS  | 71.4   | 4.613  | 676                              | 0 676 569 284 2 676   |
| HOURS  | 71.4   | 4.613  | 676                              | 0 676 569 284 2 676<br>MONTH: AUG   |
| HOURS (  | 71.4   | 3.759  | 93                               |   |
|  |  |  |                                  | MONTH: AUG  |
| 00-02  | 68.7   | 3.759  | 93                               | MONTH: AUG<br>0 93 66 13 0 93   |
| 00-02  | 68.7<br>67.8                                 | 3.759  | 93                               | MONTH: AUG  0 93 66 13 0 93  0 93 56 10 0 93  |
| 00-02<br>03-05<br>06-08                            | 68.7<br>67.8<br>67.8                         | 3.759<br>4.273<br>4.097                            | 93<br>93<br>93                   | MONTH: AUG  0 93 66 13 0 93  0 93 56 10 0 93  0 93 58 8 0 93  |
| 00-02  <br>03-05  <br>06-08  <br>09-11             | 68.7<br>67.8<br>67.8<br>71.9                 | 3.759<br>4.273<br>4.097<br>2.541                   | 93<br>93<br>93<br>93<br>62       | MONTH: AUG  0 93 66 13 0 93  0 93 56 10 0 93  0 93 58 8 0 93  0 62 61 25 0 62                                   |
| 00-02  <br>03-05  <br>06-08  <br>09-11  <br>12-14  | 68.7<br>67.8<br>67.8<br>71.9                 | 3.759<br>4.273<br>4.097<br>2.541<br>2.898          | 93<br>93<br>93<br>93<br>62<br>93 | MONTH: AUG  0 93 66 13 0 93  0 93 56 10 0 93  0 93 58 8 0 93  0 62 61 25 0 62  0 93 91 59 1 93                  |
| 00-02<br>03-05<br>06-08<br>09-11<br>12-14<br>15-17 | 68.7<br>67.8<br>67.8<br>71.9<br>73.8<br>74.5 | 3.759<br>4.273<br>4.097<br>2.541<br>2.898<br>3.038 | 93<br>93<br>93<br>93<br>62<br>93 | MONTH: AUG  0 93 66 13 0 93  0 93 56 10 0 93  0 93 58 8 0 93  0 62 61 25 0 62  0 93 91 59 1 93  0 93 93 69 4 92 |

## WET BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: SEP

|               |      | LST                   | 10 010: - 9                             | MONTH: SEP                       |             |
|---------------|------|-----------------------|---|----------------------------------|-------------|
| HOURS LST     | MFAN | STANDARD<br>DEVIATION | TOTAL<br>OBS                            | LE 32 GE 50 GE 67 GE 73 GE 30 HC | TAL<br>OURS |
| 00-02         | 60.8 | 5.893                 | 90                                      | 0 83 17 0 0                      | 90          |
| 03-05         | 59.4 | 6.164                 | 90                                      | 0 78 12 0 0                      | 90          |
| 06-08         | 58.8 | 6.383                 | 90                                      | 0 78 10 0 O                      | 90          |
| 09-11         | 64.5 | 4.755                 | 60                                      | 0 60 21 0 0                      | 60          |
| 12-14         | 66.5 | 4.193                 | 90                                      | 0 90 48 3 0                      | 90          |
| 15-17         | 66.8 | 4.138                 | 90                                      | 0 90 54 4 0                      | 90          |
| 18-20         | 64.4 | 4.789                 | 90                                      | 0 90 39 0 0                      | 90          |
| 21-23         | 61.8 | 5.240                 | 90                                      | 0 90 16 0 0                      | 90          |
| ALL<br>HOURS  | 62.8 | 5.983                 | 690                                     | 0 659 217 7 0                    | 690         |
| •••••         |      |                       | • | MONTH: OCT                       |             |
| 00-02         | 45.6 | 6.467                 | 93                                      | 3 32 0 0 0                       | 93          |
| 03-05         | 43.8 | 7.006                 | 93                                      | 5 22 0 0 0                       | 93          |
| 06-09         | 43.3 | 7.045                 | 93                                      | 5 22 0 0 0                       | 93          |
| 09-11         | 50.5 | 5.377                 | 62                                      | 0 38 0 0 0                       | 62          |
| 12-14         | 54.8 | 5.102                 | 93                                      | 0 82 0 0 0                       | 93          |
| 15-17         | 54.9 | 5.045                 | 93                                      | 0 87 0 0 0                       | 93          |
| 18-20         | 50.8 | 5.498                 | 93                                      | 0 58 0 0 0                       | 93          |
| 21-23         | 47.6 | 5.601                 | 93                                      | 0 41 0 0 0                       | 93          |
| ALI.<br>HOURS | 48.8 | 7.399                 | 713                                     | 13 382 0 0 0                     | 713         |

## WET BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: NOV

|               |      | LST                   | TO UTC: - 9  | MONTH: NOV  |
|---------------|------|-----------------------|--------------|---|
| HOURS LST     | MEAN | STANDARU<br>DEVIATION | TOTAL<br>OBS | MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F TOTAL  LE 32 GE 50 GE 67 GE 73 GE 80 HOURS |
| 00-02         | 38.0 | 10.179                | 84           | 27 13 0 0 0 8   |
| 03-05         | 36.9 | 10.743                | 84           | 28 14 0 0 0 8   |
| 06-08         | 35.7 | 11.147                | 84           | 37 15 0 0 0 8   |
| 09-11         | 40.4 | 9.833                 | 56           | 13 15 0 0 0 5   |
| 12-14         | 44.4 | 8.567                 | 84           | 12 27 0 0 0 8   |
| 15-17         | 44.4 | 8.104                 | 84           | 10 26 0 0 0 8   |
| 18-20         | 40.3 | 9.361                 | 84           | 18 20 0 0 0 8   |
| 21-23         | 38.4 | 7.922                 | 84           | 22 15 0 0 0 8   |
| ALI,<br>HOURS | 39.8 | 10.211                | 644          | 167 145 0 0 0 64  |
| •••••         |      |                       |              | MONTH: DEC  |
| 00-02         | 26.8 | 7.261                 | 89           | 75 0 0 0 0 89   |
| 03-05         | 25.3 | 8.133                 | 90           | 78 3 0 0 0 96   |
| 06-08         | 24.8 | 8.269                 | 90           | 78 0 0 0 0 96   |
| 09-17         | 30.5 | 6.402                 | 60           | 35 0 0 0 0 66   |
| 12-14         | 34.6 | 5.855                 | 90           | 26 2 0 0 0 9  |
| 15-17         | 35.2 | 5.937                 | 90           | 24 3 0 0 9  |
| 18-20         | 30.9 | 6.272                 | 86           | 46 0 0 0 0 8  |
| 21-23         | 28.4 | 6.667                 | 84           | 65 0 0 0 0 8  |
| ALT,<br>HOURG | 29.5 | 7,920                 | 679          | 427 8 0 0 0 679   |

### WET BULB TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: ALL

LST TO UTC: - 9

|              |          | LST       | r to utc: - 9 | 9    |        | MONTH   | : ALL     |          |            |           |
|--------------|----------|-----------|---------------|------|--------|---------|-----------|----------|------------|-----------|
|              | <b>.</b> |           | . <b></b>     |      |        |         | <b></b> . |          |            | • • • • • |
| HOURS        | MEAN     | STANDARD  | TOTAL         | MEAI | NUMBER | OF HOUR | S WITH    | TEMPERAT | JRES DEG F | TOTAL     |
| LST          |          | DEVIATION | OBS           |      | LE 32  | GE 50   | GE 67     | GE 73    | GE 80      | HOURS     |
| 00-02        | 44.7     | 16.496    | 1599          |      | 406    | 663     | 167       | 38       | 0          | 1599      |
| 03-05        | 43.3     | 16.899    | 1602          |      | 451    | 614     | 137       | 29       | 0          | 1602      |
| 06-08        | 43.0     | 17.417    | 1600          |      | 484    | 620     | 152       | 31       | 0          | 1600      |
| 09-11        | 48.4     | 16.388    | 1065          |      | 195    | 513     | 184       | 49       | 0          | 1065      |
| 12-14        | 51.6     | 15.186    | 1596          |      | 168    | 866     | 336       | 121      | 3          | 1596      |
| 15-17        | 52.3     | 15.041    | 1595          |      | 152    | 884     | 365       | 140      | 4          | 1595      |
| 18-20        | 49.5     | 15.996    | 1590          |      | 259    | 808     | 299       | 112      | 2          | 1590      |
| 21-23        | 46.7     | 16.174    | 1588          |      | 334    | 719     | 207       | 68       | O          | 1588      |
| ALL<br>HOURS | 47.4     | 16.568    | 12235         |      | 2449   | 5687    | 1847      | 588      | 9          | 12235     |

## DEW POINT TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90
LST TO UTC: - 9 MONTH: JAN

|              |      | LS                    | r to utc: - 9 | MONTH: JAN  |                |
|--------------|------|-----------------------|---------------|---|----------------|
| HOURS<br>LST | MEAN | STANDARD<br>DEVIATION | TOTAL<br>OBS  | MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F 1<br>LE 27 GE 37 LE 55 GE 65 | TOTAL<br>HOURS |
| 00-02        | 20.5 | 11.534                | 179           | 116 15 179 0  | 179            |
| 03-05        | 19.2 | 12.263                | 180           | 127 16 180 0  | 180            |
| 06-08        | 18.3 | 12.405                | 180           | 128 10 180 0  | 180            |
| 09-11        | 21.3 | 11.554                | 120           | 79 7 120 0  | 120            |
| 12-14        | 23.7 | 10.644                | 180           | 107 15 180 0  | 180            |
| 15-17        | 23.9 | 9.757                 | 180           | 114 16 180 0  | 180            |
| 18-20        | 22.8 | 9.901                 | 180           | 109 12 180 0  | 180            |
| 21-23        | 21.9 | 10.413                | 180           | 109 12 180 0  | 180            |
| ALL<br>HOURS | 21.4 | 11.241                | 13/9          | 889 103 1379 0  | 1379           |
|              |      |                       |               | MONTH: FEB  |                |
| 00-02        | 26.2 | 7.371                 | 165           | 98 15 165 0   | 168            |
| 03-05        | 25.5 | 7.859                 | 165           | 98 11 165 0   | 168            |
| 06-08        | 24.7 | 8.263                 | 166           | 113 11 166 0  | 168            |
| 09-11        | 27.6 | 7.208                 | 112           | 55 11 112 0   | 168            |
| 12-14        | 28.4 | 7.641                 | 168           | 78 28 168 0   | 163            |
| 15-17        | 28.2 | 8.093                 | 168           | 73 28 168 0   | 168            |
| 18-20        | 28.0 | 7.182                 | 166           | 75 14 166 0   | 168            |
| 21-23        | 26.6 | 7.323                 | 163           | 85 14 163 0   | 168            |
| ALL<br>HOURS | 26.9 | 7.764                 | 1273          | 675 132 1273 0  | 1273           |

### DEW POINT TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAR HOURS MEAN STANDARD TOTAL MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F TOTAL LST DEVIATION OBS LE 27 GE 37 LE 55 GE 65 HOURS 00-02 32.1 7.057 186 49 46 186 0 186 03 -05 31.6 7.138 186 55 44 186 0 186 06-08 31.2 7.484 186 63 46 186 186 09-11 33.6 6.894 124 25 44 124 0 124 34.0 12-14 7.219 186 32 67 186 0 186 15-17 33.7 8.088 186 41 66 186 186 18-20 33.9 7.059 186 67 186 186 21-23 33.6 7.334 186 35 62 186 ALL HOURS 7.412 1426 335 1426 MONTH: APR 00-02 38.9 6.188 170 109 170 165 03-05 38.1 6.403 171 8 105 171 165 06-08 38.0 6.458 168 7 95 168 165 09-11 38.5 7.818 111 11 65 111 165 12-14 37.9 165 8.142 19 92 165 165 39.2 15~17 165 8.426 16 105 163 165 18-20 39.8 7.860 165 14 110 165 165 39.7 21-23 6.661 167 117 167 165 ALL1282 1282 HOURS 38.8 7.315 83 798 1280 0

### DEW POINT TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: MAY LST TO UTC: - 9 ...... HOURS MEAN STANDARD TOTAL MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F TOTAL LST DEVIATION OBS LE 27 GE 37 LE 55 GE 65 ...... 00-02 51.0 5.004 180 0 180 154 0 180 50.5 5.024 03-05 180 0 180 158 0 180 4.924 06-08 50.5 180 0 180 160 0 180 09-11 52.0 5.352 120 0 120 102 0 120 12-14 6.057 180 176 180 52.2 1 138 1 15-17 52.4 6.877 179 2 174 130 179 18-20 52.2 5.967 180 0 180 132 0 180 21-23 51.7 4.923 181 0 181 145 181 0 ALL HOURS 5.630 1380 1371 1119 1380 MONTH: JUN 00-02 59.5 5.350 58.9 5.300 03-05 180 0 180 54 23 180 06-08 58.9 5.242 180 0 180 26 180 53 0 120 09-11 60.4 5.215 120 25 23 180 5.066 180 0 180 180 12-14 61.0 36 39 15-17 61.4 5.091 180 180 35 44 180 18-20 61.4 5.710 180 0 180 38 180 21-23 60.9 5.002 130 180 35 31 180 ALL 5.386 HOURS

### DEW POINT TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: JUL MEAN STANDARD HOURS TOTAL MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F TOTAL DEVIATION LE 27 GE 37 LE 55 GE 65 LST OBS 00-02 68.1 4.707 90 0 90 1 64 03-05 67.4 4.708 90 0 90 2 57 06-08 67.5 4.853 90 0 90 3 62 90 69.2 4.514 09-11 58 0 58 0 50 58 69.8 4.760 87 87 12-14 0 87 0 75 15-17 70.0 4.404 87 0 87 0 75 87 18-20 70.0 4.462 87 87 0 72 87 21-23 69.7 4.625 71 ALL HOURS 68.9 4.795 676 676 7 526 676 MONTH: AUG 00-02 67.1 4.199 93 0 62 03-05 66.5 4.480 93 0 93 2 55 93 06-08 66.2 4.349 93 2 54 93 67.7 09-11 3.987 62 0 62 0 44 93 12-14 68.2 4.479 93 0 93 2 69 93 68.9 15~17 3.968 93 0 93 0 73 93 69.1 4.499 93 2 18-20 0 93 77 93 21-23 67.9 4.648 93 0 67 93 ALLHOURS 4.503 713 713 501 713

## DEW POINT TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: SEP

|   |                                      | LST                                       | TO UTC: - 9                | 9 MONTH: SEP  |                      |
|---|--------------------------------------|---|----------------------------|---|----------------------|
| HOURS LST                                 | MEAN                                 | STANDARD<br>DEVIATION                     | TOTAL<br>OBS               | MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F<br>LE 27 GE 37 LE 55 GE 65 | TOTAL<br>HOURS       |
| 00-02                                     | 59.8                                 | 5.979                                     | 90                         | 0 90 21 17  | 90                   |
| 03-05                                     | 58.9                                 | 6.011                                     | 90                         | 0 90 23 13  | 90                   |
| 06-08                                     | 53.1                                 | 6.195                                     | 90                         | 0 90 27 13  | 90                   |
| 09-11                                     | 60.3                                 | 5.605                                     | 60                         | 0 60 11 10  | 60                   |
| 12-14                                     | 60.3                                 | 5.423                                     | 90                         | 0 90 21 19  | 90                   |
| 15-17                                     | 60.6                                 | 5.955                                     | 90                         | 0 90 21 20  | 90                   |
| 18-20                                     | 61.2                                 | 5.818                                     | 90                         | 0 90 21 27  | 90                   |
| 21-23                                     | 60.3                                 | 5.662                                     | 90                         | . 0 90 21 17  | 90                   |
| ALL<br>HOURS                              | 59.9                                 | 5.943                                     | 690                        | 0 690 166 136   | 690                  |
|   |                                      |   |                            |   |                      |
|   |                                      |   |                            | MONTH: OCT  |                      |
| 00-02                                     | 44.5                                 | 6.842                                     | 93                         | MONTH: OCT<br>O 86 88 0   | 93                   |
| 00-02                                     | 44.5<br>43.2                         | 6.842<br>7.011                            | 93<br>93                   |   | 93<br>93             |
|   |                                      |   |                            | 0 86 88 0   |                      |
| 03-05                                     | 43.2                                 | 7.011                                     | 93                         | 0 86 88 0<br>3 82 89 0  | 93                   |
| 03-05                                     | 43.2<br>42.8                         | 7.011<br>6.993                            | 93<br>93                   | 0 86 88 0<br>3 82 89 0<br>1 73 93 0                                     | 93<br>93             |
| 03-05<br>06-08<br>09-11                   | 43.2<br>42.8<br>44.8                 | 7.011<br>6.993<br>7.412                   | 93<br>93<br>62             | 0 86 88 0<br>3 82 89 0<br>1 73 93 0<br>2 56 59 0                        | 93<br>93<br>93       |
| 03-05<br>06-08<br>09-11<br>12-14          | 43.2<br>42.8<br>44.8<br>46.0         | 7.011<br>6.993<br>7.412<br>7.874          | 93<br>93<br>62<br>93       | 0 86 88 0 3 82 89 0 1 73 93 0 2 56 59 0 3 86 87 0                       | 93<br>93<br>93       |
| 03-05<br>06-08<br>09-11<br>12-14<br>15-17 | 43.2<br>42.8<br>44.8<br>46.0<br>45.6 | 7.011<br>6.993<br>7.412<br>7.874<br>8.238 | 93<br>93<br>62<br>93<br>93 | 0 86 88 0 3 82 89 0 1 73 93 0 2 56 59 0 3 86 87 0 3 82 85 0             | 93<br>93<br>93<br>93 |

# DEW POINT TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: NOV

| • • • • • •                               |  |  |                            |                                  |                             |                            |                             |                      |
|---|--|--|----------------------------|----------------------------------|-----------------------------|----------------------------|-----------------------------|----------------------|
| HOURS<br>LST                              | MEAN   | STANDARD<br>DEVIATION                              | TOTAL<br>OBS               | LE 27 GE                         | € 37                        | LE 55                      | TEMPERATURES DEG F<br>GE 65 | HOURS                |
| 00-02                                     | 36.3   |  | 84                         | 17                               | 41                          | 84                         | 0                           | 84                   |
| 03-05                                     | 35.5   | 12.042   | 84                         | 20                               | 38                          | 81                         | o                           | 84                   |
| 06-08                                     | 34.5   | 12.072   | 84                         | 20                               | 33                          | 81                         | o                           | 84                   |
| 09-11                                     | 36.1   | 11.769   | 56                         | 13                               | 26                          | 54                         | 0                           | 56                   |
| 12-14                                     | 37.1   | 10.538   | 84                         | 15                               | 42                          | 82                         | 0                           | 84                   |
| 15-17                                     | 36.6   | 10.242   | 84                         | 16                               | 42                          | 84                         | 0                           | 84                   |
| 18-20                                     | 36.1   | 11.217   | 84                         | 20                               | 43                          | 84                         | 0                           | 84                   |
| 21-23                                     | 35.9   | 11.552   | 84                         | 21                               | 40                          | 84                         | 0                           | 84                   |
| ALL<br>HOURS                              | 36.0   | 11.337   | 644                        | 142                              | 305                         | 634                        | o                           | 644                  |
|   |  |  |                            |                                  |                             |                            |                             |                      |
|   |  |  |                            |                                  |                             | H: DEC                     |                             |                      |
| 00-02                                     |  |  |                            | •••••                            |                             | H: DEC<br>89               | 0                           | 90                   |
| 00-02                                     | 25.1   |  |                            | •••••                            |                             |                            | 0<br>0                      | 90<br>90             |
|   | 25.1   | 8.379  | 89                         | 51                               | 6                           | 89                         |                             |                      |
| 03-05                                     | 25.1   | 8.379<br>8.840                                     | 89<br>90                   | 51<br>58                         | 6<br>4                      | 89<br>90                   | 0                           | 90                   |
| 03-05                                     | 25.1<br>24.0<br>23.7                         | 8.379<br>8.840<br>8.865                            | 89<br>90<br>90             | 51<br>58<br>60                   | 6<br>4<br>4                 | 89<br>90<br>90             | 0                           | 90<br>90             |
| 03-05<br>06-08<br>09-11                   | 25.1<br>24.0<br>23.7<br>27.4                 | 8.379<br>8.840<br>8.865<br>7.584                   | 89<br>90<br>90<br>60       | 51<br>58<br>60<br>30             | 6<br>4<br>4                 | 89<br>90<br>90             | 0 0                         | 90<br>90<br>90       |
| 03-05<br>06-08<br>09-11<br>12-14          | 25.1<br>24.0<br>23.7<br>27.4<br>27.4         | 8.379<br>8.840<br>8.865<br>7.584<br>7.822          | 89<br>90<br>90<br>60<br>90 | 51<br>58<br>60<br>30<br>43       | 6<br>4<br>4<br>6            | 89<br>90<br>90<br>60       | 0 0 0                       | 90<br>90<br>90<br>90 |
| 03-05<br>06-08<br>09-11<br>12-14<br>15-17 | 25.1<br>24.0<br>23.7<br>27.4<br>27.4<br>28.1 | 8.379<br>8.840<br>8.865<br>7.584<br>7.822<br>8.016 | 89<br>90<br>90<br>60<br>90 | 51<br>58<br>60<br>30<br>43<br>40 | 6<br>4<br>4<br>6<br>10<br>8 | 89<br>90<br>90<br>60<br>90 | 0 0 0 0 0                   | 90<br>90<br>90<br>90 |

# DEW POINT TEMPERATURE SUMMARY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: ALL

|              | BS1 10 01C; - 9 |                       |              | HONTH                              | MONTH. ALL |                             |                |
|--------------|-----------------|-----------------------|--------------|------------------------------------|------------|-----------------------------|----------------|
| HOURS LST    | MEAN            | STANDARD<br>DEVIATION | TOTAL<br>OBS | MEAN NUMBER OF HOUR<br>LE 27 GE 37 | S WITH     | TEMPERATURES DEG F<br>GE 65 | TOTAL<br>HOURS |
| 00-02        | 42.3            | 17.279                | 1599         | 333 951                            | 1180       | 163                         | 1599           |
| 03-05        | 41.5            | 17.537                | 1602         | 369 933                            | 1201       | 148                         | 1602           |
| 06-08        | 41.1            | 17.814                | 1600         | 392 905                            | 1209       | 155                         | 1600           |
| 09-11        | 43.0            | 17.201                | 1065         | 215 635                            | 778        | 127                         | 1065           |
| 12-14        | 43.6            | 16.959                | 1596         | 298 966                            | 1155       | 203                         | 1596           |
| 15-17        | 43.9            | 17.111                | 1595         | 305 971                            | 1142       | 215                         | 1595           |
| 18-20        | 43.9            | 17.237                | 1590         | 296 967                            | 1152       | 222                         | 1590           |
| 21-23        | 43.3            | 17.239                | 1588         | 305 968                            | 1158       | 186                         | 1588           |
| ALL<br>HOURS | 42.8            | 17.329                | 12235        | 2513 7296                          | 8975       | 1419                        | 12235          |

OPERATING LOCATION "A"

## CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY FROM HOURLY OBSERVATIONS

USAFETAC, ASHEVILLE NC PERIOD OF RECORD: JUL 80 - JUN 90 STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCKON KO LST TO UTC: - 9 MONTH: JAN HOURS RELATIVE HUMIDITY GREATER THAN OR EQUAL TO LST 10% 50% 70% 90% MEAN TOTAL OBS 60% 00-02 100.0 100.0 100.0 100.0 99.4 97.8 88.3 62.6 03-05 100.0 100.0 100.0 100.0 98.9 96.7 90.0 71.1 40.6 85.8 180 77.2 96.7 89.4 06-08 100.0 100.0 100.0 100.0 98.3 45.6 86.9 180 09-11 100.0 100.0 100.0 95.7 93.3 85.0 75.0 45.8 20.0 77.3 120 12-14 100.0 100.0 98.9 93.9 80.6 62.2 43.9 23.9 8.9 66.3 180 15-17 100.0 100.0 97.2 90.6 77.2 52.8 32.2 22.8 4.4 63.0 180 100.0 100.0 18-20 100.0 98.3 96.7 78.3 37.8 180 58.9 11.7 73.2 77.2 21-23 100.0 100.0 100.0 100-0 100.0 47.8 80.4 180 95.0 23.9 ALL HOURS 100.0 100.0 99.5 97.5 93.0 83.0 69.1 48.7 23.9 77.1 1379 MONTH: FEB 00-02 100.0 100.0 100.0 100.0 98.2 95.2 84.8 57.0 35.2 83.6 165 03-05 97.6 73.9 100.0 100.0 100.0 100.0 100.0 90.3 48.5 87.8 165 06-03 100.0 100.0 100.0 77.7 100.0 99.4 95.8 88.6 60.2 89.1 166 09-11 100.0 100.0 100.0 98.2 87.5 75.0 64.3 44.6 17.9 74.0 112 i2-14 100.0 100.0 94.6 êŽ.1 58.9 41.1 25.6 20.2 6.0 58.2 168 15-17 100.0 100.0 89.3 74.4 48.8 36.3 31.0 19.0 10.1 168 18-20 100.0 100.0 99.4 93.4 81.9 66.3 41.0 30.1 19.3 166 21-23 100.0 100.0 100.0 98.2 93.3 84.0 63.2 44.8 31.9 77.2 163 ALL HOURS 100.0 100.0 97.8 93.0 83.2 73.7 60.8 45.9 29.0 74.1 1273

### CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KC PERIOD OF RECORD: JUL 80 - JUN 90 MONTH: MAR LST TO UTC: - 9 HOURS RELATIVE HUMIDITY GREATER THAN OR EQUAL TO LST 10% 20% 30% 40% 50% 60% 70% 80% 90% MEAN TOTAL OBS 100.0 100.0 100.0 100.0 98.9 90.3 75.9 57.0 24.2 80.2 186 00-02 03-05 100.0 100.0 100.0 100.0 100.0 97.3 88.2 71.0 36.6 85.7 186 06-08 100.0 100.0 100.0 100.0 99.5 96.8 92.5 72.0 41.9 86.8 186 09-11 100.0 100.0 99.2 96.0 83.1 68.5 44.4 29.0 9.7 67.7 124 12-14 100.0 98.4 91.9 79.6 55.4 33.3 21.5 11.8 7.5 55.2 186 15-17 100.0 96.2 86.6 43.5 29.0 21.0 12.4 8.1 51.5 186 68.8 18-20 100.0 100.0 75.3 55.4 29.6 17.2 7.5 61.6 186 96.8 91.4 21-23 100.0 100.0 100.0 98.9 93.5 82.8 62.9 37.1 14.0 73.7 ALL HOURS 100.0 99.3 96.7 91.7 81.1 69.2 55.0 38.8 19.1 70.4 MONTH: APR 00-02 100.0 100.0 100.0 98.8 96.5 82.4 68.2 55.3 19.4 77.2 03-05 100.0 100.0 100.0 99.4 98.2 92.4 78.4 60.8 33.3 81.8 171 05-08 100.0 100.0 100.0 100.0 99.4 95.2 73.8 56.0 31.5 81.4 168 19.8 09-11 100.0 99.1 88.3 67.6 50.5 32.4 13.5 6.3 52.0 111 13.9 12-14 100.0 89.7 62.4 46.1 27.9 17.6 12.1 3.6 42.0 165 6.7 15-17 100.0 29.1 20.6 17.6 11.5 43.0 165 86.1 63.0 44.8 18-20 100.0 98.2 88.5 61.2 47.9 25.5 12.7 1.8 51.7 165 34.5 100.0 100.0 99.4 47.3 4.2 21-23 95.8 81.4 60.5 ALL 100.0 96.6 87.8 77.4 67.4 55.8 44.4 32.6 13.8 62.6 1282 HOURS

# CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: MAY

|              |       |               | 101 10 | 010.      | ,         |           |          | 110   | win. rmi |                   |   |
|--------------|-------|---------------|--------|-----------|-----------|-----------|----------|-------|----------|-------------------|---|
| HOURS        | <br>  | • • • • • • • | RELA'  | rive hum: | IDITY GRI | EATER THA | N OR EQU | AL TO |          | • • • • • • • • • | • |
| LST          | 10%   | 20%           | 30%    | 40%       | 50%       | 60%       | 70%      |       | 90%      | MEAN              | TOTAL OBS                               |
| 00-02        | 100.0 | 100.0         | 100.0  | 100.0     | 100.0     | 99.4      | 95.6     | 68.3  | 15.0     | 83.5              | 180                                     |
| 03-05        | 100.0 | 100.0         | 100.0  | 100.0     | 100.0     | 100.0     | 97.2     | 86.1  | 32.2     | 88.0              | 180                                     |
| 06-08        | 100.0 | 100.0         | 100.0  | 100.0     | 99.4      | 98.9      | 95.0     | 77.2  | 25.6     | 85.1              | 180                                     |
| 09-11        | 100.0 | 100.0         | 100.0  | 90.0      | 80.0      | 60.0      | 36.7     | 20.0  | 3.3      | 63.6              | 120                                     |
| 12-14        | 100.0 | 98.3          | 91.7   | 79.4      | 55.6      | 36.7      | 15.0     | 8.3   | .6       | 53.2              | 180                                     |
| 15-17        | 99.4  | 97.8          | 89.4   | 74.9      | 59.2      | 30.7      | 19.0     | 10.1  | .6       | 52.4              | 179                                     |
| 18-20        | 100.0 | 99.4          | 97.8   | 90.0      | 80.0      | 59.4      | 32.2     | 17.8  | 3.3      | 62.6              | 180                                     |
| 21-23        | 100.0 | 100.0         | 100.0  | 100.0     | 98.3      | 91.2      | 71.3     | 41.4  | 10.5     | 76.7              | 181                                     |
| ALL<br>HOURS | 99.9  | 99.4          | 97.2   | 91.9      | 84.3      | 72.6      | 58.7     | 42.1  | 11.7     | 70.9              | 1380                                    |
|              |       |               |        |           |           |           |          | м     | ONTH: JU | IN .              |   |
| 00-02        | 100.0 | 100.0         | 100.0  | 98.3      | 98.3      | 98.3      | 92.2     | 81.1  | 26.1     | 85.6              | 180                                     |
| 03~05        | 100.0 | 100.0         | 100.0  | 99.4      | 98.3      | 97.8      | 97.2     | 39.4  | 40.0     | 89.3              | 180                                     |
| 06-08        | 100.0 | 100.0         | 100.0  | 98.9      | 98.9      | 97.2      | 93.9     | 79.4  | 26.7     | 85.8              | 180                                     |
| 09-11        | 100.0 | 100.0         | 100.0  | 98.3      | 91.7      | 65.8      | 37.5     | 24.2  | 7.5      | 67.6              | 120                                     |
| 12-14        | 100.0 | 100.0         | 99.4   | 93.9      | 68.3      | 47.8      | 27.8     | 22.8  | 6.1      | 61.3              | 180                                     |
| 15-17        | 100.0 | 100.0         | 100.0  | 90.0      | 64.4      | 45.6      | 31.7     | 21.7  | 6.7      | 60.7              | 180                                     |
| 18-20        | 100.0 | 100.0         | 100.0  | 96.7      | 86.1      | 68.9      | 45.6     | 29.4  | 11.7     | 68.5              | 180                                     |
| 21-23        | 100.0 | 100.0         | 100.0  | 100.0     | 100.0     | 97.2      | 80.6     | 60.6  | 13.9     | 80.8              | 180                                     |
| ALL<br>HOURS | 100.0 | 100.0         | 99.9   | 96.9      | 88.1      | 77.8      | 64.4     | 52.2  | 17.8     | 75.3              | 1380                                    |

# CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL

| HOURS  |   |   | RELA'                                     | CIVE HUM  | IDITY GR                                       | EATER TH                                       | AN OR EQU                                    | AL TO                                       |   |                                      |   |
|--|---|---|---|---|--|--|--|---|---|--------------------------------------|---|
| LST  | 10%                                       | 20%                                       | 30%                                       | 40%   | 50%  | 60%  | 70%  | 80%   | 90%                                       | MEAN                                 | TOTAL OBS                               |
|  | ·   |   |   |   |  |  |  |   |   |                                      |   |
| 00-02  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 100.0  | 100.0  | 98.9   | 94.4  | 50.0                                      | 89.5                                 | 90                                      |
|  |   |   |   |   |  |  |  |   |   |                                      |   |
| 03-05  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 100.0  | 100.0  | 100.0  | 95.6  | 60.0                                      | 91.2                                 | 90                                      |
|  |   |   |   |   |  |  |  |   |   |                                      |   |
| 06-08  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 100.0  | 100.0  | 98.9   | 87.8  | 48.9                                      | 88.9                                 | 90                                      |
|  |   |   |   |   |  |  |  |   |   |                                      |   |
| 09-11  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 98.3   | 86.2   | 67.2   | 32.8  | 17.2                                      | 75.3                                 | 58                                      |
|  |   |   |   |   |  |  |  |   |   |                                      |   |
| 12-14  | 100.0                                     | 100.0                                     | 100.0                                     | 96.6  | 89.7   | 66.7   | 44.8   | 26.4  | 13.8                                      | 68.4                                 | 87                                      |
|  |   |   |   |   |  |  |  |   |   |                                      |   |
| 15-17  | 100.0                                     | 100.0                                     | 100.0                                     | 96.6  | 87.4   | 67.8   | 36.8   | 17.2  | 2.3                                       | 65.1                                 | 87                                      |
|  |   |   |   |   |  |  |  |   |   |                                      |   |
| 18-20  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 96.6   | 82.8   | 57.5   | 31.0  | 8.0                                       | 72.8                                 | 87                                      |
|  |   |   |   |   |  |  |  |   |   |                                      |   |
| 21-23  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 100.0  | 100.0  | 94.3   | 74.7  | 36.8                                      | 85.9                                 | 87                                      |
|  |   |   |   |   |  |  |  |   |   |                                      |   |
| ALL  |   |   |   |   |  |  |  |   |   |                                      |   |
| HOURS  | 100.0                                     | 100.0                                     | 100.0                                     | 99.1  | 96.4   | 88.2   | 75.4   | 59.0  | 30.5                                      | 80.0                                 | 676                                     |
| •••••  | • • • • • • • • • •                       | • • • • • • • •                           | • • • • • • •                             | • • • • • • • •                                 |  | • • • • • • •                                  | • • • • • • • •                              | • • • • • • •                               | • • • • • • •                             | • • • • • • • • •                    | • |
|  |   |   |   |   |  |  |  |   |   |                                      |   |
|  |   |   |   |   |  |  |  | М   | ONTH: AU                                  | G                                    |   |
| 00.00  |   |   |   |   |  |  |  |   |   |                                      |   |
| 00-02  |   |   | 400 0                                     | 100 0   | 400.0  |  |  |   |   |                                      |   |
|  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 100.0  | 100.0  | 94.6   | 76.3  | 35.5                                      | 86.0                                 | 93                                      |
| A3 AF  |   |   |   |   |  |  |  |   |   |                                      |   |
| 03-05  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 100.0  | 100.0  | 94.6<br>93.5                                 | 76.3<br>91.4                                | 35.5<br>52.7                              | 86.0<br>89.3                         | 93<br>93                                |
| ,  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 100.0  | 100.0  | 93.5   | 91.4  | 52.7                                      | 89.3                                 | 93                                      |
| 03-05  |   |   |   |   |  |  |  |   |   |                                      |   |
| 06-08  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 100.0  | 100.0  | 93.5<br>93.5                                 | 91.4<br>79.6                                | 52.7<br>39.8                              | 89.3<br>86.7                         | 93<br>93                                |
| ,  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 100.0  | 100.0  | 93.5   | 91.4  | 52.7                                      | 89.3                                 | 93                                      |
| 06-08  | 100.0                                     | 100.0<br>100.0<br>100.0                   | 100.0<br>100.0<br>100.0                   | 100.0<br>100.0<br>100.0                         | 100.0<br>100.0<br>88.7                         | 100.0<br>100.0<br>56.5                         | 93.5<br>93.5<br>37.1                         | 91.4<br>79.6<br>16.1                        | 52.7<br>39.8<br>3.2                       | 89.3<br>86.7<br>65.9                 | 93<br>93<br>62                          |
| 06-08  | 100.0                                     | 100.0                                     | 100.0                                     | 100.0   | 100.0  | 100.0  | 93.5<br>93.5<br>37.1                         | 91.4<br>79.6                                | 52.7<br>39.8                              | 89.3<br>86.7                         | 93<br>93                                |
| 06-08<br>09-11<br>12-14                            | 100.0<br>100.0<br>100.0                   | 100.0<br>100.0<br>100.0<br>100.0          | 100.0<br>100.0<br>100.0<br>100.0          | 100.0<br>100.0<br>100.0<br>92.5                 | 100.0<br>100.0<br>88.7<br>66.7                 | 100.0<br>100.0<br>56.5<br>37.6                 | 93.5<br>93.5<br>37.1<br>22.6                 | 91.4<br>79.6<br>16.1<br>8.6                 | 52.7<br>39.8<br>3.2<br>4.3                | 89.3<br>86.7<br>65.9<br>58.1         | 93<br>93<br>62<br>93                    |
| 06-08  | 100.0                                     | 100.0<br>100.0<br>100.0                   | 100.0<br>100.0<br>100.0                   | 100.0<br>100.0<br>100.0                         | 100.0<br>100.0<br>88.7                         | 100.0<br>100.0<br>56.5                         | 93.5<br>93.5<br>37.1                         | 91.4<br>79.6<br>16.1                        | 52.7<br>39.8<br>3.2                       | 89.3<br>86.7<br>65.9                 | 93<br>93<br>62                          |
| 06-08<br>09-11<br>12-14<br>15-17                   | 100.0<br>100.0<br>100.0<br>100.0          | 100.0<br>100.0<br>100.0<br>100.0          | 100.0<br>100.0<br>100.0<br>100.0          | 100.0<br>100.0<br>100.0<br>92.5<br>90.3         | 100.0<br>100.0<br>88.7<br>66.7<br>64.5         | 100.0<br>100.0<br>56.5<br>37.6                 | 93.5<br>93.5<br>37.1<br>22.6<br>22.6         | 91.4<br>79.6<br>16.1<br>8.6<br>10.8         | 52.7<br>39.8<br>3.2<br>4.3<br>5.4         | 89.3<br>86.7<br>65.9<br>58.1<br>58.0 | 93<br>93<br>62<br>93                    |
| 06-08<br>09-11<br>12-14                            | 100.0<br>100.0<br>100.0                   | 100.0<br>100.0<br>100.0<br>100.0          | 100.0<br>100.0<br>100.0<br>100.0          | 100.0<br>100.0<br>100.0<br>92.5                 | 100.0<br>100.0<br>88.7<br>66.7                 | 100.0<br>100.0<br>56.5<br>37.6                 | 93.5<br>93.5<br>37.1<br>22.6                 | 91.4<br>79.6<br>16.1<br>8.6                 | 52.7<br>39.8<br>3.2<br>4.3                | 89.3<br>86.7<br>65.9<br>58.1         | 93<br>93<br>62<br>93                    |
| 06-08<br>09-11<br>12-14<br>15-17<br>18-20          | 100.0<br>100.0<br>100.0<br>100.0<br>100.0 | 100.0<br>100.0<br>100.0<br>100.0<br>100.0 | 100.0<br>100.0<br>100.0<br>100.0<br>100.0 | 100.0<br>100.0<br>100.0<br>92.5<br>90.3<br>97.8 | 100.0<br>100.0<br>88.7<br>66.7<br>64.5<br>86.0 | 100.0<br>100.0<br>56.5<br>37.6<br>37.6<br>69.9 | 93.5<br>93.5<br>37.1<br>22.6<br>22.6<br>54.8 | 91.4<br>79.6<br>16.1<br>8.6<br>10.8<br>29.0 | 52.7<br>39.8<br>3.2<br>4.3<br>5.4<br>15.1 | 89.3<br>86.7<br>65.9<br>58.1<br>58.0 | 93<br>93<br>62<br>93<br>93              |
| 06-08<br>09-11<br>12-14<br>15-17                   | 100.0<br>100.0<br>100.0<br>100.0          | 100.0<br>100.0<br>100.0<br>100.0          | 100.0<br>100.0<br>100.0<br>100.0          | 100.0<br>100.0<br>100.0<br>92.5<br>90.3         | 100.0<br>100.0<br>88.7<br>66.7<br>64.5         | 100.0<br>100.0<br>56.5<br>37.6                 | 93.5<br>93.5<br>37.1<br>22.6<br>22.6         | 91.4<br>79.6<br>16.1<br>8.6<br>10.8         | 52.7<br>39.8<br>3.2<br>4.3<br>5.4         | 89.3<br>86.7<br>65.9<br>58.1<br>58.0 | 93<br>93<br>62<br>93                    |
| 06-08<br>09-11<br>12-14<br>15-17<br>18-20<br>21-23 | 100.0<br>100.0<br>100.0<br>100.0<br>100.0 | 100.0<br>100.0<br>100.0<br>100.0<br>100.0 | 100.0<br>100.0<br>100.0<br>100.0<br>100.0 | 100.0<br>100.0<br>100.0<br>92.5<br>90.3<br>97.8 | 100.0<br>100.0<br>88.7<br>66.7<br>64.5<br>86.0 | 100.0<br>100.0<br>56.5<br>37.6<br>37.6<br>69.9 | 93.5<br>93.5<br>37.1<br>22.6<br>22.6<br>54.8 | 91.4<br>79.6<br>16.1<br>8.6<br>10.8<br>29.0 | 52.7<br>39.8<br>3.2<br>4.3<br>5.4<br>15.1 | 89.3<br>86.7<br>65.9<br>58.1<br>58.0 | 93<br>93<br>62<br>93<br>93              |
| 06-08<br>09-11<br>12-14<br>15-17<br>18-20          | 100.0<br>100.0<br>100.0<br>100.0<br>100.0 | 100.0<br>100.0<br>100.0<br>100.0<br>100.0 | 100.0<br>100.0<br>100.0<br>100.0<br>100.0 | 100.0<br>100.0<br>100.0<br>92.5<br>90.3<br>97.8 | 100.0<br>100.0<br>88.7<br>66.7<br>64.5<br>86.0 | 100.0<br>100.0<br>56.5<br>37.6<br>37.6<br>69.9 | 93.5<br>93.5<br>37.1<br>22.6<br>22.6<br>54.8 | 91.4<br>79.6<br>16.1<br>8.6<br>10.8<br>29.0 | 52.7<br>39.8<br>3.2<br>4.3<br>5.4<br>15.1 | 89.3<br>86.7<br>65.9<br>58.1<br>58.0 | 93<br>93<br>62<br>93<br>93              |

E - 6 - 4

# CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: SEP

|              |           |       | LST TO | UTC: -   | 9             |          |           | MC     | NTH: SEP      | •        |   |
|--------------|-----------|-------|--------|----------|---------------|----------|-----------|--------|---------------|----------|---|
| HOURS        | . <b></b> |       | RELA   | FIVE HUM | <br>IDITY GRI | EATER TH | AN OR EQU | JAL TO |               |          | • |
| LST          | 10%       | 20%   | 30%    | 40%      | 50%           | 60%      | 70%       | 80%    | 90%           | MEAN     | TOTAL OBS                               |
| 00~02        | 100.0     | 100.0 | 100.0  | 100.0    | 100.0         | 100.0    | 100.0     | 98.9   | 66.7          | 92.1     | 90                                      |
| 03-05        | 100.0     | 100.0 | 100.0  | 100.0    | 100.0         | 100.0    | 100.0     | 100.0  | 85.6          | 95.5     | 90                                      |
| 06-08        | 100.0     | 100.0 | 100.0  | 100.0    | 100.0         | 100.0    | 98.9      | 97.8   | 73.3          | 93.9     | 90                                      |
| 09-11        | 100.0     | 100.0 | 100.0  | 100.0    | 95.0          | 78.3     | 43.3      | 20.0   | 10.0          | 69.3     | 60                                      |
| 12-14        | 100.0     | 100.0 | 100.0  | 98.9     | 72.2          | 34.4     | 11.1      | 6.7    | 6.7           | 57.9     | 90                                      |
| 15-17        | 100.0     | 100.0 | 100.0  | 95.6     | 68.9          | 38.9     | 17.8      | 10.0   | 6.7           | 58.8     | 90                                      |
| 18-20        | 100.0     | 100.0 | 100.0  | 100.0    | 98.9          | 88.9     | 63.3      | 43.3   | 13.3          | 76.0     | 90                                      |
| 21-23        | 100.0     | 100.0 | 100.0  | 100.0    | 100.0         | 100.0    | 95.6      | 87.8   | 35.6          | 87.5     | 90                                      |
| ALL<br>HOURS | 100.0     | 100.0 | 100.0  | 99.3     | 91.7          | 80.1     | 67.2      | 59.7   | 38.4          | 79.3     | 690                                     |
|              |           |       |        |          |               |          |           | М      | ONTH: OC      | T        |   |
|              |           |       |        |          |               |          | <b></b> . |        | • • • • • • • | <i>.</i> |   |
| 00-02        | 100.0     | 100.0 | 100.0  | 100.0    | 100.0         | 100.0    | 96.8      | 96.8   | 67.7          | 93.0     | 93                                      |
| 03-05        | 100.0     | 100.0 | 100.0  | 100.0    | 100.0         | 100.0    | 98.9      | 96.8   | 78.5          | 95.8     | 93                                      |
| 06-08        | 100.0     | 100.0 | 100.0  | 100.0    | 100.0         | 100.0    | 100.0     | 98.9   | 87.1          | 96.6     | 93                                      |
| 09-11        | 100.0     | 100.0 | 100.0  | 96.8     | 77.4          | 66.1     | 41.9      | 29.0   | 11.3          | 67.8     | 62                                      |
| 12-14        | 100.0     | 100.0 | 94.6   | 73.1     | 47.3          | 30.1     | 22.6      | 15.1   | 1.1           | 53.5     | 93                                      |
| 15-17        | 100.0     | 100.0 | 90.3   | 71.0     | 45.2          | 28.0     | 18.3      | 11.8   | 4.3           | 52.0     | 93                                      |
| 18-20        | 100.0     | 100.0 | 100.0  | 98.9     | 90.3          | 76.3     | 60.2      | 36.6   | 11.8          | 72.3     | 93                                      |
| 21-23        | 100.0     | 100.0 | 100.0  | 100.0    | 98.9          | 94.6     | 92.5      | 76.3   | 29.0          | 85.5     | 93                                      |
| ALL<br>HOURS | 100.0     | 100.0 | 98.0   | 92.3     | 82.6          | 74.8     | 67.5      | 58.9   | 37.4          | 77.5     | 713                                     |

ALL

HOURS

100.0 100.0

99.0

97.3

93.8

# CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: NOV

|              |       |       | LOI 10 | 010.      | •     |       | 110       |      |          |      |           |
|--------------|-------|-------|--------|-----------|-------|-------|-----------|------|----------|------|-----------|
| HOURS<br>LST | 10%   | 20%   | RELAT  | rive Hum: |       |       | AN OR EQU |      | 90%      | MEAN | TOTAL OBS |
| 00-02        | 100.0 | 100.0 | 100.0  | 100.0     | 100.0 | 100.0 | 94.0      | 77.4 | 57.1     | 90.1 | 84        |
| 03-05        | 100.0 | 100.0 | 100.0  | 100.0     | 100.0 | 98.8  | 95.2      | 83.3 | 71.4     | 92.4 | 84        |
| 06-08        | 100.0 | 100.0 | 100.0  | 100.0     | 100.0 | 100.0 | 98.8      | 86.9 | 72.6     | 92.8 | 84        |
| 09-11        | 100.0 | 100.0 | 100.0  | 100.0     | 91.1  | 85.7  | 62.5      | 44.6 | 17.9     | 75.6 | 56        |
| 12-14        | 100.0 | 100.0 | 100.0  | 98.8      | 76.2  | 45.2  | 29.8      | 13.1 | 8.3      | 61.2 | 84        |
| 15-17        | 100.0 | 100.0 | 100.0  | 91.7      | 67.9  | 38.1  | 26.2      | 14.3 | 9.5      | 59.7 | 84        |
| 18-20        | 100.0 | 100.0 | 100.0  | 100.0     | 97.6  | 91.7  | 67.9      | 38.1 | 17.9     | 75.4 | 84        |
| 21-23        | 100.0 | 100.0 | 100.0  | 100.0     | 100.0 | 96.4  | 86.9      | 73.8 | 41.7     | 85.0 | 84        |
| ALL<br>HOURS | 100.0 | 100.0 | 100.0  | 98.8      | 91.6  | 81.8  | 70.5      | 54.3 | 37.9     | 79.2 | 644       |
|              |       |       |        |           |       |       |           | м    | ONTH: DE | c    |           |
| 00-02        | 100.0 | 100.0 | 100.0  | 100.0     | 100.0 | 100.0 | 100.0     | 82.0 | 60.7     | 90.5 | 89        |
| 03-05        | 100.0 | 100.0 | 100.0  | 100.0     | 100.0 | 100.0 | 100.0     | 88.9 | 66.7     | 92.6 | 90        |
| 06-09        | 100.0 | 100.0 | 100.0  | 100.0     | 100.0 | 98.9  | 96.7      | 91.1 | 75.6     | 93.6 | 90        |
| 09-11        | 100.0 | 100.0 | 100.0  | 100.0     | 100.0 | 90.0  | 80.0      | 58.3 | 35.0     | 82.8 | 60        |
| 12-14        | 100.0 | 100.0 | 95.6   | 88.9      | 77.8  | 51.1  | 31.1      | 24.4 | 13.3     | 63.8 | 90        |
| 15-17        | 100.0 | 100.0 | 96.7   | 91.1      | 78.9  | 52.2  | 32.2      | 25.6 | 13.3     | 64.1 | 90        |
| 18-20        | 100.0 | 100.0 | 100.0  | 100.0     | 96.5  | 88.4  | 74.4      | 45.3 | 31.4     | 79.9 | 86        |
| 21-23        | 100.0 | 100.0 | 100.0  | 100.0     | 100.0 | 100.0 | 94.0      | 69.0 | 51.2     | 88.2 | 84        |
|              |       |       |        |           |       |       |           |      |          |      |           |

60.7

43.7

81.8

84.7 75.7

679

# CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENTE OF RELATIVE HUMIDITY FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: ALL

|              |       |       | 2671 10 | 010.     |          |          |          |       |      |      |   |
|--------------|-------|-------|---------|----------|----------|----------|----------|-------|------|------|---|
| HOURS        |       |       | RELAT   | IVE HUMI | DITY GRE | ATER THA | N OR EQU | AL TO |      |      | • |
| LST          | 10%   | 20%   | 30%     | 40%      | 50%      | 60%      | 70%      | 80%   | 90%  | MEAN | TOTAL OBS                               |
| 00-02        | 100.0 | 100.0 | 100.0   | 99.7     | 99.1     | 96.0     | 88.8     | 71.8  | 36.0 | 85.0 | 1599                                    |
| 03-05        | 100.0 | 100.0 | 100.0   | 99.9     | 99.5     | 97.9     | 92.9     | 81.3  | 48.8 | 88.6 | 1602                                    |
| 06-08        | 100.0 | 100.0 | 100.0   | 99.9     | 99.4     | 97.8     | 92.0     | 79.1  | 47.8 | 88.0 | 1600                                    |
| 09-11        | 100.0 | 99.9  | 98.7    | 94.1     | 84.8     | 68.8     | 49.3     | 30.8  | 12.4 | 69.0 | 1065                                    |
| 12-14        | 100.0 | 98.6  | 92.9    | 83.5     | 62.6     | 41.4     | 25.4     | 16.2  | 6.3  | 57.6 | 1596                                    |
| 15-17        | 99.9  | 97.9  | 91.2    | 79.3     | 58.9     | 38.6     | 25.5     | 15.8  | 6.3  | 56.2 | 1595                                    |
| 18-20        | 100.  | 99.7  | 98.1    | 92.4     | 83.6     | 68.1     | 46.9     | 28.6  | 11.5 | 67.7 | 1590                                    |
| 21-23        | 100.0 | 100.0 | 99.9    | 99.2     | 95.3     | 89.5     | 75.3     | 53.9  | 23.1 | 79.2 | 1588                                    |
| ALL<br>HOURS | 100.0 | 99.5  | 97.6    | 93.5     | 85.6     | 75.0     | 62.6     | 47.9  | 24.5 | 74.1 | 12235                                   |

| PPPPP | PPP  | AAA   | AAA   | RRRR | RRRR  | TTTTTTTTT | FFFFFFFFF |
|-------|------|-------|-------|------|-------|-----------|-----------|
| PPPPP | PPPP | AAAA  | AAAA  | RRRR | RRRRR | TTTTTTTTT | FFFFFFFFF |
| PP    | PP   | AA    | AA    | RR   | RR    | TT        | FF        |
| PP    | PP   | AA    | AA    | RR   | RR    | TT        | FF        |
| PPPPP | pppp | AA    | AA    | RRRR | RRRRR | TT        | FFFFFF    |
| PPPPP | PPP  | AAAAA | AAAAA | RRPR | RRRR  | TT        | FFFFFF    |
| PP    |      | AAAAA | AAAAA | RR   | RR    | TT        | FF        |
| PP    |      | AA    | AA    | RR   | RR    | TT        | FF        |
| PP    |      | AA    | AA    | RR   | RR    | TT        | FF        |
| PP    |      | AA    | AA    | RR   | RR    | TT        | FF        |

#### PART F

#### PRESSURE SUMMARIES

ALL PRESSURE DATA IN PART F IS TAKEN FROM HOURLY OBSERVATIONS. IT IS SUMMARIZED:

- BY EIGHT 3-HOUR STANDARD SYNOPTIC REPORTING TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

#### SEA LEVEL PRESSURE.

IN MILLIBARS, TABLES GIVE MEANS, STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS. THIS SUMMARY IS NOT AVAILABLE FOR METAR REPORTING SITES.

#### ALTIMETER SETTING.

IN INCHES OF MERCURY (HG), TABLES GIVE MEANS, STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS.

#### STATION PRESSURE.

IN INCHES OF MERCURY (HG), TABLES GIVE MEANS, STANDARD DEVIATIONS AND TOTAL OBSERVATION COUNTS.

PRESSURE CONVERSIONS ARE: 1 MILLIBAR = 0.02953 INCHES OF MERCURY (Hg).

# ALTIMETER SETTING IN INCHES FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066

STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

| HOURS<br>(LST) | STATS      | JAN        | FEB   | MAR   | APR        | MAY   | JUN   | JUL   | AUG   | SEP   | ост   | NOV   | DEC   | ANN   |
|----------------|------------|------------|-------|-------|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 0000           | L MEAN !   | 30.31      | 30.27 | 30.13 | 29.97      | 29.92 | 29.79 | 29.82 | 29.79 | 29.92 | 30.12 | 30.25 | 30.26 | 30.05 |
| 0000           | MEAN<br>SD | .170       | .138  | .169  | .139       | .133  | .154  | .116  | .117  | .128  | .088  | .134  | .160  | .239  |
|                | TOT OBS    | .170<br>59 | 55    | 62    | .139<br>56 | 60    | 60    | 30    | 31    | 30    | 31    | 28    | 29    | 531   |
|                | 101 083    | 39         | 33    | 02    | 30         | 80    | 80    | 30    | 31    | 30    | 31    | 20    | 29    | 331   |
| 0300           | MEAN       | 30.31      | 30.27 | 30.13 | 29.96      | 29.90 | 29.78 | 29.80 | 29.78 | 29.92 | 30.12 | 30.25 | 30.25 | 30.04 |
|                | SD         | .179       | .137  | .167  | .142       | .118  | .158  | .119  | .126  | .139  | .102  | .132  | .165  | .244  |
|                | TOT OBS    | 60         | 55    | 62    | 57         | 60    | 60    | 30    | 31    | 30    | 31    | 28    | 30    | 534   |
| 0600           | MEAN       | 30.30      | 30.26 | 30.13 | 29.97      | 29.90 | 29.80 | 29.81 | 29.78 | 29.92 | 30.12 | 30.24 | 30.24 | 30.04 |
|                | SD         | .181       | .139  | .162  | .145       | .123  | .156  | .128  | .129  | .144  | .122  | .137  | .164  | .240  |
|                | TOT OBS    | 60         | 55    | 62    | 57         | 50    | 60    | 30    | 31    | 30    | 31    | 28    | 30    | 534   |
| 0900           | MEAN       | .00        | .00   | .00   | .00        | .00   | .00   | .00   | .00   | .00   | .00   | .00   | .00   | .00   |
|                | SD         | .000       | .000  | .000  | .000       | .000  | .000  | .000  | .000  | .000  | .000  | .000  | .000  | .000  |
|                | TOT OBS    | 0          | 0     | 0     | 0          | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 1200           | MEAN       | 30.32      | 30.27 | 30.13 | 29.96      | 29.88 | 29.79 | 29.81 | 29.78 | 29.91 | 30.12 | 30.26 | 30.26 | 30.05 |
|                | SD         | .169       | .142  | .166  | .137       | .119  | .144  | .124  | .114  | .150  | .120  | .127  | .155  | .244  |
|                | TOT OBS    | 60         | 56    | 62    | 55         | 60    | 60    | 29    | 31    | 30    | 31    | 28    | 30    | 532   |
| 1500           | MEAN       | 30.27      | 30.22 | 30.07 | 29.91      | 29.84 | 29.76 | 29.77 | 29.75 | 29.87 | 30.07 | 30.22 | 30.21 | 30.00 |
|                | SD         | .161       | .143  | .164  | .130       | .116  | .136  | .119  | .106  | .146  | .108  | .111  | .151  | .235  |
|                | TOT OBS    | 60         | 56    | 62    | 55         | 59    | 60    | 29    | 31    | 30    | 31    | 28    | 30    | 531   |
| 1800           | MEAN       | 30.29      | 30.23 | 30.07 | 29.91      | 29.84 | 29.75 | 29.77 | 29.75 | 29.88 | 30.07 | 30.23 | 30.23 | 30.00 |
|                | SD         | .160       | .136  | .165  | .126       | .109  | .140  | .120  | .103  | .144  | .095  | .106  | .150  | .241  |
|                | TOT OBS    | 60         | 56    | 62    | 55         | 60    | 60    | 29    | 31    | 30    | 31    | 28    | 30    | 532   |
| 2100           | MEAN       | 30.31      | 30.27 | 30.11 | 29.96      | 29.88 | 29.78 | 29.81 | 29.78 | 29.92 | 30.11 | 30.26 | 30.25 | 30.04 |
|                | SD         | .162       | .134  | .168  | .130       | .111  | .147  | .116  | .107  | .134  | .097  | .106  | .157  | .239  |
|                | TOT OBS    | 60         | 54    | 62    | 55         | 60    | 60    | 29    | 31    | 30    | 31    | 28    | 28    | 528   |
| ALL            | MEAN       | 30.30      | 30.26 | 30.11 | 29.95      | 29.88 | 29.78 | 29.80 | 29.77 | 29.91 | 30.10 | 30.24 | 30.24 | 30.03 |
| HOURS          | l I        | .170       | .140  | .168  | .138       | .122  | .149  | .122  | .116  | .142  | .108  | .123  | .158  | .241  |
|                | TOT OBS    | 419        | 387   | 434   | 390        | 419   | 420   | 206   | 217   | 210   | 217   | 196   | 207   | 3722  |

# STATION PRESSURE IN INCHES FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

|                |         |       |       |       |       |       |       |       | <i>.</i> |       |       |       |       |       |
|----------------|---------|-------|-------|-------|-------|-------|-------|-------|----------|-------|-------|-------|-------|-------|
| HOURS<br>(LST) |         | JAN   | FEB   | MAR   | APR   | MAY   | JUN   | JUL   | AUG      | SEP   | OCT   | NOV   | DEC   | ANN   |
| 0000           | MEAN    | 30.09 | 30.05 | 29.91 | 29.75 | 29.70 | 29.57 | 29.60 | 29.57    | 29.70 | 29.90 | 30.03 | 30.04 | 29.83 |
| 0000           | SD      | .170  | .138  | .169  | .139  | .133  | .152  | .117  | .116     | .128  | .088  | .134  | .160  | .238  |
|                | TOT OBS | 59    | 55    | 62    | 56    | 60    | 61    | 29    | 31       | 30    | 31    | 28    | 29    | 531   |
|                | 101 063 | . 39  | 33    | 02    | 30    | 00    | ٠.    | 23    | 31       | 30    | 31    | 20    | 23    | 331   |
| 0300           | MEAN    | 30.09 | 30.05 | 29.91 | 29.74 | 29.68 | 29.56 | 29.58 | 29.56    | 29.70 | 29.90 | 30.03 | 30.03 | 29.82 |
|                | SD      | .179  | .137  | .167  | .142  | .118  | .157  | .117  | .125     | .139  | .102  | .132  | .165  | .243  |
|                | TOT OBS | 60    | 55    | 62    | 57    | 60    | 60    | 30    | 31       | 30    | 31    | 28    | 30    | 534   |
| 0600           | MEAN    | 30.08 | 30.04 | 29.91 | 29.75 | 29.68 | 29.58 | 29.59 | 29.56    | 29.70 | 29.90 | 30.02 | 30.02 | 29.82 |
|                | SD      | .181  | .139  | .162  | .145  | .123  | .154  | .126  | .128     | .144  | .122  | .137  | .164  | .240  |
|                | TOT OBS | 60    | 55    | 62    | 57    | 60    | 60    | 30    | 31       | 30    | 31    | 28    | 30    | 534   |
|                |         |       |       |       |       |       |       |       |          |       |       |       |       |       |
| 0900           | MEAN    | .00   | .00   | .00   | .00   | .00   | .00   | .00   | .00      | .00   | .00   | .00   | .00   | .00   |
|                | SD      | .000  | .000  | .000  | .000  | .000  | .000  | .000  | .000     | .000  | .000  | .000  | .000  | .000  |
|                | TOT OBS | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0        | 0     | 0     | 0     | 0     | 0     |
| 1200           | MEAN    | 30.10 | 30.05 | 29.91 | 29.74 | 29.66 | 29.57 | 29.59 | 29.56    | 29.69 | 29.90 | 30.04 | 30.04 | 29.83 |
|                | SD      | .169  | .142  | .166  | .137  | .119  | .143  | .122  | .113     | .150  | .120  | .127  | .155  | .244  |
|                | TOT OBS | 60    | 56    | 62    | 55    | 60    | 60    | 29    | 31       | 30    | 31    | 28    | 30    | 532   |
| 1500           | MEAN    | 30.05 | 30.00 | 29.85 | 29.69 | 29.63 | 29.54 | 29.56 | 29.53    | 29.65 | 29.85 | 30.00 | 29.99 | 29.78 |
| 1300           | SD      | .161  | .143  | .164  | .130  | .115  | .135  | .117  | .105     | .146  | .108  | .111  | .151  | .235  |
|                | TOT OBS | 60    | 56    | 62    | 55    | 59    | 60    | 29    | 31       | 30    | 31    | 28    | 30    | 531   |
|                | 101 000 |       | 30    | ~~    |       |       | 00    |       |          | 30    |       |       |       | 331   |
| 1800           | MEAN    | 30.07 | 30.01 | 29.85 | 29.69 | 29.62 | 29.53 | 29.55 | 29.53    | 29.66 | 29.85 | 30.01 | 30.01 | 29.78 |
|                | SD      | .160  | .136  | .165  | .126  | .109  | .139  | .119  | .103     | .144  | .095  | .106  | .150  | .240  |
|                | TOT OBS | 60    | 56    | 62    | 55    | 60    | 60    | 29    | 31       | 30    | 31    | 28    | 30    | 532   |
| 2100           | MEAN    | 30.09 | 30.05 | 29.89 | 29.74 | 29.66 | 29.56 | 29.59 | 29.56    | 29.70 | 29.89 | 30.04 | 30.03 | 29.82 |
| 2100           | SD      | .162  | .134  | .168  | .130  | .111  | .146  | .116  | .107     | .134  | .097  | .106  | .157  | .238  |
|                | TOT OBS | 60    | 54    | 62    | 55    | 60    | 60    | 29    | 31       | 30    | 31    | 28    | 28    | 528   |
|                | 101 083 | 60    | 34    | 02    | 23    | 80    | 80    | 29    | 31       | 30    | 31    | 20    | 20    | 320   |
| ALL            | MEAN    | 30.08 | 30.04 | 29.89 | 29.73 | 29.66 | 29.56 | 29.58 | 29.55    | 29.69 | 29.88 | 30.02 | 30.02 | 29.81 |
| HOURS          | SD      | .170  | .140  | .168  | .138  | .122  | .148  | .120  | .115     | .142  | .108  | .123  | .158  | .241  |
|                | TOT OBS | 419   | 387   | 434   | 390   | 419   | 421   | 205   | 217      | 210   | 217   | 196   | 207   | 3722  |

| PPPPP | PPP  | AAA   | AAA   | RRRR | RRRR  | TITITITITITI | G   | GGGG  |
|-------|------|-------|-------|------|-------|--------------|-----|-------|
| PPPPP | PPPP | AAAA  | AAAA  | RRRR | RRRRR | TTTTTTTTT    | GGG | GGGGG |
| PP    | PP   | AA    | AA    | RR   | RR    | TT           | GG  | GG    |
| PP    | PP   | AA    | AA    | RR   | RR    | TT           | GG  |       |
| PPPPP | PPPP | AA    | AA    | RRRR | RRRRR | TT           | GG  |       |
| PPPPP | PPP  | AAAAA | AAAAA | RRRR | RRRR  | TT           | GG  | GGGG  |
| PP    |      | AAAAA | AAAAA | RR   | RR    | TT           | GG  | GGGGG |
| PP    |      | AA    | AA    | RR   | RR    | TT           | GG  | GG    |
| PP    |      | AA    | AA    | RR   | RR    | TT           | GGG | GGGGG |
| PP    |      | AA    | AA    | RR   | RR    | dat.         | GC  | GGGG  |

G - 1 - 1

#### PART G

#### CROSSWIND SUMMARY

#### CROSSWIND SUMMARIES.

THESE TABLES ARE CREATED FROM HOURLY AND SPECIAL OBSERVATIONS (INCLUDING PEAK GUST REMARKS). THE TABLES ARE SUMMARIZED AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY MONTH (ALL YEARS AND THE HOURS 0600-2000 LST COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND THE HOURS 0600-2000 LST COMBINED).

THE TABLES GIVE PERCENT OCCURRENCE FREQUENCY (POF) OF THE "CROSS-RUNWAY WIND COMPONENT" FOR THE WIND SPEED CLASSES SPECIFIED IN THE TABLE HEADINGS. THERE ARE TWO COMPONENT CATEGORIES:

THE FIRST COMPONENT IS COMPUTED FROM THE REPORTED WIND DIRECTION AND WIND SPEED FROM HOURLY RECORD OR RECORD-SPECIAL OBSERVATIONS.

THE SECOND COMPONENT IS COMPUTED FROM THE HIGHEST REPORTED WIND SPEED AND DIRECTION FROM ALL OBSERVATIONS INCLUDING REMARKS, GUSTS, AND SPECIAL OBSERVATIONS.

OBSERVATION COUNTS INCLUDE CALM WINDS.

VARIABLE WINDS ARE CONSIDERED A DIRECT CROSSWIND IF THE SPEED EQUALS OR EXCEEDS THE SPECIFIED THRESHOLD WIND SPEED VALUE(S).

A TOTAL OBSERVATION COUNT IS INCLUDED.

CATEGORY B

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 180-360

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JJL 80 - JUN 90
LST TO UTC: - 9 MONTH: JAN

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

| TIME (LST)                              |                         | 000  | 00 - 020 | 00   |       | 030         | 0 - 050       | 00          |      | 06   | 00 -      | 0800  |                   | 090         | 00 - 110      | 00    |
|---|-------------------------|------|----------|------|-------|-------------|---------------|-------------|------|------|-----------|-------|-------------------|-------------|---------------|-------|
| SPEED (KTS)                             | GE10                    | GE15 | GE25     | OBS  | GE10  | GE15        | GE25          | OBS         | GE10 | GE15 | GE2       | 5 OBS | GE10              | GE15        | GE25          | OBS   |
| CATEGORY A                              |                         |      |          | 179  |       |             |               | 180         |      |      |           | 180   | .8                |             |               | 120   |
| CATEGORY B                              | .5                      |      |          | 191  |       |             |               | 197         | .5   |      |           | 213   | .7                |             |               | 147   |
|   | <br>• • • • • • •       |      |          |      |       |             | •••••         |             |      |      | ••••      |       |                   | • • • • • • | , <b></b>     |       |
| TIME (LST)                              |                         | 120  | 00 - 140 | 00   |       | 150         | 0 ~ 170       | 00          |      | 18   | 00 -      | 2000  |                   | 210         | 00 - 23       | 00    |
| SPEED (KTS)                             | GE10                    | GE15 | GE25     | OBS  | GE10  | GE15        | GE25          | OBS         | GE10 | GE15 | GE2       | 5 OBS | GE10              | GE15        | GE25          | OBS   |
| CATEGORY A                              | .6                      |      |          | 180  |       |             |               | 180         |      |      |           | 180   |                   |             |               | 180   |
| CATEGORY B                              | 1.0                     |      |          | 205  | 1.0   |             |               | 200         |      |      |           | 197   | 1.0               |             |               | 203   |
| • | <br>• • • • • • • • • • |      | •••••    |      |       |             |               |             |      |      |           |       |                   | • • • • • • | · • • • • • • | ····• |
|   |                         |      | *****    |      | ••••• | • • • • • • | • • • • • • • | • • • • • • |      |      | • • • • • |       | • • • • • • • • • |             |               | ••••  |
| TIME (LST)                              |                         |      |          |      | 0600  | - 2000      | ı             |             |      |      | ALL       | HOURS |                   |             |               |       |
| SPEED KTS                               |                         |      |          | GE10 | GE15  | GE25        | OBS           | 3           | (    | 3E10 | GE15      | GE25  | OBS               |             |               |       |
| CATEGORY A                              |                         |      |          | .2   |       |             | 840           | )           |      | .1   |           |       | 1379              |             |               |       |

962

.6

1553

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS

FROM HOURLY OBSERVATIONS

.......

MAGNETIC RUNWAY HEADING: 180-360

CATEGORY B

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO LST TO UTC: - 9

PERIOD OF RECORD: JUL 80 - JUN 90

MONTH: FEB

.8 .2

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

| TIME (LST)  |                      | 000         | 0 - 020     | 00                              |             | 030         | 0 - 05      | 00            |               | 060         | 0 - 0     | 800                                     |                   | 090         | 0 - 11      | 00        |
|-------------|----------------------|-------------|-------------|---------------------------------|-------------|-------------|-------------|---------------|---------------|-------------|-----------|---|-------------------|-------------|-------------|-----------|
| SPEED (KTS) | GE10                 | GE15        | GE25        | OBS                             | GE10        | GE15        | GE25        | OBS           | GE10          | GE15        | GE25      | OBS                                     | GE10              | GE15        | GE25        | OBS       |
| CATEGORY A  |                      |             |             | 165                             |             |             |             | 165           |               |             |           | 166                                     |                   |             |             | 112       |
| CATEGORY B  | .5                   |             |             | 185                             |             |             |             | 182           |               |             |           | 199                                     | 1.4               | .7          |             | 140       |
|             | · · · · · · · · ·    | • • • • • • | • • • • • • |                                 |             |             |             |               | • • • • • • • |             |           | • |                   | • • • • • • |             |           |
| TIME (LST)  |                      | 120         | 0 - 140     | 00                              |             | 150         | 0 - 17      | 00            |               | 180         | 00 - 2    | 000                                     |                   | 210         | 0 - 23      | 00        |
| SPEED (KTS) | GE10                 | GE15        | GE25        | OBS                             | GE10        | GE15        | GE25        | OBS           | GE10          | GE15        | GE25      | OBS                                     | GE10              | GE15        | GE25        | OBS       |
| CATEGORY A  |                      |             |             | 168                             |             |             |             | 168           |               |             |           | 166                                     |                   |             |             | 163       |
| CATEGORY B  | 2.7                  | 1.1         |             | 182                             | 1.1         |             |             | 176           | .6            |             |           | 176                                     |                   |             |             | 171       |
|             | l<br>• • • • • • • • |             |             | · · · · · · · · · · · · · · · · | · · · · · · |             |             |               |               |             |           |   |                   |             |             |           |
|             |                      | • • • • • • | • • • • • • |                                 |             | • • • • • • | • • • • • • | • • • • • • • | • • • • • • • | • • • • • • | • • • • • | •••••                                   | • • • • • • • • • |             | • • • • • • | • • • • • |
| TIME (LST)  |                      |             |             |                                 | 0600        | - 2000      | )           |               |               | F           | ALL       | HOURS                                   |                   |             |             |           |
| SPEED KTS   |                      |             |             | GE10                            | GE15        | GE25        | ОВ          | s             | G             | E10 G       | SE15      | GE25                                    | OBS               |             |             |           |
| CATEGORY A  |                      |             |             |                                 |             |             | 78          | 0             |               |             |           |   | 1273              |             |             |           |
|             |                      |             |             |                                 |             |             |             |               |               |             |           |   |                   |             |             |           |

1.1 .3 873

1411

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS

FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 180-360

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: MAR

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

| TIME (LST)                              |                    | 000         | 0 - 02 | 00        |          | 030   | 0 - 95 | 00              |      | 060   | 0 - 080 | 00            |      | 090  | 0 - 11 | 00        |
|---|--------------------|-------------|--------|-----------|----------|-------|--------|-----------------|------|-------|---------|---------------|------|------|--------|-----------|
| SPEED (KTS)                             | GE10               | GE15        | GE25   | OBS       | GE10     | GE15  | GE25   | OBS             | GE10 | GE15  | GE25    | OBS           | GE10 | GE15 | GE25   | OBS       |
| CATEGORY A                              |                    |             |        | 186       |          |       |        | 186             |      |       |         | 186           |      |      |        | 124       |
| CATEGORY B                              |                    |             |        | 196       | 1.5      |       |        | 204             |      |       |         | 228           |      |      |        | 149       |
| • | ]<br>· · · · · · · |             |        |           | <i>.</i> |       |        | • • • • • • •   |      |       |         |               |      |      |        |           |
| TIME (LST)                              |                    | 120         | 0 - 14 | 00        |          | 150   | 0 - 17 | 00              |      | 180   | 0 - 200 | 00            |      | 210  | 0 - 23 | 00        |
| SPEED (KTS)                             | GE10               | GE15        | GE25   | OBS       | GE10     | GE15  | GE25   | OBS             | GE10 | GE15  | GE25    | OBS           | GE10 | GE15 | GE25   | OBS       |
| CATEGORY A                              | 1.6                |             |        | 186       | 1.1      |       |        | 186             |      |       |         | 186           |      |      |        | 186       |
| CATEGORY B                              | 4.1                | .5          |        | 196       | 6.3      | 1.1   |        | 189             | 1.5  | .5    |         | 199           |      |      |        | 194       |
| • | <br>               |             |        |           |          |       |        | · · · · · · · · |      |       |         | • • • • • • • |      |      |        |           |
| ••••••                                  |                    | • • • • • • |        | • • • • • |          | ••••• | . ,    | • • • • • • •   |      | ••••• |         | • • • • • •   |      |      | •••••  | • • • • • |
|   | 1                  |             |        |           |          |       |        |                 |      | _     |         |               |      |      |        |           |

|      | 0600 | - 2000    |     |                    | ALL                                  | HOURS                        |                                   |
|------|------|-----------|-----|--------------------|--------------------------------------|------------------------------|-----------------------------------|
| GE10 | GE15 | GE25      | OBS | GE10               | GE15                                 | GE25                         | OBS                               |
| .6   |      |           | 868 | .4                 |                                      |                              | 1426                              |
| 2.4  | .4   |           | 961 | 1.7                | .3                                   |                              | 1555                              |
|      | .6   | GE10 GE15 | .6  | GE10 GE15 GE25 OBS | GE10 GE15 GE25 OBS GE10<br>.6 868 .4 | GE10 GE15 GE25 OBS GE10 GE15 | GE10 GE15 GE25 OBS GE10 GE15 GE25 |

CATEGORY B

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS

FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: APR

#### CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

#### CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

| TIME (LST)  |                 | 000         | 0 - 020     | 00   |      | 030       | 0 - 050     | 00  |                 | 060         | 00 - 00 | 800   |   | 090       | 0 - 110     | 00        |
|-------------|-----------------|-------------|-------------|------|------|-----------|-------------|-----|-----------------|-------------|---------|-------|---|-----------|-------------|-----------|
| SPEED (KTS) | GE10            | GE15        | GE25        | OBS  | GE10 | GE15      | GE25        | OBS | GE10            | GE15        | GE25    | OBS   | GE10                                    | GE15      | GE25        | OBS       |
| CATEGORY A  |                 |             |             | 170  |      |           |             | 171 |                 |             |         | 169   | 1.8                                     |           |             | 112       |
| CATEGORY B  |                 |             |             | 188  | .5   |           |             | 190 |                 |             |         | 199   | 5.7                                     | 1.6       |             | 122       |
| •••••       | · · · · · · · · | • • • • • • | • • • • • • |      |      | • • • • • | • • • • • • |     | •••••           | • • • • • • |         |       | • | • • • • • | • • • • • • | • • • • • |
| TIME (LST)  | [               | 120         | 0 - 140     | 00   |      | 150       | 0 - 170     | 00  |                 | 180         | 00 - 20 | 000   |   | 210       | 0 - 230     | 00        |
| SPEED (KTS) | GE10            | GE15        | GE25        | OBS  | GE10 | GE15      | GE25        | OBS | GE10            | GE15        | GE25    | OBS   | GE10                                    | GE15      | GE25        | OBS       |
| CATEGORY A  | 4.8             | 1.2         |             | 165  | 5.5  |           |             | 165 | 1.2             |             |         | 165   | .6                                      |           |             | 167       |
| CATEGORY B  | 7.5             | 3.2         | 1.1         | 187  | 7.7  | 1.1       |             | 183 | 2.2             | .6          |         | 181   | 1.1                                     |           |             | 178       |
|             | <br>            |             |             |      |      |           |             |     | • • • • • • • • | • • • • • • |         |       |   |           |             |           |
| TIME (LST)  |                 |             |             |      | 0600 | - 2000    | ı           |     |                 | i           | ALL I   | HOURS |   |           |             |           |
| SPEED KTS   |                 |             |             | GE10 | GE15 | GE25      | ОВ          | 3   | (               | JE10 (      | GE15    | GE25  | OBS                                     |           |             |           |
| CATEGORY A  |                 |             |             | 2.7  | .3   |           | 776         | 5   |                 | 1.7         | .2      |       | 1284                                    |           |             |           |

4.5 1.3 .2 872

2.9 .8 .1

1428

MAGNETIC RUNWAY HEADING: 180-360

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS

FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 180-360

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: MAY

#### CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

#### CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

| TIME (LST)  |                   | 000  | 0 - 020 | 00   |      | 030    | 0 - 0500 | 0           |      | 06   | 00 - | 0800              |      | 090  | 0 - 110 | 00  |
|-------------|-------------------|------|---------|------|------|--------|----------|-------------|------|------|------|-------------------|------|------|---------|-----|
| SPEED (KTS) | GE10              | GE15 | GE25    | OBS  | GE10 | GE15   | GE25     | OBS         | GE10 | GE15 | GE2  | 5 OBS             | GE10 | GE15 | GE25    | OBS |
| CATEGORY A  | <u> </u>          |      |         | 180  |      |        |          | 180         |      |      |      | 180               | 1.7  |      |         | 120 |
| CATEGORY B  | .5                |      |         | 215  |      |        |          | 228         |      |      |      | 253               | 1.4  |      |         | 142 |
|             | <br>· • • • • • • |      |         |      |      |        |          | · • • • • • |      |      |      | • • • • • • • • • |      |      |         |     |
| TIME (LST)  |                   | 120  | 0 - 140 | 00   |      | 150    | 0 - 170  | D           |      | 18   | 00 - | 2000              |      | 210  | 0 - 230 | 00  |
| SPEED (KTS) | GE10              | GE15 | GE25    | OBS  | GE10 | GE15   | GE25     | OBS         | GE10 | GE15 | GE2  | 5 OBS             | GE10 | GE15 | GE25    | OBS |
| CATEGORY A  | 2.2               |      |         | 180  | 1.1  |        |          | 179         |      |      |      | 180               |      |      |         | 181 |
| CATEGORY B  | 2.5               |      |         | 204  | 2.4  | .5     |          | 212         | .5   |      |      | 205               |      |      |         | 197 |
|             | <br>              |      |         |      |      |        |          | • • • • • • |      |      |      |                   |      |      |         |     |
| TIME (LST)  |                   |      |         |      | 0600 | - 2000 | 1        |             |      |      | ALL  | HOURS             |      |      |         |     |
| SPEED KTS   |                   |      |         | GE10 | GE15 | GE25   | OBS      |             | C    | E10  | GE15 | GE25              | OBS  |      |         |     |
| CATEGORY A  |                   |      |         | 1.0  |      |        | 839      |             |      | .6   |      |                   | 1380 |      |         |     |
| CATEGORY B  |                   |      |         | 1.3  | .1   |        | 1016     |             |      | .8   | .1   |                   | 1656 |      |         |     |

CATEGORY B

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS

FROM HOURLY OBSERVATIONS

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: JUN

#### CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

#### CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

| TIME (LST)  |   | 000         | 0 - 020     | 00                  |             | 030       | 0 - 050       | 0      |       | 06        | 00 -   | 0800          |   | 090         | 0 - 110 | 00        |
|-------------|---|-------------|-------------|---------------------|-------------|-----------|---------------|--------|-------|-----------|--------|---------------|---|-------------|---------|-----------|
| SPEED (KTS) | GE10                                    | GE15        | GE25        | OBS                 | GE10        | GE15      | GE25          | OBS    | GE10  | GE15      | GE2    | 5 OBS         | GE10                                    | GE15        | GE25    | OBS       |
| CATEGORY A  |   |             |             | 180                 |             |           |               | 180    |       |           |        | 180           |   |             |         | 120       |
| CATEGORY B  | 2.0                                     | 2.0         |             | 203                 |             |           |               | 227    |       |           |        | 233           | .6                                      | .6          |         | 155       |
|             | · • • • • • • •                         | • • • • • • |             |                     | • • • • •   | • • • • • | • • • • • • • |        |       | • • • • • |        | ••••••        | • |             |         | ••••      |
| TIME (LST)  |   | 120         | 0 - 140     | 00                  |             | 150       | 0 - 170       | 0      |       | 18        | 00 - : | 2000          |   | 210         | 0 - 230 | 00        |
| SPEED (KTS) | GE10                                    | GE15        | GE25        | OBS                 | GE10        | GE15      | GE25          | OBS    | GE10  | GE15      | GE2    | 5 OBS         | GE10                                    | GE15        | GE25    | OBS       |
| CATEGORY A  | .6                                      |             |             | 180                 | .6          |           |               | 180    |       |           |        | 180           |   |             |         | 180       |
| CATEGORY B  | 1.4                                     | .5          |             | 210                 | 1.0         |           |               | 200    |       |           |        | 206           | .5                                      | .5          |         | 198       |
|             |   | • • • • • • |             | • • • • • • • • • • | • • • • • • |           |               |        |       | • • • • • |        | • • • • • • • | • |             |         | • • • • • |
| TIME (LST)  | · • • • • • • • • • • • • • • • • • • • | •••••       | • • • • • • | • • • • • • • • •   | 0600        | - 2000    | • • • • • •   | •••••• | ••••• | ••••      | ALL    | HOURS         | •••••                                   | • • • • • • | ••••    | • • • • • |
| , ,         |   |             |             | on 10               |             |           |               |        |       |           |        |               | OP.                                     |             |         |           |
| SPEED KTS   |   |             |             | GE10                | GE15        | GE25      | OBS           | •      | G     | E10       | GE15   | GE25          | OBS                                     |             |         |           |
| CATEGORY A  |   |             |             | .2                  |             |           | 840           | •      |       | .1        |        |               | 1380                                    |             |         |           |

.6 .2 1004

1632

MAGNETIC RUNWAY HEADING: 180-360

USAFETAC, ASHEVILLE NC

## OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS

FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 180-360

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90 LST TO UTC: - 9 MONTH: JUL

#### CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

#### CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

| TIME (LST)  |                   | 000           | 0 - 020 | 00   |               | 030         | 0 - 05 | 00          |      | 060   | 00 -   | 0080  |      | 090         | 0 - 110     | 00        |
|-------------|-------------------|---------------|---------|------|---------------|-------------|--------|-------------|------|-------|--------|-------|------|-------------|-------------|-----------|
| SPEED (KTS) | GE10              | GE15          | GF25    | OBS  | GE10          | GE15        | GE25   | OBS         | GE10 | GE15  | GE2    | 5 OBS | GE10 | GE15        | GE25        | OBS       |
| CATEGORY A  |                   |               |         | 87   |               |             |        | 87          |      |       |        | 87    |      |             |             | 58        |
| CATEGORY B  |                   |               |         | 99   | .9            |             |        | 115         |      |       |        | 108   |      |             |             | 73        |
|             | <br>• • • • • • • |               |         |      |               |             |        |             |      |       |        |       |      |             |             |           |
| TIME (LST)  |                   | 120           | 0 - 140 | 00   |               | 150         | 0 - 17 | 00          |      | 180   | 00 - 1 | 2000  |      | 210         | 0 - 230     | 00        |
| SPEED (KTS) | GE10              | GE15          | GE25    | OBS  | GE10          | GE15        | GE25   | OBS         | GE10 | GE15  | GE2    | 5 OBS | GE10 | GE15        | GE25        | OBS       |
| CATEGORY A  |                   |               |         | 87   |               |             |        | 87          |      |       |        | 87    |      |             |             | 87        |
| CATEGORY B  | .9                |               |         | 111  |               |             |        | 99          |      |       |        | 104   |      |             |             | 103       |
|             | !<br>             |               |         |      |               |             |        |             |      |       |        |       |      |             |             |           |
|             |                   | • • • • • • • |         |      | • • • • • • • | • • • • • • | •••••  | • • • • • • |      |       | ••••   |       |      | • • • • • • | • • • • • • | • • • • • |
| TIME (LST)  |                   |               |         |      | 0600          | - 2000      |        |             |      | P     | LL     | HOURS |      |             |             |           |
| SPEED KTS   |                   |               |         | GE10 | GE15          | GE25        | OB     | S           | C    | E10 0 | E15    | GE25  | OBS  |             |             |           |
| CATEGORY A  |                   |               |         |      |               |             | 40     | 5           |      |       |        |       | 667  |             |             |           |
| CATEGORY B  |                   |               |         | .2   |               |             | 49     | 5           |      | .2    |        |       | 812  |             |             |           |

\*

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS

FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 180-360

PERIOD OF RECORD: JUL 80 - JUN 90

### TABLE FOR A SECOND STORAGE OF VISIBILITY (HOURLY OBS ONLY)

#### MINOR OF WINDS PEPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

| TIME (LST)  |                          | 900         | 0 = 11  | •               |       | 030         | i0 - 05     | 00          |                   | 060   | 00 -      | 0800            |   | 090         | 00 - 110    | 00        |
|-------------|--------------------------|-------------|---------|-----------------|-------|-------------|-------------|-------------|-------------------|-------|-----------|-----------------|---|-------------|-------------|-----------|
| SPEED (KTS) | GE10                     | GE15        | 0E25    | ù.p.⊲           | *F:1* | ::F15       | GE25        | OBS         | GE10              | GE15  | GE2       | 5 OBS           | GE10                                    | GE15        | GE25        | OBS       |
| CATEGORY A  |                          |             |         | фì              |       |             |             | 93          |                   |       |           | 93              | 3.2                                     |             |             | 62        |
| CATEGORY B  |                          |             |         | 106             |       |             |             | 117         |                   |       |           | 114             | 5.5                                     |             |             | 73        |
|             | l<br>• • • • • • • • • • |             |         |                 |       |             |             |             |                   |       |           |                 | • |             |             |           |
| TIME (LST)  |                          | 120         | 0 - 140 | 00              |       | 150         | 0 - 17      | 00          |                   | 180   | 00 -      | 2000            |   | 210         | 0 - 230     | 00        |
| SPEED (KTS) | GE10                     | GE15        | GE25    | OBS             | GE10  | GE15        | GE25        | овя         | GE10              | GE15  | GE2       | 5 OBS           | GE10                                    | GE15        | GE25        | OBS       |
| CATEGORY A  | 3.2                      |             |         | 93              | 4.3   |             |             | 93          |                   |       |           | 93              |   |             |             | 93        |
| CATEGORY B  | 5.0                      | 1.0         |         | 101             | 3.8   |             |             | 104         |                   |       |           | 108             |   |             |             | 105       |
|             | !<br>                    |             |         |                 |       |             |             |             |                   |       |           | • • • • • • •   |   |             |             |           |
|             |                          | • • • • • • |         | • • • • • • • • |       | • • • • • • | • • • • • • | • • • • • • | • • • • • • • • • |       | • • • • • | • • • • • • • • |   | • • • • • • | • • • • • • | • • • • • |
| TIME (LST)  |                          |             |         |                 | 0600  | - 2000      | •           |             |                   | i     | ALL       | HOURS           |   |             |             |           |
| SPEED KTS   |                          |             |         | GE10            | GE15  | GE25        | OB          | S           | (                 | E10 ( | GE 15     | GE25            | OBS                                     |             |             |           |
| CATEGORY A  |                          |             |         | 2.1             |       |             | 43          | 4           |                   | 1.3   |           |                 | 713                                     |             |             |           |
| CATEGORY B  |                          |             |         | 2.6             | .2    |             | 50          | 0           |                   | 1.6   | .1        |                 | 828                                     |             |             |           |

CATEGORY B

## PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS

FROM HOURLY OBSERVATIONS

| STATION NUMBER: 471066 | STATION NAME: | CAMP CASEY/TONGDUCHON KO | PERIOD OF RECORD: | JUL 80 - JUN 90 |
|------------------------|---------------|--------------------------|-------------------|-----------------|
|                        |               |                          |                   |                 |

LST TO UTC: - 9 MONTH: SEP

#### CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

#### CATEGORY P: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

MAGNETIC RUNWAY HEADING: 180-360

| TIME (LST)  | 0000 -                                     | - 0200    | 030         | 0 - 0500                                | 0600 - 0800        | 0900 - 1100        |
|-------------|--|-----------|-------------|---|--------------------|--------------------|
| SPEED (KTS) | GE10 GF15 GE                               | E25 OBS G | GE10 GE15   | GE25 OBS                                | GE10 GE.5 GE25 OBS | GE10 GE15 GE25 OBS |
| CATEGORY A  |  | 90        |             | 90                                      | 90                 | 60                 |
| CATEGORY B  |  | 109       |             | 107                                     | 116                | 67                 |
|             | <br>                                       |           |             |   |                    |                    |
| TIME (LST)  | 1200 -                                     | - 1400    | 150         | 0 - 1700                                | 1800 - 2000        | 2100 - 2300        |
| SPEED (KTS) | GE10 GE15 GE                               | E25 OBS G | GE10 GE15   | GE25 OBS                                | GE10 GE15 GE25 OBS | GE10 GE15 GE25 OBS |
| CATEGORY A  |  | 90        |             | 90                                      | 1.1 90             | 90                 |
| CATEGORY B  | 3.1  | 97        | 1.0 1.0     | 103                                     | 1.0 1.0 101        | 95                 |
|             | \<br>· · · · · · · · · · · · · · · · · · · |           |             |   |                    |                    |
|             | •    |           |             | • | •••••              | •••••              |
| TIME (LST)  |  | C         | 0600 - 2000 |   | ALL HOURS          |                    |
| SPEED KTS   |  | GE10 0    | GE15 GE25   | OBS                                     | GE10 GE15 GE25     | OBS                |
| CATEGORY A  |  | .2        |             | 420                                     | .1                 | 690                |

484

.6 .3

795

1.0 .4

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS

FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 180-360

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: OCT

#### CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

### CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

| TIME (LST)  |   | 000  | 0 - 020 | 00   |      | 030    | 0 - 050 | 00       |       | 06   | 00 - | 0800            |      | 090  | 0 - 110     | 00  |
|-------------|---|------|---------|------|------|--------|---------|----------|-------|------|------|-----------------|------|------|-------------|-----|
| SPEED (KTS) | GE10                                    | GE15 | GE25    | OBS  | GE10 | GE15   | GE25    | OBS      | GE10  | GE15 | GE2  | 5 OBS           | GE10 | GE15 | GE25        | OBS |
| CATEGORY A  | ı                                       |      |         | 93   |      |        |         | 93       |       |      |      | 93              |      |      |             | 62  |
| CATEGORY B  |   |      |         | 112  |      |        |         | 114      | .8    |      |      | 133             | 1.2  |      |             | 81  |
|             | • • • • • • •                           |      |         |      |      |        |         | <i>.</i> | ••••• |      |      |                 |      |      | • • • • • • |     |
| TIME (LST)  |   | 120  | 0 - 140 | 00   |      | 150    | 0 - 176 | 00       |       | 18   | 00 - | 2000            |      | 210  | 0 - 230     | 00  |
| SPEED (KTS) | GE10                                    | GE15 | GE25    | OBS  | GE10 | GE15   | GE25    | OBS      | GE10  | GE15 | GE2  | 5 OBS           | GE10 | GE15 | GE25        | OBS |
| CATEGORY A  | 4.3                                     |      |         | 93   | 1.1  |        |         | 93       |       |      |      | 93              |      |      |             | 93  |
| CATEGORY B  | 5.0                                     | 2.0  |         | 101  | 4.0  |        |         | 100      | 1.9   |      |      | 103             |      |      |             | 107 |
|             | · • • • • • • • • • • • • • • • • • • • |      |         |      |      |        |         |          |       |      |      | • • • • • • • • |      |      | • • • • • • |     |
| TIME (LST)  |   |      |         |      | 0600 | - 2000 |         |          |       |      | ALL  | HOURS           |      |      |             |     |
| SPEED KTS   |   |      |         | GE10 | GE15 | GE25   | ОВ      | S        | d     | E10  | GE15 | GE25            | OBS  |      |             |     |
| CATEGORY A  |   |      |         | 1.2  |      |        | 43      | 4        |       | .7   |      |                 | 713  |      |             |     |
| CATEGORY B  |   |      |         | 2.5  | .4   |        | 518     | 3        |       | 1.5  | .2   |                 | 851  |      |             |     |

CATEGORY B

# PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 180-360

2.1 .1

725

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: NOV

3.2 .2

### CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

#### CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

| TIME (LST)  | 0000 - 0200        | 0300 ~ 0500                             | 0600 - 0800                             | 0900 - 1100                             |
|-------------|--------------------|---|---|---|
| SPEED (KTS) | GE10 GE15 GE25 OBS | GE10 GE15 GE25 OBS                      | GE10 GE15 GE25 OBS                      | GE10 GE15 GE25 OBS                      |
| CATEGORY A  | 84                 | 84                                      | 84                                      | 1.8 56                                  |
| CATEGORY B  | 94                 | 103                                     | 1.9 104                                 | 1.6 64                                  |
|             | 1                  |   |   |   |
| TIME (LST)  | 1200 - 1400        | 1500 - 1700                             | 1800 - 2000                             | 2100 - 2300                             |
| SPEED (KTS) | GE10 GE15 GE25 OBS | GE10 GE15 GE25 OBS                      | GE10 GE15 GE25 OBS                      | GE10 GE15 GE25 OBS                      |
| CATEGORY A  | 84                 | 84                                      | 84                                      | 84                                      |
| CATEGORY B  | 4.3 1.1 93         | 5.6 90                                  | 2.3 88                                  | 1.1 89                                  |
|             |                    |   |   | • |
|             |                    | • | *************************************** |   |
| TIME (LST)  |                    | 0600 - 2000                             | ALL HOURS                               |   |
| SPEED KTS   | GE10               | GE15 GE25 OBS                           | GE10 GE15 GE25 O                        | вѕ                                      |
| CATEGORY A  | .3                 | 392                                     | .2 6                                    | 44                                      |

439

### PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS

FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 180-360

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9 MONTH: DEC

#### CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS,

| TIME (LST)                              |                     | 000         | 0 - 020     | 00                |      | 030         | 0 - 05    | 00       |      | 060         | 00 - 0  | 0800  |                 | 090       | 0 - 110 | 00        |
|---|---------------------|-------------|-------------|-------------------|------|-------------|-----------|----------|------|-------------|---------|-------|-----------------|-----------|---------|-----------|
| SPEED (KTS)                             | GE10                | GE15        | GE25        | OBS               | GE10 | GE15        | GE25      | OBS      | GE10 | GE15        | GE2     | obs   | GE10            | GE15      | GE25    | OBS       |
| CATEGORY A                              |                     |             |             | 89                |      |             |           | 90       |      |             |         | 90    |                 |           |         | 60        |
| CATEGORY B                              | 1.0                 |             |             | 97                | 4.1  |             |           | 97       |      |             |         | 105   |                 |           |         | 69        |
|   | <br>· • • • • • •   |             |             |                   |      |             |           | <i>.</i> |      |             |         |       |                 |           |         |           |
| TIME (LST)                              |                     | 120         | 0 - 140     | 00                |      | 150         | 0 - 17    | 00       |      | 180         | :o - :  | 2000  |                 | 210       | 0 - 230 | 00        |
| SPEED (KTS)                             | GE10                | GE15        | GE25        | OBS               | GE10 | GE15        | GE25      | OBS      | GE10 | GE15        | GE2     | obs   | GE10            | GE15      | GE25    | OBS       |
| CATEGORY A                              |                     |             |             | 90                |      |             |           | 90       |      |             |         | 86    |                 |           |         | 84        |
| CATEGORY B                              | .9                  |             |             | 107               | 3.2  |             |           | 93       | 1.1  |             |         | 90    |                 |           |         | 89        |
| • | <br>· · · · · · · · |             |             |                   |      |             |           |          |      |             |         |       |                 |           |         |           |
|   |                     | • • • • • • | • • • • • • | • • • • • • • • • |      | • • • • • • | • • • • • |          |      | • • • • • • | • • • • |       | • • • • • • • • | • • • • • |         | • • • • • |
| TIME (LST)                              |                     |             |             |                   | 0600 | - 2000      | )         |          |      | P           | TL      | HOURS |                 |           |         |           |
| SPEED KTS                               |                     |             |             | GE10              | GE15 | GE25        | ОВ        | S        | C    | SE10 6      | E15     | GE25  | OBS             |           |         |           |
| CATEGORY A                              |                     |             |             |                   |      |             | 41        | 6        |      |             |         |       | 679             |           |         |           |
| CATEGORY B                              |                     |             |             | 1.1               |      |             | 46        | 4        |      | 1.3         |         |       | 747             |           |         |           |

#### PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 180-360

CATEGORY A

CATEGORY B

STATION NUMBER: 471066 STATION NAME: CAMP CASEY/TONGDUCHON KO

.0

.3

.0

1.7

PERIOD OF RECORD: JUL 80 - JUN 90

LST TO UTC: - 9

MONTH: ALL

.0

1.2 .2

12228

.0 13993

#### CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

......

### CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

| • | • • • • • • •           | • • • • • • | • • • • • • | • • • • • • • • •                       | • • • • • • •                           | • • • • • • | • • • • • • | • • • • • • • | • | • • • • • • | • • • • • • | • • • • • • | · · · · · · · · · · · ·               | • • • • • • | • • • • • • | • • • • • |
|---|-------------------------|-------------|-------------|---|---|-------------|-------------|---------------|---|-------------|-------------|-------------|---------------------------------------|-------------|-------------|-----------|
| TIME (LST)                              |                         | 000         | 0 - 02      | იი                                      |   | 030         | 0 - 05      | 00            |   | 060         | 0 - 08      | 100         |                                       | 090         | 0 - 11      | 00        |
| SPEED (KTS)                             | GE10                    | GE15        | GE25        | OBS                                     | GE10                                    | GE15        | GE25        | OBS           | GE10                                    | GE15        | GE25        | OBS         | GE10                                  | GE15        | GE25        | OBS       |
| CATEGORY A                              |                         |             |             | 15∌6                                    |   |             |             | 1599          |   |             |             | 1598        | .8                                    |             |             | 1066      |
| CATEGORY B                              | .4                      | .2          |             | 1795                                    | .5                                      |             |             | 1881          | .2                                      |             |             | 2005        | 1.5                                   | .3          |             | 1282      |
| • | · · · · · · · · · · · · |             | • • • • • • | • | • • • • • • • •                         |             |             |               |   |             |             | •••••       |                                       | • • • • • • |             | • • • • • |
| TIME (LST)                              |                         | 120         | 0 - 14      | 00                                      |   | 150         | 0 - 17      | 00            |   | 180         | 0 - 20      | 000         |                                       | 210         | 0 - 23      | 00        |
| SPEED (KTS)                             | GE10                    | GE15        | GE25        | OBS                                     | GE10                                    | GE15        | GE25        | OBS           | GE10                                    | GE15        | GE25        | OBS         | GE10                                  | GE15        | GE25        | OBS       |
| CATEGORY A                              | 1.5                     | .1          |             | 1596                                    | 1.2                                     |             |             | 1595          | .2                                      |             |             | 1590        | .1                                    |             |             | 1588      |
| CATEGORY B                              | 3.1                     | .8          | .1          | 1794                                    | 3.1                                     | .3          |             | 1749          | .9                                      | .2          |             | 1758        | .3                                    | .1          |             | 1729      |
|   | • • • • • • •           |             |             | • | • |             | • · • • • • |               |   | • • • • • • |             |             | · · · · · · · · · · · · · · · · · · · | • • • • •   |             | • • • • • |
|   | • • • • • • •           |             |             | • • • • • • • •                         | • • • • • • • •                         | • • • • • • | •••••       |               |   |             |             | •••••       | • • • • • • • • •                     |             | •••••       | ••••      |
| TIME (LST)                              |                         |             |             |   | 0600                                    | - 2000      | •           |               |   | A           | LL F        | IOURS       |                                       |             |             |           |
|   |                         |             |             |   |   |             |             |               |   |             |             |             |                                       |             |             |           |

7445

8588

G - 2 - 13

| PPPPP | PPP             | AAA   | AAA   | RRRR | RRRR  | TITTTTTTT | нн     | нн   |
|-------|-----------------|-------|-------|------|-------|-----------|--------|------|
| PPPPP | РРРРРРРР АААААА |       | AAAA  | RRRR | RRRRR | TTTTTTTTT | нн     | HH   |
| PP    | PP              | AA    | AA    | RR   | r.r   | TT        | нн     | HH   |
| PP    | PP              | AA    | AA    | RR   | , RR  | TT        | HH     | HH   |
| PPPPP | PPPP            | AA    | AA    | RRRR | RRRRR | TT        | ннннн  | нннн |
| PPPPP | PPP             | AAAAA | ААААА | RRRR | RRRR  | TT        | нинини | ннн  |
| PP    |                 | AAAAA | AAAAA | RR   | RR    | TT        | HH     | HH   |
| PP    |                 | AA    | AA    | RR   | RR    | TT        | HH     | HH   |
| PP    |                 | AA    | AA    | RR   | RR    | TT        | нн     | HH   |
| PP    |                 | AA    | AA    | RR   | RR    | TT        | нн     | нн   |

#### PART H

#### DEGREE DAY SUMMARIES

#### DEGREE DAYS.

CREATED FROM HOURLY OBSERVATIONS (MAX+MIN/2 WHEN AVAILABLE), THESE TABLES GIVE THE THE NUMBER OF DEGREE DAYS FOR EACH MONTH IN EACH YEAR OF THE AVAILABLE PERIOD OF RECORD.

INCLUDED BENEATH EACH SUMMARY ARE STATISTICS BASED ON A 30-YEAR (1951-1980) POR (IF AVAILABLE). THE 30-YEAR POR PROVIDES AWS USERS WITH A SUMMARY CONSISTENT WITH OTHER STANDARD CLIMATIC PUBLICATIONS, NOTABLY THOSE OF THE NATIONAL CLIMATIC DATA CENTER (NCDC). NOTE THAT THE 30-YEAR POR WILL CHANGE TO 1961-1990 AS SOON AS DATA FOR DECEMBER 1990 HAS BEEN PROCESSED.

MONTHS WITH NO AVAILABLE DATA AND MONTHS WITH A VALUE OF ZERO APPEAR AS BLANKS IN THESE TABLES. ASTERISKS (\*\*\*\*) DENOTE AM INCOMPLETE MONTH WITH A DAY (OR DAYS) THAT CANNOT BE CALCULATED (FILLED IN) AUTOMATICALLY.

#### HEATING DEGREE DAYS.

ONE "HEATING DEGREE DAY" IS ASSIGNED TO REPRESENT EACH DEGREE THAT THE MEAN TEMPERATURE FALLS BELOW A DESIGNATED "BASE TEMPERATURE" OF 65 DEGREES\* FAHRENHEIT. FOR EXAMPLE, IF THE MEAN TEMPERATURE ON A GIVEN DAY IS 57 DEGREES, THAT DAY IS SAID TO HAVE 8 HEATING DEGREE DAYS.

#### COOLING DEGREE DAYS.

ONE "COOLING DEGREE DAY" IS ASSIGNED TO REPRESENT EACH DEGREE THAT THE TEMPERATURE RISES ABOVE A DESIGNATED "BASE TEMPERATURE" OF 65 DEGREES\* FAHRENHEIT. FOR EXAMPLE, IF THE MEAN TEMPERATURE FOR A GIVEN DAY IS 73 DEGREES, THAT DAY IS SAID TO HAVE 8 COOLING DEGREE DAYS.

\*65 DEGREES FAHRENHEIT HAS BEEN SELECTED AS THE NATIONWIDE STANDARD
"BASE TEMPERATURE" AT WHICH (AT LEAST THEORETICALLY) NO HEATING OR
COOLING IS REQUIRED. IF ANOTHER BASE TEMPERATURE IS JSED IN THESE
TABLES, IT WAS SPECIALLY REQUESTED BY THE STATION, AND IS NOTED.

NOTE 1. THESE SUMMARIES ARE NOT AVAILABLE FOR PART TIME PERIODS.

### HEATING DEGREE DAYS FROM HOURLY OBSERVATIONS

BASE TEMPERATURE 65

| STATION N    | UMBER: 4710 |     | ATION NA<br>T TO UTC |      | CASEY/TO | NGDUCHON | i ko |     | PERI | OD OF F | ECORD: | JAN 89 | - JUN 90     |
|--------------|-------------|-----|----------------------|------|----------|----------|------|-----|------|---------|--------|--------|--------------|
| YEARS        | JAN         | FEB | MAR                  | APR  | MAY      | JUN      | JUL  | AUG | SEP  | OCT     | NOV    | DEC    | ANN          |
| 1989<br>1990 | 1197        | 832 | 688<br>669           | **** | 58       | 4<br>8   | ***  |     | 33   | 367     | ****   | ****   | 1982<br>1874 |
| MEAN         | 1197        | 832 | 678                  |      | 58       | 6        |      |     | 33   | 367     |        |        |              |
| SD           |             |     | 13.44                |      |          | 2.83     |      |     |      |         |        |        |              |

# COOLING DEGREE DAYS FROM HOURLY OBSERVATIONS

BASE TEMPERATURE 65

| STATION N    | UMBER: 471066 |        | NAME: CAME<br>UTC: - 9 | CASEY/T    | ONGDUCHO   | n ko |     | PERI | OD OF R                                 | ECORD: J | AN 89 - | - JUN 90   |
|--------------|---------------|--------|------------------------|------------|------------|------|-----|------|---|----------|---------|------------|
| YEARS        | JAN           | FEB MA | R APR                  | MAY        | JUN        | JUL  | AUG | SEP  | OCT                                     | NOA      | DEC     | ANN        |
| 1989<br>1990 | ***           | ***    | ***                    | 39<br>**** | 154<br>140 | **** | 383 | 110  | · • • • • • • • • • • • • • • • • • • • | ****     | ****    | 686<br>140 |
| MEAN         | 1             |        |                        | 39         | 147        |      | 383 | 110  |   |          |         |            |
| SD           | I             |        |                        |            | 9.90       |      |     |      |   |          |         |            |

AWS

STATION NAME: CAMP CASEY/TONGDUCHON KO LATITUDE/LONGITUDE: 37 55 N 127 03 E

CLIMATIC BRIEF

HOURLY OBS POR: JUL 80 - JUN 90 SUMMARY OF DAY POR: MAY 53-JUN 90 HOURS SUMMARIZED: 0000 - 2300 LST

JUN 91

LST TO UTC: -09

FIELD ELEV: 196 FT STATION MSC: 471066 CALL SIGN: RKST

SUPERSEDES: JAN 86

| - 1 | JUN 91   LST 10 C                       | rc: -09       |                      |          |               |           |                                       |                |                |               |              |             |             |           |                    | 1 |
|-----|---|---------------|----------------------|----------|---------------|-----------|---------------------------------------|----------------|----------------|---------------|--------------|-------------|-------------|-----------|--------------------|---|
| Ī   | HTMOM                                   | JAN           | FEB                  | MAR      | APR           | MAY       | JUN                                   | JUL            | AUG            | SEP           | ocr          | NOV         | DEC         | ANN       | YOR                | İ |
| j   | EXTRM MAX TEMP (F) MEAN MAX TEMP (F)    | 57            | 61                   | 72<br>50 | 88<br>64      | 91<br>73  | 97<br>81                              | 102<br>84      | 100<br>86      | 91<br>78      | 84<br>67     | 75<br>52    | 57<br>38    | 102<br>62 | 37<br>37           | ĺ |
| i   | MEAN TEMP (F)                           | 25            | 30                   | 41       | 53            | 63        | 72                                    | 78             | 78             | 68            | 56           | 43          | 30          | 53        | 37                 |   |
| 1   | MEAN MIN TEMP (F)                       | 15            | 20                   | 30       | 42            | 52        | 62                                    | 70             | 70             | 58            | 45           | 34          | 22          | 44        | 37                 |   |
| ١   | EXTRM MIN TEMP (F)                      | -13           | ~6                   | 10       | 24            | 36        | 45                                    | 57             | 53             | 37            | 25           | 5           | -2          | -13       | 37                 | 1 |
| i   | D/W TEMP GE 90 (F)                      | 1 0           | l 0                  | l o      | 0             | 1         | 3                                     | 7              | 9              | 1             | 0            | l o         | О           | 21        | J 37               | İ |
|     | D/W TEMP GE 80 (F)                      | 0             | 0                    | 0        | 1             | 7         | 19                                    | 24             | 25             | 13            | 1            | 0           | 0           | 90        | 37                 | Ì |
| 1   | D/W TEMP LT 33 (F)                      | 29            | 24                   | 20       | 3             | 0         | 0                                     | 0              | 0              | 0             | 2            | 14          | 26          | 118       | 37                 |   |
|     | D/W TEMP LT 10 (F)                      | 10            | 4                    | 0        | 0             | 0         | 0                                     | 0              | 0              | 0             | 0            | #           | 3           | 17        | 37                 | ĺ |
| į   | HEATING DEGREE DAYS                     | *             | *                    | *        | *             | *         | *                                     | *              | *              | *             | *            | *           | *           | *         |                    | ĺ |
| i   | COOLING DEGREE DAYS                     | *             | *                    | 1 *      | *             |           | <b>~</b>                              | *              |                |               |              |             | *           |           | *                  | 1 |
| i   | MEAN DEWPOINT TEMP (F)                  | 21            | 26                   | 32       | 38            | 51        | 60                                    | 68             | 67             | 59            | 44           | 36          | 26          | 42        | 10                 | ĺ |
| ı   | MEAN WET BULB TEMP (F)                  | 23            | 28                   | 38       | 46            | 56        | 63                                    | 71             | 70             | 62            | 48           | 39          | 28          | 48        | 10                 | ĺ |
| Ì   | 99.95% WCPA (FT)                        | 350           | 300                  | 550      | 600           | 600       | 800                                   | 700            | 700            | 650           | 350          | 300         | 400         | 850       | 10                 | ı |
| i   | MEAN REL HUM 07 LST(%)                  | 86.9          | 89.1                 | 86.8     | 81.4          | 85.1      | 85.8                                  | 88.9           | 86.7           | 93.9          | 96.6         | 92.8        | 93.6        | 88.0      | 10                 | i |
|     | MEAN REL HUM 13 LST(%)                  | 1             |                      | 1        |               | 53.2      |                                       |                |                | 57.9          |              | 61.2        | 63.8        | 57.6      | 10                 | ĺ |
| :   |   | · · · · · · · | ·<br>• • • • • • • • |          |               |           |                                       |                | • • • • • •    |               |              |             |             |           |                    |   |
|     | MAX 24HR PRECIP (IN)                    | .89           |                      | 3.49     | 5.20          | 10.47     | 6.12                                  | 10.18          | 9.82           | 11.69         | 2.54         | 3.49        | 1.74        | 11.69     | 37                 | ĺ |
|     | MAX PRECIP (IN)                         | 2.47          | 1                    | 4.73     | 9.65          | 13.15     | 14.84                                 | 45.84<br>16.94 | 28.70<br>12.46 | 30.19<br>5.63 | 5.29<br>1.53 | 7.90        | 3.12<br>.72 |           | 37<br>37           | ĺ |
| - 1 | MEAN PRECIP (IN) MIN PRECIP (IN)        | *             | .85                  | 1.55     | 2.59          | #         | .26                                   | 5.08           | 2.24           | .13           | 1.55         | 1.52        | ./2         | 19.69     | 37                 | ĺ |
| ĺ   | D/W PRECIP GE .01 (IN)                  | 5             | 4                    | 7        | 7             | 7         | 10                                    | 16             | 13             | 8             | 5            | 7           | 6           | 95        | 37                 | ĺ |
|     | D/W PRECIP GT .50 (IN)                  | 1             | 1                    | 1        | 2             | 2         | 3                                     | A              | 7              | 3             | 1            | 1           | 1           | 31        | 37                 |   |
| •   | • | ·             | ·<br>• • • • • • •   | ·        |               |           | •••••                                 |                |                |               |              | • • • • • • |             |           | ·<br>• • • • • • • |   |
|     | MAX 24HR SNFL (IN)                      | 7.0           | 8.7                  | 5.0      | .2            | 0         | #                                     | 0              | 0              | 0             | #            | 3.3         | 7.0         | 8.7       | 37                 | ĺ |
|     | MAX SNFL (IN)                           | 18.5          | 11.1                 | 6.5      | .2<br>0       | 0         | #                                     | 0              | 0              | 0             |              | 3.3         | 9.7<br>2.2  | 32.0      | 37<br>37           |   |
|     | MEAN SNFL (IN)<br>D/W SNFL GE .1 (IN)   | 5.0           | 3.4                  | 1 1      | <u>u</u>      | 0         | , , , , , , , , , , , , , , , , , , , | 0              | 0              | 0             | ő            | 1           | 2.2         | 11.5      | 37                 | ĺ |
|     | D/W SNFL GE 1.5 (IN)                    | li            | 1                    | i        | ő             | Ö         | 0                                     | ŏ              | Ö              | ő             | ő            | 1           | 1           | 5         | 37                 | ı |
| ·   | ••••••                                  |               |                      |          | • • • • • • • |           |                                       |                |                |               | • • • • • •  |             |             |           |                    |   |
|     | MAX DLY SNO DEPTH (IN)                  | 7             | 9                    | 5        | #             | 0         | 0                                     | 0              | 0              | 0             | 0            | 4           | 7           | 9         | 37                 | ] |
|     | PRVLNG WND DIR (DEG)                    | \$35-01       | \$35-01              | \$35-01  | \$20-22       | \$20-22   | \$20-22                               | \$20-22        | \$35-01        | 35-01         | \$35-01      | \$35-01     | \$35-01     | \$35-01   | 10                 | ĺ |
|     | MEAN WND SPD (KTS)                      | 2             | 2                    | 3        | 3             | 3         | 3                                     | 3              | 3              | 2             | 2            | 2           | 2           | 3         | 10                 |   |
|     | MAX WND SPD (KTS)                       | 26            | 27                   | 29       | 40            | 42        | 31                                    | 45             | 38             | 42            | 33           | 30          | 25          | 45        | 37                 |   |
| ĺ   | SKY COVER GT 5/10 (%)                   | *             | *                    | *        | *             | *         | *                                     | *              | *              | *             | *            | *           | *           | *         | *                  | ı |
|     | D/W THUNDERSTORMS                       | 0             | #                    |          | 1             | 1         | 1                                     | 2              | 2              | 1             | 1            | 1           |             | 10        | 37                 | ı |
| -   | D/W FOG (VSBY LT 7 MI)                  | 14            | 11                   | 15       | 15            | 16        | 17                                    | 23             | 21             | 20            | 21           | 18          | 15          | 206       | 37                 | l |
| _   |   |               |                      |          |               | <b></b> - |                                       |                |                |               |              |             |             |           |                    |   |

LEGEND: ANN = ANNUAL

D/W = MEAN NUMBER OF DAYS WITH

\*\* = INSTANTANEOUS PEAK WINDS

\* - DATA NOT AVAILABLE

POR/YOR = PERIOD/YEARS OF RECORD

# = LESS THAN 0.5 DAYS OF RECORD

## = LESS THAN 0.5 DAYS OF RECORD

## = LESS THAN 0.5 DAYS OF RECORD

## = LESS THAN 0.5 DAYS OF RECORD

# = LESS THAN 0.5 DAYS OR TRACE AS APPLICABLE

S = PERCENTAGE OF CALM WINDS GREATER THAN OR EQUAL TO MEAN

WIND DIRECTION

|                   | • • • • • • • | • | • • • • • • • | • • • • • • | PERC          | ENT OCC    | URRENCE | FREQUE | NCY OF | CEILING       | AND VI | SIBILIT         |             |             |               | • • • • • • |
|-------------------|---------------|---|---------------|-------------|---------------|------------|---------|--------|--------|---------------|--------|-----------------|-------------|-------------|---------------|-------------|
|                   | Mo            | ONTH                                    | JAN           | FEB         | MAR           | APR        | MAY     | JUN    | JUL    | AUG           | SEP    | ocr             | NOV         | DEC         | ANN           | YOR         |
|                   | • • • • • •   |   |               |             |               |            | ·       |        |        | ·             | ·      |                 |             | • • • • • • | •             |             |
|                   |               | LST                                     |               |             |               | 1          | 1       | 1      |        |               | İ      |                 |             |             | ļ             |             |
|                   |               | 00 - 02                                 | 20.7          | 29.1        | 12.9          | 10.0       | 26.1    | 37.2   | 17.8   | 25.8          | 23.3   | 26.9            | 32.1        | 34.8        | 24.7          | 10          |
|                   |               | 03 - 05                                 | 23.9          | 35.2        | 21.0          | 24.0       | 36.1    | 46.1   | 31.1   | 31.2          | 38.9   | 40.9            | 45.2        | 37.8        | 34.3          | 10          |
| CIO               | g.            | 06 - 08                                 | 30.6          | 39.2        | 34.4          | 23.7       | 51.7    | 48.3   | 47.8   | 30.1          | 42.2   | 57.0            | 48.8        | 38.9        | 41.1          | 10          |
| LT 3000           | O FT          | 09 - 11                                 | 35.0          | 32.1        | 22.6          | 17.0       | 27.5    | 35.8   | 41.4   | 25.8          | 11.7   | 22.6            | 26.8        | 35.0        | 27.8          | 10          |
| AND/C             | OR            | 12 - 14                                 | 23.9          | 12.5        | 12.9          | 13.9       | 17.2    | 23.3   | 29.9   | 19.4          | 6.7    | 10.8            | 15.5        | 22.2        | 17.3          | 10          |
| VSBY              | -             | 15 - 17                                 | 20.6          | 10 !        | 12.4          | 9.7        | 15.1    | 18.9   | 17.2   | 14.0          | 10.0   | 5.4             | 10.7        | 5.6         | 12.5          | 10          |
| LT 3              | MI            | 18 - 20                                 | 21.7          | 10.8        | 11.3          | 9.1        | 16.7    | 17.8   | 18.4   | 12.9          | 2.2    | 4.3             | 8.3         | 16.3        | 12.5          | 10          |
|                   |               | 21 - 23                                 | 23.9          | 17.8        | 12.9          | 10.2       | 19.9    | 25.0   | 19.5   | 19.4          | 7.8    | 19.4            | 15.5        | 27.4        | 18.2          | 10          |
|                   |               | ALL                                     | 24.6          | 22.9        | 17.3          | 14.6       | 26.2    | 31.4   | 27.4   | 22.2          | 18.1   | 23.4            | 25.3        | 27.0        | 23.2          | 10          |
| • • • • • • • • • | • • • • • •   |   |               |             |               |            |         |        |        |               |        |                 |             |             |               |             |
|                   |               | 00 - 02                                 | 18.4          | 28.5        | 9.1           | 7.6        | 17.2    | 35.6   | 12.2   | 20.4          | 17.8   | 23.7            | 19.0        | 33.7        | 20.3          | 10          |
|                   | _             | 03 - 05                                 | 20.0          | 35.2        | 15.1          | 20.5       | 29.4    | 45.0   | 21.1   | 24.7          | 36.7   | 40.9            | 34.5        | 36.7        | 30.0          | 10          |
| CIO               |               | 06 - 08                                 | 27.2          | 38.0        | 29.6          | 21.9       | 45.6    | 45.0   | 35.6   | 28.0          | 42.2   | 50.5            | 41.7        | 36.7        | 36.8          | 10          |
| LT 1500           |               | 09 - 11                                 | 31.7          | 30.4        | 19.4          | 15.2       | 20.0    | 30.8   | 25.9   | 25.8          | 10.0   | 22.6            | 21.4        | 35.0        | 24.0          | 10          |
| AND/C             |               | 12 - 14                                 | 19.4          | 9.5         | 9.1           | 7.3        | 12.2    | 15.6   | 17.2   | 12.9          | 4.4    | 6.5<br>4.3      | 8.3<br>6.0  | 22.2        | 12.0          | 10<br>10    |
| VSB)              |               | 15 - 17<br>18 - 20                      | 15.0          | 7.1<br>8.4  | 7.5<br>8.6    | 6.1<br>4.2 | 10.6    | 10.0   | 2.3    | 6.5           | 10.0   | 4.3             | 3.6         | 15.1        | 8.2           | 10          |
| LT 3              | MI            | 21 - 23                                 | 18.9<br>21.1  | 16.0        | 7.5           | 3.6        | 15.5    | 22.2   | 9.2    | 14.0          | 3.3    | 17.2            | 1.2         | 27.4        | 13.2          | 10          |
|                   |               | 21 - 23<br>ALL                          | 21.0          |             | 13.0          | 10.7       | 20.3    | 27.0   | 15.5   | 17.3          | 15.9   | 21.2            | 16.8        | 25.8        | 18.9          | 10          |
|                   |               | l wrr                                   | 1 21.0        | 21.2        | 13.0          | 1 10.7     | 1 20.3  | 27.0   | 12.5   | 1 17.3        | 15.9   | 21.2            | 10.6        | 23.0        | 10.9          | 1 10        |
|                   | • • • • • • • | 00 ~ 02                                 | 8.4           | 10.9        | 5.9           | 1.8        | 7.8     | 16.7   | 5.6    | 10.8          | 11.1   | 22.6            | 2.4         | 18.0        | 10.2          | 10          |
|                   |               | 03 - 05                                 | 11.7          | 20.0        | 10.2          | 12.9       | 11.1    | 27.8   | 17.8   | 18.3          | 28.9   | 31.2            | 13.1        | 20.0        | 18.6          | 10          |
| CIO               | 2             | 06 - 08                                 | 21.1          | 26.5        | 17.7          | 17.2       | 31.7    | 27.8   | 26.7   | 21.5          | 40.0   | 45.2            | 25.0        | 32.2        | 27.7          | 10          |
| LT 1000           | -             | 09 - 11                                 | 17.5          | 20.5        | 9.7           | 6.2        | 9.2     | 18.3   | 13.8   | 17.7          | 5.0    | 16.1            | 17.9        | 33.3        | 15.4          | 10          |
| AND/C             |               | 12 - 14                                 | 11.7          | 7.7         | 3.2           | 2.4        | 3.9     | 8.3    | 8.0    | 5.4           | 1.1    | 1.1             | .0          | 16.7        | 5.8           | 10          |
| VSB               |               | 15 - 17                                 | 6.7           | 1.2         | 2.7           | 3.6        | 3.4     | 4.4    | .0     | 3.2           | 7.8    | 4.3             | 2.4         | .0          | 3.3           | 10          |
| LT 2              |               | 18 - 20                                 | 6.1           | .0          | 1.1           | .6         | 3.9     | 6.1    | 1.1    | 4.3           | 1.1    | 3.2             | 2.4         | 3.5         | 2.8           | 10          |
|                   |               | 21 - 23                                 | 10.0          | 1.8         | 3.2           | .0         | 6.1     | 13.5   | .0     | 8.6           | .0     | 14.0            | .0          | 11.9        | 5.7           | 10          |
|                   |               | ALL                                     | 11.4          | 10.7        | 6.6           | 5.6        | 9.6     | 15.2   | 9.0    | 10.9          | 12.2   | 17.3            | 7.5         | 16.3        | 10.7          | 10          |
|                   |               | ,                                       |               |             | · • • • • • • |            |         |        |        | ,<br>         |        | · · · · · · · · |             |             |               |             |
|                   |               | 00 - 02                                 | .0            | .0          | .5            | 1.2        | 1.1     | 0.     | 0.     | 1.1           | .0     | 12.9            | .0          | 3.4         | 1.7           | 10          |
|                   |               | ∪3 <b>~</b> 05                          | 3.3           | 1.8         | 3.8           | 7.0        | 3.9     | 1.1    | 1.1    | 2.2           | 6.7    | 22.6            | 2.4         | 3.3         | 4.9           | 10          |
| CIO               | 3             | 06 - 08                                 | 4.4           | 5.4         | 2.2           | 11.8       | 4.4     | 3.9    | 3.3    | .0            | 18.9   | 24.7            | 9.5         | 2.2         | 7.6           | 10          |
| LT 200            | FT            | 09 - 11                                 | 3.3           | 3.6         | .8            | .0         | .0      | .0     | .0     | .0            | 1.7    | 3.2             | 3.6         | 6.7         | 1.9           | 10          |
| AND/C             | OR            | 12 - 14                                 | .0            | 1.2         | 1.6           | .0         | .0      | .0     | .0     | .0            | .0     | .0              | .0          | .0          | .2            | 10          |
| VSBY              | Y             | 15 - 17                                 | .0            | .0          | .0            | .0         | .0      | .0     | .0     | .0            | .0     | .0              | .0          | .0          | .0            | 10          |
| LT 1/2            | 2 MI          | 18 - 20                                 | .0            | .0          | .0            | .0         | .0      | .0     | .0     | .0            | .0     | .0              | .0          | .0          | .0            | 10          |
|                   |               | 21 - 23                                 | .0            | .0          | .0            | .0         | .0      | .0     | .0     | .0            | .0     | 1.1             | .0          | 2.4         | .3            | 10          |
|                   |               | ALL                                     | 1.3           | 1.4         | 1.1           | 2.6        | 1.2     | .7     | .6     | .4            | 3.5    | 8.3             | 1.9         | 2.1         | 1.9           | 10          |
|                   | • • • • • • • | . <b></b>                               | • • • • • • • |             |               |            |         |        |        | • • • • • • • |        | • • • • • • •   |             |             | • • • • • • • | • • • • • • |
| HURRICA           | ANES/TRO      | OPICAL STOR                             | RMS OBSE      | ERVED FO    | OR THE        | PERIOD     | : 1954  | - 1986 |        |               |        |                 |             |             |               |             |
| HR/TS             | JAI           | N FEB                                   | MAR           | APF         | R MJ          | ΑY         | JUN     | JUL    | AUG    | SEP           | OCT    | NOV             | <i>t</i> D1 | EC          | ANN           |             |
| 60NM              | 0/0           |   | 0/0           | 0/0         |               |            | 0/0     | 0/2    | 0/5    | 0/0           | 0/0    | 0/0             | 0           | /0          | 0/7           |             |
| 120NM             | 0/0           |   | 0/0           | 0/0         |               |            | 0/0     | 2/4    | 2/10   | 0/0           | 0/0    | 0/0             |             | /o          | 4/14          |             |
|                   |               |   | - · ·         | -, -        |               |            |         |        |        |               |        |                 |             |             |               |             |
| 240NM             | 0/0           | 0/0                                     | 0/0           | 0/0         | 0,            | /1         | 1/3     | 4/13   | 5/16   | 3/1           | 0/0    | 0/0             | 0.          | /0          | 13/34         |             |

REMARKS: ALL SUMMARIES FROM SUMMARY OF DAY DATA (DESIGNATED BY 37 IN YOR COLUMN) WERE TAKEN FROM DATA THAT WAS
REPORTED ON A PART TIME BASIS (MAY 53 - FEB 88). DATA ARE MAINLY MISSING FOR 1800-0500 LST DURING THE PART TIME PERIOD.
DATA FOR MAR 88 - JUN 90 ARE FULL TIME. THE SAME RULE APPLIES TO THE HOURLY DATA SUMMARIES (DESIGNATED BY 10 IN YOR
COLUMN). THE HOURLY DATA SUMMARIES PERIOD OF RECORD ONLY GOES BACK TO JUL 80.